

# US Patent & Trademark Office

## Patent Public Search | Text View

United States Patent  
Kind Code  
Date of Patent  
Inventor(s)

12403473  
B2  
September 02, 2025  
Cai; Kunpeng et al.

### Particle sorter, particle sorting method, and micro flow path cartridge

#### Abstract

To shorten the time required to sort target particles with sufficient purity, a particle sorter is provided. A particle sorter **200** including a micro flow path cartridge **10** having a first flow path **10** with a detection area **11** and a sorting area **12**, a second flow path **20** for returning the target particle-containing sample **81** upstream from the detection region **11** of the first flow path **10**, an installation unit **110** of the micro flow path cartridge **100**, a liquid feeding unit **120**, a detection unit **130** that outputs a signal corresponding to the target particles **91** passing through the detection region **11**, a sorting mechanism **140** configured to perform a sorting operation of the target particle-containing sample **81** in a sorting region **12** based on the signal from the detection unit **130**, and a control unit **150** for controlling the liquid feeding unit **120** so as to return the sorted target particle-containing sample **81** upstream of the detection region **11** of the first flow path **10** via the second flow path **20**, and controlling the sorting mechanism **140** so as to perform a sorting operation on the returned target particle-containing sample **81**.

**Inventors:** Cai; Kunpeng (Kobe, JP), Mankar; Shruti (Kobe, JP), Maslova; Anastasia (Kobe, JP), Ajiri; Taiga (Kobe, JP), Sakai; Yumiko (Kobe, JP), Watanabe; Shunsuke (Kobe, JP), Yotoriyama; Tasuku (Kobe, JP), Tagawa; Ayato (Kobe, JP), Hasegawa; Takehiro (Kobe, JP), Miyamoto; Yoshiaki (Kobe, JP)

**Applicant:** SYSMEX CORPORATION (Kobe, JP)

**Family ID:** 76999553

**Assignee:** SYSMEX CORPORATION (Kobe, JP)

**Appl. No.:** 17/349656

**Filed:** June 16, 2021

#### Prior Publication Data

| Document Identifier | Publication Date |
|---------------------|------------------|
| US 20210394184 A1   | Dec. 23, 2021    |

## Foreign Application Priority Data

JP 2020-105774 Jun. 19, 2020

---

## Publication Classification

**Int. Cl.:** B01L3/00 (20060101); C12Q1/02 (20060101); G01N35/10 (20060101)

**U.S. Cl.:**

**CPC** B01L3/502761 (20130101); B01L3/502738 (20130101); B01L3/567 (20130101); C12Q1/02 (20130101); G01N35/1009 (20130101); B01L2200/0652 (20130101); B01L2300/0816 (20130101); B01L2300/123 (20130101); B01L2400/0415 (20130101); B01L2400/0655 (20130101)

## Field of Classification Search

**CPC:** B01L (2200/0652); B01L (2400/0655)

---

## References Cited

### U.S. PATENT DOCUMENTS

| Patent No.   | Issued Date | Patentee Name | U.S. Cl. | CPC           |
|--------------|-------------|---------------|----------|---------------|
| 4756427      | 12/1987     | Gohde et al.  | N/A      | N/A           |
| 5427946      | 12/1994     | Kricka        | 435/259  | B01J 19/0046  |
| 5587128      | 12/1995     | Wilding       | 435/6.12 | B01L 3/502715 |
| 10513679     | 12/2018     | Tabata et al. | N/A      | N/A           |
| 2010/0137163 | 12/2009     | Link et al.   | N/A      | N/A           |
| 2015/0064694 | 12/2014     | Sadri et al.  | N/A      | N/A           |
| 2018/0133715 | 12/2017     | Craig et al.  | N/A      | N/A           |
| 2018/0298324 | 12/2017     | Takeda et al. | N/A      | N/A           |

### FOREIGN PATENT DOCUMENTS

| Patent No.    | Application Date | Country | CPC |
|---------------|------------------|---------|-----|
| 1065378       | 12/2000          | EP      | N/A |
| 2191895       | 12/2009          | EP      | N/A |
| H7-242003     | 12/1994          | JP      | N/A |
| 2014-29327    | 12/2013          | JP      | N/A |
| 5845533       | 12/2015          | JP      | N/A |
| WO2016/182034 | 12/2017          | JP      | N/A |
| 2019-50778    | 12/2018          | JP      | N/A |
| 2018/067915   | 12/2017          | WO      | N/A |
| 2018/134311   | 12/2017          | WO      | N/A |
| 2018/148194   | 12/2017          | WO      | N/A |
| 2018/174748   | 12/2017          | WO      | N/A |

### OTHER PUBLICATIONS

Mechano Transformer Corporation, “What is MechaTrans®?” Web page <[https://www.mechano-transformer.com/en/technology/01\\_about.html](https://www.mechano-transformer.com/en/technology/01_about.html)>, retrieved from Internet on Jun. 10, 2021. cited by applicant

Mechano Transformer Corporation, “Application of MechaTrans®” Web page <[https://www.mechano-transformer.com/en/technology/03\\_applications.html](https://www.mechano-transformer.com/en/technology/03_applications.html)>, retrieved from Internet on Jun. 10, 2021. cited by applicant

Mechano Transformer Corporation, “Piezo Actuator : MechaTrans®” Web page <<https://www.mechano-transformer.com/en/products/mechatrans/index.html>>, retrieved from Internet on Jun. 10, 2021. cited by applicant

S. Sakuma et al., “On-chip cell sorting by high-speed local-flow control using dual membrane pumps”, Lab on a Chip, Aug. 21, 2017, pp. 2760-2767, vol. 17, No. 16, The Royal Society of Chemistry. cited by applicant

Technical Specification Sheet of The Cyto-Mine® Single Cell Analysis and Monoclonality Assurance System, 2 pages, Sphere Fluidics Limited, Cambridge, UK dated May 10, 2017. cited by applicant

L. Mazutis et al., “Single-cell analysis and sorting using droplet-based microfluidics”, Nature Protocols, Apr. 2013, pp. 870-891, vol. 8, No. 5, Nature America, Inc. cited by applicant

The Japanese Office Action issued on Jan. 9, 2024 in a counterpart Japanese patent application No. 2020-105774, 12 pages. cited by applicant

Akihiro Isozaki et al: “A practical guide to intelligent image-activated cell sorting”, Nature Protocols, Published online on Jul. 5, 2019, vol. 14, pp. 2370-2415. cited by applicant

Extended European search report issued on Nov. 10, 2021 in European patent application No. 21180003.2. cited by applicant

---

*Primary Examiner:* Levkovich; Natalia

*Attorney, Agent or Firm:* Crowell & Moring LLP

---

## **Background/Summary**

### **RELATED APPLICATIONS**

(1) This application claims priority to Japanese Patent Application No. 2020-105774, filed on Jun. 19, 2020, the entire content of which is incorporated herein by reference.

### **BACKGROUND OF THE INVENTION**

#### **1. Field of the Invention**

(2) The present invention relates to a particle sorter for separating target particles from a sample, a particle separation method, and a micro flow path cartridge.

#### **2. Description of the Related Art**

(3) In U.S. Patent Publication No. US20180298324A1, as shown in FIG. 36, discloses a replaceable flow path cartridge **900** including a sample reservoir **901**, a waste liquid reservoir **902**, a sheath liquid reservoir **903**, a sorting liquid reservoir **904**, a recovery reservoir **905**, a main flow path **906**, a sheath flow path **907**, and a sorting flow path **908**. A sample flows from the sample reservoir **901** to the main flow path **906**. The sheath liquid joins the main flow path **906** from the sheath liquid reservoir **903** through the sheath flow path **907**. Specific particles flowing through the main flow path **906** are detected in the detection region **909**. A sorting pulse flow from the sorting liquid reservoir **904** to the recovery reservoir **905** is generated by pulsed air pressure with a timing such that the particles determined to be the sorting target particles pass through the intersection of

the main flow path **906** and the sorting flow path **908** so as to separate the target particles.

## SUMMARY OF THE INVENTION

(4) In U.S. Patent Publication No. US20180298324A1, when the sample stored in the sample reservoir **901** is sent to the waste liquid reservoir **902**, the sorting target particles detected in the detection region **909** are sorted into the recovery reservoir **905**. When all the samples stored in the sample reservoir **901** are sent to the waste liquid reservoir **902**, the sorting process is completed. However, since the purity of the target particles by the sorting process (the ratio of the target particles to the total particles in the sample after the sorting process) and throughput (a number of processed particles in a unit time) are in trade-off relationship, it is necessary to slow down the flow velocity of the sample to sort target particles with sufficient purity, and, hence, it takes a long time to separate the particles. In particular, when target particles having an extremely low abundance are separated from a sample containing a large number of other non-target particles, it is difficult to separate the target particles with sufficient purity within a reasonable time.

(5) The present invention provides a particle sorter, a particle sorting method, and a micro flow path cartridge that can reduce the time required to sort target particles with sufficient purity.

(6) A particle sorter according to a first invention, shown in FIG. 1, is a particle sorter (**200**) including a micro flow path cartridge (**100**) including a first flow path (**10**) comprising a detection region (**11**) for detecting target particles contained in a sample and a sorting region (**12**) for obtaining a target particle-containing sample (**81**) containing the detected target particles, and a second flow path (**20**) for returning the target particle-containing sample to upstream of the detection region; an installation part (**110**) where the micro flow path cartridge is installed; a liquid feeder (**120**) configured to feed liquid in the micro flow path cartridge; a detector (**130**) configured to output a signal corresponding to the target particle passing through the detection region; a sorting mechanism (**140**) configured to perform a sorting operation for obtaining the target particle-containing sample in the sorting region based on the signal from the detector; and a controller (**150**) configured to control the liquid feeder such that the target particle-containing sample obtained in the sorting region is returned to upstream of the detection region via the second flow path, and control the sorting mechanism so as to perform the sorting operation on the returned target particle-containing sample.

(7) The sorting operation can be repeated a plurality of times inside the micro flow path cartridge (**100**) by returning the sample using the second flow path (**20**) formed in the micro flow path cartridge (**100**). Here, the target particle-containing sample (**81**) obtained by the sorting operation also includes particles other than the target particles (**91**) flowing near the target particles (**91**) in the sorting region (**12**). Therefore, the target particles (**91**) can be sorted with high purity even if the sample flows at a higher speed than in the case where the sorting process is performed only once by performing the sorting operation a plurality of times. As a result, the time required to sort the target particles (**91**) with sufficient purity can be shortened in the overall sorting process.

(8) A particle sorting method according to a second invention, shown in FIG. 2, is a method for sorting target particles (**91**) using a micro flow path cartridge (**100**) including a first flow path (**10**) comprising a detection region (**11**) for detecting target particles contained in a sample and a sorting region (**12**) for obtaining a target particle-containing sample (**81**) containing the detected target particles, and a second flow path (**20**) for returning the target particle-containing sample to upstream of the detection region, the particle sorting method comprising: obtaining (S1) the target particle-containing sample from the sample by feeding the sample to the first flow path of the micro flow path cartridge and performing a sorting operation in the sorting region based on a signal corresponding to the target particle passing through the detection region; returning (S2) the target particle-containing sample obtained by the obtaining to the first flow path via the second flow path; and feeding (S3) the returned target particle-containing sample to the detection region and the sorting region of the first flow path and performing the sorting operation based on the signal corresponding to the target particle passing through the detection region.

(9) In the particle sorting method according to the second invention, the first sorting step (S1) and the second sorting step (S3) can be performed a plurality of times by performing the above-mentioned return step (S2). Hence, the target particles (91) can be sorted with high purity even if the sample flows at a higher speed than compared to when the sorting process is performed only once, by performing the sorting operation a plurality of times. Therefore, the time required to sort the target particles (91) with sufficient purity can be shortened similar to the first invention.

(10) A micro flow path cartridge (100) according to a third invention, shown in FIG. 1, is the micro flow path cartridge (100) including a flow path forming body (40) in which a flow path (MC) for flowing a sample (91) containing target particles is formed; wherein the flow path comprises a first flow path (10) having a detection region (11) for detecting the target particles contained in the sample and a sorting region (12) for obtaining the detected target particles (81), and a second flow path (20) for returning the target particle-containing sample containing the target particles upstream of the detection region of the first flow path.

(11) The micro flow path cartridge (100) according to the third invention has, as described above, a flow path (MC) which includes a second flow path (20) for returning the target particle-containing sample (81) containing the sorted target particles (91) to upstream of the detection region (11) of the first flow path (10). In this way the sorting operation can be repeated a plurality of times using the second flow path (20) similar to the first invention. Therefore, the target particles (91) can be sorted with high purity even if the sample flows at a higher speed compared to when the sorting process is performed only once, by performing the sorting operation a plurality of times. As a result, the time required to sort the target particles (91) with sufficient purity can be shortened.

(12) According to the present invention, it is possible to provide a particle sorter, a particle sorting method, and a micro flow path cartridge that can reduce the time required to sort target particles with sufficient purity.

---

## Description

### BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a diagram illustrating an outline of a micro flow path cartridge and a particle sorter;
- (2) FIG. 2 is a flow chart showing a particle sorting method;
- (3) FIG. 3 is a perspective view showing a structural example of a micro flow path cartridge;
- (4) FIG. 4 is a schematic view showing an example of returning a target particle-containing sample from the second flow path to a sample chamber;
- (5) FIG. 5 is a perspective view showing a structural example of a micro flow path cartridge provided with a reservoir;
- (6) FIG. 6 is a schematic plan view of FIG. 5;
- (7) FIG. 7 is a schematic diagram illustrating the return of a target particle-containing sample via a reservoir;
- (8) FIG. 8 is a flow chart showing an example of a particle sorting method including a dilution step;
- (9) FIG. 9 is a schematic diagram describing a first example of a dilution step;
- (10) FIG. 10 is a schematic diagram for describing a second example of the dilution step;
- (11) FIG. 11 is a schematic plan view showing a micro flow path cartridge provided with a third flow path;
- (12) FIG. 12 is a schematic vertical cross-section view showing the structure of a flow path forming body;
- (13) FIG. 13 is a perspective view showing a substrate and a sheet of a flow path forming body;
- (14) FIG. 14 is a schematic view showing an example of opening and closing a flow path by pressing a sheet;

- (15) FIG. **15** is a schematic diagram describing a sorting mechanism;
- (16) FIG. **16** is a schematic view showing a flow path opening/closing unit by a displacement-enhancing type piezoelectric actuator;
- (17) FIG. **17** is a perspective view of the flow path opening/closing unit of FIG. **16**;
- (18) FIG. **18** is a schematic view showing another example of a displacement-enhancing type piezoelectric actuator;
- (19) FIG. **19** is a schematic view showing a modified example of the displacement-enhancing type piezoelectric actuator of FIG. **16**;
- (20) FIG. **20** is a schematic view showing a modified example of the displacement-enhancing type piezoelectric actuator of FIG. **18**;
- (21) FIG. **21** is a schematic view showing another structural example of a displacement-enhancing type piezoelectric actuator;
- (22) FIG. **22** is a schematic view showing a structural example of a displacement-expansion type piezoelectric actuator different from that of FIG. **21**;
- (23) FIG. **23** is a perspective view showing a specific structural example of an installation unit and a sorting mechanism;
- (24) FIG. **24** is an exploded perspective view and a plan view of the installation unit and the sorting mechanism of FIG. **23**;
- (25) FIG. **25** is a schematic view of a flow path for describing an opening/closing position by a sorting mechanism and a switching position by a liquid feed control valve;
- (26) FIG. **26** is a block diagram illustrating a specific structural example of a particle sorter;
- (27) FIG. **27** is a graph illustrating an output signal of a detection unit;
- (28) FIG. **28** is a diagram (A) and (B) illustrating the sorting operation control of the sorting mechanism by the control unit;
- (29) FIG. **29** is a schematic view (A) to (C) of a flow path illustrating the flow of operation of the particle sorter;
- (30) FIG. **30** is a schematic view (D) to (F) of a flow path illustrating the flow of operation of the particle sorter;
- (31) FIG. **31** is a flow chart (A) describing a first sorting step and a flow chart (B) describing a second sorting step;
- (32) FIG. **32** is a diagram showing the result of the sorting process according to an embodiment;
- (33) FIG. **33** is a diagram showing the result of the sorting process according to Comparative Example 1;
- (34) FIG. **34** is a graph comparing the throughputs of the sorting process between Example and Comparative Example 1;
- (35) FIG. **35** is a graph showing the relationship between throughput and purity in Example and Comparative Example 3; and
- (36) FIG. **36** is a diagram showing a conventional art.

#### DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

(37) Hereinafter, embodiments will be described with reference to the drawings.

(38) Outline of Particle Sorter

(39) An outline of the particle sorter according to the present embodiment will be described with reference to FIG. **1**.

(40) As shown in FIG. **1**, the particle sorter **200** is a device that uses the micro flow path cartridge **100** to perform a process of sorting target particles **91** in a sample **80** flowing in the flow path MC of the micro flow path cartridge **100**.

(41) Sorting means separating the target substance from the sample solution. Sample **80** is a liquid containing a large number of particles. The sample **80** includes a target particle **91** and a non-target particle **92** in addition to the target particle **91**.

(42) Particles are a general term for small objects, regardless of their constituent materials or

structures. As used herein, particles are a broad concept that includes particulate matter of cells, macromolecules, inorganic or organic materials. Examples of the target particle **91** may be (1) cells, (2) granules such as exosomes, or (3) droplets containing a predetermined component. Examples of cells include rare cells (circulating tumor cells (CTC), circulating rare cells (CRC), endothelial cancer cells and the like, primary B cells, antibody-producing hybridoma, germ cells (sperm, egg, embryo), and each single cell in cell-cell interaction and the like. Predetermined components contained in droplets include, for example, drug molecules, viruses, nucleic acids (DNA, RNA and the like), proteins (antibodies, biomarkers, enzymes) and the like.

(43) The particle sorter **200** performs a process of separating and recovering the target particle-containing sample **81** containing the target particles **91** from the sample **80** flowing through the flow path MC. Note that the term “sorting” as used herein does not mean that the collected sample contains only the target particles **91**. The sorting process by the particle sorter **200** is to increase the ratio (purity) of the number of target particles to the total number of particles in the sample. The purity of the target particles **91** in the target particle-containing sample **81** is higher than the purity of the target particles **91** in the sample **80** before sorting. Therefore, the recovered target particle-containing sample **81** contains most of the target particles **91** and some non-target particles **92** among the sample **80** that was first introduced into the micro flow path cartridge **100**. However, the number of target particles **91** in the recovered target particle-containing sample **81** is not necessarily larger than the number of non-target particles **92**. For example, when the target particles **91** are rare particles having an extremely small abundance in the sample **80**, the number of target particles **91** in the recovered sample may be less than the number of non-target particles **92** mixed in the recovered sample together with the target particles **91**.

(44) Particle Sorter Structure

(45) The particle sorter **200** includes an installation unit **110**, a liquid feeding unit **120**, a detection unit **130**, a sorting mechanism **140**, and a control unit **150**.

(46) The installation unit **110** provides an installation location for the micro flow path cartridge **100**. The installation unit **110** contacts a part of the micro flow path cartridge **100** and holds the micro flow path cartridge **100**. The installation unit **110** supports, for example, the lower surface of the micro flow path cartridge **100**.

(47) In the present embodiment, the micro flow path cartridge **100** installed in the installation unit **110** is configured with a first flow path **10** having a detection region **11** for detecting the target particles **91** contained in the sample and a branched sorting region **12** for sorting a target particle-containing sample **81** containing the detected target particles **91**, and a second flow path **20** for returning the target particle-containing sample **81** upstream of the detection region **11** of the first flow path **10**. In the first flow path **10**, the detection region **11** and the sorting region **12** are arranged in order from the upstream side.

(48) The liquid feeding unit **120** is configured to feed a liquid in the micro flow path cartridge **100**. The liquid feeding unit **120** can feed the sample **80** in the micro flow path cartridge **100** from the upstream to the downstream of the first flow path **10**. The liquid feeding unit **120** can feed the target particle-containing sample **81** that has passed through the sorting region **12** from the upstream to the downstream of the second flow path **20**. The target particle-containing sample **81** is returned to the first flow path **10** by the liquid transfer through the second flow path **20**. The liquid feeding unit **120** can feed the target particle-containing sample **81** returned to the first flow path **10** from the upstream to the downstream of the first flow path **10**.

(49) The liquid feeding unit **120** feeds the liquid in the micro flow path cartridge **100** by pressure, for example. The liquid feeding unit **120** pressurizes and feeds the liquid, for example, by applying a positive pressure to the upstream side of the flow path MC. The liquid feeding unit **120** also may send the liquid in a form of suctioning the liquid by applying a negative pressure to the downstream side of the flow path MC, for example. The liquid feeding unit **120** includes, for example, a pump and a valve.

(50) The detection unit **130** is configured to output a signal corresponding to the target particle **91** passing through the detection region **11**. That is, the target particles **91** in the sample **80** flowing from the upstream to the downstream of the first flow path **10** by the liquid feeding unit **120** are detected by the detection unit **130** when passing through the detection region **11**. The detection unit **130** outputs a signal reflecting the presence of the target particle **91** to the control unit **150**.

(51) The method for detecting the target particles **91** by the detection unit **130** is not particularly limited. The target particle **91** may be labeled for detection. For example, the target particle **91** can be labeled with a labeled antibody that specifically binds to the target particle **91**. As the labeling method, a method according to the detection method is selected from the known labeling methods. For the detection, for example, a method such as fluorescence detection, magnetic detection, image detection, or electric detection may be adopted. In fluorescence detection, the detection unit **130** detects the target particles **91** by detecting the fluorescence generated from the fluorescent label with a photodetector. In magnetic detection, the detection unit **130** detects the target particles **91** labeled with the magnetic particles by the magnetic detector. In image detection, the detection unit **130** photographs the target particles **91** passing through the detection region **11** with an image sensor, and detects the target particles **91** by image recognition. In electric detection, the detection unit **130** detects the target particles **91** based on the change in electrical resistance and the change in impedance due to the passage of the target particles **91** between electrodes provided in the detection region **11**.

(52) The sorting mechanism **140** is configured to perform a sorting operation for sorting the target particle-containing sample **81** in the sorting region **12** based on the signal from the detection unit **130**. In the sorting region **12**, the first flow path **10** is branched. The number of branches is at least two. In the example of FIG. 1, the sorting region **12** is bifurcated into a first guide path **12a** and a second guide path **12b**. The sorting mechanism **140** causes the target particles **91** detected by the detection unit **130** in the detection region **11** to flow into one specific flow path (first guide path **12a**) in the sorting region **12**. When the target particles **91** contained in the sample **80** reach the sorting region **12** one after another, the sorting mechanism **140** causes the target particles **91** to flow into the same first guide path **12a**. On the other hand, the sorting mechanism **140** causes the non-target particles **92** to flow into a flow path (second guide path **12b**) that is different from that of the target particles **91**. In this way the target particle-containing sample **81** is sorted in the sorting region **12**.

(53) The method of sorting the target particles **91** by the sorting mechanism **140** is not particularly limited. The sorting mechanism **140** may apply some external force to the target particle **91** itself or a small volume sample **80** containing the target particle **91** in the first flow path **10** for sorting. As the sorting method, for example, a laser method, a pressure method, an electric method, a magnetic method, an acoustic wave method, a flow path switching method, or the like may be employed.

(54) In the laser method, the sorting mechanism **140** irradiates the sample **80** flowing through the sorting region **12** with laser light to generate minute bubbles to cause a pressure change, thereby pushing the target particles **91** into the first guide path **12a**. In the pressure system, the sorting mechanism **140** sends the target particles **91** to the first guide path **12a** by applying pressure in a direction crossing the sorting region **12**. The pressure is applied from the outside of the micro flow path cartridge **100** or via an actuator provided inside the micro flow path cartridge **100**. In the electric method, the sorting mechanism **140** charges the target particles **91** and sends the target particles **91** to the first guide path **12a** by the principle of dielectrophoresis. In the magnetic method, the sorting mechanism **140** sends the target particles **91** to the first guide path **12a** by applying a magnetic force to the target particles **91** bonded to the magnetic particles. In the acoustic wave method, the sorting mechanism unit **140** sends the target particles **91** to the first guide path **12a** by applying an acoustic wave to the sorting region **12** by a transducer and forming a pressure gradient in the flow path MC. In the flow path switching method, the particles **91** are sent to the first guide path **12a** and the non-target particles **92** are sent to the second guide path **12b** by the



sorting mechanism **140** driving a valve structure provided in the micro flow path cartridge **100** to open and close the first guide path **12a** and the second guide path **12b** from the outside.

(55) The control unit **150** is configured to control the liquid feeding unit **120**, the detection unit **130**, and the sorting mechanism **140**. The control unit **150** controls the liquid feeding unit **120** to start, stop, open/close the valve, and the like. The control unit **150** controls the detection unit **130** and acquires a signal from the detection unit **130**. The control unit **150** controls the sorting operation by the sorting mechanism **140** based on the signal corresponding to the target particle **91**. The control unit **150** is configured by a computer and includes one or more processors and a storage unit including volatile memory and non-volatile memory.

(56) In the sorting operation, it is difficult to take out only the target particles **91** without mixing the non-target particles **92**. Therefore, the target particle-containing sample **81** includes sorted target particles **91**, and non-target particles **92** mixed with the target particles **91**.

(57) The control unit **150** controls the liquid feeding unit **120** to return the target particle-containing sample **81** sorted by the sorting mechanism **140** to upstream of the detection region **11** of the first flow path **10** via the second flow path **20**, and controls the sorting mechanism **140** to perform a sorting operation on the returned target particle-containing sample **81**. That is, in the present embodiment, the first sorting operation is performed on the sample **80**, and the second sorting operation is performed on the target particle-containing sample **81** collected as a result of the first sorting operation. The sorting operation also may be performed three or more times. The proportion of the non-target particles **92** decreases, and the purity of the target particles **91** increases by repeating the sorting operation.

(58) Particle Sorter Effectiveness

(59) In the particle sorter **200** of the present embodiment described above, the control unit **150** controls the liquid feeding unit **120** to return the target particle-containing sample **81** sorted by the sorting mechanism **140** to upstream of the detection region **11** of the first flow path **10** via the second flow path **12**, and controls the sorting mechanism **140** so as to perform a sorting operation on the returned target particle-containing sample **81**. In this way the sorting operation can be repeated a plurality of times inside the micro flow path cartridge **100** by returning the sample using the second flow path **20** formed in the micro flow path cartridge **100**. Here, the target particle-containing sample **81** obtained by the sorting operation also includes particles other than the target particles **91** flowing near the target particles **91** in the sorting region **12**. Therefore, the target particles **91** can be sorted with high purity even if the sample flows at a higher speed than in the case where the sorting process is performed only once by performing the sorting operation a plurality of times. As a result, the time required to sort the target particles **91** with sufficient purity in the entire sorting process can be shortened.

(60) Particle Sorting Method Summary

(61) Next, the particle sorting method according to the present embodiment will be summarized. The particle sorting method of the present embodiment is a method for sorting target particles **91** using a micro flow path cartridge **100** including a first flow path **10** having a detection region **11** for detecting the target particles **91** contained in the sample and a branched sorting region **12** for sorting the detected target particles **91**, and a second flow path **20** for returning the target particle-containing sample **81** containing the sorted target particles **91** to upstream of the detection region **11** of the first flow path **10**. The particle sorter **200** described above is a device that implements the particle sorting method according to the present embodiment by controlling the liquid feeding unit **120**, the detecting unit **130**, and the sorting mechanism **140** via the control unit **150**.

(62) As shown in FIG. 2, the particle sorting method includes at least a first sorting step **S1**, a return step **S2**, and a second sorting step **S3**.

(63) The first sorting step **S1** includes sending the sample **80** to the first flow path **10** of the micro flow path cartridge **100** and sorting the target particle-containing sample **81** from the sample **80** based on the signal corresponding to the target particles **91** passing through the detection region **11**.

In the case of the structural example of FIG. 1, the control unit **150** controls the liquid feeding unit **120** to feed the sample **80** from the upstream to the downstream of the first flow path **10**. The detection unit **130** outputs a signal corresponding to the target particle **91** that has reached the detection region **11**. The control unit **150** controls the sorting mechanism **140** so as to send the target particle-containing sample **81** that has reached the sorting region **12** to the first guide path **12a** based on the signal from the detection unit **130**. The control unit **150** controls the sorting mechanism **140** so as to send the sample that does not contain the target particles **91** that has reached the sorting region **12** to the second guide path **12b**.

(64) The return step S2 includes returning the target particle-containing sample **81** sorted by the first sorting step to the first flow path **10** via the second flow path **20**. In the case of the structural example of FIG. 1, after the first sorting step S1, the control unit **150** controls the liquid feeding unit **120** to send the target particle-containing sample **81** delivered to the first guide path **12a** from the upstream to the downstream of the second flow path **20**. In this way the target particle-containing sample **81** is returned upstream from the detection region **11** of the first flow path **10**.

(65) The second sorting step S3 includes sending the returned target particle-containing sample **81** to the detection region **11** and the sorting region **12** and performing a sorting operation based on the signals corresponding to the target particles **91** passing through the detection region **11**. In the case of the structural example of FIG. 1, after the return step S2, the control unit **150** controls the liquid feeding unit **120** to send the target particle-containing sample **81** from the upstream to the downstream of the first flow path **10**. The detection unit **130** outputs a signal corresponding to the target particle **91** that has reached the detection region **11**. The control unit **150** controls the sorting mechanism **140** so as to send the target particle-containing sample **81** that has reached the sorting region **12** to the first guide path **12a** based on the signal from the detection unit **130**. The control unit **150** controls the sorting mechanism **140** so as to send the sample that does not contain the target particles **91** that has reached the sorting region **12** to the second guide path **12b**. The return step S2 and the second sorting step S3 may be further repeated.

(66) In the particle sorting method according to the present embodiment, by performing the above-mentioned return step S2, the first sorting step S1 and the second sorting step S3 can be repeated a plurality of times. Hence, the target particles **91** can be sorted with high purity even if the sample flows at a higher speed than compared to when the sorting process is performed only once, by performing the sorting operation a plurality of times. Therefore, the time required to sort the target particles **91** with sufficient purity can be shortened.

(67) Micro Flow Path Cartridge Summary

(68) The micro flow path cartridge according to the present embodiment will be summarized with reference to FIG. 1.

(69) The micro flow path cartridge **100** includes a flow path MC. The flow path MC is a tubular element through which a fluid can flow. The micro flow path cartridge **100** can sort the target particles **91** from the sample **80** containing a plurality of types of particles in the flow path MC.

(70) The micro flow path cartridge **100** includes a flow path forming body **40** in which the flow path MC for flowing a sample containing the target particles **91** is formed. The flow path forming body **40** is installed in the installation unit **110** of the particle sorter **200**.

(71) Examples of the material of the flow path forming body **40** include glass, silicon, polydimethylsiloxane (PDMS), polymethylmethacrylate resin (PMMA), cyclic olefin resin (COC), cycloolefin polymer resin (COP), polyethylene terephthalate (PET), polycarbonate (PC), polytetrafluoroethylene (PTFE), metals and the like.

(72) In the present embodiment, the flow path MC includes a first flow path **10** and a second flow path **20**.

(73) The first flow path **10** has a detection region **11** for detecting the target particles **91** contained in the sample and a branched sorting region **12** for sorting the detected target particles **91**.

(74) The detection region **11** is a part of the first flow path **10**, and is located between the upstream

end and the downstream end of the first flow path **10**. The detection region **11** is arranged upstream of the sorting region **12**. The detection region **11** is configured so that the target particles **91** can be externally detected by the detection unit **130** of the particle sorter **200**. For example, when optical detection is performed, the detection region **11** has translucency and the target particles **91** in the flow path MC can be detected from outside the flow path MC.

(75) The sorting region **12** is a part of the first flow path **10**, and is located between the upstream end and the downstream end of the first flow path **10**. The sorting region **12** is arranged downstream of the detection region **11**. The sorting region **12** is connected to the detection region **11** on the upstream side. The downstream side of the sorting region **12** branches into at least two flow paths. In FIG. 1, the sorting region **12** includes a first guide path **12a** and a second guide path **12b** extending downstream, respectively. The first guide path **12a** and the second guide path **12b** are connected to each other at the upstream end to form a branched path. The first guide path **12a** directly or indirectly communicates with the second flow path **20**. The first guide path **12a** is a flow path through which the target particle-containing sample **81** flows. The second guide path **12b** is not connected to the second flow path **20**. The second guide path **12b** is a flow path through which the non-target particles **92** flow.

(76) The second flow path **20** is provided to return the target particle-containing sample **81** containing the sorted target particles **91** to the upstream side of the detection region **11** of the first flow path **10**. The liquid feeding direction in the second flow path **20** (from right to left in FIG. 1) is opposite to the liquid feeding direction in the first flow path **10** (from left to right in FIG. 1). The target particle-containing sample **81** containing the separated target particles **91** is sent to the upstream end of the second flow path **20**. The upstream side of the second flow path **20** directly or indirectly communicates with the first guide path **12a**. The downstream side of the second flow path **20** is directly or indirectly connected to the first flow path **10**.

(77) The return position of the target particle-containing sample **81** from the second flow path **20** to the first flow path **10** is at least upstream of the detection region **11**. In this way the target particle-containing sample **81** returned to the first flow path **10** is flowed again toward the downstream of the first flow path **10**, so that the target particles **91** can be detected in the detection region **11** and a sorting operation can be performed in the sorting region **12** based on the signal from the detection unit **130**.

(78) The micro flow path cartridge **100** may also be provided with a valve structure for opening and closing the flow path MC in order to supply the liquid from the upstream to the downstream of the first flow path **10** and the liquid from the upstream to the downstream of the second flow path **20**. For example, one valve structure is provided in each of the first guide path **12a**, the second guide path **12b**, and the second flow path **20**. The valve structure may be an on/off valve that opens and closes (that is, communicates and shuts off) the flow path MC, or a check valve that prevents a flow (backflow) from downstream to upstream. As will be described later, the flow path MC also may be opened and closed by applying a pressing force from the outside to the portion of the flow path MC of the micro flow path cartridge **100** to deform the pressing portion. Therefore, the micro flow path cartridge **100** does not have to be provided with a valve structure.

(79) The micro flow path cartridge **100** according to the present embodiment includes the second flow path **20** so that the flow path MC returns the target particle-containing sample **81** containing the sorted target particles **91** upstream of the detection region **11** of the first flow path **10**. In this way the sorting operation can be repeated a plurality of times using the second flow path **20**. By performing the sorting operation a plurality of times, the target particles **91** can be sorted with high purity even if the sample flows at a higher speed than in the case where the sorting process is performed only once. As a result, the time required to sort the target particles **91** with sufficient purity can be shortened.

(80) Micro Flow Path Cartridge Structural Example

(81) Next, the structure of the micro flow path cartridge **100** will be illustrated. The micro flow

path cartridge **100** also may include a liquid reservoir for accommodating a liquid such as a sample **80** or a target particle-containing sample **81**. The liquid reservoir can be, for example, a chamber, reservoir, well and the like.

(82) In the example shown in FIG. 3, the flow path forming body **40** has a flat plate shape, and a tubular chamber is provided so as to rise from the main surface of the flat plate-shaped flow path forming body **40**.

(83) As shown in FIG. 3, the flow path forming body **40** is configured with a recovery chamber **51** for collecting the target particle-containing sample **81** sorted in the sorting region **12** of the first flow path **10**. The recovery chamber **51** is connected to the downstream end of the first guide path **12a**, which is one of the branched sorting regions **12**. The target particle-containing sample **81** sent to the first guide path **12a** is housed in the recovery chamber **51**. In this way the sorted target particle-containing sample **81** can be housed in the recovery chamber **51** and then sent to the second flow path **20** without being discharged to the outside. Since the target particle-containing sample **81** can be returned without being taken out to the outside, the sampling process can be performed without the risk of contamination even if the sampling operation is performed a plurality of times.

(84) In the example of FIG. 3, the upstream end of the second flow path **20** communicates with the recovery chamber **51**. In this way the target particle-containing sample **81** can be directly sent from the recovery chamber **51** to the second flow path **20**. For example, it is possible to prevent the target particles **91** from remaining in the liquid feeding path because since the liquid feeding path of the target particle-containing sample **81** does not become unnecessarily long, compared to when all of the target particle-containing sample **81** is accommodated in the second flow path **20**.

(85) In the example of FIG. 3, the micro flow path cartridge **100** is formed with a sample chamber **52** for storing the sample **80** to be fed to the first flow path **10**. In this way the sample **80** previously injected and stored in the sample chamber **52** is supplied into the first flow path **10** by the liquid feeding unit **120** instead of supplying the sample **80** from the liquid feeding unit **120**. The downstream end of the second flow path **20** communicates with the sample chamber **52**.

(86) In this case, as shown in FIG. 4, the control unit **150** controls the liquid feeding unit **120** so as to sort the target particle-containing sample **81** from the sample **80** (see FIG. 3) fed to the first flow path **10** from the sample chamber **52**, and so that the sorted target particle-containing sample **81** is returned to the first flow path **10** via the second flow path **20** and the sample chamber **52**. In this way the sorted target particle-containing sample **81** can be housed in the sample chamber **52** that housed the original sample **80**. That is, the liquid feeding of the original sample **80** in the first sorting operation and the liquid feeding of the target particle-containing sample **81** in the second and subsequent sorting operations can be performed with the same structure. Therefore, the structure and control of the particle sorter **200** can be simplified as compared with the case where the original sample **80** and the target particle-containing sample **81** are housed in separate chambers.

(87) In the examples of FIGS. 3 and 4, the micro flow path cartridge **100** is formed with a waste chamber **55** for storing the sample **82** that has not been sorted as the target particle-containing sample **81** in the sorting region **12**. The waste chamber **55** is connected to the downstream end of the second guide path **12b**, which is the other end of the branched sorting region **12**. The sample **80** sent to the second sorting **12b** is housed in the waste chamber **55**. In this way the sorting operation can be repeated a plurality of times without discharging the unsorted sample **82** to the outside. In particular, when the micro flow path cartridge **100** provided with the sample chamber **52**, the recovery chamber **51**, and the waste chamber **55** is made disposable, the particle sorter **200** does not come into contact with the sample, and a series of operations from injection of the sample **80** to multiple sorting and disposal can be completed in the micro flow path cartridge **100**.

(88) In the examples shown in FIGS. 5 and 6, the flow path forming body **40** includes a sample chamber **52** for storing a sample to be fed to the first flow path **10**, a reservoir **53** that

communicates with the downstream end of the second flow path **20** (see FIG. 6), and a connecting flow path **53a** connected to the first flow path **10** upstream of the detection region **11**. The reservoir **53** is provided separately from the sample chamber **52**.

(89) In this case, the control unit **150** controls sorting mechanism **140** to sort the target particle-containing sample **81** from the sample **80** (see FIG. 6) sent from the sample chamber **52** to the first flow path **10** (see FIG. 1) and, as shown in FIG. 7, controls the liquid feeding unit **120** to return the sorted target particle-containing sample **81** to the first flow path **10** via the second flow path **20**, the reservoir **53**, and the connecting flow path **53a**. That is, in the first sorting step, the sample **80** is sent from the sample chamber **52** to the first flow path **10**. The sorted target particle-containing sample **81** is accommodated in the reservoir **53** via the recovery chamber **51** and the second flow path **20**. In the second sorting step, the target particle-containing sample **81** is sent from the reservoir **53** to the first flow path **10** via the connecting flow path **53a**.

(90) In this way it is possible to prevent residual particles in the sample chamber **52** from being mixed into the target particle-containing sample **81** by accommodating the target particle-containing sample **81** in the reservoir **53** separate from the sample chamber **52**. Therefore, the purity of the target particles **91** in the target particle-containing sample **81** can be increased as compared with the case where the target particle-containing sample **81** is returned to the sample chamber **52**.

(91) In the examples shown in FIGS. 6 and 7, the flow path forming body **40** includes a sheath liquid chamber **54** for storing sheath liquid and communicates with the sheath liquid chamber **54**, and a sheath liquid flow path **54a** connected upstream of the detection region **11** of the first flow path **10**, that is, downstream of the confluence point with the connecting flow path **53a** of the first flow path **10**. In the sorting operation, the control unit **150** controls the liquid feeding unit **120** to send the sample **80** or the target particle-containing sample **81** to the first flow path **10**, and send the sheath liquid from the sheath liquid chamber **54** to the first flow path via the sheath liquid flow path **54a**. As a result, the sample flow is surrounded by the sheath liquid flow at the position of the detection region **11** of the first flow path **10**.

(92) In this way the particles in the sample can be aligned by the flow of the sheath liquid, so that the target particles **91** in the detection region **11** can be detected easily and with high accuracy. Then, since the sheath liquid flow path **54a** is connected downstream from the confluence of the first flow path **10** and the connecting flow path **53a**, the target particles can be aligned by the sheath liquid flow even when a sorting operation is performed on the target particle-containing sample **81** returned via the second flow path **20**.

(93) Here, the liquid amount of the target particle-containing sample **81** sent to the recovery chamber **51** by the first sorting step is smaller than the liquid amount of the initial sample **80** by the amount of the sample **82** sent to the waste chamber **55**. For the second sorting step, the sorted target particle-containing sample **81** may be diluted.

(94) In FIG. 7, the control unit **150** is configured to control the liquid feeding unit **120** so as to dilute the target particle-containing sample **81**, and control the sorting mechanism **140** to perform a sorting operation with respect to the diluted target particle-containing sample **81**.

(95) In this way the liquid volume of the target particle-containing sample **81** can be increased by dilution, so that stable flow velocity control is possible even in the second and subsequent sorting operations. As a result, variations in sorting performance can be reduced.

(96) In this case, as shown in FIG. 8, the control unit **150** controls the liquid feeding unit **120**, detection unit **130**, and sorting mechanism **140** to perform a dilution step **S4** for diluting the target particle-containing sample **81** between the first sorting step **S1** and the second sorting step **S3**. That is, in FIG. 8, the particle sorting method of the present embodiment further includes a dilution step **S4** for diluting the target particle-containing sample **81** between the first sorting step **S1** and the second sorting step **S3**. The dilution step **S4** may be performed before the return step **S2** or after the return step **S2**.

(97) Specifically, in the example of FIG. 9, the control unit 150 controls the liquid feeding unit 120 so as to dilute the target particle-containing sample 81 in the recovery chamber 51. That is, after the first sorting step, the control unit 150 controls the liquid feeding unit 120 to send a predetermined amount of sheath liquid from the sheath liquid chamber 54 to the recovery chamber 51 via the sheath liquid flow path 54a, the first flow path 10, and the first guide path 12a. In this way uniform dilution is more easily accomplished, for example, compared to when diluting in the second flow path 20.

(98) In the example of FIG. 10, the sheath liquid for dilution is stored in the recovery chamber 51 in advance before the first sorting step. The control unit 150 controls the liquid feeding unit 120 to dilute the target particle-containing sample 81 in the recovery chamber 51 by sending the target particle-containing sample 81 to the recovery chamber 51 that stores the diluting liquid.

(99) In this way the target particle-containing sample 81 can be easily diluted simply by sending the sorted target particle-containing sample 81 to the recovery chamber 51. Since it is not necessary to transfer the dilution liquid between the sorting operation and the return operation of the target particle-containing sample 81 by the second flow path 20, the diluted target particles can be immediately sent after the initial sorting operation.

(100) Note that the dilution liquid may be injected into the recovery chamber 51 by the user in advance when the micro flow path cartridge 100 is installed in the installation unit 110, or a step can be performed to send the dilution liquid from the sheath liquid chamber 54 (refer to FIG. 9) to the recovery chamber 51 before the first sorting step.

(101) As another example, after the return step S2, the control unit 150 also may control the liquid feeding unit 120 to send the dilution liquid from the sheath liquid chamber 54 to the reservoir 53 in FIG. 6, to dilute the target particle-containing sample 81 stored in the reservoir 53.

(102) In the first and second sorting steps, it is not easy to sort all the target particles 91 flowing through the first flow path 10 into the first guide path 12a, and some of the target particles 91 cannot be sorted and are sent to the second guide path 12b. Therefore, the sample 82 sent to the second guide path 12b may be returned to the upstream of the first flow path 10.

(103) That is, in the example of FIG. 11, the flow path forming body 40 is provided with a third flow path 30 configured to return the sample that was not sorted as the target particle-containing sample 81 in the sorting region 12 of the first flow path 10 to the upstream of the detection region 11 of the first flow path 10.

(104) The control unit 150 controls the liquid feeding unit 120 to return the sample 82 that was not sorted as the target particle-containing sample 81 in the sorting region 12 of the first flow path 10 to the upstream of the detection region 11 of the first flow path 10 to send the returned sample 82 to the detection region 11 of the first flow path 10, and controls the sorting mechanism 140 (refer to FIG. 1) to perform a sorting operation based on the signal from the detection unit 130 (refer to FIG. 1).

(105) In this way not only the sorting operation for the target particle-containing sample 81 but also the sorting operation for the unsorted sample 82 can be performed to recover the target particles 91 returned from the third flow path 30 due to the sorting leakage. As a result, the recovery rate of the target particles 91 in the sample 80 can be improved.

(106) In FIG. 11, the upstream end of the third flow path 30 is connected to the waste chamber 55. The flow path forming body 40 is provided with, in addition to the third flow path 30, a second reservoir 56 communicating with the downstream end of the third flow path 30, and a connection flow path 56a connecting the upstream of the detection region 11 of the first flow path 10 and the second reservoir 56. Instead of providing the second reservoir 56 and the connection flow path 56a, the downstream end of the third flow path 30 may be connected to the sample chamber 52 or the reservoir 53, or the downstream end of the third flow path 30 may be connected upstream of the detection region 11 of the first flow path 10.

(107) Flow Path Forming Body Structure

(108) Next, a structural example of the flow path forming body **40** will be shown.

(109) As shown in FIG. **12**, the flow path forming body **40** includes a plate-shaped substrate **41** and a sheet **42** bonded to the substrate **41**. The flow path MC is formed by grooves formed on at least one of the sheet **42** side surface of the substrate **41** and the substrate **41** side surface of the sheet **42**. In the example of FIG. **13**, a groove **42a** is formed on the surface of the sheet **42** on the substrate **41** side, and the groove **42a** is covered by the surface of the sheet **42** on the sheet **42** side to form a flow path MC having a tubular structure capable of flowing a liquid. In this way the flow path forming body **40** can be configured with a simple structure in which the sheet **42** is simply attached to the substrate **41**.

(110) The first flow path **10** and the second flow path **20** have, for example, a depth D of 1  $\mu\text{m}$  or more and 1000  $\mu\text{m}$  or less, and a width W of 1  $\mu\text{m}$  or more and 1000  $\mu\text{m}$  or less. The particle sorter **200** of the present embodiment is particularly suitable for a micro flow path cartridge **100** having such a micro flow path.

(111) In the case of FIG. **12**, liquid reservoirs such as the sample chamber **52**, the recovery chamber **51**, the sheath liquid chamber **54**, and the reservoir **53** are formed on the main surface of the substrate **41** opposite to the sheet **42**. The substrate **41** is formed with through holes **41a** that penetrate the substrate **41** in the thickness direction from the main surface to the surface on the sheet **42** side. The through hole **41a** connects the inner bottom portion of the liquid reservoir such as the sample chamber **52**, the recovery chamber **51**, the sheath liquid chamber **54**, and the reservoir **53** with the flow path MC (groove portion **42a** of the sheet **42**). In this way the liquid inside the liquid reservoir is allowed to flow through the through hole **41a** to the flow path MC by applying pressure to the upper surface opening side of the liquid reservoir such as the sample chamber **52**, the recovery chamber **51**, the sheath liquid chamber **54**, and the reservoir **53**.

(112) In the example shown in FIG. **14**, the sheet **42** is made of a material that is more flexible than the substrate **41** and can be elastically deformed by pressing. For example, the substrate **41** is a glass substrate and the sheet **42** is a PDMS sheet. The sorting region **12** of the first flow path **10** is configured so that the flow path MC can be blocked by pressing the sheet **42** from the outside. In the example of FIG. **13**, the sorting mechanism unit **140** has a pressing part **142a** that can move in the direction of approaching and separating from the sheet **42**. The sheet **42** is pressed by the pressing part **142a**.

(113) In this way the flow path can be easily opened and closed simply by applying a pressing force from the outside to the sheet **42** that covers the flow path portion of the sorting region **12**. Then, the target particles **91** that have reached the sorting region **12** can be easily sorted by opening and closing the flow path.

(114) Sorting Mechanism Structure

(115) Next, the structure of the sorting mechanism **140** will be described.

(116) In the example shown in FIG. **15**, the sorting mechanism **140** includes a flow path opening/closing unit **141** that opens and closes at least one of the branched flow paths in the sorting region **12** of the first flow path **10**. In this way the sorting mechanism **140** can be constructed with a compact configuration in which the flow path opening/closing unit **141** is provided, so that the structure of the particle sorter **200** can be simplified.

(117) In the example of FIG. **15**, the sorting region **12** of the first flow path **10** is bifurcated into a first guide path **12a** that guides the sample to the collection chamber **51** and a second guide path **12b** that is different from the first guide path. The flow path opening/closing unit **141** is provided one by one in the first guide path **12a** and the second guide path **12b**.

(118) The control unit **150** is configured to control the sorting mechanism **140** so as to distribute the sample **80** and the target particle-containing sample **81** sent to the sorting region **12** to the first guide path **12a** based on the signal from the detection unit **130** (see FIG. **1**).

(119) In this way the sorting mechanism **140** is configured by a flow path switching mechanism that distributes the flow of the sample to either the first guide path **12a** or the second guide path

12b. Since the sorting operation can be performed by just switching the flow path, the configuration of the sorting mechanism **140** can be simplified.

(120) The flow path opening/closing unit **141** is a pinch valve. The flow path opening/closing unit **141** is configured to close at least one of the branched flow paths by deforming the region in which at least one of the branched flow paths of the micro flow path cartridge **100** is formed by pressing from the outside.

(121) In this way the flow path opening/closing unit **141** can be configured with a simple structure of simply pressing the micro flow path cartridge **100** from the outside. Since the flow path opening/closing unit **141** does not come into contact with the liquid inside the micro flow path cartridge **100**, contamination can be prevented.

(122) FIGS. **16** to **22** show a structural example of the flow path opening/closing unit **141**. In FIGS. **16** to **22**, the sheet **42**, which is the lower surface of the flow path forming body **40**, is shown upside down so as to be located on the upper side in the drawing.

(123) In the example shown in FIG. **16**, the flow path opening/closing unit **141** includes a displacement-enhancing type piezoelectric actuator. In this way the flow path MC can be opened and closed at high speed by the highly responsive piezoelectric actuator, so that it is possible to prevent particles other than the target particles **91** from being mixed into the sorted sample. On the other hand, the piezoelectric actuator has a drawback in that the amount of displacement that can be generated is small, but since the amount of displacement can be increased by the displacement-enhancing type piezoelectric actuator, the flow path MC can be opened and closed reliably even when the flow path MC of the micro flow path cartridge **100** is pressed from the outside.

(124) The displacement-enhancing type piezoelectric actuator includes a movable member **142** having a pressing portion **142a** facing the pressing position of the micro flow path cartridge **100**, a piezoelectric element **143** that moves the movable member **142**, and a fixing member **144** which holds the piezoelectric element **143** and the movable member **142**. The movable member **142** is configured to displace the pressing portion **142a** by a displacement amount larger than the displacement amount of the piezoelectric element **143**.

(125) In this way the displacement amount of the pressing portion **142a** required to reliably open and close the flow path MC of the micro flow path cartridge **100** can be easily obtained by expanding the displacement of the piezoelectric element **143** via the movable member **142**.

(126) In the example shown in FIG. **16**, one end of the piezoelectric element **143** extending vertically is fixed to the fixing member **144**. At the other end of the piezoelectric element **143** is provided a contact member **143a** that comes into contact with the movable member **142**. The piezoelectric element **143** is a so-called stack type piezoelectric actuator in which a plurality of piezoelectric bodies are laminated in the displacement generation direction. The piezoelectric element **143** expands and contracts in the vertical direction, which is the stacking direction, when a voltage is applied. The movable member **142** is arranged on the other end side of the piezoelectric element **143** so as to come into contact with the contact member **143a**. The movable member **142** has a cantilever structure extending from the fixing member **144** along the sheet **42** of the flow path forming body **40**. The movable member **142** has a straight plate-like shape. A pressing portion **142a** is provided at the tip of the movable member **142** in a convex shape toward the sheet **42**. The contact member **143a** is arranged so as to come into contact with the movable member **142** at a position between the fixed end of the movable member **142** and the pressing portion **142a**. In this way the displacement of the piezoelectric element **143** is expanded by the ratio of the length  $L1$  from the fixed end to the contact member **143a** and the length  $L2$  from the fixed end to the pressing portion **142a**. That is, the relationship of  $d2=d1 \times (L2/L1)$  is established between the displacement  $d1$  of the piezoelectric element **143** and the displacement  $d2$  of the pressing portion **142a**. Note that  $L1 < L2$ .

(127) As shown in FIG. **17**, the fixing member **144** is provided on the lower surface (upper surface in FIG. **17**) of the installation unit **110**. The pressing portion **142a** closes the flow path MC by



pushing up from beneath the sheet **42**, which is the lower surface of the flow path forming body **40** exposed from the opening of the installation unit **110**.

(128) In the example shown in FIG. **18**, a pressing portion **142a** is formed at one end of the movable member **142**, and the contact member **143a** of the piezoelectric element **143** is arranged at the other end of the movable member **142**. Then, the fixing member **144** rotatably holds the movable member **142** at a position between the pressing portion **142a** and the contact member **143a**. When the piezoelectric element **143** pushes up the other end of the movable member **142**, the movable member **142** rotates around the holding position via the fixing member **144** as a fulcrum, and the pressing portion **142a** is displaced toward the sheet **42**. In this case, the displacement of the piezoelectric element **143** is increased only by a ratio ( $L3/L4$ ) of the length  $L3$  from the contact member **143a** to the holding position (fulcrum) and the length  $L4$  from the holding position (fulcrum) to the pressing portion **142a**. Note that  $L3 < L4$ .

(129) As shown in FIGS. **19** and **20**, the piezoelectric actuator also may be provided with an energizing member **145** that energizes the movable member **142** in the direction in which the pressing portion **142a** releases the pressing. When the flow path MC is opened again after the flow path MC is closed by the energizing member **145**, the pressing portion **142a** can be returned to the original position, so that the flow path MC can be reliably opened.

(130) Other Examples of Displacement-Enhancing Piezoelectric Actuators

(131) There are various types of displacement-enhancing piezoelectric actuator structures, and the structure is not limited to a specific structure. In the following, variations of the displacement-enhancing type piezoelectric actuator will be illustrated.

(132) In FIG. **21**, the movable member **142** has a pressing portion **142a** at the tip and support portions **142b** and **142c** branched in a Y shape at the other end side. One support portion **142b** is supported by the fixing member **144** via an elastic hinge **146**. The other support portion **142c** is connected to the piezoelectric element **143** via an elastic hinge **146**. In this way the movable member **142** is pressed via the elastic hinge **146**, and the pressing portion **142a** is displaced toward the sheet **42** side when the piezoelectric element **143** is extended.

(133) In FIG. **22**, the movable member **142** has a pressing portion **142a** at the tip and Y-shaped support portions **142d** and **142e** at the other end side. The pair of support portions **142d** and **142e** are annularly connected via a plurality of elastic hinges **146**. The piezoelectric element **143** is arranged inside the annular portion, and both ends are connected to separate elastic hinges **146**. In this way the movable member **142** is pressed via the elastic hinges **146** at both ends, and the pressing portion **142a** is displaced toward the sheet **42** side when the piezoelectric element **143** contracts.

(134) Specific Structural Example of Particle Sorter

(135) A more specific structural example of the particle sorter **200** of the present embodiment will be described with reference to FIGS. **23** to **26**. The micro flow path cartridge **100** installed in the particle sorter **200** will be described by taking the configurations shown in FIGS. **5** and **6** as an example.

(136) Sample **80** is, for example, diluted and fluorescently labeled blood, and the target particle **91** is, for example, fluorescently labeled blood cells. The micro flow path cartridge **100** sorts the target cells, which are the target particles **91**, from cells other non-target cells, which are the non-target particles **92**. Target cells are rare cells that circulate in the blood. In the following embodiments, the target cells are circulating cancer cells (CTCs) in the blood, and the non-target cells are red blood cells, white blood cells, platelets and the like.

(137) Installation Unit

(138) As shown in FIGS. **23** and **24**, the installation unit **110** includes a cartridge holder **111** and a cover member **112**. The installation unit **110** detachably supports the micro flow path cartridge **100**. The micro flow path cartridge **100** is a disposable consumable part. The micro flow path cartridge **100** is installed in the installation unit **110** by the user and is used in a sorting process. When the

sorting process is completed, the micro flow path cartridge is removed from the installation unit **110**. When a sorting process is performed on another sample **80**, a new micro flow path cartridge **100** is installed in the installation unit **110**.

(139) The cartridge holder **111** has a bottom portion **111a** that supports the peripheral edge portion of the micro flow path cartridge **100** from below. The bottom portion **111a** has a frame-like shape with an opening (see FIG. 17) at the center so as to expose the formed portions of the flow path MC such as the detection region **11** and the sorting region **12** of the micro flow path cartridge **100** downward.

(140) The cartridge holder **111** has a wall-shaped side surface portion **111b** that rises upward from the outer peripheral portion of the bottom portion **111a**.

(141) The cover member **112** is detachably attached (or can be opened and closed) on the upper surface of the cartridge holder **111**. The cover member **112** is provided so as to cover the upper surface opening of the liquid reservoir in the micro flow path cartridge **100** held by the cartridge holder **111**. That is, the cover member **112** seals the upper surface openings of the sample chamber **52**, the recovery chamber **51**, the reservoir **53**, the waste chamber **55**, and the sheath liquid chamber **54** of the micro flow path cartridge **100**. Note that a seal member for air-tightly sealing the upper surface opening is provided on the lower surface of the cover member **112**.

(142) As shown in FIG. 24, the cover member **112** is formed with one communication hole **112a** for each of the sample chamber **52**, the recovery chamber **51**, the reservoir **53**, the waste chamber **55**, and the sheath liquid chamber **54**. The communication hole **112a** penetrates the cover member **112** in the thickness direction. Each communication hole **112a** is connected to the liquid feeding unit **120** one by one on the upper surface of the cover member **112** via a pipe member **121** (see FIG. 26) described later.

(143) A sorting mechanism **140** is provided below the installation unit **110**. The sorting mechanism **140** includes a base member **147** attached to the lower surface of the cartridge holder **111**, and a flow path opening/closing unit **141** provided on the base member **147**. The liquid feeding unit **120** also includes a liquid feeding control valve **122** for switching the liquid flow path in the micro flow path cartridge **100** to control the liquid feeding path. These liquid feed control valves **122** are also provided on the base member **147**.

(144) The flow path opening/closing unit **141** is composed of a pinch valve provided with a displacement-enhancing piezoelectric actuator (see FIG. 17). The flow path opening/closing unit **141** is provided so as to project downward from the base member **147**. The flow path opening/closing unit **141** closes the flow path MC by pressing the sheet **42**, which is the lower surface of the flow path forming body **40**, upward so that the pressing portion **142a** pushes up from below. The flow path opening/closing unit **141** is provided one by one corresponding to the first guide path **12a** and the second guide path **12b** (see FIG. 25) downstream of the sorting region **12**. Specifically, the two flow path opening/closing units **141** are provided so that the opening/closing position P1 of the first guide path **12a** and the opening/closing position P2 of the second guide path **12b** in FIG. 25 can be closed by pressing, respectively.

(145) The liquid feed control valve **122** provided on the base member **147** is also comprised of a pinch valve that closes the flow path MC by pressing and deforming the sheet **42** of the flow path forming body **40**, similar to the flow path opening/closing unit **141**. Therefore, the liquid feed control valve **122** is provided so as to face upward with respect to the lower surface of the micro flow path cartridge **100**. Note that the liquid feed control valve **122** is a cylinder valve of a type in which the pressing portion is operated by an air cylinder, unlike the flow path opening/closing unit **141**.

(146) A plurality of liquid feed control valves **122** are provided on the flow path MC so that the flow path of the micro flow path cartridge **100** can be switched according to the processing step.

(147) Specifically, as shown in FIG. 25, each liquid feed control valve **122** is provided with a switching position P3 upstream of the connection position with the connection flow path **53a** in the

first flow path **10**, switching position **P4** on one sheath liquid flow path **54a** and switching position **P5** on the other sheath liquid flow path **54a**, a switching position **P6** on the second flow path **20** and a switching position **P7** on the connection flow path **53a**. When the liquid feed control valve **122** at any position is turned on, the liquid feed control valve **122** presses the sheet **42** to close the corresponding flow path. When the liquid feed control valve **122** is turned off, the pressing of the sheet **42** by the liquid feed control valve **122** is released, and the corresponding flow path is opened.

(148) Note that the liquid feed control valve **122** is not provided on the first guide path **12a** and the second guide path **12b**. That is, the first guide path **12a** at the opening/closing position **P1** and the second guide path **12b** at the opening/closing position **P2** are opened and closed by the corresponding flow path opening/closing units **141**, respectively. The flow path opening/closing unit **141** is configured to perform not only the sorting operation but also the opening/closing of the flow path for controlling the liquid feed.

#### (149) Liquid Feeding Unit

(150) As shown in FIG. **26**, the liquid feeding unit **120** is individually connected to each liquid reservoir (collection chamber **51**, sample chamber **52**, reservoir **53**, sheath liquid chamber **54**, waste chamber **55**) of the micro flow path cartridge **100** via the pipe member **121**. The liquid feeding unit **120** includes the plurality of liquid feeding control valves **122** described above.

(151) The liquid feeding unit **120** is configured to supply liquid to the flow path MC of the micro flow path cartridge **100** by applying pressure under the control of the control unit **150**. The liquid feeding unit **120** can individually apply positive pressure to the recovery chamber **51**, the sample chamber **52**, the reservoir **53**, the sheath liquid chamber **54**, and the waste chamber **55** to send the internal liquid to the flow path MC. The liquid feeding unit **120** can individually open the recovery chamber **51**, the sample chamber **52**, the reservoir **53**, the sheath liquid chamber **54**, and the waste chamber **55** to the atmosphere to accommodate the liquid sent from the flow path MC inside. The liquid feeding unit **120** may include an air pressure source **123** such as an air pump, a pressure regulator (regulator) **124**, and a pressure supply unit **125**. The liquid feeding unit **120** adjusts the liquid feeding speed from each chamber and reservoir by adjusting the pressure supplied from the air pressure source **123** by the pressure regulator **124** under the control of the control unit **150**. The pressure supply unit **125** includes a multi-port valve terminal capable of individually controlling the on and off of the pressure supply to each liquid feed control valve **122**. Under the control of the control unit **150**, the liquid feed unit **120** individually switches the pressure supply from the air pressure source **123** on and off for each liquid feed control valve **122** by the pressure supply unit **125**, so that each liquid feed control valve **122** operates individually.

#### (152) Detection Unit

(153) The detection unit **130** is provided below the installation unit **110**. The detection unit **130** detects the target particles **91** from the lower surface side on which the sheet **42** is arranged in the flow path forming body **40**. The detection unit **130** is configured to optically detect the target particles **91** passing through the detection region **11**. Note that, as shown in FIG. **24**, the base member **147** is configured with a notch-shaped penetrating portion **147a** over a range including the detection region **11** and the sorting region **12** in which the pressing portion **142a** is arranged. The detection unit **130** detects the target particles **91** passing through the detection region **11** from below the base member **147** via the region LP of the penetration portion **147a**. In FIG. **26**, the detection unit **130** includes a light source **131**, an optical system **132**, and a photodetector **133**.

(154) The light source **131** generates excitation light for the fluorescent label bound to the target particles **91**. The light source **131** is composed of, for example, a semiconductor laser element.

(155) The optical system **132** includes an objective lens **132a** and dichroic mirrors **132b** and **132c**.

(156) The photodetector **133** is configured to detect fluorescence generated from a fluorescent label excited by excitation light, and output a signal according to the fluorescence intensity. The photodetector **133** is a photon counter. For the photodetector **133**, for example, a photomultiplier

tube or an MPPC (multi-pixel photon counter) is used.

(157) The excitation light emitted from the light source **131** is reflected by the dichroic mirror **132b**, passes through the objective lens **132a**, and irradiates the detection region **11**. When the target particles **91** passing through the detection region **11** are irradiated with excitation light, fluorescence is generated from the fluorescent label. The fluorescent light passes through the objective lens **132a** and the dichroic mirror **132b**, is reflected by the dichroic mirror **132c**, and is detected by the photodetector **133**. When the detection unit **130** detects the fluorescence generated by irradiating the target particles **91** with the excitation light, the detection unit **130** outputs an electric signal corresponding to the detected fluorescence.

(158) Control Unit

(159) The control unit **150** is composed of, for example, a CPU. The control unit **150** performs various processes based on a program stored in the storage unit **151**. The storage unit **151** is composed of a RAM, a ROM, a hard disk and the like.

(160) The control unit **150** controls the liquid feeding unit **120** so that the sample chamber **52**, the recovery chamber **51**, the reservoir **53**, the waste chamber **55**, and the sheath liquid chamber **54** are individually pressurized or opened to the atmosphere. The control unit **150** switches the liquid feeding path of the liquid by controlling the liquid supply control valve **122** of the liquid supply unit **120** and the flow path opening/closing unit **141** to open and close each position on the flow path MC.

(161) The control unit **150** is individually connected to the two flow path opening/closing units **141** via the driver circuit **152**. When the pressing unit **142a** is operated to close the flow path MC, the control unit **150** applies a predetermined operating voltage from the driver circuit **152** to the piezoelectric element **143** of the flow path opening/closing unit **141**. In this way the flow path MC is closed as a result of the displacement of the pressing portion **142a** due to the expansion and contraction operation of the piezoelectric element **143**.

(162) When the flow path MC is opened, the control unit **150** stops the voltage application from the driver circuit **152** to the piezoelectric element **143** of the flow path opening/closing unit **141**. In this way the pressing portion **142a** releases the pressure on the sheet **42**, and the flow path MC is opened.

(163) The control unit **150** individually controls each liquid supply control valve **122** arranged at the switching position P3 to the switching position P7 (see FIG. 25) via the pressure supply unit **125** of the liquid feeding unit **120**.

(164) The control unit **150** performs controls for carrying out the particle sorting method of the present embodiment. That is, as shown in FIG. 2, the control unit **150** controls the liquid feeding unit **120**, the detection unit **130**, and the sorting mechanism **140** to perform first sorting step S1, the return step S2, and the second sorting step S3. The first sorting step S1 is a step sorting the target particle-containing sample **81** by controlling the liquid feeding unit **120** so as to feed the sample **80** to the first flow path **10** of the micro flow path cartridge **100**, and sorting the target particle-containing sample **81** by controlling the sorting mechanism **140** to perform a sorting operation based on the signal from the detection unit **130**. The return step S2 is a step of controlling the liquid feeding unit **120** so that the target particle-containing sample **81** sorted by the first sorting step S1 is returned to the first flow path **10** via the second flow path **20**. The second sorting step S3 is a step of controlling the liquid feeding unit **120** to send the returned target particle-containing sample **81** to the detection region **11** and sorting region **12** of the first flow path **10**, and controlling the sorting mechanism **140** to perform a sorting operation based on the signal from the detection unit **130**.

(165) In this way the first sorting step S1 is performed on the sample **80** and the second sorting step S3 is successively performed on the target particle-containing sample **81** sorted by the first sorting step S1 within the micro flow path cartridge **100** by performing the return step S2. Note that, as shown in FIG. 8, the control unit **150** controls the liquid feeding unit **120** and the sorting mechanism **140** so as to further perform the dilution step S4.

(166) Sorting Operation Controls

(167) Next, the control of the sorting operation using the sorting mechanism unit **140** will be described.

(168) As shown in FIG. **26**, the control unit **150** sends liquid by the liquid feeding unit **120** and acquires a signal from the detection unit **130**. Even if the non-target particles **92** are irradiated with excitation light when the non-target particles **92** in the sample **80** pass through the detection region **11**, the fluorescence of a specific wavelength due to the fluorescent label of the target particles **91** does not occur. When the target particles **91** in the sample **80** pass through the detection region **11**, the fluorescent label is excited by the excitation light, and the generated fluorescence of a specific wavelength is detected by the detection unit **130**. As a result, as shown in FIG. **27**, the signal of the detection unit **130** has a rise (peak) of the fluorescence intensity of a specific wavelength. The control unit **150** determines that the target particles **91** have been detected when the detected fluorescence intensity is equal to or higher than a preset threshold value TH. When the detected fluorescence intensity is less than the threshold value TH, the control unit **150** determines that the target particles **91** have not been detected.

(169) As shown in FIG. **28A**, when the fluorescence intensity is less than the threshold value TH, the control unit **150** closes the first guide path **12a** (opening/closing position P1) by the flow path opening/closing unit **141** of the first guide path **12a**, and the flow path opening/closing unit **141** of the second guide path **12b** opens the second guide path **12b** (opening/closing position P2). In this way the non-target particles **92** are sent to the second guide path **12b**.

(170) As shown in FIG. **28B**, when the fluorescence intensity is equal to or higher than the threshold value TH, the control unit **150** causes the flow path opening/closing unit **141** of the first guide path **12a** to open the first guide path **12a**, and flow path opening/closing unit **141** of the second guide path **12b** is closed by the flow path opening closing unit **141** of **12b**. In this way the target particles **91** are sent to the first guide path **12a**.

(171) Here, the flow velocity of the sample in the first flow path **10** is controlled to a predetermined value by the liquid feeding unit **120**. Therefore, the time t1 required for the target particles **91** detected in the detection region **11** to reach the sorting region **12** is known. As shown in FIG. **27**, the control unit **150** controls the flow path opening/closing unit **141** to open the first guide path **12a** and close the second guide path **12b** at the timing when the time t1 elapses after the fluorescence intensity equal to or higher than the threshold value TH is detected. Then, the control unit **150** keeps the state in which the first guide path **12a** is open and the second guide path **12b** is closed for a predetermined time t2. The predetermined time t2 is a margin time for the target particles **91** that have reached the sorting region **12** to reliably pass through the opening/closing position P1 by the flow path opening/closing unit **141** based on the flow velocity in the first flow path **10**.

(172) In this way the target particles **91** are sorted into the first guide path **12a** in the sorting region **12**. The sample **81** containing target particles to be sorted contains sample components (that is, target particles **91**, non-target particles **92**, and liquid phase) that have passed through the opening/closing position P1 by the flow path opening/closing unit **141** during a predetermined time t2. When the predetermined time t2 elapses, the control unit **150** controls the flow path opening/closing unit **141** so as to close the first guide path **12a** and open the second guide path **12b**.

(173) Particle Sorter Operation

(174) Next, the flow of operation of the particle sorter **200** will be described with reference to FIGS. **29** and **30**. Note that in FIGS. **29** and **30** the structures other than the micro flow path cartridge **100** shall be referred to with reference to FIGS. **23** to **26**.

(175) First, as a preliminary preparation, the user injects the sample **80** into the sample chamber **52** of the new micro flow path cartridge **100**, and injects the sheath liquid into the sheath liquid chamber **54**. The user installs the micro flow path cartridge **100** in the installation unit **110** and attaches the cover member **112**. This prepares for the sorting process. Thereafter, the sorting process operation by the particle sorter **200** is started according to the operation input of the user.

(176) The control unit **150** starts the first sorting step **S1** (see FIGS. **8** and **31A**). In step **S11** as shown in FIG. **31A**, the control unit **150** executes a process of feeding the sample **80** of the sample chamber **52** and the sheath liquid of the sheath liquid chamber **54** to the first flow path **10**. Specifically, as shown in FIG. **29A**, the control unit **150** causes each liquid feed control valve **122** to operate so as to open the flow paths of the switching position **P3**, the switching position **P4**, and the switching position **P5**, and close the flow paths of the switching position **P6** and the switching position **P7**. The control unit **150** controls the liquid feeding unit **120** so as to apply positive pressure to the sample chamber **52** and the sheath liquid chamber **54** to open the recovery chamber **51**, the waste chamber **55**, and the reservoir **53** to the atmosphere. In this way the sample **80** is sent from the sample chamber **52** to the first flow path **10**, and the sheath liquid is sent from the sheath liquid chamber **54** to the first flow path **10** via the sheath liquid flow path **54a**. The feeding of the sample and the sheath liquid is continued until the first sorting step **S1** is completed.

(177) When the liquid feeding is started, in step **S12**, the control unit **150** detects the target particles **91** based on the signal of the detection unit **130**. Since the liquid feeding is continued, the sample **80** flowing through the first flow path **10** passes through the detection region **11**. When the target particle **91** is not detected in the detection region **11** (step **S12**: NO), the fluorescence intensity obtained from the signal of the detection unit **130** does not reach the threshold value **TH**, so that the control unit **150** closes the first guide path **12a** and controls the flow path opening/closing unit **141** so as to maintain the state in which the second guide path **12b** is open. The control unit **150** continues the detection process in step **S12**. The unsorted sample **82** is sent to the waste chamber **55** via the second guide path **12b**.

(178) As shown in FIG. **29B**, when the target particle **91** passes through the detection region **11**, the fluorescence intensity obtained from the signal of the detection unit **130** becomes equal to or higher than the threshold value **TH** (see FIG. **27**) (step **S12**: YES). In this case, the control unit **150** executes a process of sorting the target particle-containing sample **81** into the first guide path **12a** in step **S13**. Specifically, the control unit **150** controls the flow path opening/closing unit **141** so as to open the first guide path **12a** and close the second guide path **12b**. In this way the target particle-containing sample **81** is sorted into the first guide path **12a**. After the elapse of the predetermined time **t2**, the control unit **150** closes the first guide path **12a** and switches to a state in which the second guide path **12b** is opened. Next, in step **S14**, the control unit determines whether the entire amount of the sample **80** in the sample chamber **52** has been sent to the first flow path **10**. If the entire amount of the sample **80** in the sample chamber **52** has been sent to the first flow path **10** (step **S14**: YES), the process proceeds to step **S4** (see FIG. **8**). If the entire amount of the sample **80** in the sample chamber **52** has not been sent to the first flow path **10** (step **S14**: NO), the process is returned to step **S12**. Note that to determine whether the entire amount of the sample **80** in the sample chamber **52** has been sent to the first flow path **10**, the time required for sending the entire amount of liquid is calculated from the volume of the sample and the liquid feeding speed can be determined beforehand, then determined whether the elapsed time from the start of liquid feeding of the sample has reached the calculated time.

(179) In this way the first sorting step **S1** is performed. The first sorting step **S1** is carried out until the total amount of the sample **80** in the sample chamber **52** has been transferred. After the completion of the first sorting step **S1**, all the target particle-containing sample **81** sorted into the first guide path **12a** is stored in the recovery chamber **51**.

(180) Next, the control unit **150** performs a dilution step **S4** (see FIG. **8**) for diluting the target particle-containing sample **81** by sending the sheath liquid to the recovery chamber **51**. Specifically, as shown in FIG. **29C**, the control unit **150** causes each liquid feed control valve **122** to operate to open the flow paths of the switching position **P4** and the switching position **P5**, and close the flow paths of the switching position **P3**, the switching position **P6**, and the switching position **P7**. The control unit **150** controls the flow path opening/closing unit **141** so as to maintain the state in which the first guide path **12a** is open and the second guide path **12b** is closed. The

control unit **150** controls the liquid supply unit **120** so as to apply a positive pressure to the sheath liquid chamber **54** to open the sample chamber **52**, the recovery chamber **51**, the waste chamber **55**, and the reservoir **53** to the atmosphere. In this way the sheath liquid from the sheath liquid chamber **54** is sent to the recovery chamber **51** through the sheath liquid flow path **54a**, the detection region **11**, and the first guide path **12a**. The control unit **150** continues to send the sheath liquid at a predetermined flow rate for a predetermined time, so that a preset amount of the sheath liquid is accommodated in the recovery chamber **51** as a diluted liquid. As a result, the target particle-containing sample **81** is diluted to a predetermined concentration. Note that the dilution step **S4** may be executed before the first sorting step **S1**. In this way the target particle-containing sample **81** and the sheath liquid can be mixed more effectively in the recovery chamber **51**.

(181) Next, the control unit **150** carries out the return step **S2** (see FIG. **8**). In step **S2**, the control unit **150** controls the liquid feeding unit **120** so that the diluted target particle-containing sample **81** in the recovery chamber **51** is returned upstream of the detection region **11** of the first flow path **10**. Specifically, as shown in FIG. **30D**, the control unit **150** causes each liquid feed control valve **122** to operate to open the flow path at the switching position **P6** and close the flow paths at the switching position **P3**, the switching position **P4**, the switching position **P5**, and the switching position **P7**. The control unit **150** controls the flow path opening/closing unit **141** so as to close the first guide path **12a**. The control unit **150** applies a positive pressure to the recovery chamber **51** to control the liquid supply unit **120** so as to open the sample chamber **52**, the sheath liquid chamber **54**, the waste chamber **55**, and the reservoir **53** to the atmosphere. In this way the diluted target particle-containing sample **81** in the recovery chamber **51** is sent to the reservoir **53** through the second flow path **20**. The control unit **150** causes the entire amount of the target particle-containing sample **81** in the recovery chamber **51** to be stored in the reservoir **53**. Note that the time required to feed all the liquid in the recovery chamber **51** can be calculated beforehand from the storage capacity of the recovery chamber **51** and the liquid feed velocity, and the total amount of the liquid in the recovery chamber **51** may be sent from the recovery chamber **51** for a period longer than the calculated time in order to store the entire amount of the diluted target particle-containing sample **81** in the recovery chamber **51** to the reservoir **53**.

(182) Next, the control unit **150** starts the second sorting step **S3** (see FIGS. **8** and **31B**). In step **S31** as shown in FIG. **31B**, the control unit **150** executes a process of feeding the target particle-containing sample **81** of the reservoir **53** and the sheath liquid of the sheath liquid chamber **54** to the first flow path **10**. Specifically, as shown in FIG. **30E**, the control unit **150** causes each liquid feed valve **122** to operate to open the flow paths of the switching position **P4**, the switching position **P5**, and the switching position **P7**, and close the flow paths of the switching position **P3** and the switching position **P6**. The control unit **150** controls the liquid supply unit **120** so as to apply positive pressure to the reservoir **53** and the sheath liquid chamber **54** to open the sample chamber **52**, the recovery chamber **51**, and the waste chamber **55** to the atmosphere. In this way the target particle-containing sample **81** is sent from the reservoir **53** to the first flow path **10** via the connection flow path **53a**, and the sheath liquid is sent from the sheath liquid chamber **54** to the first flow path **10** via the sheath liquid flow path **54a**.

(183) The content of the detection and sorting operations in the second sorting step **S3** are the same as those in the first sorting step **S1**. That is, as shown in FIG. **31B**, the control unit **150** executes the detection process (step **S32**), the sorting process (step **S33**), and the total liquid feed determination process (step **S34**). The detection process (step **S32**), the sorting process (step **S33**), and the total liquid feed determination process (step **S34**) are the same processes of step **S12**, step **S13**, and step **S14** in the first sorting step **S1** of FIG. **31A**, respectively, detailed description thereof will be omitted. As shown in FIG. **30F**, when the target particle **91** is detected in the detection region **11** and the fluorescence intensity obtained from the signal of the detection unit **130** becomes equal to or higher than the threshold value **TH**, the control unit **150** controls the flow path opening/closing unit **141** so as to open the first guide path **12a** and close the second guide path **12b**. When the

fluorescence intensity is less than the threshold value TH, the control unit 150 switches to a state in which the first guide path 12a is closed and the second guide path 12b is opened. In this way the target particle-containing sample 81 is again dispensed into the first guide path 12a.

(184) The second sorting step S3 is carried out until the total amount of the target particle-containing sample 81 in the reservoir 53 has been transferred. After the completion of the second sorting step S3, all the target particle-containing samples 81 resorted into the first guide path 12a are stored in the recovery chamber 51.

(185) Note that in the target particle-containing sample 81 flowing through the first flow path 10, the number of non-target particles 92 is significantly reduced as compared with the sample 80 in the first sorting step S1. Therefore, in the second sorting step S3, the non-target particles 92 mixed in the target particle-containing sample 81 are further removed, and the purity of the target particles 91 in the target particle-containing sample 81 is increased.

(186) Here, the liquid feeding velocity in the second sorting step S3 may be the same as the liquid feeding velocity in the first sorting step S1, or may be different from the liquid feeding velocity in the first sorting step S1. For example, the control unit 150 may control the liquid feeding unit 120 so that the flow velocity of the sample in the first sorting step S1 is greater than the flow velocity of the target particle-containing sample 81 in the second sorting step S3. In other words, the flow velocity of the target particle-containing sample 81 in the second sorting step S3 may be lower than the flow velocity of the sample in the first sorting step S1. The flow velocity of the target particle-containing sample 81 can be adjusted by controlling the pressure regulator 124 and changing the magnitude of the positive pressure supplied to the first flow path 10.

(187) In this way the first sorting step S1 can be completed in a short time. Then, in the second sorting step S3 for the target particle-containing sample 81 whose purity of the target particles 91 has been increased by the first sorting step S1, the sorting accuracy can be improved by feeding the liquid at a relatively low flow velocity. As a result, the purity of the target particles can be effectively improved while shortening the time required for sorting.

(188) As described above, the target particle 91 is sorted by the particle sorter 200 of the present embodiment. In the above description, an example is shown in which the first sorting step S1 and the second sorting step S3 are performed a total of two sorting steps, but the sorting step may be performed three or more times. The third and subsequent sorting steps are a repetition of the dilution step S4, the return step S2, and the second sorting step S3.

## EXAMPLES

(189) Next, the results of various experiments performed for verification of the particle sorter of the present embodiment will be described.

### Examples

(190) The purity of the target particles 91 and required time were measured when a first sorting process and a second sorting process (that is, a total of two sorting steps) were performed by the particle sorter of the embodiment using the micro flow path cartridge 100 shown in FIG. 25.

(191) Sample and Sheath Liquid

(192) As described below, samples were prepared by regarding different types of fluorescent beads as target particles 91 and non-target particles 92. Target particles: Green fluorescent beads (15 μm in diameter, manufactured by Thermo Scientific) Non-target particles: Red fluorescent beads (3.2 μm in diameter, manufactured by Thermo Scientific) Sheath liquid: Ultrapure water containing 2% surfactant

(193) The volume of the sample, the concentration and number of total particles (total of target particles and non-target particles), the number of target particles, and the purity of the target particles are shown in Table 1 below.

(194) TABLE-US-00001

| TABLE 1 | Example                    | Before-sorting sample      | Total particles | Target particles |
|---------|----------------------------|----------------------------|-----------------|------------------|
| Volume  | Concentration              | Quantity                   | Quantity        | Purity           |
| [μL]    | [particles/mL]             | [particles]                | [particles]     | [%]              |
| 100     | 1.17 × 10 <sup>sup.8</sup> | 1.17 × 10 <sup>sup.7</sup> | 653             | 0.0056           |



(195) Note that the purity of the target particles=(number of target particles/total number of particles). The purity (0.0056%) of the target particles in the sample assumes a sorting process using rare particles having an extremely small content in the sample, such as CTC in the blood sample, as the target particles.

(196) After injecting the sample and the sheath liquid into the sample chamber **52** and the sheath liquid chamber **54** of the micro flow path cartridge **100**, respectively, the sorting process by the particle sorter **200** (first sorting step, dilution step, return step, and second sorting step) was carried out under the following conditions.

(197) Experimental Conditions

(198) Sample flow rate: 12.2  $\mu\text{L}/\text{min}$  (set value) Sheath fluid flow velocity: 130  $\mu\text{L}/\text{min}$  Sampling rate of detection unit: 100 kHz Switching speed of flow path opening/closing unit: 310 Hz Amount of sheath liquid added in the dilution step: 200  $\mu\text{L}$

(199) Note that the flow velocity was the same in the first sorting step and the second sorting step.

(200) The results of the sorting process (after the first sorting step and the second sorting step) according to the examples are shown in Table 2 below. Note that the number of particles is the result of measuring the recovered target particle-containing sample with a flow cytometer.

(201) TABLE-US-00002 TABLE 2 Example After 1.sup.st and 2.sup.nd sorting steps Total Target particles particles Quantity Quantity Purity Recovery Processing time Throughput [particles] [particles] [%] rate [%] [sec] [event/sec] 2012 518 25.7 79.2 1442 8114

(202) As a result of the two sorting steps (first sorting step and second sorting step) according to the examples, the purity of the target particles was 25.7% and processing time was 1442 seconds. From Tables 1 and 2, it can be seen that the target particles were concentrated about 4600 times from the purity of the target particles (0.0056%) in the before-sorting sample to the purity of 25.7%. The recovery rate of the target particles was about 80%. In addition, throughput was calculated as an evaluation index for processing efficiency. Throughput=(total number of processed particles/processing time). The sorting for each particle is called an event. The throughput of the examples was 8114 (events/sec).

Comparative Example 1 and Comparative Example 2

(203) Next, the time required to obtain a purity equivalent to the purity (25.7%) of the example was measured in a one-time sorting step as Comparative Example 1 and Comparative Example 2.

(204) For comparison with the Example, in Comparative Example 1 and Comparative Example 2, only one sorting step was carried out using the same micro flow path cartridge as in Example. Therefore, in Comparative Example 1 and Comparative Example 2, the second flow path **20** and the reservoir **53** are not used. The particle sorter **200** used in Comparative Example 1 and Comparative Example 2 was also the same as in the above-mentioned Example.

(205) Sample and Sheath Liquid

(206) The particles and sheath liquid used in Comparative Example 1 and Comparative Example 2 are the same as those in the above-mentioned Example.

(207) Experimental Conditions

(208) Sample flow rate: 10.5  $\mu\text{L}/\text{min}$  (set value) Sheath fluid flow velocity: 130  $\mu\text{L}/\text{min}$  Sampling rate of detection unit: 100 kHz Switching speed of flow path opening/closing unit: 310 Hz

(209) Table 3 below shows the volume of the sample, the concentration and number of total particles (total of target particles and non-target particles), the number of target particles, and the purity of the target particles in Comparative Example 1 and Comparative Example 2.

(210) TABLE-US-00003 TABLE 3 Comparative Example Before-sorting sample Total particles Target particles Volume Concentration Quantity Quantity Purity [ $\mu\text{L}$ ] [particles/mL] [particles] [particles] [%] Comp. 100  $1.051 \times 10^{\text{sup.6}}$   $1.051 \times 10^{\text{sup.5}}$  613 0.58 Ex. 1 Comp. Ex. 2

(211) Here, in Comparative Example 1 and Comparative Example 2, the concentration of the total particles was diluted to 1/100 as compared with the above-mentioned Example. The purity of the target particles in the before-sorting sample was 0.58%.

(212) The results of the sorting process according to Comparative Example 1 and Comparative Example 2 are shown in Table 4 below.

(213) TABLE-US-00004 TABLE 4 Comparative Example After sorting step (one sort only) Total Target Through- particles particles Processing put Quantity Quantity Purity Recovery time [event/ [particles] [particles] [%] rate [%] [sec] sec] Comp. 1824 536 29.4 87.4 343 306 Ex. 1 Comp. 1594 604 37.9 98.5 570 185 Ex. 2

(214) In Comparative Example 1, the purity of the target particles was 29.4%, and in Comparative Example 2, the purity of the target particles was 37.9%. Therefore, in Comparative Example 1 and Comparative Example 2, almost the same results as those in the above-mentioned Examples were obtained with respect to the purity of the sorted target particles.

(215) In Comparative Example 1, the processing time was 343 seconds, and in Comparative Example 2, the processing time was 570 seconds. The throughput of Comparative Example 1 was 306 (event/sec), and the throughput of Comparative Example 2 was 185 (event/sec).

(216) Considerations

(217) As shown in FIG. 32, in the above-mentioned example, it took 1442 seconds to obtain a target particle-containing sample having a purity of 25.7% from the sample having a before-sorting purity of 0.0056%. On the other hand, in Comparative Example 1 (see FIG. 33), it took 343 seconds to obtain a target particle-containing sample having the same purity as that of the Example from a sample having a before-sorting purity of 0.58%, which was 100 times that of Example. In Comparative Example 2, it took 570 seconds.

(218) As described above, in Comparative Example 1 and Comparative Example 2, it was necessary to increase the number of non-target particles 100 times in order to make the purity of the target particles equivalent to that of the above-mentioned Example. In order to process the total amount of the sample (purity of 0.0056%) used in the above Example so that the same results can be obtained by the methods of Comparative Examples 1 and 2, the volume of the sample is 100 times as large as that of the simple calculation and, hence, the processing time required for this is 100 times longer. That is, in the case of Comparative Example 1, a processing time of 34,300 seconds is required. Hence, in the above-mentioned Example (1442 seconds), when the same before-sorting sorting is processed to the same degree of purity, the time required for the sort is reduced to about 1/24 as compared with Comparative Example 1 (34300 seconds).

(219) Throughput is a simple example of this result. It can be seen that in the above embodiment, 8114 particles are processed per second, whereas in Comparative Example 1, only 306 particles are processed per second, and in Comparative Example 2, only 185 particles are processed per second. As shown in FIG. 34, the throughput of the Example is about 27 times that of the Comparative Example 1. From the above, it was confirmed that the particle sorter **200**, the particle sorting method, and the micro flow path cartridge **100** of the present embodiment can shorten the time required for sorting the target particles with sufficient purity.

Comparative Example 3

(220) The result of investigating the relationship between the purity of the target particles and the throughput in the sorting process will be described.

(221) In Comparative Example 3, as shown in Table 5 below, the sorting process was performed only once using three types of before-sorting samples (Sample 1, Sample 2, and Sample 3) in which the ratio of the target particles was adjusted to a constant value and the concentrations of the total particles were different were used. For each sample, the experimental conditions of the sorting step are the same as those of Comparative Example 1 and Comparative Example 2.

(222) TABLE-US-00005 TABLE 5 Comparative Example 3 Sample 1 Sample 2 Sample 3 Total particle concentration 603310 301655 150827 [particles/mL] Target particle ratio [%] 0.53% 0.53% 0.53% Volume [μL] 200 400 800 Processing time [sec] 326 717 1221 Throughput [event/sec] 370 168 99 Purity [%] 26.8 57.6 80.3

(223) Sample 2 is a 2-fold dilution of Sample 1. Sample 3 is a 2-fold dilution of Sample 2. Since

the samples diluted 2-fold are processed under the same experimental conditions, the throughput of sample 2 is about  $\frac{1}{2}$  that of sample 1 and that of sample 3 is about  $\frac{1}{2}$  that of sample 2. As can be seen from Table 5, the purity of Sample 1 was 26.8%, that of Sample 2 was 57.6%, and that of Sample 3 was 80.3%.

(224) Considerations

(225) A graph plotting the relationship between the throughput and the obtained purity for Samples 1 to 3 is shown in FIG. 35. In FIG. 35, the vertical axis is the purity of the target particles and the horizontal axis is the throughput. From FIG. 35, it can be seen that there is a trade-off relationship between the throughput of the sorting process and the purity of the target particles. That is, in the micro flow path cartridge that performs the sorting process only once, such as the interchangeable flow path cartridge **900** of FIG. 36, the trade-off relationship as shown in FIG. 35 is established between the throughput and the purity. It can be seen that it is difficult to increase the throughput (processing speed) beyond this relationship.

(226) FIG. 35 also plots the results of the above embodiment using the micro flow path cartridge **100** of this embodiment. From FIG. 35, it was confirmed that in the present embodiment, processing with high throughput, which cannot be achieved by only one sorting process, is possible. In this way according to the present embodiment the particle sorter **200**, the particle sorting method, and the micro flow path cartridge **100** of the present embodiment were confirmed to reduce the processing time that cannot be achieved by performing the sorting process only once.

(227) In addition to this, the present embodiment has the following advantages.

(228) Consider performing the sorting step a plurality of times similar to the Examples by the user collecting the target particle-containing sample obtained by using the replaceable flow path cartridge **900** (see FIG. 36), which performs the sorting process only once, by a pipette or the like, and injecting that sample again into the replaceable flow path cartridge **900**. However, in this case, since it is necessary to take out the sample to the outside of the cartridge, contamination and human error may occur. In addition, the target particles may be damaged due to pipetting. On the other hand, in the present embodiment, since the plurality of sorting steps are completed only inside the micro flow path cartridge **100**, contamination and human error due to taking out the sample to the outside can be prevented. Moreover, since pipetting is not required, damage to the target particles is suppressed. This can be said to be a great merit especially when performing the sorting process using cells or the like as the target particles **91**.

(229) FACS (Fluorescence assisted cell sorting) using a flow cytometer is another method of particle sorting. While FACS can achieve high throughput, it has disadvantages in that the damage to particles in the sorting process is great and the process is performed in an open environment, so that there is a risk of contamination. On the other hand, in the present embodiment, since the sorting mechanism unit **140** performs sorting by opening and closing the flow path, damage to the particles can be suppressed. Also, since the sorting process is executed only inside the micro flow path cartridge **100**, the occurrence of contamination can be prevented.

(230) It should be noted that the embodiments disclosed herein are exemplary in all respects and are not considered to be restrictive. The scope of the present invention is indicated not by the description of the above embodiments but by the scope of the claims, and includes meanings equivalent to the claims and all changes within the scope thereof.

(231) For example, although the liquid feeding unit **120**, the detection unit **130**, the sorting mechanism **140**, the control unit **150**, the storage unit **151**, and the driver circuit **152** are provided separately from the micro flow path cartridge **100** in the above-described embodiment, at least part of these also may be incorporated in the micro flow path cartridge **100**. For example, the light source **131**, the optical system **132**, and the photodetector **133** that configure the detection unit **130** may be incorporated in the micro flow path cartridge **100**, or the photodetector **133** may be incorporated. The sorting mechanism **140** may be incorporated in the micro flow path cartridge

**100**, the flow path opening/closing unit **141** configuring the sorting mechanism unit **140** may be incorporated, or the liquid feed control valve **122** may be incorporated.

## Claims

1. A particle sorter comprising: a micro flow path cartridge including a first flow path, a second flow path, and a third flow path, an installation part, a liquid feeder, a detector, a sorting device, and a controller, wherein: the first flow path comprises: a detection region where the detector is located to detect target particles contained in a sample, and a sorting region disposed to receive flow from the detection region, the sorting region having at least two flow paths, the sorting region where the sorting device is located for obtaining a target particle-containing sample containing the detected target particles, one end of the second flow path connects to the detection region, and the other end of the second flow path is configured to obtain the target particle-containing sample for returning the target particle-containing sample to the detection region, and one end of the third flow path connects to the detection region, and the other end of the third flow path is configured to obtain other sample that is not the target particle-containing sample for returning the other sample to the detection region; the installation part comprises a cartridge holder for supporting the micro flow path cartridge; the liquid feeder comprises a pressure regulator for providing pressure to drive liquid in the micro flow path cartridge via the first flow path; the detector is configured to output a signal corresponding to the target particle passing through the detection region; the sorting device is configured to perform a sorting operation for obtaining the target particle-containing sample in the sorting region based on the signal from the detector, and the sorting device comprises a flow path opening/closing unit that opens and closes at least one of the flow paths in the sorting region of the first flow path; and the controller is in communication with the liquid feeder and the sorting device, wherein: the controller is programmed to control the liquid feeder such that the target particle-containing sample obtained in the sorting region is returned to the detection region via the second flow path, and the controller is programmed to control the sorting device to perform the sorting operation on the returned target particle-containing sample.
2. The particle sorter according to claim 1, wherein the controller is further programmed to execute: a first sorting process of controlling the liquid feeder so that the sample is fed to the first flow path of the micro flow path cartridge and of controlling the sorting device to obtain the target particle-containing sample by performing the sorting operation based on the signal from the detector; a return process of controlling the liquid feeder so that the target particle-containing sample obtained by the first sorting process is returned to the first flow path via the second flow path; and a second sorting process of controlling the liquid feeder so that the returned target particle-containing sample is fed to the detection region and the sorting region of the first flow path, and of controlling the sorting device to perform the sorting operation based on the signal from the detector.
3. The particle sorter according to claim 2, wherein the controller is further programmed to control the liquid feeder so that flow velocity of the sample in the first sorting process is greater than flow velocity of the target particle-containing sample in the second sorting process.
4. The particle sorter according to claim 1, wherein the controller is further programmed to control the liquid feeder so as to dilute the target particle-containing sample and is programmed to control the sorting device to perform a sorting operation on the diluted target particle-containing sample.
5. The particle sorter according to claim 4, wherein the micro flow path cartridge further comprises a recovery chamber configured to collect the target particle-containing sample; and the controller is further programmed to control the liquid feeder so as to dilute the target particle-containing sample within the recovery chamber.
6. The particle sorter according to claim 5, wherein the controller is further programmed to control the liquid feeder so as to dilute the target particle-containing sample within the recovery chamber

by sending the target particle-containing sample to the recovery chamber that stores a diluting liquid.

7. The particle sorter according to claim 1, wherein the micro flow path cartridge further comprises: a sample chamber for storing the sample to be sent to the first flow path, a reservoir communicating with the second flow path, and a connecting flow path connecting the reservoir and the detection region of the first flow path; and the controller is further programmed to control the sorting device so as to obtain the target particle-containing sample from the sample sent from the sample chamber to the first flow path, and is programmed to control the liquid feeder so that the target particle-containing sample is returned to the first flow path via the second flow path, the reservoir and the connecting flow path.

8. The particle sorter according to claim 1, wherein the micro flow path cartridge further comprises a sample chamber for storing a sample to be fed to the first flow path; and the controller is further programmed to control the liquid feeder so as to obtain the target particle-containing sample from the sample sent from the sample chamber to the first flow path, and return the target particle-containing sample to the first flow path via the second flow path and the sample chamber.

9. The particle sorter according to claim 1, wherein the controller is further programmed to control the liquid feeder so as to return the sample that was not obtained as the target particle-containing sample in the sorting region of the first flow path to the detection region of the first flow path via the third flow path and to feed the returned sample to the detection region of the first flow path, and is programmed to control the sorting device to perform the sorting operation based on the signal from the detector.

10. The particle sorter according to claim 1, wherein the micro flow path cartridge further comprises a recovery chamber for collecting the obtained target particle-containing sample, and wherein the sorting region of the first flow path is configured so as to branch the first flow path into a first guide path that guides the target particle-containing sample to the recovery chamber and a second guide path different from the first guide path; and the controller is further programmed to control the sorting device so as to guide the target particle-containing sample to the first guide path.

11. The particle sorter according to claim 1, wherein the flow path opening/closing unit comprises a pinch valve, and is configured to close at least one of the flow paths in the sorting region via deformation by pressing a region of the micro flow path cartridge in which at least one of the flow paths is formed.

12. The particle sorter according to claim 11, wherein the flow path opening/closing unit comprises a displacement-enhancing piezoelectric actuator.

13. The particle sorter according to claim 12, wherein the displacement-enhancing piezoelectric actuator comprises: a movable member having a pressing part facing a pressing position of the micro flow path cartridge, a piezoelectric element for moving the movable member, and a fixing member for holding the piezoelectric element and the movable member; and the movable member is configured to displace the pressing part with a displacement amount larger than a displacement amount of the piezoelectric element.

14. The particle sorter according to claim 1, wherein the first flow path and the second flow path have: a depth of 1  $\mu\text{m}$  or more and 1000  $\mu\text{m}$  or less, and a width of 1  $\mu\text{m}$  or more and 1000  $\mu\text{m}$  or less.

---