

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12405241
B2
September 02, 2025
Sun; Yu Long et al.

Electrochemical test strip for testing multiple indicators, and testing method thereof

Abstract

The present invention provides an electrochemical test strip (200) for detecting multiple indicators and a test method thereof. The electrochemical test strip includes a first biosensor (100) provided with an insulating substrate (1), a first electrode system, a first channel forming layer (4) and a first upper cover layer (5), and a second biosensor (101) provided with an insulating substrate (8), a second electrode system, a second channel forming layer (11) and a second upper cover layer (12). The first biosensor (100) and the second biosensor (101) are located on the front and back sides of the electrochemical test strip (200), respectively. A sample addition port (6) of the electrochemical test strip (200) is in liquid communication with a first channel forming area (55) of the first biosensor (100) and a second channel forming area (56) of the second biosensor (101), respectively.

Inventors: Sun; Yu Long (Zhejiang, CN), Cheng; Yan (Zhejiang, CN), Zhang; Li (Zhejiang, CN), Huang; Yong Gang (Zhejiang, CN), Shi; Jin Liang (Zhejiang, CN)

Applicant: LEADWAY (HK) LIMITED (Sheung Wan Hong Kong, CN)

Family ID: 76772277

Assignee: LEADWAY (HK) LIMITED (Sheung Wan Hong Kong, CN)

Appl. No.: 18/003383

Filed (or PCT Filed): January 13, 2021

PCT No.: PCT/CN2021/071526

PCT Pub. No.: WO2021/143730

PCT Pub. Date: July 22, 2021

Prior Publication Data

Foreign Application Priority Data

CN202020074643.1Jan. 14, 2020

Publication Classification

Int. Cl.: G01N27/30 (20060101); G01N27/327 (20060101); G01N27/416 (20060101)

U.S. Cl.:

CPCG01N27/307 (20130101); G01N27/3275 (20130101); G01N27/4161 (20130101);

Field of Classification Search

CPC:G01N (27/26); G01N (27/30); G01N (27/307); G01N (27/3275); G01N (27/4161); G01N (27/327); G01N (27/3272)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5997817	12/1998	Crismore et al.	N/A	N/A
6299757	12/2000	Feldman et al.	N/A	N/A
7144485	12/2005	Hsu et al.	N/A	N/A
8021528	12/2010	Jang	N/A	N/A
8182747	12/2011	Marquant et al.	N/A	N/A
8323467	12/2011	MacFie et al.	N/A	N/A
8617366	12/2012	Winarta et al.	N/A	N/A
8632664	12/2013	MacFie et al.	N/A	N/A
2005/0247573	12/2004	Nakamura	204/403.01	G01N 27/3272
2007/0068808	12/2006	Lee	N/A	N/A
2008/0149480	12/2007	Bell	204/403.14	C12Q 1/001
2015/0072404	12/2014	Chen	N/A	N/A
2015/0276671	12/2014	Huang et al.	N/A	N/A
2017/0176410	12/2016	Hughes et al.	N/A	N/A
2019/0233870	12/2018	Buck et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
203519550	12/2013	CN	N/A
204129003	12/2014	CN	N/A
204594927	12/2014	CN	N/A
106353387	12/2016	CN	N/A
106996951	12/2016	CN	N/A
107085023	12/2016	CN	N/A
206876623	12/2017	CN	N/A

207020121	12/2017	CN	N/A
109115854	12/2018	CN	N/A
109358101	12/2018	CN	N/A
109946352	12/2018	CN	N/A
109946353	12/2018	CN	N/A
209148584	12/2018	CN	N/A
113125528	12/2020	CN	N/A
113125529	12/2020	CN	N/A
214539366	12/2020	CN	N/A
214539367	12/2020	CN	N/A
214749932	12/2020	CN	N/A
215894465	12/2021	CN	N/A
215894466	12/2021	CN	N/A
0533229	12/2004	KR	N/A
2021143730	12/2020	WO	N/A

OTHER PUBLICATIONS

English Machine Translation CN109115854 (Year: 2018). cited by examiner

International Preliminary Report on Patentability issued in PCT/CN2021/071526 dated Jul. 19, 2022—incl Engl lang tansl (13 pages total). cited by applicant

First Office Action issued by CNIPA in Chinese Patent Application No. 202110042814.1 dated Jan. 12, 2023—incl Engl lang tansl (9 pages total). cited by applicant

Response to First Office Action issued by CNIPA in Chinese Patent Application No.

202110042814.1 dated May 16, 2023—incl Engl lang tansl (8 pages total). cited by applicant

First Office Action issued by CNIPA in Chinese Patent Application No. 202110044560.7 dated Jan. 12, 2023—incl Engl lang tansl (9 pages total). cited by applicant

Response to First Office Action issued by CNIPA in Chinese Patent Application No.

202110044560.7 dated May 16, 2023—incl Engl lang tansl (8 pages total). cited by applicant

International Search Report issued in PCT/CN2021/071526 on Apr. 1, 2021. cited by applicant

Primary Examiner: Kaur; Gurpreet

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) The present invention is filed under 35 U.S.C. § 371 as the U.S. national phase of International Application No. PCT/CN2021/071526, filed Jan. 13, 2021, which designated the United States and claims the benefit of priority of Chinese Patent Application No. 202020074643.1 filed Jan. 14, 2020, the contents of each of which are being hereby incorporated by reference in their entirety for all purposes.

FIELD OF THE INVENTION

(2) The present invention relates to a electrochemical test strip for detecting multiple indicators in a sample such as blood and a test method thereof, belonging to the technical field of electroanalytical chemical detection.

BACKGROUND OF THE INVENTION

(3) Electrochemical test strips with an electrode system have been widely used for rapid detection of biological samples, for example, for detection of various physiological indicators such as glucose, cholesterol and blood ketone in a blood sample. The basic structure of an electrochemical

test strip includes an insulating substrate, an electrode system located on the insulating substrate, a channel forming layer, and an upper cover. The electrode system includes at least a working electrode and a counter electrode, and a reaction reagent covers at least one working electrode. A sample under detection passes through a channel forming area on the channel forming layer to react with the reaction reagent and generate a detectable signal. An analyzer connected to the electrochemical test strip arrives at a detection result according to this signal.

(4) At present, most existing electrochemical test strips can only detect single sample indicator, and if multiple indicators are to be detected, different electrochemical test strips can only be used to detect different physiological indicators respectively. If it needs to complete detection of multiple physiologic indicators, patients must be subjected to blood sample collection multiple times. Multiple times of sampling not only bring pain to patients, but also take a long detection time and have cumbersome detection steps.

(5) Chronic kidney disease and its resulting end-stage renal disease are a group of common chronic progressive diseases that pose a serious threat to human life and health, and have the characteristics of high prevalence, high mortality, high health care expenditure, low awareness rate, etc. In the diagnosis of renal function indicators of patients suffering from chronic renal disease, it is often necessary to obtain three physiological indicators—creatinine, urea and uric acid—in blood at the same time. Through detecting the three indicators, the degree of renal diseases of patients can be effectively detected and corresponding judgments can be made, which can be used as the basis for selecting further therapeutic regimens. At present, the detection of renal function indicators in the market mainly uses a single indicator test kit in conjunction with a large biochemical equipment. The test kit is expensive, long in test time and cumbersome in test steps, and thus is not suitable for popularization in townships and community health centers.

SUMMARY OF THE INVENTION

(6) In view of deficiencies of the detection in the prior art, the present invention provides a novel electrochemical test strip which is available for detecting multiple sample indicators, thereby overcoming the limitations of the prior art: detection of only single sample indicator and the detection is dependent on use of a large biochemical equipment. The electrochemical test strip can be applied to detection in conjunction with a portable detecting instrument, and has the characteristics of small size, anti-interference property, low price and disposability, which provides convenience for inspection operations.

(7) The present invention provides an electrochemical test strip for detecting multiple indicators, comprising a first biosensor which comprises an insulating substrate, a first electrode system disposed on the insulating substrate, a first channel forming layer and a first upper cover layer, a first channel forming area disposed in the first channel forming layer, the first channel forming area disposed above at least one electrode of the first electrode system, wherein the electrochemical test strip further comprises a second biosensor, and the second biosensor comprises an insulating substrate, a second electrode system disposed on the insulating substrate, a second channel forming layer and a second upper cover layer, a second channel forming area disposed in the second channel forming layer, the second channel forming area disposed above at least one electrode of the second electrode system; the first biosensor and the second biosensor are located on the front and back sides of the electrochemical test strip, respectively, and the electrical connection end of the first biosensor and the electrical connection end of the second biosensor are located at the same end of the electrochemical test strip; and the sample addition port of the electrochemical test strip is in liquid communication with the first channel forming area of the first biosensor and the second channel forming area of the second biosensor respectively.

(8) Further, the first electrode system comprises an electrode system for measuring a first indicator and an electrode system for measuring a second indicator.

(9) Further, the second electrode system comprises an electrode system for measuring a third indicator.

(10) Further, the second electrode system comprises an electrode system for measuring a fourth indicator.

(11) Further, the electrode system for measuring the first indicator and the electrode system for measuring the second indicator are located on two opposed sides of the sample addition port, respectively.

(12) Further, the electrode system for measuring the third indicator and the electrode system for measuring the fourth indicator are located on two opposed sides of the sample addition port, respectively.

(13) Further, the first biosensor and the second biosensor share one insulating substrate, or the first biosensor and the second biosensor each comprise an insulating substrate.

(14) Further, a first reaction region forming layer is disposed between the insulating substrate and first channel forming layer of the first biosensor, and/or a second reaction region forming layer is disposed between the insulating substrate and second channel forming layer of the second biosensor.

(15) Further, the sample addition port comprises a notch in the first upper cover layer and a notch in the second upper cover layer.

(16) Further, the notches in the first upper cover layer and the second upper cover layer are located on the same side of the electrochemical test strip and aligned in position, and the notch in the first upper cover layer is larger than that in the second upper cover layer.

(17) Further, the electrochemical test strip is also provided with a label for distinguishing the front and back sides of the electrochemical test strip.

(18) Further, the label is a conductive automatic power-on contact and is disposed in at least one of the insulating substrate of the first biosensor and the insulating substrate of the second biosensor.

(19) Further, the label is a colored insulating material; when the first upper cover layer and the first upper cover layer are transparent, the side of the insulating substrate of the first biosensor facing the first channel forming layer and the side of the insulating substrate of the second biosensor facing the second channel forming layer are made of materials of different colors; and when the first upper cover layer and the second upper cover layer are opaque, the first upper cover layer and the second upper cover layer are made of materials of different colors.

(20) Further, the electrochemical test strip is used for measuring at least two indicators of glucose, cholesterol, hemoglobin, glycosylated hemoglobin, uric acid, urea, creatinine, bilirubin, ketone body, HCT and pH value. A method for detecting multiple indicators comprises providing the electrochemical test strip as described in the present invention.

(21) The present invention further provides an electrochemical test strip for detecting renal function indicators, comprising a first biosensor which comprises an insulating substrate, a first electrode system disposed on the insulating substrate, a first channel forming layer and a first upper cover layer, a first channel forming area disposed in the first channel forming layer, the first channel forming area disposed above at least one electrode of the first electrode system, wherein the electrochemical test strip further comprises a second biosensor, and the second biosensor comprises an insulating substrate, a second electrode system disposed on the insulating substrate, a second channel forming layer and a second upper cover layer, a second channel forming area disposed in the second channel forming layer, the second channel forming area disposed above at least one electrode of the second electrode system; the electrochemical test strip further comprises a sample addition port in liquid communication with the first channel forming area of the first biosensor and the second channel forming area of the second biosensor, respectively; the first biosensor and the second biosensor are located on the front and back sides of the electrochemical test strip, respectively; and the first biosensor is used for determining two indicators of urea, creatinine and uric acid, and the second biosensor is used for determining a remaining third indicator of urea, creatinine and uric acid.

(22) Further, the first electrode system comprises an electrode system for measuring urea and an

electrode system for measuring creatinine.

(23) Further, the second electrode system comprises an electrode system for measuring uric acid.

(24) Furthermore, urea is measured using a potentiometric method.

(25) Further, creatinine or uric acid is measured using an amperometric method.

(26) Further, the electrode system for measuring urea and the electrode system for measuring creatinine are located on two opposed sides of the sample addition port, respectively.

(27) Further, the second electrode system further comprises an electrode system for measuring HCT.

(28) Further, the first channel forming area is divided into two parts, the first part of the first channel forming area is disposed above the electrode system for measuring creatinine, the second part of the first channel forming area is disposed above the electrode system for measuring urea, and the width of the first part of the first channel forming area is greater than the width of the second part of the first channel forming area.

(29) Further, a first reaction region forming layer is disposed between the insulating substrate and first channel forming layer of the first biosensor, and/or a second reaction region forming layer is disposed between the insulating substrate and second channel forming layer of the second biosensor.

(30) A method for detecting renal function indicators comprises providing the electrochemical test strip as described in the present invention.

(31) The present invention further provides an electrochemical test strip, comprising a first biosensor which comprises an insulating substrate, a first electrode system disposed on the insulating substrate, and a first channel forming layer, a first channel forming area disposed in the first channel forming layer, the first channel forming area disposed above at least one electrode of the first electrode system, the sample addition port being in liquid communication with the first channel forming area, wherein the first electrode system comprises an electrode system for measuring a first indicator and an electrode system for measuring a second indicator, and the electrode system for measuring the first indicator and the electrode system for measuring the second indicator are located on two opposed sides of the sample addition port, respectively.

(32) Further, the first biosensor is provided with a hydrophilic element located at or near a diverging point of the first biosensor.

(33) Further, the hydrophilic element is located below the first channel forming area.

(34) Further, the first electrode system comprises an electrode system for measuring a first indicator and an electrode system for measuring a second indicator, and the hydrophilic element is located between the electrode system for measuring the first indicator and the electrode system for measuring the second indicator.

(35) Further, a hydrophobic insulating region is disposed between the hydrophilic element and the first electrode system of the first biosensor.

(36) Further, the electrochemical test strip also comprises a second biosensor, which comprises an insulating substrate, a second electrode system disposed on the insulating substrate, a second channel forming layer and a second upper cover layer, wherein a second channel forming area is disposed in the second channel forming layer, the second channel forming area disposed above at least one electrode of the second electrode system; and the first biosensor and the second biosensor are disposed on the front and back sides of the electrochemical test strip, respectively.

(37) Further, the first biosensor and the second biosensor share one insulating substrate, or the first biosensor and the second biosensor each comprise an insulating substrate.

(38) Further, the second biosensor is provided with a hydrophilic element located at or near a diverging point of the second biosensor.

(39) Further, the second electrode system comprises an electrode system for measuring a third indicator and an electrode system for measuring a fourth indicator, and the hydrophilic element is located between the electrode system for measuring the third indicator and the electrode system for

measuring the fourth indicator.

(40) Further, a hydrophobic insulating region is disposed between the hydrophilic element and the second electrode system of the second biosensor.

(41) The present invention further provides an electrochemical test strip for detecting multiple indicators in a sample, which comprises a sample addition port and a first biosensor, the first biosensor comprising an insulating substrate, a first electrode system disposed on the insulating substrate, a first channel forming layer and a first upper cover layer, a first channel forming area disposed in the first channel forming layer, the first channel forming area disposed above at least one electrode of the first electrode system, wherein the electrochemical test strip further comprises a second biosensor, and the second biosensor comprises an insulating substrate, a second channel forming layer and a second upper cover layer, a second channel forming area disposed in the second channel forming layer, the second channel forming area disposed above at least one electrode of the second electrode system; and the first biosensor and the second biosensor are located on the front and back sides of the electrochemical test strip, respectively.

(42) Further, the sample addition port comprises a notch disposed in the insulating substrate of the first biosensor and a notch disposed in the insulating substrate of the second biosensor, a notch disposed in the first channel forming layer and being in liquid communication with the first channel forming area, a notch disposed in the second channel forming layer and being in liquid communication with the second channel forming area, and a notch disposed in the first upper cover layer and a notch disposed in the second upper cover layer; and the notches in the insulating substrate, the first channel forming layer and the first upper cover layer of the first biosensor and the notches in the insulating substrate, the second channel forming layer and the second upper cover layer of the second biosensor are located on the same side of the electrochemical test strip and aligned in position.

(43) Further, the notch in the first upper cover layer is larger than the notch in the second upper cover layer.

(44) Further, the sample addition port comprises a first sample addition port located in the first biosensor and a second sample addition port located in the second biosensor, and the first sample addition port and the second sample addition port are located on the same side or two opposite sides of the electrochemical test strip.

(45) Further, a first reaction region forming layer is disposed between the insulating substrate and the first channel forming layer of the first biosensor, and a second reaction region forming layer is disposed between the insulating substrate and the second channel forming layer of the second biosensor.

(46) Further, the first reaction region forming layer is provided with a notch in a position corresponding to the notch in the first channel forming layer, and the second reaction region forming layer is provided with a notch in a position corresponding to the notch in the second channel forming layer.

(47) Beneficial effects of the present invention: (1) the electrochemical test strip adopted in the present invention is assembled by two biosensors to achieve electrode arrangement on the its front and back sides, so that a single electrochemical test strip can be utilized to detect multiple indicators. (2) The sample addition port employs a notch design, and the dimension of the notch located in the first upper cover layer in the first biosensor is larger than that of the notch in the second upper cover layer in the second biosensor, which is beneficial to loading the sample on the second insulating substrate of the second biosensor, facilitating the rapid flow of the sample into the electrochemical test strip. (3) Diffusion components assisting diffusion of reaction reagents can be disposed at two ends of each electrode used for detecting creatinine, urea and uric acid, which is conducive to the diffusion of the reaction reagents in corresponding reaction regions. (4) Whether in the first biosensor or in the second biosensor, there is a sample filling electrode made of carbon ink, which not only can be used for detecting whether the sample flowing to the first electrode

system or the second electrode system is adequate but also can function as a diffusion component. (5) In the detection of four indicators consisting of urea, creatinine, uric acid and HCT, the HCT value measured once can simultaneously achieve HCT correction on the measured values of three analytes, i.e., creatinine, uric acid and urea, and eventually complete the detection on multiple indicators including creatinine, uric acid, urea, HCT and the like in a short time, and the detection results are accurate.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 shows an exploded view of a first biosensor of a first electrochemical test strip, with the first insulating substrate without a notch.
- (2) FIG. 2 is a schematic diagram of the first biosensor in FIG. 1 when being assembled together.
- (3) FIG. 3 is an exploded diagram of a second biosensor of the first electrochemical test strip, with the second insulating substrate without a notch.
- (4) FIG. 4 is a schematic diagram of the second biosensor in FIG. 3 when being assembled together.
- (5) FIG. 5 is an exploded view of a second electrochemical test strip.
- (6) FIG. 6 is a schematic diagram of the electrochemical test strip in FIG. 5 when being assembled together.
- (7) FIG. 7 is a lateral schematic diagram of the electrochemical test strip, with the first biosensor and the second biosensor not sharing the same insulating substrate.
- (8) FIG. 8 is a lateral schematic diagram of the electrochemical test strip, with the first biosensor and the second biosensor sharing the same insulating substrate.
- (9) FIG. 9 is an exploded view of a first biosensor of a third electrochemical test strip, with one side of the first insulating substrate provided with a notch.
- (10) FIG. 10 shows an exploded view of a second biosensor of the third electrochemical test strip, with one side of the second insulating substrate provided with a notch.
- (11) FIG. 11(a) is a schematic diagram of the first biosensor in FIG. 9 when being assembled together, and FIG. 11(b) shows a schematic view of the second biosensor in FIG. 10 when being assembled together, with the dimension of the notch located on one side of the first upper cover layer being larger than that of the notch located on one side of the second upper cover layer.
- (12) FIG. 12(a) is a schematic diagram of the first biosensor in FIG. 9 when being assembled together, and FIG. 12(b) differs from FIG. 11b is that the dimension of the notch located on one side of the first upper cover layer is equal to that of the notch located on one side of the second upper cover layer.
- (13) FIG. 13(a) is an exploded view of a first biosensor of a fourth electrochemical test strip, and FIG. 13(b) is a schematic diagram of the first biosensor in (a) when being assembled together.
- (14) FIG. 14 is a schematic diagram of the first biosensor containing a hydrophilic element when being assembled together.
- (15) FIG. 15 is a schematic diagram of the second biosensor containing a hydrophilic element when being assembled together.
- (16) FIG. 16 is a schematic diagram of the second biosensor including an automatic power-on contact when being assembled together.
- (17) FIG. 17 is a linearity experiment evaluation diagram of urea.
- (18) FIG. 18 is a linearity experiment evaluation diagram of creatinine.
- (19) FIG. 19 is a linearity experiment evaluation diagram of uric acid.

DETAILED DESCRIPTION OF THE EMBODIMENTS

- (20) In a first embodiment of the invention, as shown in FIGS. 1 to 7, an electrochemical test strip

200 includes a first biosensor **100** and a second biosensor **101**, and the first biosensor **100** and the second biosensor **101** do not share the same insulating substrate. The first biosensor **100** has a first electrical connection end **7** and the second biosensor **101** has a second electrical connection end **13**. The electrochemical test strip **200** can be connected with an electrical connector of a detecting instrument by locating the first electrical connection end **7** and the second electrical connection end **13** at the same end of the electrochemical test strip **200**. The sample addition port of the electrochemical test strip **200** includes a first sample addition port **601** located on the lateral side of the first biosensor **100** and a second sample addition port **602** located on the lateral side of the second biosensor **101**.

(21) The first biosensor **100** is sequentially provided with a first insulating substrate **1**, a first electrode system disposed on the first insulating substrate **1**, a first reaction region forming layer **3**, a first channel forming layer **4** and a first upper cover layer **5**. The first insulating substrate **1**, the first reaction region forming layer **3**, the first channel forming layer **4** and the first upper cover layer **5** are all made of an insulating material. The first electrode system includes a first indicator reference electrode **21**; a first indicator working electrode **22**; a second indicator working electrode **23**; a second indicator counter electrode **24**; first conductive contact **79**, second conductive contact **77**, third conductive contact **76** and fourth conductive contact **80** located at the first electrical connection end **7**, and a first conductive trace **74** connecting the first indicator reference electrode **21** with the first contact **79**, a second conductive trace **82** connecting the first indicator working electrode **22** with the second contact **77**, a third conductive trace **72** connecting the second indicator working electrode **23** with the third contact **76**, and a fourth conductive trace **73** connecting the second indicator counter electrode **24** with the fourth contact **80**. The first indicator reference electrode **21** and first indicator working electrode **22** are located on one side of the first sample addition port **601**, and the second indicator working electrode **23** and second indicator counter electrode **24** are located on the other opposite side of the first sample addition port **601**.

(22) The first reaction region forming layer **3** covers the first electrode system. The first reaction region forming layer **3** has three spaced reaction regions: a first reaction region **42**, a second reaction region **41** and a third reaction region **43**. The shapes of the reaction regions can be selected from rectangle, oval, circle, chamfered rectangle and other geometric shapes. The second reaction region **41** contains a first indicator first reaction reagent, the first reaction region **42** contains a first indicator second reaction reagent, and the third reaction region **43** contains a second indicator reaction reagent. The third reaction region **43** at least partially exposes the second indicator working electrode **23** and the second indicator counter electrode **24**, the second reaction region **41** at least partially exposes the first indicator reference electrode **21**, and the first reaction region **42** at least partially exposes the first indicator working electrode **22**.

(23) The first channel forming layer **4** is disposed over the first reaction region forming layer **3**, the first channel forming layer **4** has a first channel forming area **55**, a notch **62** is disposed on one side of the first channel forming layer **4**, and the notch **62** is in fluid communication with the first channel forming area **55**. Preferably, the first channel forming area **55** is located in the middle region of the first channel forming layer **4**, and the notch **62** is located in the middle part of one side of the first channel forming layer **4**. The notch **62** divides the first channel forming area **55** into two parts. After a sample is added from the first sample addition port **601**, the sample enters into the first biosensor **100**, and when the sample enters into the first channel forming layer **4** through the notch **62**, sample diverging occurs at this moment, with one part of the sample flowing into the first part of the first channel forming area **55** and the other part of the sample flowing into the second part of the first channel forming area **55**. The sample flowing into the first part of the first channel forming area **55** eventually flows to the second indicator working electrode **23** and the second indicator counter electrode **24** through the third reaction region **43**, and the sample flowing into the second part of the first channel forming area **55** eventually flows to the first indicator reference electrode **21** and the first indicator working electrode **22** through the second reaction

region **41** and the first reaction region **42**.

(24) The first part of the first channel forming area **55** at least partially exposes the third reaction region **43**. The second part of the first channel forming area **55** at least partially exposes the second reaction region **41** and the first reaction region **42**, and the width of the first part of the first channel forming area **55** may be less than, equal to, or greater than the width of the second part of the first channel forming area **55**. For example, when the first indicator under detection is urea and the second indicator under detection is creatinine, the width of the first part of the first channel forming area **55** is greater than the width of the second part of the first channel forming area **55**, which can completely expose the third reaction region **43** and the advantage is that when the concentration of an indicator such as creatinine in the sample is detected by the amperometric method, the detected current signal is related to the area of the third reaction region **43**, and when the third reaction region **43** is completely exposed by the first part of the first channel forming area **55**, all of the third reaction region **43** is effective area and can generate effective signals, so that the usage amounts of reaction reagents can be reduced; and when the concentration of an indicator such as urea in the sample is detected by the potentiometric method, the detected potential signal is not much correlated with the area of the second reaction region **41** and the first reaction region **42**, so that reducing the width of the second part of the first channel forming area **55** can reduce the usage amount of the sample.

(25) The first upper cover layer **5** is disposed over the first channel forming layer **4**. The first upper cover layer **5** forms a first sample channel together with the first channel forming area **55**, the second reaction region **41**, the first reaction region **42** and the third reaction region **43**.

(26) The first upper cover layer **5** is provided with a first air hole **51** and a second air hole **52** for discharging the air in the first sample channel during sample addition. The first air hole **51** is located above the first part of the first channel forming area **55** and is in communication with the first part of the first channel forming area **55** on the air path. The second air hole **52** is located above the second part of the first channel forming area **55** and in communication with the second part of the first channel forming area **55** on the air path.

(27) The second biosensor **101** is sequentially provided with a second insulating substrate **8**, a second electrode system disposed on the second insulating subsystem substrate **8**, a second reaction region forming layer **10**, a second channel forming layer **11** and a second upper cover layer **12**. The second insulating substrate **8**, the second reaction region forming layer **10**, the second channel forming layer **11** and the second upper cover layer **12** are all made of an insulating material.

(28) The second electrode system includes a third indicator counter electrode **29**, a third indicator working electrode **30**, fifth conductive contact **86** and sixth conductive contact **84** located at the second electrical connection end **13**, a fifth conductive trace **91** connecting the third indicator counter electrode **29** with the fifth contact **86**, and a sixth conductive trace **89** connecting the third indicator working electrode **30** with the sixth contact **84**. More conductive traces or contacts can be disposed on the second insulating substrate **8** as needed.

(29) The second reaction region forming layer **10** covers the second electrode system. The second reaction region forming layer **10** has a fourth reaction region **46**. The shape of the fourth reaction region **46** can be selected from rectangle, oval, circle, chamfered rectangle and other geometric shapes. The fourth reaction region **46** contains a third indicator reaction reagent. Preferably, the fourth reaction region **46** partially exposes the third indicator counter electrode **29** and the third indicator working electrode **30**.

(30) The second channel forming layer **11** is disposed over the second reaction region forming layer **10**, the second channel forming layer **11** has a second channel forming area **56**, a notch **66** is disposed on one side of the second channel forming layer **11**, and the notch **66** is in fluid communication with one end or the middle part of the second channel forming area **56**. After a sample is added through the second sample addition port **602**, the sample enters into the second biosensor **101** and then enters into the second channel forming area **56** through the notch **66** and

eventually flows to the third indicator counter electrode **29** and the third indicator working electrode **30**.

(31) The second upper cover layer **12** is disposed over the second channel forming layer **11**. The second upper cover layer **12** forms a second sample channel together with the second channel forming area **56** and the fourth reaction region **46**. The second upper cover layer **12** contains a third air hole **53**. The second sample channel is used to provide a sample to the third indicator counter electrode **29** and the third indicator working electrode **30**, dissolve the reaction reagent in the fourth reaction region **46** and react to generate an electrical signal. The third air hole **53** is located above the second sample channel, and is in communication with the second sample channel on the air path to discharge the air in the second sample channel when the sample is added.

(32) In the first biosensor **100**, one side of the first upper cover layer **5** is provided with a notch **61**, one side of the first channel forming layer **4** is provided with a notch **62**, and one side of the first reaction region forming layer **3** is provided with a notch **63**. The first insulating substrate **1** is without a notch. The notch **61**, the notch **62** and the notch **63** are disposed on the same side of the first biosensor **100** and are aligned in position. The word “align(ed)” as mentioned herein refers to that when two notches are aligned, one of the two notches completely overlaps with the projected region of the other notch if the dimensions (i.e., size and/or shape) of the two notches are the same, and one of the notches is located inside the projected region of the other notch if the dimensions of the two notches are not the same. When the first insulating substrate **1**, the first reaction region forming layer **3**, the first channel forming layer **4** and the first upper cover layer **5** of the first biosensor **100** are assembled together, the notch **61**, the notch **62** and the notch **63** together form the first sample addition port **601**. In the second biosensor **101**, one side of the second upper cover layer **12** is provided with a notch **65**, one side of the second channel forming layer **11** is provided with a notch **66**, and one side of the second reaction region forming layer **10** is provided with a notch **67**. The second insulating substrate **8** is without a notch. The notch **65**, the notch **66** and the notch **67** are disposed on the same side of the second biosensor **101** and are aligned in position. When the second insulating substrate **8**, the second reaction region forming layer **10**, the second channel forming layer **11** and the second upper cover layer **12** of the second biosensor **101** are assembled together, the notch **65**, the notch **66** and the notch **67** together form the second sample addition port **602**. As neither the first insulating substrate **1** nor the second insulating substrate **8** is provided with a notch, the first sample addition port **601** and the second sample addition port **602** do not form into a whole. When the first biosensor **100** and the second biosensor **101** are assembled together, the first sample addition port **601** and the second sample addition port **602** are located on the same side of the electrochemical test strip **200** and are aligned in position. The first sample addition port **601** and the second sample addition port **602** may also be located on the same side of the electrochemical test strip **200**, but not aligned in position, and furthermore, the first sample addition port **601** and the second sample addition port **602** may also be located on different sides of the electrochemical test strip **200**.

(33) When the first biosensor **100** and the second biosensor **101** are assembled together, after the sample is added through the first sample addition port **601**, the sample flows into the first biosensor **100** and enters into the first channel forming area **55** through the notch **61** and the notch **62**, and the notch **62** divides the first channel forming area **55** into two parts, therefore, the sample entering the first channel forming area **55** undergoes diverging at this time, with one part of the sample flowing into the first part of the first channel forming area **55**, and the other part of the sample flowing into the second part of the first channel forming area **55**. The sample flowing into the first part of the first channel forming area **55** eventually flows to the second indicator working electrode **23** and the second indicator counter electrode **24** through the third reaction region **43**, and the sample flowing into the second part of the first channel forming area **55** eventually flows to the first indicator reference electrode **21** and the first indicator working electrode **22** through the second reaction region **41** and the first reaction region **42**. After the sample is added through the second sample

addition port **602**, the sample enters into the second biosensor **101** and then enters into the second channel forming area **56** through the notch **65** and the notch **66**, and the sample flowing into the second channel forming area **56** passes through the fourth reaction region **46** and eventually flows to the third indicator counter electrode **29** and the third indicator working electrode **30**.

(34) In the electrochemical test strip of the present invention, the first indicator reference electrode **21** and the first indicator working electrode **22** are used to detect the first indicator in the sample, the second indicator working electrode **23** and the second indicator counter electrode **24** are used to detect the second indicator in the sample, and the third indicator counter electrode **29** and the third indicator working electrode **30** are used to detect the third indicator in the sample. The first, second and third indicators can be the levels of analytes such as glucose, cholesterol, hemoglobin, glycosylated hemoglobin, uric acid, urea, creatinine, bilirubin and ketone body in the sample, or the physicochemical properties of the sample, such as pH value and HCT, or whether the added amount of the sample is adequate. During the detection, electrochemical parameters such as current, potential, electric quantity, conductance and resistance generated after addition of the sample can be detected as needed, and then the levels or presence or absence of the different indicators to be measured can be determined based on the detected electrochemical parameters.

(35) The second reaction region **41** contains the first indicator first reaction reagent, the first reaction region **42** contains the first indicator second reaction reagent, the third reaction region **43** contains the second indicator reaction reagent, and the fourth reaction region **46** contains the third indicator reaction reagent. The four reaction reagents can be respectively added to the corresponding reaction regions by a method such as solution dropping or screen printing. The present invention combines solution dropping and screen printing methods to add the four reaction reagents to the corresponding four reaction regions, respectively.

(36) For the sake of facilitating illustration, here the first indicator reference electrode **21** and the first indicator working electrode **22** detect urea in the sample by the potentiometric method, the second indicator working electrode **23** and the second indicator counter electrode **24** detect creatinine in the sample by the amperometric method, and the third indicator counter electrode **29** and the third indicator working electrode **30** detect uric acid in the sample by the amperometric method. In order to detect urea, the first indicator first reaction reagent contains a buffer, such as PBS; a polymer binder, such as methylcellulose; a surfactant, such as Triton X-100; and urease. The first indicator second reaction reagent contains a buffer, such as PBS; a polymer binder, such as methylcellulose; a surfactant, such as Triton X-100; and electron carrier, such as a ruthenium compound (for example, hexaammineruthenium chloride), potassium ferricyanide or potassium ferrioxalate. In order to detect creatinine, the second indicator reaction reagent contains a buffer, such as PBS; a polymer binder, such as methylcellulose; a stabilizer, such as sucrose; a surfactant, such as Triton X-100; creatininase, creatinekinase, and sarcosine oxidase; and an electron carrier, such as a ruthenium compound, potassium ferricyanide or potassium ferrioxalate. In order to detect urea, the third indicator reaction reagent contains a buffer, such as PBS; a polymer binder, such as methylcellulose; a stabilizer, such as trehalose; a surfactant, such as Triton X-100; and an electron carrier, such as ruthenium compound, potassium ferricyanide or potassium ferrioxalate. The first indicator first reaction reagent and the first indicator second reaction reagent for detecting urea, and the second indicator reaction reagent for detecting creatinine can be added to the second reaction region **41**, the first reaction region **42** and the third reaction region **43** respectively in a manner of solution dropping or the like; and the third indicator reaction reagent for detecting uric acid is added to the fourth reaction region **46** through screen printing.

(37) There are many methods for preparing the electrochemical test strip of the present invention, one of which is selected for introduction here. This method can be divided into five processes: a screen printing process, a first base card solution fixing process, a second base card solution fixing process, a laminating process and a cutting process.

(38) In the screen printing process, each electrode in the first electrode system is formed on the first

insulating substrate **1** by screen printing of silver ink, each conductive trace and each contact in the first electrode system are formed on the first insulating substrate **1** by screen printing of conductive carbon ink, there is no special sequence requirements on whether the electrodes or the conductive traces and contacts are printed at first, and their printing can be carried out at the same time. Each electrode in the second electrode system is formed on the second insulating substrate **8** by screen printing of silver ink, each conductive trace and each contact in the second electrode system are formed on the second insulating substrate **8** by screen printing of conductive carbon ink, there is no special sequence requirements on whether the electrodes or the conductive traces and contacts are printed at first, and their printing can be carried out at the same time. In addition, there is no special sequence requirement on whether the first electrode system or the second electrode system is printed at first, and their printing can be carried out at the same time.

(39) Then, the first reaction region forming layer **3** covering the first electrode system and a second reaction region forming layer **10** covering the second electrode system are formed respectively through screen printing of insulating carbon ink, wherein whether in the first electrode system or the second electrode system, each electrode is formed by screen printing of silver ink, and each conductive trace and contact are formed by screen printing of conductive carbon ink.

(40) In the first base card solution fixing process, on the first insulating substrate **1** and the first reaction region forming layer **3** with screen printing completed, the first indicator first reaction reagent solution and the first indicator second reaction reagent solution for detecting the first indicator and the second indicator reaction reagent solution for detecting the second indicator are fixed to the second reaction region **41**, the first reaction region **42** and the third reaction region **43** of the first reaction region forming layer **3**, respectively. The first channel forming layer **4** is affixed to the first reaction region forming layer **3**, wherein the width of the third reaction region formed is 1.0 to 3.0 mm, and the width of the second reaction region **41** and the width of the first reaction region **42** are 0.5 to 2.0 mm; then the first upper cover layer **5** covers the first channel forming layer **4**, and then is rolled to enable tight affixing of the first channel forming layer **4** and the first upper cover layer **5**, thus completing the production of an electrochemical test base card. Wherein, when the first reaction region forming layer **3** is screen printed, a hydrophobic insulating material (such as insulating ink) can be printed on the first insulating substrate **1** by the screen printing method, and then the first reaction region **42**, the second reaction region **41** and the third reaction region **43** which are spaced each other are cut on the first reaction region forming layer **3** by laser cutting or other methods. It is also possible that in screen printing, some regions of the first insulating substrate **1** and the second insulating substrate **8** are not printed with an insulating material, so that the second reaction region **41**, the first reaction region **42** and the third reaction region **43** which are spaced each other are generated on the first reaction region forming layer **3**, and a fourth reaction region **46** is generated on the second reaction region forming layer **10**.

(41) In the second base card solution fixing process, the solution fixing process is performed on the second electrode system and the second reaction region forming layer **10** with screen printing completed, the second indicator reaction reagent solution for detecting the third indicator is fixed to the fourth reaction region **46** of the second reaction region forming layer **10**. The second channel forming layer **11** is affixed to the second reaction region forming layer **10**, wherein the width of the fourth reaction region **46** formed is 1.0 to 3.0 mm; then the second upper cover layer **12** covers the second channel forming layer **11**, and then is rolled to enable tight affixing of the second channel forming layer **11** and the second upper cover layer **12**, thus completing the production of a second base card. When the second reaction region forming layer **10** is screen printed, a hydrophobic insulating material (such as insulating ink) can be printed on the second insulating substrate **8** by the screen printing method, and then the fourth reaction region **46** is cut on the second reaction region forming layer **10** by laser cutting or other methods. It is also possible that during screen printing, one region of the second insulating substrate **8** is not printed with an insulating material, so that the fourth reaction region **46** is generated on the second reaction region forming layer **10**.

(42) In the laminating process, the first insulating substrate **1** of the first base card and the second insulating substrate **8** of the second base card are adhered together by an adhesive such as double-sided adhesive tape, and then rolled to enable tight affixing of the first base card and the second base card to form an electrochemical test base card. In the cutting process, the electrochemical test base card is cut into multiple electrochemical test strips.

(43) In addition, the first reaction region forming layer **3** and the second reaction region forming layer **10** may be selected as a double-sided adhesive tape or single-sided adhesive tape, so that the first reaction region forming layer **3** and the second reaction region forming layer **10** are adhered to the first insulating substrate **1** and the second insulating substrate **8**, respectively. In addition, the first reaction region forming layer **3** or the second reaction region forming layer **10** may be supported by a plastic sheet and then coated with a pressure-sensitive adhesive or a photosensitive polymer on one side thereof, wherein the photosensitive polymer is bound to the insulating substrate under the action of ultrasonic wave.

(44) In the second embodiment of the present invention, an electrochemical test strip is utilized to detect multiple indicators in a sample. It differs from the first embodiment in that as shown in FIGS. **1**, **2**, **5** and **6**, the first electrode system further includes a pair of electrodes for detecting whether the added sample is adequate or not: a first sample filling electrode **25** and a second sample filling electrode **26**, and the first reaction region forming layer **3** also has a first exposure hole **44** and a second exposure hole **45**. The first indicator reference electrode **21**, the first indicator working electrode **22**, the second indicator working electrode **23** and the second indicator counter electrode **24** are located between the first sample filling electrode **25** and the second sample filling electrode **26**, and the first sample filling electrode **25** and the second sample filling electrode **26** are connected with a seventh contact **78** and an eighth contact **75** disposed at the first electrical connection end **7** respectively by a seventh conductive trace **81** and an eighth conductive trace **71**. The first sample filling electrode **25** is closest to the first electrical connection end **7**, and the second sample filling electrode **26** is farthest from the first electrical connection end **7**. The positions of the first sample filling electrode **25** and the second sample filling electrode **26** can also be adjusted, so that the second sample filling electrode **26** is closest to the first electrical connection end **7**, and the first sample filling electrode **25** is farthest from the first electrical connection end **7**. The first sample filling electrode **25** and the second sample filling electrode **26** are made of conductive materials and may be formed on the first insulating substrate by screen printing. When the sample is added through the first sample addition port **601**, the sample is divided into two parts at the first biosensor **100** and flows in two opposite directions: one part of the sample flows toward the first electrical connection end **7** to the first indicator reference electrode **21** and the first indicator working electrode **22**; and the other part of the sample flows in the opposite direction to the second indicator working electrode **23** and the second indicator counter electrode **24**. After addition of the sample, whether the sample flowing to the first indicator reference electrode **21** and the first indicator working electrode **22** and the sample flowing to the second indicator working electrode **23** and the second indicator counter electrode **24** are adequate can be determined by detecting an electrical signal such as current, voltage or impedance between the first sample filling electrode **25** and the second sample filling electrode **26**.

(45) The first exposure hole **44** at least partially exposes the first sample filling electrode **25** and the second exposure hole **45** at least partially exposes the second sample filling electrode **26**. The first exposure hole **44** is in communication with a first air hole **51** disposed in the first biosensor **100** on the air path, thereby facilitating flowing of the sample to the second indicator working electrode **23** and the second indicator counter electrode **24**. The second exposure hole **45** is in communication with a second air hole **52** disposed in the first biosensor **100** on the air path, thereby facilitating flowing of the sample to the first indicator reference electrode **21** and the first indicator working electrode **22**. The first part of the first channel forming area **55** at least partially exposes the third reaction region **43** and the first exposure hole **44**. The second part of the first channel forming area

55 at least partially exposes the second reaction region **41**, the first reaction region **42**, and the second exposure hole **45**. Of course, the third reaction region **43** and the first exposure hole **44** may be merged into a whole. Moreover, the second reaction region **41** and the first reaction region **42** may be merged into a whole, or only one of the two is left.

(46) In the third embodiment of the present invention, an electrochemical test strip is utilized to detect multiple indicators in a sample. It differs from the first embodiment in that as shown in FIGS. **3** and **4**, the second electrode system is further provided with a third sample filling electrode **27** for detecting whether the added sample is adequate or not; and the second reaction region forming layer **10** has a third exposure hole **47**. The third sample filling electrode **27** is connected with a ninth contact **85** through a ninth conductive trace **90**. The distance from the third sample filling electrode **27** to the second electrical connection end **13** is less than the distance from any one of the third indicator counter electrode **29** and the third indicator working electrode **30** to the second electrical connection end **13**. The third exposure hole **47** at least partially exposes the third sample filling electrode **27**. The third exposure hole **47** is in communication with the third air hole **53** disposed in the second biosensor **101** on the air path.

(47) When a sample is added through the second sample addition port **602**, the sample flows into the second biosensor **101**, and whether the sample flowing to the third indicator counter electrode **29** and the third indicator working electrode **30** is adequate can be determined by detecting the signal between the third sample filling electrode **27** and the third indicator counter electrode **29** or the third indicator working electrode **30**. In the fourth embodiment of the present invention, as shown in FIGS. **3** to **5**, an electrochemical test strip is utilized to detect multiple indicators in a sample. It differs from the first embodiment in that the second electrode system of the second biosensor is further provided with a pair of special HCT electrodes **28** for detecting the indicator HCT in the sample to correct the test differences caused by different HCT level in the blood sample; the notch **66** disposed on one side of the second channel forming layer **11** is in liquid communication with the middle part of the second channel forming area **56**; the second reaction region forming layer **10** has a fourth exposure hole **48**, a fifth exposure hole **49** and a sixth exposure hole **50**; and the second upper cover layer **12** contains a third air hole **53** and a fourth air hole **54**. In the pair of HCT electrodes **28**, one of the HCT electrodes is connected with a tenth contact **83** through a tenth conductive trace **88**, and the other HCT electrode is connected to an eleventh contact **87** through an eleventh conductive trace **92**. The pair of special HCT electrodes **28** is located on one side of the second sample addition port **602**, and the third indicator counter electrode **29** and the third indicator working electrode **30** are located on the other opposite side of the second sample addition port **602**. Of course, the pair of special HCT electrodes **28** may also be located on the same side of the second sample addition port **602** as the third indicator counter electrode **29** and the third indicator working electrode **30**, and at this time the notch **66** disposed on one side of the second channel forming layer **11** is in liquid communication with one end of the second channel forming area **56** and of course, it may also be in liquid communication with the middle part of the second channel forming area **56**.

(48) The fourth exposure hole **48** and the fifth exposure hole **49** each expose at least partially one of the pair of HCT electrodes **28**. In the three exposure holes, the distance between the sixth exposure hole **50** and the second electrical connection end **13** is the largest, followed by the distance between the fifth exposure hole **49** and the second electrical connection end **13**, and the distance between the fourth exposure hole **48** and the second electrical connection end **13** is the smallest. The sixth exposure hole **50** is located near the third exposure hole **49** to partially expose the insulating region of the second insulating substrate **8**. The purpose of providing the sixth exposure hole **50** is that the sixth exposure hole **50** is in communication with the fourth air hole **54** disposed on the second biosensor **101** on the air path, thereby facilitating sample to adequately cover the pair of HCT electrodes **28**.

(49) When each of the HCT electrodes **28** is manufactured, the conductive material in the middle

region of each HCT electrode **28** is distributed more evenly, and the electrical signal thus measured is better, so that the fifth exposure hole **49** and the sixth exposure hole **50** preferably each expose the middle region of each HCT electrode **28**. In addition, when the electrochemical biosensor **200** is assembled, even if a relative offset occurs between the second reaction region forming layer **10** and the second insulating substrate **8**, it is possible to ensure that the area of the HCT electrode exposed by the fifth exposure hole **49** and the sixth exposure hole **50** remains the same, thereby ensuring the consistency of electrical signals generated by different batches of electrochemical biosensors **200**. Of course, the fourth exposure hole **48**, the fifth exposure hole **49** and the sixth exposure hole **50** can be partially merged, for example, the fourth exposure hole **48** and the fifth exposure hole **49** can be merged together, the fifth exposure hole **49** and the sixth exposure hole **50** can also be merged together, and even the fourth exposure hole **48**, the fifth exposure hole **49** and the sixth exposure hole **50** can also be merged together. In addition, the fourth exposure hole **48**, the fifth exposure hole **49** and the sixth exposure hole **50** can also be merged with the fourth reaction region **46**.

(50) The notch **66** is in liquid communication with the middle part of the second channel forming area **56**, which divides the second channel forming area **56** into two parts, so that after the sample is added through the second sample addition port **602**, when the sample enters into the second channel forming layer **11** through the notch **66**, sample diverging occurs: one part of the sample flowing into the first part of the second channel forming area **56** and the other part flowing into the second part of the second channel forming area **56**. The sample flowing into the first part of the second channel forming area **56** eventually flows to the pair of HCT electrodes **28** through the fourth exposure hole **48** and the fifth exposure hole **49** to detect the HCT value of the sample, and the sample flowing into the second part of the second channel forming area **56** eventually flows to the third indicator counter electrode **29** and the third indicator working electrode **30** through the fourth reaction region **46** to detect the third indicator.

(51) The fourth air hole **54** is located above the first part of the second channel forming area **56**, and is in communication with the first part of the second channel forming area **56** and the sixth exposure hole **50** on the air path to discharge the air in the second sample channel when the sample is added. The third air hole **53** is located above the second part of the second channel forming area **56**, and is in communication with the second part of the second channel forming area **56** on the air path to discharge the air in the second sample channel when the sample is added.

(52) The electrochemical test strip of the present embodiment can measure four indicators: a first indicator (such as urea) measured by the first indicator reference electrode **21** and the first indicator working electrode **22** disposed in the first biosensor **100**; a second indicator (such as creatinine) measured by the second indicator working electrode **23** and the second indicator counter electrode **24** disposed in the first biosensor **100**; a third indicator (such as uric acid) measured by the third indicator counter electrode **29** and the third indicator working electrode **30** disposed in the second biosensor **101**; and HCT measured by the pair of HCT electrodes **28** disposed in the second biosensor **101**. The layouts of the electrodes for detecting the four indicators consisting of urea, creatinine, urea and HCT in the first biosensor **100** and the second biosensor **101** can also be adjusted as needed. For example, the electrodes for detecting three of the indicators can be disposed in the first biosensor **100** or the second biosensor **101** at the same time, and the electrodes for detecting the remaining indicator is disposed in the second biosensor **101** or the first biosensor **100**. In addition, the pair of HCT electrodes **28** in the present embodiment may also be replaced with a pair of electrodes for detecting an analyte such as glucose in the sample.

(53) In the fifth embodiment of the present invention, an electrochemical test strip is utilized to detect multiple indicators in the sample. It differs from the first embodiment in that as shown in FIG. **8**, the first biosensor **100** and the second biosensor **101** share the same insulating substrate, that is, they share the first insulating substrate **1**, which reduces the thickness and manufacturing cost of the electrochemical biosensor **200**. In addition, the preparation of the electrochemical test

strip in the present embodiment is substantially the same as that in the first embodiment, except that in the screen printing process, the first electrode system and the first reaction region forming layer are printed on the front side of the first insulating substrate **1**; the second electrode system and the second reaction region forming layer are printed on the back side of the first insulating substrate **1**; then, the first base card solution fixing process, the second base card solution fixing process, the laminating process and the cutting process are carried out as in the first embodiment, so as to prepare the electrochemical test strip in the present embodiment.

(54) In the sixth embodiment of the present invention, an electrochemical test strip is utilized to detect multiple indicators in a sample. It differs from the first embodiment in that as shown in FIGS. **5** and **12**, in the first biosensor **100**, one side of the first insulating substrate **1** is also provided with a notch **64**, and the notch **64** is disposed in the same side of the first biosensor **100** as the notches **61**, **62** and **63** and aligned with them in position to form the first sample addition port **601** together; and in the second biosensor **101**, one side of the second insulating substrate **8** is provided with a notch **68**, and the notch **68** is disposed in the same side of the second biosensor **101** as the notches **65**, **66** and **67** and aligned with them in position to form the second sample addition port **602** together. The first sample addition port **601** and the second sample addition port **602** jointly constitute the sample addition port **6** of the electrochemical test strip. The dimension of the notch **65** is the same as that of the notch **61**.

(55) In the seventh embodiment of the present invention, an electrochemical test strip is utilized to detect multiple indicators in a sample. It differs from the sixth embodiment in that as shown in FIGS. **5** and **9** to **11**, the dimension of the notch **65** is smaller than that of the notch **61**, which is beneficial to loading the sample in the second biosensor **101** (in particular the second upper cover layer **12**), facilitating the rapid flow of the sample into the first biosensor **100** and the second sensor **101**. Of course, the dimension of the notch **65** may also be smaller than that of the notch **61**.

(56) Of course, in terms of the first biosensor **100**, both the first upper cover layer **5** and the first insulating substrate **1** may be without a notch, or only the first upper cover layer **5** or the first insulating substrate **1** is provided with a notch, or the first upper cover layer **5** and the first insulating substrate **1** each are provided with a notch. In terms of the second biosensor **101**, both the second insulating substrate **8** and the second upper cover **12** may be without a notch, or only the second insulating substrate **8** or the second upper cover **12** is provided with a notch, or the second insulating substrate **8** and the second upper cover **12** each are provided with a notch.

(57) In the eighth embodiment of the invention, an electrochemical test strip is utilized to detect multiple indicators. It differs from the second embodiment in that as shown in FIGS. **13** to **14**, multiple diffusion components are disposed on the first insulating substrate **1** of the first biosensor **100**, wherein a diffusion component **33** is disposed on each of the two opposed sides of the first indicator reference electrode **21**, and a diffusion component **33** is disposed on one side of the first indicator working electrode **22**, and the first sample filling electrode **25** is on the other opposed side of the first indicator working electrode **22**. Preferably, the first sample filling electrode **25** is made of conductive ink, so that the first sample filling electrode **25** can also act as a diffusion component. The purpose of disposing multiple diffusion components on the front insulating substrate **1** is to facilitate the rapid and uniform diffusion of the reaction reagent solutions in the reaction regions when the first indicator first reaction reagent solution is added to the second reaction region **41** and the first indicator second reaction reagent solution is added to the first reaction region **42**.

(58) At least one diffusion component may also be placed only on one side of the first indicator working electrode **22** and/or the first indicator reference electrode **21** as needed. The first reaction region **42** covers at least a part of each diffusion component disposed on two opposed sides or one side of the first indicator reference electrode **21**.

(59) Similarly, at least one diffusion component may also be placed on one or two opposed sides of the second indicator working electrode **23** and the second indicator counter electrode **24** as needed. Similarly, at least one diffusion component may also be disposed only on one or two opposed sides

of the third indicator counter electrode **29** and the third indicator working electrode **30** on the second insulating substrate **8** as needed. Since the third sample filling electrode **27** is located on one side of the third indicator counter electrode **29**, the third sample filling electrode **27** may also act as a diffusion component when the third sample filling electrode **27** is made of conductive ink. (60) In the ninth embodiment of the present invention, an electrochemical test strip is utilized to detect multiple indicators in a sample. It differs from the first embodiment in that as shown in FIG. 5, on the basis of the first embodiment, the electrochemical test strip further comprises the first sample filling electrode **25**, second sample filling electrode **26**, first exposure hole **44** and second exposure hole **45** in the second embodiment, the third sample filling electrode **27** and third exposure hole **47** in the third embodiment, the pair of special HCT electrodes **28**, fourth exposure hole **48**, fifth exposure hole **49** and sixth exposure hole **50** in the fourth embodiment, and the diffusion component(s) in the eighth embodiment; and a notch **64** is also disposed in one side of the first insulating substrate **1** and a notch **68** is also disposed in one side of the second insulating substrate **8**, the dimension of the notch **65** being smaller than the dimension of the notch **61**. The first part of the second channel forming area **56** at least partially exposes the fourth reaction region **46** and the third exposure hole **47**. The second part of the second channel forming area **56** at least partially exposes the fourth exposure hole **48**, the fifth exposure hole **49** and the sixth exposure hole **50**.

(61) The notch **66** divides the second channel forming area **56** into two parts, and the second sample channel is correspondingly divided into two parts. The first part of the second sample channel is used to provide a sample to the pair of HCT electrodes **28** and can be used to detect the HCT value of the sample. The second part of the second sample channel is used to provide the sample to the third indicator counter electrode **29** and the third indicator working electrode **30**, dissolve the reaction reagent in the fourth reaction region **46** and react, thereby generating an electrical signal. The fourth air hole **54** is located above the first part of the second sample channel, and is in communication with the first part of the second sample channel and the sixth exposure hole **50** on the air path to discharge the air in the first part of the second sample channel when the sample is added. The third air hole **53** is located above the second part of the second sample channel, and is in communication with the second part of the second sample channel and the third exposure hole **47** on the air path to discharge the air in the second part of the second sample channel when the sample is added.

(62) In the tenth embodiment of the present invention, an electrochemical test strip is utilized to detect multiple indicators in a sample. It differs from the eighth embodiment in that as shown in FIGS. 14 and 15, the electrochemical test strip further contains a hydrophilic element. When the sample flows to the first channel forming area, the sample diverging occurs, and the position where the diverging occurs is the diverging point. At the diverging point, a part of the sample flows to the second indicator working electrode **23**, the second indicator counter electrode **24** and the first sample filling electrode **26**, and the other part of the sample flows to the first indicator reference electrode **21**, the first indicator working electrode **22** and the second sample filling electrode **25**. A first hydrophilic element **31** and a second hydrophilic element **32** located at or near the sample diverging point are disposed on the first insulating substrate **1**. The first hydrophilic element **31** and the second hydrophilic element **32** may be made of a hydrophilic material. The second indicator working electrode **23** and the second indicator counter electrode **24** are located on one side of the sample diverging point, and the first indicator reference electrode **21** and the first indicator working electrode **22** are located on the other opposite side of the sample diverging point; and the distance from the second indicator working electrode **23** or the second indicator counter electrode **24** to the sample diverging point is greater than the distance from the first hydrophilic element **31** to the sample diverging point, and the distance from the first indicator reference electrode **21** or the first indicator working electrode **22** to the sample diverging point is greater than the distance from the second hydrophilic element **32** to the sample diverging point. A hydrophobic insulting region is

disposed for separation between the first hydrophilic element **31** and the second hydrophilic element **32**, between the first hydrophilic element **31** and the second indicator working electrode **23** or the second indicator counter electrode **24**, and between the second hydrophilic element **32** and the second indicator counter electrode **24** or the second indicator working electrode **23**. Such design can avoid mutual interference between the diverged samples, and at the same time, the design of the first hydrophilic element **31** and the second hydrophilic element **32** is beneficial to more rapid flow of the samples into the third reaction region **43**, the second reaction region **41**, and the first reaction region **42** and the electrodes exposed thereby of the first biosensor **100**. More hydrophilic elements can also be provided, or only one hydrophilic element can be provided.

(63) In terms of the second biosensor **101**, when the sample flows onto the second insulating substrate **8**, sample diverging occurs, with one part of the sample flowing to a pair of HCT electrodes **28** and the other part of the sample flowing to the third indicator counter electrode **29**, the third indicator working electrode **30** and the third sample filling electrode **27**. Preferably, as shown in FIG. **15**, one or more corresponding hydrophilic elements, for example, two hydrophilic elements, i.e., the third hydrophilic element **34** and the fourth hydrophilic element **35**, may also be disposed at or near the sample diverging point on the second insulating substrate **8**, and the material and location arrangement of the third hydrophilic element **34** and the fourth hydrophilic element **35** are similarly to those of the first hydrophilic element **31** and the second hydrophilic element **32** on the first insulating substrate **1**.

(64) In the eleventh embodiment of the present invention, an electrochemical test strip is utilized to detect multiple indicators in a sample. It differs from the first embodiment in that as shown in FIG. **16**, a conductive automatic power-on contact **93** can also be disposed on the second insulating substrate **8**, and the automatic power-on contact **93** is located at the second electrical connection end **13**; when the electrochemical test strip is inserted into the electrical connector of a detecting instrument in a correct direction, the automatic power-on contact **93** can form a closed circuit with the detecting instrument, so that the detecting instrument can be powered on automatically; and when the electrochemical test strip is inserted in an opposite direction, the automatic power-on contact **93** cannot form a closed circuit with the detecting instrument, so that the detecting instrument cannot be automatically powered on, and then the electrochemical test strip cannot perform the detection. Therefore, providing the automatic power-on contact **93** can help the detecting instrument identify the front and back sides of the electrochemical test strip, and prevent incorrect insertion and insertion of other mismatched electrochemical test strips. It is also possible that an automatic power-on contact located at the first electrical connection end **7** is disposed on the first insulating substrate **1**, or one such automatic power-on contact is disposed on each of the first insulating substrate **1** and the second insulating substrate **8**, so that the detecting instrument can be powered on automatically only when the electrochemical test strip is used with a detecting instrument mated with the same.

(65) In the twelfth embodiment of the present invention, its similarity with the first embodiment is that both the first upper cover layer and the second upper cover layer are transparent, so that even after the electrochemical test strip has been assembled, the colors of the first insulating substrate **1** and the second insulating substrate **8** can also be observed, and it differs from the first embodiment in that the first insulating substrate **1** and the second insulating substrate **8** can be made of insulating materials of different colors, so that the front and back sides of the electrochemical test strip can be distinguished by observing the colors of the first insulating substrate **1** and the second insulating substrate **8**, that is, the first biosensor **100** and the second biosensor **101** can be distinguished, thereby preventing the electrochemical test strip from being inversely inserted into the detecting instrument. The first upper cover layer and the second upper cover layer may also be opaque, and at this time the first upper cover layer and the second upper cover layer can be made of insulating materials of different colors, so that the front and back sides of the electrochemical test strip can be distinguished by observing the colors of the first upper cover layer and the second

upper cover layer, that is, the first biosensor and the second biosensor can be distinguished, thereby preventing the electrochemical test strip from being inversely inserted into the detecting instrument.

(66) In the present invention, each electrode system is made of any conductive material, such as carbon film, gold, silver, tin oxide/gold, platinum, other precious metals or their oxides. The surface of the first upper cover layer facing the first channel forming layer and the surface of the second upper cover layer facing the second channel forming layer are coated with a layer of hydrophilic material. Any hydrophilic element used in the present invention is made of a hydrophilic material. The hydrophilic material mentioned in the present invention can be selected from starch, polysaccharide, cellulosic molecules, polyacrylic acid, polyacrylamide, polyvinyl alcohol, polyurethane, polyamide and carbon ink. The hydrophilic element is preferably conductive carbon ink.

(67) The electrochemical test strip is provided with a label for distinguishing the front and back sides of the electrochemical test strip, and the label is a conductive automatic power-on contact, a colored insulating material, a word, a letter, a graph, etc. It can be reasonably deduced that according to the twelve embodiments of the present invention, at least one of the second embodiment, the third embodiment, the fourth embodiment, the fifth embodiment, the sixth embodiment, the seventh embodiment, the eighth embodiment, the tenth embodiment, the eleventh embodiment and the twelfth embodiment of the present invention may be combined with the first embodiment of the present invention.

(68) Depending on test needs, the electrochemical test strip of the present invention can also be used to detect two or more indicators in a sample, the two or more indicators being selected from glucose, cholesterol, hemoglobin, glycated hemoglobin, uric acid, urea, creatinine, bilirubin, ketone bodies, HCT and pH value. For example, the first biosensor can include a blood glucose detection electrode system and a urea detection electrode system, and the second biosensor can include a cholesterol detection electrode system and a ketone body detection electrode system.

Example 1 Reaction Reagents

(69) Taking the electrochemical test strip of the ninth embodiment as an example, this electrochemical test strip is illustrated by the fact that the first indicator reference electrode **21** and the first indicator working electrode **22** detect urea in the sample by the potentiometric method, the second indicator working electrode **23** and the second indicator counter electrode **24** detect creatinine in the sample by the amperometric method, and the third indicator counter electrode **29** and the third indicator working electrode **30** detect uric acid in the sample by the amperometric method.

(70) In order to detect urea, the first indicator first reaction reagent contained in the second reaction region **41** of the first reaction region forming layer **3** includes 0.05 to 0.5M PBS (pH 5.8-8.0), methylcellulose 0.1-10% (w/w), Triton X-100 0.1% to 1.0% (v/v), and urease (2280 to 8712 U/mL); and the first indicator second reaction reagent contained in the first reaction region **42** of the first reaction region forming layer **3** includes 0.05 to 0.5M PBS (pH 5.8-8.0), methylcellulose 0.1-10% (w/w), Triton X-100 0.1% to 1.0% (v/v), and a ruthenium compound, potassium ferricyanide or potassium ferrocyanide 1.0% to 4.5% (w/w).

(71) To detect creatinine, the second indicator reaction reagent contained in the third reaction region **43** of the first reaction region forming layer **3** includes 0.05 to 0.5M PBS (pH 5.8 to 8.0), a polymer binder (such as methylcellulose) 0.1-10% (w/w), sucrose 0.25% to 1% (w/w), Triton X-100 0.1%-1% (v/v), creatinase (500-5000 U/mL), creatinekinase (500-5000 U/mL), sarcosine oxidase (500-5000 U/mL), and a ruthenium compound, potassium ferricyanide or potassium ferrocyanide 1.0-4.5% (w/w).

(72) To detect uric acid, the third indicator reaction reagent contained in the fourth reaction region **46** of the second reaction region forming layer **3** includes 0.05 to 0.5M PBS (pH 5.8 to 8.0), a polymer binder (such as methyl cellulose) 0.1-10% (w/w), trehalose 0.25% to 1% (w/w), Triton X-

100 0.1% to 1.0% (v/v), and a ruthenium compound, potassium ferricyanide or potassium ferrocyanide 2.0 to 10% (w/w).

Example 2 Detection of Clinical Samples

(73) The electrochemical test strip in Example 1 is utilized to detect the levels of urea, creatinine and uric acid in a clinical blood sample.

(74) When the first biosensor **100** and the second biosensor **101** are assembled together, after the sample is added through the sample addition port **6**, a part of the sample flows into the first biosensor **100** and enters into the first channel forming area **55** through the notch **61** and the notch **62**, and the notch **62** divides the first channel forming area **55** into two parts, therefore, the sample entering the first channel forming area **55** undergoes diverging at this time, with one part of the sample flowing into the first part of the first channel forming area **55**, and the other part of the sample flowing into the second part of the first channel forming area **55**. The sample flowing into the first part of the first channel forming area **55** eventually flows to the second indicator working electrode **23** and the second indicator counter electrode **24** through the third reaction region **43**, and the sample flowing into the second part of the first channel forming area **55** eventually flows to the first indicator reference electrode **21** and the first indicator working electrode **22** through the second reaction region **41** and the first reaction region **42**. The part of the sample flowing into the second biosensor **101** enters the second channel forming area **56** through the notch **65** and the notch **66**, the notch **66** divides the second channel forming area **56** into two parts, wherein one part of the sample flowing into the second channel forming area **56** flows into the first part of the second channel forming area **56**, and the other part flows into the second part of the second channel forming area **56**. The sample flowing into the first part of the second channel forming area **56** eventually flows to the pair of HCT electrodes **28** through the fourth exposure hole **48** and the fifth exposure hole **49**, and the sample flowing into the second part of the second channel forming area **56** eventually flows to the third indicator counter electrode **29** and the third indicator working electrode **30** through the fourth reaction region **46**.

(75) Before testing, the electrochemical test strip is inserted into an electrical connector of a detecting instrument, and the first and second biosensors of the electrochemical test strip are electrically connected to the electrical connector of the detecting instrument. Then, urea, creatinine and uric acid in the sample are detected after a sample is added for a period of time.

(76) After addition of a blood sample, urea in the sample reacts with the first indicator first reaction reagent and the first indicator second reaction reagent, and the potential signal generated between the first indicator reference electrode and the first indicator working electrode is directly proportional to the urea concentration in the sample, so the urea concentration is measured by the potentiometric method and the test time is 3 s to 100 s. Such detecting instrument can convert the detected potential signal into a corresponding urea concentration value. After addition of the blood sample, creatinine in the sample reacts with the second indicator reaction reagent, and the current signal generated after applying a voltage is directly proportional to the creatinine concentration in the sample, so the amperometric method is used for measurement, and the test time is 3 s to 100 s. Such detecting instrument can convert the detected current signal into a corresponding creatinine concentration value. After addition of the blood sample, uric acid in the sample reacts with the third indicator reaction reagent, and the current signal generated after applying a voltage is directly proportional to the uric acid concentration in the sample, so the amperometric method is used for measurement, and the test time is 2 s to 100 s. Such detecting instrument can convert the detected current signal into a corresponding uric acid concentration value.

(77) In addition, the electrochemical test strip also contains a pair of special HCT electrodes, which can be used to measure the HCT value of a blood sample, and the measured HCT value can be used to correct the measured urea, creatinine and uric acid concentrations at the same time, so that the measurement results are more accurate.

(78) A clinical blood sample is taken and detected by using the electrochemical test strip of the

present invention and the plasma derived from the blood sample is detected by Mindray BS-350E fully automated biochemical analyzer. The detection results of urea are as shown in Table 1 and FIG. 17, the detection results of creatinine are as shown in Table 2 and FIG. 18, the detection results of uric acid are as shown in Table 3 and FIG. 19.

(79) TABLE-US-00001 TABLE 1 Linearity research results of urea Biochemical value of plasma urea (mmol/L) 3 6 11 16 23 30 37 43 Readings in the present invention (mmol/L) Reading 1 2.9 5.9 11.1 16.7 21.0 31.8 41.6 43.1 Reading 2 2.7 6.6 10.6 15.7 22.4 31.6 39.0 43.2 Reading 3 2.9 6.4 10.1 15.6 21.8 30.4 38.9 41.4 Average value 2.83 6.30 10.60 16.00 21.73 31.27 39.83 42.57 Standard deviation SD 0.12 0.36 0.50 0.61 0.70 0.76 1.53 1.01 Coefficient of variation CV 4.1% 5.7% 4.7% 3.8% 3.2% 2.4% 3.8% 2.4% Deviation from biochemical -3.0% 8.2% -5.2% 0.6% -5.3% 4.3% 6.6% 0.1% value of plasma urea %

(80) As shown in Table 1 and FIG. 17, the linearity research results of urea show that the linear correlation coefficients $R_{\text{sup.2}}=0.99549$ and $R=0.99774$, and the slope of the linear equation is between 0.90 and 1.10, indicating that urea has a good linear correlation in the concentration range of 3 to 43 mmol/L, and has a good detection accuracy in this concentration range, and the deviations from the biochemical value of plasma urea are all within 10%.

(81) TABLE-US-00002 TABLE 2 Linearity research results of creatinine Biochemical value of plasma urea ($\mu\text{mol/L}$) 35 60 126 281 451 599 816 995 Readings in the present invention ($\mu\text{mol/L}$) Reading 1 39 55 120 269 420 627 750 997 Reading 2 37 53 121 280 399 602 781 971 Reading 3 36 55 124 268 417 590 771 998 Average value 37.3 54.3 121.7 272.3 412.0 606.3 767.3 988.7 Standard deviation SD 1.53 1.15 2.08 6.66 11.36 18.88 15.82 15.31 Coefficient of variation CV 4.1% 2.1% 1.7% 2.4% 2.8% 3.1% 2.1% 1.5% Deviation from biochemical 6.7% -9.4% -3.4% -3.1% -8.6% 1.2% 6.0% 0.5% value of plasma urea %

(82) As shown in Table 2 and FIG. 18, the linearity research results of creatinine show that the linear correlation coefficients $R_{\text{sup.2}}=0.99722$ and $R=0.99861$, and the slope of the linear equation is between 0.90 and 1.10, indicating that creatinine has a good linear correlation in the concentration range of 35 to 995 $\mu\text{mol/L}$, and has a good detection accuracy in this concentration range, and the deviations from the biochemical value of plasma creatinine are all within 10%.

(83) TABLE-US-00003 TABLE 3 Linearity research results of uric acid Biochemical value of plasma urea ($\mu\text{mol/L}$) 120 252 382 520 730 929 1109 1313 Readings in the present invention ($\mu\text{mol/L}$) Reading 1 105 250 398 535 723 992 1130 1371 Reading 2 119 258 394 528 733 946 1098 1362 Reading 3 119 265 367 535 733 941 1135 1357 Average value 114.3 257.7 386.3 532.7 731.3 959.7 1121.0 1363.3 Standard deviation SD 8.08 7.51 16.86 4.04 7.64 28.11 20.07 7.09 Coefficient of variation CV 7.1% 2.9% 4.4% 0.8% 1.0% 2.9% 1.8% 0.5% Deviation from biochemical -4.7% 2.2% 1.1% 2.4% 0.2% 3.3% 1.1% 3.8% value of plasma urea %

(84) As shown in Table 3 and FIG. 19, the linearity research results of uric acid show that the linear correlation coefficients $R_{\text{sup.2}}=0.99939$ and $R=0.99969$, and the slope of the linear equation is between 0.90 and 1.10, indicating that uric acid has a good linear correlation in the concentration range of 120 to 1313 $\mu\text{mol/L}$, and has a good detection accuracy in this concentration range, and the deviations from the biochemical value of plasma uric acid are all within 10%.

Claims

1. An electrochemical test strip for detecting multiple indicators, comprising a first biosensor which comprises an insulating substrate, a first electrode system disposed on the insulating substrate, a first channel forming layer and a first upper cover layer, a first channel forming area disposed in the first channel forming layer, the first channel forming area disposed above at least one electrode of the first electrode system, wherein the electrochemical test strip further comprises a second biosensor, and the second biosensor comprises an insulating substrate, a second electrode system disposed on the insulating substrate, a second channel forming layer and a second upper cover

layer, a second channel forming area disposed in the second channel forming layer, the second channel forming area disposed above at least one electrode of the second electrode system; the first biosensor and the second biosensor are located on the front and back sides of the electrochemical test strip, respectively, and the electrical connection end of the first biosensor and the electrical connection end of the second biosensor are located at the same end of the electrochemical test strip; and the sample addition port of the electrochemical test strip is in liquid communication with the first channel forming area of the first biosensor and the second channel forming area of the second biosensor, respectively, wherein the sample addition port comprises a notch in the first upper cover layer and a notch in the second upper cover layer.

2. The electrochemical test strip according to claim 1, wherein the first electrode system comprises an electrode system for measuring a first indicator and an electrode system for measuring a second indicator.

3. The electrochemical test strip according to claim 2, wherein the second electrode system comprises an electrode system for measuring a third indicator.

4. The electrochemical test strip according to claim 3, wherein the second electrode system comprises an electrode system for measuring a fourth indicator.

5. The electrochemical test strip according to claim 2, wherein the electrode system for measuring the first indicator and the electrode system for measuring the second indicator are located on two opposed sides of the sample addition port, respectively.

6. The electrochemical test strip according to claim 4, wherein the electrode system for measuring the third indicator and the electrode system for measuring the fourth indicator are located on two opposed sides of the sample addition port, respectively.

7. The electrochemical test strip according to claim 1, wherein the first biosensor and the second biosensor share one insulating substrate, or the first biosensor and the second biosensor each comprise an insulating substrate.

8. The electrochemical test strip according to claim 1, wherein a first reaction region forming layer is disposed between the insulating substrate and the first channel forming layer of the first biosensor, and/or a second reaction region forming layer is disposed between the insulating substrate and the second channel forming layer of the second biosensor.

9. The electrochemical test strip according to claim 1, wherein the notches in the first upper cover layer and the second upper cover layer are located on the same side of the electrochemical test strip and aligned in position, and the notch in the first upper cover layer is larger than that in the second upper cover layer.

10. The electrochemical test strip according to claim 1, wherein the electrochemical test strip is also provided with a label for distinguishing the front and back sides of the electrochemical test strip.

11. The electrochemical test strip according to claim 10, wherein the label is a conductive automatic power-on contact and is disposed in at least one of the insulating substrate of the first biosensor and the insulating substrate of the second biosensor.

12. The electrochemical test strip according to claim 10, wherein the label is a colored insulating material; when the first upper cover layer and the second upper cover layer are transparent, the side of the insulating substrate of the first biosensor facing the first channel forming layer and the side of the insulating substrate of the second biosensor facing the second channel forming layer are made of materials of different colors; and when the first upper cover layer and the second upper cover layer are opaque, the first upper cover layer and the second upper cover layer are made of materials of different colors.

13. The electrochemical test strip according to claim 1, wherein the electrochemical test strip is used for measuring at least two indicators selected from glucose, cholesterol, hemoglobin, glycated hemoglobin, uric acid, urea, creatinine, bilirubin, ketone body, HCT and pH value.

14. A method for detecting multiple indicators, comprising providing the electrochemical test strip

according to claim 1.

15. The method according to claim 14, wherein the first electrode system comprises an electrode system for measuring a first indicator and an electrode system for measuring a second indicator.

16. The method according to claim 15, wherein the second electrode system comprises an electrode system for measuring a third indicator.

17. The method according to claim 16, wherein the second electrode system comprises an electrode system for measuring a fourth indicator.

18. The method according to claim 16, wherein the first indicator is urea, the second indicator is creatinine and the third indicator is uric acid.

19. The method according to claim 18, wherein the first indicator is measured potentiometrically, and the second indicator and the third indicator are measured amperometrically.
