

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250282557

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Kono; Makoto et al.

Article Transport Facility

Abstract

An article transport facility includes a plurality of transport vehicles and a control system. In order to select a target transport vehicle to be caused to perform transport processing from among transport vehicles not holding any article, the control system executes selection processing including calculating an evaluation cost for each of the transport vehicles not holding any article, using a cost whose value is related to a factor affecting the travel time of the corresponding transport vehicle and whose value increases as the travel time is longer, and selecting the transport vehicle having the smallest evaluation cost as the target transport vehicle. In the selection processing executed when a specific holding section is the transport origin, the control system calculates the evaluation cost based on both a receiving cost and a delivery cost.

Inventors: Kono; Makoto (Komaki-shi, JP), Hagiwara; Koichi (Komaki-shi, JP)

Applicant: Daifuku Co., Ltd. (Osaka-shi, JP)

Family ID: 96931703

Appl. No.: 19/071177

Filed: March 05, 2025

Foreign Application Priority Data

JP 2024-034195 Mar. 06, 2024

Publication Classification

Int. Cl.: B65G43/08 (20060101); H01L21/677 (20060101)

U.S. Cl.:

CPC B65G43/08 (20130101); H01L21/67724 (20130101); H01L21/6773 (20130101); H01L21/67733 (20130101); B65G2201/0297 (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

[0001] This application claims priority to Japanese Patent Application No. 2024-034195 filed Mar. 6, 2024, the disclosure of which is hereby incorporated by reference in its entirety.

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0002] The present invention relates to an article transport facility including a plurality of transport vehicles that move along a predetermined travel route to transport articles, and a control system that causes the transport vehicles to perform transport processing in which a transport origin and a transport destination have been designated for the articles.

2. Description of Related Art

[0003] For example, JP 2020-66499A discloses a transport system for use in a factory that manufactures a semiconductor product. In this transport system, in order to perform various types of processing on articles, the articles are transported between processing steps by transport vehicles. Typically, a system controller that manages the system issues a transport command, and, based on the transport command, a transport vehicle receives a designated article at a transport origin where the article is located, and transports the article to a designated transport destination.

[0004] When selecting which transport vehicle among a plurality of transport vehicles is to transport an article, in order to transport the article rationally from the viewpoint of the transport time and the like, the transport vehicle located closest to the location where the target article is stored (transport origin) is often selected. However, for example, when the route structure is complex or when there are constraints on the movement of the transport vehicles along a route, it can be possible for a transport vehicle that has received an article to travel along any of a plurality of routes to the transport destination, that is to say, a plurality of routes from the transport origin to the transport destination. Therefore, if the distance between the transport origin and the transport vehicle is used solely as the selection criterion for selecting a transport vehicle to transport an article, it may not be possible to transport the article rationally.

SUMMARY OF THE INVENTION

[0005] In view of the above circumstances, there is a demand for an article transport facility that can realize the transport of articles in a highly rational manner.

[0006] The following is a technology for solving the foregoing problems.

[0007] An article transport facility according to an aspect of the present invention is an article transport facility including: [0008] a plurality of transport vehicles configured to travel along a predetermined travel route and transport an article; [0009] a control system configured to cause the plurality of transport vehicles to perform transport processing in which a transport origin and a transport destination are designated for respective articles; and [0010] a plurality of article holding sections at respective locations along the travel route and configured to store articles and transfer articles with the plurality of transport vehicles, [0011] at least one of the plurality of article holding sections being a specific holding section to and from which an article is transferable by a transport vehicle located in a specific zone among a plurality of specific zones on the travel route, [0012] the control system being further configured to, in order to select a target transport vehicle to be caused to perform the transport processing from among a plurality of transport vehicles not holding any article, execute selection processing including (i) calculating an evaluation cost for each of the plurality of transport vehicles not holding any article, using a cost whose value is related to a factor affecting a travel time of the corresponding transport vehicle and whose value increases as the travel time is longer, and (ii) selecting a transport vehicle having a smallest evaluation cost as the target transport vehicle, and [0013] in the selection processing executed in a case where the specific

holding section is the transport origin, the control system calculates the evaluation cost based on both a receiving cost and a delivery cost, the receiving cost being the cost corresponding to a travel time from a current position of the corresponding transport vehicle to the transport origin, and the delivery cost being the cost corresponding to a travel time of the corresponding transport vehicle from the transport origin to the transport destination.

[0014] According to this configuration, when the specific holding section is set as the transport origin, the target transport vehicle to perform transport processing can be selected based on both the cost corresponding to the travel time from the current position of the transport vehicle to the transport origin and the cost corresponding to the travel time of the transport vehicle from the transport origin to the transport destination. In other words, the target transport vehicle can be selected based further on the situation after the transport vehicle receives the article at the transport origin. Therefore, with this configuration, it is possible to realize highly rational article transport.

[0015] Further features and advantages of the technology disclosed herein will become more apparent from the following description of exemplary and non-limiting embodiments described with reference to the drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] The terms Fig., Figs., Figure, and Figures are used interchangeably in the specification to refer to the corresponding figures in the drawings.

[0017] FIG. 1 is a plan view of an article transport facility.

[0018] FIG. 2 is a front view of an article holding section.

[0019] FIG. 3 is a front view of a specific holding section.

[0020] FIG. 4 is an illustrative diagram conceptually showing receiving costs and delivery costs.

[0021] FIG. 5 is an illustrative diagram showing evaluation costs calculated for respective transport vehicles.

[0022] FIG. 6 is a diagram showing a comparative example of evaluation costs for a transport vehicle A and a transport vehicle B.

[0023] FIG. 7 is a diagram showing another example of a specific zone.

DESCRIPTION OF THE INVENTION

[0024] Hereinafter, an embodiment of an article transport facility will be described with reference to the drawings.

[0025] As shown in FIG. 1, an article transport facility **100** includes a plurality of transport vehicles **1** that move along a predetermined travel route **9** to transport articles W (see FIGS. 2 and 3), and a control system **2** that causes the transport vehicles **1** to perform transport processing in which a transport origin F and a transport destination T have been designated for the articles W.

[0026] In the present embodiment, the travel route **9** is set such that the travel directions of the transport vehicles **1** are fixed directions. In other words, the travel route **9** is a one-way route, and the transport vehicles **1** cannot travel backward.

[0027] As shown in FIGS. 2 and 3, in the present embodiment, the travel route **9** is set at a position distant above the floor surface. For example, the travel route **9** is configured using a rail **90** provided near the ceiling. The transport vehicles **1** are configured as so-called overhead transport vehicles, and travel on the rail **90** along the travel route **9**.

[0028] Various types of articles W can be handled in the article transport facility **100**. In the present embodiment, the article transport facility **100** is used in a semiconductor manufacturing factory. Examples of the article W include a substrate storage container (so-called FOUP: Front Opening Unified Pod) that store substrates such as wafers or panels, and a reticle storage container (so-called reticle pod) that stores reticles. In this case, the transport vehicles **1** transport the articles W,

such as substrate storage containers or reticle storage containers, between processing steps along the travel route **9**.

[0029] As shown in FIG. **1**, article holding sections **3** that are capable of holding the articles **W**, and to and from which the transport vehicles **1** can transfer the articles **W**, are disposed at a plurality of locations along the travel route **9**.

[0030] As shown in FIG. **2**, in the present embodiment, each of the article holding sections **3** includes a load port adjacent to a processing device **30** that performs processing on the articles **W**. This processing performed on the articles **W** means processing performed on the stored object (substrate or reticle) contained in the article **W** serving as the storage container. The processing devices **30** perform various types of processing such as thin film formation, photolithography, and etching.

[0031] The transport vehicle **1** can receive an article **W** that has been processed by the processing device **30** from the article holding section **3**, and deliver an article **W** that has not been processed by the processing device **30** to the article holding section **3**. The transport vehicle **1** includes a gripping section **10** configured to be able to grip an article **W**, and is configured to transfer the article **W** between the gripping section **10** and the article holding section **3**.

[0032] In the illustrated example, the load port serving as the article holding section **3** is disposed below the travel route **9** of the transport vehicle **1**. The transport vehicle **1** transfers the article **W** between the article holding section **3** and the gripping section **10** by lifting and lowering the gripping section **10**.

[0033] Also, as shown in FIG. **2**, in the case where the article holding section **3** is offset laterally from the travel route **9** rather than being positioned directly below the travel route **9**, the transport vehicle **1** positions the gripping section **10** directly above the article holding section **3** by sliding the gripping section **10** laterally from the vehicle body. Thereafter, the transport vehicle **1** transfers the article **W** between the article holding section **3** and the gripping section **10** by lifting and lowering the gripping section **10**.

[0034] Furthermore, due to the structure of the article holding section **3**, there may be constraints on the orientation of the article **W** to be placed in the article holding section **3**. In such a case, the transport vehicle **1** changes the orientation of the article **W** held by the gripping section **10** by rotating the gripping section **10** about the vertical axis. Accordingly, the article **W** can be oriented in a proper orientation relative to the article holding section **3**.

[0035] As described above, in the present embodiment, the transport vehicle **1** includes a slide mechanism for sliding the gripping section **10**, a lifting mechanism for lifting and lowering the gripping section **10**, and a turning mechanism for turning the gripping section **10**. When an article **W** is being received or delivered, the time required for the receiving or delivering operation varies depending on whether or not the gripping section **10** is slid, lifted and lowered, or turned. Note that the above-mentioned receiving and delivering operation can also be called a “transfer operation”.

[0036] As shown in FIG. **1**, at least one of the article holding sections **3** is a specific holding section **3S** to and from which an article **W** can be transferred by a transport vehicle **1** located in any of a plurality of specific zones **Z** on the travel route **9**.

[0037] The specific zones **Z** include a first specific zone **Z1** and a second specific zone **Z2** that are next to each other. Here “next to each other” means that the first specific zone **Z1** and the second specific zone **Z2** are arranged side by side in a manner other than a manner in which they are continuous with each other along the direction in which the travel route **9** extends. Therefore, the first specific zone **Z1** and the second specific zone **Z2** do not need to be parallel with each other. In this example, the first specific zone **Z1** and the second specific zone **Z2** are arranged side by side in the left-right direction.

[0038] In the present embodiment, the travel direction of the transport vehicle **1** permitted in the first specific zone **Z1** and the travel direction of the transport vehicle **1** permitted in the second specific zone **Z2** are set different from each other. In the example shown in FIG. **1**, in the first

specific zone **Z1**, the transport vehicle **1** is permitted to move only downward in the figure. In the second specific zone **Z2**, the transport vehicle **1** is permitted to move only upward in the figure. [0039] In this manner, the first specific zone **Z1** and the second specific zone **Z2** are next to each other, and are zones in which the permitted travel directions of the transport vehicle **1** are different from each other. However, when the travel route **9** is viewed as a whole, the first specific zone **Z1** and the second specific zone **Z2** are connected such that the transport vehicle **1** can travel between them via a connection zone. Any route included in the travel route **9** that can connect the first specific zone **Z1** and the second specific zone **Z2** to each other can be a connection zone.

[0040] As shown in FIG. **3**, in the present embodiment, the specific holding section **3S** includes a buffer for temporarily storing the articles **W**. In the illustrated example, a buffer serving as the specific holding section **3S** is disposed between the first specific zone **Z1** and the second specific zone **Z2**. This specific holding section **3S** can be accessed by both the transport vehicle **1** located in the first specific zone **Z1** and the transport vehicle **1** located in the second specific zone **Z2**. In other words, the articles **W** can be transferred between the specific holding section **3S** and any of the transport vehicles **1**.

[0041] As shown in FIG. **1**, the control system **2** is configured to cause the transport vehicles **1** to perform transport processing. In this example, a host control device that performs overall control of the transport vehicles **1** constitutes the control system **2**. However, in a broad sense, the control system **2** is constituted by various control devices in the article transport facility **100**. For example, transport vehicle control devices (not shown) provided in the transport vehicles **1** may constitute a part or the whole of the control system **2**.

[0042] The control system **2** includes, for example, a processor such as a microcomputer, and a peripheral circuit such as a memory. Processing and functions are realized by cooperation between the hardware and a program executed on the processor of a computer or the like.

[0043] In the transport processing that the control system **2** causes a transport vehicle **1** to perform, a transport origin **F** where an article **W** is held and a transport destination **T** of the article **W** are designated. At that time, the control system **2** also designates a route from the transport origin **F** to the transport destination **T**. The control system **2** can extract a plurality of routes, select an optimal route (the route that minimizes the total time required from when a transport command is issued to when the transport processing is completed) from among the extracted routes, and designate the optimal route for the transport vehicle **1**. In executing the transport processing, the transport vehicle **1** moves to the transport origin **F** to receive an article **W**, and transports the received article **W** to the transport destination **T** and delivers the article **W** there. The control system **2** is configured to execute selection processing for selecting a target transport vehicle **1**, which is the transport vehicle **1** to be caused to perform transport processing, from among a plurality of transport vehicles **1** that are not holding an article **W**.

[0044] Here, since there are a plurality of transport vehicles **1** on the travel route **9**, each of the transport vehicles **1** is a candidate for selection as the target transport vehicle **1**. The travel route **9** from each of the transport vehicles **1** to the transport origin **F** varies depending on the current position of the transport vehicle **1**. In other words, there are a plurality of travel routes **9** from the transport vehicles **1** to the transport origin **F**.

[0045] However, in the case where an article holding section **3** other than the specific holding section **3S** is the transport origin **F**, the travel route **9** after the transport vehicle **1** receives the article **W** at the transport origin **F**, that is to say, the travel route **9** from the transport origin **F** to the transport destination **T**, is the same regardless of which transport vehicle **1** is selected as the target transport vehicle **1**. This is because, as described above, one-way travel is performed along the travel route **9**, and a rational travel route **9** from the article holding section **3** (transport origin **F**) to the transport destination **T** is easy to determine uniquely.

[0046] In the case where the specific holding section **3S** is the transport origin **F**, the travel route **9** from the transport origin **F** to the transport destination **T** also differs depending on which transport

vehicle **1** is selected as the target transport vehicle **1**. In other words, since the permitted travel direction of the transport vehicle **1** is different between the first specific zone **Z1** and the second specific zone **Z2**, when the transport vehicle **1** in the first specific zone **Z1** receives an article **W** from the specific holding section **3S** (transport origin **F**), the subsequent travel route **9** to the transport destination **T** is different from when the transport vehicle **1** in the second specific zone **Z2** receives the article **W** from the specific holding section **3S** (transport origin **F**).

[0047] In view of the above-described circumstances, selection processing is executed to select a target transport vehicle **1** that is to execute the transport processing.

[0048] As shown in FIG. **4**, by executing selection processing, the control system **2** calculates an evaluation cost C_x for each transport vehicle **1** using costs C , which are values regarding factors that affect the travel time of the transport vehicle **1** and increase as the travel time becomes longer, and selects a target transport vehicle **1** based on the evaluation cost C_x .

[0049] In selection processing in the case where the specific holding section **3S** is the transport origin **F**, the evaluation cost C_x is calculated based on both a receiving cost C_r , which is a cost C corresponding to the travel time of the transport vehicle **1** from a current position **P** to the transport origin **F**, and a delivery cost C_g , which is a cost C corresponding to the travel time of the transport vehicle **1** from the transport origin **F** to the transport destination **T**. Note that the receiving cost C_r and the delivery cost C_g are both calculated by adding a variable cost, which is calculated taking into account the presence of other transport vehicles **1** on the route at the present time or in the future, to a reference cost calculated on the assumption that there are no other transport vehicles **1** on the route. Furthermore, when a route is defined by one or more links, the reference cost and variable cost can be calculated for each of the links.

[0050] FIG. **4** is a diagram conceptually showing the receiving cost C_r and the delivery cost C_g . FIG. **4** also illustrates four transport vehicles **A** to **D**, with each transport vehicle **1** having a different current position **P**.

[0051] The receiving cost C_r and the delivery cost C_g are calculated as quantitative values to facilitate comparison between the transport vehicles **A** to **D**.

[0052] Factors that affect the travel time of the transport vehicle **1** include, for example, the travel distance of the transport vehicle **1**, the structure of the travel route **9**, congestion on the travel route **9**, the time required for the transfer of the article **W**, and the number of other transport vehicles **1** on the travel route **9**. The costs C are set to increase as the travel time of the transport vehicle **1** increases due to such factors. In the present embodiment, the receiving cost C_r and the delivery cost C_g are calculated using at least one of the following: a distance cost, which increases as the travel distance of the transport vehicle **1** becomes longer; a structure cost, which increases as the maximum travel speed of the transport vehicle **1** decreases according to the structure of the travel route **9** of the transport vehicle **1**; a congestion cost, which increases as the degree of congestion on the travel route **9** of the transport vehicle **1** increases; a transfer cost, which increases as the time it takes for the transport vehicle **1** to transfer the article **W** between the article holding section **3** and the transport destination **T** becomes longer; and an other vehicle cost, which increases as the number of other transport vehicles **1** present on the travel route **9** of the transport vehicle **1** increases.

[0053] The distance cost is determined according to the length of the travel distance of the transport vehicle **1**. In other words, the distance cost required from the current position **P** of the transport vehicle **1** to the transport origin **F** is determined according to the length of the travel route **9** from the current position **P** of the transport vehicle **1** to the transport origin **F**. Also, the distance cost required from the transport origin **F** to the transport destination **T** is determined according to the length of the travel route **9** from the transport origin **F** to the transport destination **T**. The longer the travel distance is, the longer the travel time of the transport vehicle **1** is, and therefore the distance cost becomes relatively larger.

[0054] The structure cost is determined according to the structure of the travel route **9**. For

example, in a straight line portion of the travel route **9**, the maximum travel speed of the transport vehicle **1** is likely to be set higher, the travel time of the transport vehicle **1** is accordingly shorter, and thus the structure cost is relatively smaller. On the other hand, in a curved portion of the travel route **9** and at a junction portion where multiple travel routes **9** join, the maximum travel speed of the transport vehicle **1** is likely to be set lower, the travel time of the transport vehicle **1** is accordingly longer, and thus the structure cost is relatively larger.

[0055] The congestion cost is determined according to the degree of congestion (congestion level) on the travel route **9**. The higher the congestion level is, the longer the travel time of the transport vehicle **1** is, and therefore the congestion cost becomes relatively larger. The congestion level is set according to, for example, the number of transport vehicles **1** in a predetermined section of the travel route **9**, the passing speed or the passing time of the transport vehicles **1**, and the like. The congestion level may also be set based on the length of the congestion. The length of the congested may be the length of congestion that actually exists on the travel route **9**, or the length of congestion that does not currently exist but is predicted to occur in the future.

[0056] The transfer cost is determined according to the time taken for the transport vehicle **1** to transfer the article W. As described above, in the present embodiment, the transport vehicle **1** includes a slide mechanism for sliding the gripping section **10**, a lifting mechanism for lifting and lowering the gripping section **10**, and a turning mechanism for turning the gripping section **10**. When an article W is delivered or received, the time required for the transfer operation varies depending on whether the gripping section **10** is slid and the amount of sliding, whether it is lifted or lowered and the amount of lifting or lowering, and whether it is turned and the amount of turning. The longer the time required for the transfer operation is, the longer the travel time of the transport vehicle **1** is, and therefore the transfer cost becomes relatively higher.

[0057] The other vehicle cost is determined according to the number of other transport vehicles **1** that are present on the travel route **9**. The movement of a transport vehicle **1** is constrained by the presence of other transport vehicles. As the number of other transport vehicles **1** increases, the number of constraints also increases, the travel time tends to accordingly become longer, and thus the other vehicle cost becomes relatively higher. Furthermore, the number of other transport vehicles **1** may be the number of other transport vehicles **1** that are actually present, or the number of other transport vehicles **1** that may be present in the future.

[0058] At least one of the distance cost, the structure cost, the congestion cost, the transfer cost, and the other vehicle cost is used to calculate the receiving cost C_r and the delivery cost C_g . These five costs can be called “element costs”, and the receiving cost C_r and the delivery cost C_g are calculated by, for example, adding element costs together, multiplying element costs together, or by a combination of these. In selection processing in the case where the specific holding section **3S** is set as the transport origin F, the control system **2** calculates the evaluation cost C_x based on both the calculated receiving cost C_r and the calculated delivery cost C_g .

[0059] Note that in selection processing in the case where an article holding section **3** other than the specific holding section **3S** is set as the transport origin F, the evaluation cost C_x is calculated based on the receiving cost C_r , which is the cost C corresponding to the travel time from the current position P of the transport vehicle **1** to the transport origin F. In other words, the delivery cost C_g is not taken into consideration. The reason for this is that, as described above, the travel route **9** from the transport origin F to the transport destination T is the same regardless of which transport vehicle **1** is selected as the target transport vehicle **1**.

[0060] FIG. 5 shows the evaluation cost C_x for each of the transport vehicles A to D.

[0061] By executing selection processing, the control system **2** calculates the evaluation cost C_x for each transport vehicle **1**, and selects the transport vehicle **1** with the smallest evaluation cost C_x as the target transport vehicle **1**. In the present embodiment, the evaluation cost C_x is calculated for each transport vehicle **1** by adding up the receiving cost C_r and the delivery cost C_g . The control system **2** compares the evaluation costs C_x calculated for the transport vehicles **1** to determine the

smallest evaluation cost that results in the lowest evaluation cost C_x , and selects the transport vehicle **1** associated with the smallest evaluation cost as the target transport vehicle **1**.

[0062] In the example shown in FIG. 5, the evaluation cost C_x for the transport vehicle B is the smallest evaluation cost, and therefore the control system **2** selects the transport vehicle B as the target transport vehicle **1**.

[0063] FIG. 6 illustrates an example in which, in selection processing in the case where the specific holding section **3S** is set as the transport origin F, the evaluation cost C_x is calculated using only the distance cost. The evaluation costs C_x of the transport vehicle A and the transport vehicle B, which are at different current positions P, will be compared with reference to FIG. 6.

[0064] In the example shown in FIG. 6, the current position P of the transport vehicle A is closer to the transport origin F than the current position P of the transport vehicle B is. Therefore, the receiving cost C_r of the transport vehicle A is smaller than that of the transport vehicle B. In the selection processing, if only the travel route **9** from the current position P of the transport vehicle **1** to the transport origin F is taken into consideration, the transport vehicle A that has the smallest receiving cost C_r is selected as the target transport vehicle **1**.

[0065] However, since the specific holding section **3S** is the transport origin F, the travel route **9** from the first specific zone **Z1** to the transport destination T in the case where the transport vehicle A receives the article W is different from the travel route **9** from the second specific zone **Z2** to the transport destination T in the case where the transport vehicle B receives the article W. Therefore, the delivery cost C_g of each of the transport vehicle A and the transport vehicle B must also be taken into consideration.

[0066] In the example shown in FIG. 6, the travel route **9** from the second specific zone **Z2** to the transport destination T in the case where the transport vehicle B receives the article W is shorter than the travel route **9** from the first specific zone **Z1** to the transport destination T in the case where the transport vehicle A receives the article W. Therefore, the delivery cost C_g of the transport vehicle B is smaller than that of the transport vehicle A.

[0067] In the present embodiment, the evaluation cost C_x is calculated by adding up the receiving cost C_r and the delivery cost C_g for each transport vehicle **1**.

[0068] In the example shown in FIG. 6, the evaluation cost C_x (receiving cost C_r + delivery cost C_g) for the transport vehicle B is smaller than the evaluation cost C_x (receiving cost C_r + delivery cost C_g) for the transport vehicle A. Therefore, the control system **2** selects the transport vehicle B as the target transport vehicle **1** in the selection processing. Accordingly, the transport of the article W from the transport origin F to the transport destination T can be rationally performed using the transport vehicle B.

Other Embodiments

[0069] Next, other embodiments will be described. [0070] (1) In the above embodiment, an example has been described in which the first specific zone **Z1** and the second specific zone **Z2** are side by side in the left-right direction. However, the present invention is not limited to such an example, and the first specific zone **Z1** and the second specific zone **Z2** need only be arranged side by side in a manner other than a manner in which they are continuous with each other along the direction in which the travel route **9** extends. Therefore, for example, as shown in FIG. 7, in a portion where a plurality of travel routes **9** exist along the vertical direction, the first specific zone **Z1** and the second specific zone **Z2** may be side by side in the up-down direction. In this case, both the transport vehicle **1** in the first specific zone **Z1** and the transport vehicle **1** in the second specific zone **Z2** can transfer an article W with the article holding section **3** located below both the first specific zone **Z1** and the second specific zone **Z2**. Therefore, such an article holding section **3** is also considered to be a specific holding section **3S**. [0071] (2) In the above embodiment, an example has been described in which the travel direction

[0072] of the transport vehicle **1** permitted in the first specific zone **Z1** and the travel direction of the transport vehicle **1** permitted in the second specific zone **Z2** are set different from each other.

However, the present invention is not limited to such an example, and these travel directions may be set to the same direction. [0073] (3) In the above embodiment, an example has been described in which the evaluation cost C_x is calculated by adding up the receiving cost C_r and the delivery cost C_g for each transport vehicle **1**. However, the present invention is not limited to such an example, and the evaluation cost C_x may be calculated by, for example, multiplying the receiving cost C_r and the delivery cost C_g . [0074] (4) In the above embodiment, an example has been described in which the evaluation cost C_x of the transport vehicle **1** is calculated based on three locations, namely the current position P of the transport vehicle **1**, the transport origin F , and the transport destination T . However, the evaluation cost C_x may be calculated additionally based on a fourth location that the transport vehicle **1** can travel to, for example. An example of the fourth location is a maintenance station where maintenance, inspection, and the like are performed on the transport vehicle **1**. If the transport vehicle **1** needs repair or charging, the transport vehicle **1** travels to the maintenance station (fourth location) after completing transport processing. The calculation of the evaluation cost C_x also takes into consideration the cost required for the transport vehicle **1** to travel to the maintenance station. [0075] (5) In the above embodiment, an example has been described in which the travel route **9** is configured using the rail **90** provided near the ceiling. However, the present invention is not limited to such an example, and a configuration is possible in which the travel route **9** is configured using a rail disposed near the floor surface, and the transport vehicle **1** is configured to move along the rail. Alternatively, a configuration is possible in which the travel route **9** is configured using magnetic tape disposed on the floor surface, and the transport vehicle **1** is configured to travel along the magnetic tape. [0076] (6) Note that the configurations disclosed in the above-described embodiments may be combined with configurations disclosed in other embodiments as long as no contradiction arises. Regarding such other configurations as well, the embodiments disclosed in this specification are merely examples in all respects. Therefore, various modifications can be made as appropriate within the scope of the present disclosure.

Overview of Present Embodiment

[0077] The following is an overview of the present embodiment.

[0078] An article transport facility according to an aspect of the present invention is an article transport facility including: [0079] a plurality of transport vehicles configured to travel along a predetermined travel route and transport an article; [0080] a control system configured to cause the plurality of transport vehicles to perform transport processing in which a transport origin and a transport destination are designated for respective articles; and [0081] a plurality of article holding sections at respective locations along the travel route and configured to store articles and transfer articles with the plurality of transport vehicles, [0082] at least one of the plurality of article holding sections being a specific holding section to and from which an article is transferable by a transport vehicle located in a specific zone among a plurality of specific zones on the travel route, [0083] the control system being further configured to, in order to select a target transport vehicle to be caused to perform the transport processing from among a plurality of transport vehicles not holding any article, execute selection processing including (i) calculating an evaluation cost for each of the plurality of transport vehicles not holding any article, using a cost whose value is related to a factor affecting a travel time of the corresponding transport vehicle and whose value increases as the travel time is longer, and (ii) selecting a transport vehicle having a smallest evaluation cost as the target transport vehicle, and [0084] in the selection processing executed in a case where the specific holding section is the transport origin, the control system calculates the evaluation cost based on both a receiving cost and a delivery cost, the receiving cost being the cost corresponding to a travel time from a current position of the corresponding transport vehicle to the transport origin, and the delivery cost being the cost corresponding to a travel time of the corresponding transport vehicle from the transport origin to the transport destination.

[0085] According to this configuration, when the specific holding section is set as the transport origin, the target transport vehicle to perform transport processing can be selected based on both

the cost corresponding to the travel time from the current position of the transport vehicle to the transport origin and the cost corresponding to the travel time of the transport vehicle from the transport origin to the transport destination. In other words, the target transport vehicle can be selected based further on the situation after the transport vehicle receives the article at the transport origin. Therefore, with this configuration, it is possible to realize highly rational article transport. [0086] It is preferable that in the selection processing executed in a case where an article holding section other than the specific holding section is the transport origin, the control system calculates the evaluation cost based on the receiving cost, which is the cost corresponding to the travel time from the current position of the corresponding transport vehicle to the transport origin.

[0087] For example, in the case where the travel direction of the transport vehicles on the travel route is limited to one direction and an article holding section other than a specific holding section is set as the transport origin, the travel route to the transport destination (travel route from the transport origin to the transport destination) after the transport vehicle receives the article at the transport origin is the same regardless of which transport vehicle is selected. In such a case, there is little need to use the delivery cost when calculating the evaluation cost. According to this configuration, in selection processing in the case where an article holding section other than a specific holding section is set as the transport origin, the evaluation cost is calculated based on the receiving cost, and therefore the delivery cost can be excluded from the calculation elements, thereby making it possible to reduce the computational load on the control system.

[0088] It is preferable that the plurality of specific zones include a first specific zone and a second specific zone that are next to each other, [0089] the plurality of transport vehicles are permitted to travel in a first travel direction in the first specific zone and permitted to travel in a second travel direction different from the first travel direction in the second specific zone, and [0090] the first specific zone and the second specific zone are connected in such a manner that the plurality of transport vehicles can travel between the first specific zone and the second specific zone via a connection zone.

[0091] The travel route for arriving at the specific holding section differs depending on whether the transport vehicle passes through the first specific zone or the second specific zone, and it is highly likely that the travel route from the specific holding section to the transport destination will also differ. However, as described above, the evaluation cost, which serves as an indicator for selecting the target transport vehicle, is calculated based on both the receiving cost corresponding to the travel route of the transport vehicle to the specific holding section, and the delivery cost corresponding to the travel route from the specific holding section to the transport destination. Therefore, even when the first specific zone and the second specific zone are provided on the travel route as in this configuration, the control system can select the most suitable transport vehicle as the target transport vehicle.

[0092] It is preferable that the receiving cost and the delivery cost are calculated using at least one of a distance cost, a structure cost, a congestion cost, a transfer cost, and an other vehicle cost,

[0093] the distance cost being a cost that increases as a travel distance of the corresponding transport vehicle increases, [0094] the structure cost being a cost that increases as a maximum travel speed of the corresponding transport vehicle decreases according to a structure of the travel route traveled by the corresponding transport vehicle, [0095] the congestion cost being a cost that increases as a congestion level in the travel route traveled by the corresponding transport vehicle increases, [0096] the transfer cost being a cost that increases as a transfer time increases, the transfer time being a time required for the corresponding transport vehicle to perform article transfer with the article holding section and perform article transfer at the transport destination, and [0097] the other vehicle cost being a cost that increases as a total number of other transport vehicles in the travel route traveled by the corresponding transport vehicle increases.

[0098] According to this configuration, various costs can be appropriately determined based on various factors that affect the travel time of the transport vehicle. Since these costs are used in

calculating the receiving cost and the delivery cost, and thus used in calculating the evaluation cost, it is possible to appropriately select the target transport vehicle.

INDUSTRIAL APPLICABILITY

[0099] The technology disclosed herein is applicable to an article transport facility including a plurality of transport vehicles that move along a predetermined travel route to transport articles, and a control system that causes the transport vehicles to perform transport processing in which a transport origin and a transport destination have been designated for the articles.

Claims

1. An article transport facility comprising: a plurality of transport vehicles configured to travel along a predetermined travel route and transport an article; a control system configured to cause the plurality of transport vehicles to perform transport processing in which a transport origin and a transport destination are designated for respective articles; and a plurality of article holding sections at respective locations along the travel route and configured to store articles and transfer articles with the plurality of transport vehicles, and wherein: at least one of the plurality of article holding sections is a specific holding section to and from which an article is transferable by a transport vehicle located in a specific zone among a plurality of specific zones on the travel route, the control system is further configured to, in order to select a target transport vehicle to be caused to perform the transport processing from among a plurality of transport vehicles not holding any article, execute selection processing comprising (i) calculating an evaluation cost for each of the plurality of transport vehicles not holding any article, using a cost whose value is related to a factor affecting a travel time of the corresponding transport vehicle and whose value increases as the travel time is longer, and (ii) selecting a transport vehicle having a smallest evaluation cost as the target transport vehicle, and in the selection processing executed in a case where the specific holding section is the transport origin, the control system calculates the evaluation cost based on both a receiving cost and a delivery cost, the receiving cost is the cost corresponding to a travel time from a current position of the corresponding transport vehicle to the transport origin, and the delivery cost is the cost corresponding to a travel time of the corresponding transport vehicle from the transport origin to the transport destination.
2. The article transport facility according to claim 1, wherein in the selection processing executed in a case where an article holding section other than the specific holding section is the transport origin, the control system calculates the evaluation cost based on the receiving cost, which is the cost corresponding to the travel time from the current position of the corresponding transport vehicle to the transport origin.
3. The article transport facility according to claim 1, wherein: the plurality of specific zones comprise a first specific zone and a second specific zone that are next to each other, the plurality of transport vehicles is permitted to travel in a first travel direction in the first specific zone and permitted to travel in a second travel direction different from the first travel direction in the second specific zone, and the first specific zone and the second specific zone are connected in such a manner that the plurality of transport vehicles can travel between the first specific zone and the second specific zone via a connection zone.
4. The article transport facility according to claim 1, wherein: the receiving cost and the delivery cost are calculated using at least one of a distance cost, a structure cost, a congestion cost, a transfer cost, and an other vehicle cost, the distance cost is a cost that increases as a travel distance of the corresponding transport vehicle increases, the structure cost is a cost that increases as a maximum travel speed of the corresponding transport vehicle decreases according to a structure of the travel route traveled by the corresponding transport vehicle, the congestion cost is a cost that increases as a congestion level in the travel route traveled by the corresponding transport vehicle increases, the transfer cost is a cost that increases as a transfer time increases, and the transfer time is a time

required for the corresponding transport vehicle to perform article transfer with the article holding section and perform article transfer at the transport destination, and the other vehicle cost is a cost that increases as a total number of other transport vehicles in the travel route traveled by the corresponding transport vehicle increases.
