

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250284236

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

ISHIHARA; Yoshiaki

IMAGE FORMING APPARATUS THAT DETECTS PRESENCE OF SHEET ON TRANSPORT ROUTE, AND POSTURE OF BRANCH GUIDE, WITH SINGLE SENSOR

Abstract

An image forming apparatus includes an image forming device; a fixing device; a first transport route; a second transport route; a branch guide that assumes a first posture and a second posture; a sheet contact member that assumes a non-contact posture and a contacting posture; a detection object that assumes a first posture, when the branch guide assumes the first posture and when the sheet contact member assumes the non-contact posture, and assumes a second posture, when the branch guide assumes the second posture and when the sheet contact member assumes the contacting posture; and a sensor that outputs a first signal, when the detection object is in the first posture, and outputs a second signal, when the detection object is in the second posture.

Inventors: ISHIHARA; Yoshiaki (Osaka, JP)

Applicant: KYOCERA Document Solutions Inc. (Osaka, JP)

Family ID: 1000008531483

Assignee: KYOCERA Document Solutions Inc. (Osaka, JP)

Appl. No.: 19/074775

Filed: March 10, 2025

Foreign Application Priority Data

JP 2024-037363

Mar. 11, 2024

Publication Classification

Int. Cl.: G03G15/00 (20060101)

U.S. Cl.:

Background/Summary

INCORPORATION BY REFERENCE

[0001] This application claims priority to Japanese Patent Application No. 2024-037363 filed on Mar. 11, 2024, the entire contents of which are incorporated by reference herein.

BACKGROUND

[0002] The present disclosure relates to an image forming apparatus, and in particular to a technique to detect occurrence of sheet jam and a posture of a branch guide.

[0003] In relation to existing image forming apparatuses, some techniques to detect occurrence of sheet jam, and the posture of a branch guide, are known. An example of such techniques includes deciding, when the sheet jam is detected, whether a branch guide plate is located at the home position, displaying a message to the effect that the jam has occurred, when the branch guide plate is located at the home position, and displaying, when the branch guide plate is not located at the home position, the message to the effect that the jam has occurred, after locating the branch guide plate at the home position.

SUMMARY

[0004] The disclosure proposes further improvement of the foregoing technique.

[0005] In an aspect, the disclosure provides an image forming apparatus including an image forming device, a fixing device, a first transport route, a second transport route, a branch guide, a sheet contact member, a detection object, and a sensor. The image forming device forms an image on a sheet. The fixing device fixes the image onto the sheet. The first transport route extends from the fixing device to a delivery port. The second transport route is branched from the first transport route, and extends toward the image forming device. The branch guide assumes a first guide posture, to guide the sheet to the first transport route, and assumes a second guide posture, to guide the sheet to the second transport route. The sheet contact member assumes a non-contact posture, when not in contact with the sheet on the first transport route, and assumes a contacting posture, when in contact with the sheet on the first transport route. The detection object assumes a first detection posture, when the branch guide assumes the first guide posture, assumes a second detection posture, when the branch guide assumes the second guide posture, assumes the first detection posture, when the sheet contact member assumes the non-contact posture, and assumes the second detection posture, when the sheet contact member assumes the contacting posture. The sensor outputs a first signal, when the detection object is in the first detection posture, and outputs a second signal, when the detection object is in the second detection posture.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0006] FIG. 1 is a schematic cross-sectional view showing a structure of an image forming apparatus;

[0007] FIG. 2 is a block diagram showing a configuration of the image forming apparatus;

[0008] FIG. 3 is a partially enlarged front view showing a fixing device and related parts;

[0009] FIG. 4 is a partially enlarged front view showing the fixing device and the related parts;

[0010] FIG. 5 is a partially enlarged front view showing the fixing device and the related parts; and

[0011] FIG. 6 is a flowchart showing an abnormality detection process.

DETAILED DESCRIPTION

[0012] Hereafter, an image forming apparatus according to an embodiment of the disclosure will be described, with reference to the drawings. FIG. 1 is a schematic cross-sectional view showing a structure of the image forming apparatus 1 according to the embodiment of the disclosure. FIG. 2 is a block diagram showing a configuration of the image forming apparatus 1. FIG. 3 to FIG. 5 are partially enlarged front views each showing a fixing device 14 and related parts, installed in the image forming apparatus 1.

Configuration of Apparatus

[0013] As shown in FIG. 1, the image forming apparatus 1 is a tandem-type color printer. In a casing 11 of the image forming apparatus 1, a sheet feeding device 12, an image forming device 13, and a fixing device 14 are accommodated.

[0014] Inside the casing 11, a sheet transport route 111 is provided that extends from the sheet feeding device 12 to the fixing device 14, via the image forming device 13. A plurality of transport roller pairs 112 are provided, at predetermined positions along the sheet transport route 111. The transport roller pairs 112 each serve to transport a sheet P along the sheet transport route 111.

[0015] The casing 11 further includes therein a first transport route 113 extending from the fixing device 14 to a delivery port 153, and a second transport route 114 branched from the first transport route 113, and merging with the sheet transport route 111 at a position upstream of the image forming device 13 in a sheet transport direction.

[0016] The sheet feeding device 12 includes a sheet feeding tray 121, a pickup roller 122, and a sheet feeding roller pair 123. The pickup roller 122 draws out the sheets P stored in the sheet feeding tray 121, one by one. The sheet feeding roller pair 123 delivers the sheet P drawn out by the pickup roller 122, to the sheet transport route 111.

[0017] The image forming device 13 forms an image, constituted of a toner image, on the sheet P. The image forming device 13 includes image forming units 131M, 131C, 131Y, and 131K, an intermediate transfer belt 132, a primary transfer roller 133, and a secondary transfer roller 134.

[0018] The image forming units 131M, 131C, 131Y, and 131K respectively correspond to magenta, cyan, yellow, and black colors. The image forming units 131M, 131C, 131Y, and 131K each include a photoconductor drum 135, so that the toner image is formed thereon, through charging, exposing, developing, and transferring processes, using developing agents respectively corresponding to the mentioned colors.

[0019] The intermediate transfer belt 132 is stretched around a drive roller 136 and a follower roller 137. The intermediate transfer belt 132 is made to revolve, by the rotating motion of the drive roller 136. The follower roller 137 is made to rotate, by the revolving motion of the intermediate transfer belt 132.

[0020] The primary transfer roller 133 is located so as to oppose one of the photoconductor drums 135, via the intermediate transfer belt 132. The primary transfer roller 133 is made to rotate, by the revolving motion of the intermediate transfer belt 132. The primary transfer roller 133 transfers the toner image formed on the photoconductor drum 135 to the intermediate transfer belt 132, as primary transfer.

[0021] The secondary transfer roller 134 transfers the toner image on the intermediate transfer belt 132 to the sheet P delivered from the sheet feeding device 12, as secondary transfer. The secondary transfer roller 134 is located so as to oppose the drive roller 136, via the intermediate transfer belt 132. The secondary transfer roller 134 is made to rotate, by the revolving motion of the intermediate transfer belt 132.

[0022] The fixing device 14 includes a pressure roller 141 and a fixing roller 142. The pressure roller 141 is made to rotate about the axial line, by the driving force of a drive motor. The fixing roller 142 includes a fixing belt and a heater. The fixing belt is a generally cylindrical endless belt, rotatably supported by a shaft. The heater is provided inside the fixing belt, in contact with the inner circumferential surface of the fixing belt.

[0023] The fixing roller **142** is pressed against the pressure roller **141** by a pressing member, so as to define a nip region. The fixing roller **142** is made to rotate by the rotating motion of the pressure roller **141**, in pressure-contact therewith. The fixing device **14** heats and presses the sheet P, having the toner image transferred thereto, through the nip region, thereby fixing the toner image onto the sheet P. As result, a full-color image is formed on the sheet P.

[0024] The image forming apparatus **1** further includes an output tray **151**, and a delivery roller **152** shown in FIG. **3**. The delivery roller **152** is made to rotate about the axial line, by the driving force of the drive motor. In this embodiment, the pressure roller **141** and the delivery roller **152** are connected to the same drive motor. The delivery roller **152** delivers the sheet P on which the full-color image has been formed, to the output tray **151** through the delivery port **153**.

[0025] The sheet P having the full-color image formed thereon is delivered to either of the first transport route **113** and the second transport route **114**, by a branch guide **40** shown in FIG. **3**. For example, when the image is formed only on one face of the sheet P, the branch guide **40** guides the sheet P that has passed the fixing device **14** to the first transport route **113**, so that the delivery roller **152** delivers the sheet P to the output tray **151**.

[0026] On the other hand, when the image is formed on both faces of the sheet P, the branch guide **40** once guides the sheet P that has passed the fixing device **14**, with an image formed on one face, to the first transport route **113**, so that the delivery roller **152** discharges a part of the sheet P to outside of the apparatus. Then, when the delivery roller **152** rotates reversely so that the sheet P is switched back, the branch guide **40** guides the sheet P to the second transport route **114**, and feeds the sheet P toward the merging point with the sheet transport route **111**. The image forming device **13** forms an image on the back face of the sheet P, transported along the sheet transport route **111**. The branch guide **40** guides the sheet P that has again passed the fixing device **14** to the first transport route **113**, so that the delivery roller **152** delivers the sheet P to the output tray **151**.

[0027] Referring to FIG. **2**, the image forming apparatus **1** includes a control device **100**. The control device **100** includes a processor, a random-access memory (RAM), and a read-only memory (ROM). The processor is, for example, a central processing unit (CPU), a micro processing unit (MPU), or an application-specific integrated circuit (ASIC).

[0028] The control device **100** is electrically connected to the sheet feeding device **12**, the image forming device **13**, the fixing device **14**, a display device **16**, an operation device **17**, a hard disk drive (HDD) **18**, and a communication device **19**. The control device **100** acts as a controller **10**, when the processor executes the computer programs stored in the built-in ROM or HDD **18**.

[0029] The controller **10** controls the overall operation of the image forming apparatus **1**. Here, the controller **10** may be constituted in the form of a logic circuit, instead of being realized by the operation according to the computer program, or constituted of two or more control devices.

[0030] The display device **16** is, for example, constituted of an LCD or an organic light-emitting diode (OLED) display. The display device **16** displays various types of screen related to the functions that the image forming apparatus **1** is configured to perform.

[0031] The operation device **17** includes a plurality of hard keys. The operation device **17** also includes a touch panel overlaid on the display device **16**. The operation device **17** receives an instruction from the user. The operation device **17** may also include soft keys displayed on the display device **16**.

[0032] The HDD **18** contains the computer programs for realizing the functions of the image forming apparatus **1**. In this embodiment, the HDD **18** contains a detection program for executing an abnormality detection process.

[0033] The communication device **19** includes a communication module such as a local area network (LAN) board. The controller **10** performs data communication through the communication device **19**, with an external device such as a personal computer (PC) connected via a network.

[0034] A power source is connected to each of the components of the image forming apparatus **1**. When the user turns the power on, the power is supplied to those components from the power

source.

[0035] Referring now to FIG. 3 to FIG. 5, the configuration of the fixing device **14** and the related parts will be described in detail. FIG. 3 illustrates the state before the image forming operation, FIG. 4 illustrates the state where the sheet P is being delivered to the first transport route **113**, and FIG. 5 illustrates the state where the sheet P is being delivered to the second transport route **114**. [0036] As shown in FIG. 3, the image forming apparatus **1** includes an actuator **20**, the branch guide **40**, a lever **60**, and a sensor **80**, which are provided around the fixing device **14**.

[0037] The actuator **20** includes a rotation shaft **22**, a first contact piece **24**, and a second contact piece **26**. The rotation shaft **22** is rotatably supported, at a position on the upper side of the fixing device **14**. The first contact piece **24** is projecting from the rotation shaft **22**, in the direction orthogonal to the axial direction thereof. The second contact piece **26** is projecting from the rotation shaft **22**, in the direction orthogonal to the axial direction thereof, but different from the projecting direction of the first contact piece **24** (in this case, approximately 120° from the first contact piece **24**, clockwise in FIG. 3).

[0038] The actuator **20** is a sheet contact member, configured to assume a non-contact posture, when not in contact with the sheet P on the first transport route **113**, and assume a contacting posture when in contact with the sheet P on the first transport route **113**. To be more specific, when the sheet P is not present on the first transport route **113**, the actuator **20** assumes the non-contact posture, in which the first contact piece **24** is present on the first transport route **113**, as shown in FIG. 3 and FIG. 5. When the sheet P is present on the first transport route **113**, the first contact piece **24** makes contact with the sheet P on the first transport route **113** as shown in FIG. 4, and therefore the actuator **20** rotates clockwise in FIG. 4 about the rotation shaft **22**, thereby assuming the contacting posture.

[0039] The branch guide **40** includes a rotation shaft **42**, a guide member **44**, and a contact member **46**. The rotation shaft **42** is rotatably supported, at a position on the upper side of the fixing device **14**. The guide member **44** is projecting from the rotation shaft **42**, such that the longitudinal direction of the guide member **44** is aligned with the axial direction of the rotation shaft **42**. The contact member **46** is projecting from the rotation shaft **42**, in the direction orthogonal to the axial direction of the rotation shaft **42**, but different from the projecting direction of the guide member **44** from the rotation shaft **42** (in this case, approximately 180° from the guide member **44**, counterclockwise in FIG. 3).

[0040] To guide the sheet P to the first transport route **113**, the branch guide **40** assumes a first guide posture, in which a first face **44A** of the guide member **44** forms a part of the first transport route **113**, as shown in FIG. 3 and FIG. 4. To guide the sheet P to the second transport route **114**, the branch guide **40** assumes a second guide posture, in which a second face **44B** of the guide member **44**, on the opposite side of the first face **44A**, forms a part of the second transport route **114**, as shown in FIG. 5.

[0041] To shift the branch guide **40** from the first guide posture to the second guide posture, the controller **10** operates a solenoid provided in the branch guide **40** in the forward direction, for a predetermined moving time (in this case, 120 msec), thereby rotating the branch guide **40** counterclockwise in FIG. 3 to FIG. 5, about the rotation shaft **42**.

[0042] The lever **60** includes a rotation shaft **62**, a contact piece **64**, and a detection piece **66** serving as a detection object. The rotation shaft **62** is rotatably supported at a position beside the fixing device **14**. The contact piece **64** is projecting from the rotation shaft **62**, in a direction orthogonal to the axial direction thereof. The detection piece **66** is projecting from the rotation shaft **62**, in the direction orthogonal to the axial direction thereof, but different from the projecting direction of the contact piece **64** (in this case, approximately 120° from the contact piece **64**, counterclockwise in FIG. 3).

[0043] When the branch guide **40** assumes the first guide posture, the lever **60** assumes a first detection posture, in which the contact member **46** of the branch guide **40** is not in contact with the

contact piece **64** of the lever **60**, as shown in FIG. **3** and FIG. **4**. When the branch guide **40** assumes the second guide posture, the contact member **46** of the branch guide **40** makes contact with the contact piece **64** of the lever **60**, because of the counterclockwise rotation of the branch guide **40**, so that the lever **60** rotates clockwise about the rotation shaft **62**, thereby assuming the second detection posture, as shown in FIG. **5**.

[0044] When the actuator **20** assumes the non-contact posture, the lever **60** assumes the first detection posture, in which the second contact piece **26** of the actuator **20** is in contact with the contact piece **64** of the lever **60**, as shown in FIG. **3**. When the actuator **20** assumes the contacting posture, the second contact piece **26** of the actuator **20** presses the contact piece **64** of the lever **60**, because of the clockwise rotation of the actuator **20**, so that the lever **60** rotates clockwise about the rotation shaft **62**, thereby assuming the second detection posture, as shown in FIG. **4**.

[0045] The sensor **80** is a photosensor for sensing the detection piece **66** of the lever **60**, and includes a light emitter and a photodetector opposed to each other. The sensor **80** outputs an OFF signal (first signal), when the lever **60** is in the first detection posture, in which the detection piece **66** of the lever **60** is located at the light-shielding position, in other words between the light emitter and the photodetector, as shown in FIG. **3**.

[0046] The sensor **80** outputs an ON signal (second signal), when the lever **60** is in the second detection posture, in which the detection piece **66** of the lever **60** is located at a light-transmitting position, in other words a position deviated from between the light emitter and the photodetector, as shown in FIG. **4** and FIG. **5**.

[0047] As described above, when the actuator **20** assumes the non-contact posture, and the branch guide **40** assumes the first guide posture, as shown in FIG. **3**, the sensor **80** outputs the OFF signal. In contrast, when the actuator **20** assumes the contacting posture as shown in FIG. **4**, or when the branch guide **40** assumes the second guide posture as shown in FIG. **5**, the sensor **80** outputs the ON signal.

[0048] Thus, according to this embodiment, when the sensor **80** is outputting the ON signal, it can be presumed that, in the image forming apparatus **1**, the sheet P is present on the first transport route **113**, or the branch guide **40** is in the second guide posture.

[0049] Here, in the case where the image forming apparatus **1** is normally operating before the image forming by the image forming device **13** (e.g., during a warm-up phase), the actuator **20** assumes the non-contact posture and the branch guide **40** assumes the first guide posture, and therefore the sensor **80** outputs the OFF signal (first signal). Accordingly, when the sensor **80** outputs the ON signal before the image forming by the image forming device **13**, which indicates that abnormality has occurred inside the image forming apparatus **1**, it is necessary to identify the reason that the sensor **80** is outputting the ON signal.

[0050] In this embodiment, therefore, the controller **10** executes an abnormality detection process, by operating according to the detection program, when the sensor **80** is outputting the ON signal before the image forming by the image forming device **13**. The abnormality detection process includes causing the branch guide **40** to shift from the second guide posture to the first guide posture, causing the display device **16** to display a notification screen indicating that the sheet P is located on the first transport route **113**, when the sensor **80** is still outputting the ON signal after the branch guide **40** has shifted the posture, and keeping from causing the display device **16** to display the notification screen, when the sensor **80** outputs the OFF signal after the branch guide **40** has shifted the posture.

Operation

[0051] FIG. **6** is a flowchart showing the abnormality detection process. Referring to FIG. **6**, the operation of the image forming apparatus **1** for executing the abnormality detection process will be described in detail.

[0052] Upon receipt of an image forming instruction from the user, through the operation device **17**, the controller **10** starts to execute the abnormality detection process specified in FIG. **6**. First,

the controller **10** decides whether the sensor **80** is outputting the OFF signal (step S10). When the sensor **80** is outputting the OFF signal (YES at step S10), the controller **10** finishes the abnormality detection process.

[0053] When the sensor **80** is outputting the ON signal (NO at step S10), the controller **10** instructs the fixing device **14** to reduce the fixing pressure. To be more specific, the controller **10** causes the fixing device **14** to reduce the pressing force of the pressing member against the fixing roller **142**, thereby reducing the fixing pressure (step S11). After step S11, the controller **10** causes the drive motor for driving the pressure roller **141** and the delivery roller **152** to rotate at full speed, with the heater of the fixing roller **142** turned off (step S12).

[0054] After step S12, the controller **10** starts counting the elapsed time after the start of the full-speed rotation, and repeatedly decides that a predetermined standby time (in this case, 350 msec) has not been reached, until the elapsed time reaches the predetermined standby time (NO at step S13).

[0055] When the elapsed time reaches the predetermined standby time (YES at step S13), the controller **10** stops the full-speed rotation, and operates the solenoid provided in the branch guide **40** in the reverse direction, for a period of time obtained by dividing the predetermined moving time (in this case, 120 msec) by a predetermined number of times (in this case, 3 times), in other words 40 msec (step S14).

[0056] Because of the operation of step S14, the branch guide **40** rotates clockwise about the rotation shaft **42**, over a prespecified distance (in this case, the distance obtained by dividing the distance corresponding to the travel from the second guide posture to the first guide posture, by the predetermined number of times). Accordingly, when the branch guide **40** assuming a posture close to the second guide posture is shifted to the first guide posture, the detection piece **66** of the lever **60** moves from the light-transmitting position to the light-shielding position, thereby causing the sensor **80** to output the OFF signal.

[0057] After step S14, the controller **10** decides whether the sensor **80** is outputting the OFF signal (step S15). When the sensor **80** is outputting the OFF signal (YES at step S15), the controller **10** finishes the abnormality detection process.

[0058] In contrast, when the sensor **80** is outputting the ON signal (NO at step S15), the controller **10** decides whether the number of operation times of the solenoid is equal to or less than the predetermined number of times (i.e., 3 times) (step S16). In this case, since the solenoid has been operated only once, the controller **10** decides that the number of operation times is less than the predetermined number of times (YES at step S16), and returns to step S14.

[0059] The controller **10** repeats the operation of step S14 to step S16, until the sensor **80** outputs the OFF signal, before the number of operation times of the solenoid reaches the predetermined number of times (YES at step S15), or until the number of operation times of the solenoid reaches the predetermined number of times (NO at step S16).

[0060] When the number of operation times of the solenoid reaches the predetermined number of times, the branch guide **40** moves to the position corresponding to the first guide posture, though the branch guide **40** was assuming the second guide posture, at the time that the abnormality detection process started.

[0061] When the number of operation times of the solenoid reaches the predetermined number of times (NO at step S16), while the sensor **80** is outputting the ON signal (NO at step S15), the controller **10** determines that the sensor **80** is outputting the ON signal not because of the posture of the branch guide **40**, but because of the actuator **20** assuming the contacting posture, and causes the display device **16** to display the notification screen indicating that the sheet P is present on the first transport route **113** (step S17). After step S17, the controller **10** finishes the abnormality detection process.

[0062] To implement the aforementioned known technique, a sensor for detecting the sheet jam, and also a sensor for detecting whether the branch guide plate is located at the home position, are

necessary. Since the image forming apparatus already includes many sensors to realize various functions, providing such additional sensors leads to an increase in manufacturing cost.

[0063] According to the foregoing embodiment, in contrast, the presence of the sheet P on the first transport route **113**, and the posture of the branch guide **40** can both be detected, with the single sensor **80**. Therefore, the number of sensors can be reduced, which leads to reduction in cost, compared with the case where the sensor for detecting the occurrence of sheet jam and the sensor for detecting the posture of the branch guide **40** are separately provided.

[0064] According to the embodiment, when the sensor **80** is outputting the ON signal, before the image forming by the image forming device **13**, the controller **10** causes the branch guide **40** to shift the posture from the second guide posture to the first guide posture. Then, when the sensor **80** is still outputting the ON signal after the posture has been changed, the controller **10** causes the display device **16** to display the notification screen indicating that the sheet P is present on the first transport route **113**.

[0065] Accordingly, it can be identified that it is because the sheet P is present on the first transport route **113**, that the sensor **80** is outputting the ON signal before the image forming operation, and also the user can be made aware of such situation. As result, the user can easily eliminate the cause of the abnormality, for example by opening the cover of the image forming apparatus **1** and removing the sheet P on the first transport route **113**. According to the embodiment, further, the controller **10** keeps from causing the display device **16** to display the notification screen, when the sensor **80** outputs the OFF signal, after the posture of the branch guide **40** is changed.

[0066] Therefore, the notification screen can be prevented from being displayed in vain, when the sheet P is not present on the first transport route **113**. In addition, in the case where the sensor outputs the ON signal before the image forming operation, because of the posture of the branch guide **40**, the branch guide **40** is shifted to the first guide posture. As result, the cause of the abnormality can be automatically eliminated.

Other Variations

[0067] The disclosure may be modified in various manners, without limitation to the foregoing embodiment and the variations thereof. For example, although the image forming device **13** is configured to form an image on the sheet P according to the foregoing embodiment, the disclosure is not limited to such embodiment. The image forming device **12** may form an image on a different recording medium. Such different recording medium can be exemplified by an overhead projector (OHP) sheet.

[0068] Although the image forming apparatus **1** according to the disclosure is exemplified by the tandem-type color printer in the embodiment, the image forming apparatus **1** may instead be an electrophotographic image forming apparatus, a color multifunction peripheral, a monochrome multifunction peripheral, a copier, or a facsimile machine.

[0069] Further, the configurations and processings described in the foregoing embodiments with reference to FIG. **1** to FIG. **6** are merely exemplary, and in no way intended to limit the disclosure to those configurations and processings.

[0070] While the present disclosure has been described in detail with reference to the embodiments thereof, it would be apparent to those skilled in the art the various changes and modifications may be made therein within the scope defined by the appended claims.

Claims

1. An image forming apparatus comprising: an image forming device that forms an image on a sheet; a fixing device that fixes the image onto the sheet; a first transport route extending from the fixing device to a delivery port; a second transport route branched from the first transport route, and extending toward the image forming device; a branch guide that assumes a first guide posture, to guide the sheet to the first transport route, and assumes a second guide posture, to guide the

sheet to the second transport route; a sheet contact member that assumes a non-contact posture, when not in contact with the sheet on the first transport route, and assumes a contacting posture, when in contact with the sheet on the first transport route; a detection object that assumes a first detection posture, when the branch guide assumes the first guide posture, assumes a second detection posture, when the branch guide assumes the second guide posture, assumes the first detection posture, when the sheet contact member assumes the non-contact posture, and assumes the second detection posture, when the sheet contact member assumes the contacting posture; and a sensor that outputs a first signal, when the detection object is in the first detection posture, and outputs a second signal, when the detection object is in the second detection posture.

2. The image forming apparatus according to claim 1, further comprising: a display device; and a control device including a processor, and configured to act, when the processor executes a computer program, as a controller that: causes the branch guide to shift from the second guide posture to the first guide posture, when the sensor is outputting the second signal, before an image forming operation by the image forming device; and causes the display device to display a notification screen indicating that the sheet is present on the first transport route, when the sensor is still outputting the second signal, after the branch guide has shifted the posture.

3. The image forming apparatus according to claim 2, wherein, when the sensor outputs the first signal, after the branch guide has shifted the posture, the controller keeps from causing the display device to display the notification screen.

4. The image forming apparatus according to claim 1, wherein the detection object includes a rotation shaft, a contact piece, and a detection piece, the contact piece and the detection piece projecting from the rotation shaft in a direction orthogonal to an axial direction of the rotation shaft, but in different directions from each other, the detection object assumes the first detection posture in which an end portion of the branch guide is not in contact with the contact piece, when the branch guide is assuming the first guide posture, assumes the second detection posture in which the end portion of the branch guide is in contact with the contact piece, when the branch guide is assuming the second guide posture, assumes the first detection posture in which an end portion of the sheet contact member is in contact with the contact piece, when the sheet contact member is assuming the non-contact posture, and assumes the second detection posture in which the end portion of the sheet contact member presses the contact piece, when the sheet contact member assumes the contacting posture, and the sensor outputs the first signal, when the detection object is in the first detection posture and the detection piece is located at a predetermined position, and outputs the second signal, when the detection object is in the second detection posture and the detection piece is deviated from the predetermined position.
