

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250287544

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

REN; Junheng et al.

POWER CONVERSION APPARATUS, PHOTOVOLTAIC SYSTEM, AND HEAT SINK

Abstract

A power conversion apparatus includes a heat sink and a power module. The heat sink includes a plurality of condensation teeth and an evaporator. The plurality of condensation teeth are spaced apart from each other in a thickness direction of the condensation tooth, and an airflow channel parallel to a second direction is provided between two adjacent condensation teeth. Each condensation tooth has a condensation channel and a solid region that extend in a first direction, and the condensation channel is located on a side of the solid region. The first direction, the second direction, and the thickness direction are perpendicular to each other. In the power conversion apparatus provided, the solid region has a good thermal conductivity, and heat of the evaporator can be effectively transferred to the condensation tooth through the solid region.

Inventors: REN; Junheng (Dongguan, CN), LI; Jiyang (Dongguan, CN), HONG; Fangjun (Shanghai, CN)

Applicant: Huawei Digital Power Technologies Co., Ltd. (Shenzhen, CN)

Family ID: 1000008528672

Assignee: Huawei Digital Power Technologies Co., Ltd. (Shenzhen, CN)

Appl. No.: 19/070699

Filed: March 05, 2025

Foreign Application Priority Data

CN

202410265892.1

Mar. 07, 2024

Publication Classification

Int. Cl.: H05K7/20 (20060101); H02J3/38 (20060101); H02M1/32 (20070101); H02M7/04 (20060101); H02M7/44 (20060101)

U.S. Cl.:

CPC **H05K7/20409** (20130101); **H02J3/381** (20130101); **H02M1/327** (20210501);
H02M7/04 (20130101); **H02M7/44** (20130101); H02J2300/24 (20200101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to Chinese Patent Application No. 202410265892.1, filed on Mar. 7, 2024, which is hereby incorporated by reference in its entirety.

TECHNICAL FIELD

[0002] The embodiments relate to the field of energy technologies, and to a power conversion apparatus, a photovoltaic system, and a heat sink.

BACKGROUND

[0003] With continuous development and wide application of green energy, importance of electric energy in people's daily life has become increasingly prominent. In a process of transmitting or using electric energy, a parameter like a voltage or a current of the electric energy needs to be converted or adjusted. For example, a photovoltaic power generation device may include a solar panel and an inverter. The solar panel can convert solar energy into a direct current, and the inverter can convert the direct current generated by the solar panel into an alternating current and then output the alternating current to the outside. During actual use, the inverter generates a large amount of heat. Therefore, heat needs to be dissipated for the inverter, to ensure operating performance and reliability of the inverter. Currently, air cooling is used to dissipate heat for the inverter. In simple terms, a heat sink may be disposed on an outer surface of the inverter, heat of the inverter can be conducted to the heat sink through heat transfer, and external airflow can take away the heat of the heat sink when flowing through a surface of the heat sink, to cool the inverter. However, as operating power of the inverter continuously increases, heat dissipation requirements of the inverter also significantly increase. Consequently, simply using the air cooling heat sink to dissipate heat for the inverter cannot satisfy a heat dissipation requirement of the inverter. Therefore, how to improve heat dissipation performance of the heat sink becomes an urgent problem to be resolved.

SUMMARY

[0004] The embodiments provide a power conversion apparatus, a photovoltaic system, and a heat sink that have good heat dissipation performance.

[0005] According to a first aspect, the embodiments provide a power conversion apparatus, including a heat sink and a power module. The heat sink includes a plurality of condensation teeth and an evaporator, and each condensation tooth extends in a first direction. The plurality of condensation teeth are spaced apart from each other in a thickness direction of the condensation tooth, and an airflow channel in a second direction is provided between two adjacent condensation teeth. The first direction, the second direction, and the thickness direction are all perpendicular to each other. Each condensation tooth has a condensation channel and a solid region. Both the condensation channel and the solid region extend in the first direction, and condensation channels are located on a same side of the solid region in the second direction. The evaporator has an evaporation cavity, and each condensation channel communicates with the evaporation cavity. The evaporator has a first surface and a second surface that are opposite to each other, and both the first surface and the second surface are perpendicular to the first direction. An end of each condensation tooth in the first direction is connected to the first surface, the power module is attached to the second surface, and a projection of the power module in the first direction overlaps the solid region.

[0006] In the power conversion apparatus provided in the embodiments, the evaporation cavity accommodates the cooling working medium, and heat generated by the power module can be conducted to the evaporator in a heat transfer manner. The cooling working medium in the evaporation cavity flows into the condensation channel after being heated and gasified, so that the power module can be effectively cooled. In addition, during actual application, the airflow channel may be parallel to a gravity direction (the second direction). According to a principle that hot air rises, a flow speed of air in the airflow channel is increased, and heat dissipation efficiency of the heat sink is improved. The condensation tooth further includes the solid region, and the solid region has a good thermal conductivity. Therefore, heat of the evaporator can be further effectively transferred to the condensation tooth through the solid region. In addition, the projection of the power module in the first direction overlaps the solid region, so that heat generated by the power module can be transferred to the solid region through a short heat conduction path. This improves heat transfer efficiency of the heat sink. In addition, the condensation channel is located on a side of the solid region in the second direction. Therefore, during actual use, when the condensation channel is located on an upper side of the solid region, consumption of the cooling working medium can be effectively reduced, and a problem of insufficiency of the cooling working medium can be avoided.

[0007] In an example, in a cross section perpendicular to an extension direction (such as the first direction) of the condensation channel, a ratio of a size of the condensation channel in the second direction (for example, the gravity direction) to a size of the condensation channel in the thickness direction (for example, a horizontal direction) is greater than or equal to 3. In this way, the cooling working medium can better implement condensation and backflow in the condensation channel, and has better cooling performance.

[0008] In an example, the solid region further has a cavity, and the cavity may be a closed cavity or an open cavity. When the cavity is an open cavity, the cavity may communicate with the evaporation cavity. Alternatively, it may be understood that, during specific disposing, the solid region may include only a solid material, or may include a cavity structure. After a flow channel communicates with the evaporation cavity, the cavity can store and release the cooling working medium, to avoid the problem of the insufficiency of the cooling working medium in the heat sink.

[0009] In an example, the condensation tooth further has a liquid collection cavity, and the liquid collection cavity communicates with the evaporation cavity. The liquid collection cavity is located on a side that is of the solid region and that is away from the condensation channel. For example, during actual use, the liquid collection cavity may be located on a lower side of the solid region, so that the liquid collection cavity can store and release the cooling working medium, to avoid the problem of the insufficiency of the cooling working medium in the heat sink.

[0010] In an example, the evaporator includes a first side wall and a second side wall. The first side wall and the second side wall are disposed opposite to each other in the first direction, and the evaporation cavity is located between the first side wall and the second side wall. An end of the condensation tooth is connected to the first side wall, and the power module may be attached to a surface of the second side wall. The evaporation cavity includes a thermally conductive rib, one end of the thermally conductive rib is connected to the first side wall, and the other end is connected to the second side wall. Heat of the second side wall may be effectively transferred to the first side wall through the thermally conductive rib, so that heat transfer efficiency and temperature uniformity of the evaporator can be effectively improved. In addition, the thermally conductive rib is connected between the first side wall and the second side wall, so that structural strength of the evaporator can be further effectively improved.

[0011] In an example, a flow channel is formed between two adjacent thermally conductive ribs, and the two adjacent flow channels communicate with each other, so that flow efficiency of the cooling working medium in the evaporation cavity can be ensured.

[0012] During specific disposing, the thermally conductive rib is in a long strip shape and extends

in the second direction. Alternatively, the thermally conductive rib is a protrusion, and a plurality of protrusions are spaced apart from each other in the evaporation cavity.

[0013] In an example, the heat sink further includes a heat dissipation fin, and the heat dissipation fin is located in the airflow channel and is connected to an outer surface of the condensation fin. Heat in the condensation fin can be conducted to the heat dissipation fin for dissipation, and the heat dissipation fin has a large heat exchange area. This can improve heat dissipation performance of the heat sink.

[0014] In an example, the heat sink further includes a confluence plate, the confluence plate is disposed opposite to the evaporator, and the plurality of condensation teeth are connected between the evaporator and the confluence plate. The confluence plate has a condensation confluence cavity, and the condensation channel communicates with the condensation confluence cavity. The cooling working medium condensed in the condensation channel may flow to the condensation confluence cavity, so that backflow efficiency of the liquid cooling working medium can be improved.

[0015] In an example, the power conversion apparatus includes a plurality of heat sinks, and the plurality of heat sinks are stacked in the second direction, or are stacked in the first direction. Alternatively, when the power conversion apparatus includes more than three heat sinks, the heat sinks may be disposed in the second direction, or may be disposed in the first direction.

[0016] In an example, the plurality of heat sinks include a first heat sink and a second heat sink, and the first heat sink and the second heat sink are stacked in the second direction. For example, during actual use, the first heat sink may be located on an upper side of the second heat sink. A projection of an airflow channel of the first heat sink in the second direction (for example, the gravity direction) is greater than a projection of an airflow channel of the second heat sink in the gravity direction. That is, air flowing through the airflow channel of the first heat sink may be divided into two parts. A part of air flows through the airflow channel of the second heat sink and then flows through the airflow channel of the first heat sink. The other part of air directly flows from the outside through the airflow channel of the first heat sink.

[0017] In an example, the plurality of heat sinks include a first heat sink and a second heat sink, and the first heat sink and the second heat sink are stacked in the second direction. For example, during actual use, the first heat sink may be located on an upper side of the second heat sink. The first heat sink further includes first heat dissipation fins, and the first heat dissipation fin is located in the airflow channel of the first heat sink. The second heat sink further includes second heat dissipation fins, and the second heat dissipation fin is located in the airflow channel of the second heat sink. A layout density of the first heat dissipation fins is greater than a layout density of the second heat dissipation fins. After the layout density of the second heat dissipation fins is small, resistance of air flowing through the second heat dissipation fin can be decreased, so that air still has a high circulation speed when flowing through the first heat dissipation fin. In addition, after the arrangement density of the first heat dissipation fins is large, a heat exchange area between the first heat dissipation fin and air can be increased, and heat dissipation efficiency of the first heat sink can be ensured. In addition, temperature uniformity between the first heat sink and the second heat sink can be further ensured.

[0018] In an example, the evaporator has a first positioning protrusion or a first positioning groove, the condensation tooth has a second positioning groove or a second positioning protrusion, and the first positioning protrusion is inserted into the second positioning groove, or the second positioning protrusion is inserted into the first positioning groove. Precision and reliability of a connection between the condensate tooth and the evaporator can be improved through positioning cooperation between the first positioning protrusion and the second positioning groove or positioning cooperation between the first positioning groove and the second positioning protrusion.

[0019] In an example, the power conversion apparatus is a rectifier or an inverter.

[0020] According to a second aspect, the embodiments further provide a photovoltaic system. The photovoltaic system may include a photovoltaic power generation device and the foregoing power

conversion apparatus. The power conversion apparatus is connected to the photovoltaic power generation device, and is configured to convert a direct current generated by the photovoltaic power generation device into an alternating current. The foregoing power conversion apparatus can be configured to effectively cool a power module, and an adverse situation like performance deterioration caused by an excessively high temperature of the power module can be prevented. In this way, working performance and safety of the photovoltaic system are ensured.

[0021] According to a third aspect, the embodiments further provide a heat sink, including a plurality of condensation teeth and an evaporator. The plurality of condensation teeth are spaced apart from each other in a thickness direction of the condensation tooth, and an airflow channel in a second direction is provided between two adjacent condensation teeth. The first direction, the second direction, and the thickness direction are all perpendicular to each other. Each condensation tooth has a condensation channel and a solid region. Both the condensation channel and the solid region extend in the first direction, and condensation channels are located on a same side of the solid region in the second direction. The evaporator has an evaporation cavity, and each condensation channel communicates with the evaporation cavity. The evaporator has a first surface and a second surface that are opposite to each other, and both the first surface and the second surface are perpendicular to the first direction. An end of each condensation tooth in the first direction is connected to the first surface.

[0022] In the heat sink provided in the embodiments, the evaporation cavity accommodates a cooling working medium, and heat generated by the power module can be conducted to the evaporator in a heat transfer manner. The cooling working medium in the evaporation cavity flows into the condensation channel after being heated and gasified, so that the heat sink can be effectively cooled. In addition, during actual application, the airflow channel may be parallel to a gravity direction (the second direction). According to a principle that hot air rises, a flow speed of air in the airflow channel is increased, and heat dissipation efficiency of the heat sink is improved. The condensation tooth further includes the solid region, and the solid region has a good thermal conductivity. Therefore, heat of the evaporator can be further effectively transferred to the condensation tooth through the solid region. In addition, the condensation channel is located on a side of the solid region in the second direction. Therefore, during actual use, when the condensation channel is located on an upper side of the solid region, consumption of the cooling working medium can be effectively reduced, and a problem of insufficiency of the cooling working medium can be avoided.

[0023] In an example, in a cross section perpendicular to an extension direction (such as the first direction) of the condensation channel, a ratio of a size of the condensation channel in the second direction (for example, the gravity direction) to a size of the condensation channel in the thickness direction (for example, a horizontal direction) is greater than or equal to 3. In this way, the cooling working medium can better implement condensation and backflow in the condensation channel, and has better cooling performance.

[0024] In an example, the solid region further has a cavity, and the cavity may be a closed cavity or an open cavity. When the cavity is an open cavity, the cavity may communicate with the evaporation cavity. Alternatively, it may be understood that, during specific disposing, the solid region may include only a solid material, or may include a cavity structure. After a flow channel communicates with the evaporation cavity, the cavity can store and release the cooling working medium, to avoid the problem of the insufficiency of the cooling working medium in the heat sink.

[0025] In an example, the condensation tooth further has a liquid collection cavity, and the liquid collection cavity communicates with the evaporation cavity. The liquid collection cavity is located on a side that is of the solid region and that is away from the condensation channel. For example, during actual use, the liquid collection cavity may be located on a lower side of the solid region, so that the liquid collection cavity can store and release the cooling working medium, to avoid the problem of the insufficiency of the cooling working medium in the heat sink.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0026] FIG. 1 is a simple diagram of a structure of a conventional photovoltaic power generation device according to an embodiment;

[0027] FIG. 2 is a diagram of a three-dimensional structure of a power conversion apparatus according to an embodiment;

[0028] FIG. 3 is a diagram of a cross-sectional structure along A-A in FIG. 2;

[0029] FIG. 4 is a diagram of a cross-sectional structure of a power conversion apparatus according to an embodiment;

[0030] FIG. 5 is a diagram of another cross-sectional structure of a power conversion apparatus according to an embodiment;

[0031] FIG. 6 is a diagram of another cross-sectional structure of a power conversion apparatus according to an embodiment;

[0032] FIG. 7 is a diagram of another cross-sectional structure of a power conversion apparatus according to an embodiment;

[0033] FIG. 8 is a diagram of a three-dimensional structure of an evaporator according to an embodiment;

[0034] FIG. 9 is a diagram of a cross-sectional structure along B-B in FIG. 8;

[0035] FIG. 10 is a diagram of another three-dimensional structure of an evaporator according to an embodiment;

[0036] FIG. 11 is a diagram of another three-dimensional structure of an evaporator according to an embodiment;

[0037] FIG. 12 is a diagram of a three-dimensional structure of a power conversion apparatus according to an embodiment;

[0038] FIG. 13 is a diagram of a cross-sectional structure along C-C in FIG. 12;

[0039] FIG. 14 is a diagram of a three-dimensional structure of a power conversion apparatus according to an embodiment;

[0040] FIG. 15 is a diagram of an exploded structure of a heat sink according to an embodiment;

[0041] FIG. 16 is a diagram of another exploded structure of a heat sink according to an embodiment;

[0042] FIG. 17 is a diagram of a side structure of a power conversion apparatus according to an embodiment;

[0043] FIG. 18 is a diagram of another side structure of a power conversion apparatus according to an embodiment;

[0044] FIG. 19 is a diagram of another three-dimensional structure of a power conversion apparatus according to an embodiment;

[0045] FIG. 20 is a diagram of another three-dimensional structure of a power conversion apparatus according to an embodiment;

[0046] FIG. 21 is a diagram of another three-dimensional structure of a power conversion apparatus according to an embodiment;

[0047] FIG. 22 is a diagram of another three-dimensional structure of a power conversion apparatus according to an embodiment;

[0048] FIG. 23 is a diagram of another cross-sectional structure of a power conversion apparatus according to an embodiment; and

[0049] FIG. 24 is a block diagram of a structure of a photovoltaic system according to an embodiment.

DETAILED DESCRIPTION OF EMBODIMENTS

[0050] To make the objectives, solutions, and advantages clearer, the following further describes

the embodiments in detail with reference to the accompanying drawings.

[0051] For ease of understanding a heat sink provided in the embodiments, the following first describes an application scenario of the heat sink.

[0052] The heat sink provided in embodiments may be applied to a plurality of scenarios in which there is a heat dissipation requirement. For example, the heat sink may be used in a power conversion apparatus, in other words, the power conversion apparatus may include the heat sink and a power module. The heat sink may be configured to cool the power module, so that the power module is in a normal temperature range, to ensure working performance and safety of the power module.

[0053] For example, as shown in FIG. 1, a photovoltaic power generation device may include a power conversion apparatus **01**. The power conversion apparatus **01** can convert a direct current generated by a solar panel into an alternating current and then output the alternating current to the outside. During actual use, the power conversion apparatus **01** may include a power module **011** and a heat sink **02**. The power module **011** includes power components such as a circuit board **010** and a power transistor **012**. The power transistor **012** is electrically connected to a conductive line in the circuit board **010**. During actual application, the power module **011** generates a large amount of heat. Therefore, heat needs to be dissipated for the power module **011**, to ensure operating performance and reliability of the power module **011**. Currently, air cooling is used to dissipate heat for the power module **011**. In simple terms, the heat sink **02** can be disposed at a position, on the power module **011**, corresponding to the power transistor **012**. The heat sink **02** may include heat dissipation fins **021**. An airflow can quickly take away heat of the heat dissipation fins **021** when flowing through gaps between the heat dissipation fins **021**, to cool the power module **011**. In summary, heat generated by the power module **011** can be transferred to the heat dissipation fins **021** of the heat sink **02** through heat conduction, and an airflow flowing through the heat dissipation fins **021** can quickly take away heat of the heat sink **02**, to cool the power module **011**.

[0054] However, as operating power of the power module **011** continuously increases, heat dissipation requirements of the power module **011** also significantly increase. Consequently, simply using the air cooling heat sink **02** to dissipate heat for the power module **011** cannot satisfy a heat dissipation requirement of the power module **011**.

[0055] Therefore, embodiments provide a heat sink with good heat dissipation performance and a power conversion apparatus equipped with the heat sink.

[0056] To make the objectives, solutions, and advantages of the embodiments clearer, the following further describes the embodiments in detail with reference to the accompanying drawings and specific embodiments.

[0057] As shown in FIG. 2 and FIG. 3, in an example provided in the embodiments, a power conversion apparatus **20** includes a heat sink **10** and a power module **21**. It should be noted that the power module **21** may be a chip, a component, a package body, or the like that is in the power conversion apparatus **20** and that is configured to implement power conversion. Alternatively, the power module **21** is a heat source that needs to be cooled in the power conversion apparatus **20**. A specific structural form and type of the power module **21** are not limited. In addition, the heat sink **10** includes a plurality of condensation teeth **12** (six condensation teeth are shown in the figure) and an evaporator **11**. The plurality of condensation teeth **12** are parallel to each other and are spaced apart from each other in a thickness direction of the condensation tooth **12**, and an airflow channel **100** parallel to a second direction is formed between two adjacent condensation teeth **12**. For example, when the second direction is consistent with a gravity direction, both the top and the bottom of the airflow channel **100** communicate with the outside; and external air may enter the airflow channel **100** from the bottom of the airflow channel **100**, and be discharged from the top of the airflow channel **100**. As shown in FIG. 3, each condensation tooth **12** has a condensation channel **120** and a solid region **121**. Both the condensation channel **120** and the solid region **121** extend in a first direction, and the condensation channel **120** is located on a side of the solid region

121. The evaporator **11** has an evaporation cavity **110**, and each condensation channel **120** communicates with the evaporation cavity **110**. An outer surface of the evaporator **11** includes a first surface **1001** and a second surface **1002** that are opposite to each other, and both the first surface **1001** and the second surface **1002** are perpendicular to the first direction. An end of each condensation tooth **12** in the first direction is connected to the first surface **1001**, the power module **21** is attached to the second surface **1002**, and a projection of the power module **21** in the first direction overlaps the solid region **121**.

[0058] For example, the evaporation cavity **110** accommodates a cooling working medium. The cooling working medium may be a medium, for example, Freon, that can generate gas-liquid two-phase conversion. A specific type of the cooling working medium is not limited. Heat generated by the power module **21** can be conducted to the evaporator **11**. The cooling working medium in the evaporation cavity **110** flows to the condensation channel **120** after being heated and gasified. The gasified cooling working medium is cooled and liquefied when flowing in the condensation channel **120**, and may flow back to the evaporation cavity **110**, so that the cooling working medium circulates in the evaporation cavity **110** and the condensation channel **120**, and the power module **21** can be effectively cooled. In addition, during actual use, the airflow channel **100** may be parallel to the gravity direction, in other words, the second direction is parallel to the gravity direction. Therefore, external air may enter the airflow channel **100** from the bottom of the airflow channel **100**, and be discharged from the top of the airflow channel **100**. When external air flows through the airflow channel **100**, the air is heated by the condensation tooth **12**, and a temperature of the air gradually increases. According to a principle that hot air rises, after the airflow channel **100** is parallel to the gravity direction, a flow speed of air in the airflow channel **100** is increased. This improves heat dissipation efficiency of the heat sink **10**.

[0059] In addition, as shown in FIG. 3, the condensation tooth **12** includes the condensation channel **120** and the solid region **121**. Heat of the evaporator **11** may be transferred to the condensation tooth **12** in two manners: gas-liquid conversion and heat transfer of the cooling working medium, so that heat transfer efficiency is good. For example, the liquid cooling working medium in the evaporation cavity **110** is gasified after being heated and enters the condensation channel **120**. When external air flows through the airflow channel **100**, a temperature of the condensation tooth **12** can be effectively reduced. Therefore, the gaseous cooling working medium can be cooled and liquefied in the condensation channel **120**. In other words, heat in the evaporator **11** may be transferred to the condensation tooth **12** through the cooling working medium. In addition, the condensation tooth **12** further includes the solid region **121**, and the solid region **121** has a good thermal conductivity. Therefore, heat of the evaporator **11** can be further effectively transferred to the condensation tooth **12** through the solid region **121**.

[0060] As shown in FIG. 3, in the example provided in the embodiments, the condensation channel **120** is located on the side of the solid region **121** in the second direction. For example, during actual use, after the second direction is parallel to the gravity direction, the condensation channel **120** may be located on an upper side of the solid region **121**. Therefore, consumption of the cooling working medium can be effectively reduced, and a problem of insufficiency of the cooling working medium can be avoided. Alternatively, it may be understood that the liquid cooling working medium flows downward under an action of gravity. In the example provided in the embodiments, the solid region **121** in the condensation tooth **12** is located on a lower side of the condensation channel **120**, and the solid region **121** significantly occupies internal space of the condensation tooth **12**. In this way, a larger amount of cooling working medium can enter the condensation channel **120** and the evaporation cavity **110**. Therefore, during actual application, a problem of insufficient cooling working medium in the condensation channel **120** and the evaporation cavity **110** can be avoided. In addition, when consumption of the cooling working medium is small, the problem of the insufficiency of the cooling working medium in the condensation channel **120** and the evaporation cavity **110** can also be effectively reduced or avoided.

[0061] Alternatively, it may be understood that, disposing of the solid region **121** can effectively increase a size of the condensation tooth **12**, so that a heat exchange area between the condensation tooth **12** and external air is increased, and heat dissipation efficiency of the heat sink **10** is improved.

[0062] It should be noted that, in the foregoing example, an example in which the solid region **121** includes only a thermally conductive material is used for description. For example, the solid region **121** may be a solid metal body made of copper, aluminum, or an alloy material. Alternatively, it may be understood that the entire condensation tooth **12** may be made of copper, aluminum, or an alloy material, so that the entire condensation tooth **12** has a good thermal conductivity and structural strength.

[0063] During specific disposing, the heat sink **10** may include two, three, or more condensation teeth **12**. For ease of understanding the solutions of the embodiments, the following uses an example in which the heat sink **10** includes six condensation teeth **12** for description.

[0064] When the condensation tooth **12** is disposed, a structural shape of the condensation tooth **12** may be diversified, and a quantity of condensation channels **120** and a shape of the condensation channel **120** may also be diversified.

[0065] For example, as shown in FIG. 4, in an example provided in the embodiments, the condensation tooth **12** is of a roughly rectangular plate structure. In the first direction, the condensation tooth **12** includes a first end (for example, a left end in FIG. 4) and a second end (for example, a right end in FIG. 4), and the first end is of a closed structure. The condensation tooth **12** includes three condensation channels **120** spaced apart from each other in the second direction, and the three condensation channels **120** all extend in the first direction. An end (for example, a right end in FIG. 4) of each condensation channel **120** extends to the second end, to facilitate communication with the evaporation cavity **110**.

[0066] It should be noted that, during specific disposing, the condensation tooth **12** may include one condensation channel **120**, or may include two or more condensation channels **120**. When the condensation tooth **12** includes three or more condensation channels **120**, a distance between two adjacent condensation channels **120** may be the same or may be different. This is not limited.

[0067] During specific disposing, a cross-sectional shape and a size of the condensation channel **120** may also be diversified.

[0068] For example, as shown in FIG. 5, in an example provided in the embodiments, a shape of a cross section perpendicular to an extension direction of the condensation channel **120** is a rectangle, and a ratio of a size H of the condensation channel **120** in the second direction to a size L of the condensation channel **120** in the thickness direction is greater than or equal to 3. In this way, the condensation tooth **12** has good cooling performance. For example, refer to FIG. 4. During actual use, the gaseous cooling working medium enters the condensation channel **120** from the second end (for example, the right end in FIG. 4), and flows toward the first end (for example, the left end in FIG. 4). In addition, in a circulation process, the gaseous cooling working medium is cooled and liquefied. Under an action of gravity, the liquid cooling working medium is deposited at the bottom of the condensation channel **120**, and flows back from the right end of the condensation channel **120** to the evaporation cavity **110**, to implement circulation of the cooling working medium.

[0069] In the example provided in the embodiments, the ratio of the height size H of the condensation channel **120** to the width size L of the condensation channel **120** is appropriately set, so that effective circulation space can be provided for the gaseous cooling working medium, and the gaseous cooling working medium can effectively flow in the condensation channel **120**. In addition, effective circulation space can be further provided for the liquid cooling working medium, so that the liquid cooling working medium can be effectively discharged from the condensation channel **120**. In this way, good cooling efficiency is achieved.

[0070] During specific disposing, the ratio of the size H of the condensation channel **120** in the

second direction to the size L of the condensation channel **120** in the thickness direction may be 3, 3.1, 3.5, 4, or the like. During actual application, the ratio may be appropriately set based on an actual requirement. Details are not described herein.

[0071] In addition, it should be noted that, in the foregoing example, an example in which the cross section of the condensation channel **120** is a rectangle is used for description. In another example, the cross section of the condensation channel **120** may alternatively be an ellipse, a polygon, or another irregular shape. During actual application, the specific shape and the size of the condensation channel **120** may be appropriately selected and set based on an actual requirement. For example, a hydraulic diameter of the condensation channel **120** may be greater than or equal to 2 mm, so that good condensation, backflow, and the like of the cooling working medium can be implemented in the condensation channel **120**. The hydraulic diameter is a ratio of four times an area to a circumference in the cross section of the condensation channel **120**. During specific disposing, parameters such as the size and the shape of the condensation channel **120** may be appropriately set based on an actual requirement. Details are not described herein.

[0072] When the condensation tooth **12** is manufactured, the condensation tooth **12** may be manufactured through a process like plate bending molding or welding, or may be manufactured in a manner for manufacturing a profile, for example, hot pressing molding, cold drawing molding, cold extrusion molding, or hot extrusion molding. A specific manufacturing process of the condensation tooth **12** is not limited.

[0073] In addition, during specific disposing, the solid region **121** may be of a solid structure, in other words, the solid region **121** includes only a solid material. In another example, the solid region **121** may alternatively be of a hollow structure.

[0074] For example, as shown in FIG. 6, in an example provided in the embodiments, the solid region **121** may further include a cavity **1211**, and an end (a right end in FIG. 6) of the cavity **1211** extends to the second end of the condensation tooth **12**. A weight and material consumption of the condensation tooth **12** can be effectively reduced by disposing the cavity **1211**. In addition, the cavity **1211** may further accommodate a cooling working medium. When a liquid level of the liquid cooling working medium in the evaporation cavity **110** is lower than that in the cavity **1211**, the cooling working medium in the cavity **1211** may be supplemented to the evaporation cavity **110**. In this way, a problem of insufficiency of the cooling liquid can be effectively reduced or avoided.

[0075] In the example provided in FIG. 6, an example in which the cavity **1211** is an open cavity is used for description. However, in another example, the cavity **1211** may alternatively be a closed cavity located inside the solid region **121**. Alternatively, when the cavity **1211** is an open cavity, the cavity **1211** may communicate with the outside, but not communicate with the evaporation cavity **110**.

[0076] During specific disposing, parameters such as a quantity of cavities **1211**, and a cross-sectional shape and a length of the cavity **1211** may be appropriately set based on an actual requirement. Details are not described herein.

[0077] In addition, as shown in FIG. 7, in another example provided in the embodiments, the condensation tooth **12** further has a liquid collection cavity **122**. The liquid collection cavity **122** is located on a side that is of the solid region **121** and that is away from the condensation channel **120**, and the liquid collection cavity **122** communicates with the evaporation cavity **110**. For example, during actual use, the liquid collection cavity **122** may be located on a lower side of the solid region **121**, and the condensation channel **120** is located on the upper side of the solid region **121**. The liquid collection cavity **122** may accommodate a cooling working medium. When the liquid level of the liquid cooling working medium in the evaporation cavity **110** is lower than that in the liquid collection cavity **122**, the cooling working medium in the liquid collection cavity **122** may be supplemented to the evaporation cavity **110**. In this way, the problem of the insufficiency of the cooling liquid can be effectively reduced or avoided.

[0078] In addition, a weight and material costs of the condensation tooth **12** can also be effectively

reduced by disposing the liquid collection cavity **122**. Alternatively, during actual application, when the liquid level of the liquid cooling working medium in the liquid collection cavity **122** is low, the gaseous cooling working medium may also flow to the liquid collection cavity **122**, and is condensed and liquefied in the liquid collection cavity **122**. This can effectively improve heat dissipation performance of the heat sink **10**.

[0079] During specific disposing, parameters such as a quantity of liquid collection cavities **122**, and a cross-sectional shape and a length of the liquid collection cavity **122** may be appropriately set based on an actual requirement. Details are not described herein.

[0080] When the evaporator **11** is disposed, a structure type of the evaporator **11** may also be diversified.

[0081] For example, as shown in FIG. **8**, in an example provided in the embodiments, an overall appearance of the evaporator **11** is a rectangular plate structure. The evaporator **11** includes a first side wall **111** and a second side wall **112**. The first side wall **111** and the second side wall **112** are disposed opposite to each other in a horizontal direction, and the evaporation cavity **110** is located between the first side wall **111** and the second side wall **112**. A first surface **1001** of the second side wall **112** may be attached to the power module, so that heat of the power module can be effectively transferred to the evaporator **11**. A second surface **1002** of the first side wall **111** is configured to connect to the condensation tooth **12**. The first side wall **111** has a plurality of through holes **1111** that penetrate into the evaporation cavity **110**. Refer to FIG. **7** and FIG. **8**. After a right end of the condensation tooth **12** is connected to the first side wall **111** of the evaporator **11**, the condensation channel **120** can communicate with the through hole **1111**, so that the condensation channel **120** communicates with the evaporation cavity **110**. During specific disposing, the condensation tooth **12** and the evaporator **11** may be fastened through welding, bonding, or the like, or may be fastened in another manner. This is not limited.

[0082] In addition, in some examples, a first positioning structure may alternatively be disposed on the first side wall **111**, and a second positioning structure may be disposed at the right end of the condensation tooth **12**, to increase positioning precision between the condensation tooth **12** and the evaporator **11**. For example, the first positioning structure may be a groove or a protrusion, and the second positioning structure may be a protrusion or a groove. Effective positioning between the condensation tooth **12** and the evaporator **11** may be implemented through insertion fitting between the groove and the protrusion. During specific disposing, specific structure types of the first positioning structure and the second positioning structure may be appropriately set based on an actual requirement. This is not limited.

[0083] It may be understood that, in another example, the entire evaporator **11** may alternatively be in a polyhedron like a cube, or may be in another irregular shape. During actual application, a structural shape of the evaporator **11** may be appropriately set and adjusted. Details are not described herein.

[0084] In addition, refer to FIG. **8** and FIG. **9**. In the example provided in the embodiments, the evaporation cavity **110** further includes a thermally conductive rib **113**. One side of the thermally conductive rib **113** is connected to the first side wall **111**, and the other side is connected to the second side wall **112**. Heat transfer between the first side wall **111** and the second side wall **112** can be implemented through the thermally conductive rib **113**, so that heat of the second side wall **112** can be efficiently transferred to the first side wall **111**, and dissipated through the first side wall **111**. In addition, the thermally conductive rib **113** is provided, so that heat of the second side wall **112** can be conducted to the first side wall **111** in a heat transfer manner, to effectively improve heat dissipation efficiency of the second side wall **112** and temperature uniformity of the evaporator **11**. The condensation tooth **12** is located on the first side wall **111**, and heat of the first side wall **111** can be effectively conducted to the condensation tooth **12** in a heat transfer manner. The condensation tooth **12** can provide a large heat dissipation area. Therefore, heat dissipation performance of the heat sink **10** can be effectively improved.

[0085] When the thermally conductive rib **113** is disposed, shapes, a specified quantity, and a position layout of thermally conductive ribs **113** may be diversified.

[0086] For example, as shown in FIG. **9**, in an example provided in the embodiments, the heat sink **10** includes five thermally conductive ribs **113**, and each thermally conductive rib **113** is in a straight strip shape extending in the second direction. In addition, the plurality of thermally conductive ribs **113** are sequentially spaced apart from each other. The thermally conductive rib **113** is disposed, so that structural strength and the temperature uniformity of the evaporator **11** can be effectively improved.

[0087] For example, the thermally conductive rib **113** is connected between the first side wall **111** and the second side wall **112**, and can effectively connect and support the first side wall **111** and the second side wall **112**. When the first side wall **111** or the second side wall **112** of the evaporator **11** is subject to an external squeezing force, the thermally conductive rib **113** can effectively resist the external squeezing force, to improve pressure resistance performance of the evaporator **11**. In addition, the thermally conductive rib **113** is fastened to the first side wall **111** and the second side wall **112**. When pressure in the evaporation cavity **110** is large, the thermally conductive rib **113** can effectively connect the first side wall **111** and the second side wall **112**, to prevent the first side wall **111** and the second side wall **112** from an adverse situation like protrusion, to effectively improve explosion-proof performance of the evaporator **11**.

[0088] It may be understood that, during specific disposing, a connection between the thermally conductive rib **113** and the first side wall **111** or the second side wall **112** may alternatively be disposed in a non-fastening manner.

[0089] For example, the thermally conductive rib **113** may be fastened to the first side wall **111** and abut against the second side wall **112**. Alternatively, the thermally conductive rib **113** may be fastened to the second side wall **112** and abut against the first side wall **111**. Alternatively, the thermally conductive rib **113** may abut against both the first side wall **111** and the second side wall **112**. The thermally conductive rib **113** may be effectively fastened in the evaporation cavity **110** by using a squeezing force between the first side wall **111** and the second side wall **112**, so that an adverse situation like position deviation of the thermally conductive rib **113** is avoided.

[0090] In addition, heat of the second side wall **112** can be effectively transferred to the first side wall **111** through the thermally conductive rib **113**, so that a temperature difference between the second side wall **112** and the first side wall **111** can be effectively reduced. In this way, temperature uniformity of the evaporator **11** in the horizontal direction can be improved. In addition, the heat may be further transferred in a length direction of the thermally conductive rib **113**. Therefore, heat of a local hot spot can be effectively diffused, and the temperature uniformity of the evaporator **11** can be further improved.

[0091] During manufacturing, the thermally conductive rib **113** may be a mechanical member that is independently manufactured and formed, and then the thermally conductive rib **113** is fastened in the evaporation cavity **110**. Alternatively, the thermally conductive rib **113** and the first side wall **111** or the thermally conductive rib **113** and the second side wall **112** may be an integrally formed mechanical member. A manufacturing manner of the evaporator **11** is not limited.

[0092] In addition, as shown in FIG. **9**, in the example provided in the embodiments, in the length direction of the thermally conductive rib **113**, neither of two ends of the thermally conductive rib **113** extends to an inner wall of the evaporation cavity **110**, so that the thermally conductive rib **113** can be prevented from significantly blocking normal flow of the cooling working medium. For example, the thermally conductive rib **113** can divide the evaporation cavity **110** to some extent, and a flow channel structure can be formed between two adjacent thermally conductive ribs **113**. Because neither of the two ends of the thermally conductive rib **113** extends to the inner wall of the evaporation cavity **110**, flow channel structures on two sides of the thermally conductive rib **113** communicate with each other. That is, the cooling working medium located on two sides of the thermally conductive rib **113** can effectively flow from the two ends of the thermally conductive rib

113, to effectively ensure effective flow of the cooling working medium in the entire evaporation cavity **110**. For example, the gaseous cooling working medium may effectively flow in space between the top of the thermally conductive rib **113** and the inner wall of the evaporation cavity **110**, and the liquid cooling working medium can implement effective circulation in space between the bottom of the thermally conductive rib **113** and the inner wall of the evaporation cavity **110**. [0093] In another example, two ends of the thermally conductive rib **113** may alternatively extend to an inner wall of the evaporation cavity **110**, and a structure like a notch may be disposed in a middle part of the thermally conductive rib **113** or at another position, so that the cooling working medium located on two sides of the thermally conductive rib **113** can flow through the notch, to ensure effective circulation of the cooling working medium.

[0094] In addition, in another example, the thermally conductive rib **113** may alternatively be of a long strip structure like a curve shape or a fold line shape. During actual application, a shape of the thermally conductive rib **113** may be flexibly set and adjusted based on an actual requirement.

[0095] As shown in FIG. 9, in the example provided in the embodiments, a region in which the evaporator **11** is attached to the power module **21** may be defined as a thermally conductive region **1121**. During specific disposing, a vertical projection of the thermally conductive rib **113** on the second side wall **112** may be located in the thermally conductive region **1121**, so that heat of the thermally conductive region **1121** can be effectively transferred to the first side wall **111** through the thermally conductive rib **113**.

[0096] In addition, as shown in FIG. 7, in the example provided in the embodiments, in the first direction, a projection of the solid region **121** of the condensation tooth **12** on the evaporator **11** overlaps the thermally conductive region **1121**. Alternatively, it may be understood that the projection of the power module **21** in the first direction overlaps the solid region **121**. The thermally conductive region **1121**, the thermally conductive rib **113**, and the solid region **121** can form a short heat transfer path. Heat of the thermally conductive region **1121** can be transferred to the second side wall **112** through the thermally conductive rib **113**, and heat of the second side wall **112** can be effectively transferred to the condensation tooth **12** through the solid region **121**, so that heat transfer efficiency is high. This can effectively improve heat dissipation efficiency of the heat sink **10**.

[0097] In the foregoing example, an example in which the thermally conductive rib **113** is in a long strip shape is used for description. In another example, the thermally conductive rib **113** may alternatively be in a block shape.

[0098] For example, as shown in FIG. 10, in the example provided in the embodiments, the evaporator **11** includes a plurality of protrusions **114**, shapes and sizes of the protrusions **114** are substantially the same, and the plurality of protrusions **114** are evenly arranged in an array.

[0099] Alternatively, as shown in FIG. 11, in another example provided in the embodiments, a layout density of the protrusions **114** in a region corresponding to the thermally conductive region **1121** is high, and a layout density of the protrusions **114** in another region is low. In other words, heat of the thermally conductive region **1121** can be effectively transferred to the second side wall **112** through the densely arranged protrusions **114**. In this way, good heat transfer efficiency can be achieved.

[0100] In addition, the protrusion **144** can further enable the liquid cooling working medium to boil in the evaporation cavity **110**, so that gasification efficiency of the cooling working medium can be effectively improved, to improve heat dissipation performance of the heat sink **10**. In addition, in some embodiments, sandblasting, sintering, or the like may alternatively be used to perform coarsening, hole forming, or the like on the inner wall of the evaporation cavity **110**, to enable the liquid cooling working medium to boil in the evaporation cavity **110**. During specific disposing, the coarsening or hole processing may be performed on the entire inner wall of the evaporation cavity **110**. Alternatively, the coarsening or hole processing may be performed only in an orthographic projection region of the thermally conductive region **1121**. Alternatively, the coarsening or hole

processing may be performed on a surface of the protrusion **114**. Details are not described herein. [0101] It may be understood that, during actual application, a shape, a size, and location distribution of the protrusion **114** may be appropriately set based on an actual requirement. Details are not described herein.

[0102] In addition, as shown in FIG. **12** and FIG. **13**, in the example provided in the embodiments, the heat sink **10** further includes a confluence plate **13**, the confluence plate **13** is disposed opposite to the evaporator **11**, and the plurality of condensation teeth **12** are connected between the evaporator **11** and the confluence plate **13**. The confluence plate **13** has a condensation confluence cavity, and the condensation channel **120** communicates with the condensation confluence cavity.

[0103] In the example provided in the embodiments, a structure of the confluence plate **13** is substantially the same as that of the evaporator **11**. Thus, an overall appearance of the confluence plate **13** is a rectangular plate-shaped structure, the confluence plate **13** has the condensation confluence cavity **130**, and the condensation confluence cavity **130** communicates with each condensation channel **120**.

[0104] It should be noted that, in the foregoing example, when the heat sink **10** does not include the confluence plate **13**, the condensation channel **120** and the liquid collection cavity **122** in the condensation tooth **12** are in a structural form in which one end is closed and the other end is open.

[0105] After the heat sink **10** includes the confluence plate **13**, the condensation channel **120** in the condensation tooth **12** is in a structural form in which two ends are open, that is, one end of the condensation channel **120** communicates with the evaporation cavity **110**, and the other end communicates with the condensation confluence cavity **130**. One end of the liquid collection cavity **122** communicates with the evaporation cavity **110**, and the other end communicates with the condensation confluence cavity **130**.

[0106] During specific application, the specific structure of the confluence plate **13** may be disposed the same as or similar to that of the evaporator **11**. In addition, a connection manner between the confluence plate **13** and the condensation tooth **12** may also be appropriately set with reference to a connection manner between the evaporator **11** and the condensation tooth **12**. Details are not described herein.

[0107] In the example provided in the embodiments, the confluence plate **13** is disposed to communicate with the plurality of condensation channels **120**, so that the liquid cooling working medium condensed in the condensation channel **120** can be discharged into the condensation confluence cavity **130**. This can effectively prevent the liquid cooling working medium from accumulating in the condensation channel **120**. In this way, sufficient space can be provided for another cooling working medium.

[0108] In addition, the condensation confluence cavity **130** can accommodate a large amount of liquid cooling working medium, to help reduce a size of the evaporator **11**. Alternatively, it may be understood that, during actual application, to ensure the heat dissipation performance of the heat sink **10**, a large evaporation cavity **110** needs to be provided in the evaporator **11** to accommodate a sufficient amount of the cooling working medium, to avoid an adverse situation like dry burning. In an example provided in the embodiments, the condensation confluence cavity **130** is provided, so that effective accommodation space can be provided for the liquid cooling working medium, and the liquid cooling working medium can be effectively transferred to the evaporation cavity **110**. Therefore, an adverse situation like dry burning of the evaporator **11** can be effectively prevented, and the size of the evaporator **11** can be reduced.

[0109] It should be noted that, in the foregoing example, the evaporation cavity **110** of the evaporator **11** includes a structure like the thermally conductive rib **113** or the protrusion **114**. When the confluence plate **13** is disposed, the condensation confluence cavity **130** of the confluence plate **13** may also include a structure like a thermally conductive rib **113** or a protrusion **114**.

[0110] In addition, as shown in FIG. **14**, in an example provided in the embodiments, the heat sink

10 further includes a heat dissipation fin **14**. The heat dissipation fin **14** is located in the airflow channel **100**, and is connected to the outer surface of the condensation tooth **12**. The heat of the condensation tooth **12** may be effectively transferred to the heat dissipation fin **14** through heat conduction. The heat dissipation fin **14** has a large heat exchange area, and the air flowing through the airflow channel **100** can quickly take away heat of the heat dissipation fin **14**, to effectively improve condensation efficiency of the cooling working medium in the condensation channel **120**. [0111] During actual application, the heat dissipation fin **14** may be fastened between two adjacent condensation teeth **12**, so that overall integration and structural strength of an assembly of condensation teeth **12** can be effectively improved. During actual application, the assembly of the condensation teeth **12** may be assembled as a whole.

[0112] During specific disposition, a structure type of the heat dissipation fin **14** may be diversified.

[0113] For example, as shown in FIG. **14**, the heat dissipation fin **14** may be of a bent sheet structure. Also, in another example, the heat dissipation fin **14** may alternatively be of a flat sheet structure or the like. A specific structural shape of the heat dissipation fin **14** is not limited.

[0114] During actual application, the heat dissipation fin **14** may be independently manufactured and formed, and then fastened to the condensation tooth **12** through welding or the like.

[0115] Alternatively, the heat dissipation fin **14** and the condensation tooth **12** may be manufactured by using an integrated molding process.

[0116] During actual application, a specific structure type and a manufacturing manner of the heat dissipation fin **14** may be appropriately selected and adjusted. Details are not described herein.

[0117] In addition, during specific manufacturing, a structural composition of the entire heat sink **10** may also be diversified.

[0118] For example, as shown in FIG. **15**, in an example provided in the embodiments, the first side wall **111** and the second side wall **112** of the evaporator **11** are two mutually independent mechanical parts. A side that is of the second side wall **112** and that faces the first side wall **111** has a groove (not shown in the figure), and the first side wall **111** covers the groove of the second side wall **112** to form the evaporation cavity **110**. The first side wall **111** has a narrow and long through hole **1111**, to facilitate interconnection with the condensation channel in the condensation tooth **12**. The first side wall **131** and the second side wall **132** of the confluence plate **13** are two mutually independent mechanical parts. A side that is of the second side wall **132** and that faces the first side wall **131** has a groove, and the first side wall **131** covers the groove of the second side wall **132**, to form the condensation confluence cavity **130**. The first side wall **131** has a narrow and long through hole **1311**, to facilitate interconnection with the condensation channel in the condensation tooth **12**. In addition, a protrusion **1321** is formed in the groove of the second side wall **132**. Further, a protrusion (not shown in the figure) is also formed in the groove of the second side wall **112**.

[0119] During specific disposing, the first side wall **111** and the second side wall **112** may be fastened through welding or the like. Correspondingly, the first side wall **131** and the second side wall **132** may be fastened through welding or the like. This is not limited.

[0120] During specific disposing, the protrusion **1321** and the second side wall **132** may be of an integrated structure, or the protrusion **1321** and the second side wall **132** may be separately formed, and then the protrusion **1321** is fastened in the groove of the second side wall **132** through welding or the like.

[0121] Alternatively, in some examples, the protrusion may be replaced with a fin structure.

[0122] For example, as shown in FIG. **16**, in an example provided in the embodiments, the evaporator **11** includes a meshed fin structure **115**, and the confluence plate **13** includes a meshed fin structure **133**. The fin structure **115** may be fastened to the first side wall **111** or the second side wall **112** through welding or the like. Correspondingly, the fin structure **115** may be fastened to the first side wall **131** or the second side wall **132** through welding or the like.

[0123] Thus, during actual application, a specific structural form and a composition manner of the heat sink **10** may be appropriately set based on an actual requirement. Details are not described herein.

[0124] In addition, in the foregoing example, an example in which the power conversion apparatus **20** includes one heat sink **10** is used for description. However, in another example, the power conversion apparatus **20** includes two or more heat sinks **10**.

[0125] For example, as shown in FIG. **17**, in an example provided in the embodiments, the power conversion apparatus **20** includes two heat sinks: a first heat sink **10a** and a second heat sink **10b**. The first heat sink **10a** is configured to cool a power module **21a**, the second heat sink **10b** is configured to cool a power module **21b**. Structures of the first heat sink **10a** and the second heat sink **10b** are substantially the same as the structure of the heat sink **10** shown in FIG. **14**. Details are not described herein again. The first heat sink **10a** and the second heat sink **10b** are stacked in the second direction. For example, during actual use, the first heat sink **10a** may be located on an upper side of the second heat sink **10b**. External air may enter an airflow channel of the second heat sink **10b** from the bottom of the second heat sink **10b**, be discharged from the top of the second heat sink **10b** to an airflow channel of the first heat sink **10a**, and be discharged from the top of the first heat sink **10a**.

[0126] In addition, as shown in FIG. **17**, in the example provided in the embodiments, the airflow channel of the first heat sink **10a** includes first heat dissipation fins **14a**, the airflow channel of the second heat sink **10b** includes second heat dissipation fins **14b**, and a layout density of the first heat dissipation fins **14a** is greater than a layout density of the second heat dissipation fins **14b**. After the layout density of the second heat dissipation fins **14b** is small, resistance of air flowing through the second heat dissipation fin **14b** can be decreased, so that air still has a high circulation speed when flowing through the first heat dissipation fin **14a**. In addition, after the arrangement density of the first heat dissipation fins **14a** is large, a heat exchange area between the first heat dissipation fin **14a** and air can be increased, and heat dissipation efficiency of the first heat sink **10a** can be ensured. In addition, when air sequentially flows through the first heat sink **10a** and the second heat sink **10b**, a temperature gradually increases. Therefore, when the layout density of the first heat dissipation fins **14a** is greater than the layout density of the second heat dissipation fins **14b**, temperature uniformity between the first heat sink **10a** and the second heat sink **10b** can be further ensured.

[0127] In addition, as shown in FIG. **18**, in another example provided in the embodiments, a projection of the airflow channel of the first heat sink **10a** in the second direction is greater than a projection of the airflow channel of the second heat sink **10b** in the second direction. That is, air flowing through the airflow channel of the first heat sink **10a** may be divided into two parts. A part of air flows through the airflow channel of the second heat sink **10b** and then flows through the airflow channel of the first heat sink **10a**. The other part of air directly flows from the outside through the airflow channel of the first heat sink **10a**. This can effectively ensure heat dissipation performance of the first heat sink **10a**, and can ensure temperature uniformity between the first heat sink **10a** and the second heat sink **10b**.

[0128] In addition, in another example, the power conversion apparatus **20** may further include three or more heat sinks.

[0129] For example, as shown in FIG. **19**, in an example provided in the embodiments, the power conversion apparatus **20** includes three heat sinks: a heat sink **10a**, a heat sink **10b**, and a heat sink **10c**. The three heat sinks are arranged in the first direction. The heat sink **10a** is configured to cool a power module **21a**, the heat sink **10b** is configured to cool a power module **21b**, and the heat sink **10c** is configured to cool a power module **21c**. During specific disposing, the three heat sinks are independent of each other.

[0130] Alternatively, as shown in FIG. **20**, the three heat sinks may be integrated. In this embodiment, an evaporator **11a**, an evaporator **11b**, and an evaporator **11c** in the heat sink **10a**, the

heat sink **10b**, and the heat sink **10c** may be of an integrated structure, and a confluence plate **13a**, a confluence plate **13b**, and a confluence plate **13c** may be of an integrated structure. This can effectively improve integration. In addition, evaporation cavities in the three evaporators may be independent of each other, or may communicate with each other. Correspondingly, condensation confluence cavities in the three confluence plates may be independent of each other, or may communicate with each other.

[0131] Alternatively, as shown in FIG. **21** and FIG. **22**, in the example provided in the embodiments, the power conversion apparatus **20** includes six heat sinks: a heat sink **10a**, a heat sink **10b**, a heat sink **10c**, a heat sink **10d**, a heat sink **10e**, and a heat sink **10f**. The heat sink **10a** is configured to cool a power module **21a**, the heat sink **10b** is configured to cool a power module **21b**, the heat sink **10c** is configured to cool a power module **21c**, the heat sink **10d** is configured to cool a power module **21d**, the heat sink **10e** is configured to cool a power module **21e**, and the heat sink **10f** is configured to cool a power module **21f**.

[0132] During specific disposing, the six heat sinks may be independent of each other, or the six heat sinks may be integrated. Details are not described herein.

[0133] In addition, during specific application, the heat sinks may be independently used in a plurality of different types of electronic devices, to dissipate heat for the electronic devices. Alternatively, the heat sinks may be integrated into an electronic device for application.

[0134] For example, as shown in FIG. **23**, in the example provided in the embodiments, the heat sink **10** may be used in the power conversion apparatus **20**. The power conversion apparatus **20** may further include components such as an inductor **23** and the power module **21**. The power module **21** includes a circuit board **22** and a power component **211**. The power component **211** is disposed on a side of the circuit board **22** and is electrically connected to a conductive line in the circuit board **22**. Further, during actual application, the inductor **23** may alternatively be connected to a conductive line in the circuit board **22**, to implement a function like filtering. The power component **211** may include components configured to implement power conversion, for example, a power transistor and a power conversion circuit. Alternatively, the power conversion apparatus **20** may be a rectifier, an inverter, or the like.

[0135] In addition, during specific disposing, the power conversion apparatus **20** may further include a fan **24**. The fan **24** may be located on a lower side of the heat sink **10**, and is configured to generate an airflow that flows through the airflow channel of the heat sink **10**, to improve heat dissipation efficiency of the heat sink **10**.

[0136] During actual application, the power conversion apparatus **20** may be used in a plurality of scenarios in which electric energy needs to be adjusted and controlled.

[0137] For example, as shown in FIG. **24**, embodiments of the embodiments further provide a photovoltaic system. The photovoltaic system may include a power generation device and a power conversion apparatus. The power conversion apparatus may be connected to the power generation device, and is configured to effectively process electric energy generated by the power generation device, to output processed electric energy to the outside.

[0138] During actual application, the power generation device may be a solar panel. The solar panel may generate a direct current, and the power conversion apparatus may convert the direct current generated by the solar panel into an alternating current and then output the alternating current to the outside.

[0139] Additionally, in another example, the photovoltaic system may further include a battery, a battery management system, and the like. In addition, during actual application, the power conversion apparatus may be used in a plurality of scenarios in which electric energy needs to be adjusted and controlled. A specific application scenario of the power conversion apparatus is not limited.

[0140] In various embodiments, unless otherwise stated or there is a logic conflict, terms and/or descriptions in different embodiments are consistent and may be mutually referenced, and features

in different embodiments may be combined based on an internal logical relationship thereof, to form a new embodiment.

[0141] “A plurality of” refers to two or more than two. “And/or” describes an association relationship between associated objects and indicates that three relationships may exist. For example, A and/or B may indicate the following three cases: only A exists, both A and B exist, and only B exists, where A and B may be singular or plural.

[0142] It may be understood that numerical symbols involved in embodiments are differentiated merely for ease of description, but are not used to limit the scope of the embodiments. The sequence numbers of the foregoing processes do not mean execution sequences, and the execution sequences of the processes should be determined based on functions and internal logic of the processes.

Claims

1. A power conversion apparatus comprising: a heat sink, wherein the heat sink comprises a plurality of condensation teeth spaced apart from each other in a thickness direction of the plurality of condensation teeth, and each condensation tooth extends in a first direction, an airflow channel in a second direction is provided between two adjacent condensation teeth, the first direction, the second direction, and the thickness direction are all perpendicular to each other; each condensation tooth has a condensation channel and a solid region, both the condensation channel and the solid region extend in the first direction, the condensation channel is located on a side of the solid region in the second direction; and an evaporator comprising an evaporation cavity, a first surface and a second surface that are opposite to each other, both the first surface and the second surface are perpendicular to the first direction; each condensation channel communicates with the evaporation cavity, and an end of each condensation tooth in the first direction is connected to the first surface; a power module is attached to the second surface, wherein a projection of the power module in the first direction overlaps the solid region.
2. The power conversion apparatus according to claim 1, wherein, in a cross section perpendicular to the first direction, a ratio of a size of the condensation channel in the second direction to a size of the condensation channel in the thickness direction is greater than or equal to 3.
3. The power conversion apparatus according to claim 1, wherein the solid region further comprises a cavity and the cavity is a closed cavity or the cavity communicates with the evaporation cavity.
4. The power conversion apparatus according to claim 1, wherein each condensation tooth further comprises: a liquid collection cavity located on a side of the solid region that is away from the condensation channel and the liquid collection cavity communicates with the evaporation cavity.
5. The power conversion apparatus according to claim 4, wherein the evaporator further comprises: a first side wall and a second side wall, the first side wall and the second side wall are disposed opposite to each other in the first direction, the evaporation cavity is located between the first side wall and the second side wall, one end of each condensation tooth is connected to the first side wall, the power module is attached to a surface of the second side wall, the evaporation cavity comprises a thermally conductive rib, a first end of the thermally conductive rib is connected to the first side wall, and a second end of the thermally conductive rib is connected to the second side wall.
6. The power conversion apparatus according to claim 5, wherein a flow channel is formed between two adjacent thermally conductive ribs, and two adjacent flow channels communicate with each other.
7. The power conversion apparatus according to claim 6, wherein the thermally conductive rib is in a long strip shape and extends in the second direction; or the thermally conductive rib is a protrusion, and each protrusion of a plurality of protrusions is spaced from each other in the evaporation cavity.

- 8.** The power conversion apparatus according to claim 1, wherein the heat sink further comprises: a heat dissipation fin located in the airflow channel and connected to an outer surface of the condensation fin.
- 9.** The power conversion apparatus according to claim 1, wherein the heat sink further comprises: a confluence plate disposed opposite to the evaporator, the plurality of condensation teeth is connected between the evaporator and the confluence plate, the confluence plate has a condensation confluence cavity, and the condensation channel communicates with the condensation confluence cavity.
- 10.** The power conversion apparatus according to claim 1, further comprising: a plurality of heat sinks disposed in either the first direction or the second direction.
- 11.** The power conversion apparatus according to claim 10, wherein the plurality of heat sinks further comprises: a first heat sink and a second heat sink that are stacked in the second direction and a projection of an airflow channel of the first heat sink in the second direction is greater than a projection of an airflow channel of the second heat sink in the second direction.
- 12.** The power conversion apparatus according to claim 10, wherein the plurality of heat sinks further comprises: a first heat sink and a second heat sink that are stacked in the second direction; the first heat sink further comprises first heat dissipation fins, each first heat dissipation fin is located in the airflow channel of the first heat sink, the second heat sink further comprises second heat dissipation fins, each second heat dissipation fin is located in the airflow channel of the second heat sink, and a layout density of the first heat dissipation fins is greater than a layout density of the second heat dissipation fins.
- 13.** The power conversion apparatus according to claim 1, wherein the evaporator has a first positioning protrusion or a first positioning groove, each condensation tooth has a second positioning groove or a second positioning protrusion, and the first positioning protrusion is inserted into the second positioning groove, or the second positioning protrusion is inserted into the first positioning groove.
- 14.** The power conversion apparatus according to claim 1, wherein the power conversion apparatus is either a rectifier or an inverter.
- 15.** A heat sink comprising: a plurality of condensation teeth, wherein each condensation tooth of the plurality of condensation teeth extends in a first direction, the plurality of condensation teeth is spaced apart from each other in a thickness direction of the plurality of condensation teeth, an airflow channel in a second direction is provided between two adjacent condensation teeth, the first direction, the second direction, and the thickness direction are all perpendicular to each other, each condensation tooth has a condensation channel and a solid region, both the condensation channel and the solid region extend in the first direction, and the condensation channel is located on a side of the solid region in the second direction; an evaporator comprises: an evaporation cavity, wherein each condensation channel communicates with the evaporation cavity; a first surface and a second surface that are opposite to each other, wherein both the first surface and the second surface are perpendicular to the first direction and an end of each condensation tooth in the first direction is connected to the first surface.
- 16.** The heat sink according to claim 15, wherein, in a cross section perpendicular to the first direction, a ratio of a size of the condensation channel in the second direction to a size of the condensation channel in the thickness direction is greater than or equal to 3.
- 17.** The heat sink according to claim 15, wherein the solid region further comprises a cavity and the cavity is a closed cavity, or the cavity communicates with the evaporation cavity.
- 18.** The heat sink according to claim 15, wherein each condensation tooth further comprises: a liquid collection cavity located on a side of the solid region that is away from the condensation channel and the liquid collection cavity communicates with the evaporation cavity.
- 19.** The heat sink according to claim 1, further comprising: a heat dissipation fin located in the airflow channel and connected to an outer surface of the condensation fin.

20. The heat sink according to claim 15, further comprising: a confluence plate disposed opposite to the evaporator, wherein the plurality of condensation teeth is connected between the evaporator and the confluence plate, the confluence plate has a condensation confluence cavity, and the condensation channel communicates with the condensation confluence cavity.
