

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250287546

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Garcia; Cosme

DATA CENTER THERMAL MANAGEMENT USING AISLE CONTAINMENT THERMOGRAPHIC CURTAINS

Abstract

The technical solution provides thermal management of data centers using containment curtains with thermographic material layers configured to change color in response to temperature changes. The solutions can identify, using video data, a layer of thermographic material applied on a portion of a material of a curtain disposed adjacent to a cabinet housing a plurality of computing devices configured to process requests and generate heat. The solutions can detect that a color of a portion of a layer of thermographic material is indicative of a temperature of a flow of air impacted by the heat. The solutions can determine, using the color and the location input into one or more machine learning (ML) models trained on the plurality of colors of a plurality of thermographic materials on a plurality of curtains adjacent to cabinets housing computing devices, that a computing device of the plurality of computing devices generates the heat that impacts the flow of air toward the portion of the layer. The solutions can load balance the requests across the plurality of computing devices responsive to the determination.

Inventors: Garcia; Cosme (Alpharetta, GA)

Applicant: ADP, Inc. (Roseland, NJ)

Family ID: 1000008531319

Assignee: ADP, Inc. (Roseland, NJ)

Appl. No.: 19/075412

Filed: March 10, 2025

Related U.S. Application Data

us-provisional-application US 63563872 20240311

Publication Classification

Int. Cl.: H05K7/20 (20060101); **G01K11/12** (20210101); **G01K13/024** (20210101); **G06F1/20** (20060101)

U.S. Cl.:

CPC H05K7/20745 (20130101); **G01K11/12** (20130101); **G01K13/024** (20210101); **G06F1/206** (20130101); **H05K7/20136** (20130101); **H05K7/20209** (20130101);

Background/Summary

CROSS-REFERENCES TO RELATED APPLICATIONS [0001] This application claims the benefit of priority under 35 U.S.C. § 119 to U.S. Provisional Patent Application No. 63/563,872, filed Mar. 11, 2024, which is hereby incorporated by reference herein in its entirety.

TECHNICAL FIELD

[0002] The present disclosure relates generally to thermal management of data centers, and particularly to thermal management using airflow curtains with thermographic material layers including without limitation, systems and methods for data center thermal management using thermographic materials.

BACKGROUND

[0003] Data centers can include computing devices, including servers, storage systems and networking devices (e.g., routers and switches), that can be stacked in housing cabinets. These housing cabinets can be arranged in rows forming aisles. During operation, computing devices can generate heat, which unless dissipated, can adversely affect the performance and longevity of the computing devices.

SUMMARY

[0004] The technical solutions described herein provide thermal management of data centers using curtains with a thermographic material layer that can change color in response to temperature changes, facilitating identification of hot spots in the data centers. The curtains can be made with a transparent material, opaque material, or have any other level of translucency. As cabinets with computing devices can be arranged into aisles, distribution of heat generated by computing devices can impact the flow of air around the aisle, based on the device locations and heat generation as well as the aisle geometry. This can result in concentrated heated airflow (e.g., hotspots) formed in some locations within the aisle, which can cause some computing devices to be thermally impacted differently than others. While heat sensors and thermal imaging cameras can help identify the hotspots, such solutions can be complex and energy inefficient. The technical solutions of this disclosure overcome these challenges by providing airflow curtains formed from a thermographic material layer that can change color as the temperature of the curtain changes, thereby providing a continuous thermal distribution feedback. The technical solutions can utilize thermographic layers to monitor thermal distribution in and around the aisles to take corrective actions for improved thermal management, including using machine learning (ML) modeling to balance computing load across the computing devices, based on detected thermographic material hotspots.

[0005] An aspect of solutions can relate to a system. The system can include a plurality of cabinets. The system can include a plurality of computing devices housed within each cabinet of the plurality of cabinets to generate heat. The system can include one or more portions of transparent material to form a curtain adjacent to the plurality of cabinets to control a flow of air impacted by the heat. The system can include one or more layers of thermographic material applied on the one or more portions of transparent material to change a color of the one or more layers of the thermographic material responsive to a change in temperature caused by the flow of air.

[0006] An aspect of solutions can relate to a system. The system can include one or more processors coupled with memory and configured to identify, using one or more video frames captured by a camera, one or more layers of thermographic material. The one or more layers of thermographic material can be applied on one or more portions of a transparent material of a curtain. The curtain can be disposed adjacent to a plurality of cabinets housing a plurality of computing devices configured to process requests and generate heat. The one or more processors can be configured to detect that a color of a portion of a layer of the one or more layers of thermographic material is indicative of a temperature of a flow of air impacted by the heat. The one or more processors can be configured to determine, using the color and the location input into one or more machine learning (ML) models trained on the plurality of colors of a plurality of thermographic materials on a plurality of curtains adjacent cabinets housing computing devices, that a computing device of the plurality of computing devices generates the heat that impacts the flow of air toward the portion of the layer. The one or more processors can be configured to load balance requests across the plurality of computing devices responsive to the determination.

[0007] An aspect of solutions can relate to a non-transitory computer readable medium storing program instructions to cause at least one processor of a device to identify, using one or more video frames captured by a camera, one or more layers of thermographic material applied on one or more portions of a transparent material of a curtain. The curtain can be disposed adjacent to a plurality of cabinets housing a plurality of computing devices configured to process requests and generate heat. The instructions can cause the at least one processor to detect that a color of a portion of a layer of the one or more layers of thermographic material is indicative of a temperature of a flow of air impacted by the heat. The instructions can cause the at least one processor to determine, using the color and the location input into one or more machine learning (ML) models trained on the plurality of colors of a plurality of thermographic materials on a plurality of curtains adjacent cabinets housing computing devices, that a computing device of the plurality of computing devices generates the heat that impacts the flow of air toward the portion of the layer. The instructions can cause the at least one processor to load balance requests across the plurality of computing devices responsive to the determination.

[0008] An aspect of solutions can relate to a method. The method can include identifying, by one or more processors coupled with memory, using one or more video frames captured by a camera, one or more layers of thermographic material applied on one or more portions of a transparent material of a curtain. The curtain can be disposed adjacent to a plurality of cabinets housing a plurality of computing devices processing requests and generating heat. The method can include detecting, by the one or more processors, that a color of a portion of a layer of the one or more layers of thermographic material is indicative of a temperature of a flow of air impacted by the heat. The method can include determining, by the one or more processors, using the color and the location input into one or more machine learning (ML) models trained on the plurality of colors of a plurality of thermographic materials on a plurality of curtains adjacent cabinets housing computing devices, that a computing device of the plurality of computing devices generates the heat that impacts the flow of air toward the portion of the layer. The method can include load balancing, by the one or more processors, the requests across the plurality of computing devices responsive to the determination.

[0009] An aspect of solutions can relate to a method. The method can include one or more processors coupled with memory identifying a plurality of cabinets. The method can include the one or more processors identifying a plurality of computing devices housed within each cabinet of the plurality of cabinets to generate heat. The method can include detecting, by the one or more processors, one or more portions of transparent material to form a curtain adjacent to the plurality of cabinets to control a flow of air impacted by the heat. The method can include detecting, by the one or more processors, one or more layers of thermographic material applied on the one or more portions of transparent material to change a color of the one or more layers of the thermographic

material responsive to a change in temperature caused by the flow of air.

[0010] An aspect of solutions can relate to an apparatus. The apparatus can include a curtain that extends along at least a portion of an array of cabinets that house a plurality of computing devices in a data center. The curtain can include an opening to receive heat dissipated from the plurality of computing devices at the at least the portion of the array. The curtain can include a thermographic material configured to change color to indicate an amount of the heat dissipated by the plurality of computing devices located at the at least the portion of the array.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0011] Aspects of the present disclosure are described in the detailed description which follows, in reference to the noted plurality of drawings by way of non-limiting examples of exemplary embodiments of the present disclosure.

[0012] FIG. 1 is an illustrative example of a material strip having thermographic layers that can be used for temperature detection in a curtain of a data room aisle.

[0013] FIG. 2 illustrates another example of a material strip having thermographic layers arranged in various shapes, such as strips or a grid, to be used for temperature detection in a curtain of a data room aisle.

[0014] FIG. 3 illustrates an example of a data room having cabinets housing computing devices for processing data.

[0015] FIG. 4 illustrates an example of a data room having cabinets and curtains with thermographic layers.

[0016] FIG. 5 illustrates an example of a data room having hot and cold aisles separated by cabinets and curtains with thermographic layers showing hotspot locations.

[0017] FIG. 6 illustrates an example block diagram of a system for load balancing of computing devices using curtains with thermographic layers and machine learning.

[0018] FIG. 7 illustrates an example block diagram of a computing system that can be used for implementing the technical solutions of the present disclosure, including in computing devices or data processing systems.

[0019] FIG. 8 shows an example process flow of method for providing thermal management solutions using data room curtains with thermographic layers.

DETAILED DESCRIPTION

[0020] The technical solutions described herein provide systems and methods for thermal management of data centers using curtains having thermographic material that is configured to change color in response to temperature changes. Data rooms that include cabinets storing computing devices (e.g., servers processing network traffic requests) can experience elevated temperatures due to heat generated by the devices. Airflow generated by these devices can produce hotspots, which can include localized areas in which temperatures are higher than that of surrounding areas. These hotspots can be indicative of various issues in the data room, including faulty or overheated computing devices due to overuse, or particular manner of use.

[0021] However, pinpointing or otherwise identifying or locating the hotspots can be challenging. Containment curtains that can be used to control the airflow in the data room (e.g., to separate the air from hot and cold aisles) lack the ability to pinpoint the sources of heat within enclosed spaces. While thermal sensors can be deployed to help understand the heat distribution in the data room, such systems are complex, costly, and energy inefficient. The solutions presented in this disclosure address these challenges by providing airflow curtains made of transparent materials embedded with thermographic layers capable of real-time color-changing, thereby providing a constant and energy-efficient real-time feedback of temperature fluctuations. The current solutions can use

thermographic layers to monitor thermal distribution in and around aisles, facilitating corrective measures for enhanced thermal management, including identification of overheated computing devices or suggesting corrective measures to the airflow to eliminate or reduce the hotspots in the data room. Additionally, machine learning (ML) modeling can be utilized to provide solutions, based on the thermographic layer readings, including computing device load balancing based on identified hotspots detected by the thermographic materials. In some examples, the thermographic layer readings can be used as input to systems that adjust the airflow based on such input.

[0022] FIG. 1 illustrates an example **100** of a material strip **110** having thermographic layers **115** that can be used for temperature detection in a curtain of a data room aisle. Example **100** provides a side view **102** of a cross-section of a material strip **110** with a thermographic layer **115** applied thereon. Example **100** also provides a front view **104** of a same or a different material strip **110** having one or more thermographic layers **115**, which can include a plurality of different thermographic materials **120**.

[0023] Material strip **110** can include any type, form, shape or size of material that can be used as a curtain controlling airflow between different regions of a data room. Material strip **110** can include a partially or fully transparent or translucent material, such as a sheet of clear or partially clear plastic or polymer. Material strip **110** can include any material, such as a polyvinyl chloride (PVC), nylon, or other transparent or partially transparent materials, including vinyl, polyester, polyurethane, rubber, silicone, acrylic, polyurethane terephthalate (Mylar) or polypropylene. Material strips **110** can be used as, or be combined with other material strips **110**, to form curtains between these areas. Material strips **110** can act as airflow barriers, allowing for the division of space into distinct zones while maintaining visibility and accessibility. For instance, one or more material strips **110** can include PVC or nylon materials and can provide an effective thermal barrier between the hot and cool aisles housing rows of server cabinets. Material strips **110** can provide both visibility and insulation, allowing for visual monitoring of the server cabinets, aisles or hotspots, while also providing adequate thermal separation.

[0024] Thermographic material **120** can include any material or a substance that changes color or appearance in response to a temperature change. Thermographic material **120** can include a material that opaque or at least partially translucent or transparent at one temperature and opaque or less transparent or translucent at another temperature. The material can be translucent or transparent by any percentage of light throughput, such as up to 5%, 10%, 20%, 40%, 60%, 70%, 90%, 95% or more than 95%. Thermographic material **120** can include a material that is transparent or translucent at one temperature and exhibits a color (e.g., red or black) when subjected to another temperature range. Thermographic material **120** can include any thermographic materials, such as liquid crystal mixtures, or thermochromic inks and paints. Thermographic material **120** can adjust its color, texture, hue or opacity based on temperature variations. In doing so, when applied to temperature variations, thermographic material **120** can be used to identify temperature changes with particular temperature range. Thermographic material **120** can include one or more polymers and plastics that can include inherent thermochromic properties, such as altering color or transparency as temperatures shift. Thermographic material **120** can include thermochromic pigments, microencapsulated materials, and alloys, which can provide different temperature-sensitive reactions. Thermographic material **120** can be configured to change its color in response to experiencing a temperature over a specific temperature range, such as for example, any temperature range between 30-100 F, such as 60-70F, 70-80 F or 80-90 F.

[0025] Thermographic layer **115** can include any layer of one or more thermographic materials **120**. Thermographic layer **115** can include a layer of material deposited, painted, sprayed, coated or otherwise applied on top of a material strip **110** material (e.g., nylon or PVC used a thermal curtain in a data room). Thermographic layer **115** can include thermographic materials **120** inserted, doped or implanted into material strips **110**. Thermographic layers **115** can include multiple layers of one or more same or different types of materials.

[0026] FIG. 2 illustrates an example **200** of a material strip **110** having various types of thermographic materials **120** applied as one or more thermographic layers **115** and arranged in various shapes (e.g., as strips or a tile grid) on top of a material strip **110**. Various thermographic materials **120A-E** can be configured to cover, or be responsive to, different temperature ranges and can be used for temperature detection in a curtain of a data room aisle to cover a broad range of temperature.

[0027] As shown in the top portion of FIG. 2, thermographic layer **115** can include an arrangement in which elongate strips of thermographic materials **120A**, **120B**, **120C**, **120D** and **120E** can be applied along the material strip **110**. Thermographic materials **120A-E** can be applied next to each other, thereby covering at least a portion of the material strip **110**. As shown, for example, in the bottom portion of FIG. 2, a thermographic layer **115** can include an arrangement in which square-shaped portions of different thermographic materials **120A-E** are arranged as a grid or tiled across the surface of the material strip **110**.

[0028] While several arrangements and/or configurations of the thermographic layer **115** are depicted in the accompanying figures, it is understood that several other combinations are possible and covered by the present application. In some examples, the arrangement of the thermographic materials **120A-E** can use different shapes from those depicted; for example, triangles, circles, rectangles, polygons, curved strips, or any other shape may be used. Further, in some examples, the thermographic materials may be arranged on the inside of the material strip **110**. Alternatively, in some examples, a subset of the thermographic materials, say **120A-C**, is on the inside, and the remaining thermographic materials, in this case **120D-E**, are on the outside of the material strip **110**. Several other combinations are possible.

[0029] FIG. 3 illustrates an example **300** of a data room **305** including a plurality of cabinets **310** for housing computing devices **315** configured for processing data (e.g., network traffic of a data center). Example **300** shows a data room having a plurality of cabinets **310** arranged or stacked in rows to form aisles **325**. Cabinets can include computing devices **315** which can face the same side, such that some of the aisles **325** have all the computing devices **315** from the cabinets **310** from either side facing the aisle **325** (e.g., a hot aisle). Cabinets can include computing devices **315** facing away from the aisle **325**, such that all computing devices **315** are not facing towards a particular aisle **325** (e.g., a cold aisle).

[0030] Data room **305** can include any room, area or a facility for housing and operating computing resources and data infrastructure. Data room **305** can include a location in which servers, network switches, or other computing resources of an enterprise (e.g., a company or an organization) are housed for operation. Data room **305** can include an area configured to provide suitable conditions for the storage, processing, and management of digital information, including sensitive and proprietary data. Data room **305** can include specialized equipment such as server racks, network cabinets, and cooling systems (e.g., air conditioning systems) to support the operation of the computing devices **315** (e.g., servers, switches, routers, and storage devices).

[0031] Cabinets **310** can include any enclosure or structure designed or dedicated for storing or housing computing devices for data management and processing. Cabinets **310** can be configured to provide physical protection, organization, and efficient management of computing devices, such as servers, computers, switches, routers, power supplies, or other devices for supporting or providing data infrastructure. Cabinets **310** can include server racks that can include metal frames with adjustable shelves or rails to accommodate different types and sizes of equipment. Cabinets can include enclosures configured for organizing networking devices such as switches and routers, including cable management solutions and ventilation systems (e.g., fans or convection cooling slits) to provide improved airflow and cooling.

[0032] Computing devices **315** can include any type or form of an electrical, electronic or computing device for a data processing infrastructure. Computing device **315** can include any device or a system serving various functions in data processing, storage, and networking. For

example, computing devices **315** can include servers, including computers designed to handle large volumes of data processing tasks. Computing devices **315** can include rack-mounted servers, blade servers, or tower servers, each offering specific advantages in terms of scalability, density, and performance. Computing devices **315** can include switches and routers to facilitate data communication and connectivity within a data center. Computing devices **315** can include storage devices, such as NAS (Network Attached Storage) or SAN (Storage Area Network) devices, which can be housed in cabinets to provide centralized data storage and retrieval capabilities.

[0033] Airflow features **320** on cabinets **310** can include any device, system, feature, structure or a component that can facilitate, adjust, impact or otherwise manage airflow within, from, to, or around any computing devices **315**, cabinets **310**, aisles **325** or data rooms **305**. Airflow features **320** can include components, features or devices designed or configured to direct, redirect, distribute, or modify airflow to adjust airflow or heat distribution and improve cooling efficiency. Airflow features **320** can include slits, holes or through-holes for facilitating airflow, perforated doors allowing air ingress and egress, brush grommets sealing cable entry points while allowing airflow, blanking panels preventing or controlling air recirculation, internal baffles or fins directing airflow along specific paths, and hot aisle/cold aisle containment systems separating hot and cold air streams. Airflow features **320** can include active cooling components, such as fans, cold plates, air conditioning units, precision air conditioners, chilled water systems, liquid cooling systems, cold aisle and hot aisle containment systems (e.g., curtains), in-row cooling units or heat exchangers. Airflow features **320** can include variable speed fans for adaptive cooling, as well as rack-level cooling systems providing targeted airflow to computing devices. Airflow features **320** can be controlled by a data processing system, which can include controllers for adjusting, operating or managing airflow features **320** to make adjustments to airflow or heat distribution (e.g., attenuation or removal of hotspots) in a data room **305**.

[0034] An aisle **325** can include any space, corridor or passageway created between adjacent rows of cabinets **310**. Aisle **325** can include a space between two or more cabinets **310** to provide access for maintenance, equipment installation, and airflow management. Aisles **325** can be used for operation and organization within the data room **305**, facilitating ease of movement, accessibility to computing devices **315** and airflow control. Aisles **325** can be configured as hot or cold aisles, depending on the intended purpose in airflow management. For example, an aisle **325** can be configured as a hot aisle to contain heated exhaust airflow from the computing devices **315** generating heat. For example, an aisle **325** can be configured as a cold aisle **325** to contain or supply cool air to the front intake of the computing devices **315**, thereby cooling the computing devices.

[0035] FIG. 4 illustrates an example **400** of a data room **305** having cabinets **310** whose airflow is contained by containment curtains **405** formed using material strips **110** with thermographic layers **115**. Example **400** includes two adjacent or parallel rows of cabinets **310** forming an aisle **325**. Aisle **325** can have its airflow contained using the cabinets **310** blocking the airflow on the sides of the aisle and curtains **405** covering the two ends of the aisle **325**. Curtains **405** can also be disposed on top of the cabinets **310** to cover the sides of the aisle **325** above the cabinet level. Curtain brackets **410** can be used to suspend the curtains **405** (e.g., material strips **110**) from a ceiling of a data room **305** and provide mechanical support for the curtains **405**.

[0036] Curtain **405** can include any barrier for controlling, containing or directing airflow and separating different temperature zones within the data room **305**. Curtain **405** can include any flexible material acting as a flexible barrier for an area within the data room **305**. Curtain **405** can be formed by material strips **110** and can facilitate the regulation and direction of air movement within a defined space. Curtains **405** can serve to partition areas, such as between hot and cold aisles **325** in a data room **305**, to improve airflow management and temperature distribution. Material strips **110** can be used in these curtains **405** and can include thermographic material **115** that can change color in response to temperature changes and provide visual cues for monitoring

airflow patterns and identifying hotspots or other areas of concern.

[0037] Curtain bracket **410** can include any component, device, structure or a system for suspending, holding or providing mechanical support for the curtain **405** or material strips **110**. Bracket **410** can include one or more brackets or structures that can be mounted on a ceiling of a data room **305**, along with strings tied to the curtain **405** to hold the curtain in place (e.g., at a particular height and over a particular area).

[0038] FIG. 5 illustrates an example **500** of a data room **305** having hot and cold aisles **325** separated by cabinets **310** and curtains **405** that can show locations of hotspots **520** using thermographic layers **115**. Example **500** can include a data room **305** having adjacent rows of cabinets **310** forming aisles **325**. Some of the aisles **325** can be configured as hot aisles for cycling or routing the heated airflow **505** from the computing devices **315** in the cabinets **310**. Some of the aisles **325** can be configured as cold aisles for cycling or routing the cooled airflow **510** from the computer room air conditioner (CRAC) **515**.

[0039] For example, heated air can exit from the computing devices **315** in the cabinets **310** and flow into the hot aisle **325** that can be contained using curtains **405** formed using interconnected material strips **110**. The material strips **110** can be connected to each other using magnets at the edges of the material strips **110**, which can facilitate sealing of the curtain **405**. Material strips **110** can include thermographic layers **115** that can include markers **525** for identifying locations of hotspots **520**. The technical solutions can include a data processing system that can utilize video frames from cameras to identify locations of hotspots **520** on the thermographic layers **115** based on the locations of one or more markers **525**.

[0040] Computer room air conditioner (CRAC) **515** can include any cooling system that can be used to regulate the temperature or humidity levels within a data room **305**. CRAC **515** can receive heated airflow **505** that can include heated air currents from convective heat dissipated from the computing devices **315** housed in cabinets within the data room **305**. CRAC **515** can include and utilize refrigeration and air circulation functionalities to cool the incoming heated airflow **505** to create cooled airflow **510**. CRAC **515** can redistributing the cooled airflow **510** back into the room, using curtains **405** or geometries of the data room **305** (e.g., ducts, pipes, linings or room features) to provide the cooled airflow **510** to the computing devices **315** within the cabinets **310**. CRAC **515** can include components such as compressors, condensers, evaporators, and fans to facilitate the air-cooling process. CRAC **515** can be managed and controlled by the data processing system to facilitate timely and controlled airflow and cooling to facilitate the reliable operation and performance within the data room **305**.

[0041] FIG. 6 illustrates an example block diagram of a system **600** for load balancing of computing devices **315** using curtains with thermographic layers **115** and machine learning. Example system **600** can include a data room **305** having one or more cameras **605** for capturing video streams **610** of a plurality of video frames **615**. Camera **605** can capture frames **615** any portion of the data room **305**, including cabinets **310** having computing devices **315**, curtains **405** having thermographic layers **115** identifying hotspots **520** based on locations of markers **525**. Across a network **602**, a data processing system (DPS) **625** can receive the video stream from the camera **605** and process it with a video processor **630**. DPS **625** can include one or more machine learning (ML) models **640** for processing video stream **610** to identify the locations of the hotspots **520** and determine corrective action to take to reduce the hotspots **520**. The corrective action can include using a load balancer **660** to adjust load balancing of the network requests **665** processed by the computing devices **315** so as to address, reduce or eliminate the hotspot **520**. The corrective action can include using a thermal manager **650** to correct airflow features **320** and adjust the heated airflow **505** or cooled airflow **510** in the data room **305**.

[0042] Camera **605** can include any combination of hardware and software for capturing images of a data room **305**. Camera **605** can include a hardware device, such as an image capture device, to capture visual data, including digital images or digital videos. Camera **605** can include a digital

camera, an infrared or a thermal camera, a surveillance camera, a webcam, a digital single lens reflex camera or any other type or form of a camera device. Camera **605** can capture images or videos in the forms of video streams **610** of any number of video frames **615**. Camera **605** can include optical components for image capture and electronic components for signal processing and transmitting the captured data to a data processing system **625** for further analysis and processing. [0043] Video stream **610** can include any continuous flow of visual data, such as images or video frames, that can be captured by camera **605**. Video stream **610** can include data captured and transmitted in real-time and can be used for continuous surveillance or monitoring of an area, such as a data room **305**. Video stream **610** can include a sequence of frames **615** that can represent or include individual snapshots or images of a visual scene (e.g., data room **305**) captured by the camera **605**. Video stream **610** can include a live feed from a surveillance cameras **605** monitoring server racks or equipment cabinets **310** for temperature fluctuations or airflow issues, as exhibited or reflected in the thermographic layers **115**.

[0044] A frame **615** can include any individual or still image of a video stream **610** captured and transmitted by a camera **605**. Frame **615** can include an image of a sequence of 1, 5, 10, 15, 30, 60, 90, 120 images captured by camera **605** per second. Each frame **615** can include visual information representing a specific moment in time within the data room **305**, such as a snapshot of a data room. Each frame **615** can include or represent a state or position of a curtain **405**, any changes to color in the thermographic layers **115**, any hotspots **520** or markers **525**, which can be used by the DPS **625** to determine airflow movement or corrective action to take. Frames **615** can include still images of server racks or cabinets **310**, computing devices **315** (e.g., servers) or airflow patterns as reflected in the thermographic materials **120** on the curtains **405**, as captured by surveillance cameras **605** in the data room **305**.

[0045] Data processing system (DPS) **625** can include any combination of hardware and software for monitoring temperature of a data room **305** using curtains **405** having transparent material strips **110** with thermographic layers **115** exhibiting hotspots **520**. DPS **625** can include any computer code, functions and data processed or executed on one or more servers, virtual machines, Software as a Service (SaaS), cloud-based systems or any other computing environment. DPS **625** can receive, parse and process video stream **610** and identify video frames **615**. DPS **625** can detect distinct features within the frames **615**, including curtains **405**, material strips **110**, thermographic layers **115**, markers **525** and hotspots **520**.

[0046] Data processing system **625** can include a computational framework configured to analyze and process video streams **610** captured by camera **605** to identify airflow movements, hotspots **520** or corrective actions to take. DPS **625** can include, or be implemented by, computing systems, such as servers, processors, and storage systems, as well as software components for data analysis, machine learning, and decision-making.

[0047] Video processor **630** can include any combination of hardware and software for processing videos streams **610**. Video processor **630** can include the functionality for analyzing and processing video streams **610**, frames **615** and identifying their features. Video processor **630** can include hardware or software algorithms for utilizing ML models **640** to extract relevant data from the video stream **610**, such as detecting anomalies or identifying patterns, airflow movements or hotspots **520** on the curtains **405**.

[0048] Machine learning (ML) models **640** can include any computational algorithms that can learn patterns and relationships from data to make predictions or decisions relating color changing of thermographic layers **115**, hotspots **520** and the related airflow movement. ML models **640** can be trained to determine sources of increased heat, reasons for particular hotspot **520** formation or corrective actions to take to alleviate or reduce the hotspots **520**. ML models **640** can be trained using datasets on computational fluid dynamics (CFD) analysis for airflow in a data room. ML models **640** can be trained on historical data to recognize patterns and anomalies the airflow movement based on the features captured in the video streams **610**, such as hotspots **520** with

respect to markers **525**. For instance, ML model **640** can identify a formation of a hotspot **520**, based on a thermographic layer **115** changing color (e.g., to form the hotspot **520**). ML model **640** can determine, based on the location of the hotspot, a cause of the hotspot, such as a faulty computing device **315**, an overheated or overburdened computing device **315**, a blocked or malfunctioning airflow feature **320**, or a change or adjustment to make to the CRAC **515** or an airflow feature **320** to address or change the speed or direction of the airflow (e.g., **505** or **510**). [0049] ML models **640** can include and utilize any ML architecture, such as transformer architecture, convolutional neural network (CNN) architecture or a graph neural network (GNN) architecture, for processing video streams and identifying airflow patterns and causes of hotspots. For example, ML models **640** can include neural networks trained to detect temperature fluctuations or airflow disruptions in surveillance videos within the data room. For instance, ML models **640** can include CNN ML model to extract features from visual data and identify anomalies or hotspots. For example, ML models **640** can include GNN architecture to model relationships between different components in data room **305**, such as CRAC **515**, cabinets **310**, aisle **325**, curtains **405** and discern airflow pathways.

[0050] Thermal manager **650** is a component of the data processing system **625** responsible for monitoring and managing thermal conditions within the data room. It receives input from ML models **640** analyzing video streams **610** and makes adjustments to airflow systems or cooling infrastructure to maintain optimal thermal conditions for equipment operation. Examples of thermal managers include automated HVAC systems or intelligent control systems that adjust fan speeds or airflow patterns based on ML model predictions.

[0051] Load balancer **660** can include any combination of hardware and software for distributing incoming requests **665** among multiple computing devices **315**. Load balancer **660** can include the functionality to distribute the requests **665** across the computing devices **315** to improve or optimize the performance and resource utilization. Load balancer **660** can even out computational tasks related to network traffic processing performed by the computing devices **315**. Load balancer **660** can utilize video processing and ML models **640** to determine from determined or inferred air movements, which of the computing devices are to have their network traffic increased and which one are to have their network traffic reduced.

[0052] Requests **665** can include any incoming requests, data or processing tasks directed to the computing devices **315** of the data room **305**. Requests **665** can include any type and form of requests serviced by computing devices, such as hypertext transfer protocol (HTTP) requests, HTTP secure (HTTPS) requests, file transfer protocol (FTP) requests, domain name system (DNS) requests, simple mail transfer protocol (SMTP) requests, secure shell (SSH) requests, structured query language (SQL) requests, application programming interface (API) call or any other type and form of requests in the network traffic that computing devices can service. Requests **665** can include requests for real-time video analysis, inference of ML models, or adjustments to thermal management systems based on detected anomalies in video streams **610**.

[0053] Network **602** can include one or more types of networks that can be used for communication between a camera **605** and a DPS **625**. Network **602** can include one or more Local Area Networks (LANs), which can be used within a limited geographical area, such as an office or building, and Wide Area Networks (WANs), which span larger distances and can connect devices across cities or countries. Network **602** can include one or more Metropolitan Area Networks (MANs) which can be utilized to cover a city or metropolitan area. Network **602** can support internet-based connections, using protocols like TCP/IP, and enable access to cloud-based data processing systems. Network **602** can include or support wireless networks, such as Wi-Fi and cellular networks, as well as Virtual Private Networks (VPNs) which can provide security to public networks. Network **602** can include or utilize Intranets (e.g., private networks within an organization) facilitating internal communications.

[0054] FIG. 7 illustrates a block diagram of a computing system **700** for implementing the

embodiments of the present solution, in accordance with embodiments. FIG. 7 illustrates a block diagram of an example computing system **700**, which can also be referred to as the computer system **700**. Computing system **700** can be used to implement elements of the systems and methods described and illustrated herein, such as for example, commands, instructions or data described herein. Computing system **700** can be included in and run any device (e.g., DPS **625**, ML models **640**, or any other feature or component of example systems **100-600**).

[0055] Computing system **700** can include at least one bus data bus **705** or other communication device, structure or component for communicating information or data. Computing system **700** can include at least one processor **710** or processing circuit coupled to the data bus **705** for executing instructions or processing data or information. Computing system **700** can include one or more processors **710** or processing circuits coupled to the data bus **705** for exchanging or processing data or information along with other computing systems **700**. Computing system **700** can include one or more main memories **715**, such as a random-access memory (RAM), dynamic RAM (DRAM), cache memory or other dynamic storage device, which can be coupled to the data bus **705** for storing information, data and instructions to be executed by the processor(s) **710**. Main memory **715** can be used for storing information (e.g., data, computer code, commands or instructions) during execution of instructions by the processor(s) **710**.

[0056] Computing system **700** can include one or more read only memories (ROMs) **720** or other static storage device **725** coupled to the bus **705** for storing static information and instructions for the processor(s) **710**. Storage devices **725** can include any storage device, such as a solid-state device, magnetic disk or optical disk, which can be coupled to the data bus **705** to persistently store information and instructions.

[0057] Computing system **700** may be coupled via the data bus **705** to one or more output devices **735**, such as speakers or displays (e.g., liquid crystal display or active-matrix display) for displaying or providing information to a user. Input devices **730**, such as keyboards, touch screens or voice interfaces, can be coupled to the data bus **705** for communicating information and commands to the processor(s) **710**. Input device **730** can include, for example, a touch screen display (e.g., output device **735**). Input device **730** can include a cursor control, such as a mouse, a trackball, or cursor direction keys, for communicating direction information and command selections to the processor(s) **710** for controlling cursor movement on a display.

[0058] The processes, systems and methods described herein can be implemented by the computing system **700** in response to the processor **710** executing an arrangement of instructions contained in main memory **715**. Such instructions can be read into main memory **715** from another computer-readable medium, such as the storage device **725**. Execution of the arrangement of instructions contained in main memory **715** causes the computing system **700** to perform the illustrative processes described herein, such as actions or functions of the DPS **625**. One or more processors **710** in a multi-processing arrangement may also be employed to execute the instructions contained in main memory **715**. Hard-wired circuitry can be used in place of or in combination with software instructions together with the systems and methods described herein. Systems and methods described herein are not limited to any specific combination of hardware circuitry and software.

[0059] Although an example computing system has been described in FIG. 7, the subject matter including the operations described in this specification can be implemented in other types of digital electronic circuitry, or in computer software, firmware, or hardware, including the structures disclosed in this specification and their structural equivalents, or in combinations of one or more of them.

[0060] In one aspect, the technical solutions can be directed to a system, such as a system including features or components shown in examples **100-600**. The system can include a data room **305** having a plurality of cabinets **310** and a plurality of computing devices **315** housed within each cabinet **310** of the plurality of cabinets **310**. Computing devices **315** can be configured to operate or process network traffic and generate heat upon such processing or operation. The processing of

network traffic or data can include processing of network requests **665**. The system can include one or more portions of transparent material to form a curtain **405** adjacent to the plurality of cabinets **310** to control a flow of air (e.g., **505**, **510**) impacted by the heat. The curtain **405** can be formed by connecting or suspending side-by-side of the plurality of material strips **110**. The system can include one or more layers of thermographic material (e.g., **115**) applied on the one or more portions of transparent material **110** to change a color of the one or more layers of the thermographic material (e.g., **115**) responsive to a change in temperature caused by the flow of air (e.g., **505**, **510**).

[0061] The one or more portions of transparent material **110** includes a plurality of strips of a polymer material, vinyl or nylon material. The polymer, vinyl or nylon material can be at least partially transparent to light in a visible spectral range (e.g., 380-700 nm wavelength). The plurality of strips **110** can include at least two strips of the plurality of strips suspended vertically (e.g., from a bracket **410**) and at least partly overlapping side by side with each other to form the curtain **405**. The one or more layers of thermographic material (e.g., **115**) can include a layer of a plurality of thermographic materials (e.g., **120A-E**). Each thermographic material (e.g., **120**) of the plurality of thermographic materials (e.g., **120**) can correspond to a separate portion of the layer **115**.

[0062] The one or more layers of thermographic material **115** can include a plurality of layers of the thermographic materials **115**. The plurality of layers **115** can be applied one on top of another. Each layer of the plurality of layers of the thermographic materials (e.g., **115**) can include a thermographic material **120** configured to change color responsive to experiencing temperature within a predetermined temperature range. The temperature ranges for various thermographic materials **120** can vary, such as that each of the thermographic materials **120** reacts to changes in temperatures within a different temperature range than other thermographic materials **120**.

[0063] The one or more layers of thermographic material **115** can include a plurality of portions of a layer **115** covering a plurality of portions of a surface of the transparent material **110**. Each of the portions of the layer **115** can include a different thermographic material **120** of a plurality of thermographic materials **120**. A layer **115** of the one or more layers of the thermographic material (e.g., **115**) can include a first portion of the layer **115** covering a first portion of the transparent material **110** and including a first thermographic material **120** configured to change color responsive to a change in temperature over a first temperature range. The layer **115** can include a second portion of the layer **115** covering a second portion of the transparent material **110** and including a second thermographic material **120** configured to change color responsive to a change in temperature over a second temperature range different than the first temperature range.

[0064] The system can include an aisle **325** formed by the plurality of cabinets **310**. The system can include a bracket **410** to suspend the curtain **405** adjacent to the aisle **325** to control the flow of air (e.g., **505** or **510**) within the aisle **325** impacted by the heat generated by the plurality of cabinets **310**. Each computing device of the plurality of computing devices **310** can include one or more integrated circuits (e.g., processors **710**) to process data responsive to requests **665** and generate the heat to impact the flow of air (e.g., **505**, **510**) in the aisle **325** responsive to the processing of data.

[0065] The system can include one or more features **320** of the plurality of cabinets **310** to control the flow of air (e.g., **505**, **510**) within the aisle. The one or more features **320** can be adjustable responsive to a change in the color of the one or more layers of the thermographic material. The system can include the plurality of cabinets **310** including a first plurality of cabinets **310** on a first side of the aisle **325** and a second plurality of cabinets **310** on a second side of the aisle **325**. The aisle **325** can be parallel to a second aisle **325** formed by the second plurality of cabinets **310** and a third plurality of cabinets **310** comprising one or more computing devices **315** of the plurality of computing devices **315**. The curtain **405** can form a barrier surrounding the aisle **325** to preclude the flow of air (e.g., airflows **505**, **510**) along at least a length of the aisle **325** and a width of the aisle **325**.

[0066] An aspect of the technical solutions can be directed to a system, such as a system including

characteristics of examples **100-700**. The system can include one or more processors **710** coupled with memory (e.g., **715, 720, 725**) and configured to implement functionality of a DPS **625**. The one or more processors **710** can be configured to implement the functionalities of the technical solutions by storing instructions, commands or computer code configured or designed to perform the tasks of the technical solutions using the one or more processors **710**.

[0067] The one or more processors **710** can be configured to identify, using one or more video frames **615** of a video stream **610** captured by a camera **605**, one or more layers of thermographic material **115**. The one or more layers (e.g., **115**) of thermographic material **120** can be applied on one or more portions of a transparent material **110** of a curtain **405**. The curtain **405** can be disposed adjacent to a plurality of cabinets **310** housing a plurality of computing devices **315** configured to process requests and generate heat. The one or more processors **710** can be configured to detect that a color of a portion of a layer **115** of the one or more layers of thermographic material (e.g., **115**) is indicative of a temperature of a flow of air (e.g., **505, 510**) impacted by the heat.

[0068] The one or more processors **710** can train, identify and retrieve one or more machine learning (ML) models **640** that can be trained on the plurality of colors of a plurality of thermographic materials **120** on a plurality of curtains **405** adjacent cabinets **310** housing computing devices **315**. The one or more ML models **640** can be trained using various sources of heat and various housing structures arranged in various arrangements (e.g., aisles or stacks) around various types of data rooms **305** to determine or identify airflow (e.g., **505** or **510**) around the room based on hotspots **520**. The one or more processors **710** can be configured to determine, using the color and the location input into the one or more ML models **640**, that a computing device of the plurality of computing devices generates the heat that impacts the flow of air (e.g., **505, 510**) toward the portion of the layer **115** on the curtain **405**.

[0069] The one or more processors **710** can be configured to take corrective action responsive to the determination of the temperature based on the hotspot **520** on a thermographic layer **115**. For example, the one or more processor **710** can load balance the requests **655** incoming to the computing devices **315** across the plurality of computing devices **315** responsive to the determination of the hotspot **520**. The one or more ML models **640** can identify the locations of the specific computing devices **315** in the data room **305**, and based on the location of the hotspot **520** with respect to the identified location of one or more markers **525**, determine to adjust the number or flow rate of requests **655** to the identified computing device **315** to load balance the computing device **315** and adjust the temperature or the airflow (e.g., **505, 510**). The one or more processors **710** can be configured to adjust the operation or positioning of an airflow feature **320** to correct the airflow and alleviate or impact the airflow, thereby redistributing the heat and reducing the hotspot **520**.

[0070] The one or more processors **710** can be configured to configured to determine that a second computing device **315** of the plurality of computing devices **315** processes more network traffic than the computing device **315**. The one or more processors **710** can be configured to determine to provide one or more new requests **665** to the second computing device **315** responsive to the determination that the computing device **315** generates the heat that impacts the flow of air (e.g., **505, 510**).

[0071] The one or more processors **710** can be configured to identify a marker **525** on the curtain. The one or more processors **710** can be configured to detect, responsive to a location of the marker **525** on the curtain **405**, a location of the portion of the layer **115**. The one or more processors **710** can be configured to identify the one or more layers **115** of thermographic material **120**. The one or more processors **710** can be configured to identify the layer of the one or more layers (e.g., **115**) using the one or more video frames **615** input into the one or more ML models **640**. The one or more processors **710** can be configured to detect that the color of the portion of the layer **115** has changed using the one or more ML models **640** and in response to this detection, identify the

temperature at the hotspot **520**.

[0072] The one or more processors **710** can be configured to detect, using the one or more ML models **640**, that the color of the portion of the layer **115** has changed. The one or more processors **710** can be configured to determine a temperature at the location of the portion of the layer **115** responsive to the detected color of the portion of the layer **115**. The one or more processors **710** can be configured to determine, using the one or more ML models the flow of air impacted by the heat. The one or more processors **710** can be configured to adjust, responsive to the determination, an airflow feature to change the flow of air (e.g., **505**, **510**).

[0073] The one or more processors **710** can be configured to determine the flow of air (e.g., **505**, **510**) impacted by the heat using the one or more ML models **640**. The one or more processors **710** can be configured to generate settings for features **320** to control the flow of air (e.g., **505**, **510**) based at least on the color and the location input into the one or more ML models **640**.

[0074] In an aspect, the technical solutions can be directed to a non-transitory computer readable medium. The non-transitory computer readable medium can store program instructions to cause at least one processor of a device to perform any actions of the technical solutions (e.g., **DPS 625** or its components or features) when executed by the at least one processor. The instructions, when executed by the at least one processor, can configure the at least one processor **710** to identify, using one or more video frames **615** captured by a camera **605**, one or more layers of thermographic material **115** applied on one or more portions of a transparent material **110** of a curtain **405**. The curtain **405** can be disposed adjacent to a plurality of cabinets **310** housing a plurality of computing devices **315** configured to process requests and generate heat. The instructions, when executed by the at least one processor **710**, can configure the at least one processor **710** to detect that a color of a portion of a layer **115** of the one or more layers of thermographic material (e.g., **115**) is indicative of a temperature of a flow of air (e.g., **505**, **510**) impacted by the heat.

[0075] The instructions, when executed by the at least one processor **710**, can configure the at least one processor **710** to determine, using the color and the location input into one or more machine learning (ML) models **640** trained on the plurality of colors of a plurality of thermographic materials **120** on a plurality of curtains **405** adjacent to cabinets **310** housing computing devices **315**, that a computing device **315** of the plurality of computing devices generates the heat that impacts the flow of air (e.g., **505**, **510**) toward the portion of the layer **115**. The instructions, when executed by the at least one processor, can configure the at least one processor **710** to load balance the requests **665** across the plurality of computing devices **315** responsive to the determination by the one or more ML models **640**.

[0076] FIG. **8** shows another example process flow of a method **800** for ML-based thermal management of a data room using curtains with thermographic layers. Method **800** can include, for example, an example process flow for implementing load balancing across computing devices using ML-based thermal management of a data room based on color changes on thermographic layers of containment curtains. Method **800** can be implemented using the system tools, devices and components discussed herein (e.g., system examples **100-700**) discussed, for example in connection with FIGS. **1-7**. Method **800** can include acts **805-825**. At act **805**, a layout of a data room can be identified. At act **810**, a curtain with a thermographic layer can be identified. At act **815**, a change in color on thermographic material portion can be detected. At act **820**, a computing device impacting the airflow can be determined. At act **825**, take adjustment action to change temperature around the identified computing device.

[0077] At act **805**, a layout of a data room can be identified. The method can include identifying, by one or more processors coupled with memory, a plurality of cabinets. The method can include identifying, by the one or more processors, a plurality of computing devices housed within each cabinet of the plurality of cabinets to generate heat. The method can include detecting, by the one or more processors, one or more portions of transparent material to form a curtain adjacent to the

plurality of cabinets to control a flow of air impacted by the heat. The method can include detecting, by the one or more processors, one or more layers of thermographic material applied on the one or more portions of transparent material to change a color of the one or more layers of the thermographic material responsive to a change in temperature caused by the flow of air.

[0078] At act **810**, a curtain with a thermographic layer can be identified. The method can include identifying, by one or more processors coupled with memory, using one or more video frames captured by a camera, one or more layers of thermographic material applied on one or more portions of a transparent material of a curtain. The curtain disposed adjacent to a plurality of cabinets housing a plurality of computing devices configured to process requests and generate heat.

[0079] At act **815**, a change in color on thermographic material portion can be detected. The method can include detecting, by the one or more processors, that a color of a portion of a layer of the one or more layers of thermographic material is indicative of a temperature of a flow of air impacted by the heat. For example, one or more ML models can determine, based on image frames input into the one or more ML models, that the color of the portion of the layer on a curtain has changed and that it indicates a particular temperature or a temperature range.

[0080] At act **820**, a computing device impacting the airflow can be determined. The method can include determining, by the one or more processors, using the color and the location input into one or more machine learning (ML) models trained on the plurality of colors of a plurality of thermographic materials on a plurality of curtains adjacent to cabinets housing computing devices, that a computing device of the plurality of computing devices generates the heat that impacts the flow of air toward the portion of the layer. For example, the one or more ML models can determine, based on one or more image frames input into the one or more ML models, a location of a marker and a location of a hotspot (e.g., color change on the thermographic material layer). The one or more ML models can determine the location of the hotspot, based on the color change. The one or more ML models can determine the temperature or the temperature range of the airflow or air current adjacent to, or impacting, the hotspot.

[0081] At act **825**, an adjustment action is performed to change temperature around the identified computing device. The adjustment action can include taking any corrective action to address the hotspot, operation of one or more computing devices, or airflow features, responsive to the determination at **820**. The method can include load balancing, by the one or more processors, the requests across the plurality of computing devices responsive to the determination. The method can include adjusting the position or the operation of the airflow feature, responsive to the determination, in order to impact or change the flow of air. The method can include identifying a faulty computing device, a faulty airflow feature or an error in the system. The method can include identifying an error with an air conditioning unit or a fan. Alternatively, or in addition, the adjustment action can include adjusting an airflow that causes cooler (or higher) temperature air to flow in the vicinity of the identified computing device. The airflow can be adjusted by changing the direction of one or more vents, airflow controllers, etc. Alternatively, the airflow can be adjusted by changing the temperature of the air being channeled to the data room, and in particularly in the vicinity of the identified computing device. Several other such actions can be taken as part of the adjustment action.

[0082] The foregoing examples have been provided merely for the purpose of explanation and are in no way to be construed as limiting of the present disclosure. While aspects of the present disclosure have been described with reference to an exemplary embodiment, it is understood that the words which have been used herein are words of description and illustration, rather than words of limitation. Changes may be made, within the purview of the appended claims, as presently stated and as amended, without departing from the scope and spirit of the present disclosure in its aspects. Although aspects of the present disclosure have been described herein with reference to particular means, materials and embodiments, the present disclosure is not intended to be limited to the particulars disclosed herein; rather, the present disclosure extends to all functionally equivalent

structures, methods and uses, such as are within the scope of the appended claims.

[0083] The systems described above can provide multiple ones of any or each of those components and these components can be provided on either a standalone system or on multiple instantiations in a distributed system. Example and non-limiting module implementation elements can include components, such as detectors or sensors providing or using any value determined herein or sensors providing any value that is a precursor to a value determined herein. Implementation elements can also include a datalink or network hardware including communication chips, oscillating crystals, communication links, cables, twisted pair wiring, coaxial wiring, shielded wiring, transmitters, receivers, or transceivers, logic circuits, hard-wired logic circuits, reconfigurable logic circuits in a particular non-transient state configured according to the module specification, any actuator including at least an electrical, hydraulic, or pneumatic actuator, a solenoid, an op-amp, analog control elements (springs, filters, integrators, adders, dividers, gain elements), or digital control elements.

[0084] While operations are depicted in the drawings in a particular order, such operations are not required to be performed in the particular order shown or in sequential order, and all illustrated operations are not required to be performed. Actions described herein can be performed in a different order and functions from one illustrated block can be called by other functions in other blocks. Also, although many of the examples presented herein involve specific combinations of method acts or system elements, those acts, and those elements may be combined in other ways to accomplish the same objectives. Acts, elements and features discussed in connection with one implementation are not intended to be excluded from a similar role in other implementations or implementations.

[0085] The phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting. The use of “including” “comprising” “having” “containing” “involving” “characterized by” “characterized in that” and variations thereof herein, is meant to encompass the items listed thereafter, equivalents thereof, and additional items, as well as alternate implementations consisting of the items listed thereafter exclusively. In one implementation, the systems and methods described herein consist of one, each combination of more than one, or all of the described elements, acts, or components.

[0086] Any references to implementations or elements or acts of the systems and methods herein referred to in the singular may also embrace implementations including a plurality of these elements, and any references in plural to any implementation or element or act herein may also embrace implementations including only a single element. References in the singular or plural form are not intended to limit the presently disclosed systems or methods, their components, acts, or elements to single or plural configurations. References to any act or element being based on any information, act or element may include implementations where the act or element is based at least in part on any information, act, or element.

[0087] Any implementation disclosed herein may be combined with any other implementation or embodiment, and references to “an implementation,” “some implementations,” “one implementation” or the like are not necessarily mutually exclusive and are intended to indicate that a particular feature, structure, or characteristic described in connection with the implementation may be included in at least one implementation or embodiment. Such terms as used herein are not necessarily all referring to the same implementation. Any implementation may be combined with any other implementation, inclusively or exclusively, in any manner consistent with the aspects and implementations disclosed herein.

[0088] References to “or” may be construed as inclusive so that any terms described using “or” may indicate any of a single, more than one, and all of the described terms. References to at least one of a conjunctive list of terms may be construed as an inclusive OR to indicate any of a single, more than one, and all of the described terms. For example, a reference to “at least one of ‘A’ and ‘B’” can include only ‘A’, only ‘B’, as well as both ‘A’ and ‘B’. Such references used in

conjunction with “comprising” or other open terminology can include additional items.

[0089] Where technical features in the drawings, detailed description or any claim are followed by reference signs, the reference signs have been included to increase the intelligibility of the drawings, detailed description, and claims. Accordingly, neither the reference signs nor their absence have any limiting effect on the scope of any claim elements. Modifications of described elements and acts such as variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations can occur without materially departing from the teachings and advantages of the subject matter disclosed herein. For example, elements shown as integrally formed can be constructed of multiple parts or elements, the position of elements can be reversed or otherwise varied, and the nature or number of discrete elements or positions can be altered or varied. Other substitutions, modifications, changes and omissions can also be made in the design, operating conditions and arrangement of the disclosed elements and operations without departing from the scope of the present disclosure. Coupled elements can be electrically, mechanically, or physically coupled with one another directly or with intervening elements. Scope of the systems and methods described herein is thus indicated by the appended claims, rather than the foregoing description, and changes that come within the meaning and range of equivalency of the claims are embraced therein.

Claims

1.-30. (canceled)

31. A system, comprising: one or more processors, coupled with memory, to: identify, using one or more image frames captured by a camera, one or more layers of thermographic material applied on one or more portions of a material of a curtain, the curtain disposed adjacent to a plurality of cabinets housing a plurality of computing devices configured to process requests and generate heat; detect that a color of a portion of a layer of the one or more layers of thermographic material is indicative of a temperature of a flow of air impacted by the heat; determine, using the color and a location of the portion of the layer input into one or more machine learning (ML) models trained on the plurality of colors of a plurality of thermographic materials on a plurality of curtains adjacent to cabinets housing computing devices, that a computing device of the plurality of computing devices generates the heat that impacts the flow of air toward the portion of the layer; and load balance the requests across the plurality of computing devices responsive to the determination.

32. The system of claim 31, wherein the one or more processors: determine that a second computing device of the plurality of computing devices processes more network traffic than the computing device; and determine to provide one or more new requests to the second computing device responsive to the determination that the computing device generates the heat that impacts the flow of air.

33. The system of claim 31, wherein the one or more processors: identify a marker on the curtain; and detect, responsive to a location of the marker on the curtain, a location of the portion of the layer.

34. The system of claim 31, wherein the one or more processors: identify the one or more layers of thermographic material; and identify the layer of the one or more layers using the one or more image frames input into the one or more ML models.

35. The system of claim 31, wherein the one or more processors: detect, using the one or more ML models, that the color of the portion of the layer has changed; and responsive to the detected color of the portion of the layer determine a temperature at a location of the portion.

36. The system of claim 31, wherein the one or more processors: determine, using the one or more ML models the flow of air impacted by the heat; and adjust, responsive to the determination, an airflow feature to change the flow of air.

37. The system of claim 31, wherein the one or more processors: generate settings for features to control the flow of air based at least on the color and the location input into the one or more ML models.

38. The system of claim 31, wherein the curtain disposed adjacent to the plurality of cabinets is configured to control the flow of air impacted by the heat from the plurality of cabinets and the one or more layers of thermographic material is configured to change the color of the portion of the layer responsive to a change in temperature caused by the flow of air.

39. The system of claim 31, wherein the one or more portions of material includes a plurality of strips of a polymer material, the polymer material at least partially transparent to light in a visible spectral range.

40. The system of claim 39, wherein the plurality of strips includes at least two strips of the plurality of strips suspended vertically and at least partly overlapping side by side with each other to form the curtain.

41. The system of claim 31, wherein the one or more layers of thermographic material includes a plurality of layers of the thermographic materials, each layer of the plurality of layers including a thermographic material configured to change color responsive to experiencing temperature within a predetermined temperature range.

42. The system of claim 31, wherein the one or more layers of thermographic material includes a plurality of portions of a layer covering a plurality of portions of a surface of a material of the curtain, each of the portions of the layer including a different thermographic material of a plurality of thermographic materials.

43. The system of claim 31, wherein the layer of the one or more layers of the thermographic material includes a first portion of the layer covering a first portion of the material and including a first thermographic material configured to change color responsive to a change in temperature over a first temperature range and a second portion of the layer covering a second portion of the material and including a second thermographic material configured to change color responsive to a change in temperature over a second temperature range different than the first temperature range.

44. A method, comprising: identifying, by one or more processors coupled with memory, using one or more image frames captured by a camera, one or more layers of thermographic material applied on one or more portions of a material of a curtain, the curtain disposed adjacent to a plurality of cabinets housing a plurality of computing devices configured to process requests and generate heat; detecting, by the one or more processors, that a color of a portion of a layer of the one or more layers of thermographic material is indicative of a temperature of a flow of air impacted by the heat; determining, by the one or more processors, using the color and a location of the portion of the layer input into one or more machine learning (ML) models trained on the plurality of colors of a plurality of thermographic materials on a plurality of curtains adjacent to cabinets housing computing devices, that a computing device of the plurality of computing devices generates the heat that impacts the flow of air toward the portion of the layer; and load balancing, by the one or more processors, the requests across the plurality of computing devices responsive to the determination.

45. The method of claim 44, comprising: determining, by the one or more processors, that a second computing device of the plurality of computing devices processes more network traffic than the computing device; and determining, by the one or more processors, to provide one or more new requests to the second computing device responsive to the determination that the computing device generates the heat that impacts the flow of air.

46. The method of claim 44, comprising: identifying, by the one or more processors, a marker on the curtain; and detecting, by the one or more processors, responsive to a location of the marker on the curtain, a location of the portion of the layer.

47. The method of claim 44, comprising: identifying, by the one or more processors, the one or more layers of thermographic material; and identifying, by the one or more processors, the layer of

the one or more layers using the one or more image frames input into the one or more ML models.

48. The method of claim 44, comprising: detecting, by the one or more processors, using the one or more ML models, that the color of the portion of the layer has changed; and determining, by the one or more processors, responsive to the detected color of the portion of the layer, a temperature at a location of the portion.

49. The method of claim 44, comprising: determining, by the one or more processors, using the one or more ML models the flow of air impacted by the heat; and adjusting, by the one or more processors, responsive to the determination, an airflow feature to change the flow of air.

50. A non-transitory computer readable medium storing program instructions to cause at least one processor of a device to: identify, using one or more image frames captured by a camera, one or more layers of thermographic material applied on one or more portions of a material of a curtain, the curtain disposed adjacent to a plurality of cabinets housing a plurality of computing devices configured to process requests and generate heat; detect that a color of a portion of a layer of the one or more layers of thermographic material is indicative of a temperature of a flow of air impacted by the heat; determine, using the color and a location of the portion of the layer input into one or more machine learning (ML) models trained on the plurality of colors of a plurality of thermographic materials on a plurality of curtains adjacent to cabinets housing computing devices, that a computing device of the plurality of computing devices generates the heat that impacts the flow of air toward the portion of the layer; and load balance the requests across the plurality of computing devices responsive to the determination.
