

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250280880

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

KIM; Ick Joong et al.

AEROSOL GENERATING ARTICLE AND AEROSOL GENERATING SYSTEM

Abstract

An aerosol generating article includes an aerosol generating material that is heated by exposure to microwaves and a first capsule that is crushed by exposure to the microwaves, wherein the first capsule includes a first core including a first material and a first microwave-responsive material, and a first shell surrounding the first core.

Inventors: KIM; Ick Joong (Daejeon, KR), KI; Sung Jong (Daejeon, KR), PARK; In Su (Daejeon, KR), SONG; Ho Rim (Daejeon, KR)

Applicant: KT&G CORPORATION (Daejeon, KR)

Family ID: 1000008562633

Assignee: KT&G CORPORATION (Daejeon, KR)

Appl. No.: 19/065374

Filed: February 27, 2025

Foreign Application Priority Data

KR 10-2024-0033315

Mar. 08, 2024

KR 10-2025-0008185

Jan. 20, 2025

Publication Classification

Int. Cl.: A24F40/46 (20200101); A24D1/20 (20200101); A24F40/20 (20200101)

U.S. Cl.:

CPC A24F40/46 (20200101); A24D1/20 (20200101); A24F40/20 (20200101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] This application claims priority to and the benefit of Korean Patent Application No. 10-2024-0033315, filed on Mar. 8, 2024, and Korean Patent Application No. 10-2025-0008185, filed on Jan. 20, 2025, the contents of which are incorporated by reference herein in their entireties.

BACKGROUND

1. Field

[0002] Embodiments relate to an aerosol generating article and an aerosol generating system, and more particularly, to an aerosol generating article and an aerosol generating system capable of generating aerosols by being heated by a dielectric heating method.

2. Description of the Related Art

[0003] Recently, there has been an increasing demand for an alternative method of overcoming disadvantages of general cigarettes. For example, there has been an increasing demand for a system that generates an aerosol by heating a cigarette (or “an aerosol generating article”) by using an aerosol generating device, other than a method of generating an aerosol by burning the cigarette.

[0004] In the aerosol generating system of the related art, an aerosol generating article is heated by a heating element that uses an electrical resistance heating method or an induction heating method and surrounds the outside of the aerosol generating article or is inserted into the aerosol generating article.

SUMMARY

[0005] In the aerosol generating system of the related art, a region of an aerosol generating article which is close to a heating element may be heated to a relatively high temperature, and a region of the aerosol generating article which is far from the heating element may be heated to a relatively low temperature. Because an aerosol generating article is heated unevenly, active ingredients (e.g., nicotine and/or an aerosol generating material) in a region heated to a relatively low temperature may not be fully transferred and remain in the aerosol generating article. In addition, the amount of active ingredients transferred to a user is not constant throughout the entire heating period, and also a taste of smoking may not be constant.

[0006] In addition, in the general aerosol generating system of the related art, an aerosol generating article is heated through heat conduction from a heating element, and accordingly, a certain preheating time may be required to heat the aerosol generating article. In addition, an aerosol generated at the beginning of a heating period when the temperature of an aerosol generating article does not increase sufficiently may not include sufficient active ingredients.

[0007] In addition, a flavoring material that adds flavor to an aerosol has high volatility, and accordingly, a capsule is used to prevent the flavoring material from being lost. In general, a capsule includes a core that includes a flavoring material and a shell surrounding the core. The capsule is embedded in the aerosol generating article, and when used, a user presses a portion in which the capsule is embedded to crush the capsule. When the capsule is crushed, the flavoring material may be released to add flavor to an aerosol. However, a user may have difficulty in crushing a capsule depending on the thickness, strength, softness, viscosity, and so on of a shell.

[0008] Objects to be achieved by embodiments of the disclosure are not limited to the objects described above, and objects not described may be clearly understood by a person of skill in the art to which the embodiments belong from the present specification and the attached drawings.

[0009] Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments of the disclosure.

[0010] According to an embodiment, an aerosol generating article includes an aerosol generating

material that is heated by exposure to microwaves and a first capsule that is crushed by exposure to the microwaves, wherein the first capsule includes a first core including a first material and a first microwave-responsive material and a first shell surrounding the first core.

[0011] According to another embodiment, an aerosol generating system includes an aerosol generating article and an aerosol generating device configured to accommodate the aerosol generating article, wherein the aerosol generating device includes a heater assembly configured to generate microwaves for heating the aerosol generating article.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0012] The above and other aspects, features, and advantages of certain embodiments of the disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

[0013] FIG. 1 is a diagram illustrating an example of a structure of a first capsule included in an aerosol generating article according to an embodiment;

[0014] FIG. 2 is a schematic view of an aerosol generating article according to an embodiment;

[0015] FIG. 3 is a schematic view of an aerosol generating article according to another embodiment;

[0016] FIG. 4 is a schematic view of an aerosol generating article according to another embodiment;

[0017] FIG. 5 is a perspective view of an aerosol generating device according to an embodiment;

[0018] FIG. 6 is an internal block diagram of an aerosol generating device according to an embodiment;

[0019] FIG. 7 is an internal block diagram of a dielectric heating unit of FIG. 6;

[0020] FIG. 8 is a perspective view of a heater assembly according to an embodiment;

[0021] FIG. 9 is a cross-sectional view of the heater assembly of FIG. 8; and

[0022] FIG. 10 is a perspective view schematically illustrating a heater assembly according to another embodiment.

DETAILED DESCRIPTION

[0023] Hereinafter, embodiments of the disclosure are described in detail with reference to the attached drawings, and regardless of the drawing symbols, identical or similar components are given the same reference numerals, and redundant descriptions thereof are omitted.

[0024] Suffixes “module”, “unit”, and “portion” used for components in the following description are given or used interchangeably only for the sake of convenience of describing the disclosure and do not have distinct meanings or functions in themselves.

[0025] Also, in describing the embodiments disclosed in the disclosure, when it is determined that detailed descriptions of the related known technologies may obscure the gist of the embodiments disclosed in the disclosure, the detailed descriptions are omitted. Also, the attached drawings are only for easy understanding of the embodiments disclosed in the disclosure, and the technical idea disclosed in the disclosure is not limited by the attached drawings and should be understood to include all changes, equivalents, and substitutes included in the idea and technical scope of the disclosure.

[0026] Terms including ordinal numbers, such as “first”, “second”, and so on, may be used to describe various components, but the components are not limited by the terms. The terms described above are used only for the purpose of distinguishing one component from another component.

[0027] When a component is described to be “connected” or “coupled” to another component, it should be understood that the component may be directly connected or coupled to another component and may be connected or coupled thereto with other components therebetween. In

addition, when it is described that a component is “directly connected” or “directly coupled” to another component, it should be understood that there are no other components therebetween. [0028] Singular expressions include plural expressions unless the context clearly dictates otherwise.

[0029] As described herein, when an expression, such as “at least one” precedes arranged elements, the expression modifies all of the arranged elements rather than each of the arranged elements. For example, an expression “at least one of a, b, and c” should be interpreted to include a, b, c, a and b, a and c, b and c, or a and b and c.

[0030] Throughout the specification, an “aerosol generating device” may be a device that generates an aerosol from an aerosol generating material to generate an aerosol that is directly inhalable into a user's lungs through the user's mouth.

[0031] Throughout the specification, an “aerosol generating article” means an article used in smoking. For example, an aerosol generating article may be a combustible cigarette used in a manner that is ignited and combusted, or may be a heating-type cigarette used in a manner that is heated by an aerosol generating device.

[0032] Throughout the specification, an “aerosol generating system” may include an aerosol generating device and an aerosol generating article. For example, an aerosol generating system may heat an aerosol generating article by using an aerosol generating device and deliver the generated aerosol to a user.

[0033] Throughout the specification, a “puff” means inhalation of a user. Inhalation may mean drawing an aerosol into a user's mouth, nose, or lungs through the user's mouth or nose.

[0034] FIG. 1 is a diagram illustrating an example of a structure of a first capsule included in an aerosol generating article according to an embodiment.

[0035] Referring to FIG. 1, a first capsule **16-1** may include a first core **16-1c** and a first shell **16-1s** surrounding the first core **16-1c**. The first core **16-1c** may include a first material. When the first shell **16-1s** is crushed, the first material included in the first core **16-1c** may be released from the first core.

[0036] The first material may include at least one selected from the group including a flavoring material, nicotine, caffeine, and cannabinoid.

[0037] The flavoring material may add flavor to an aerosol generated by an aerosol generating article **10** of FIGS. 2 to 4. The flavoring material may include a natural flavoring material and/or synthetic flavoring material. For example, the synthetic flavoring material may include at least one selected from the group including ester, alcohol, aldehyde, ketone, phenol, ether, lactone, hydrocarbon, a nitrogen-containing compound, a sulfur-containing compound, and acid.

[0038] In addition, the natural flavoring material may include one or more oils selected from the group consisting of, for example, star anise, basil, calamus, caraway, pepper, cascarilla, ginger, sage, clary sage, clove, coriander, *eucalyptus*, fennel, pimento, juniper, fenugreek, laurel, mace, almond, anise, *artemisia*, apricot, strawberry, fig, ylang ylang, wintergreen, plum, elder, chamomile, galanga, quince, guava, cranberry, prickly ash, sandalwood, chamomile, jasmine, *ginseng*, cinnamon, star fruit, cinnamon, spearmint, apple mint, peppermint, geranium, thyme, tansy, tangerine, tuberose, peppermint, passion fruit, vanilla, rose, coffee, cypress, pine, mango, beeswax, musk, maple, melon, peach, lavender, and rosemary.

[0039] The term “cannabinoid” refers to any one of a class of naturally occurring compounds found in some species of *cannabis* plant, *Cannabis sativa*, *Cannabis indica*, and *Cannabis ruderalis*. A cannabinoid compound that occurs naturally in the *cannabis* plant includes cannabidiol (CBD) and tetrahydrocannabinol (THC). The term “cannabinoid” is used to describe both naturally occurring cannabinoids and synthetically produced cannabinoids.

[0040] The first capsule **16-1** may be crushed by exposure to microwaves. When the first core **16-1c** is exposed to microwaves, the first core **16-1c** may include a first microwave-responsive material to be crushed. The first microwave-responsive material may be heated by exposure to

microwaves. Heat generated by the first microwave-responsive material may be transferred to the first shell **16-1s** so that the first capsule **16-1** may be crushed. The first microwave-responsive material may function as a dielectric. Electric charges of the dielectric may vibrate or rotate according to microwave resonance, and the dielectric may be heated by frictional heat generated while the electric charges vibrate or rotate, and thus, the first shell **16-1** may be crushed.

[0041] A general capsule may be crushed by pressure applied by a user's finger. In contrast to this, the first capsule **16-1** may be crushed by microwaves generated by a heater assembly of an aerosol generating device to be described below, and accordingly, user intervention is not required to crush the first capsule **16-1**.

[0042] The first microwave-responsive material may include one or more selected from the group consisting of glycerin, propylene glycol, ethylene glycol, dipropylene glycol, diethylene glycol, triethylene glycol, tetraethylene glycol, and oleyl alcohol, but is not limited thereto.

[0043] The first core **16-1c** may include the first microwave-responsive material with about 20 wt % to about 40 wt % of the total weight of the first core **16-1c**. When the first core **16-1c** includes the first microwave-responsive material with about 20 wt % or less of the total weight of the first core **16-1c**, the first capsule **16-1** may not be crushed even when exposed to microwaves having a frequency of 2.4 GHz to 2.5 GHz. In addition, when the first core **16-1c** includes the first microwave-responsive material with about 50 wt % or more of the total weight of the first core **16-1c**, suitability for manufacturing the capsule may be reduced. For example, the first core **16-1c** may include the first microwave-responsive material with about 20 wt % to about 40 wt % or about 25 wt % to about 35 wt % of the total weight of the first core **16-1c**.

[0044] The first shell **16-1s** may surround the first core **16-1c**. The first shell **16-1s** is illustrated to be spherical, but is not limited thereto, and the cross section of the first shell **16-1s** may be locally elliptical or may be a partially deformed circular shape.

[0045] The first shell **16-1s** may include a plurality of layers. For example, the first shell **16-1s** may include an inner shell **16-1si** and an outer shell **16-1so** surrounding the inner shell **16-1si**.

[0046] The inner shell **16-1si** may include a fat-soluble material. The fat-soluble material may mean a hydrophobic material that is dissolved in a non-polar solvent such as benzene. As the inner shell **16-1si** includes the fat-soluble material, the first core **16-1c** may include a water-soluble material.

[0047] When a shell and a core of a capsule include a material of the same properties (e.g., both include a water-soluble material or both include a fat-soluble material), the shell and the core may be mixed by the same properties, and accordingly the shell may not stably retain the material of the core. In the case of the capsule of the related art, because the shell generally includes a single layer of a water-soluble material, there is a technical limitation that the core needs to include a fat-soluble material. On the other hand, as the inner shell **16-1si** in direct contact with the first core **16-1c** includes the fat-soluble material, the first capsule **16-1** of the aerosol generating article according to an embodiment may stably retain the water-soluble material (e.g., the first microwave reactive material) in the first core **16-1c**.

[0048] The inner shell **16-1si** may include a fat-soluble wax. For example, the inner shell **16-1si** may include one or more plant waxes selected from the group consisting of carnauba wax, candela wax, castor wax, ouricury palm wax, cocoa butter, and shea butter. In addition, the inner shell **16-1si** may include one or more animal waxes selected from the group consisting of shellac wax and beeswax.

[0049] A melting point of the inner shell **16-1si** may be about 38° C. to about 95° C. When the melting point of the inner shell **16-1si** is within the above-described range, the capsule may be smoothly manufactured, and may be appropriately melted or crushed by heating the first microwave-responsive material.

[0050] The inner shell **16-1si** may have a hardness of about 9 penetration unit (PU) to about 156 PU in a needle penetration test according to ASTM D1321 international standards. When the

hardness of the inner shell **16-1si** is within the above-described range, the first capsule **16-1** may be exposed to microwaves to be smoothly crushed and simultaneously prevented from being crushed by an unintended impact. For example, the inner shell **16-1si** may have the hardness of about 15 PU to about 96 PU, or the hardness of about 20 PU to about 75 PU.

[0051] The inner shell **16-1si** may further include an oil such as an intermediate chain triglyceride in addition to the waxes such as the examples described above. The melting point and the hardness of the inner shell **16-1si** may be adjusted by adjusting a ratio of oils included in the inner shell **16-1si**. Accordingly, it is possible to adjust the crushing characteristics of the first capsule **16-1** by adjusting the ratio of waxes and oils included in the inner shell **16-1si**. For example, the oils included in the inner shell **16-1si** may be about 1 wt % to about 80 wt % or about 10 wt % to about 50 wt % of the total weight of the inner shell **16-1si**.

[0052] The outer shell **16-1so** may include a water-soluble material. The outer shell **16-1so** may be located at the outermost portion of the first capsule **16-1**. The outer shell **16-1so** may include a material having elasticity and/or flexibility to prevent the first capsule **16-1** from being unintentionally crushed.

[0053] For example, the outer shell **16-1so** may include one or more water-soluble polymers selected from the group consisting of gelatin, agar, carrageenan, gelatin gum, pectin, starch, and alginate. In addition, the outer shell **16-1so** may include at least one of a starch derivative, such as dextrin, maltodextrin, or cyclodextrin, a cellulose derivative, such as hydroxypropyl methyl cellulose (HPMC), hydroxypropyl cellulose (HPC), methyl cellulose (MC), or carboxymethyl cellulose (CMC), polyvinyl alcohol, or polyol.

[0054] The first shell **16-1s** may have a thickness of about 5 μm to about 50 μm . The thickness of the first shell **16-1s** may mean a sum of the thickness of the inner shell **16-1si** and the thickness of the outer shell **16-1so**. When the thickness of the first shell **16-1s** is within the above-described range, the first shell **16-1s** may be exposed to microwaves to be easily crushed, and may have mechanical strength capable of preventing the first shell **16-1s** from being crushed even by an unintended impact. In addition, a drying time of the first shell **16-1s** may be shortened during a manufacturing process of the first capsule **16-1**. For example, the first shell **16-1s** may have a thickness of about 10 μm to about 50 μm , about 15 μm to about 50 μm , about 10 μm to about 40 μm , or about 20 μm to about 40 μm .

[0055] The inner shell **16-1si** may have a thickness of about 1.5 μm to about 20 μm . When the thickness of the inner shell **16-1si** is within the above-described range, materials included in the first core (**16-1c**) may be stably retained, and manufacturing efficiency may be improved. For example, the inner shell **16-1si** may have a thickness of about 2.5 μm to about 20 μm , about 4 μm to about 20 μm , about 2.5 μm to about 16 μm , or about 5 μm to about 16 μm .

[0056] The outer shell **16-1so** may have a thickness of about 3.5 μm to about 30 μm . When the thickness of the outer shell **16-1so** is within the above-described range, the outer shell **16-1s** may be easily applied to the aerosol generating article based on excellent elasticity, flexibility, and mechanical strength of the first shell **16-1s**, and may be easily crushed by exposure to microwaves. For example, the outer shell **16-1so** may have a thickness of about 7.5 μm to about 30 μm , about 9 μm to about 30 μm , about 7.5 μm to about 24 μm , or about 15 μm to about 24 μm .

Experimental Example: Measurement of Quality of Capsule According to Thickness of Shell

[0057] A plurality of first capsules having the same structure as the first capsule **16-1** shown in FIG. 1 were manufactured by varying the thickness of the first shell, and the capsule manufacturing suitability, stick manufacturing suitability, and capsule crushing performance of the manufactured first capsule were evaluated. Evaluation results are shown in Table 1 below.

[0058] Capsule manufacturing suitability is an evaluation item with respect to the manufacturing suitability of capsule. Capsule manufacturing suitability was comprehensively evaluated whether the capsule is easily dried during the manufacturing process, whether the capsule is easily formed without problems such as collapsing or crushing due to the lack of mechanical strength of the

capsule, and whether the capsule maintains its shape after manufacturing.

[0059] Capsule manufacturing suitability was evaluated based on the following criteria. [0060] ◦:

Capsule is easy to manufacture and may maintain its shape [0061] Δ: Capsule is not easy to

manufacture or does not maintain its shape [0062] X: Capsule may not be manufactured

[0063] Stick manufacturing suitability is an evaluation item with respect to the manufacturing suitability of the aerosol generating article including the capsule. Stick manufacturing suitability was comprehensively evaluated whether the capsule is easily inserted into the aerosol generating article and whether the capsule is not crushed and maintains its shape in the process of applying the capsule to the aerosol generating article.

[0064] Stick manufacturing suitability was evaluated based on the following criteria. [0065] ◦:

Capsule may be easily applied to the aerosol generating article [0066] Δ: The shape of the capsule is deformed or easily crushed in the process of applying the capsule to the aerosol generating article

[0067] X: Capsule may not be applied to the aerosol generating article

[0068] Capsule crushing performance is an item that evaluates whether the capsule is properly crushed by exposure to microwaves. Capsule crushing performance was comprehensively evaluated whether the capsule is crushed at an appropriate time and whether the capsule is crushed smoothly so that a material included in the core of the capsule is sufficiently discharged. The microwave-responsive material included in the core of the capsule was glycerin.

[0069] Capsule crushing performance was evaluated based on the following criteria. [0070] ◦:

Capsule is exposed to microwaves at a frequency of 2.45 GHz and easily crushed [0071] Δ:

Capsule is exposed to microwaves at the frequency of 2.45 GHz and not easily crushed [0072] X:

Capsule is exposed to microwaves at the frequency of 2.45 GHz and not crushed

TABLE-US-00001 TABLE 1 Thickness of first shell (μm) 5 10 20 30 40 50 80 100 Capsule Δ ○

○ ○ ○ ○ Δ X manufacturing suitability Stick X Δ ○ ○ ○ ○ ○ — manufacturing suitability

Capsule — Δ ○ ○ ○ Δ X — crushing performance

[0073] As shown in Table 1, it may be confirmed that when the thickness of the first shell is 80 μm or more, the drying time of the capsule is excessively increased or is not dried during the manufacturing process, and thus the manufacturing of the capsule is unsuitable. In addition, when the thickness of the first shell is 10 μm or less, the first capsule did not maintain its shape due to the lack of mechanical strength of the first shell, and the stick manufacturing suitability was insufficient, such as the capsule being easily crushed in the process of applying the capsule to the aerosol generating article. When the thickness of the first shell exceeds 50 μm, it may be confirmed that the first capsule is difficult to be crushed even when exposed to microwaves. When the first shell has a thickness of about 10 μm to about 50 μm, it was confirmed that the capsule has excellent quality in all the items.

[0074] FIG. 2 is a schematic view of an aerosol generating article according to an embodiment.

[0075] Referring to FIG. 2, an aerosol generating article **10** may include an aerosol generating rod **11** and a filter rod **12**. The filter rod **12** may be disposed downstream from the aerosol generating rod **11**.

[0076] “Upstream” and “downstream” may be determined based on a direction in which air flows when a user inhales an aerosol by using the aerosol generating article **10**. For example, when a user inhales an aerosol by using the aerosol generating article **10** illustrated in FIG. 2, air moves from the aerosol generating rod **11** toward the filter rod **12**, and accordingly, the aerosol generating rod **11** is located upstream from the filter rod **12**. In addition, a person skilled in the art will easily understand that “upstream” and “downstream” may be relative depending on relationships between components.

[0077] The aerosol generating rod **11** may include a tobacco material. The aerosol generating rod **11** may be heated to generate an aerosol containing nicotine. The tobacco material may be in the form of a tobacco strand, a tobacco particle, a tobacco sheet, a tobacco bead, a tobacco granule, tobacco powder, or tobacco extract but is not limited thereto.

[0078] For example, the aerosol generating rod **11** may include a plurality of tobacco strands, and the plurality of tobacco strands may include cut tobacco sheets. The cut tobacco sheets may be obtained by cutting tobacco sheets. The cut tobacco sheets may be made by the following process. Tobacco raw materials are pulverized to make a slurry in which an aerosol generating material (e.g., glycerin, propylene glycol, etc.), a flavoring liquid, a binder (e.g., guar gum, xanthan gum, carboxymethyl cellulose, etc.), water, etc. are mixed. The slurry may include natural pulp or cellulose, and one or more binders may be mixed to be used as the slurry. The slurry may be cast to form a sheet, and then dried to make a tobacco sheet. The tobacco sheet may be cut, crimped, or shredded to make a cut tobacco sheet. The tobacco raw material may be tobacco leaves, tobacco stems, and/or tobacco fines generated during tobacco processing. In addition, other additives, such as wood cellulose fibers, may also be included in the tobacco sheet.

[0079] In addition, the aerosol generating rod **11** may include tobacco cut sheets made by mixing and processing various types of tobacco leaves, and then cutting the tobacco leaves. In addition, the aerosol generating rod **11** may include a mixture of cut tobacco sheets and tobacco cut sheets.

[0080] In another example, the aerosol generating rod **11** may include a plurality of tobacco granules. The tobacco granules may be particles each having a diameter of about 100 μm to about 2,000 μm . The plurality of tobacco granules may be manufactured by extruding a mixture of tobacco leaf powder, a pH adjuster, and a solvent.

[0081] The plurality of tobacco granules may be between filter materials. The filter materials may each include, for example, a fiber bundle of cellulose acetate fiber strands. The plurality of tobacco granules may be in a uniformly dispersed form between a plurality of cellulose fibers. In another example, the filter material may include a crimped paper sheet. The crimped paper sheet may be inside the aerosol generating rod **11** in a wound state. The crimped paper sheet may be wound around an axis extending in the longitudinal direction of the aerosol generating rod **11**. The plurality of tobacco granules may be dispersed inside the wound paper sheet.

[0082] The tobacco material may include an aerosol generating material. For example, the aerosol generating material may include at least one of glycerin, propylene glycol, ethylene glycol, dipropylene glycol, diethylene glycol, triethylene glycol, tetraethylene glycol, or oleyl alcohol, but is not limited thereto. In addition, the tobacco material may also include another additive, such as a flavoring agent, a humectant, and/or organic acid. In addition, a flavoring liquid, such as menthol or a humectant, may be added to the tobacco material by being sprayed onto the tobacco material.

[0083] The aerosol generating rod **11** may also include other plant materials than the tobacco material. For example, the aerosol generating rod **11** may include an herbal material. The aerosol generating rod **11** may also include a sheet including the herbal material. The herbal material may include at least one of mint, lemongrass, cinnamon, a clover leaf, a rose petal, and corn silk but is not limited thereto. An aerosol generating material may be impregnated into the sheet including the herbal material.

[0084] In addition, the aerosol generating rod **11** may include an aerosol generating substrate impregnated with a liquid aerosol generating composition. The aerosol generating substrate may include a crimped sheet, and the liquid aerosol generating composition may be included in the aerosol generating rod **11** in a state of being impregnated in the crimped sheet. In addition, other additives, such as flavoring agents, humectants, and/or organic acids, and a flavoring liquid may be included in the aerosol generating rod **11** in a state in which the flavoring liquid is absorbed in the crimped sheet.

[0085] The aerosol generating substrate may be disposed inside the aerosol generating rod **11** in a wound state. The wound aerosol generating substrate may be wound around an axis extending in the longitudinal direction of the aerosol generating article **10**, but is not limited thereto.

[0086] The crimped sheet may be a sheet formed of a polymer material. For example, the polymer material may include at least one of paper, cellulose acetate, lyocell, and polylactic acid. For example, the crimped sheet may be a paper sheet that does not generate an off-flavor due to heat,

even when the crimped sheet is heated to a high temperature.

[0087] The liquid aerosol generating composition may include nicotine. The nicotine may include freebase nicotine and/or nicotine salt. The freebase nicotine may mean neutral nicotine that has not been protonated. For example, when a strong base, such as ammonia, is added to a positively charged nicotine salt, the strong base is converted into a cation, and the nicotine salt may become freebase nicotine, which is in a neutral state.

[0088] In addition, the liquid aerosol generating composition may include an aerosol generating material. The above description on the aerosol generating material may be equally applied to the aerosol generating material included in a tobacco material.

[0089] The liquid aerosol generating composition may be impregnated into the aerosol generating substrate in a ratio of about 0.05 g to about 1.0 g per 1 g of the aerosol generating material. For example, the liquid aerosol generating composition may be impregnated into the aerosol generating substrate in a ratio of about 0.1 g to about 0.8 g per 1 g of the aerosol generating material.

[0090] An aerosol generating material included in the aerosol generating rod **11** may be heated by exposure to microwaves. Here, the aerosol generating material may function as a dielectric. Electric charges of the dielectric may vibrate or rotate due to microwave resonance, and the dielectric is heated due to frictional heat generated while the electric charges vibrate or rotate, and thus, the aerosol generating rod **11** may be heated.

[0091] The aerosol generating rod **11** may include a first capsule **16-1**. For example, the aerosol generating rod **11** may include a plurality of tobacco strands, and the first capsule **16-1** may be surrounded by the plurality of tobacco strands. In another example, the aerosol generating rod **11** may include a crimped sheet impregnated with a liquid aerosol generating composition, and the first capsule **16-1** may be surrounded by the crimped sheet.

[0092] The filter rod **12** may be composed of a plurality of segments. The filter rod **12** may include a first segment **12-1** for cooling an aerosol and a second segment **12-2** for filtering a preset component included in the aerosol. FIG. 2 illustrates that the filter rod **12** includes two segments, but the embodiment is not limited thereto. For example, the filter rod **12** may include a single segment. In addition, the filter rod **12** may further include at least one segment that performs another function.

[0093] The filter rod **12** may filter some components included in an aerosol passing through the filter rod **12**. The filter rod **12** may include a filter material. For example, the filter rod **12** may be a cellulose acetate filter. The filter rod **12** may be manufactured by adding a plasticizer (e.g., triacetin) to cellulose acetate tow.

[0094] There is no limitation on a shape of the filter rod **12**. For example, the filter rod **12** may be a cylindrical rod or a hollow tubular rod. In addition, the filter rod **12** may be a recessed rod. When the filter rod **12** is composed of multiple segments, at least one of the multiple segments may have a different shape from the other segments.

[0095] The filter rod **12** may generate flavor. For example, a flavoring liquid may be sprayed onto the filter rod **12**, or a separate fiber coated with a flavoring liquid may be inserted inside the filter rod **12**.

[0096] The filter rod **12** may include the first segment **12-1** that cools an aerosol. The first segment **12-1** may include a polymer material or a biodegradable polymer material. For example, the first segment **12-1** may include polylactic acid but is not limited thereto. In another example, the first segment **12-1** may include a hollow cellulose acetate tube or a paper tube made of paper.

[0097] At least one hole **12-1h** may be formed in an outer surface of the first segment **12-1**. At least one hole **12-1h** may be formed along the circumference of the first segment **12-1** to form at least one row. At least one hole **12-1h** may cause external air to be introduced into the first segment **12-1**. The external air introduced into the first segment **12-1** may be mixed with a high-temperature aerosol generated by the aerosol generating rod **11**.

[0098] The aerosol generating article **10** may include a wrapper **14** surrounding one of the aerosol

generating rod **11** and the filter rod **12**. In addition, the wrapper **14** may surround both the aerosol generating rod **11** and the filter rod **12**. The wrapper **14** may be located at the outermost part of the aerosol generating article **10**. The wrapper **14** may be a single wrapper but may also be a combination of multiple wrappers.

[0099] The aerosol generating article **10** may be wrapped overlappingly by two or more wrappers **14**. For example, the aerosol generating rod **11** may be wrapped by a first wrapper **14-1**, the first segment **12-1** of the filter rod **12** may be wrapped by a second wrapper **14-2**, and the second segment **12-2** of the filter rod **12** may be wrapped by a third wrapper **14-3**. In addition, the aerosol generating article **10** may be entirely rewrapped by a fourth wrapper **14-4**.

[0100] The first wrapper **14-1** may surround the aerosol generating rod **11**. The first wrapper **14-1** may be a combination of paper and metal foil, such as aluminum foil. For example, the first wrapper **14-1** may be a stacked sheet in which paper and metal foil are stacked. The first wrapper **14-1** may be a stacked sheet in which the paper is disposed on one side of the metal foil or may be a stacked sheet in which the paper is disposed on both sides of the metal foil.

[0101] The paper of the first wrapper **14-1** may include an oil-resistant material. For example, the paper of the first wrapper **14-1** may include polyvinyl alcohol (PVOH) or silicone. The paper of the first wrapper **14-1** may have a surface coated with polyvinyl alcohol or silicone.

[0102] The second wrapper **14-2** may surround the first segment **12-1** of the filter rod **12**. The second wrapper **14-2** may include a paper roll. The paper roll of the second wrapper **14-2** may be a porous roll or a non-porous roll. At least one perforation **15** may be formed in the second wrapper **14-2**. For example, the second wrapper **14-2** may wrap the first segment **12-1** having at least one hole **12-1h** formed therein, and at least one perforation **15** formed in the second wrapper **14-2** may be formed at a position corresponding to at least one hole **12-1h** formed in the first segment **12-1**.

[0103] The third wrapper **14-3** may surround the second segment **12-2** of the filter rod **12**. The third wrapper **14-3** may include a hard roll having a greater thickness and basis weight than a general paper roll. For example, the hard paper may have a thickness of about 70 μm to about 150 μm , and a weight of about 50 g/m.^{sup.2} to about 100 g/m.^{sup.2}. In addition, the hard paper may include an oil-resistant material. For example, the hard paper may have a surface processed with an oil-resistant material, such as polyvinyl alcohol or silicone.

[0104] The fourth wrapper **14-4** may collectively wrap the aerosol generating rod **11** wrapped by the first wrapper **14-1**, the first segment **12-1** of the filter rod **12** which is wrapped by the second wrapper **14-2**, and the second segment **12-2** of the filter rod **12** which is wrapped by the third wrapper **14-3**. The fourth wrapper **14-4** may prevent the outside of the aerosol generating article **10** from being contaminated by an aerosol generated by the aerosol generating article. A liquid material may be generated from the aerosol generating article **10** by a user's puff. For example, the liquid material (e.g., moisture, etc.) may be generated as an aerosol generated from the aerosol generating article **10** is cooled by external air. As the fourth wrapper **14-4** wraps an outer surface of the aerosol generating article **10**, the generated liquid material may be prevented from leaking out of the aerosol generating article **10**.

[0105] FIG. 3 is a schematic view of an aerosol generating article according to another embodiment.

[0106] Referring to FIG. 3, the aerosol generating article **10** may include a front end plug **13**, an aerosol generating rod **11**, a filter rod **12**, and a wrapper **14**. The descriptions made above on the aerosol generating rod **11**, the filter rod **12**, and the wrapper **14** of the aerosol generating article **10** of FIG. 2 may be applied, in the same manner, to the aerosol generating rod **11**, the filter rod **12**, and the wrapper **14** of the aerosol generating article **10** of FIG. 3.

[0107] The front end plug **13** may be disposed upstream from the aerosol generating rod **11**. The front end plug **13** may be located on one side of the aerosol generating rod **11** which is opposite to the filter rod **12**. The front end plug **13** may prevent the aerosol generating rod **11** from escaping to the outside. In addition, the front end plug **13** may prevent a liquefied aerosol from the aerosol

generating rod **11** from moving to an aerosol generating device during smoking.

[0108] The front end plug **13** may include cellulose acetate. For example, the front end plug **13** may be a hollow cellulose acetate tube.

[0109] The front end plug **13** may be wrapped by a fifth wrapper **14-5**. The fifth wrapper **14-5** may be a combination of paper and metal foil, such as aluminum foil. For example, the fifth wrapper **14-5** may be a stacked sheet in which paper and metal foil are stacked. The fifth wrapper **14-5** may be a stacked sheet in which paper is on one side of metal foil, or a stacked sheet in which paper is on both sides of metal foil.

[0110] In addition, the front end plug **13** may be wrapped overlappingly by two or more wrappers **14**. For example, the front end plug **13** may be wrapped by the fifth wrapper **14-5**, the aerosol generating rod **11** may be wrapped by the first wrapper **14-1**, the first segment **12-1** of the filter rod **12** may be wrapped by the second wrapper **14-2**, and the second segment **12-2** of the filter rod **12** may be wrapped by the third wrapper **14-3**. In addition, the aerosol generating article **10** may be entirely repackaged by the fourth wrapper **14-4**.

[0111] The front end plug **13** may also be heated to generate an aerosol. The front end plug **13** may include an aerosol generating material. In addition, the front end plug **13** may include other additives, such as a humectant and/or organic acid and may include a flavoring liquid, such as menthol. For example, the aerosol generating material may include at least one of glycerin, propylene glycol, ethylene glycol, dipropylene glycol, diethylene glycol, triethylene glycol, tetraethylene glycol, or oleyl alcohol. The aerosol generating material may include the same material as the first microwave-responsive material. The aerosol generating material may be heated by exposure to microwaves, thereby generating an aerosol.

[0112] The front end plug **13** may include an aerosol generating substrate. An aerosol generating material may be impregnated into the aerosol generating substrate. The aerosol generating substrate may include a crimped sheet, and the aerosol generating material may be included in the front end plug **13** in a state of being impregnated in the crimped sheet. In addition, other additives, such as a flavoring agent, a humectant, and/or organic acid, may be included in the front end plug **13** in a state of being impregnated in the crimped sheet.

[0113] The aerosol generating substrate may be disposed inside the front end plug **13** in a wound state. The wound aerosol generating substrate may be wound around an axis extending in the longitudinal direction of the aerosol generating article **10** but is not limited thereto.

[0114] The crimped sheet may be a sheet composed of a polymer material. For example, the polymer material may include at least one of paper, cellulose acetate, lyocell, and polylactic acid. For example, the crimped sheet may be a paper sheet that does not generate an off-flavor due to heat, even when the crimped sheet is heated to a high temperature.

[0115] The front end plug **13** may have a length of about 7 mm to about 20 mm, and the aerosol generating rod **11** may have a length of about 7 mm to about 20 mm. However, the length of the front end plug **13** and the length of the aerosol generating rod **11** may be appropriately changed.

[0116] FIG. **4** is a schematic view of an aerosol generating article according to another embodiment.

[0117] Referring to FIG. **4**, the aerosol generating article **10** may include an aerosol generating rod **11**, a filter rod **12**, and a wrapper **14**. The descriptions made above on the aerosol generating rod **11**, the filter rod **12**, and the wrapper **14** of the aerosol generating article **10** of FIG. **2** may be applied, in the same manner, to the aerosol generating rod **11**, the filter rod **12**, and the wrapper **14** of the aerosol generating article **10** of FIG. **4**.

[0118] The aerosol generating article **10** may include a first capsule **16-1** and a second capsule **16-2**. The second capsule **16-2** may have the same shape and size as the first capsule **16-1** but is not limited thereto.

[0119] The second capsule **16-2** may include a second core and a second shell surrounding the second core. The second core may include a second material. When the second shell is crushed, the

second material included in the second core may be released.

[0120] The second capsule **16-2** may be exposed to microwaves and crushed. The second shell may include a second microwave-responsive material to be exposed to microwaves and crushed. The second microwave-responsive material is heated by exposure to microwaves, and thus, the second shell may be crushed. The second microwave-responsive material may function as a dielectric. Electric charges of the dielectric may vibrate or rotate due to microwave resonance, and the dielectric is heated due to frictional heat generated while the electric charges vibrate or rotate, and thus, the second shell may be heated.

[0121] Description made above on the first capsule **16-1** may be applied, in the same manner, to the second capsule **16-2**. In addition, the second core, the second material, the second shell, and the second microwave-responsive material included in the second capsule **16-2** may respectively include the same materials as the first core, the first material, the first shell, and the first microwave-responsive material included in the first capsule **16-1**, or may include different materials.

[0122] For example, the second core, the second shell, and the second microwave-responsive material may respectively be the same as the first core, the first shell, and the first microwave-responsive material, while the second material may be different from the first material. In another example, the first capsule **16-1** may have the same components as the second capsule **16-2**, except for the first microwave-responsive material and the second microwave-responsive material. In another example, the second core, the second material, the second shell, and the second microwave-responsive material may respectively include the same materials as the first core, the first material, the first shell, and the first microwave-responsive material, while contents of the microwave-responsive materials included in the respective cores may be different from each other.

[0123] The first capsule **16-1** may be crushed at different times from the second capsule **16-2**. For example, the first capsule **16-1** may be crushed at the beginning of a heating period, and the second capsule **16-2** may be crushed at the end of the heating period. Here, the “heating period” may mean a time length from the time when a heater assembly of an aerosol generating device to be described below starts heating to the time when the heating ends. In addition, a part corresponding to an initial time of the entire heating period, for example, a time length corresponding to about half of the heating period, may correspond to an “early part of the heating period”, and the other time lengths may correspond to a “latter half of the heating period”.

[0124] As the first capsule **16-1** and the second capsule **16-2** are crushed at different times, the first material and the second material may be released at different times. Because the first material and the second material are released at different times, an active material (e.g., a flavoring material, nicotine, etc.) may be prevented from being depleted in the latter half of the heating period.

[0125] For example, when the first material includes a different flavoring material from the second material, an aerosol having different flavors depending on times of crushing of respective capsules may be provided. For example, when the first capsule **16-1** is crushed at the beginning of the heating period and the second capsule **16-2** is crushed at the latter half of the heating period, an aerosol to which flavor of the first material is added may be provided at the beginning of the heating period, and an aerosol to which flavor of the second material is added may be provided at the latter half of the heating period.

[0126] The first capsule **16-1** may be located upstream from the second capsule **16-2** and may be crushed earlier than the second capsule **16-2**. As the capsule located upstream is crushed earlier than the capsule located downstream, flavors added to an aerosol may be prevented from being mixed together.

[0127] For example, when the second capsule **16-2** located downstream is crushed in the beginning of the heating period and the first capsule **16-1** located upstream is crushed in the latter half of the heating period, the first material released in the latter half of the heating period may pass through the second capsule **16-2** together with an aerosol. Therefore, a problem that the first material is

mixed with the second material may occur.

[0128] In contrast to this, when the first capsule **16-1** located upstream is crushed in the beginning of the heating period and the second capsule **16-2** located downstream is crushed in the latter half of the heating period, the second material released in the latter half of the heating period does not pass through the first capsule **16-1**, and accordingly, the problem that the first material is mixed with the second material may be prevented.

[0129] The first microwave-responsive material may include a different material from the second microwave-responsive material. For example, the first microwave-responsive material may include glycerin, and the second microwave-responsive material may include propylene glycol.

Accordingly, a heating speed of the first microwave-responsive material which is heated by microwaves is different from a heating speed of the second microwave-responsive material which is heated by microwaves, and as a result, the first capsule **16-1** may be crushed at different times from the second capsule **16-2**.

[0130] The first shell and the second shell may each include the same material as the microwave-responsive material, but may have different contents from each other. For example, the first microwave-responsive material and the second microwave-responsive material may each include glycerin, the first core may include glycerin with about 35 wt % to about 40 wt % of the total weight of the first core, and the second core may include glycerin with about 20 wt % to about 25 wt % of the total weight of the second core. Accordingly, the first core having a large content of microwave-responsive material may react more sensitively to microwaves than the second core having a small content of microwave-responsive material, and as a result, the first capsule **16-1** may be crushed earlier than the second capsule **16-2**.

[0131] FIG. 2 to FIG. 4 illustrate examples in which the aerosol generating article **10** has a rod shape, but the embodiments are not limited thereto. For example, the aerosol generating article may have a sheet shape. The aerosol generating article having a sheet shape may have a circular cross-section when viewed in a direction perpendicular to the longitudinal direction of the aerosol generating article. However, the aerosol generating article is not limited thereto and may have a polygonal shape including a triangle, a rectangle, a square, and a pentagon.

[0132] The aerosol generating article having a sheet shape may include a sheet of an aerosol generating substrate and the first capsule disposed on the sheet of the aerosol generating substrate. The aerosol generating article having a sheet shape may have a thickness of about 1 mm to about 20 mm. For example, the aerosol generating article having a sheet shape may have a thickness of about 5 mm to about 15 mm. A diameter of the first capsule included in the aerosol generating article having a sheet shape may be less than a thickness of the aerosol generating article. For example, the aerosol generating article having a sheet shape may have a thickness of about 5 mm to about 10 mm, and a diameter of the first capsule may be about 1 mm to about 3.5 mm.

[0133] A sheet of an aerosol generating substrate may be a solid member including an aerosol generating material. The first capsule may be disposed inside a solid member including an aerosol generating material. The solid member including an aerosol generating material may include a tobacco material. For example, the solid member including an aerosol generating material may be an integrated tobacco solid member.

[0134] For example, the aerosol generating article having a sheet shape may be manufactured by using a manufacturing method including a step of preparing a tobacco composition including tobacco powder, a binder, and an aerosol generating material, a step of inserting the tobacco composition into a frame having a sheet shape, a step of inserting the first capsule into the tobacco composition inserted in the frame having a sheet shape, and a step of drying the tobacco composition in which the first capsule is inserted.

[0135] The sheet of the aerosol generating substrate may have a porous structure including a plurality of pores. For example, the sheet of the aerosol generating substrate may include a porous tobacco solid member. For example, the sheet of the aerosol generating substrate may have a

specific surface area of 200 m.sup.2/g to 1,000 m.sup.2/g. In addition, the sheet of the aerosol generating substrate may have a specific surface area of 300 m.sup.2/g to 800 m.sup.2/g.

[0136] FIG. 5 is a perspective view of an aerosol generating device according to an embodiment.

[0137] Referring to FIG. 5, an aerosol generating device **100** according to an embodiment may include a housing **110**, which may accommodate an aerosol generating article **10**, and a heater assembly **200** for heating the aerosol generating article **10** accommodated in the housing **110**.

[0138] The housing **110** may form the entire appearance of the aerosol generating device **100**, and components of the aerosol generating device **100** may be arranged in an internal space (or a “mounting space”) of the housing **110**. For example, a heater assembly **200**, a battery, a processor, and/or a sensor may be arranged in the internal space of the housing **110**, but the components arranged in the internal space of the housing **110** are not limited thereto.

[0139] An insertion hole **110h** may be formed in one region of the housing **110**, and at least one region of an aerosol generating article **10** may be inserted into the housing **110** through the insertion hole **110h**. For example, the insertion hole **110h** may be formed in one region of an upper surface (for example, a surface facing the z direction) of the housing **110**, but the position of the insertion hole **110h** is not limited thereto. In another embodiment, the insertion hole **110h** may also be formed in one region of a side surface (for example, a surface facing the x direction) of the housing **110**.

[0140] The heater assembly **200** is arranged in the interior space of the housing **110** and may heat the aerosol generating article **10** inserted or accommodated in the housing **110** through the insertion hole **110h**. For example, the heater assembly **200** may surround at least a part of the aerosol generating article **10** inserted or accommodated in the housing **110** to heat the aerosol generating article **10**.

[0141] According to an embodiment, the heater assembly **200** may heat the aerosol generating article **10** by using a dielectric heating method. In the disclosure, the “dielectric heating method” means a method of heating a dielectric, which is a heating target, by using resonance of microwaves and/or an electric field (or a magnetic field) of the microwaves. The microwaves are used as an energy source for heating a heating target and generated by high-frequency power, and accordingly, the microwaves may be used interchangeably with microwave power below.

[0142] Electric charges or ions of a dielectric included in the aerosol generating article **10** may vibrate or rotate due to microwave resonance inside the heater assembly **200**, and heat is generated in the dielectric due to the frictional heat generated while the electric charges or ions vibrate or rotate, and accordingly, the aerosol generating article **10** may be heated.

[0143] As the aerosol generating article **10** is heated by the heater assembly **200**, an aerosol may be generated from the aerosol generating article **10**. In the disclosure, an “aerosol” may mean gas particles generated by mixing air and vapor generated as the aerosol generating article **10** is heated.

[0144] The aerosol generated from the aerosol generating article **10** may pass through the aerosol generating article **10** or may be discharged to the outside of the aerosol generating device **100** through an empty space between the aerosol generating article **10** and the insertion hole **110h**. A user may smoke by bringing their mouth into contact with a region of the aerosol generating article **10** exposed to the outside of the housing **110** and inhaling the aerosol discharged to the outside of the aerosol generating device **100**.

[0145] The aerosol generating device **100** according to the embodiment may further include a cover **111** that is movably arranged in the housing **110** to open or close the insertion hole **110h**. For example, the cover **111** may be slidably coupled to an upper surface of the housing **110** and may expose the insertion hole **110h** to the outside of the aerosol generating device **100** or cover the insertion hole **110h** such that the insertion hole **110h** is not exposed to the outside of the aerosol generating device **100**.

[0146] In one example, the cover **111** may expose the insertion hole **110h** to the outside of the aerosol generating device **100** at a first position (or an “open position”). When the aerosol

generating device **100** is exposed to the outside, the aerosol generating article **10** may be inserted into the housing **110** through the insertion hole **110h**.

[0147] In another example, the cover **111** may cover the insertion hole **110h** at a second position (or a “closed position”), and accordingly, the insertion hole **110h** may be prevented from being exposed to the outside of the aerosol generating device **100**. In this case, the cover **111** may prevent an external foreign material from being introduced into the heater assembly **200** through the insertion hole **110h** when the aerosol generating device **100** is not in use.

[0148] An aerosol generating device according to another embodiment includes the heater assembly **200** for heating the aerosol generating article **10** and an aerosol generating material in a liquid or gel state, and may also include a cartridge (or a “vaporizer”) for heating the aerosol generating material. An aerosol generated from the aerosol generating material may move to the aerosol generating article **10** through an airflow passage connecting the cartridge to the aerosol generating article **10**, be mixed with the aerosol generated from the aerosol generating article **10**, and then pass through the aerosol generating article **10** to be transferred to a user.

[0149] FIG. **6** is an internal block diagram of an aerosol generating device according to an embodiment.

[0150] Referring to FIG. **6**, an aerosol generating device **100** may include an input unit **102**, an output unit **103**, a sensor **104**, a communication unit **105**, a memory **106**, a battery **107**, an interface **108**, a power converter **109**, and a dielectric heater **200**. However, an internal configuration of the aerosol generating device **100** is not limited to the configuration illustrated in FIG. **6**. Depending on designs of the aerosol generating device **100**, some of components illustrated in FIG. **6** may be omitted, or new components may be added to the aerosol generating device **100**.

[0151] The input unit **102** may receive a user input. For example, the input unit **102** may be provided as a single pressure push button. In another example, the input unit **102** may be a touch panel including at least one touch sensor. The input unit **102** may transmit an input signal to the processor **101**. The processor **101** may supply power to the dielectric heater **200** based on user input, or control the output unit **103** such that a user notification is output.

[0152] The output unit **103** may output information on a state of the aerosol generating device **100**. The output unit **103** may output charging and discharging states of the battery **107**, a heating state of the dielectric heater **200**, an insertion state of the aerosol generating article **10**, and error information of the aerosol generating device **100**. To this end, the output unit **103** may include a display, a haptic motor, and an audio output unit.

[0153] The sensor **104** may detect a state of the aerosol generating device **100** or an ambient state of the aerosol generating device **100** and transmit the detected information to the processor **101**. The processor **101** may control the aerosol generating device **100** to perform various functions, such as heating control of the dielectric heater **200**, smoking restriction, determining whether the aerosol generating article **10** is inserted, and displaying a notification based on the detected information.

[0154] The sensor **104** may include a temperature sensor, a puff sensor, and an insertion detection sensor.

[0155] The temperature sensor may detect the temperature inside the dielectric heater **200** in a non-contact manner, or may directly obtain the temperature of a resonator by coming into contact with the dielectric heater **200**. According to an embodiment, the temperature sensor may also detect the temperature of the aerosol generating article **10**. Also, the temperature sensor may be arranged adjacent to the battery **107** to obtain the temperature of the battery **107**. The processor **101** may control the power supplied to the dielectric heater **200** based on temperature information of the temperature sensor.

[0156] The puff sensor may detect a user's puff. The puff sensor may detect a user's puff based on at least one of a temperature change, a flow amount change, a power change, and a pressure change. The processor **101** may control the power supplied to the dielectric heater **200** based on

puff information of the puff sensor. For example, the processor **101** may count the number of puffs and disconnect the power supplied to the dielectric heater **200** when the number of puffs reaches a preset maximum number of puffs. In another example, the processor **101** may disconnect the power supplied to the dielectric heater **200** when no puff is detected for a preset time or more.

[0157] The insertion detection sensor may be arranged inside an accommodation space **220h** (see FIG. **9**) or adjacent to the accommodation space **220h** and detect insertion and removal of the aerosol generating article **10** accommodated in the insertion hole **110h**. For example, the insertion detection sensor may include an inductive sensor and/or a capacitance sensor. The processor **101** may supply power to the dielectric heater **200** when the aerosol generating article **10** is inserted into the insertion hole **110h**.

[0158] According to the embodiment, the sensor **104** may further include a reuse detection sensor, a motion detection sensor, a humidity sensor, a barometric pressure sensor, a magnetic sensor, a cover removal detection sensor, a position sensor (or a global positioning sensor (GPS)), a proximity sensor, and so on. Functions of the respective sensor may be intuitively inferred from names of the respective sensors, and accordingly, detailed descriptions thereof are omitted.

[0159] The communication unit **105** may include at least one communication module for communicating with an external electronic device. The processor **101** may control the communication unit **105** such that information on the aerosol generating device **100** is transmitted to an external electronic device. Also, the processor **101** may receive information from the external electronic device through the communication unit **105** and control components included in the aerosol generating device **100**. For example, the information transmitted between the communication unit **105** and the external electronic device may include user authentication information, firmware update information, user smoking pattern information, and so on.

[0160] The memory **106** is a hardware that stores various types of data processed by the aerosol generating device **100**, and may store the data processed by the processor **101** and the data to be processed by the processor **101**. For example, the memory **106** may store operation times of the aerosol generating device **100**, the greatest number of puffs, the current number of puffs, at least one temperature profile, data on a user's smoking pattern, and so on.

[0161] The battery **107** may supply power to the dielectric heater **200** such that the aerosol generating article **10** may be heated. Also, the battery **107** may supply power required for operations of the other components provided in the aerosol generating device **100**. The battery **107** may be a rechargeable battery or a detachable and removable battery.

[0162] The interface **108** may include a connection terminal that may be physically connected to an external electronic device. The connection terminal may include at least one or a combination of a high-definition multimedia interface (HDMI) connector, a Universal Serial Bus (USB) connector, a secure digital (SD) card connector, or an audio connector (for example, a headphones connector). The interface **108** may transmit and receive information to and from an external electronic device through the connection terminal, or may charge power.

[0163] The power converter **109** may convert direct current (DC) power supplied from the battery **107** into alternating current (AC) power. Also, the power converter **109** may provide the AC power to the dielectric heater **200**. The power converter **109** may be an inverter including at least one switching element, and the processor **101** may control turning the switching element included in the power converter **109** on or off to convert DC power into AC power. The power converter **109** may be configured by a full bridge or a half bridge.

[0164] The dielectric heater **200** may heat the aerosol generating article **10** by using a dielectric heating method. The dielectric heater **200** may correspond to the heater assembly **200** of FIG. **5**.

[0165] The dielectric heater **200** may heat the aerosol generating article **10** by using microwaves and/or an electric field of the microwaves (hereinafter, referred to as microwaves or microwave power when there is no need for distinction). A heating method of the dielectric heater **200** may be a method of heating a heating target by forming microwaves in a resonance structure, rather than a

method of radiating microwaves by using an antenna. The resonance structure is described below with reference to FIG. 8 and below.

[0166] The dielectric heater **200** may output high-frequency microwaves to a resonator **220** (see FIG. 7). The microwaves may be power in an industrial scientific and medical (ISM) equipment band allowed for heating but are not limited thereto. The resonator **220** may be designed by considering wavelengths of the microwaves such that the microwaves may resonate within the resonator **220**.

[0167] The aerosol generating article **10** may be inserted into the resonator **220**, and a dielectric material in the aerosol generating article **10** may be heated by the resonator **220**. For example, the aerosol generating article **10** may include a polar material, and molecules in the polar material may be polarized in the resonator **220**. The molecules may vibrate or rotate due to a polarization phenomenon, and the aerosol generating article **10** may be heated by frictional heat generated during the vibration or rotation of the molecules. The dielectric heater **200** is described in more detail below with reference to FIG. 7.

[0168] The processor **101** may control all operations of the aerosol generating device **100**. The processor **101** may be implemented by an array of a plurality of logic gates, or may be implemented by a combination of a general-purpose microprocessor and a memory storing a program that may be executed by the general-purpose microprocessor. Also, the processor **101** may be implemented by another type of hardware.

[0169] The processor **101** may control the DC power supplied from the battery **107** to the power converter **109** according to the power demand of the dielectric heater **200**, and/or the AC power supplied from the power converter **109** to the dielectric heater **200**. In one embodiment, the aerosol generating device **100** may include a converter that boosts or lowers DC power, and the processor **101** may adjust a level of the DC power by controlling the converter. Also, the processor **101** May control the AC power supplied to the dielectric heater **200** by adjusting a switching frequency and duty ratio of a switching element included in the power converter **109**.

[0170] The processor **101** may control a heating temperature of the aerosol generating article **10** by controlling microwave power of the dielectric heater **200** and a resonance frequency of the dielectric heater **200**. Therefore, an oscillator **210**, an isolator **240**, a power monitor **250**, and a matching transformer **260** illustrated in FIG. 7 and described below may also be components of the processor **101**.

[0171] The processor **101** may control microwave power of the dielectric heater **200** based on temperature profile information stored in the memory **106**. That is, the temperature profile may include information on a target temperature of the dielectric heater **200** over time, and the processor **101** may control the microwave power of the dielectric heater **200** over time.

[0172] The processor **101** may adjust the frequency of a microwave such that the resonance frequency of the dielectric heater **200** is constant. The processor **101** may track the change in resonance frequency of the dielectric heater **200** in real time according to the heating of a heating target and control the dielectric heater **200** such that the microwave frequency according to the changed resonance frequency is output. That is, the processor **101** may change the microwave frequency in real time regardless of the pre-stored temperature profile.

[0173] FIG. 7 is an internal block diagram of the dielectric heater **200** of FIG. 6.

[0174] Referring to FIG. 7, the dielectric heater **200** may include the oscillator **210**, the isolator **240**, the power monitor **250**, the matching transformer **260**, a microwave output unit **230**, and a resonator **220**. However, an internal configuration of the dielectric heater **200** is not limited to the configuration illustrated in FIG. 7. Depending on designs of the dielectric heater **200**, some of the components illustrated in FIG. 7 may be omitted, or new components may be added to the dielectric heater **200**.

[0175] The oscillator **210** may receive AC power from the power converter **109** and generate high-frequency microwave power. According to an embodiment, the power converter **109** may be

included in the oscillator **210**. The microwave power may be selected from among 915 MHz, 2.45 GHz, and 5.8 GHz frequency bands included in an ISM band.

[0176] The oscillator **210** may include a solid-state-based RF generation device and generate microwave power by using the solid-state-based RF generation device. The solid-state-based RF generation device may be implemented by a semiconductor. When the oscillator **210** is implemented by a semiconductor, there is an advantage in that the dielectric heater **200** is reduced in size and increases in lifespan.

[0177] The oscillator **210** may output microwave power to the resonator **220**. The oscillator **210** may include a power amplifier that increases or decreases the microwave power, and the power amplifier may adjust the microwave power under the control by the processor **101**. For example, the power amplifier may decrease or increase an amplitude of a microwave. By adjusting the amplitude of the microwave, the microwave power may be adjusted.

[0178] The processor **101** may adjust the microwave power output from the oscillator **210** based on a pre-stored temperature profile. For example, the temperature profile may include target temperature information according to a preheating period and a smoking period, and the oscillator **210** may supply microwave power as first power in the preheating period and supply microwave power as second power that is less than the first power in the smoking period.

[0179] The isolator **240** may block the microwave power input from the resonator **220** to the oscillator **210**. Most of the microwave power output from the oscillator **210** is absorbed by a heating target, but depending on heating patterns of the heating target, a part of the microwave power may be reflected by the heating target and transmitted again to the oscillator **210**. This is because the impedance viewed from the oscillator **210** toward the resonator **220** changes due to the depletion of polar molecules according to the heating of the heating target. The meaning of “impedance viewed from the oscillator **210** toward the resonator **220** changes” may be the same as the meaning of “a resonance frequency of the resonator **220** changes”. When the microwave power reflected from the resonator **220** is input to the oscillator **210**, the oscillator **210** may fail, and the expected output performance may not be achieved. The isolator **240** may absorb the microwave power reflected from the resonator **220** by guiding the microwave power in a preset direction without returning the microwave power to the oscillator **210**. Due to this, the isolator **240** may include a circulator and a dummy load.

[0180] The power monitor **250** may monitor both the microwave power output from the oscillator **210** and the microwave power reflected from the resonator unit **220**. The power monitor **250** may transmit information on the microwave power and the reflected microwave power to the matching transformer **260**.

[0181] The matching transformer **260** may match the impedance of the resonator **220** viewed from the oscillator **210** to the impedance of the oscillator **210** viewed from the resonator **220** such that the reflected microwave power is reduced. Impedance matching may have the same meaning as matching the frequency of the oscillator **210** to the resonance frequency of the resonator **220**. Therefore, the matching transformer **260** may vary the frequency of the oscillator **210** to match the impedance of the matching transformer **260**. That is, the matching transformer **260** may adjust the frequency of the microwave power output from the oscillator **210** such that the reflected microwave power is reduced. The impedance matching of the matching transformer **260** may be performed in real time regardless of a temperature profile.

[0182] In addition, the oscillator **210**, the isolator **240**, the power monitor **250**, and the matching transformer **260** described above may be separate components from the microwave output unit **230** and resonator **220** described below, and may be implemented as a microwave source in the form of a chip. Also, according to an embodiment, the oscillator **210**, the isolator **240**, the power monitor **250**, and the matching transformer **260** described above may also be implemented as a part of the processor **101**.

[0183] The microwave output unit **230** may cause microwave power to be input to the resonator

220 and may correspond to a coupler of FIG. 7 and below. The microwave output unit **230** may be implemented in the form of an SMA, SMB, MCX, or MMCX connector. The microwave output unit **230** may connect a chip-shaped microwave source to the resonator **220**, and accordingly, the microwave power generated by the microwave source may be transmitted to the resonator **220**.

[0184] The resonator **220** may heat a heating target by forming microwaves within a resonance structure. The resonator **220** may include an accommodation space in which the aerosol generating article **10** is accommodated, and the aerosol generating article **10** may be exposed to microwaves to be dielectrically heated. For example, the aerosol generating article **10** may include a polar material, and molecules in the polar material may be polarized by the microwaves within the resonator **220**. The molecules may vibrate or rotate due to a polarization phenomenon, and the aerosol generating article **10** may be heated by frictional heat generated during the vibration or rotation of the molecules.

[0185] The resonator **220** may include at least one internal conductor such that microwaves may resonate, and the microwaves may resonate in the resonator **220** according to an arrangement, a thickness, a length, and so on of the internal conductor.

[0186] The resonator **220** may be designed by considering wavelengths of microwaves such that the microwaves may resonate in the resonator **220**. In order for microwaves to resonate in the resonator **220**, a short end having a closed cross-section and an open end having at least one region of a cross-section opened in an opposite direction to the closed end are required. Also, a length between the short end and the open end has to be set to an integer multiple of a quarter wavelength of a microwave. The resonator **220** according to the disclosure selects a quarter wavelength of a microwave to reduce a size of a device. That is, the length between the short end and the open end of the resonator **220** may be set to a quarter wavelength of a microwave.

[0187] The resonator **220** may include a dielectric accommodation space. The dielectric accommodation space **226** is different from the accommodation space of the aerosol generating article **10**, and a material that may change all resonance frequencies of the resonator **220** and reduce a size of the resonator **220** is provided in the dielectric accommodation space **226**. In one embodiment, a dielectric with a low microwave absorbance may be accommodated in the dielectric accommodation space **226**. This is to prevent the phenomenon in which energy that has to be transferred to a heating target is transferred to a dielectric and the dielectric itself is heated. A microwave absorbance may be represented as a loss tangent, which is a ratio of a real part a complex dielectric constant to an imaginary part of the complex dielectric constant. In one embodiment, a dielectric with a loss tangent less than a preset size may be accommodated in the dielectric accommodation space **226**, and the preset size may be 1/100. For example, the dielectric may be at least one of quartz, tetrafluoroethylene, and aluminum oxide, or a combination thereof but is not limited thereto.

[0188] FIG. 8 is a perspective view of a heater assembly according to an embodiment.

[0189] Referring to FIG. 8, a heater assembly **200** according to an embodiment may include an oscillator **210** and a resonator **220**. An aerosol generating article **10** illustrated in FIG. 8 may refer to the aerosol generating article **10** illustrated in FIG. 2. FIG. 8 may be an example of the heater assembly **200** and the dielectric heater **200** described above, and redundant descriptions thereof are omitted below.

[0190] The oscillator **210** may generate microwaves of a designated frequency band when power is supplied to the oscillator **210**. The microwaves generated by the oscillator **210** may be transmitted to the resonator **220** through a coupler (not illustrated).

[0191] The resonator **220** may include an accommodation space **220h** for accommodating at least one region of the aerosol generating article **10** and may heat the aerosol generating article **10** in a dielectric heating manner by resonating the microwaves generated by the oscillator **210**. For example, electric charges of an aerosol generating material included in the aerosol generating article **10** may vibrate or rotate according to the resonance of the microwaves, and the aerosol

generating material may be heated by the frictional heat generated when the electric charges vibrate or rotate, and accordingly, the aerosol generating article **10** may be heated.

[0192] According to an embodiment, the resonator **220** may be formed of a material with a low microwave absorption rate to prevent the microwave generated by the oscillator **210** from being absorbed by the resonator **220**.

[0193] Hereinafter, a specific structure of the resonator **220** of the heater assembly **200** is described with reference to FIG. **9**.

[0194] FIG. **9** is a cross-sectional view of the heater assembly **200** of FIG. **8**. FIG. **9** shows a cross-section of the heater assembly **200** of FIG. **8** taken along line A-A'.

[0195] Referring to FIG. **9**, the heater assembly **200** according to an embodiment may include an oscillator **210**, a resonator **220**, and a coupler **230**. Components of the heater assembly **200** may be the same as or similar to at least one of the components of the heater assembly **200** illustrated in FIG. **8**, and redundant descriptions thereof are omitted below.

[0196] The oscillator **210** may generate microwaves of a specified frequency band when an AC voltage is applied to the oscillator **210**, and the microwaves generated by the oscillator **210** may be transmitted to the resonator **220** through the coupler **230**.

[0197] According to an embodiment, the oscillator **210** may be fixed to the resonator **220** to prevent the oscillator **210** from being separated from the resonator **220** during use of an aerosol generating device. In one example, the oscillator **210** may be fixed onto the resonator **220** by being supported by a bracket **220b** protruding in the x direction in one region of the resonator **220**. In another example, the oscillator **210** may also be fixed onto the resonator **220** in a manner of being attached to one region of the resonator **220** without the bracket **220b**.

[0198] Although FIG. **9** illustrates only an embodiment in which the oscillator **210** is fixed to one region of the resonator **220** facing the x direction, a position of the oscillator **210** is not limited to the illustrated embodiment. In another embodiment, the oscillator **210** may also be fixed to another region of the resonator **220** facing the -z direction.

[0199] The resonator **220** may surround at least one region of the aerosol generating article **10** inserted in an aerosol generating device, and the aerosol generating article **10** may be heated by the microwaves generated by the oscillator **210**. For example, dielectric materials included in the aerosol generating article **10** may be heated by an electric field generated inside the resonator **220b** by microwaves, and the aerosol generating article **10** may be heated by the heat generated in the dielectric (that is, an aerosol generating material).

[0200] According to an embodiment, the resonator **220** may include an outer conductor **221**, a first inner conductor **223**, and a second inner conductor **225**.

[0201] The outer conductor **221** may form the entire appearance of the resonator **220**, and components of the resonator **220** having a hollow interior may be arranged inside the outer conductor **221**. The outer conductor **221** may include an accommodation space **220h** in which the aerosol generating article **10** may be accommodated, and the aerosol generating article **10** may be inserted into the outer conductor **221** through the accommodation space **220h**.

[0202] According to an embodiment, the outer conductor **221** may include a first surface **221a**, a second surface **221b** facing the first surface **221a**, and a side surface **221c** surrounding a free space between the first surface **221a** and the second surface **221b**. At least some (for example, the first inner conductor **223** and the second inner conductor **225**) of the components of the resonator **220** may be arranged in an internal space of the resonator **220** which is formed by the first surface **221a**, the second surface **221b**, and the side surface **221c**.

[0203] The first inner conductor **223** is formed in a hollow cylindrical shape extending in a direction from the first surface **221a** of the outer conductor **221** toward an internal space of the outer conductor **221**, and when the microwaves generated by the oscillator **210** is transmitted, an electric field may be generated inside the first inner conductor **223**. According to an embodiment, the first inner conductor **223** may also be referred to as a “first resonator” that generates an electric

field through resonance of microwaves.

[0204] According to an embodiment, one region of the first inner conductor **223** may be in contact with the coupler **230** connected to the oscillator **210**, and as the microwaves transmitted through the coupler **230** resonate, an electric field may be generated inside the first inner conductor **223**. For example, the coupler **230** may pass through the outer conductor **221**, one end of the coupler **230** may be in contact with the oscillator **210**, and the other end of the coupler **230** may be in contact with one region of the first inner conductor **223**, and as microwaves generated by the oscillator **210** are transmitted to the first inner conductor **223** through the coupler **230**, an electric field may be generated inside the first inner conductor **223**.

[0205] The second inner conductor **225** may be formed in a hollow cylindrical shape extending from the second surface **221b** of the outer conductor **221** toward an inner space of the outer conductor **221**. The second inner conductor **225** may be arranged in the inner space of the outer conductor **221** to be separated from the first inner conductor **223** by a preset distance, and there may be a gap **227** between the first inner conductor **223** and the second inner conductor **225**.

[0206] Inductive coupling may be made between the second inner conductor **225** and the first inner conductor **223**, and accordingly, when an electric field is generated inside the first inner conductor **223**, an induced electric field may also be generated inside the second inner conductor **225**. In the disclosure, the “inductive coupling” may mean a coupling relationship in which energy may be magnetically transferred by mutual inductance between two conductors.

[0207] For example, when the microwaves generated by the oscillator **210** are transmitted to the first internal conductor **223**, an electric field may be generated inside the first internal conductor **223** by resonance, and an induced electric field may be generated inside a second internal conductor **225** inductively coupled to the first internal conductor **223**. According to an embodiment, the second internal conductor **225** may also be referred to as a “second resonator” that generates an electric field through resonance of microwaves.

[0208] According to an embodiment, the resonator **220** may include a short end having a closed cross-section to have a quarter length ($\lambda/4$) of a wavelength λ of a microwave, and an open end that is placed on an opposite side of the short end and that has a cross-section of which at least one region is opened.

[0209] In one example, the resonator **220** may include a closing portion **224** placed inside the first inner conductor **223** and closing a cross-section of the first inner conductor **223**, and as a cross-section of the first inner conductor **223** is closed by the closing portion **224**, a short end may be formed in a first region **2231** of the first inner conductor **223** where the closing portion **224** is arranged. The closing portion **224** is not in a second region **2232** spaced apart from the first region **2231** of the first inner conductor **223**, and accordingly, a cross-section of the second region **2232** may be opened, and as a result, an open end may be formed in the second region **2232** of the first inner conductor **223**. That is, when viewed from an xz plane, the first internal conductor **223** may be formed in a “ㄱ” (Korean alphabet) shape on the whole and include a short end and an open end, and according to a structure of the first internal conductor **223** described above, the first internal conductor **223** may operate as a resonator having a quarter wavelength of a microwave.

[0210] In another example, the accommodation space **220h** may be formed in one region of the second internal conductor **225** which faces the short end, and accordingly, a cross-section of the second internal conductor **225** may be opened, and as a result, when viewing the resonator **220** on the whole, a short end may be formed in the first region **2231** of the first internal conductor **223**, and an open end may be formed in one end of the second internal conductor **225** which faces the short end, and accordingly, resonance of a quarter wavelength may be generated inside the resonator **220**.

[0211] According to the resonance structure of the resonator **220** described above, an electric field may not be transferred to an external region of the resonator **220** where there is no conductor, such as the first internal conductor **223** or the second internal conductor **225**. Therefore, the heater

assembly **200** may prevent an electric field from leaking to the outside of the heater assembly **200** without a separate shielding member for shielding the electric field.

[0212] The aerosol generating article **10** inserted into the internal space of the outer conductor **221** through the accommodation space **220h** may be surrounded by the first internal conductor **223** and the second internal conductor **225** to be heated by a dielectric heating method. For example, a part of the aerosol generating article **10** inserted into the inner space of the outer conductor **221** may be arranged inside the first inner conductor **223** and the second inner conductor **225**, and another part thereof may be arranged outside the first inner conductor **223** and the second inner conductor **225**. When a dielectric included in the aerosol generating article **10** is heated by an electric field generated inside and outside the first inner conductor **223** and/or the second inner conductor **225**, the aerosol generating article **10** may be heated.

[0213] According to an embodiment, when the aerosol generating article **10** is inserted into the resonator **220** through the accommodation space **220h**, the aerosol generating rod **11** of the aerosol generating article **10** may be at a position corresponding to the gap **227** between the first internal conductor **223** and the second internal conductor **225**.

[0214] A resonance peak may be generated in an end portion of the first internal conductor **223** operating as the first resonator and an end portion of the second internal conductor **225** operating as the second resonator, and accordingly, a stronger electric field may be generated in the end portions compared to other regions, and as a result, the strongest electric field may be generated in the gap **227** between the first internal conductor **223** and the second internal conductor **225** among the internal regions of the resonator **220**. In the heater assembly **200** according to an embodiment, the aerosol generating rod **11** including a dielectric that is heated by an electric field is arranged at a position corresponding to the gap **227** where the electric field is strongest, and accordingly, heating efficiency (or “dielectric heating efficiency”) of the heater assembly **200** may be increased.

[0215] According to an embodiment, the resonator **220** may further include the dielectric accommodation space **226** for accommodating a dielectric. The dielectric accommodation space **226** may be formed in a space between the outer conductor **221**, the first inner conductor **223**, and the second inner conductor **225**, and a dielectric with a low microwave absorbance may be accommodated in the dielectric accommodation space **226**. For example, the dielectric may be formed of at least one of quartz, tetrafluoroethylene, and aluminum oxide, or a combination thereof but is not limited thereto.

[0216] The heater assembly **200** according to an embodiment may generate an electric field similar to the electric field of the resonator **220** that does not include a dielectric by arranging a dielectric inside the dielectric accommodation space **226** and may reduce the entire size of the resonator **220**. That is, in the heater assembly **200** according to an embodiment, a size of the resonator **220** may be reduced through the dielectric arranged inside the dielectric accommodation space **226**, and a mounting space of the resonator **220** in an aerosol generating device may be reduced, and as a result, the aerosol generating device may be miniaturized.

[0217] FIG. **10** is a perspective view schematically illustrating a heater assembly according to another embodiment.

[0218] A heater assembly **300** according to the embodiment illustrated in FIG. **10** may include a resonator **320** that generates microwave resonance, and a coupler **311** that supplies microwaves to the resonator **320**. An aerosol generating article **10** illustrated in FIG. **10** may refer to the aerosol generating article **10** illustrated in FIG. **2**.

[0219] The resonator **320** may include a case **321**, a plurality of plates **323a** and **323b**, and a connector **322** that connects the plurality of plates **323a** and **323b** to the case **321**.

[0220] The coupler **311** may supply microwaves to at least one of the plurality of plates **323a** and **323b** to generate microwave resonance in the resonator **320**.

[0221] The resonator **320** may surround at least one region of the aerosol generating article **10** inserted into the aerosol generating device **100**. The coupler **311** may supply the microwaves

generated by an oscillator (not illustrated) to the resonator **320**. When microwaves are supplied to the resonator **320**, microwave resonance occurs in the resonator **320**, and accordingly, the resonator **320** may heat the aerosol generating article **10**. For example, dielectrics included in the aerosol generating article **10** may be heated by an electric field generated inside the resonator **220** by microwaves, and the aerosol generating article **10** may be heated by the heat generated by the dielectrics.

[0222] The case **321** of the resonator **320** functions as an “outer conductor”. The case **321** has a hollow shape in which the inside of the case **321** is empty, and accordingly, components of the resonator **320** may be arranged inside the case **321**.

[0223] The case **321** may include an accommodation space **320h** in which the aerosol generating article **10** may be accommodated, and an opening **321a** into which the aerosol generating article **10** may be inserted. The opening **321a** may be connected to the accommodation space **320h**. The opening **321a** is opened toward the outside of the case **321**, and accordingly, the accommodation space **320h** may be connected to the outside through the opening **321a**. Therefore, the aerosol generating article **10** may be inserted into the accommodation space **320h** of the case **321** through the opening **321a** of the case **321**.

[0224] Although FIG. **10** illustrates that the case **321** has a square cross-sectional shape, the shape of the case **321** may be changed to various shapes. For example, the case **321** may have one of various cross-sectional shapes, such as a rectangle, an ellipse, or a circle. The case **321** may extend in one direction.

[0225] The plurality of plates **323a** and **323b** that may function as an “internal conductor” of the resonator **320** may be arranged inside the case **321**.

[0226] The plurality of plates **323a** and **323b** may be arranged to be separated from each other in a circumferential direction of the aerosol generating article **10** accommodated in the accommodation space **320h**. The plurality of plates **323a** and **323b** may include a first plate **323a** surrounding one region of the aerosol generating article **10** and a second plate **323b** surrounding another region of the aerosol generating article **10**.

[0227] The plurality of plates **323a** and **323b** may be connected to the case **321** through the connector **322**. Also, one end of the first plate **323a** may be connected to one end of the second plate **323b** by the connector **322**. Therefore, closed ends may be formed at ends of the plurality of plates **323a** and **323b** by the connector **322**.

[0228] An end **323af** of the first plate **323a** and an end **323bf** of the second plate **323b** may be separated from each other and be opened. Because the ends **323af** and **323bf** are separated from each other, open ends may be formed at the other ends of the plurality of plates **323a** and **323b**.

[0229] A resonator assembly may be completed by connecting the plurality of plates **323a** and **323b** to the connector **322**. A shape of a cross-section taken along a longitudinal direction of the resonator assembly may include a “horseshoe-shape”.

[0230] The plurality of plates **323a** and **323b** may extend toward a longitudinal direction of the aerosol generating article **10**. At least a part of each of the plurality of plates **323a** and **323b** may be curved to protrude outwardly from the center of the longitudinal direction of the aerosol generating article **10**.

[0231] For example, when the aerosol generating article **10** has a cylindrical shape, the plurality of plates **323a** and **323b** may be curved in a circumferential direction along an outer circumferential surface of the aerosol generating article **10**. A radius of curvature of a cross-section of each of the plurality of plates **323a** and **323b** may be equal to a radius of curvature of the aerosol generating article **10**. The radius of curvature of the cross-section of each of the plurality of plates **323a** and **323b** may be variously modified. For example, the radius of curvature of the cross-section of each of the plurality of plates **323a** and **323b** may be greater or less than the radius of curvature of the aerosol generating article **10**.

[0232] According to the structure in which the plurality of plates **323a** and **323b** are curved in a

circumferential direction along an outer circumferential surface of the aerosol generating article **10**, a more uniform electric field is formed in the resonator **320**, and accordingly, the heater assembly **300** may uniformly heat the aerosol generating article **10**.

[0233] The open ends of the ends **323af** and **323bf** of the plurality of plates **323a** and **323b** may face the opening **321a** of the case **321**. The opening **321a** of the case **321** may be separated from the ends **323af** and **323bf** of the plurality of plates **323a** and **323b** to be far away therefrom.

[0234] The open ends of the ends **323af** and **323bf** of the plurality of plates **323a** and **323b** may be aligned with respect to the opening **321a** of the case **321**. Therefore, when the aerosol generating article **10** is inserted into the accommodation space **320h** through the opening **321a** of the case **321**, a part of the aerosol generating article **10** which is placed in the accommodation space **320h** may be surrounded by the plurality of plates **323a** and **323b**.

[0235] The plurality of plates **323a** and **323b** are arranged on an opposite side of the center of a longitudinal direction of the aerosol generating article **10**. The embodiments are not limited to the number of the plurality of plates **323a** and **323b**, and the number of the plurality of plates **323a** and **323b** may be, for example, three, four, or more.

[0236] The plurality of plates **323a** and **323b** may be arranged to be symmetrical to a central axis of a longitudinal direction of the aerosol generating article **10**, that is, a direction in which the aerosol generating article **10** extends.

[0237] At least one of the plurality of plates **323a** and **323b** may be in contact with the coupler **311** connected to an oscillator (not illustrated). Specifically, at least a part of the first plate **323a** may be in contact with the coupler **311**. As the microwaves transmitted to the first plate **323a** through the coupler **311** resonate in the plurality of plates **323a** and **323b**, an electric field may be generated in the plurality of plates **323a** and **323b** and the connector **322**.

[0238] The coupler **311** may pass through the case **321**, and accordingly, one end of the coupler **311** may be in contact with an oscillator (not illustrated), and the other end of the coupler **311** may be in contact with one region of the first plate **323a**. As the microwaves generated by the oscillator (not illustrated) are transmitted to the plurality of plates **323a** and **323b** and the connector **322** through the coupler **311**, an electric field may be generated inside an assembly of the plurality of plates **323a** and **323b** and the connector **322**.

[0239] Also, according to a structure of the resonator **320** of the heater assembly **300**, a triple resonance mode may be formed in the resonator **320**. Resonance of a transverse electric & magnetic (TEM) mode of microwaves is formed between the plurality of plates **323a** and **323b**. Also, resonances of the TEM mode different from the resonance formed between the plurality of plates **323a** and **323b** may be formed respectively between the first plate **323a** and an upper plate of the case **321** and between the second plate **323b** and a lower plate of the case **321**.

[0240] As triple resonance is generated in the resonator **320** of the heater assembly **300**, the aerosol generating article **10** may be heated more effectively and uniformly.

[0241] The resonator **320** according to the embodiment described above may include a short end of which cross-section is closed to have a quarter length $\lambda/4$ of a wavelength λ of a microwave, and an open end of which cross-section is in an opposite direction to the short end and at least one region is opened.

[0242] In FIG. **10**, a region of one end of the resonator **320** corresponding to a left region forms a short end closed by a structure in which one end of each of the plurality of plates **323a** and **323b** and the connector **322** are connected to the case **321**. In FIG. **10**, a region of the other end of the resonator **320** corresponding to a right region forms an open end by opening the opening **321a** of the case **321** to the outside. With the structure of the resonator **320**, the resonator **320** may operate as a resonator having a quarter wavelength of a microwave.

[0243] According to a resonance structure of the resonator **320** described above, an electric field may not be transferred to an external region of the resonator **320**. Therefore, the heater assembly **300** may prevent an electric field from leaking to the outside of the heater assembly **300** even

without a separate shielding member for shielding the electric field.

[0244] The aerosol generating article **10** inserted into the accommodation space **320h** of the case **321** may be surrounded by the first plate **323a** and the second plate **323b** to be heated by a dielectric heating method. For example, a part including a medium (for example, the aerosol generating rod **11**) of the aerosol generating article **10** inserted into the accommodation space **320h** of the case **321** may be arranged in a space between the first plate **323a** and the second plate **323b**. The aerosol generating article **10** may be heated when a dielectric included in the aerosol generating article **10** is heated by an electric field generated in a space between the first plate **323a** and the second plate **323b**.

[0245] When the aerosol generating article **10** is inserted into the resonator **320** through the accommodation space **320h**, the aerosol generating rod **11** of the aerosol generating article **10** may be placed between the plurality of plates **323a** and **323b**.

[0246] A length **L4** of the aerosol generating rod **11** may be greater than a lengths **L1** of each of the plurality of plates **323a** and **323b**. Therefore, a front end **11f** of the aerosol generating rod **11** in contact with the filter rod **12** may be placed at a position that protrudes more than the other end **323af** of the first plate **323a** and the other end **323bf** of the second plate **323b** in a direction toward the opening **321a** of the case **321**.

[0247] A resonance peak may be formed at the other end of each of the plurality of plates **323a** and **323b** that operate as resonators, and accordingly, a stronger electric field may be generated compared to other regions. When the aerosol generating article **10** is inserted into the heater assembly **300**, the aerosol generating rod **11** including a dielectric that may generate heat by an electric field may be arranged to correspond to a region where an electric field is strongest, and accordingly, heating efficiency (or “dielectric heating efficiency”) of the heater assembly **300** may be increased.

[0248] Also, in the aerosol generating article **10** illustrated in FIG. 3, the sum of lengths of the front end plug **13** and the aerosol generating rod **11** may be greater than the length **L1** of each of the plurality of plates **323a** and **323b**. That is, a length from an upstream end of the aerosol generating article **10** to a downstream end of the aerosol generating rod **11** may be greater than the length **L1** of each of the plurality of plates **323a** and **323b**.

[0249] Referring to FIG. 10, the length **L1** of each of the plurality of plates **323a** and **323b** may be less than a length **L1+L2** of an internal space of the case **321**. Therefore, the other ends of the plurality of plates **323a** and **323b** may be placed inside the case **321** rather than the opening **321a**. That is, the other ends of the plurality of plates **323a** and **323b** may be separated from a rear end of the opening **321a** by a distance **L2**.

[0250] A length from the rear end of the opening **321a** where the opening **321a** is connected to the case **321** to a front end of the opening **321a** where the opening **321a** is opened may be **L3**. A total length of the case **321** in the longitudinal direction of the case **321** may be **L**. An entire length **L** of the case **321** may be determined by the sum of the length **L1** of each of the plurality of plates **323a** and **323b**, the length **L2** which is a separated distance between the rear end of the opening **321a** and the plurality of plates **323a** and **323b**, and the length **L3** of a protrusion of the opening **321a** from the case **321**.

[0251] In order to prevent leakage of microwaves, the front end of the opening **321a** in which the opening **321a** is opened is placed at a position in which the opening **321a** protrudes from the case **321** by the length of **L3**. As the opening **321a** of the case **321** protrudes from the case **321**, the opening **321a** may function to prevent microwaves inside the case **321** of the resonator **320** from leaking to the outside of the case **321**.

[0252] The resonator **320** may further include a dielectric accommodation space **327** for accommodating a dielectric. The dielectric accommodation space **327** may be formed in a free space between the case **321** and the plurality of plates **323a** and **323b**. A dielectric with a low microwave absorbance may be accommodated in the dielectric accommodation space **327**.

[0253] By providing a dielectric inside the dielectric accommodation space **327**, the entire size of the resonator **320** of the heater assembly **300** may be reduced, and an electric field at the same level as the electric field generated by the resonator that does not include a dielectric may be generated. That is, a mounting space of the resonator **320** in an aerosol generating device may be reduced by reducing a size of the resonator **320** through a dielectric arranged inside the dielectric accommodation space **327**, and as a result, the aerosol generating device may be miniaturized.

[0254] An aerosol generating system according to an embodiment may include the aerosol generating article **10** and the aerosol generating device **100**. For example, the aerosol generating system according to an embodiment may include the aerosol generating article **10** of FIGS. 2 to 4 described above and the aerosol generating device **100** illustrated in FIGS. 5 to 10.

[0255] In the general aerosol generating system of the related art, a heating element surrounds an external portion of an aerosol generating article or is inserted into the aerosol generating article to heat the aerosol generating article. In this case, a region of the aerosol generating article which is close to a heating element may be heated to a relatively high temperature, and a region of the aerosol generating article which is relatively far from the heating element may be heated to a relatively low temperature.

[0256] For example, in an aerosol generating system in which a heating element surrounds the outside of an aerosol generating article, only an external region of the aerosol generating article may be intensively heated, and an internal region of the aerosol generating article may not be sufficiently heated. In another example, in an aerosol generating system in which a heating element is inserted into an aerosol generating article, only an internal region of an aerosol generating article may be intensively heated, and an external region of the aerosol generating article may not be sufficiently heated.

[0257] As an aerosol generating article is heated unevenly, an active ingredient (for example, nicotine and/or an aerosol generating material) in a region of the aerosol generating article which is heated to a relatively low temperature may not be completely transferred and may remain inside the aerosol generating article.

[0258] Also, as an aerosol generating article is heated unevenly, the amount of active ingredients of an aerosol transferred to a user may not be uniform in the entire heating period, and a taste of smoke may not be constant.

[0259] Also, in the general aerosol generating system of the related art, the temperature of an aerosol generating article increases as heat energy is conducted from a high-temperature heating element, and accordingly, a certain amount of preheating time may be required to heat the aerosol generating article. Also, an aerosol, which is generated at the beginning of a heating period in which the temperature of an aerosol generating article is not sufficiently increased, may not sufficiently include nicotine or an aerosol generating material.

[0260] Here, the “heating period” may mean a time length from a point in time when a heater assembly of an aerosol generating device starts heating to a point in time when the heating ends. Also, a time period corresponding to an initial part of the entire heating period, for example, a time period corresponding to about half of the heating period, may correspond to the “beginning of the heating period”, and the other time period may correspond to the “latter half of the heating period”.

[0261] In the aerosol generating system according to an embodiment, an aerosol generating material, which is a dielectric dispersed in a medium (for example, the aerosol generating rod **11** of FIGS. 2 and 4, or the front end plug **13** and the aerosol generating rod **11** of FIG. 3) of the aerosol generating article **10** is heated by a dielectric heating method, and thus, a problem of uneven heating of the aerosol generating article **10** may be resolved.

[0262] For example, in an aerosol generating system according to an embodiment, the aerosol generating article **10** may be uniformly heated, and thus, the amount of active ingredients (for example, nicotine and/or an aerosol generating material) of an aerosol transferred to a user may be constant throughout the entire heating period, and a taste of smoke may be provided with constant

quality. Also, the entire region of the aerosol generating article **10** is uniformly heated, and thus, most of the nicotine and/or aerosol generating material included in the aerosol generating article **10** may be transferred.

[0263] Also, a process of conducting heat energy from a heating element to the aerosol generating article **10** may be omitted, and thus, the time required for preheating may be reduced. Also, an aerosol generated at the beginning of a heating period of the aerosol generating article **10** included in an aerosol generating device may include a sufficient amount of nicotine and aerosol generating material.

[0264] Any of the embodiments or other embodiments of the disclosure described above are not mutually exclusive or distinct. Any of the embodiments or other embodiments of the disclosure described above may be combined or used together in respective configurations or functions thereof.

[0265] For example, a configuration A described in a certain embodiment and/or a drawing may be combined with a configuration B described in another embodiment and/or drawing. That is, even when coupling of configurations is not directly described, the coupling may be made except a case in which the coupling is described to be impossible.

[0266] The above detailed description should not be construed as limiting in all aspects and should be considered as illustrative. The scope of the disclosure should be determined by a reasonable interpretation of the appended claims, and all changes within the equivalent scope of the disclosure are included in the scope of the disclosure.

[0267] The entire region of an aerosol generating article according to the embodiments is uniformly heated, and thus, most of the active ingredients included in the aerosol generating article may be transferred. In addition, because an aerosol generating article may be uniformly heated, the amount of active ingredients of an aerosol transferred to a user is uniform throughout the entire heating period, and a taste of smoking may be provided with constant quality.

[0268] In addition, a capsule of an aerosol generating article according to the embodiments may be easily crushed without the intervention of a user.

[0269] An aerosol generating system according to the embodiments may reduce the time required for preheating, and an aerosol generated at the beginning of the heating period may also include a sufficient amount of active ingredients.

[0270] Effects of the embodiments are not limited to the effects described above, and effects that are not described may be clearly understood by those skilled in the art from the present specification and the attached drawings.

Claims

1. An aerosol generating article comprising an aerosol generating material that is heated by exposure to microwaves and a first capsule that is crushed by exposure to the microwaves, wherein the first capsule comprises: a first core including a first material and a first microwave-responsive material; and a first shell surrounding the first core.
2. The aerosol generating article of claim 1, wherein the first material includes at least one selected from the group including a flavoring material, nicotine, caffeine, and cannabinoid.
3. The aerosol generating article of claim 1, wherein each of the microwaves has a frequency of 2.4 GHz to 2.5 GHz.
4. The aerosol generating article of claim 1, wherein the first core includes the first microwave-responsive material with 20 wt % to 40 wt % of a total weight of the first core.
5. The aerosol generating article of claim 1, wherein the first microwave-responsive material includes at least one selected from the group including glycerin, propylene glycol, ethylene glycol, dipropylene glycol, diethylene glycol, triethylene glycol, tetraethylene glycol, and oleyl alcohol.
6. The aerosol generating article of claim 1, wherein the first shell includes an inner shell including

a fat-soluble material and an outer shell surrounding the inner shell and including a water-soluble material.

7. The aerosol generating article of claim 6, wherein the inner shell includes a fat-soluble wax.

8. The aerosol generating article of claim 6, wherein the outer shell includes one or more water-soluble polymers selected from the group consisting of gelatin, agar, carrageenan, gelatin gum, pectin, starch, and alginate.

9. The aerosol generating article of claim 1, wherein the first shell has a thickness of 5 μm to 50 μm .

10. The aerosol generating article of claim 1, further comprising: an aerosol generating rod including the aerosol generating material and the first capsule, and a filter rod disposed downstream from the aerosol generating rod.

11. The aerosol generating article of claim 1, further comprising: a second capsule that is crushed by exposure to the microwaves, wherein the second capsule includes a second core including a second material and a second microwave-responsive material and a second shell surrounding the second core.

12. The aerosol generating article of claim 11, wherein the first capsule and the second capsule are crushed at different times by exposure to the microwaves.

13. The aerosol generating article of claim 11, wherein the first capsule is disposed upstream from the second capsule and is crushed earlier than the second capsule by exposure to the microwaves.

14. An aerosol generating system comprising: the aerosol generating article according to claim 1; and an aerosol generating device configured to accommodate the aerosol generating article, wherein the aerosol generating device includes a heater assembly configured to generate microwaves for heating the aerosol generating article.

15. The aerosol generating system of claim 14, wherein the heater assembly includes a resonator configured to generate the microwaves, the resonator includes a plurality of plates separated from each other in a circumferential direction of the aerosol generating article, and the microwaves are resonated by the plurality of plates.
