

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250281863

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

PARK; Geunyoung et al.

FILTER ASSEMBLY AND AIR CLEANER INCLUDING THE SAME

Abstract

A filter assembly is disclosed. The filter assembly includes a filter unit including a filter, a first case coupled to a lower end of the filter unit, and a second case coupled to the lower end of the filter unit. The filter unit includes a first molding provided at the lower end of the filter unit and in contact with the first case, and a second molding provided at an upper end of the filter unit and in contact with the second case. Each of the first case and the second case comprises a non-polar polymer material.

Inventors: PARK; Geunyoung (Suwon-si, KR), JEONG; Sekwan (Suwon-si, KR), WOO; Dongwoo (Suwon-si, KR), YUN; Soyoung (Suwon-si, KR)

Applicant: Samsung Electronics Co., Ltd. (Suwon-si, KR)

Family ID: 1000008533170

Appl. No.: 19/075284

Filed: March 10, 2025

Foreign Application Priority Data

KR	10-2024-0031624	Mar. 05, 2024
KR	10-2024-0031627	Mar. 05, 2024
KR	10-2024-0070387	May. 29, 2024

Related U.S. Application Data

parent WO continuation PCT/KR2024/020603 20241218 PENDING child US 19075284

Publication Classification

Int. Cl.: B01D46/00 (20220101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a continuation of International Application No. PCT/KR2024/020603 designating the United States, filed on Dec. 18, 2024, in the Korean Intellectual Property Receiving Office and claiming priority to Korean Patent Application Nos. 10-2024-0031624, filed on Mar. 5, 2024, 10-2024-0031627, filed on Mar. 5, 2024, and 10-2024-0070387, filed on May 29, 2024, in the Korean Intellectual Property Office, the disclosures of each of which are incorporated by reference herein in their entireties.

BACKGROUND

Field

[0002] The disclosure relates to a filter assembly and an air cleaner including the same.

Description of Related Art

[0003] An air cleaner is a device that intakes, purifies, and discharges contaminated air. The air cleaner takes in air containing contaminants through a front inlet using a blower, passes the intake air through a filter assembly to remove the contaminants, and discharges the purified air through an upper or side outlet. The filter assembly is replaced at regular or random cycles depending on a location where the air cleaner is used. The used filter assembly is discarded together with a filter and a plastic case supporting the filter. Recently, with the emergency of environment, safety, and health (EHS), research is being conducted on the filter assembly that may separate and discharge the filter of the used filter assembly from a case and recycle the case.

SUMMARY

[0004] Embodiments of the disclosure provide a filter assembly capable of separating and discharging a filter from a case and improving air leakage occurring between the case and the filter, and an air cleaner including the same.

[0005] According to an example embodiment of the present disclosure, a filter assembly includes: a filter unit including a filter; a first case coupled to a lower end of the filter unit; and a second case coupled to an upper end of the filter unit. The filter unit may include: a first molding provided at the lower end of the filter unit and in contact with the first case; and a second molding provided at an upper end of the filter unit and in contact with the second case. Each of the first case and the second case may comprise a non-polar polymer material.

[0006] Each of the first molding and the second molding may comprise a urethane resin.

[0007] The urethane resin may include a curable two-component urethane adhesive.

[0008] The non-polar polymer material may comprise a material having a surface energy of 33 dynes/cm or less.

[0009] A surface of the first case, in contact with the first molding, may be formed by lapping processing. A surface of the second case, in contact with the second molding, may be formed by the lapping processing.

[0010] Each of the first case and the second case may comprise polypropylene or polyethylene.

[0011] Each of the first case and the second case may include a strength-reinforcing material included in polypropylene and/or polyethylene. The strength-reinforcing material may include at least one of talc, glass fiber, and carbon black.

[0012] The filter assembly may further include: a fastening structure comprising a fastener configured to detachably fasten the lower end of the filter unit and the first case and detachably fasten the upper end of the filter unit and the second case.

[0013] The filter unit may include: a first filter having a cylindrical shape and having the first molding coupled along the lower end and the second molding coupled along the upper end; and a second filter provided on an inner side of the first filter. The fastening structure may include: a plurality of first hooks provided along a lower end of the second filter; a plurality of second hooks provided along an upper end of the second filter; a plurality of first catches provided in the first case and having fastening holes to which the plurality of first hooks are configured to be fastened; and a plurality of second catches provided in the second case and having fastening holes to which the plurality of second hooks are fastened.

[0014] Each of the first case and the second case may have a rectangular loop shape. At least one first catch among the plurality of first catches may be disposed to be biased at a certain angle from a virtual first straight line crossing two opposing corners of the first case. At least one second catch among the plurality of second catches may be disposed to be biased at a certain angle from a virtual second straight line crossing two opposing corners of the second case.

[0015] The first catch biased from the virtual first straight line and the second catch biased from the virtual second straight line may each be fastened to the second filter to face each other.

[0016] A spacing between the plurality of first catches disposed on a first side surface of the first case and a spacing between the plurality of first catches disposed on a second side surface adjacent to the first side surface of the first case may be different. A spacing between the plurality of second catches disposed on a first side surface of the first case and a spacing between the plurality of first second catches disposed on a second side surface adjacent to the first side surface of the first case may be different.

[0017] The first case may further include a plurality of first handles provided at each corner of the first case. The second case may further include a plurality of second handles provided at each corner of the second case.

[0018] The second filter may include a plurality of post-filters continuously disposed along an inner side surface of the first filter.

[0019] The first case may include: a first coupling groove having a loop shape and into which the first molding is configured to be inserted; and a second coupling groove formed along one side of the first coupling groove and into which the lower end of the second filter is configured to be inserted. The second case may include: a third coupling groove having a loop shape and into which the second molding is configured to be inserted; and a fourth coupling groove formed along one side of the third coupling groove and into which the upper end of the second filter is configured to be inserted.

[0020] The first filter may be configured as a dust collection filter. The second filter may be configured as a deodorizing filter.

[0021] The filter unit may further include a third filter surrounding the first filter.

[0022] The third filter may include a microfiber filter having a mesh shape.

[0023] According to an example embodiment of the present disclosure, an air cleaner includes: a main body including a receiving space and a discharge space separated from the receiving space; a blower fan disposed between the receiving space and the discharge space, configured to take in external air into the receiving space and discharge the external air to an outside of the main body through the discharge space; and a filter assembly comprising a filter retractably inserted into the receiving space of the main body and configured to purify the external air introduced into the receiving space. The filter assembly may include: a filter unit including a first molding comprising urethane resin provided along a lower end and a second molding comprising urethane resin provided along an upper end, and having a cylindrical shape; a first case configured to support the lower end of the filter unit while being in contact with the first molding; a second case configured to support the upper end of the filter unit while being in contact with the second molding; a fastening structure including a fastener configured to detachably fasten the lower end of the filter

unit and the first case and detachably fasten the upper end of the filter unit and the second case. Each of the first case and the second case may comprise a non-polar polymer material.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0024] The above and other aspects, features and advantages of certain embodiments of the present disclosure will be more apparent from the following detailed description, taken in conjunction with the accompanying drawings, in which:

[0025] FIG. 1 is an exploded perspective view illustrating an example in which a filter assembly is mounted on an air cleaner according to various embodiments;

[0026] FIG. 2 is a diagram illustrating a front view of an air cleaner according to various embodiments;

[0027] FIG. 3 is a perspective view illustrating an air cleaner that takes in contaminated air and discharges purified air according to various embodiments;

[0028] FIG. 4 is an exploded perspective view illustrating the filter assembly according to various embodiments;

[0029] FIG. 5 is a perspective view illustrating the filter assembly according to various embodiments;

[0030] FIG. 6 is a partial exploded perspective view illustrating an example in which a post-filter is combined with a dust collection filter of the filter assembly according to various embodiments;

[0031] FIG. 7 is an exploded perspective view illustrating an example of applying a two-component urethane adhesive to a first case of the filter assembly according to various embodiments;

[0032] FIG. 8 is a perspective view illustrating an example of temporarily bonding the dust collection filter to the first case of a filter assembly according to various embodiments;

[0033] FIG. 9 is a diagram illustrating an enlarged view of a part of the dust collection filter according to various embodiments;

[0034] FIG. 10 is a diagram illustrating a plan view of the first case of the filter assembly according to various embodiments;

[0035] FIG. 11 is a cross-sectional view taken along line A-A' of FIG. 10 according to various embodiments;

[0036] FIG. 12 is a perspective view illustrating the first case of the filter assembly according to various embodiments;

[0037] FIG. 13 is a diagram illustrating a side view of an example in which a plurality of post-filters are combined with the first case and the second case of the filter assembly according to various embodiments;

[0038] FIG. 14 is a partial enlarged perspective view of a structure in which a fourth post-filter and the first case of the filter assembly are mutually fastened according to various embodiments; and

[0039] FIG. 15 is an exploded perspective view illustrating the first case separated from a filter unit of the filter assembly according to various embodiments.

DETAILED DESCRIPTION

[0040] Hereinafter, various example embodiments will be described in greater detail with reference to the accompanying drawings. The various example embodiments described in the disclosure may be variously modified. A specific embodiment may be illustrated in the drawings and be described in detail in a detailed description. However, the specific embodiment illustrated in the accompanying drawings is provided only to allow various embodiments to be easily understood. Therefore, it should be understood that the spirit of the present disclosure is not limited by the specific example embodiment illustrated in the accompanying drawings, but includes all the

modifications, equivalents, and substitutions included in the spirit and the scope of the present disclosure. Furthermore, those skilled in the art will recognize that various changes and modifications can be made to various embodiments described herein without departing from the scope and spirit of the present disclosure.

[0041] In the present disclosure, terms including ordinal numbers such as “first,” “second,” and the like, may be used to describe various components. However, these components are not limited by these terms. These terms are used only to distinguish one component from another component. It should be further understood that terms “include” or “have” used in the disclosure specify the presence of features, numerals, steps, operations, components, parts mentioned in the disclosure, or combinations thereof, but do not preclude the presence or addition of one or more other features, numerals, steps, operations, components, parts, or combinations thereof. It is to be understood that when one component is referred to as being “connected to” or “coupled to” another component, one component may be connected directly to or coupled directly to another component or be connected to or coupled to another component with the other component interposed therebetween. On the other hand, it is to be understood that when one component is referred to as being “connected directly to” or “coupled directly to” another component, it may be connected to or coupled to another component without the other component interposed therebetween. In the present disclosure, the expression “same” may refer not only completely matching, but may also including a degree of difference considering a processing error range. When it is determined that a detailed description for known functions or configurations related to the disclosure may unnecessarily obscure the gist of the disclosure, the detailed description therefor may be abbreviated or omitted.

[0042] Hereinafter, various example embodiments of the disclosure will be described in greater detail with reference to the accompanying drawings. However, embodiments of the present disclosure may be implemented in various different forms and are not limited to one or any specific embodiment of the present disclosure described herein.

[0043] FIG. 1 is an exploded perspective view illustrating an example in which a filter assembly **100** is mounted on an air cleaner **10** according to various embodiments. FIG. 2 is a diagram illustrating a front view of an air cleaner according to various embodiments. The air cleaner **10** illustrated in FIG. 2 is illustrated with a first cover **31** removed for convenience of description.

[0044] Referring to FIG. 1, the air cleaner **10** may include a main body **11**, a blower fan **20** disposed inside the main body **11**, the first cover **31**, a second cover **32**, a third cover **33**, and a fourth cover **34** that are detachably mounted on front, rear, left, and right side surfaces of the main body **11**, respectively, and the filter assembly **100** that purifies contaminated air introduced into the inside of the main body **11** from the outside of the main body **11**.

[0045] The main body **11** may include a receiving space **13** into which the filter assembly **100** is retractably inserted. A size of the receiving space **13** may correspond to a size of the filter assembly **100** or may have a size slightly larger than the size of the filter assembly **100** so that the insertion and withdrawal of the filter assembly **100** may be facilitated. The receiving space **13** may be opened to the front, rear, left, and right side surfaces of the main body **11**, respectively, so that external air may move from the front, rear, left, and right side surfaces of the main body **11** into the receiving space **13**, respectively.

[0046] The main body **11** may include a discharge space **15** for discharging air purified by the filter assembly **100** to the outside of the main body **11**. The discharge space **15** may be opened to the front, rear, left, and right side surfaces of the main body **11**, respectively, so that the air purified by the filter assembly **100** may move to the outside of the main body **11** through the front, rear, left, and right side surfaces of the main body **11**.

[0047] The discharge space **15** may be disposed at a higher position than the receiving space **13**. For example, the receiving space **13** may be disposed under the main body **11**, and the discharge space **15** may be disposed above the main body **11**.

[0048] Referring to FIG. 2, the blower fan **20** may be disposed inside the main body **11**. For

example, the blower fan **20** may be disposed between the receiving space **13** and the discharge space **15**. The blower fan **20** may provide a suction force that sucks (or causes to be taken in) external air of the main body **11** into the receiving space **13**. The blower fan **20** may provide a discharge force that makes air taken into the receiving space **13** flow into the discharge space **15**. [0049] The first, second, third, and fourth covers **31**, **32**, **33**, and **34** may be detachably mounted on the front, rear, left, and right side surfaces of the main body **11**. The first cover **31** may be detachably connected to the front side surface of the main body **11** for replacement of the filter assembly **100**, and the second, third, and fourth covers **32**, **33**, and **34** may be fixedly connected to the main body **11**. The first, second, third, and fourth covers **31**, **32**, **33**, and **34** may each be formed in a grill shape having a plurality of slits through which air may pass.

[0050] Referring to FIG. **3**, when the blower fan **20** is driven, the external air may be introduced into the receiving space **13** through the first, second, third, and fourth covers **31**, **32**, **33**, and **34**. Among the contaminant (e.g. dust) contained in the external air, dust having a size larger than the plurality of slits of the first, second, third, and fourth covers **31**, **32**, **33**, and **34** may be filtered by the first, second, third, and fourth covers **31**, **32**, **33**, and **34** and removed from the external air. The purified air may flow from the receiving space **13** to the discharge space **15** by the blower fan **20**. The purified air flowing into the discharge space **15** may be discharged to the front, rear, left, and right side surfaces of the main body **11** through the first, second, third, and fourth covers **31**, **32**, **33**, and **34**, respectively.

[0051] Referring to FIG. **3**, when the blower fan **20** is driven, the pressure of the receiving space **13** may be lower than the atmospheric pressure. The external air existing around the main body **11** may be sucked into the receiving space **13** through the front, rear, left, and right side surfaces of the main body **11**, respectively. The dust contained in the external air may be removed as the external air passes through the filter assembly **100**. The purified air may flow from the receiving space **13** to the discharge space **15** by the blower fan **20**. The purified air flowing into the discharge space **15** may be discharged to the front, rear, left, and right side surfaces of the main body **11**, respectively.

[0052] The filter assembly **100** is inserted into the receiving space **13** and may purify the external air introduced into the receiving space **13** from the outside of the main body **11**. The filter assembly **100** may remove contaminants (e.g., fine dust, odorous substances) contained in the external air.

[0053] The filter assembly **100** may be formed in a tubular shape in which a guide passage **101** (see FIG. **1**) is provided on the inside. By driving the blower fan **20**, the external air sucked into the receiving space **13** through the first, second, third, and fourth covers **31**, **32**, **33**, and **34** may be introduced into the guide passage **101** from the outside of the filter assembly **100**. The contaminants contained in the external air may be filtered by the filter assembly **100**. The purified air may flow into the blower fan **20** along the guide passage **101** of the filter assembly **100** and then be discharged to the front, rear, left, and right side surfaces of the main body **11** through the discharge space **15**, respectively.

[0054] The filter assembly **100** may be formed in a rectangular cylinder shape including the front, rear, left side, and right side surfaces corresponding to the first, second, third, and fourth covers **31**, **32**, **33**, and **34**, respectively. A shape of the filter assembly **100** is not limited to a rectangular cylinder. For example, when the main body **11** has a cylindrical shape, the filter assembly may be formed in a cylindrical shape. In this way, the filter assembly **100** may have a shape corresponding to the shape of the main body **11**.

[0055] The air cleaner **10** according to an embodiment of the present disclosure may further include an electric dust collecting filter on the inside of the main body **11**. The electric dust collecting filter may be disposed downstream of the filter assembly **100** in a flow direction of air. For example, the electric dust collecting filter may be disposed between the filter assembly **100** and the blower fan **20**. The electric dust collecting filter may be configured to collect dust using, for example, electrostatic force. The electric dust collecting filter may form an electric field. The dust contained in the external air may be collected in the electric dust collecting filter by the electric

field formed by the electric dust collecting filter. Organic matters such as bacteria and viruses contained in the external air may be removed by the electric field formed by the electric dust collecting filter.

[0056] After a certain period of use, a user may take out the filter assembly **100** whose lifespan has expired from the receiving space **13**, separate a filter unit **110** that filters dust from a first case **150** and a second case **160**, and then throw the filter unit **110** away in a trash can. Since the filter unit **110** is configured to have flexibility, the shape of the filter unit **110** may be easily changed. When a side surface of the filter unit **110** is compressed, the guide passage **101** narrows and a volume of the filter unit **110** is reduced. For example, the filter unit **110** may be compressed from a three-dimensional cylinder shape to a roughly flat shape. Therefore, the filter unit **110** may be discharged in a reduced volume.

[0057] Hereinafter, an example configuration of the filter assembly **100** according to various embodiments will be described in greater detail with reference to the drawings.

[0058] FIG. **4** is an exploded perspective view illustrating the filter assembly **100** according to various embodiments. FIG. **5** is a perspective view illustrating the filter assembly **100** according to various embodiments, and illustrates the filter assembly **100** with a pre-filter **121** surrounding a dust collecting filter **123** being removed. FIG. **6** is an exploded perspective view illustrating an example in which the post-filter is combined with the dust collection filter of the filter assembly according to various embodiments.

[0059] Referring to FIG. **4**, the filter assembly **100** may include the filter unit **110**, and the first case **150** and the second case **160** that are each detachably coupled to the filter unit **110**.

[0060] The filter unit **110** may be formed in a loop shape so that the guide passage **101** may be formed on the inside. The filter unit **110** may be configured to have flexibility so that it may be unfolded or folded when discarded after being separated from the first case **150** and the second case **160**. The filter unit **110** may be configured to maintain an approximately square cylinder shape. The shape of the filter unit **110** is not limited to a square cylinder, and may be configured to maintain an n-polygon cylinder shape (where n is a natural number greater than or equal to 3) or a cylindrical shape. For example, the first case **150** may include an opening (**151**) formed to form a loop shape corresponding to the filter unit **110**. The second case **160** may include an opening **161** formed to form a loop shape corresponding to the filter unit **110**.

[0061] Referring to FIGS. **4** and **5**, the filter unit **110** may include the dust collection filter **123**, a first molding **125** provided under the dust collection filter **123**, a second molding **127** provided above the dust collection filter **123**, first, second, third, and fourth post-filters **131**, **132**, **133**, and **134** disposed along an inner side surface of the dust collection filter **123**, and the pre-filter **121** surrounding an outer side surface of the dust collection filter **123**.

[0062] The external air passing from the outside of the filter unit **110** to the inside (e.g., guide passage **101**) of the filter unit **110** may sequentially pass through the pre-filter **121**, the dust collecting filter **123**, and the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134**, thereby removing dust and odor particles contained in the external air.

[0063] The pre-filter **121** may be formed as a thin-film mesh. The pre-filter **121** may use a thin-film mesh filter (e.g., a microfiber filter). The pre-filter **121** may be coupled to or separated from the dust collecting filter **123** by male/female Velcro tapes provided at each end. The pre-filter **121** may capture fine dust contained in the external air. The pre-filter **121** may be disposed upstream of the dust collecting filter **123** based on the air flow direction.

[0064] The dust collecting filter **123** may use a high efficiency particulate air (HEPA) filter, but is not limited thereto, and may use various types of filters. The dust collecting filter **123** may capture ultrafine dust contained in air that has been primarily filtered by the pre-filter **121**.

[0065] The dust collecting filter **123** may include the first molding **125** that may minimize or improve air leakage between a lower end of the dust collecting filter **123** and the first case **150**. The dust collecting filter **123** may include the second molding **127** that may minimize or improve air

leakage between an upper end of the dust collecting filter **123** and the first case **160**.

[0066] The first molding **125** may be provided in a loop shape along the lower end of the dust collecting filter **123**. The first molding **125** may cover a bottom surface of the dust collecting filter **123**, a lower end of the outer side surface of the dust collecting filter **123**, and a lower end of an inner side surface of the dust collecting filter **123**, respectively. The first molding **125** may be made of a flexible material. When the dust collecting filter **123** is coupled with the first case **150**, the first molding **125** may be in close contact with the first case **150**. The first molding **125** may minimize or improve air leakage between the lower end of the dust collecting filter **123** and the first case **150**.

[0067] The second molding **127** may be provided in a loop shape along the upper end of the dust collecting filter **123**. The second molding **127** may cover an upper surface of the dust collecting filter **123**, an upper end of the outer side surface of the dust collecting filter **123**, and an upper end of the inner side surface of the dust collecting filter **123**, respectively. The second molding **127** may be made of the same material as the first molding **125**. When the dust collecting filter **123** is coupled with the second case **160**, the second molding **127** may be in close contact with the second case **160**. The second molding **127** may minimize or improve air leakage between the upper end of the dust collecting filter **123** and the second case **160**.

[0068] Referring to Table 1 below, a filter fabric applied to the dust collecting filter **123** has a dust collecting efficiency of 99.98%. In this case, the particle size of the filter fabric is 0.3 μm . The dust collection efficiency of the filter assembly **100** having the dust collection filter **123** to which the filter fabric is applied is 99.97% when the first molding **125** and the second molding **127** are applied, and the leakage rate is 0.01% compared to the dust collection efficiency of the filter fabric. On the other hand, the dust collection efficiency of the filter assembly **100** to which the first molding **125** and the second molding **127** are not applied is 97.86%, and the leakage rate is 2.12% compared to the dust collection efficiency of the filter fabric. Therefore, the filter assembly **100** may have high dust collection efficiency due to the first molding **125** and the second molding **127**.

TABLE-US-00001

TABLE 1	Urethane Molding	Division Presence	Absence	Dust collecting Filter
fabric	99.98%	99.98%	efficiency	filter assembly
	99.97%	97.86%	[% , @0.3 μm]	Leakage rate
	0.01%	2.21%		

[0069] The filter assembly **100** may improve the dust collection efficiency of the filter by minimizing/reducing the air leakage as the first molding **125** and the second molding **127** of the dust collection filter **123** are closely attached to the first case **150** and the second case **160**. The dust collection filter **123** may be easily separated from the first case **150** and the second case **160** by the first molding **125** and the second molding **127**.

[0070] The first molding **125** and the second molding **127** may be made of a material (e.g., urethane resin) having flexibility and predetermined strength. The dust collection filter **123** may maintain a three-dimensional shape by the strength of the first molding **125** and the second molding **127** when not coupled to the first case **150** and the second case **160**. When the force for compressing the dust collecting filter **123** exceeds the strength of the first molding **125** and the second molding **127**, the first molding **125** and the second molding **127** may be easily deformed. The used dust collecting filter **123** may be discarded in a state in which its volume is reduced as it is easily compressed.

[0071] Referring to FIG. 6, the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134** may include activated carbon. The first, second, third, and fourth post-filters **131**, **132**, **133**, and **134** may be disposed downstream of the dust collecting filter **123** based on the direction of air flow. The first, second, third, and fourth post-filters **131**, **132**, **133**, and **134** may adsorb and filter out odor particles or gas particles contained in the air secondarily filtered by the dust collecting filter **123**.

[0072] The first, second, third, and fourth post-filters **131**, **132**, **133**, and **134** may be configured to have the same size, respectively. The first, second, third, and fourth post-filters **131**, **132**, **133**, and **134** may be disposed to correspond to four surfaces of inner sides of the dust collecting filter **123**,

respectively.

[0073] The lower and upper ends of the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134** may be configured to be detachably connected to the first case **150** and the second case **160**, respectively. The fastening structure between the first, second, third and fourth post-filters **131**, **132**, **133**, and **134** and the first case **150** and the second case **160** is described below.

[0074] The filter unit **110** according to various embodiments includes the plurality of first, second, third and fourth post-filters **131**, **132**, **133**, and **134**, but is not limited thereto. For example, the post-filter may be formed in a single square cylinder shape. In addition, the post-filter may be formed in a cylindrical shape corresponding to the shape of the dust collection filter **123** when the dust collection filter **123** is formed in a cylindrical shape.

[0075] The filter unit **110** according to various embodiments may be configured not to include the pre-filter **121** and include the dust collection filter **123** and the first, second, third and fourth post-filters **131**, **132**, **133**, and **134**.

[0076] Hereinafter, a method of forming the first molding **125** at the lower end of the dust collecting filter **123** will be described in greater detail with reference to the drawings.

[0077] FIG. **7** is a an exploded perspective view illustrating an example of applying a two-component urethane adhesive to a first case of the filter assembly according to various embodiments. FIG. **8** is a perspective view illustrating an example of temporarily bonding the dust collection filter to the first case of the filter assembly according to various embodiments. FIG. **9** is a diagram illustrating an enlarged view of a part of the dust collection filter according to various embodiments.

[0078] Referring to FIG. **7**, a urethane adhesive (e.g., a two-component urethane adhesive) **125a** is applied to a first coupling groove **153** of the first case **150** into which the lower end of the dust collecting filter **123** is inserted. The two-component urethane adhesive **125a** may include a main agent and a curing agent, and the main agent and the curing agent may be cured by a chemical reaction with each other. The two-component urethane adhesive **125a** is maintained in a liquid state before being cured.

[0079] A lower end **123a** of the dust collecting filter **123** is pushed into the first coupling groove **153** of the first case **150** to which the two-component urethane adhesive **125a** is applied. The dust collecting filter **123** may be configured to have an approximately square cylinder shape by folding the filter paper in a zigzag manner. The two-component urethane adhesive **125a** may be introduced into the inside of the lower end **123a** of the dust collecting filter **123** to a predetermined height when the lower end **123a** of the dust collecting filter **123** is inserted into the first coupling groove **153** of the first case **150**.

[0080] Referring to FIG. **8**, the dust collecting filter **123** is left in a state where the lower end of the dust collecting filter **123** is inserted into the first coupling groove **153** of the first case **150** while the two-component urethane adhesive **125a** is cured. The lower end **123a** of the dust collecting filter **123** may be bonded to the first case **150** by the two-component urethane adhesive **125a**.

[0081] The two-component urethane adhesive **125a** may become the first molding **125** coupled to the lower end of the dust collecting filter **123** after being cured. The cured first molding **125** may be firmly attached to the lower end of the dust collecting filter **123**. The first molding **125** may have flexibility that is not too hard and may be easily bent or stretched.

[0082] Referring to FIG. **9**, the first molding **125** may be maintained in a shape corresponding to the first coupling groove **153** of the first case **150**. The first molding **125** may have a predetermined thickness t .

[0083] After forming the first molding **125** at the lower end of the dust collecting filter **123**, the second molding **127** may be formed at the upper end of the dust collecting filter **123** by a method substantially the same as the method of forming the first molding **125**. In the process of forming the first molding **125** and the second molding **127** at the lower end and upper end of the dust collecting filter **123**, respectively, the dust collecting filter **123** may be temporarily bonded to the

first case **150** and the second case **160**.

[0084] The first case **150** and the second case **160** may be made of a material that may be easily separated from the first molding **125** and the second molding **127** of the dust collecting filter **123**. When the first molding **125** and the second molding **127** are made of a urethane resin, the first case **150** and the second case **160** may be made of a material that does not form an ionic bond or a covalent bond with the first molding **125** and the second molding **127**. For example, the first case **150** and the second case **160** may be made of a nonpolar polymer resin having a surface energy of about 33 dynes/cm or less. For example, the polymer resin may be polyolefin. The polyolefin-based polymer resin may include polypropylene and polyethylene. The polypropylene and polyethylene have chemical stability, durability, and light weight, and are easy to process and inexpensive. The surface energy of polypropylene is about 29 to 31 dynes/cm. The surface energy of polypropylene is about 30 to 31 dynes/cm.

[0085] The first case **150** and the second case **160** may be configured by mixing polypropylene and a strength-reinforcing material to reinforce strength. The strength-reinforcing material may include at least one of talc, glass fiber, and carbon black. For example, the first case **150** and the second case **160** may each be made of a mixture of 80% of polypropylene and 20% of talc. In addition, the first case **150** and the second case **160** may each be made of a mixture of 80% of polypropylene, 10% of talc, and 10% of glass fiber.

[0086] Since the first case **150** and the second case **160** are made of a material having low surface energy, they may be easily separated from the first molding **125** and the second molding **127** while being temporarily bonded thereto.

[0087] In the disclosure, the first case **150** and the second case **160** are described as examples of being used as jigs for forming the first molding **125** and the second molding **127**, but are not limited thereto. For example, the first molding **125** provided at the lower end of the dust collecting filter **123** may be formed by a separate jig having a groove formed on one surface having substantially the same shape as the first coupling groove **153** of the first case **150**. In this case, the jig may be made of a material having low surface energy (e.g., about 33 dynes/cm or less) so that the first molding **125** may be easily separated from a groove of the jig after being cured.

[0088] FIG. **10** is a diagram illustrating a plan view of the first case of the filter assembly according to various embodiments. FIG. **11** is a cross-sectional view taken along line A-A' of FIG. **10** according to various embodiments.

[0089] Referring to FIG. **10**, the first case **150** may include the first coupling groove **153** to which the lower end of the filter unit **110** is coupled, and a second coupling groove **155** to which the lower ends of the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134** are coupled.

[0090] The first coupling groove **153** of the first case **150** may be formed in a loop shape along an upper surface of the first case **150**. The first coupling groove **153** of the first case **150** may be formed by a first rib **152a** and a second rib **152b** protruding to a predetermined height on the upper surface of the first case **150**. The heights of the first rib **152a** and the second rib **152b** may be approximately greater than the thickness t of the first molding **125** (see FIG. **9**).

[0091] The first coupling groove **153** of the first case **150** may be configured to correspond to the lower end of the dust collecting filter **123**. For example, when the dust collecting filter **123** has a square cylinder shape, the first coupling groove **153** of the first case **150** may be formed in an approximately square shape.

[0092] Referring to FIG. **11**, the lower end of the dust collecting filter **123** may be inserted into the first coupling groove **153** of the first case **150**. The first molding **125** provided at the lower end of the dust collecting filter **123** may be closely attached to the first coupling groove **153** of the first case **150**. Accordingly, the air leakage between the upper end of the dust collecting filter **123** and the second case **160** may be minimized or improved.

[0093] In order to increase the detachability between the first molding **125** and the first coupling groove **153** of the first case **150**, the first coupling groove **153** of the first case **150** may be

configured to have a low surface roughness. For example, the first case **150** may be manufactured by injection molding. In this case, a plurality of unevennesses may be formed on the surface of the first coupling groove **153** of the first case **150** depending on the quality of the mold. The plurality of unevennesses may strengthen the adhesion between the first molding **125** of the dust collecting filter **123** and the first coupling groove **153** of the first case **150**, thereby reducing the detachability. Therefore, the first coupling groove **153** of the first case **150** may be smoothed on the surface by lapping processing (e.g., #3000 lapping processing).

[0094] The first case **150** may be subjected to the lapping processing only in the first coupling groove **153** with which the first molding **125** is in close contact, but is not limited thereto. For example, in the case where a number of unevennesses are formed in the entire first case **150** due to the low quality of the mold for injecting the first case **150**, the lapping processing may be performed on the entire first case **150**.

[0095] The second coupling groove **155** of the first case **150** may be provided in a loop shape on the upper surface of the first case **150** along the first coupling groove **153** of the first case **150**. The second coupling groove **155** of the first case **150** may be positioned closer to the center portion of the first case **150** than the first coupling groove **153**. The second coupling groove **155** of the first case **150** may be formed by the second rib **152b** and the third rib **152c**. The second rib **152b** may be a configuration commonly used to form the first coupling groove **153** and the second coupling groove **155**. The lower ends of the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134** may be inserted into the second coupling groove **155** of the first case **150**, respectively.

[0096] Referring to FIG. **10**, the first case **150** may have handles **157** provided at each of the four corners. Each of the plurality of handles **157** may be provided with a gripping jaw **157a** for end portion of fingers to be caught.

[0097] A user may easily separate the first case **150** from the lower ends of the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134** by pulling one of the plurality of handles **157** in a direction away from the lower ends of the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134**.

[0098] The second case **160** may include substantially the same structure as the first case **150**. For example, the second case **160** may have a third coupling groove into which the upper end of the dust collection filter **123** is inserted and which is in close contact with the second molding **127**. The third coupling groove of the second case **160** may be smoothed by the lapping processing to improve detachability from the second molding **127**. The second case **160** may have a fourth coupling groove into which the upper ends of the first, second, third and fourth post-filters **131**, **132**, **133**, and **134** are inserted, respectively.

[0099] When the first case **150** and the second case **160** are coupled to the dust collection filter **123**, the first coupling groove **153** of the first case **150** and the third coupling groove of the second case **160** may be disposed to face each other. The second coupling groove **155** of the first case **150** and the fourth coupling groove of the second case **160** may be disposed to face each other.

[0100] The second case **160** may have handles provided at each of the four corners. The second case **160** may be separated from the upper ends of the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134** by pulling the plurality of handles in a direction away from the upper ends of the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134**.

[0101] Hereinafter, referring to the drawings, the structure of the filter assembly **100** for fastening between the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134** of the filter unit **110** and the first and second cases **150** and **160** will be described in greater detail.

[0102] FIG. **12** is a perspective view illustrating the first case of the filter assembly according to various embodiments. FIG. **13** is a diagram illustrating a side view of an example in which a plurality of post-filters are combined with the first case and the second case of the filter assembly according to various embodiments.

[0103] Referring to FIGS. **12** and **13**, the fastening structure of the filter assembly **100** may include

a plurality of first catches **158** and a plurality of second catches **159** provided in the first case **150**, and a plurality of first hooks **138** and a plurality of second hooks **139** provided at the lower ends of the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134**, respectively. The plurality of first hooks **138** may be detachably fastened to fastening holes **158a** of the plurality of first catches **158** of the first case **150**. The plurality of second hooks **139** may be detachably fastened to fastening holes **159a** of the plurality of second catches **159** of the first case **150**.

[0104] In addition, the fastening structure of the filter assembly **100** may include a plurality of third catches **168** and a plurality of fourth catches **169** provided in the second case **160**, and a plurality of third hooks **138-1** and a plurality of fourth hooks **139-1** provided on the upper ends of the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134**, respectively. The plurality of third hooks **138-1** may be detachably fastened to the plurality of third catches **168** of the second case **160**. The plurality of fourth hooks **139-1** may be detachably fastened to the plurality of fourth catches **169** of the second case **160**.

[0105] The fastening structure between the second case **160** and the first, second, third and fourth post-filters **131**, **132**, **133**, and **134** is substantially the same as the fastening structure between the first case **150** and the first, second, third and fourth post-filters **131**, **132**, **133**, and **134**. Therefore, the fastening structure between the first case **150** and the first, second, third and fourth post-filters **131**, **132**, **133**, and **134** will be described in greater detail below.

[0106] The plurality of first catches **158** of the first case **150** may extend to an edge of the second rib **152b** in the same direction as a protruding direction of the second rib **152b** at a predetermined interval. For example, the plurality of first catches **158** may be positioned to correspond to the centers of the front, rear, left, and right side surfaces of the first case **150**. In this case, the number of the plurality of first catches **158** of the first case **150** may be four.

[0107] The plurality of first catches **158** of the first case **150** may correspond to the plurality of first hooks **138** each provided at the lower ends of the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134**, respectively. The plurality of first catches **158** of the first case **150** may include the fastening hole **158a** to which the plurality of first hooks **138** of the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134** are fastened, respectively.

[0108] The plurality of second catches **159** of the first case **150** may extend to the edge of the second rib **152b** in the same direction as the protruding direction of the second rib **152b**. The plurality of second catches **159** of the first case **150** may be disposed at positions adjacent to four corners of the first case **150**, respectively.

[0109] For example, as illustrated in FIG. **12**, one second catch **159-1** of the plurality of second catches **159** of the first case **150** may be disposed at a position that is biased at a first angle C1 with respect to a virtual first straight line B1 that crosses opposing corners of the first case **150**. Another second catch **159-2** of the plurality of second catches **159** may be disposed at a position that is biased at a second angle C2 with respect to a virtual second straight line B2 that is orthogonal to the virtual first straight line B1 and crosses the opposing corners of the first case **150**. The first angle C1 and the second angle C2 may be substantially the same.

[0110] The two second catches **159-1** and **159-2** disposed on both sides of the first catch **158-1** may be disposed closer to the first catch **158-1** than the other adjacent first catches **158-2** and **158-3**, respectively. The remaining two second catches **159-3** and **159-4** may be disposed symmetrically to the two second catches **159-1** and **159-2**.

[0111] As illustrated in FIG. **13**, the first case **150** and the second case **160** may be each fastened to the lower and upper ends of the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134** so that the plurality of second catches **159** of the first case **150** and the plurality of fourth catches **169** of the second case **160** are symmetrical to each other. In this case, the plurality of first and second catches **158** and **159** of the first case **150** are fastened to the plurality of first and second hooks **138** and **139** provided at the lower portions of the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134**. In addition, the plurality of third and fourth catches **168** and **169** of the

second case **160** are fastened to the plurality of third and fourth hooks **138-1** and **139-1** provided at the upper portions of the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134**.

[0112] In this way, by the fastening structure in which the plurality of first and second catches **158** and **159** of the first case **150** and the plurality of third and fourth catches **168** and **169** of the second case **160** are configured symmetrically to each other, the fastening between the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134** and the first and second cases **150** and **160** is not easily separated even if the upper and lower portions of the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134** are twisted in opposite directions around a Z-axis. Accordingly, the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134** and the first and second cases **150** and **160** may be firmly connected to each other. The dust collecting filter **123** having flexibility may stably maintain a square cylinder shape by the fastening structure.

[0113] Hereinafter, an example of separating the first case **150** from the lower ends of the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134** will be described in greater detail with reference to the drawings.

[0114] FIG. **14** is an enlarged partial perspective view illustrating a structure in which the fourth post-filter and the first case of the filter assembly are mutually fastened according to various embodiments. FIG. **15** is an exploded perspective view illustrating an example in which the first case is separated from the filter unit of the filter assembly according to various embodiments.

[0115] Referring to FIG. **14**, the handle **157** of the first case **150** is pulled in a direction away from the lower ends of the first, second, third, and fourth post-filters **131**, **132**, **133**, and **134**. The second catch **159** adjacent to the handle **157** of the first case **150** may be pulled in the direction in which the handle **157** is pulled.

[0116] In this case, a left portion **159b** of the second catch **159** adjacent to the corner of the first case **150** is moved in the direction in which the handle **157** is pulled before a right portion **159c** of the second catch **159**. After the left portion **139a** of the second hook **139** of the fourth post-filter **134** adjacent to the corner of the first case **150** is separated from the fastening hole **159a** of the second catch **159** before the right portion **139b** of the second hook **139**, the right portion **139b** of the second hook **139** may be separated from the fastening hole **159a** of the second catch **159**.

[0117] In this way, the second catch **159** of the first case **150** and the second hook **139** of the fourth post-filter **134** fastened thereto are disposed to be biased to one side from the center (e.g., the virtual first straight line **B1**) of the corner of the first case **150**, so the second catch **159** of the first case **150** and the second hook **139** of the fourth post-filter **134** may be easily separated.

[0118] In this way, when the remaining handles **157** of the first case **150** are each pulled in the direction away from the first, second, and third post-filters **131**, **132**, and **133**, as illustrated in FIG. **15**, the first case **150** may be easily separated from the filter unit **110** without effort. The second case **160** may be easily separated from the upper end of the filter unit **110** in the same way as the method of separating the first case **150** from the lower end of the filter unit **110**.

[0119] The used filter assembly **100** discharges the filter unit **110** separately from the first case **150** and the second case **160**.

[0120] While the present disclosure has been illustrated and described above with reference to various embodiments, it will be understood by those skilled in the art that various changes in form and detail may be made without departing from the spirit and scope of the present disclosure including the appended claims and their equivalents. It will also be understood that any of the embodiment(s) described herein may be used in conjunction with any other embodiment(s) described herein.

Claims

1. A filter assembly, comprising: a filter unit including a filter; a first case coupled to a lower end of the filter unit; and a second case coupled to the upper end of the filter unit, wherein the filter unit

includes: a first molding provided at the lower end of the filter unit and in contact with the first case; and a second molding provided at an upper end of the filter unit and in contact with the second case; and each of the first case and the second case comprising a non-polar polymer material.

2. The filter assembly as claimed in claim 1, wherein each of the first molding and the second molding comprises a urethane resin.
3. The filter assembly as claimed in claim 2, wherein the urethane resin comprises a curable two-component urethane adhesive.
4. The filter assembly as claimed in claim 1, wherein the non-polar polymer material has a surface energy of 33 dynes/cm or less.
5. The filter assembly as claimed in claim 1, wherein a surface of the first case, in contact with the first molding, is formed by lapping processing, and a surface of the second case, in contact with the second molding, is formed by the lapping processing.
6. The filter assembly as claimed in claim 4, wherein each of the first case and the second case comprises polypropylene or polyethylene.
7. The filter assembly as claimed in claim 4, wherein each of the first case and the second case includes a strength-reinforcing material included in the polypropylene or polyethylene, wherein the strength-reinforcing material includes at least one of talc, glass fiber, and carbon black.
8. The filter assembly as claimed in claim 1, further comprising: a fastening structure including a fastener configured to detachably fasten the lower end of the filter unit and the first case and to detachably fasten the upper end of the filter unit and the second case, wherein the filter unit includes: a first filter having a cylindrical shape wherein first molding is coupled along the lower end and the second molding is coupled along the upper end; and a second filter provided on an inner side of the first filter, and the fastening structure includes: a plurality of first hooks provided along a lower end of the second filter; a plurality of second hooks provided along an upper end of the second filter; a plurality of first catches provided in the first case and having fastening holes to which the plurality of first hooks are configured to be fastened; and a plurality of second catches provided in the second case and having fastening holes to which the plurality of second hooks are configured to be fastened.
9. The filter assembly as claimed in claim 8, wherein each of the first case and the second case has a rectangular loop shape, at least one first catch among the plurality of first catches is disposed to be biased at a certain angle from a virtual first straight line crossing two opposing corners of the first case, and at least one second catch among the plurality of second catches is disposed to be biased at a certain angle from a virtual second straight line crossing two opposing corners of the second case.
10. The filter assembly as claimed in claim 9, wherein the first catch biased from the virtual first straight line and the second catch biased from the virtual second straight line are each configured to be fastened to the second filter to face each other.
11. The filter assembly as claimed in claim 9, wherein a spacing between the plurality of first catches disposed on a first side surface of the first case and a spacing between the plurality of first catches disposed on a second side surface adjacent to the first side surface of the first case are different, and a spacing between the plurality of second catches disposed on the first side surface of the first case and the spacing between the plurality of second catches disposed on the second side surface adjacent to the first side surface of the first case are different.
12. The filter assembly as claimed in claim 9, wherein the first case further includes a plurality of first handles provided at each corner of the first case, the second case further includes a plurality of second handles provided at each corner of the second case, and the second filter includes a plurality of post-filters continuously disposed along an inner side surface of the first filter.
13. The filter assembly as claimed in claim 9, wherein the first case includes: a first coupling groove having a loop shape and into which the first molding is configured to be inserted; and a

second coupling groove formed along one side of the first coupling groove and into which the lower end of the second filter is configured to be inserted, and the second case includes: a third coupling groove having a loop shape and into which the second molding is configured to be inserted; and a fourth coupling groove formed along one side of the third coupling groove and into which the upper end of the second filter is configured to be inserted.

14. The filter assembly as claimed in claim 9, wherein the first filter is configured as a dust collection filter, the second filter is configured as a deodorizing filter, the filter unit further includes a third filter surrounding the first filter, and the third filter is configured as a microfiber filter having a mesh shape.

15. An air cleaner, comprising: a main body including a receiving space and a discharge space separated from the receiving space; a blower fan disposed between the receiving space and the discharge space, configured to cause external air to be taken into the receiving space and to discharge the external air to an outside of the main body through the discharge space; and a filter assembly including a filter retractably inserted into the receiving space of the main body and configured to purify the external air introduced into the receiving space, wherein the filter assembly includes: a filter unit including a first molding comprising urethane resin provided along a lower end and a second molding comprising urethane resin provided along an upper end, and has a cylindrical shape; a first case configured to support the lower end of the filter unit while being in contact with the first molding; a second case configured to support the upper end of the filter unit while being in contact with the second molding; a fastening structure comprising a fastener configured to fasten the lower end of the filter unit and the first case and to fasten the upper end of the filter unit and the second case, and each of the first case and the second case comprises a non-polar polymer material, and the non-polar polymer material has a surface energy of 33 dynes/cm or less.
