

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250282217

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

ROAT; Joshua Taylor et al.

VEHICLE DIFFERENTIAL DISCONNECT ASSEMBLY

Abstract

A vehicle differential disconnect assembly includes a differential case and a differential gear set carried within the differential case. The differential gear set includes a differential carrier rotatably supported within the differential case. A clutch ring includes interior spline splines engaged with exterior splines of the differential case and being movable to engage exterior splines on the differential carrier. An actuator assembly includes a solenoid with a plunger that engages a rocker that is pivotally mounted to a support structure and connected to the plunger. A shift fork is operably engaged with the clutch ring and slidably mounted for translation along an axis. The shift fork includes an engagement feature for receiving an end of the rocker, wherein activation of the actuator causes pivotal movement of the rocker to cause the shift fork to translate along the axis.

Inventors: ROAT; Joshua Taylor (Portland, OR), Yoder; Bryan (Corvallis, OR), Averill; Bryan M. (Portland, OR)

Applicant: Warn Automotive, LLC (Milwaukie, OR)

Family ID: 96948569

Appl. No.: 19/070081

Filed: March 04, 2025

Related U.S. Application Data

us-provisional-application US 63562840 20240308

Publication Classification

Int. Cl.: B60K17/346 (20060101); B60K23/08 (20060101); F16D27/118 (20060101)

U.S. Cl.:

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application claims the benefit of U.S. Provisional Application No. 63/562,840, filed on Mar. 8, 2024. The entire disclosure of the above application is incorporated herein by reference.

FIELD

[0002] The present disclosure relates to a vehicle differential disconnect assembly.

BACKGROUND

[0003] This section provides background information related to the present disclosure which is not necessarily prior art.

[0004] Differential drives are generally known in the motor vehicle industry. Differential drives are used in conjunction with the transmission and drive shaft or propeller shaft (prop shaft) to turn the automotive vehicle wheels at different speeds when the vehicle is going around a curve, in order to differentiate the speed of each wheel individually, and to provide the proper amount of torque to each wheel in slipping, turning, or other road-to-wheel conditions.

[0005] In a traditional torque on demand drive train layout of an automotive vehicle there is a primary driven front/rear axle, and a secondary driven “hang on” axle that is connected via a prop shaft or drive shaft and a torque transfer coupling to the primary driven axle. The torque transfer coupling is usually directly in front of and upstream of the secondary driven axle. The axle differential creates the division of power (or torque) to each side shaft of the axle. The primary driven axle can also include a differential which divides necessary power to the side shaft of each front axle shaft and then the wheels. The division of torque between the front and rear axle is completed by the torque transfer coupling which is typically a separate unit on the drive train system and requires space for its housing and other related parts. In a known traditional configuration, a torque transfer coupling for an automotive vehicle is located between the primary and secondary driven axles of the vehicle and may include a friction clutch pack which is loaded via a ball ramp mechanism. The ball ramp mechanism may be engaged by an electric motor. An electronic control unit senses slip conditions of the wheels, monitors current driving conditions of the vehicle and applies a current to the electric motor which will engage the clutch via the ball ramp mechanism and distribute torque to each wheel, as necessary.

SUMMARY

[0006] This section provides a general summary of the disclosure, and is not a comprehensive disclosure of its full scope or all of its features.

[0007] According to an aspect of the present disclosure, a vehicle differential disconnect assembly includes a differential case and a differential gear set carried within the differential case. The differential gear set includes a differential carrier rotatably supported within the differential case and supporting a bearing pin that supports a pair of bevel gears in meshing engagement with a pair of side shaft gears. A clutch ring includes a first set of splines engaged with a second set of splines of the differential case and being movable to engage a third set of splines on the differential carrier. An actuator assembly that engages a rocker that is pivotally mounted to a support structure and connected to the plunger. A shift fork is directly or indirectly engaged with the clutch ring and slidably mounted for translation along an axis. The shift fork includes an engagement feature for receiving an end of the rocker, wherein activation of the actuator causes pivotal movement of the rocker to cause the shift fork to translate along the axis.

[0008] A clutch ring mount can be utilized to engage the shift fork to the clutch ring. The clutch

ring mount can include an annular ring portion with an exterior groove and a plurality of arms that engage the clutch ring through windows in the differential housing,

[0009] According to a further aspect, the first set of splines on the clutch ring that engage the second set of splines on the differential case include exterior splines and the first set of splines on the clutch ring that engage the third set of splines on the differential carrier include interior splines.

[0010] According to a further aspect, the first set of splines on the clutch ring that engage second set of splines on the differential case include interior splines and the first set of splines on the clutch ring that engage the third set of splines on the differential carrier include interior splines.

[0011] According to a further aspect, the actuator assembly further comprises a solenoid with a plunger.

[0012] According to a further aspect, the actuator assembly includes one of a bi-stable actuator assembly and a mono-stable actuator assembly.

[0013] According to a further aspect, the first set of splines of the clutch ring include a plurality of stepped splines including a slider spline portion engaged with the second set of splines of the of the differential case and the plurality of stepped splines including a coupler spline portion being movable to engage the second set of splines on the second rotatable member, wherein the slider spline portion being configured to have less backlash with the first set of exterior splines than a backlash between the coupler spline portion and the second set of exterior splines.

[0014] According to a further aspect, the actuator includes at least one electric coil, a core movable relative to the electric coil and a plunger attached to the core and to the rocker, a pair of longitudinally spaced recesses associated with one of the core and the plunger and configured to be engaged by a spring detent mechanism.

[0015] According to an aspect of the present disclosure, a clutch engagement assembly includes a first rotatable member having a first set of exterior splines. A second rotatable member has a second set of exterior splines adjacent to the first set of exterior splines. A clutch ring includes a plurality of stepped interior splines including a slider spline portion engaged with the first set of splines of the first rotatable member and the stepped interior splines including a coupler spline portion being movable to engage the second set of splines on the second rotatable member, wherein the slider spline portion is configured to have less backlash with the first set of exterior splines than a backlash between the coupler spline portion and the second set of exterior splines. An actuator assembly is engaged with the clutch ring and operable to move the coupler spline portion of the clutch ring between an engaged and a disengaged position with the second set of splines.

[0016] According to a further aspect, the slider spline portion includes interior splines on the clutch ring and the slider spline portion has a smaller pitch diameter than the coupler spline portion.

[0017] According to a further aspect, the slider spline portion includes one of a different size and shape than the coupler spline portion.

[0018] According to an aspect of the present disclosure, a clutch engagement assembly includes a first rotatable member having a first set of exterior splines. A second rotatable member has a second set of exterior splines adjacent to the first set of exterior splines. A clutch ring includes a plurality of stepped interior splines including a slider spline portion engaged with the first set of splines of the first rotatable member and the stepped interior splines including a coupler spline portion being movable to engage the second set of splines on the second rotatable member. The slider spline portion is configured to have less backlash with the first set of exterior splines than a backlash between the coupler spline portion and the second set of exterior splines. A solenoid actuator assembly is engaged with the clutch ring and operable to move the clutch ring between an engaged and a disengaged position with the second set of splines. The solenoid actuator assembly includes at least one electric coil, a core movable relative to the electric coil and a plunger attached to the core and to a shift mechanism that engages the clutch ring. A pair of longitudinally spaced recesses are associated with one of the core and the plunger and configured to be engaged by a spring detent mechanism.

[0019] According to a further aspect, the pair of longitudinally spaced recesses are disposed directly on the core.

[0020] According to a further aspect, the pair of longitudinally spaced recesses are disposed on a catch mounted to the plunger.

[0021] Further areas of applicability will become apparent from the description provided herein. The description and specific examples in this summary are intended for purposes of illustration only and are not intended to limit the scope of the present disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0022] The drawings described herein are for illustrative purposes only of selected embodiments and not all possible implementations, and are not intended to limit the scope of the present disclosure.

[0023] FIG. 1 is a cross-sectional view of a vehicle differential having a disconnect assembly according to the principles of the present disclosure;

[0024] FIG. 2 is a perspective view of the actuator assembly according to the principles of the present disclosure;

[0025] FIG. 3 is an exploded perspective view of the clutch ring and the differential carrier housing portion of the differential case;

[0026] FIG. 4 is a cross-sectional view of the actuator assembly according to the principles of the present disclosure;

[0027] FIG. 5 is a detailed cross-sectional view of the shift fork and clutch ring;

[0028] FIG. 6 is a perspective view of the rocker according to the principles of the present disclosure;

[0029] FIG. 7 is a cross-sectional view of an alternative vehicle differential having a disconnect assembly shown in a connected state according to the principles of the present disclosure;

[0030] FIG. 8 is a cross-sectional view of the alternative vehicle differential having a disconnect assembly shown in a disconnected state according to the principles of the present disclosure;

[0031] FIG. 9 is an exploded perspective view of the alternative vehicle differential having a clutch ring mount according to the principles of the present disclosure;

[0032] FIG. 10 is a detailed cross-sectional view of the clutch ring mount engaged with the clutch ring;

[0033] FIG. 11 is a cross-sectional view of a clutch ring having slider splines engaging exterior splines of the case and coupler splines engaging the exterior splines of the carrier;

[0034] FIG. 12 is a detailed cross-sectional view of a clutch ring having slider splines and coupler splines according to the principles of the present disclosure;

[0035] FIG. 13 is a perspective view of a net forged clutch ring having slider splines and coupler splines according to the principles of the present disclosure;

[0036] FIG. 14 is a perspective view of a machined clutch ring having slider splines and coupler splines according to the principles of the present disclosure;

[0037] FIG. 15 is a plan view of a mechanically latched solenoid according to the principles of the present disclosure;

[0038] FIG. 16 is a cross sectional view of the mechanically latched solenoid latched in an extended position according to the principles of the present disclosure;

[0039] FIG. 17 is a cross sectional view of the mechanically latched solenoid latched in a retracted position according to the principles of the present disclosure; and

[0040] FIG. 18 is a cross sectional view of an alternative mechanically latched solenoid latched in an extended position according to the principles of the present disclosure.

[0041] Corresponding reference numerals indicate corresponding parts throughout the several views of the drawings.

DETAILED DESCRIPTION

[0042] Example embodiments will now be described more fully with reference to the accompanying drawings.

[0043] With reference to FIG. 1 a differential disconnect assembly **10** is shown including a differential case **12**. A differential gear set **14** is disposed within the differential case **12**. The differential gearset **14** includes two differential bevel gears **16, 18** that are rotatably arranged on a bearing pin **20** that forms a rotational axis for the differential bevel gears **16, 18**. A carrier **22** supports the bearing pin **20**. The carrier **22** is rotatably supported within the case **12** by a pair of bearing assemblies **24, 26**. The carrier **22** includes a plurality of exterior splines **28**. First and second differential side shaft gears **30, 32** are in meshing engagement with the bevel gears **16, 18**. A rotational axis of the side shaft gears **30, 32** intersect the rotational axis of the bevel gears **16, 18**. The differential case **12** can include a differential carrier housing portion **12A** and a planetary gear housing portion **12B** that allow for the assembly of the carrier **22** therein.

[0044] A clutch ring **34** has interior splines **36** that engage exterior splines **38** on the differential case **12**. The clutch ring **34** is axially movable into and out of engagement with the exterior splines **28** of the carrier **22** in order to rotatably engage or disengage the carrier **22** to the differential case **12**. With reference to FIG. 3, the differential carrier housing portion **12A** can include a plurality of engagement windows **39** that expose the exterior splines **38** on the differential case **12**. With continued reference to FIG. 3, the interior splines **36** of the clutch ring **34** can be extended in the location of the engagement windows and truncated where there are no engagement windows **39**. The engagement windows **39** (three are shown, but more or less can be utilized) provide an engagement interface with the differential carrier housing portion **12A**. The recessed window cutouts **39** provide optimal strength and integrity to the system as opposed to passing all the way through. An actuator assembly **40** is operable to axially move a shift fork **42** that engages the clutch ring **34**.

[0045] The actuator assembly **40** includes a mounting bracket (or other support structure) **44** that can be mounted to the differential case **12**. A gasket or seal can be provided between the mounting bracket **44** and the differential case **12**. The mounting bracket **44** can include a recessed groove for receiving the gasket. The mounting bracket **44** can be made from aluminum and includes a solenoid portion **44a** for mounting a solenoid **46**. The solenoid **46** includes a plunger **48** that engages a rocker **50**. The actuator does not need to include a solenoid and can include a vacuum actuator, a cam actuator, a motor-driven actuator, a pneumatic actuator, a hydraulic actuator, or any other actuator that would be known in the art. As shown in FIG. 2, the rocker **50** is pivotally mounted to the mounting bracket or other support structure **44** and is engaged with the shift fork **42**. The actuator assembly **40** may be reoriented at any angle in relation to the central axis of clutch ring **34** travel. The actuator assembly **40** may also be offset laterally from the axis of clutch ring **34** travel or rotated circumferentially around the axis of clutch ring **34** travel. The actuator assembly **40** is partially submerged in oil which reduces noise, vibration and harshness. As shown in FIG. 4, an oil seal **51** can engage the plunger **48**. Not pictured, the actuator assembly **40** may be positioned directly in line with the axis of clutch ring **34** travel, eliminating the need for the shift fork **42** and rocker **50**. In this embodiment, the clutch ring **34** is actuated by a series of push pins (not pictured) coupled directly to the clutch ring.

[0046] With reference to FIGS. 1 and 2, the shift fork **42** is slidably supported on an elongated translation pin **54** extending from a lower portion **44b** of the mounting bracket **44**. The pin **54** ensures the rotational rocker movement is properly converted to linear movement only when force is transferred to the shift fork **42**. As shown in FIG. 5, the shift fork **42** includes a bushing **55** that slides along the translation pin **54**. The bushing **55** can be made from VESPEL or other low friction material. The elongated translation pin **54** can extend parallel to an axis of rotation of the side shaft

gears **30**, **32**. When the solenoid **46** is actuated, the plunger **48** moves in fore and aft directions and pivots the rocker **50** to cause the shift fork **42** to translate along the translation pin **54**. As best shown in FIG. **2**, the shift fork **42** includes a pair of arms **56a**, **56b** that engage with the clutch ring **34** to move the clutch ring **34** from an engaged to a disengaged position and vice versa. As shown in FIG. **5**, the shift fork **42** can include wear pads **57** for engaging the clutch ring **34**. The wear pads **57** can be made from VESPEL or other low friction material.

[0047] With reference to FIG. **6**, the rocker **50** can be made from plastic or metal and can include a pair of integral pivot arms **62** extending from a mid-portion **50a** of the rocker **50**. An upper end **50b** of the rocker **50** includes snap engagement members **64a**, **64b** for engagement with a cross pin **48a** of the plunger **48**. As shown in FIG. **6**, a pair of optional latches **64c** are provided for engaging a top end of the cross pin **48a** of the plunger **48**. The pair of latches **64c** have a tapered inner face to facilitate insertion of the cross pin **48a**. The pair of latches **64c** can flex laterally outward when the cross pin is inserted and snap back to secure the cross pin in place. A lower end **50c** of the rocker **50** includes a rounded interface for engagement with a V-shaped channel **66** in an upper surface of the shift fork **42**.

[0048] Accordingly, in operation, the rocker **50** is pivotally mounted to the mounting bracket **44** and the cross pin **48a** of the plunger **48** of the solenoid **46** is connected to the snap engagement members **64a**, **64b** for allowing the solenoid to move the rocker **50** in a pivoting motion. As the rocker **50** is pivoted, the lower end **50c** of the rocker **50** moves the shift fork **42** linearly along the translation pin **54**. When the plunger **48** is retracted, the shift fork **42** is extended into engagement with the exterior splines **28** of the carrier **22** and when the plunger **48** is extended, the shift fork **52** is retracted out of engagement with the exterior splines **28** of the carrier **22**. The linear movement of the shift fork **42** creates a more durable design and requires less space and less material as compared to a pivoting shift fork design. The rocker **50** allows for an optimal design fit to the differential **10** as well as an easy customizable rocker profile.

[0049] The design also positions the line of force between the rocker **50** and the shift fork **42** very close to the shift fork translation pin **54**, thereby eliminating translation stiction. The use of the rocker **50** may be applicable to other disconnects.

[0050] The solenoid **46** can be “bi-stable” with a magnetic latching mechanism so that current is not needed when the solenoid is extended or retracted. However, a mono-stable solenoid may also be used.

[0051] With reference to FIGS. **7** and **8**, a differential disconnect assembly **110** is shown connected to a differential case **112** (partially shown in FIGS. **7** and **8**). A differential gear set **114** is disposed within the differential case **112**. The differential gearset **114** includes two differential bevel gears **116**, **118** that are rotatably arranged on a bearing pin **120** that forms a rotational axis for the differential bevel gears **116**, **118**. A carrier **122** supports the bearing pin **120**. The carrier **122** is rotatably supported within the case **112** by a pair of bearing assemblies **124**, **126**. The carrier **122** includes a plurality of exterior splines **128**. First and second differential side shaft gears **130**, **132** are in meshing engagement with the bevel gears **116**, **118**. A rotational axis of the side shaft gears **130**, **132** intersect the rotational axis of the bevel gears **116**, **118**. The differential case **112** can include a differential carrier housing portion **112A** and a planetary gear housing portion (shown in FIG. **1**) that allow for the assembly of the carrier **122** therein.

[0052] With reference to FIG. **9**, a clutch ring **134** has exterior splines **136** that engage interior splines **138** on the differential case **112A**. The clutch ring **134** has interior splines **137** that are axially movable into and out of engagement with the exterior splines **128** of the carrier **122** in order to rotatably engage or disengage the carrier **122** to the differential case **112A**. With reference to FIG. **9**, the differential carrier housing portion **112A** can include a plurality of engagement windows **139** that expose the clutch ring **134**. With continued reference to FIG. **9**, the exterior splines **136** of the clutch ring **134** can be interrupted in the location of the engagement windows **139**. A clutch ring mount **160** includes an annular ring portion **162** with an exterior groove **164**. A

plurality of arms **166** extend axially from the annular ring portion **162** and include an interior groove **168** that engage the clutch ring **134**. The clutch ring mount **160** can be made from plastic or other material that allow the arms **166** to flex for snap engagement of the grooves **168** with the clutch ring **134**. The engagement windows **139** (six are shown, but more or less can be utilized) provide an engagement interface for each of the plurality of arms **166** to engage the clutch ring within the differential case **112**. As shown in FIGS. **7** and **8**, an actuator assembly **140** is operable to axially move a shift fork **142** that engages the clutch ring mount **160** that in turn moves the clutch ring **134**.

[0053] The clutch ring mount **160** allows the actuator assembly **140** to be mounted at an alternative location for easier packaging of the actuator assembly **140**. The actuator assembly **140** includes a mounting bracket (or other support structure) **144** that can be mounted near the differential case **112**. The mounting bracket **144** can be made from aluminum and includes a solenoid portion **144a** for mounting a solenoid **146**. The solenoid **146** includes a plunger **148** that engages a rocker **150**. The actuator does not need to include a solenoid and can include a vacuum actuator, a cam or other actuator. As shown in FIGS. **7** and **8**, the rocker **150** is pivotally mounted to the mounting bracket **144** or other support structure **144** and is engaged with the shift fork **142**. The rocker **150** can take on various forms.

[0054] With reference to FIGS. **7** and **8**, the shift fork **142** is slidably supported on an elongated translation pin **154** extending from a lower portion **144b** of the mounting bracket **144**. The translation pin **154** ensures the rotational rocker movement is properly converted to linear movement only when force is transferred to the shift fork **142**. The elongated translation pin **154** can extend parallel to an axis of rotation of the side shaft gears **130**, **132**. When the solenoid **146** is actuated, the plunger **148** moves in fore and aft directions and pivots the rocker **150** to cause the shift fork **142** to translate along the translation pin **154**. As best shown in FIGS. **7** and **8**, the shift fork **142** includes a pair of arms **56a**, **56b** that engage with the clutch ring mount **160** to move the clutch ring **134** from an engaged position (FIG. **7**) to a disengaged position (FIG. **8**) and vice versa.

[0055] The clutch ring mount **160** allows the clutch ring **134** to be more easily machined. The clutch ring mount **160** can be made from plastic and is easy to form. The design allows the torque to be distributed across more splines which makes for a more robust design. The clutch ring mount **160** also reduces backlash and provides improved noise, vibration and harshness.

[0056] With reference to FIGS. **11** and **12** a clutch ring **234** having stepped splines **236** including slider spline portions **236a** engaging exterior splines **238** of an axle **212** and coupler spline portions **236b** engaging the exterior splines **228** of a wheel bearing coupler **222**. Many applications require an actuator to have minimal NVH when shifting. These requirements make it difficult to tune the backlash between the coupler splines and the axle splines with a common clutch ring spline size. Typically the interface between the clutch ring and the coupling splines on the wheel hub requires much more backlash than the sliding splines on the axle. Accordingly, the stepped splines **236** including slider spline portions **236a** engaging exterior splines **238** of the axle **212** and coupler spline portions **236b** engaging the exterior splines **228** of the wheel bearing coupler **222** reduces the systems overall backlash to a minimum. The slider spline portions **236a** are aligned with the coupler spline portions **236b** such that the number of slider spline portions **236a** and the coupler spline portions are the same, but the shape of the slider spline portions **236a** are different than the coupler spline portions **236b** with the slider spline portions **236a** having a larger tooth thickness than the coupler spline portions **236b**. (The larger tooth thickness of **236a** results in a tighter fit with the mating spline **38**. The tighter fit results in less backlash) The coupler spline portion **236b** has a smaller tooth thickness resulting in more backlash with coupler spline **228**. Additionally spline **236a** and **236b** will have but not limited to the same pitch diameter. The slider spline portions **236a** can have a wider dimension than the coupler spline portions **236b** in an axial direction. The slider spline portions are configured to have a reduced backlash with the exterior splines **238** of the axle **212** than the coupler spline portions **236b** have with the exterior splines **228**

of the wheel bearing coupler **222**.

[0057] As shown in FIG. **13**, a net forged clutch ring **234'** with net-forged splines allows for the stepped splines **236** having two different spline portions **236a**, **236b** having different shapes/sizes. As shown in FIG. **13**, the inner slider spline portions **236a** have a tighter space width of the external coupler spline portions **236b**. The coupler spline portions **236b** can have a pointed and blended tooth end detail. FIG. **14** shows a perspective view of the clutch ring **234** that has been machined at the outer diameter from the net-forged clutch ring of FIG. **13** to provide an outer annular groove **238** and to remove excess material from the net forged clutch ring.

[0058] With reference to FIGS. **15-17**, a mechanically latched solenoid assembly **346** is shown according to an optional embodiment of the present disclosure. The mechanically latched solenoid assembly **346** includes a solenoid housing **348** supporting first and second fixed coils **350**, **352** and a movable core **354**. A plunger **356** is attached to the core **354**. The plunger **356** includes a pair of longitudinally spaced recesses **358** that can be formed directly on the plunger or on a catch **360** that is mounted to the plunger **356**. The catch **360** can be threadedly connected to the plunger and can support a pin **48a** that is connected to the rocker **50** as disclosed herein. A ball detent **362** is supported by the solenoid mount and has a ball **364** that is biased by a spring into engagement with the recesses **358** of the plunger **356**. The solenoid **346** can be actuated in an extended or a retracted direction and the ball detent engages either a forward or rearward one of the recesses **358** to latch the plunger **356** in the extended or retracted position.

[0059] In an alternative embodiment as shown in FIG. **18**, the longitudinally spaced ball recesses **358** can be formed in the outer surface of the core **354** of the solenoid and the ball detent **362** can be mounted to the solenoid housing **348** so that the ball **364** of the ball detent **362** engages with either the forward or rearward recess **358** to latch the plunger **356** in either the forward or rearward direction.

[0060] Example embodiments are provided so that this disclosure will be thorough, and will fully convey the scope to those who are skilled in the art. Numerous specific details are set forth such as examples of specific components, devices, and methods, to provide a thorough understanding of embodiments of the present disclosure. It will be apparent to those skilled in the art that specific details need not be employed, that example embodiments may be embodied in many different forms and that neither should be construed to limit the scope of the disclosure. In some example embodiments, well-known processes, well-known device structures, and well-known technologies are not described in detail.

[0061] The terminology used herein is for the purpose of describing particular example embodiments only and is not intended to be limiting. As used herein, the singular forms “a,” “an,” and “the” may be intended to include the plural forms as well, unless the context clearly indicates otherwise. The terms “comprises,” “comprising,” “including,” and “having,” are inclusive and therefore specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof. The method steps, processes, and operations described herein are not to be construed as necessarily requiring their performance in the particular order discussed or illustrated, unless specifically identified as an order of performance. It is also to be understood that additional or alternative steps may be employed.

[0062] When an element or layer is referred to as being “on,” “engaged to,” “connected to,” or “coupled to” another element or layer, it may be directly on, engaged, connected or coupled to the other element or layer, or intervening elements or layers may be present. In contrast, when an element is referred to as being “directly on,” “directly engaged to,” “directly connected to,” or “directly coupled to” another element or layer, there may be no intervening elements or layers present. Other words used to describe the relationship between elements should be interpreted in a like fashion (e.g., “between” versus “directly between,” “adjacent” versus “directly adjacent,” etc.). As used herein, the term “and/or” includes any and all combinations of one or more of the

associated listed items.

[0063] Although the terms first, second, third, etc. may be used herein to describe various elements, components, regions, layers and/or sections, these elements, components, regions, layers and/or sections should not be limited by these terms. These terms may be only used to distinguish one element, component, region, layer or section from another region, layer or section. Terms such as “first,” “second,” and other numerical terms when used herein do not imply a sequence or order unless clearly indicated by the context. Thus, a first element, component, region, layer or section discussed below could be termed a second element, component, region, layer or section without departing from the teachings of the example embodiments.

[0064] Spatially relative terms, such as “inner,” “outer,” “beneath,” “below,” “lower,” “above,” “upper,” and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. Spatially relative terms may be intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. For example, if the device in the figures is turned over, elements described as “below” or “beneath” other elements or features would then be oriented “above” the other elements or features. Thus, the example term “below” can encompass both an orientation of above and below. The device may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein interpreted accordingly.

[0065] The foregoing description of the embodiments has been provided for purposes of illustration and description. It is not intended to be exhaustive or to limit the disclosure. Individual elements or features of a particular embodiment are generally not limited to that particular embodiment, but, where applicable, are interchangeable and can be used in a selected embodiment, even if not specifically shown or described. The same may also be varied in many ways. Such variations are not to be regarded as a departure from the disclosure, and all such modifications are intended to be included within the scope of the disclosure.

Claims

1. A vehicle differential disconnect assembly, comprising: a differential case; a differential gear set carried within the differential case and including a differential carrier rotatably supported within the differential case, the differential carrier supporting a bearing pin that supports a pair of bevel gears in meshing engagement with a pair of side shaft gears; a clutch ring including a first set of splines engaged with a second set of splines of the differential case and being movable to engage a third set of splines on the differential carrier; an actuator assembly that engages a rocker that is pivotally mounted to a support structure and connected to the plunger; and a shift fork operably engaged with the clutch ring and slidably mounted for translation along an axis, the shift fork including an engagement feature for receiving an end of the rocker, wherein activation of the actuator causes pivotal movement of the rocker to cause the shift fork to translate along the axis.
2. The vehicle differential disconnect assembly according to claim 1, further comprising a clutch ring mount connected between the shift fork and the clutch ring.
3. The vehicle differential disconnect assembly according to claim 2, wherein the clutch ring mount includes an annular ring portion with an exterior groove engaged by the shift fork.
4. The vehicle differential disconnect assembly according to claim 3, wherein the clutch ring mount includes a plurality of arms extending axially from the annular ring portion and including a groove engaging the clutch ring.
5. The vehicle differential disconnect assembly according to claim 4, wherein the plurality of arms each extend through a respective window in the differential case.
6. The vehicle differential disconnect assembly according to claim 1, wherein the first set of splines on the clutch ring that engage the second set of splines on the differential case include exterior splines and the first set of splines on the clutch ring that engage the third set of splines on the

differential carrier include interior splines.

7. The vehicle differential disconnect assembly according to claim 1, wherein the first set of splines on the clutch ring that engage second set of splines on the differential case include interior splines and the first set of splines on the clutch ring that engage the third set of splines on the differential carrier include interior splines.
8. The vehicle differential disconnect assembly according to claim 1, wherein the actuator assembly further comprises a solenoid with a plunger.
9. The vehicle differential disconnect assembly according to claim 1, wherein the actuator assembly includes one of a bi-stable actuator assembly and a mono-stable actuator assembly.
10. The vehicle differential disconnect assembly according to claim 1, wherein the first set of splines of the clutch ring include a plurality of stepped splines including a slider spline portion engaged with the second set of splines of the of the differential case and the plurality of stepped splines including a coupler spline portion being movable to engage the second set of splines on the second rotatable member, wherein the slider spline portion being configured to have less backlash with the first set of exterior splines than a backlash between the coupler spline portion and the second set of exterior splines.
11. The vehicle differential disconnect assembly according to claim 1, wherein the actuator includes at least one electric coil, a core movable relative to the electric coil and a plunger attached to the core and to the rocker, a pair of longitudinally spaced recesses associated with one of the core and the plunger and configured to be engaged by a spring detent mechanism.
12. A clutch engagement assembly, comprising: a first rotatable member having a first set of exterior splines; a second rotatable member having a second set of exterior splines adjacent to the first set of exterior splines; a clutch ring including a plurality of stepped interior splines including a slider spline portion engaged with the first set of splines of the first rotatable member and the stepped interior splines including a coupler spline portion being movable to engage the second set of splines on the second rotatable member, wherein the slider spline portion is configured to have less backlash with the first set of exterior splines than a backlash between the coupler spline portion and the second set of exterior splines; and an actuator assembly engaged with the clutch ring and operable to move the coupler spline portion of the clutch ring between an engaged and a disengaged position with the second set of splines.
13. The clutch engagement assembly according to claim 12, wherein the slider spline portion includes interior splines on the clutch ring and the slider spline portion has a smaller pitch diameter than the coupler spline portion.
14. The clutch engagement assembly according to claim 12, wherein the slider spline portion includes one of a different size and shape than the coupler spline portion.
15. A clutch engagement assembly, comprising: a first rotatable member having a first set of exterior splines; a second rotatable member having a second set of exterior splines adjacent to the first set of exterior splines; a clutch ring including a plurality of stepped interior splines including a slider spline portion engaged with the first set of splines of the first rotatable member and the stepped interior splines including a coupler spline portion being movable to engage the second set of splines on the second rotatable member, wherein the slider spline portion being configured to have less backlash with the first set of exterior splines than a backlash between the coupler spline portion and the second set of exterior splines; and a solenoid actuator assembly engaged with the clutch ring and operable to move the clutch ring between an engaged and a disengaged position with the second set of splines, the solenoid actuator assembly including at least one electric coil, a core movable relative to the electric coil and a plunger attached to the core and to a shift mechanism that engages the clutch ring, a pair of longitudinally spaced recesses associated with one of the core and the plunger and configured to be engaged by a spring detent mechanism.
16. The clutch engagement assembly according to claim 15, wherein the pair of longitudinally spaced recesses are disposed directly on the core.

17. The clutch engagement assembly according to claim 15, wherein the pair of longitudinally spaced recesses are disposed on a catch mounted to the plunger.
