

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250285235

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

CHOI; Honggyu et al.

ELECTRONIC DEVICE AND OPERATING METHOD OF THE SAME

Abstract

An electronic device configured to convert a still image into a video, includes: memory in which one or more instructions are stored; and at least one processor, wherein the one or more instructions, when executed by the at least one processor individually or collectively, cause the electronic device to: obtain flow information about a first image, obtain a plurality of transformation images obtained by transforming the first image, based on the flow information about the first image, obtain residual information about the plurality of transformation images, based on the plurality of transformation images and the first image, and generate a plurality of frame images, based on the plurality of transformation images and the residual information about the plurality of transformation images.

Inventors: CHOI; Honggyu (Suwon-si, KR), KANG; Soomin (Suwon-si, KR), AHN; Iljun (Suwon-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 1000008531896

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 19/173278

Filed: April 08, 2025

Foreign Application Priority Data

KR 10-2024-0032184

Mar. 06, 2024

KR 10-2024-0180225

Dec. 06, 2024

Related U.S. Application Data

parent WO continuation PCT/KR2025/002919 20250305 PENDING child US 19173278

Publication Classification

Int. Cl.: **G06T5/60** (20240101); **G06T3/18** (20240101); **G06T3/4046** (20240101); **G06T7/246** (20170101)

U.S. Cl.:

CPC **G06T5/60** (20240101); **G06T3/18** (20240101); **G06T3/4046** (20130101); **G06T7/246** (20170101); **G06T2207/10016** (20130101); **G06T2207/20084** (20130101); **G06T2207/20092** (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application is a by-pass continuation application of International Application No. PCT/KR2025/002919, filed on Mar. 5, 2025, which is based on and claims priority to Korean Patent Application No. 10-2024-0032184, filed on Mar. 6, 2024, and Korean Patent Application No. 10-2024-0180225, filed on Dec. 6, 2024, in the Korean Intellectual Property Office, the disclosures of which are incorporated by reference herein their entireties.

BACKGROUND

1. Field

[0002] The disclosure relates to an electronic device for converting a still image into a video and an operating method of the electronic device.

2. Description of Related Art

[0003] As data traffic increases exponentially with the development of computer technology, artificial intelligence has become an important trend for leading future innovation. Artificial intelligence mimics human thinking, and thus, is applicable to virtually all industries limitlessly. Representative technologies of artificial intelligence include pattern recognition, machine learning, expert systems, neural networks, and natural language processing.

[0004] A neural network models the characteristics of human biological nerve cells by using mathematical expressions, and mimics a human's learning ability. The neural network is able to generate a mapping between input data and output data. The neural network's ability to generate such mapping may be expressed as the learning ability of the neural network. Also, the neural network has a generalization ability to generate correct output data with respect to input data that has not been used for learning, based on a learning result.

[0005] The neural network may be used for image processing, and in particular, image processing for generating an image, removing noise or artifacts of an image, or increasing a resolution of an image may be performed by using, for example, a deep neural network (DNN).

SUMMARY

[0006] An electronic device according to an embodiment of the disclosure may convert a still image into a video.

[0007] The electronic device according to an embodiment of the disclosure may include memory in which one or more instructions are stored and at least one processor including a processing circuit.

[0008] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, may cause the electronic device to obtain flow information about a first image.

[0009] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, may cause the electronic device to obtain

a plurality of transformation images obtained by transforming the first image, based on the flow information.

[0010] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, may cause the electronic device to obtain residual information about the plurality of transformation images based on the plurality of transformation images and the first image.

[0011] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, may cause the electronic device to generate a plurality of frame images based on the plurality of transformation images and the residual information.

[0012] The operating method of the electronic device according to an embodiment of the disclosure may include obtaining flow information about a first image.

[0013] The operating method of the electronic device according to an embodiment of the disclosure may include obtaining a plurality of transformation images obtained by transforming the first image, based on the flow information.

[0014] The operating method of the electronic device according to an embodiment of the disclosure may include obtaining residual information about the plurality of transformation images based on the plurality of transformation images and the first image.

[0015] The operating method of the electronic device according to an embodiment of the disclosure may include generating a plurality of frame images based on the plurality of transformation images and the residual information.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] The above and other aspects, features, and advantages of certain embodiments of the disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

[0017] FIG. 1 illustrates an operation in which an electronic device converts a still image into a video, according to an embodiment of the disclosure;

[0018] FIG. 2 illustrates a configuration of an image processing module, according to an embodiment of the disclosure;

[0019] FIG. 3 illustrates a encoder included in a feature extraction unit, according to an embodiment of the disclosure;

[0020] FIG. 4 illustrates a residual block, according to an embodiment of the disclosure;

[0021] FIG. 5 illustrates a flow generation unit, according to an embodiment of the disclosure;

[0022] FIG. 6 illustrates an attention block, according to an embodiment of the disclosure;

[0023] FIG. 7 illustrates a down block, according to an embodiment of the disclosure;

[0024] FIG. 8 illustrates a spatial attention block, according to an embodiment of the disclosure;

[0025] FIG. 9 illustrates an up block, according to an embodiment of the disclosure;

[0026] FIG. 10 illustrates a feature transformation unit and a feature decoding unit, according to an embodiment of the disclosure;

[0027] FIG. 11 illustrates a residual generation unit, according to an embodiment of the disclosure;

[0028] FIG. 12 illustrates a residual synthesis unit, according to an embodiment of the disclosure;

[0029] FIG. 13 illustrates an operating method of an electronic device, according to an embodiment of the disclosure;

[0030] FIG. 14 illustrates an operation in which an electronic device converts a still image into a video, according to an embodiment of the disclosure;

[0031] FIG. 15 illustrates an operation in which an electronic device converts a still image into a

video, according to an embodiment of the disclosure;

[0032] FIG. **16** illustrates an operation in which an electronic device converts a still image into a video, according to an embodiment of the disclosure;

[0033] FIG. **17** illustrates an operation in which an electronic device converts a still image into a video, according to an embodiment of the disclosure;

[0034] FIG. **18** illustrates a configuration of an electronic device, according to an embodiment of the disclosure; and

[0035] FIG. **19** illustrates a configuration of an electronic device, according to an embodiment of the disclosure.

DETAILED DESCRIPTION

[0036] The terms used herein will be briefly described, and the disclosure will be described in detail.

[0037] The terms used herein are general terms currently widely used in the art in consideration of functions in the disclosure, but the terms may vary according to the intention of one of ordinary skill in the art, precedents, or new technology in the art. Also, some of the terms used herein may be arbitrarily chosen by the present applicant, and in this case, these terms are defined in detail below. Accordingly, the specific terms used herein should be defined based on the unique meanings thereof and the whole context of the disclosure.

[0038] When a certain part “includes” a certain component, the part does not exclude another component but may further include another component, unless the context clearly dictates otherwise. Also, the term “. . . unit” or “. . . module” refers to a unit that performs at least one function or operation, and the unit may be implemented as hardware or software or as a combination of hardware and software. The “unit” and the “module” used in the disclosure refer to a hardware component such as a processor or a circuit, and/or a software component executed by a hardware component such as a processor. The “unit” and the “module” may be implemented by a program that is stored in a storage medium which may be addressed, and is executed by a processor. For example, the “unit” the “module” may be implemented by components such as software components, object-oriented software components, class components, and task components, processes, functions, attributes, procedures, sub-routines, segments of a program code, drivers, firmware, a micro code, a circuit, data, a database, data structures, tables, arrays, and parameters.

[0039] Embodiments will now be described more fully with reference to the accompanying drawings for one of ordinary skill in the art to be able to perform the embodiments without any difficulty. However, the disclosure may be embodied in many different forms and is not limited to the embodiments set forth herein. For clarity, portions irrelevant to the descriptions of the disclosure are omitted in the drawings, and like components are denoted by like reference numerals throughout the specification.

[0040] In an embodiment of the specification, the term “user” refers to a person who controls a system, a function, or an operation, and may include a developer, a manager, or an installation engineer.

[0041] Also, in an embodiment of the specification, an ‘image’ or a ‘picture’ may refer to a still image, a moving image including a plurality of consecutive still images (or frames), or a video.

[0042] The phrase “at least one of,” when used with a list of items, means that different combinations of one or more of the listed items may be used, and only one item in the list may be needed. For example, “at least one of A, B, and C” includes any of the following combinations: A, B, C, A and B, A and C, B and C, and A and B and C, and any variations thereof. As an additional example, the expression “at least one of a, b, or c” may indicate only a, only b, only c, both a and b, both a and c, both b and c, all of a, b, and c, or variations thereof. Similarly, the term “set” means one or more. Accordingly, the set of items may be a single item or a collection of two or more items.

[0043] FIG. 1 illustrates an operation in which an electronic device converts a still image into a video, according to an embodiment of the disclosure.

[0044] The electronic device according to an embodiment of the disclosure may be implemented as any of various electronic devices such as a mobile phone, a tablet PC, a digital camera, a camcorder, a laptop computer, a desktop, an electronic book reader, a digital broadcasting terminal, a personal digital assistant (PDA), a portable multimedia player (PMP), a navigation device, an MP3 player, a camcorder, an Internet protocol television (IPTV), a digital television (DTV), or a wearable device.

[0045] Referring to FIG. 1, an electronic device **100** according to an embodiment of the disclosure may generate a video **20** including a plurality of frame images, by processing a first image **10** by using an image processing module (e.g., an image processing network). In this case, the plurality of frame images included in the video **20** may be images in which details (e.g., structure information such as edges and detailed texture information included in the first image) included in the first image **10** are maintained. Also, the plurality of frame images may be high-quality images that do not include artifacts caused by warping and image qualities of the plurality of frame images are not degraded compared to the first image **10**.

[0046] The image processing module according to an embodiment of the disclosure may include suitable logic, circuitry, interfaces, and/or code that may enable a still image to be converted into a video. The image processing module may include one or more neural networks. For example, the image processing module may include an encoder that converts an input image into a compressed representation or extracts features of the input image, a decoder that restores the compressed representation to an original resolution, and a U-Net having an encoder-decoder structure. However, the disclosure is not limited to the above examples. The image processing module may include various neural networks.

[0047] Hereinafter, the image processing module according to an embodiment of the disclosure will be described in detail with reference to the drawings.

[0048] FIG. 2 illustrates a configuration of an image processing module, according to an embodiment of the disclosure.

[0049] Referring to FIG. 2, an image processing module **200** according to an embodiment of the disclosure may include a feature extraction unit **210**, a feature transformation unit **220**, a feature decoding unit **230**, a noise generation unit **240**, a flow generation unit **250**, a residual generation unit **260**, and a residual synthesis unit **270**. However, the disclosure is not limited to the above examples.

[0050] The feature extraction unit **210** may extract feature information from a first image **201** by using an encoder. The encoder is a network for extracting feature information from an image and may include one or more convolutional neural networks (CNN). The feature extraction unit **210** will be described in detail with reference to FIGS. 3 and 4.

[0051] The noise generation unit **240** may randomly generate noise images. For example, the noise generation unit **240** may generate noise images following a Gaussian distribution (normal distribution). However, the disclosure is not limited to the above example.

[0052] The flow generation unit **250** may generate flow information (flow map) based on the feature information extracted by the feature extraction unit **210** and the noise images generated by the noise generation unit **240**, by using a flow generation network. The flow generation network may include a U-Net having an encoder-decoder structure. The flow generation network will be described in detail with reference to FIGS. 5 to 9.

[0053] The feature transformation unit **220** may generate transformed feature information, by performing warping by applying the flow information generated by the flow generation unit **250** to the feature information extracted by the feature extraction unit **210**. The feature decoding unit **230** may generate transformed images by processing the transformed feature information, by using a decoder. The decoder may restore compressed information (e.g., feature information) to an original

resolution. The feature transformation unit **220** and the feature decoding unit **230** will be described in detail with reference to FIG. **10**.

[0054] The residual generation unit **260** may generate residual information (residual map) based on the transformed images generated by the feature transformation unit **220**, the first image **201**, and the noise images generated by the noise generation unit **240**, by using a residual generation network. The residual generation network may include a U-Net having an encoder-decoder structure. The residual generation network will be described in detail with reference to FIG. **11**.

[0055] The residual synthesis unit **270** may generate a plurality of frame images **202** by synthesizing the residual information generated by the residual generation unit **260** with the transformed images generated by the feature decoding unit **230**. The residual synthesis unit **270** will be described in detail with reference to FIG. **12**.

[0056] Hereinafter, the feature extraction unit **210**, the feature transformation unit **220**, the feature decoding unit **230**, the noise generation unit **240**, the flow generation unit **250**, the residual generation unit **260**. The residual synthesis unit **270** will be described in detail with reference to the drawings.

[0057] FIG. **3** illustrates an encoder included in the feature extraction unit **210**, according to an embodiment of the disclosure.

[0058] Referring to FIG. **3**, the feature extraction unit **210** according to an embodiment of the disclosure may include an encoder **300**. The encoder **300** according to an embodiment of the disclosure may extract feature information **302** of a first image **301**. The encoder **300** may include one or more convolutional layers **310**, one or more residual blocks **320** (“ResBlk” **320** in FIG. **3**), a normalization layer **330** (“Norm” **330**), and an activation layer **340** (“ACTIVATION FUNCTION” **340**).

[0059] In the convolutional layer **310** (“Conv” **310**) according to an embodiment of the disclosure, a convolution operation may be performed between input data (or input image) input to the convolutional layer **310** and a kernel included in the convolutional layer **310**.

[0060] The residual block **320** according to an embodiment of the disclosure may include a skip connection that skips one or more layers included in the residual block **320**. The residual block will be described in detail with reference to FIG. **4**.

[0061] FIG. **4** illustrates the residual block **320**, according to an embodiment of the disclosure.

[0062] Referring to FIG. **4**, the residual block **320** (“ResBlk” **320** in FIG. **4**) may include one or more normalization layers **410** (“Norm” **410**), activation layers **420** (“ACTIVATION FUNCTION” **420**), convolutional layers **430** (“Conv” **430**), and a summation layer **440**. Also, the residual block **320** may include a skip connection **450** that performs a convolution operation on input data input to the residual block **320** and transmits a result to the summation layer **440**.

[0063] In the normalization layer **410**, a range of values of data input to the normalization layer **410** may be adjusted. In the normalization layer **410**, batch normalization, layer normalization, instance normalization, group normalization, etc. may be performed.

[0064] In the activation layer **420**, an activation function operation of applying an activation function to input data input to the activation layer **420** may be performed. The activation function operation is an operation for introducing non-linear characteristics, and examples of the activation function may include a sigmoid function, a Tanh function, a rectified linear unit (ReLU) function, a leaky ReLU function, an exponential linear unit (ELU) function, and a Swish function (sigmoid linear unit (SiLU) function). However, the disclosure is not limited to the above examples.

[0065] In the convolutional layer **430**, a convolution operation may be performed between input data input to the convolutional layer **430** and a kernel included in the convolutional layer.

[0066] In the summation layer **440**, an element-wise summation operation of pieces of data input to the summation layer **440** may be performed.

[0067] Referring back to FIG. **3**, in the normalization layer **330**, a range of values of data input to the normalization layer **330** may be adjusted. In the normalization layer **330**, batch normalization,

layer normalization, instance normalization, group normalization, etc. may be performed.

[0068] In the activation layer **340**, an activation function operation of applying an activation function to input data (input to the activation layer **340**) may be performed. The activation function operation is an operation for introducing non-linear characteristics. Examples of the activation function may include a sigmoid function, a Tanh function, a rectified linear unit (ReLU) function, a leaky ReLU function, an exponential linear unit (ELU) function, and a Swish function (sigmoid linear unit (SiLU) function). However, the disclosure is not limited to the above examples.

[0069] The encoder **300** according to an embodiment of the disclosure may output the feature information **302** about the first image **301**.

[0070] FIG. **5** illustrates a flow generation unit, according to an embodiment of the disclosure.

[0071] Referring to FIG. **5**, the flow generation unit **250** may include a flow generation network **500**. The flow generation network **500** may include a U-Net having an encoder-decoder structure.

[0072] The flow generation network **500** may include one or more concatenation layers, one or more convolutional layers, a temporal attention block, a spatial attention block, a normalization layer, one or more residual blocks, down blocks, and up blocks.

[0073] Noise information **501** generated by the noise generation unit **240** and the feature information **302** about a first image may be input to the flow generation network **500**. The noise information **501** and the feature information **302** about the first image may be input to a first concatenation layer **511**.

[0074] In the first concatenation layer **511**, pieces of data input to the first concatenation layer **511** may be concatenated. For example, data obtained by concatenating the noise information **501** (first input data) and the feature information **302** about the first image (second input data) along a channel direction may be output from the first concatenation layer **511**.

[0075] In a first convolutional layer **521** ("Conv" **521**), a convolution operation may be performed between input data and a kernel included in the first convolutional layer **521**.

[0076] Data output from the first convolutional layer **521** may be input to a first temporal attention block **531** ("Temporal attn" **531** in FIG. **5**). Also, data output from the first convolutional layer **521** may be input to a second concatenation layer **512** of FIG. **5** described below.

[0077] In the first temporal attention block **531**, attention may be applied within a time axis for each position of pixels included in input data. Here, attention may refer to a method of finding related features by using similarity between features, aggregating the related features into one, and extracting aggregated feature information.

[0078] In the first temporal attention block **531**, an attention operation may be performed. An attention operation refers to an operation of obtaining correlation information (e.g., similarity information) between query data "q" and key data "k", obtaining a weight based on the correlation information, reflecting the weight in value data "v" mapped to the key data k, and performing a weighted sum on the value data "v" in which the weight is reflected.

[0079] In this case, an attention operation (performed based on query data "q", key data "k", and value data "v" obtained from the same input data) may be referred to as a self-attention operation.

[0080] The attention operation performed in the first temporal attention block **531** will be described in detail with reference to FIG. **6**.

[0081] FIG. **6** illustrates an attention block, according to an embodiment of the disclosure.

[0082] Referring to FIG. **6**, in the first temporal attention block **531**, query data "q", key data "k", and value data "v" may be obtained, based on input data input to the first temporal attention block **531**.

[0083] For example, in a linear layer **611** ("Linear" **611**), linear transformation of data input to the linear layer **611** may be performed. For example, a multiplication operation may be performed between data input to the linear layer **611** and a weight matrix included in the linear layer **611**.

[0084] Data obtained by performing the multiplication operation with the weight matrix in the linear layer **611** may be input to a split layer **620** ("Split" **620**).

[0085] The data input to the split layer **620** may be split into a preset number. For example, the data input to the split layer **620** may each be split into query data “q”, key data “k”, and value data “v”.

[0086] The query data “q”, key data “k”, and value data “v” may be respectively input to reshape layers **631**, **632**, and **633** (“reshape” **631**, “reshape” **632**, “reshape” **633**). In the reshape layers **631**, **632**, and **633**, the input data may be reshaped to a specific dimension.

[0087] First correlation data “e” may be obtained through an element-wise multiplication operation between the query data (“q”) and key data (“k”) reshaped in the reshape layers **631** and **632**.

[0088] Second correlation data may be obtained by adding a position bias (“pos bias”) to the first correlation data.

[0089] The first temporal attention block **531** may obtain weight data A by applying a softmax function (“softmax” in FIG. **6**) to the second correlation data, and may perform an element-wise multiplication operation between the weight data A and the value data reshaped in the reshape layer **633**.

[0090] In a reshape layer **634** (“reshape” **634**), first output data “a” may be obtained by reshaping data obtained by performing the element-wise multiplication operation.

[0091] The first temporal attention block **531** may obtain second output data by performing a multiplication operation between the first output data a and a weight matrix included in a linear layer **612** (“Linear” **612**).

[0092] Referring back to FIG. **5**, data output from the first temporal attention block **531** may be sequentially image-processed in a normalization layer **540** (“Norm” **540**) and a first residual block **551** (“ResBlk” **551**).

[0093] Data output from the first temporal attention block **531** may be input to the normalization layer **540**.

[0094] In the normalization layer **540**, a range of values of data input to the normalization layer **540** may be adjusted. In the normalization layer **540**, batch normalization, layer normalization, instance normalization, group normalization, etc. may be performed.

[0095] Data output from the normalization layer **540** may be input to the first residual block **551**.

[0096] In the first residual block **551**, operations illustrated and described with reference to FIG. **4** may be performed, and data output from the first residual block **551** may be input to a first down block **561** (“Down Block” **561** in FIG. **5**).

[0097] The first down block **561** will be described in detail with reference to FIG. **7**.

[0098] FIG. **7** illustrates a down block, according to an embodiment of the disclosure.

[0099] Referring to FIG. **7**, the first down block **561** according to an embodiment of the disclosure may include one or more residual blocks, a spatial attention block, a temporal attention block, and a down sampling layer.

[0100] Data input to the first down block **561** according to an embodiment of the disclosure may be sequentially image-processed in two residual blocks **711** (“ResBlk” **711**) and **712** (“ResBlk” **712**), a spatial attention block **720** (“Spatial Attn” **720**), a temporal attention block **730** (“Temporal Attn” **730**), and a down sampling layer **740** (“Down sample” **740**).

[0101] In the two residual blocks **711** and **712**, operations illustrated and described with reference to FIG. **4** may be performed. Also, in the temporal attention block **730**, operations illustrated and described with reference to FIG. **6** may be performed.

[0102] In the spatial attention block **720**, attention may be applied within a space axis for each input frame. Here, attention may refer to a method of finding related features by using similarity between features, aggregating the related features into one, and extracting aggregated feature information.

[0103] In the spatial attention block **720**, an attention operation may be performed. An attention operation refers to an operation of obtaining correlation information (e.g., similarity information) between query data “q” and key data “k”, obtaining a weight based on the correlation information, reflecting the weight in value data “v” mapped to the key data k, and performing a weighted sum

on the value data “v” in which the weight is reflected.

[0104] In this case, an attention operation performed (based on query data “q”, key data “k”, and value data “v” obtained from the same input data) may be referred to as a self-attention operation.

[0105] The attention operation performed in the spatial attention block **720** will be described in detail with reference to FIG. **8**.

[0106] FIG. **8** illustrates a spatial attention block, according to an embodiment of the disclosure.

[0107] Referring to FIG. **8**, in the spatial attention block **720**, query data “q”, key data “k”, and value data “v” may be obtained based on input data input to the spatial attention block **720**.

[0108] For example, the input data may be input to a convolutional layer **811** (“Conv” **811**). A convolution operation may be performed between the input data input to the convolutional layer **811** and a kernel included in the convolutional layer **811**.

[0109] Data obtained by performing the convolution operation with the kernel in the convolutional layer **811** may be input to a split layer **820** (“Split” **820**).

[0110] The data input to the split layer **820** may be split into a preset number. For example, the data input to the split layer **820** may be split into three pieces of data. The three pieces of data split by the split layer **820** may be respectively input to reshape layers **831**, **832**, and **833** (“reshape” **831**, **832**, **833**). In each of the reshape layers **831**, **832**, and **833**, the input data may be reshaped to a specific dimension.

[0111] The data reshaped in the reshape layers **831**, **832**, and **833** may be query data “q”, key data “k”, and value data “v”.

[0112] A weight matrix w may be obtained through an element-wise multiplication operation between the query data “q” and the key data “k”.

[0113] The spatial attention block **720** may obtain weight data A by applying a softmax function to the weight matrix w, and the spatial attention block **720** may perform an element-wise multiplication operation between the weight data A and the value data “v”. Data obtained by performing the element-wise multiplication operation may be input to a reshape layer **834** (“reshape” **834**).

[0114] In the reshape layer **834**, first output data a may be obtained by reshaping the data obtained by performing the element-wise multiplication operation.

[0115] The first output data may be input to a convolutional layer **812** (“Conv” **812**). The spatial attention block **720** may obtain second output data by performing a convolution operation between the input first output data and a kernel included in the convolutional layer **812**, in the convolutional layer **812**.

[0116] Referring back to FIG. **7**, data output from the spatial attention block **720** may be input to the temporal attention block **730**.

[0117] In the temporal attention block **730**, operations illustrated and described with reference to FIG. **6** may be performed. Data processed in the temporal attention block **730** may be input to the down sampling layer **740** and a first up block **581** (“Up Block” **581**) of FIG. **5**. The first up block **581** of FIG. **5** will be described below in detail.

[0118] The down sampling layer **740** may include a convolutional layer. In the down sampling layer, a size (dimension) or a resolution of data input through a convolution operation may be reduced.

[0119] Referring back to FIG. **5**, data output from the first down block **561** may be input to a second down block **562** (“Down Block” **562**) located next to the first down block **561**. In the second down block **562**, operations illustrated and described with reference to FIG. **7** may be performed. Also, in a third down block **563** (“Down Block” **563**) and a fourth down block **564** (“Down Block” **564**), operations illustrated and described with reference to FIG. **7** may be performed.

[0120] Data output from the fourth down block **564** may be input the second residual block **552** (“ResBlk” **552**). In the second residual block **552**, operations illustrated and described with

reference to FIG. 4 may be performed.

[0121] Data output from the second residual block 552 may be input to a spatial attention block 570 (“Spatial Attn” 570). In the spatial attention block 570, operations illustrated and described with reference to FIG. 8 may be performed.

[0122] Data output from the spatial attention block 570 may be input to a third residual block 553 (“ResBlk” 553). In the third residual block 553, operations illustrated and described with reference to FIG. 4 may be performed.

[0123] Data output from the third residual block 553 may be input to a second temporal attention block 532 (“Temporal Attn” 532). In the second temporal attention block 532, operations illustrated and described with reference to FIG. 6 may be performed.

[0124] Data output from the second temporal attention block 532 may be input to the first up block 581. The first up block 581 will be described in detail with reference to FIG. 9.

[0125] FIG. 9 illustrates an up block, according to an embodiment of the disclosure.

[0126] Referring to FIG. 9, the first up block 581 according to an embodiment of the disclosure may include an up sampling layer, a summation layer, one or more residual blocks, a spatial attention block, and a temporal attention block.

[0127] Data input to the first up block 581 according to an embodiment of the disclosure may be sequentially image-processed in an up sampling layer 910 (“Upsample” 910, a summation layer 920, two residual blocks (a first residual block 931 (“ResBlk” 931) and a second residual block 932 (“ResBlk” 932)), a spatial attention block 940 (“Spatial Attn” 940), and a temporal attention block 950 (“Temporal Attn” 950).

[0128] Data input to the first up block 581 may be input to the up sampling layer 910.

[0129] In the up sampling layer 910, a size (dimension) or a resolution of the input data may be increased. For example, in the up sampling layer 910, a resolution that is reduced through down sampling may be restored to an original size or a larger size. In one embodiment, in the up sampling layer 910, detailed information of an image may be restored to improve the quality of the image. In the up sampling layer 910, a size (dimension) or a resolution of input data may be increased through deconvolution operation, nearest neighbor up sampling, bilinear, bicubic interpolation, or pixel shuffling. However, the disclosure is not limited to the above examples.

[0130] Data output from the up sampling layer 910 may be input to the summation layer 920. Also, data output from the temporal attention block 730 included in the first down block 561 of FIG. 7 may also be input to the summation layer 920.

[0131] In the summation layer 920, an element-wise summation operation of pieces of data input to the summation layer 920 may be performed.

[0132] Data output from the summation layer 920 may be input to the first residual block 931. In the first residual block 931, operations illustrated and described with reference to FIG. 4 may be performed, and data output from the first residual block 931 may be input to the second residual block 932. Even in the second residual block 932, operations illustrated and described with reference to FIG. 4 may be performed, and data output from the second residual block 932 may be input to the spatial attention block 940.

[0133] In the spatial attention block 940, operations illustrated and described with reference to FIG. 8 may be performed, and data output from the spatial attention block 940 may be input to the temporal attention block 950.

[0134] In the temporal attention block 950, operations illustrated and described with reference to FIG. 6 may be performed, and final output data of the first up block 581 may be obtained.

[0135] Referring back to FIG. 5, data output from the first up block 581 may be input to a second up block 582 (“Up Block” 582), and in the second up block 582, operations illustrated and described with reference to FIG. 9 may be performed.

[0136] Also, even in a third up block 583 (“Up Block” 583) and a fourth up block 584 (“Up Block” 584), operations illustrated and described with reference to FIG. 9 may be performed.

[0137] Data output from the fourth up block **584** may be input to the concatenation layer **512**.

[0138] In the concatenation layer **512**, data output from the convolutional layer **521** of FIG. 5 and data output from the fourth up block **584** may be concatenated. For example, data obtained by concatenating data output from the convolutional layer **521** of FIG. 5 and data output from the fourth up block **584** along a channel direction may be output.

[0139] Data output from the concatenation layer **512** may be input to a residual block **554** (“ResBlk **554**”). In the residual block **554**, operations illustrated and described with reference to FIG. 4 may be performed, and data output from the residual block **554** may be input to the convolutional layer **522** (“Conv” **522**).

[0140] In the convolutional layer **522**, a convolution operation may be performed between the input data and a kernel. In the convolutional layer **522**, flow information may be obtained.

[0141] FIG. 10 illustrates a feature transformation unit and a feature decoding unit, according to an embodiment of the disclosure.

[0142] Referring to FIG. 10, the flow information **502** and the feature information **302** extracted by the encoder **300** according to an embodiment of the disclosure may be input to the feature transformation unit **220**. The flow information **502** may be generated through the flow generation network **500** illustrated and described with reference to FIG. 5. In an embodiment, the flow information **502** may be generated based on a user input. For example, the flow information may be generated based on flow direction information set by a user. However, the disclosure is not limited to the above examples.

[0143] The feature transformation unit **220** according to an embodiment of the disclosure may include a warping module **1001**. The warping module **1001** may transform (warp) the feature information by applying the flow information **502** to the feature information **302**. The warping module **1001** may obtain transformed feature information.

[0144] The transformed feature information may be input to the feature decoding unit **230**.

[0145] The feature decoding unit **230** according to an embodiment of the disclosure may include a decoder **1002** that may restore the transformed feature information into an original resolution. Accordingly, the decoder **1002** may obtain transformed frame images **1003**.

[0146] Referring to FIG. 10, the decoder **1002** may include one or more convolutional layers, residual blocks, up sampling layers, and a normalization layer.

[0147] The transformed feature information output from the warping module **1001** may be input to a first convolutional layer **1011** (“Conv” **1011**) of the decoder **1002**. In the first convolutional layer **1011**, a convolution operation may be performed between the input data and a kernel.

[0148] Data output from the first convolutional layer **1011** may be input to a first residual block **1021** (“ResBlk” **1021**). In the first residual block **1021**, operations illustrated and described with reference to FIG. 4 may be performed, and data output from the first residual block **1021** may be input to a second residual block **1022** (“ResBlk” **1022**). In the second residual block **1022**, the third residual block **1023** (“ResBlk” **1023**), the fourth residual block **1024** (“ResBlk” **1024**), and the fifth residual block **1025** (“ResBlk” **1025**), operations illustrated and described with reference to FIG. 4 may be performed, and data output from the fifth residual block **1025** may be input to a first up sampling layer **1031** (“Upsample” **1031**).

[0149] In the first up sampling layer **1031**, an operation of increasing a size (dimension) or a resolution of the input data may be performed. For example, in the first up sampling layer **1031**, a deconvolution operation, nearest neighbor up sampling, bilinear, bicubic interpolation, or pixel shuffling may be performed.

[0150] Data output from the first up sampling layer **1031** may be input to a second convolutional layer **1012** (“Conv” **1012**). In the second convolutional layer **1012**, a convolution operation may be performed between the input data and a kernel included in the second convolutional layer **1012**.

[0151] Data output from the second convolutional layer **1012** may be input to a sixth residual block **1026** (“ResBlk” **1026**).

[0152] Even in the sixth to eighth residual blocks **1026**, **1027**, and **1028** (“ResBlk” **1026**, **1027**, and **1028**), operations illustrated and described with reference to FIG. **4** may be performed, and data output from the eighth residual block **1028** may be input to a second up sampling layer **1032** (“Upsample” **1032**).

[0153] In the second up sampling layer **1032**, an operation of increasing a size (dimension) or a resolution of the input data may be performed. For example, in the second up sampling layer **1032**, a deconvolution operation, nearest neighbor up sampling, bilinear, bicubic interpolation, or pixel shuffling may be performed.

[0154] Data output from the second up sampling layer **1032** may be input to a third convolutional layer **1013** (“Conv” **1013**). In the third convolutional layer **1013**, a convolution operation may be performed between the input data and a kernel included in the third convolutional layer **1013**.

[0155] Data output from the third convolutional layer **1013** may be input to a ninth residual block **1029** (“ResBlk” **1029**).

[0156] Even in the ninth to 11.sup.th residual blocks **1029**, **1051**, and **1052** (“ResBlk” **1029**, **1051**, and **1052**), operations illustrated and described with reference to FIG. **4** may be performed, and data output from the 11.sup.th residual block **1052** may be input to a normalization layer **1040** (“Norm” **1040**).

[0157] In the normalization layer **1040**, a range of values of data input to the normalization layer **1040** may be adjusted. In the normalization layer **1040**, batch normalization, layer normalization, instance normalization, group normalization, etc. may be performed.

[0158] Data output from the normalization layer **1040** may be input to a fourth convolutional layer **1014** (“Conv” **1014**). In the fourth convolutional layer **1014**, a convolution operation may be performed between the input data and a kernel included in the fourth convolutional layer **1014**.

[0159] In the fourth convolutional layer **1014**, the transformed frame images **1003** may be obtained.

[0160] FIG. **11** illustrates a residual generation unit, according to an embodiment of the disclosure.

[0161] Referring to FIG. **11**, the residual generation unit **260** may include a residual generation network **1100**. The residual generation network **1100** may include a U-Net having an encoder-decoder structure.

[0162] The residual generation network **1100** may include one or more concatenation layers, one or more convolutional layers, a temporal attention block, a spatial attention block, a normalization layer, a residual block, a down block, and a up sample block.

[0163] Noise information **1101** generated in the noise generation unit **240**, the first image **301**, and the transformed frame images **1003** may be input to the residual generation network **1100**. The noise information **1101**, the first image **301**, and the transformed frame images **1003** may be input to a first concatenation layer **1111**.

[0164] In the first concatenation layer **1111**, pieces of data input to the first concatenation layer **1111** may be concatenated. For example, when the noise information **1101**, the first image **301**, and the transformed frame images **1003** are input to the first concatenation layer **1111**, in the first concatenation layer **1111**, input data obtained by concatenating the noise information **1101**, the first image **301**, and the transformed frame images **1003** along a channel direction may be output.

[0165] In a first convolutional layer **1121** (“Conv” **1121**), a convolution operation may be performed between input data and a kernel included in the first convolutional layer **1121**.

[0166] Data output from the first convolutional layer **1121** may be input to a first temporal attention block **1131** (“Temporal Attn” **1131**). Also, data output from the first convolutional layer **1121** may be input to a second concatenation layer **1112** of FIG. **11**.

[0167] In the first temporal attention block **1131**, attention may be applied within a time axis for each location of pixels included in input data. Here, attention may refer to a method of finding related features by using similarity between features, aggregating the related features into one, and extracting aggregated feature information.

[0168] In the first temporal attention block **1131**, operations illustrated and described with reference to FIG. **6** may be performed. Data output from the first temporal attention block **1131** may be input to a normalization layer **1140** (“Norm” **1140**).

[0169] In the normalization layer **1140**, a range of values of data input to the normalization layer **1140** may be adjusted. In the normalization layer **1140**, batch normalization, layer normalization, instance normalization, group normalization, etc. may be performed.

[0170] Data output from the normalization layer **1140** may be input to a first residual block **1151** (“ResBlk” **1151**).

[0171] In the first residual block **1151**, operations illustrated and described with reference to FIG. **4** may be performed, and data output from the first residual block **1151** may be input to a first down block **1161** (“Down Block” **1161**).

[0172] In the first down block **1161**, operations illustrated and described with reference to FIG. **7** may be performed, and data output from the first down block **1161** may be input to a second down block **1162**.

[0173] Even in the second to fourth down blocks **1162**, **1163**, and **1164** (“Down Block” **1162**, **1163**, **1164**), operations illustrated and described with reference to FIG. **7** may be performed.

[0174] Data output from the fourth down block **1164** may be input to a second residual block **1152** (“ResBlk” **1152**). In the second residual block **1152**, operations illustrated and described with reference to FIG. **4** may be performed.

[0175] Data output from the second residual block **1152** may be input to a spatial attention block **1170** (“Spatial Attn” **1170**). In the spatial attention block **1170**, operations illustrated and described with reference to FIG. **8** may be performed.

[0176] Data output from the spatial attention block **1170** may be input to a third residual block **1153** (“ResBlk” **1153**). In the third residual block **1153**, operations illustrated and described with reference to FIG. **4** may be performed.

[0177] Data output from the third residual block **1153** may be input to a second temporal attention block **1132** (“Temporal Attn” **1132**). In the second temporal attention block **1132**, operations illustrated and described with reference to FIG. **6** may be performed.

[0178] Data output from the second temporal attention block **1132** may be input to a first up block **1181** (“Up Block” **1181**). In the first up block **1181**, operations illustrated and described with reference to FIG. **9** may be performed, and data output from the first up block **1181** may be input to a second up block **1182** (“Up Block” **1182**).

[0179] Even in the second to fourth up blocks **1182**, **1183**, and **1184** (“Up Block” **1182**, **1183**, **1184**), operations illustrated and described with reference to FIG. **9** may be performed, and data output from the fourth up block **1184** may be input to the second concatenation layer **1112**.

[0180] In the second concatenation layer **1112**, data output from the fourth up block **1184** and data output from the first convolutional layer **1121** may be concatenated along a channel direction and may be output to a fourth residual block **1154** (“ResBlk” **1154**).

[0181] In the fourth residual block **1154**, operations illustrated and described with reference to FIG. **4** may be performed, and data output from the fourth residual block **1154** may be input to a second convolutional layer **1122** (“Conv” **1122**).

[0182] In the second convolutional layer **1122**, a convolution operation may be performed between the input data and a kernel included in the second convolutional layer **1122**. In the second convolutional layer **1122**, residual information **1103** may be obtained.

[0183] FIG. **12** illustrates a residual synthesis unit, according to an embodiment of the disclosure.

[0184] Referring to FIG. **12**, the residual synthesis unit **270** according to an embodiment of the disclosure may include a summation layer. In a summation layer **1210**, an element-wise summation operation of pieces of data input to the summation layer **1210** may be performed. In the summation layer **1210**, an element-wise summation operation may be performed between the residual information **1103** generated by the residual generation unit **260** and the transformed frame images

1003 output from the feature decoding unit **230**. The summation layer **1210** may obtain a plurality of frame images **1220**.

[0185] The plurality of frame images **1220** may be images in which details included in the first image **301** (e.g., structural information such as edges and detailed texture information included in the first image) are maintained. Also, the plurality of frame images may be high-quality images that do not include artifacts caused by warping and whose image quality is not degraded compared to the first image **301**.

[0186] FIG. **13** illustrates an operating method of an electronic device, according to an embodiment of the disclosure.

[0187] Referring to FIG. **13**, the electronic device **100** according to an embodiment of the disclosure may obtain flow information about a first image (**S1310**).

[0188] For example, the electronic device **100** may obtain flow information about the first image by using the flow generation network **500** illustrated and described with reference to FIG. **5**. In this case, noise information generated in a noise generation unit and feature information about the first image may be input to the flow generation network **500**.

[0189] In one embodiment, the electronic device **100** may generate flow information based on a user input. For example, when a user input that sets a direction of a motion appearing in a video is received, the electronic device **100** may generate flow information so that the motion occurs in the direction.

[0190] In one embodiment, based on a user input that selects a specific object in the first image, the electronic device **100** may generate only flow information about the selected object by segmenting the selected object so that a motion occurs only for the selected object. However, the disclosure is not limited to the above examples.

[0191] The electronic device **100** according to an embodiment may obtain a plurality of transformation images obtained by transforming the first image, based on the flow information (**S1320**).

[0192] The electronic device **100** may extract feature information of the first image. For example, the electronic device **100** may extract feature information of the first image by using the encoder **300** illustrated and described with reference to FIG. **3**.

[0193] The electronic device **100** may generate transformed feature information by performing warping by applying the flow information to the extracted feature information.

[0194] The electronic device **100** may obtain a plurality of transformation images by decoding the transformed feature information by using the decoder **1002** illustrated and described with reference to FIG. **10**.

[0195] The electronic device **100** according to an embodiment of the disclosure may obtain residual information about the plurality of transformation images based on the plurality of transformation images and the first image (**S1330**).

[0196] The electronic device **100** may generate residual information about the plurality of transformation images by using the residual generation network **1100** illustrated and described with reference to FIG. **11**. In this case, the noise information generated in the noise generation unit, the first image, and the plurality of transformation images may be input to the residual generation network **1100**.

[0197] The electronic device **100** according to an embodiment of the disclosure may generate a plurality of frame images based on the plurality of transformation images and the residual information (**S1340**).

[0198] The electronic device **100** may generate a plurality of frame images by summing the plurality of transformation images and the residual information.

[0199] FIG. **14** illustrates an operation in which an electronic device converts a still image into a video, according to an embodiment of the disclosure.

[0200] Referring to FIG. **14**, the electronic device **100** according to an embodiment of the

disclosure may display a plurality of images on a display. For example, the electronic device **100** may execute a photo application based on a user input that requests to execute the photo application. When the photo application is executed, the electronic device **100** may display images pre-stored in the electronic device **100**.

[0201] When the electronic device **100** receives a user input that selects a first image **1410** from among the plurality of images, the electronic device **100** may enlarge and display the selected first image **1410**. The electronic device **100** may select a portion of the first area **1410** or may edit attributes of the first image **1410**, based on a user input. Also, the electronic device **100** may convert the first image **1410** into a video **1430**, based on a user input that selects a video generation menu **1420**. For example, the electronic device **100** may generate a plurality of frame images included in the video **1430** by image-processing the first image **1410** using the image processing module **200** illustrated and described with reference to FIGS. **2** to **12**. The electronic device **100** may extract feature information from the first image **1410** using the feature extraction unit **210**. The electronic device **100** may generate first noise images using the noise generation unit **240**. The electronic device **100** may generate flow information (flow map) based on the first noise images extracted by the feature extraction unit **210** and the first noise images by using the flow generation unit **250**. The electronic device **100** may generate transformed feature information by warping by applying the flow information to the extracted feature information by using the feature transformation unit **220**. The electronic device **100** may generate transformed images by decoding the transformed feature information using the feature decoding unit **230**.

[0202] The electronic device **100** may generate second noise images by using the noise generation unit **240**. The electronic device **100** may generate residual information (residual map) based on the transformed images, the first image **1410**, and the second noise images by using the residual generation unit **260**. The electronic device **100** may generate a plurality of frame images by synthesizing the residual information with the transformed images by using the residual synthesis unit **270**.

[0203] The electronic device **100** may display the video **1430** including the generated plurality of frame images on the display.

[0204] FIG. **15** illustrates an operation in which an electronic device converts a still image into a video, according to an embodiment of the disclosure.

[0205] Referring to FIG. **15**, the electronic device **100** according to an embodiment of the disclosure may display a plurality of images on a display. For example, the electronic device **100** may execute a photo application based on a user input that requests to execute the photo application. When the photo application is executed, the electronic device **100** may display images pre-stored in the electronic device **100**.

[0206] When the electronic device **100** receives a user input that selects a first image **1510** from among the plurality of images, the electronic device **100** may enlarge and display the selected first image **1510**. The electronic device **100** may select a portion of the first image **1510** or may edit attributes of the first image **1510** based on a user input.

[0207] Also, the electronic device **100** may set a motion for the first image **1510** based on a user input that selects a motion setting module **1520**. A user may set a direction of the motion by a drag input. For example, the electronic device **100** may receive a touch input that drags from left to right, and may set a direction of a motion to a first direction **1550**. When a direction of a motion is set to the first direction **1550**, it may mean that a motion in which at least one object included in the first image **1510** moves in the first direction **1550** is set or a motion in which a viewpoint of viewing at least one object included in the first image **1510** moves in the first direction **1550** is set. However, the disclosure is not limited to the above examples.

[0208] The electronic device **100** may obtain flow information based on the set direction of the motion. For example, the electronic device **100** may generate flow information indicating the first direction.

[0209] In one embodiment, the electronic device **100** may convert the first image **1510** into a video **1540** based on a user input that selects a video generation module **1530**. For example, the electronic device **100** may generate a plurality of frame images included in the video **1540** by image-processing the first image **1510** by using the flow information **1560** and the image processing module **200** illustrated and described with reference to FIGS. **2** to **12**. The electronic device **100** may extract feature information from the first image **1510** by using the feature extraction unit **210**. The electronic device **100** may generate transformed feature information by applying the flow information **1560** generated based on the motion input by the user to the extracted feature information, by using the feature transformation unit **220**. For example, the electronic device **100** may use the flow information **1560** indicating the first direction **1550**, without generating flow information through a flow generation network. The electronic device **100** obtain transformed feature information by performing warping by applying the flow information **1560** indicating the first direction **1550** to the feature information extracted from the first image **1510**. The electronic device **100** may generate transformed images by decoding the transformed feature information by using the feature decoding unit **230**.

[0210] The electronic device **100** may generate noise images using the noise generation unit **240**. The electronic device **100** may generate residual information (residual map) based on the transformed images, the first image **1510**, and the noise images using the residual generation unit **260**. The electronic device **100** may generate a plurality of frame images by synthesizing the residual information with the transformed images by using the residual synthesis unit **270**.

[0211] The electronic device **100** may display the video **1540** including the generated plurality of frame images on the display. The generated video **1540** may include a motion in which at least one object included in the first image **1310** moves in the first direction **1550**. In one embodiment, the generated video **1540** may include a motion in which a viewpoint of viewing at least one object included in the first image **1510** moves in the first direction **1550**. However, the disclosure is not limited to the above examples.

[0212] FIG. **16** illustrates an operation in which an electronic device converts a still image into a video, according to an embodiment of the disclosure.

[0213] Referring to FIG. **16**, the electronic device **100** according to an embodiment of the disclosure may generate a video in which only a specific object (among objects included in a still image) moves.

[0214] For example, the electronic device **100** may display a first image **1610** on a display. The first image **1610** may be an image selected based on a user input. The first image **1610** may include at least one object. The electronic device **100** may receive a user input that selects a first object **1620** from among objects included in the first image **1610**.

[0215] The electronic device **100** may segment the first object **1620** through object segmentation. Object segmentation may refer to a method of identifying and separating a specific object or a specific area in an image. Object segmentation may be used to identify a boundary of an object in units of pixels in an image, and assign a different color to each object or separate an object from a background. The electronic device **100** may generate a mask **1630** indicating a first object area in the first image **1610** through object segmentation.

[0216] The electronic device **100** may convert the first image **1610** into a video **1640** based on a user input that requests to generate a video. The electronic device **100** may generate the video **1640** in which only the first object **1620** moves in the first image **1610**. For example, the electronic device **100** may generate a plurality of frame images included in the video **1640** by image-processing the first image **1610** by using the image processing module **200** illustrated and described with reference to FIGS. **2** to **12**.

[0217] The electronic device **100** may extract feature information from the first image **1610** by using the feature extraction unit **210**. The electronic device **100** may generate first noise images by using the noise generation unit **240**. The electronic device **100** may generate flow information

(flow map) based on the feature information extracted by the feature extraction unit **210** and the first noise images by using the flow generation unit **250**. In this case, the electronic device **100** may apply the mask **1630** indicating the first object area to the flow information generated through a flow generation network. The flow information to which the mask **1630** is applied may indicate only flow information of the first object area. The electronic device **100** may generate transformed feature information by performing warping by applying the flow information to which the mask **1630** is applied to the extracted feature information, by using the feature transformation unit **220**. The electronic device **100** may generate transformed images by decoding the transformed feature information by using the feature decoding unit **230**.

[0218] The electronic device **100** may generate second noise images by using the noise generation unit **240**. The electronic device **100** may generate residual information (e.g., a residual map) based on the transformed images, the first image **1410**, and the second noise images by using the residual generation unit **260**. In this case, the electronic device **100** may apply the mask **1630** indicating the first object area to the residual information generated through a residual generation network. The electronic device **100** may generate the video **1640** including the plurality of frame images by synthesizing the residual information to which the mask **1630** is applied with the transformed images by using the residual synthesis unit **270**.

[0219] Accordingly, the electronic device **100** may generate the video **1640** in which only the first object moves. The electronic device **100** may display the generated video **1640** on the display.

[0220] FIG. **17** illustrates an operation in which an electronic device converts a still image into a video, according to an embodiment of the disclosure.

[0221] Referring to FIG. **17**, the electronic device **100** according to an embodiment of the disclosure may generate a video in which only a specific object among objects included in a still image moves.

[0222] For example, the electronic device **100** may display a first image **1710** on a display. The first image **1710** may be an image selected based on a user input. The first image **1710** may include at least one object. The electronic device **100** may receive a user input that selects a first object **1720** from among objects included in the first image **1710**.

[0223] The electronic device **100** may segment the first object **1720**, through object segmentation. The electronic device **100** may generate a mask **1730** indicating a first object area in the first image **1710** through object segmentation.

[0224] Also, the electronic device **100** may set a motion for the first object **1720** based on a user input that selects a motion setting menu **1740**. A user may set a direction of a motion by a drag input. For example, the electronic device **100** may receive a touch input that drags from left to right, and may set a direction of a motion to a first direction **1750**. When a direction of a motion is set, it may mean that a motion in which the first object **1720** moves in the first direction **1750** is set. However, the disclosure is not limited to the above examples.

[0225] The electronic device **100** may obtain flow information based on the set direction of the motion. For example, the electronic device **100** may generate flow information **1760** indicating the first direction.

[0226] The electronic device **100** may convert the first image **1710** into a video **1780** based on a user input that requests to generate a video. For example, the electronic device **100** may generate a plurality of frame images included in the video **1780** by performing an image-processing operation on the first image **1710** by using the flow information **1760** and the image processing module **200** illustrated and described with reference to FIGS. **2** to **12**.

[0227] The electronic device **100** may extract feature information from the first image **1710** by using the feature extraction unit **210**. The electronic device **100** may generate transformed feature information by applying the flow information **1760** generated based on the motion input by the user to the extracted feature information, by using the feature transformation unit **220**. For example, the electronic device **100** may apply the mask **1730** indicating the first object area to the flow

information **1760** indicating the first direction **1750**, without generating flow information through a flow generation network. Flow information **1760** to which the mask **1730** is applied may indicate only flow information of the first object area.

[0228] The electronic device **100** may obtain transformed feature information by performing warping by applying the flow information **1770** to which the mask **1730** is applied to the feature information extracted from the first image **1710**, by using the feature transformation unit **220**. The electronic device **100** may generate transformed images by decoding the transformed feature information, by using the feature decoding unit **230**.

[0229] The electronic device **100** may generate noise images by using the noise generation unit **240**. The electronic device **100** may generate residual information (residual map) based on the transformed images, the first image **1710**, and the noise images by using the residual generation unit **260**. In this case, the electronic device **100** may apply the mask **1730** indicating the first object area to the residual information generated through a residual generation network. The electronic device **100** may generate the video **1780** including the plurality of frame images by synthesizing the residual information to which the mask **1730** is applied with the transformed images by using the residual synthesis unit **270**.

[0230] Accordingly, the electronic device **100** may generate the video **1780** in which only the first object moves in the first direction. The electronic device **100** may display the generated video **1780** on the display.

[0231] FIG. **18** illustrates a configuration of an electronic device, according to an embodiment of the disclosure.

[0232] The electronic device **100** of FIG. **18** may be configured to perform an image processing operation by using the image processing module **200**. The image processing module **200** according to an embodiment of the disclosure may include one or more neural networks. For example, the image processing module **200** may include an encoder that is configured to convert an input image into a compressed representation or extracts features of the input image, a decoder that is configured to restore the compressed representation to an original resolution, and a U-Net having an encoder-decoder structure. However, the disclosure is not limited to the above examples. The image processing module **200** may include various neural networks.

[0233] Referring to FIG. **18**, the electronic device **100** according to an embodiment of the disclosure may include a processor **110**, memory **120**, and a display **130**.

[0234] The processor **110** according to an embodiment of the disclosure may control an overall operation of the electronic device **100**. The processor **110** according to an embodiment of the disclosure may execute one or more programs stored in the memory **120**.

[0235] The memory **120** according to an embodiment of the disclosure may store various data, a program, or an application for driving and controlling the electronic device **100**. The program stored in the memory **120** may include one or more instructions. The program (the one or more instructions) or the application stored in the memory **120** may be executed by the processor **110**.

[0236] The processor **110** according to an embodiment of the disclosure may include at least one of a central processing unit (CPU), a graphics processing unit (GPU), or a video processing unit (VPU). According to an embodiment of the disclosure, the processor **110** may be implemented as a system-on-chip (SoC) in which at least one of a CPU, a GPU, or a VPU is integrated. In one embodiment, the processor **110** may further include a neural processing unit (NPU).

[0237] The processor **110** according to an embodiment of the disclosure may generate a plurality of frame images (video) by processing a first image by using the image processing module **200** including one or more neural networks. In this case, the plurality of frame images included in the video may be images in which details included in the first image **301** (e.g., structural information such as edges and detailed texture information included in the first image) are maintained. Also, the plurality of frame images may be high-quality images that do not include artifacts caused by warping and whose image quality is not degraded compared to the first image.

[0238] The processor **110** according to an embodiment of the disclosure may obtain feature information of the first image. For example, the processor **110** may extract feature information of the first image by using the encoder **300** illustrated and described with reference to FIG. **3**. A structure and an operation of the encoder **300** have been described in detail with reference to FIGS. **3** and **4**, and thus, a detailed description thereof will be omitted.

[0239] The processor **110** according to an embodiment of the disclosure may obtain flow information about the first image. For example, the processor **110** may generate flow information about the first image by using the flow generation network **500** illustrated and described with reference to FIG. **5**. A structure and an operation of the flow generation network **500** have been described in detail with reference to FIGS. **5** to **9**, and thus, a detailed description thereof will be omitted.

[0240] In one embodiment, the processor **110** may generate flow information based on a user input. For example, when a user input that sets a direction of a motion appearing in the video is received, the processor **110** may generate flow information based on the direction of the motion so that in the generated video, the motion occurs in the direction set by the user.

[0241] In one embodiment, based on a user input that selects a specific object in the first image, the processor **110** may generate only flow information about the selected object by segmenting the selected object so that a motion occurs only for the selected object. However, the disclosure is not limited to the above example.

[0242] The processor **110** according to an embodiment of the disclosure may obtain a plurality of transformation images obtained by transforming the first image, based on the flow information. For example, the processor **110** may generate transformed feature information by performing warping by applying the flow information to the extracted feature information. Also, the processor **110** may obtain a plurality of transformation images by decoding the transformed feature information by using the decoder **1002** illustrated and described with reference to FIG. **10**. A structure and an operation of the decoder **1002** have been described in detail with reference to FIG. **10**, and thus, a detailed description thereof will be omitted.

[0243] The processor **110** according to an embodiment of the disclosure may obtain residual information about the plurality of transformation images based on the plurality of transformation images and the first image. For example, the processor **110** may generate residual information about the plurality of transformation images by using the residual generation network **1100** illustrated and described with reference to FIG. **11**. In this case, noise information generated in a noise generation unit, the first image, and the plurality of transformation images may be input to the residual generation network **1100**. A structure and an operation of the residual generation network **1100** have been described in detail with reference to FIG. **11**, and thus, a detailed description thereof will be omitted.

[0244] The processor **110** according to an embodiment of the disclosure may generate a plurality of frame images based on the plurality of transformation images and the residual information. For example, the processor **110** may generate a plurality of frame images by summing the plurality of transformation images and the residual information.

[0245] The encoder **300**, the flow generation network **500**, the decoder **1002**, and the residual generation network **1100** according to an embodiment of the disclosure may each be a network trained by a server or an external device. The external device may train the encoder **300**, the flow generation network **500**, the decoder **1002**, and the residual generation network **1100** based on training data.

[0246] The server or the external device may determine parameter values used in a plurality of layers and a plurality of blocks included in the encoder **300**, the flow generation network **500**, the decoder **1002**, and the residual generation network **1100**.

[0247] The electronic device **100** according to an embodiment of the disclosure may receive the encoder **300**, the flow generation network **500**, the decoder **1002**, and the residual generation

network **1100** whose training is completed from the server or the external device, and may store the encoder **300**, the flow generation network **500**, the decoder **1002**, and the residual generation network **1100** in the memory **120**. For example, the memory **120** may store structures and parameter values of the encoder **300**, the flow generation network **500**, the decoder **1002**, and the residual generation network **1100** according to an embodiment of the disclosure, and the processor **110** may generate a plurality of frame images (video) from the first image according to an embodiment of the disclosure by using the parameter values stored in the memory **120**.

[0248] The display **130** according to an embodiment of the disclosure generates a driving signal by converting an image signal, a data signal, an OSD signal, and a control signal processed by the processor **110**. The display **130** may be implemented as a plasma display panel (PDP), a liquid crystal display (LCD), an organic light-emitting diode (OLED), or a flexible display, or may be implemented as a three-dimensional (3D) display. Also, the display **130** may include a touchscreen, and may be used as an input device in addition to an output device.

[0249] The display **130** according to an embodiment of the disclosure may display the generated plurality of frame images (video) by using the image processing module **200**.

[0250] FIG. **19** illustrates a configuration of an electronic device, according to an embodiment of the disclosure.

[0251] An electronic device **1900** of FIG. **19** may be an embodiment of the electronic device **100** illustrated and described with reference to FIGS. **1** to **18**.

[0252] Referring to FIG. **19**, the electronic device **1900** according to an embodiment of the disclosure may include a sensing unit **1910**, a communication unit **1920**, a processor **1930**, an A/V input unit **1940**, an output unit **1950**, memory **1960**, and a user input unit **1970**.

[0253] The processor **1930** of FIG. **19** corresponds to the processor **110** of FIG. **18**, the memory **1960** of FIG. **19** corresponds to the memory **130** of FIG. **18**, and a display **1951** of FIG. **19** corresponds to the display **130** of FIG. **18**, and thus, a repeated description thereof will be omitted.

[0254] The sensing unit **1910** may include a sensor that detects a state of the electronic device **1900** or a state around the electronic device **1900**. Also, the sensing unit **1910** may transmit information detected by the sensor to the processor **1930**.

[0255] The communication unit **1920** may include, but is not limited to a short-range wireless communication unit or a mobile communication unit, in response to the performance and structure of the electronic device **1900**.

[0256] Examples of the short-range communication unit may include, but are not limited to, a Bluetooth communication unit, a Bluetooth low energy (BLE) communication unit, a near-field communication unit, a wireless local area network (WLAN) (Wi-Fi) communication unit, a Zigbee communication unit, an infrared data association (IrDA) communication unit, a Wi-Fi direct (WFD) communication unit, an ultra-wideband (UWB) communication unit, an Ant+ communication unit, and a microwave (uWave) communication unit.

[0257] The mobile communication unit transmits and receives a wireless signal to and from at least one of a base station, an external terminal, or a server on a mobile communication network. Here, the wireless signal may include a voice call signal, a video call signal, or various types of data according to text/multimedia message transmission/reception.

[0258] The communication unit **1920** according to an embodiment of the disclosure may receive an image from an external device or may transmit an image.

[0259] The processor **1930** according to an embodiment of the disclosure may convert a first image into a plurality of frame images (video) by using the image processing module **200** according to an embodiment of the disclosure.

[0260] The processor **1930** according to an embodiment of the disclosure may include a single-core, a dual-core, a triple-core, a quad-core, or multiples thereof. Also, the processor **1930** may include a plurality of processors.

[0261] The memory **1960** according to an embodiment of the disclosure may include at least one

type of storage medium from among a flash memory type, a hard disk type, a multimedia card micro type, a card type memory (e.g., an SD or XD memory), a random-access memory (RAM), a static random-access memory (SRAM), a read-only memory (ROM), an electrically erasable programmable read-only memory (EEPROM), a programmable read-only memory (PROM), a magnetic memory, a magnetic disk, and an optical disk.

[0262] The A/V inputter **1940** for inputting an audio signal or a video signal may include a camera **1941** and a microphone **1942**. The camera **1941** may obtain image frames such as a still image or a moving image via an image sensor, in a video call mode or an imaging mode. An image captured by the image sensor may be processed by the processor **1930** or a separate image processor.

[0263] An image frame processed by the camera **1941** may be stored in the memory **1960** or may be transmitted to the outside through the communication unit **1920**. Two or more cameras **1941** may be provided according to a configuration of the electronic device **1900**.

[0264] The microphone **1942** receives an external sound signal and processes the external sound signal into electrical voice data. For example, the microphone **1942** may receive a sound signal from an external device or a speaker. The microphone **1942** may use various noise removal algorithms for removing noise generated in a process of receiving an external sound signal.

[0265] The output unit **1950** for outputting an audio signal, a video signal, or a vibration signal may include the display **1951**, a sound output unit **1952**, and a vibration motor **1953**.

[0266] The display **1951** according to an embodiment of the disclosure may display a plurality of frame images (video) generated through the image processing module **200**.

[0267] The sound output unit **1952** outputs audio data received from the communication unit **1920** or stored in the memory **1960**. Also, the sound output unit **1952** outputs a sound signal related to a function (e.g., a call signal reception sound, a message reception sound, or a notification sound) performed by the electronic device **1900**. The sound output unit **1952** may include a speaker, a buzzer, etc.

[0268] The vibration unit **1953** may output a vibration signal. For example, the vibration unit **1953** may output a vibration signal corresponding to an output of audio data or video data (e.g., a call signal reception sound or a message reception sound). Also, the vibration unit **1953** may output a vibration signal when a touch is input to the touchscreen.

[0269] The user input unit **1970** refers to a means by which a user inputs data for controlling the electronic device **1900**. Examples of the user input unit **1970** may include, but are not limited to, a key pad, a dome switch, a touch pad (e.g., contact capacitance type, pressure resistive type, infrared (IR) detection type, surface ultrasonic wave conduction type, integral tension measuring type, or piezoelectric effect type), a jog wheel, and a jog switch.

[0270] Block diagrams of the electronic devices **100** and **1900** of FIGS. **18** and **19** are block diagrams for an embodiment of the disclosure. Components of the block diagram may be integrated, added, or omitted according to specifications of the electronic devices **100** and **1900** that are actually implemented. That is, when necessary, two or more components may be combined into one component, or one component may be divided into two or more components. Also, a function performed in each block is intended to describe embodiments of the disclosure, and its detailed operations or devices do not limit the scope of the disclosure.

[0271] An electronic device according to an embodiment of the disclosure may include memory in which one or more instructions are stored and at least one processor including a processing circuit.

[0272] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to obtain flow information about a first image.

[0273] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to obtain a plurality of transformation images obtained by transforming the first image, based on the flow information.

[0274] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to obtain residual information about the plurality of transformation images based on the plurality of transformation images and the first image.

[0275] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to generate a plurality of frame images based on the plurality of transformation images and the residual information.

[0276] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to extract feature information of the first image.

[0277] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to generate the flow information based on the feature information.

[0278] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to generate first noise information.

[0279] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to generate the flow information by performing a first image processing operation on the first noise information and the feature information.

[0280] The first image processing operation may be performed by a U-Net network including an encoder and a decoder.

[0281] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to extract feature information of the first image.

[0282] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to obtain the plurality of transformation images by warping the feature information based on the flow information.

[0283] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to generate second noise information.

[0284] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to generate the residual information by performing a second image processing operation on the second noise information, the plurality of transformation images, and the first image.

[0285] The second image processing operation may be performed by a U-Net network including an encoder and a decoder.

[0286] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to output a video including the plurality of frame images.

[0287] The electronic device may further include a display.

[0288] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to control the display to display a plurality of images.

[0289] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to receive a first user input that selects the first image from among the plurality of images and a second user input that requests to generate a video for the first image.

[0290] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to generate the plurality of frame images based on the second user input.

[0291] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to receive a third user input that sets motion information about the first image.

[0292] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to generate the flow information based on the third user input.

[0293] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to receive a fourth user input that selects a first object from among at least one object included in the first image.

[0294] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to generate the plurality of frame images in which only the first object in the first image moves, based on the fourth user input.

[0295] The one or more instructions, when executed by the at least one processor according to an embodiment of the disclosure individually or collectively, cause the electronic device to obtain the plurality of transformation images by applying the flow information only to the first object.

[0296] An operating method of an electronic device according to an embodiment of the disclosure may include obtaining flow information about a first image.

[0297] The operating method of the electronic device according to an embodiment of the disclosure may include obtaining a plurality of transformation images obtained by transforming the first image, based on the flow information.

[0298] The operating method of the electronic device according to an embodiment of the disclosure may include obtaining residual information about the plurality of transformation images based on the plurality of transformation images and the first image.

[0299] The operating method of the electronic device according to an embodiment of the disclosure may include generating a plurality of frame images based on the plurality of transformation images and the residual information.

[0300] The obtaining of the flow information may include extracting feature information of the first image.

[0301] The obtaining of the flow information may include generating the flow information based on the feature information.

[0302] The generating of the flow information based on the feature information may include generating first noise information.

[0303] The generating of the flow information based on the feature information may include generating the flow information by performing a first image processing operation on the first noise information and the feature information.

[0304] The first image processing operation may be performed by a U-Net network including an encoder and a decoder.

[0305] The obtaining of the plurality of transformation images may include extracting feature information of the first image.

[0306] The obtaining of the plurality of transformation images may include obtaining the plurality of transformation images by warping the feature information based on the flow information.

[0307] The obtaining of the residual information may include generating second noise information.

[0308] The obtaining of the residual information may include generating the residual information by performing a second image processing operation on the second noise information, the plurality of transformation images, and the first image.

[0309] The second image processing operation may be performed by a U-Net network including an encoder and a decoder.

[0310] The operating method may further include outputting a video including the plurality of frame images.

[0311] The operating method may include displaying a plurality of images.

[0312] The operating method may further include receiving a first user input that selects the first image from among the plurality of images and a second user input that requests to generate a video for the first image.

[0313] The generating of the plurality of frame images may include generating the plurality of frame images based on the second user input.

[0314] The obtaining of the flow information may include receiving a third user input that sets motion information about the first image.

[0315] The obtaining of the flow information may include generating the flow information based on the third user input.

[0316] The operating method may further include receiving a fourth user input that selects a first object from among at least one object included in the first image.

[0317] The obtaining of the flow information may include obtaining flow information about the first object.

[0318] The obtaining the plurality of transformation images obtained by transforming the first image based on the flow information may include obtaining the plurality of transformation images by applying the flow information about the first object only to the first object in the first image.

[0319] The plurality of frame images may include a plurality of frame images in which only the first object in the first image moves.

[0320] An operating method of an electronic device according to an embodiment may be implemented as program commands executable through various computer means and may be recorded on a computer-readable medium. The computer-readable medium may include program commands, data files, data structures, and the like separately or in combinations. The program commands recorded on the computer-readable medium may be specially designed and configured for the disclosure or may be well-known to and be usable by one of ordinary skill in the art of computer software. Examples of the computer-readable recording medium include a magnetic medium such as a hard disk, a floppy disk, or a magnetic tape, an optical medium such as a compact disc read-only memory (CD-ROM) or a digital versatile disc (DVD), a magneto-optical medium such as a floptical disk, and a hardware device specially configured to store and execute program commands such as a ROM, a random-access memory (RAM), or a flash memory. Examples of the program commands include high-level language code that may be executed by a computer by using an interpreter or the like as well as machine language code made by a compiler.

[0321] Also, an image processing apparatus and an operating method of an image processing apparatus according to embodiments of the disclosure may be provided in a computer program product. The computer program product may be a product purchasable between a seller and a purchaser.

[0322] The computer program product may include a software program and a computer-readable storage medium in which the software program is stored. For example, the computer program product may include a S/W program-type product (e.g., a downloadable application) electronically distributed through a manufacturer of an electronic device or an electronic market (e.g., Google Play™ store or App Store). For electronic distribution, at least a portion of the software program may be stored in a storage medium or temporarily generated. In this case, the storage medium may be a storage medium of a server of the manufacturer, a server of the electronic market, or a relay server that temporarily stores the software program.

[0323] The computer program product may include a storage medium of a server or a storage medium of a client device in a system including the server and the client device. In one

embodiment, when there is a third device (e.g., a smartphone) communicating with the server or the client device, the computer program product may include a storage medium of the third device. In one embodiment, the computer program product may include a software program itself transmitted from the server to the client device or the third device or from the third device to the client device.

[0324] In this case, one of the server, the client device, and the third device may perform a method according to embodiments of the disclosure by executing the computer program product. In one embodiment, at least two of the server, the client device, and the third device may perform a method according to embodiments of the disclosure in a distributed fashion by executing the computer program product.

[0325] For example, the server (e.g., a cloud server or an artificial intelligence (AI) server) may execute the computer program product stored in the server, and may control the client device communicating with the server to perform a method according to embodiments of the disclosure.

[0326] The scope of the disclosure is not limited to the above embodiments described above. Various modifications and improvements made by one of ordinary skill in the art by using the basic concept of the disclosure defined by the claims are also within the scope of the disclosure.

Claims

1. An electronic device configured to convert a still image into a video, the electronic device comprising: memory in which one or more instructions are stored; and at least one processor, wherein the one or more instructions, when executed by the at least one processor individually or collectively, cause the electronic device to: obtain flow information about a first image, obtain a plurality of transformation images obtained by transforming the first image, based on the flow information about the first image, obtain residual information about the plurality of transformation images, based on the plurality of transformation images and the first image, and generate a plurality of frame images, based on the plurality of transformation images and the residual information about the plurality of transformation images.
2. The electronic device of claim 1, wherein the one or more instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: extract feature information of the first image, and generate the flow information about the first image, based on the feature information.
3. The electronic device of claim 2, wherein the one or more instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: generate first noise information, and generate the flow information about the first image by performing a first image processing operation on the first noise information and the feature information, wherein the first image processing operation is performed by a U-Net network comprising an encoder and a decoder.
4. The electronic device of claim 1, wherein the one or more instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: extract feature information of the first image, and obtain the plurality of transformation images by warping the feature information based on the flow information about the first image.
5. The electronic device of claim 1, wherein the one or more instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: generate second noise information, and generate the residual information about the plurality of transformation images by performing a second image processing operation on the second noise information, the plurality of transformation images, and the first image, wherein the second image processing operation is performed by a U-Net network comprising an encoder and a decoder.
6. The electronic device of claim 1, wherein the one or more instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to output the

video comprising the plurality of frame images.

7. The electronic device of claim 1, further comprising a display, wherein the one or more instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: control the display to display a plurality of images, receive a first user input that selects the first image from among the plurality of images and receive a second user input that requests to generate the video for the first image, and generate the plurality of frame images, based on the second user input.

8. The electronic device of claim 1, wherein the one or more instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: receive a third user input that sets motion information about the first image, and generate the flow information about the first image, based on the third user input.

9. The electronic device of claim 1, wherein the one or more instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to: receive a fourth user input that selects a first object from among at least one object in the first image, and generate the plurality of frame images in which only the first object moves, based on the fourth user input.

10. The electronic device of claim 9, wherein the one or more instructions, when executed by the at least one processor individually or collectively, further cause the electronic device to obtain the plurality of transformation images by applying the flow information about the first image only to the first object.

11. An operating method performed by an electronic device configured to convert a still image into a video, the operating method comprising: obtaining flow information about a first image; obtaining a plurality of transformation images obtained by transforming the first image based on the flow information about the first image; obtaining residual information about the plurality of transformation images, based on the plurality of transformation images and the first image; and generating a plurality of frame images, based on the plurality of transformation images and the residual information about the plurality of transformation images.

12. The operating method of claim 11, wherein the obtaining of the flow information about the first image, comprises: extracting feature information of the first image; and generating the flow information about the first image, based on the feature information.

13. The operating method of claim 12, wherein the generating of the flow information about the first image based on the feature information, comprises: generating first noise information; and generating the flow information about the first image by performing a first image processing operation on the first noise information and the feature information, wherein the first image processing operation is performed by a U-Net network comprising an encoder and a decoder.

14. The operating method of claim 11, wherein the obtaining of the plurality of transformation images, comprises: extracting feature information of the first image; and obtaining the plurality of transformation images by warping the feature information based on the flow information about the first image.

15. The operating method of claim 11, wherein the obtaining of the residual information about the plurality of transformation images, comprises: generating second noise information; and generating the residual information about the plurality of transformation images by performing a second image processing operation on the second noise information, the plurality of transformation images, and the first image, wherein the second image processing operation is performed by a U-Net network comprising an encoder and a decoder.

16. The operating method of claim 11, further comprising outputting the video comprising the plurality of frame images.

17. The operating method of claim 11, further comprising: displaying a plurality of images; and receiving a first user input that selects the first image from among the plurality of images and receiving a second user input that requests to generate the video for the first image, wherein the

generating of the plurality of frame images comprises generating the plurality of frame images based on the second user input.

18. The operating method of claim 11, wherein the obtaining of the flow information about the first image, comprises: receiving a third user input that sets motion information about the first image; and generating the flow information about the first image, based on the third user input.

19. The operating method of claim 11, further comprising receiving a fourth user input that selects a first object from among at least one object in the first image, wherein the obtaining of the plurality of transformation images obtained by transforming the first image based on the flow information about the first image, comprises obtaining the plurality of transformation images by applying the flow information about the first object only to the first object in the first image, and wherein only the first object moves in the plurality of frame images.

20. At least one non-transitory computer-readable recording medium storing a program for executing the operating method of claim 11.
