

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250283605

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

ZHANG; Guangrong et al.

STOVE TABLE

Abstract

A stove table includes: a stove, a connection portion being provided on a top of the stove; and a plurality of splicing members provided along a circumference of the connection portion. Any two adjacent splicing members are detachably connected, and each of the splicing members is detachably connected to the connection portion through a splicing structure. In response to that the stove table is in use, the plurality of splicing members are spliced with the connection portion to form a table surface.

Inventors: ZHANG; Guangrong (Shenzhen, CN), XIE; Bo (Shenzhen, CN), LI; Cuilong (Shenzhen, CN), JIN; Weiqun (Shenzhen, CN)

Applicant: SHINERICH INDUSTRIAL LTD. (Shenzhen, CN)

Family ID: 1000008018965

Assignee: SHINERICH INDUSTRIAL LTD. (Shenzhen, CN)

Appl. No.: 18/769691

Filed: July 11, 2024

Foreign Application Priority Data

CN

202420435756.8

Mar. 06, 2024

Related U.S. Application Data

parent WO continuation PCT/CN2024/094201 20240520 PENDING child US 18769691

Publication Classification

Int. Cl.: F24B1/193 (20060101); F24B1/195 (20060101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] The present application is a continuation application of International Application No. PCT/CN2024/094201, filed on May 20, 2024, which claims priority to Chinese Patent Application No. 202420435756.8, filed on Mar. 6, 2024. The disclosures of the above-mentioned applications are incorporated herein by reference in their entireties.

TECHNICAL FIELD

[0002] The present application relates to the technical field of stove tables, and in particular to a stove table.

BACKGROUND

[0003] The stove table generally includes a table surface, a brazier, and a stove body for installing the table surface and the brazier. The fuel is added to the brazier, and then the fuel on the brazier is ignited for heating. The stove table is widely used in colder areas.

[0004] In the existing stove table, the plurality of table plates and the stove body are fixed and assembled with screws to form a table surface, so that the user needs to repeatedly install or disassemble the screws on the table plate during the installation and disassembly of the table plate. Therefore, the existing stove table has the problem of inconvenient assembly among the plurality of table plates and the stove.

SUMMARY

[0005] The main purpose of the present application is to provide a stove table, aiming to solve the problem of inconvenient assembly among the plurality of table plates and the stove in the existing stove table.

[0006] To achieve the above purpose, the present application provides a stove table, including:

[0007] a stove, a connection portion is provided on a top of the stove; and [0008] a plurality of splicing members provided along a circumference of the connection portion, any two adjacent splicing members are detachably connected, and each of the splicing members is detachably connected to the connection portion through a splicing structure; [0009] in response to that the stove table is in use, the plurality of splicing members are spliced with the connection portion to form a table surface.

[0010] In an embodiment, the splicing structure includes at least one connection member provided on a side of the splicing member; an installation hole matched with the connection member is provided on an outer sidewall of the connection portion, and the connection member is detachably connected to the installation hole.

[0011] In an embodiment, the connection member includes a head portion and a rod portion connected to the head portion, and a diameter of the head portion is larger than a diameter of the rod portion; and [0012] the installation hole includes a fixed end and a connection end communicated with the fixed end; the head portion is inserted into the installation hole through the connection end, and the rod portion is configured to move to the fixed end.

[0013] In an embodiment, the stove table further includes: [0014] a sealing member configured for sealing the installation hole, the sealing member is provided with a protrusion matched with a shape of the installation hole, and the sealing member is detachably connected to the installation hole through the protrusion.

[0015] In an embodiment, an accommodation chamber is provided in the stove, and a plurality of

soft magnetic strips are provided on an inner wall of the accommodation chamber and configured to be magnetically fixed with the splicing member.

[0016] In an embodiment, the stove table further includes: [0017] a splicing cover, a top surface of the connection portion is provided with a first opening communicated with the accommodation chamber, and the splicing cover is configured to cover the first opening.

[0018] In an embodiment, a side of the stove is provided with a second opening communicated with the accommodation chamber; and

[0019] the stove includes a door panel configured for opening or closing the second opening, and the door panel is provided with a storage rack.

[0020] In an embodiment, the stove table further includes: [0021] a brazier, an inner wall of the first opening is provided with an installation portion, and the brazier is installed on the installation portion.

[0022] In an embodiment, each of the splicing members is provided with a fixed pin and a connection hole; and [0023] in response to that two adjacent splicing members are spliced in place, the fixed pin of each splicing member is detachably connected with the connection hole of another splicing member adjacent to the splicing member.

[0024] In an embodiment, the splicing member is provided with an installation bracket, and the installation bracket includes a base plate connected to the splicing member and connection arms provided on both sides of the base plate; and [0025] the fixed pin is provided with an elastic member; the fixed pin is movably provided on the installation bracket, and the elastic member is provided between the two connection arms.

[0026] In the technical solution of the present application, the plurality of splicing members are detachably connected with each other, and the plurality of splicing members are detachably connected to the connection portion through the splicing structure to form the table surface. The splicing structure is provided on the splicing member, so that the splicing member are detachably connected to the connection portion through the splicing structure, replacing the existing stove table in which the plurality of table plates and the stove are fixedly spliced together through screws to form the table surface, and avoiding the cumbersome operation of installing or disassembling screws between the plurality of table plates and the stove in the related art, thereby solving the problem of inconvenient assembly between the table plates and the stove of the stove table in the related art.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0027] In order to illustrate the technical solutions in the embodiments of the present application or in the related art more clearly, the following briefly introduces the accompanying drawings required for the description of the embodiments or the related art. Obviously, the drawings in the following description are only part of embodiments of the present application. For those skilled in the art, other drawings can also be obtained according to the structures shown in these drawings without any creative effort.

[0028] FIG. 1 is a schematic decomposed structural view of a stove table according to an embodiment of the present application.

[0029] FIG. 2 is a bottom view of the stove table in FIG. 1.

[0030] FIG. 3 is an enlarged schematic view at A in FIG. 2.

[0031] FIG. 4 is a schematic connection view of the stove table in use state according to an embodiment of the present application.

[0032] FIG. 5 is a schematic connection view of the stove table in storage state according to an embodiment of the present application.

[0033] FIG. 6 is a bottom view of a splicing member.

[0034] FIG. 7 is a structural schematic view of a sealing member.

[0035] FIG. 8 is a structural schematic view of a connection member.

[0036] The realization of the objective, functional characteristics, and advantages of the present application are further described with reference to the accompanying drawings.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0037] The technical solutions of the embodiments of the present application will be described in more detail below with reference to the accompanying drawings. It is obvious that the embodiments to be described are only some rather than all of the embodiments of the present application. All other embodiments obtained by those skilled in the art based on the embodiments of the present application without creative efforts shall fall within the scope of the present application.

[0038] It should be noted that if there are directional indications, such as up, down, left, right, front, back, etc., involved in the embodiments of the present application, the directional indications are only used to explain a certain posture as shown in the accompanying drawings. If the specific posture changes, the directional indication also changes accordingly.

[0039] In addition, if there are descriptions related to “first”, “second”, etc. in the embodiments of the present application, the descriptions of “first”, “second”, etc. are only for the purpose of description, and should not be construed as indicating or implying relative importance or implicitly indicates the number of technical features indicated. Thus, a feature delimited with “first”, “second” may expressly or implicitly include at least one of that feature. Besides, the meaning of “and/or” appearing in the application includes three parallel scenarios. For example, “A and/or B” includes only A, or only B, or both A and B. In addition, the technical solutions between the various embodiments can be combined with each other, but must be based on the realization by those skilled in the art. When the combination of technical solutions is contradictory or cannot be realized, it should be considered that the combination of such technical solutions does not exist or fall within the scope of protection claimed in the present application.

[0040] In the related art, the plurality of table plates and the stove body are fixedly assembled with each other by screws to form a table surface, so that the user needs to repeatedly install or disassemble the screws on the table plate during the process of installing and disassembling the table plate. Therefore, the existing stove table has the problem of inconvenient assembly between the plurality of table plates and the stove **10**. Therefore, the present application provides a stove table. A plurality of splicing members **20** are detachably connected with each other, and the plurality of splicing members **20** are detachably connected to the connection portion **11** through the splicing structure **21** to form the table surface. The splicing structure **21** is provided on the splicing member **20**, so that the splicing member **20** are detachably connected to the connection portion **11** through the splicing structure **21**, replacing the existing stove table in which the plurality of table plates and the stove **10** are fixedly spliced together through screws to form the table surface, and avoiding the cumbersome operation of installing or disassembling screws between the plurality of table plates and the stove **10** in the related art, thereby solving the problem of inconvenient assembly between the table plates and the stove of the stove table in the related art.

[0041] As shown in FIG. 1 to FIG. 5, the stove table of the present application includes a stove **10** and a plurality of splicing members **20**. A connection portion **11** is provided on a top of the stove **10**; the plurality of splicing members **20** are provided along the circumference of the connection portion **11**, any two adjacent splicing members **20** are detachably connected, and each of the splicing members **20** is detachably connected to the connection portion **11** through a splicing structure **21**. When the stove table is in the use state, the plurality of splicing members **20** are spliced together with the connection portion **11** to form a table surface.

[0042] In this embodiment, the connection portion **11** includes four first sides for connecting the splicing members **20**, and the four first sides are respectively provided along the circumference of

the connection portion **11**. The splicing member **20** is a plate-shape structure, and any two adjacent splicing members **20** are detachably connected. A splicing structure **21** is provided on a second side of the splicing member **20** which is relatively longer, and the splicing structure **21** is a step screw. One end of the splicing structure **21** is threadedly connected to the splicing member **20**, so that a part of the splicing structure **21** is located outside the splicing member **20**. The number of the splicing members **20** is corresponding to the number of the first sides. Four splicing members **20** are respectively connected to the four first sides one by one through the splicing structures **21**, so as to be detachably connected to form a table surface. Therefore, the user only needs to sequentially connect the part of the splicing structure **21** located outside the splicing member **20** with the first side by hanging, and the table surface can be spliced. Compared with the existing stove table in which the plurality of table plates and the installation portion **112** of the stove **10** are fixedly spliced by screws to form the table surface, the cumbersome operation of screwing is avoided for installation or disassembly between the plurality of table plates and the installation portion **112** of the stove **10** in the related art, thereby solving the problem of inconvenient assembly between the table plate and the stove **10** of the existing stove table.

[0043] As shown in FIG. 1, FIG. 6 and FIG. 8, in this embodiment, the splicing structure **21** includes at least one connection member **211** provided on the side of the splicing member **20**, and the outer wall of the connection portion **11** is provided with an installation hole **111** matched with the connection member **211**, and the connection member **211** is detachably connected to the installation hole **111**.

[0044] In this embodiment, in order to improve the stability of the connection between the splicing member **20** and the connection portion **11**, a plurality of connection members **211** are provided, a plurality of installation holes **111** are provided, and the number of the installation holes **111** is matched with the number of the connection member **211**. The plurality of installation holes **111** are provided along the outer sidewall of the connection portion **11** in the circumferential direction. The splicing member **20** is cooperated with the installation hole **111** corresponding to the outer sidewall of the connection portion **11** through at least one connection member **211** on the side, so that the connection member **211** is detachably connected to the installation hole **111**, thereby simplifying the assembly connection between the splicing member **20** and the connection portion **11**.

[0045] As shown in FIG. 1, FIG. 6 and FIG. 8, in this embodiment, the connection member **211** includes a head portion **2111** and a rod portion **2112** connected to the head portion **2111**, and the diameter of the head portion **2111** is larger than the diameter of the rod portion **2112**. The installation hole **111** includes a fixed end **1111** and a connection end **1112** communicated with the fixed end **1111**, the head portion **2111** can be inserted into the installation hole **111** through the connection end **1112**, and the rod portion **2112** can be displaced to the fixed end **1111**.

[0046] In this embodiment, the rod portion **2112** includes a thread section, and the rod portion **2112** is connected to the splicing member **20** through the thread section, so that the head portion **2111** is located outside the splicing member **20**, thereby facilitating the splicing installation of the splicing member **20** and the connection portion **11**. The installation hole **111** is gourd-shaped, and the installation hole **111** includes a fixed end **1111** and a connection end **1112** which are communicated with each other and of different sizes. The diameter of the connection end **1112** is larger than the diameter of the fixed end **1111** and the diameter of the head portion **2111** respectively, the diameter of the head portion **2111** is larger than the diameter of the rod portion **2112**, and the diameter of the fixed end **1111** is the same as the diameter of the rod portion **2112**. Therefore, when the splicing member **20** is spliced with the connection portion **11**, the connection member **211** first passes through the connection end **1112** through the head portion **2111**, so that the connection member **211** is inserted into the installation hole **111**, and then the connection member **211** is driven to move in a direction close to the fixed end **1111**, so that the rod portion **2112** is fixed in the fixed end **1111**, thereby simplifying the splicing method of the splicing member **20** and the connection portion **11**. Similarly, when the splicing member **20** is disassembled from the connection portion **11**, the user

drives the connection member **211** to move toward the connection end **1112**, so that the rod portion **2112** moves from the fixed end **1111** to the connection end **1112**, and then the user pulls out the splicing member **20** in a direction away from the connection portion **11** to complete the disassembly.

[0047] As shown in FIG. 5 and FIG. 7, in this embodiment, the stove table further includes a sealing member **30** configured for sealing the installation hole **111**, and the sealing member **30** is provided with a protrusion **31** matching the shape of the installation hole **111**, and the sealing member **30** is detachably connected in the installation hole **111** through the protrusion **31**.

[0048] In this embodiment, when the stove table is in the storage state, the splicing member **20** is disassembled from the connection portion **11**, and the plurality of splicing members **20** are placed in the stove **10**. In order to make the stove table in the storage state beautiful in appearance, the sealing member **30** is detachably connected to the installation hole **111**, thereby preventing foreign debris from entering the installation hole **111**, and also preventing the installation hole **111** structure from being directly exposed to the stove table, which ensures the overall appearance of the stove table. In order to enable the sealing member **30** to better seal the installation hole **111**, the sealing member **30** is provided with a protrusion **31** matching the shape of the installation hole **111**. The sealing member **30** can fill the inner wall of the installation hole **111** through the protrusion **31**, thereby further preventing foreign debris from entering the installation hole **111**.

[0049] As shown in FIG. 4 and FIG. 5, in this embodiment, the stove **10** is provided with an accommodation chamber **12**, and the inner wall of the accommodation chamber **12** is provided with a plurality of soft magnetic strips **121** configured to be magnetically fixed with the splicing member **20**.

[0050] In this embodiment, when the stove table is in the storage state, the accommodation chamber **12** is configured to store the plurality of splicing members **20**. In order to improve the stability of the connection between the splicing member **20** and the inner wall of the accommodation chamber **12**, a plurality of soft magnetic strips **121** are provided on the inner wall of the accommodation chamber **12** and configured to be magnetically fixed on the inner wall of the accommodation chamber **12** through the soft magnetic strips **121**.

[0051] As shown in FIG. 1 and FIG. 4, in this embodiment, the stove table further includes a splicing cover **40**, and the top surface of the connection portion **11** is provided with a first opening communicated with the accommodation chamber **12**. The splicing cover **40** covers the first opening.

[0052] In this embodiment, the splicing cover **40** covers the first opening on the top surface of the connection portion **11**, so that the splicing cover **40** is cooperated with other splicing members **20** to form a complete table surface, and the user can use the stove table as a table in summer when the stove **10** is not used, thereby increasing the diversity of the use of the stove table.

[0053] As shown in FIG. 4 and FIG. 5, in this embodiment, the side of the stove **10** is provided with a second opening communicated with the accommodation chamber **12**, and the stove **10** includes a door panel **13** for opening or closing the second opening. The door panel **13** is provided with a storage rack **131**.

[0054] In this embodiment, in order to facilitate the user to store the splicing member **20**, the second opening communicated with the accommodation chamber **12** is provided on the side of the stove **10**, and the user can place the plurality of splicing members **20** in the accommodation chamber **12** through the second opening. When the stove table is in use, a storage rack **131** is provided on the door panel **13**, and the storage rack **131** is configured to store the sealing member **30** and the splicing cover **40** and other parts that are not needed temporarily, thereby improving the convenience of using the stove table.

[0055] As shown in FIG. 1 and FIG. 5, in this embodiment, the stove **10** also includes a brazier **14**, the inner wall of the first opening is provided with an installation portion **112**, and the brazier **14** is installed on the installation portion **112**.

[0056] In this embodiment, in order to improve the stability of the connection between the brazier **14** and the connection portion **11**, the brazier **14** is installed on the installation portion **112** by screws. Coal is placed on the brazier **14**, and the brazier **14** includes a connecting pipe and an igniter communicated with the connecting pipe. The other side of the connecting pipe is communicated with the gas bottle, and the gas fuel is transported to the outer periphery of the igniter through the connecting pipe to ignite and burn the coal, so that the user can heat the stove table. It should be noted that the gas bottle can also be placed in the accommodation chamber **12**, or the gas bottle can be placed outside the stove table.

[0057] As shown in FIG. 2, FIG. 3 and FIG. 6, in this embodiment, each of the splicing members **20** is provided with a fixed pin **22** and a connection hole **24**. When two adjacent splicing members **20** are spliced in place, the fixed pin **22** of each splicing member **20** is detachably connected to the connection hole **24** of adjacent splicing member **20**.

[0058] In this embodiment, the fixed pin **22** is provided at the other end away from the connection hole **24**. In order to improve the stability of the splicing between the plurality of splicing members **20**, adjacent splicing members **20** are fixedly connected by the fixed pin **22** and the connection hole **24**, and the fixed pin **22** on each splicing member **20** is extended into the connection hole **24** of adjacent splicing member **20** for locking, thereby preventing the splicing member **20** from sagging due to external force and falling off from the connection portion **11**. As shown in FIG. 2, FIG. 3 and FIG. 6, in this embodiment, the splicing member **20** is provided with an installation bracket **23**, and the installation bracket **23** includes a base plate **231** connected to the splicing member **20** and a connection arm **232** provided on both sides of the base plate **231**. The fixed pin **22** is provided with an elastic member **221**, and the fixed pin **22** is movably provided on the installation bracket **23**. The elastic member **221** is provided between the two connection arms **232**.

[0059] In this embodiment, in order to improve the stability of the connection between adjacent splicing members **20**, an installation bracket **23** is provided on the splicing member **20**, and the fixed pin **22** is movably provided on the installation bracket **23**. The two ends of the elastic member **221** are elastically abutted against the connection arms **232** on both sides respectively. When the fixed pin **22** is locked with the connection hole **24**, since the elastic member **221** has the elasticity, the elastic member **221** can alleviate the displacement of the fixed pin **22** from the connection hole **24** due to the influence of external force, so that the fixed pin **22** can only move under the drive of the user, thereby improving the connection stability between the fixed pin **22** and the connection hole **24**, and further improving the connection stability between each of the splicing members **20**.

[0060] In this embodiment, the fixed pin **22** includes a connection section and a driven section connected to the connection section, the driven section is tilted relative to the connection section, and the elastic member **221** is provided on the connection section. The user drives the driven section to move toward or away from the connection hole **24**, so that one end of the driven section extends into the connection hole **24** of the other splicing member **20** or the driven section extends out of the connection hole **24** of the other splicing member **20**, thereby achieving a locked connection or disassembly between the fixed pin **22** and the connection hole **24**.

[0061] The above descriptions are only embodiments of the present application, and are not intended to limit the scope of the present application. Under the inventive concept of the present application, any equivalent structural transformations made by using the contents of the description and drawings of the present application, or direct/indirect applications in other related technical fields are included in the scope of the present application.

Claims

1. A stove table, comprising: a stove, wherein a connection portion is provided on a top of the stove; and a plurality of splicing members provided along a circumference of the connection portion, wherein any two adjacent splicing members are detachably connected, and each of the

splicing members is detachably connected to the connection portion through a splicing structure; wherein in response to that the stove table is in use, the plurality of splicing members are spliced with the connection portion to form a table surface.

2. The stove table according to claim 1, wherein the splicing structure comprises at least one connection member provided on a side of the splicing member; an installation hole matched with the connection member is provided on an outer sidewall of the connection portion, and the connection member is detachably connected to the installation hole.

3. The stove table according to claim 2, wherein the connection member comprises a head portion and a rod portion connected to the head portion, and a diameter of the head portion is larger than a diameter of the rod portion; and the installation hole comprises a fixed end and a connection end communicated with the fixed end; the head portion is inserted into the installation hole through the connection end, and the rod portion is configured to move to the fixed end.

4. The stove table according to claim 3, further comprising: a sealing member configured for sealing the installation hole, wherein the sealing member is provided with a protrusion matched with a shape of the installation hole, and the sealing member is detachably connected to the installation hole through the protrusion.

5. The stove table according to claim 1, wherein an accommodation chamber is provided in the stove, and a plurality of soft magnetic strips are provided on an inner wall of the accommodation chamber and configured to be magnetically fixed with the splicing member.

6. The stove table according to claim 5, further comprising: a splicing cover, wherein a top surface of the connection portion is provided with a first opening communicated with the accommodation chamber, and the splicing cover is configured to cover the first opening.

7. The stove table according to claim 6, wherein a side of the stove is provided with a second opening communicated with the accommodation chamber; and the stove comprises a door panel configured for opening or closing the second opening, and the door panel is provided with a storage rack.

8. The stove table according to claim 6, further comprising: a brazier, wherein an inner wall of the first opening is provided with an installation portion, and the brazier is installed on the installation portion.

9. The stove table according to claim 1, wherein each of the splicing members is provided with a fixed pin and a connection hole; and in response to that two adjacent splicing members are spliced in place, the fixed pin of each splicing member is detachably connected with the connection hole of another splicing member adjacent to the splicing member.

10. The stove table according to claim 9, wherein the splicing member is provided with an installation bracket, and the installation bracket comprises a base plate connected to the splicing member and connection arms provided on both sides of the base plate; and the fixed pin is provided with an elastic member; the fixed pin is movably provided on the installation bracket, and the elastic member is provided between the two connection arms.
