

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250285844

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

KIMURA; Kentaro

SUSCEPTOR

Abstract

There is provided a susceptor including: a ceramic plate including a first surface and a second surface; an internal electrode embedded in the ceramic plate; a metal layer provided as an RF electrode on an entirety or a part of the second surface of the ceramic plate; a cooling plate provided at a predetermined distance from the second surface; a heat transfer space present between the metal layer and the cooling plate, and configured to enable heat transfer through gas; a seal member provided along outer peripheries of the ceramic plate and the cooling plate between the ceramic plate and the cooling plate, to impart airtightness to the heat transfer space; and an RF conduction member provided at a position on an inner peripheral side of the seal member between the ceramic plate and the cooling plate to secure electric connection between the metal layer and the cooling plate.

Inventors: KIMURA; Kentaro (Handa-Shi, JP)

Applicant: NGK INSULATORS, LTD. (Nagoya-City, JP)

Family ID: 1000008128288

Assignee: NGK INSULATORS, LTD. (Nagoya-City, JP)

Appl. No.: 18/805646

Filed: August 15, 2024

Related U.S. Application Data

parent WO continuation PCT/JP2024/008613 20240306 PENDING child US 18805646

Publication Classification

Int. Cl.: H01J37/32 (20060101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] This application is a continuation application of PCT/JP2024/008613 filed Mar. 6, 2024, the entire contents of which are incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

[0002] The present disclosure relates to a susceptor.

2. Description of the Related Art

[0003] In a film formation apparatus and an etching apparatus for a semiconductor manufacturing process, a susceptor is used to support a wafer. As such a susceptor, a susceptor including a ceramic plate on which the wafer is to be placed, an RF electrode inducing generation of high-frequency plasma, and a cooling plate is widely used. The ceramic plate generally has a configuration in which an internal electrode such as a heater electrode, an RF electrode, an electrostatic chuck (ESC) electrode is embedded inside a ceramic substrate made of aluminum nitride (AlN) or the like excellent in heat resistance and corrosion resistance.

[0004] Patent Literature 1 (JP2023-5203A) discloses a substrate support that supports a substrate and includes a substrate attraction part including an attraction electrode for holding the substrate, and RF electrode part to which RF power is supplied, and a substrate temperature adjuster including a heater electrode for adjusting a temperature of the substrate, and discloses a stacked-layer structure in which the RF electrode part is interposed between the substrate attraction part and the substrate temperature adjuster.

[0005] Patent Literature 2 (JP6884110B) discloses an electrostatic puck assembly including an upper puck plate, a lower puck plate joined to the upper puck plate by first metal joining, a backing plate joined to a bottom surface of the lower puck plate by second metal joining, and an electrically conductive gasket. The upper puck plate contains AlN or Al.sub.2O.sub.3, and has a first thermal expansion coefficient. The upper puck plate further includes one or more heating elements, and one or more electrodes for electrostatically fixing the substrate. The lower puck plate contains a material having the first thermal expansion coefficient or a second thermal expansion coefficient. The backing plate is a plate having a disc shape and containing AlN or Al.sub.2O.sub.3, and has a first diameter less than a second diameter of the lower puck plate. The electrically conductive gasket is disposed on the bottom surface of the lower puck plate outside the first diameter of the backing plate.

CITATION LIST

Patent Literature

[0006] Patent Literature 1: JP2023-5203A

[0007] Patent Literature 2: JP6884110B

SUMMARY OF THE INVENTION

[0008] As a typical example of the RF electrode in the existing susceptor, a metal mesh (for example, molybdenum mesh) embedded in the ceramic plate is known. In such an existing structure, the metal mesh tends to undulate due to flexibility thereof. Therefore, it is difficult to control uniformization of the distance between the top surface of the ceramic plate and the metal mesh in plane, important to realize a desired RF function, and incident ion concentration generated by voltage application to the RF electrode is varied due to deviation of in-plane distribution of the

distance. Therefore, it is desirable to provide a configuration in which the in-plane variation of the distance between the top surface of the ceramic plate and the metal mesh can be easily suppressed. [0009] In the semiconductor manufacturing apparatus for etching, the susceptor is desired to have high heat removal property in order to promptly dissipate heat input from the plasma from the susceptor. However, in the susceptor having high heat removal property, an expensive joining method such as metal diffusion joining (for example, TCB joining) is currently adopted for connection between the ceramic plate and the cooling plate. Therefore, it is advantageous if the ceramic plate and the cooling plate are connected by an inexpensive method.

[0010] The present inventors have found that by disposing, on a bottom surface side of the ceramic plate embedded with the internal electrode, a metal layer as an RF electrode, a heat transfer space sealed by a seal member, and a cooling plate in order and also disposing, in the heat transfer space, an RF conduction member electrically connecting the metal layer and the cooling plate, it is possible to provide a susceptor that has an inexpensive configuration suitable for suppressing in-plane variation of a distance between a top surface of the ceramic plate and the RF electrode.

[0011] An object of the present invention is to provide a susceptor having an inexpensive configuration that includes an RF function and is suitable for suppressing in-plane variation of a distance between a top surface of a ceramic plate and an RF electrode.

[0012] The present disclosure provides the following aspects.

Aspect 1

[0013] A susceptor comprising: [0014] a ceramic plate having a disc shape and including a first surface and a second surface; [0015] an internal electrode embedded in the ceramic plate; [0016] a metal layer provided as an RF electrode on an entirety or a part of the second surface of the ceramic plate; [0017] a cooling plate having a disc shape and provided at a predetermined distance from the second surface of the ceramic plate; [0018] a heat transfer space present between the metal layer and the cooling plate, and configured to enable heat transfer through gas; [0019] a seal member provided along outer peripheries of the ceramic plate and the cooling plate between the ceramic plate and the cooling plate, to impart airtightness to the heat transfer space; and [0020] an RF conduction member provided at a position on an inner peripheral side of the seal member between the ceramic plate and the cooling plate, and configured to secure electric connection between the metal layer and the cooling plate.

Aspect 2

[0021] The susceptor according to aspect 1, wherein the metal layer has a thickness of 3 μm to 500 μm .

Aspect 3

[0022] The susceptor according to aspect 1 or 2, wherein the metal layer is a layer formed by printing or plating, or a metal sheet.

Aspect 4

[0023] The susceptor according to any one of aspects 1 to 3, wherein the ceramic plate contains aluminum nitride and/or aluminum oxide.

Aspect 5

[0024] The susceptor according to any one of aspects 1 to 4, wherein the cooling plate is made of a metal or a metal matrix composite.

Aspect 6

[0025] The susceptor according to any one of aspects 1 to 5, wherein the RF conduction member includes an elongated metal part wound in a spiral shape.

Aspect 7

[0026] The susceptor according to any one of aspects 1 to 6, further comprising a terminal rod connected to the internal electrode, and configured to extend in a direction away from the second surface across the second surface, the metal layer, the heat transfer space, and the cooling plate.

Aspect 8

[0027] The susceptor according to aspect 7, wherein the cooling plate includes an opening hole through which the terminal rod passes, and a surface of the opening hole is covered with an insulating member to insulate the terminal rod from the cooling plate.

Aspect 9

[0028] The susceptor according to any one of aspects 1 to 8, wherein the cooling plate includes an internal space for a cooling medium to flow inside the cooling plate.

Aspect 10

[0029] The susceptor according to any one of aspects 1 to 9, further comprising a fixing member provided along the outer periphery of the susceptor, the fixing member fixing the ceramic plate, the metal layer, the seal member, the RF conduction member, and the cooling plate to be brought into contact with one another.

Aspect 11

[0030] The susceptor according to aspect 10, wherein the ceramic plate includes a small-diameter portion having a relatively small diameter and providing the first surface, and a large-diameter portion having a relatively large diameter and providing the second surface, such that the large-diameter portion and the small-diameter portion form a step portion, and wherein the fixing member is configured to be engageable with the step portion.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0031] FIG. 1 is a schematic cross-sectional view illustrating an example of a susceptor according to the present disclosure.

[0032] FIG. 2 is a schematic plan view of the susceptor illustrated in FIG. 1.

[0033] FIG. 3 is a schematic perspective view illustrating an example of an RF conduction member.

DETAILED DESCRIPTION OF THE INVENTION

[0034] A susceptor according to the present invention is a table for supporting a wafer, used for a semiconductor manufacturing apparatus, in particular, for a film formation apparatus or an etching apparatus for a semiconductor manufacturing process. The susceptor according to the present invention preferably includes a ceramic heater for a semiconductor film formation apparatus. Typical examples of the film formation apparatus include a CVD (chemical vapor deposition) apparatus (for example, thermal CVD apparatus, plasma CVD apparatus, optical CVD apparatus, and MOCVD apparatus), and a PVD (physical vapor deposition) apparatus, and the film formation apparatus is especially preferably a plasma CVD apparatus.

[0035] FIGS. 1 and 2 illustrate one aspect of a susceptor 10. The susceptor 10 illustrated in FIG. 1 includes a ceramic plate 12, an internal electrode 14, a metal layer 16, a cooling plate 18, a heat transfer space 20, a seal member 22, and an RF conduction member 24. The ceramic plate 12 has a disc shape and includes a first surface 12a and a second surface 12b. The internal electrode 14 is embedded in the ceramic plate 12. The metal layer 16 is provided as an RF electrode on an entirety or a part of the second surface 12b of the ceramic plate 12. The cooling plate 18 has a disc shape, and is provided at a predetermined distance from the second surface 12b of the ceramic plate 12. The heat transfer space 20 is a space enabling heat transfer through gas, and is present between the metal layer 16 and the cooling plate 18. The seal member 22 is provided along outer peripheries of the ceramic plate 12 and the cooling plate 18 between the ceramic plate 12 and the cooling plate 18, so as to impart airtightness to the heat transfer space 20. The RF conduction member 24 is a member securing electric connection between the metal layer 16 and the cooling plate 18, and is provided at a position on an inner peripheral side of the seal member 22 between the ceramic plate 12 and the cooling plate 18. In this way, by disposing, on the second surface 12b side of the

ceramic plate **12** embedded with the internal electrode **14**, the metal layer **16** as the RF electrode, the heat transfer space **20** sealed by the seal member **22**, and the cooling plate **18** in order and also disposing, in the heat transfer space **20**, the RF conduction member **24** electrically connecting the metal layer **16** and the cooling plate **18**, it is possible to provide the susceptor that has an inexpensive configuration suitable for suppressing in-plane variation of a distance between the first surface **12a** of the ceramic plate **12** and the metal layer **16** (RF electrode).

[0036] As described above, in the existing structure, the metal mesh tends to undulate due to flexibility thereof. Therefore, it is difficult to control uniformization of the distance between the top surface of the ceramic plate and the metal mesh in plane, important to realize a desired RF function, and incident ion concentration generated by voltage application to the RF electrode is varied due to deviation of in-plane distribution of the distance. In other words, the RF function is affected by the distance between the top surface of the ceramic plate and the RF electrode. Therefore, when the in-plane variation occurs on the above-described distance in a product, incidence on the wafer is varied, which causes characteristic variation of a wafer surface. For example, in a case where the wafer surface is etched by incidence of ions or radicals, when electron density and a temperature are varied due to the above-described in-plane variation, product performance is largely affected. Therefore, it is desirable to provide a configuration in which the in-plane variation of the distance between the top surface of the ceramic plate and the metal mesh can be easily suppressed. In this regard, according to the present invention, the RF electrode such as a metal mesh is not embedded in the ceramic plate **12**, but the metal layer **16** is formed on an entirety or a part of the second surface **12b** of the ceramic plate **12**, and the metal layer **16** is used as the RF electrode. In the configuration, after the second surface **12b** of the ceramic plate **12** is processed so as to improve smoothness, the metal layer **16** can be formed by an inexpensive method such as printing, plating, and sheet bonding, and can be used as the RF electrode. For example, desired flatness and parallelism (relative to first surface **12a**) are imparted to the second surface **12b** of the ceramic plate **12** by a common machining process or the like, and then, the metal layer **16** is formed on the second surface **12b** of the ceramic plate **12**, which makes it possible to easily secure a parallelism of a top surface of the metal layer **16** relative to the first surface **12a** of the ceramic plate **12**. Performing formation of the ceramic plate **12** and formation of the metal layer **16** in different processes as described above makes it possible to reduce a manufacturing cost. Accordingly, it is possible to suppress the in-plane variation of the distance between the first surface **12a** of the ceramic plate **12** and the metal layer **16** (RF) electrode. As a result, it is possible to inexpensively realize the desired RF function.

[0037] In the semiconductor manufacturing apparatus for etching, the susceptor is desired to have high heat removal property in order to promptly dissipate heat input from the plasma from the susceptor. However, in the susceptor having high heat removal property, an expensive joining method such as metal diffusion joining (for example, TCB joining) is currently adopted for connection between the ceramic plate and the cooling plate. Therefore, it is advantageous if the ceramic plate and the cooling plate are connected by an inexpensive method. In this regard, according to the present invention, the cooling plate is not joined to the second surface **12b** of the ceramic plate **12** by the expensive joining method, but the cooling plate **18** is disposed through the heat transfer space **20** sealed by the seal member **22**. The heat transfer space **20** is formed when the seal member **22** is provided along the outer peripheries of the ceramic plate **12** and the cooling plate **18** so as to impart airtightness to the heat transfer space **20**, and enables heat transfer through gas. In addition, electric connection between the metal layer **16** as the RF electrode and the cooling plate **18** is secured by the RF conduction member **24** provided at the position on the inner peripheral side of the seal member **22**. These configurations are inexpensively obtainable because the expensive joining method such as the metal diffusion joining (for example, TCB joining) is not required. Nevertheless, the heat generated in the ceramic plate **12** can be efficiently removed through the heat transfer space **20** and the cooling plate **18** adjacent thereto. In addition, since the

heat transfer space **20** is sealed by the seal member **22**, it is possible to prevent corrosive gas used for cleaning in a chamber from entering the heat transfer space **20**. As a result, it is possible to avoid corrosion of the metal layer **16** by the corrosive gas.

[0038] In terms of excellent heat conductivity, high electric insulation property, thermal expansion characteristics close to silicon, and the like, a main portion (namely, ceramic substrate) of the ceramic plate **12** other than embedded members such as the internal electrode **14** preferably contains aluminum nitride and/or aluminum oxide, and more preferably contains aluminum nitride.

[0039] The ceramic plate **12** has a disc shape. However, the ceramic plate **12** formed in the disc shape is not required to have a complete circular shape in a planar view, and the ceramic plate **12** may have an incomplete circular shape partially cut away, such as an orientation flat in a planar view. A size of the ceramic plate **12** is appropriately determined based on a diameter of the wafer assumed to be used and is not particularly limited. In a case of a circular shape, a diameter of the ceramic plate **12** is typically 150 mm to 450 mm, and is typically 320 mm to 380 mm especially for a 300 mm silicon wafer. A thickness of the ceramic plate **12** is typically 10 mm to 25 mm.

[0040] The first surface **12a** and the second surface **12b** of the ceramic plate **12** are preferably flat and parallel to each other. As described above, the desired flatness and parallelism (relative to first surface **12a**) are imparted to the second surface **12b** of the ceramic plate **12** by a common machining process or the like, and then, the metal layer **16** is formed on the second surface **12b** of the ceramic plate **12**, which makes it possible to effectively suppress the in-plane variation of the distance between the first surface **12a** of the ceramic plate **12** and the metal layer **16** (RF electrode). As a result, it is possible to inexpensively realize the desired RF function. For example, the flatness of the second surface **12b** is preferably 50 μm or less, and more preferably 20 μm or less. The parallelism of the second surface **12b** relative to the first surface **12a** is preferably 50 μm or less, and more preferably 20 μm or less. The flatness and the parallelism are terms defined in JIS B 0621-1984. More specifically, the flatness is defined as a minimum interval between two planes that are geometrically parallel to each other when a planar body (second surface **12b**) is sandwiched between the two planes. The parallelism of the planar body (second surface **12b**) to a datum plane (corresponding to first surface **12a**) is defined as an interval between two planes that are geometrically parallel to each other and are parallel to the datum plane (corresponding to first surface **12a**) when the planar body (second surface **12b**) is sandwiched between the two planes.

[0041] Preferably, the ceramic plate **12** includes a small-diameter portion **12c** having a relatively small diameter and providing the first surface **12a**, and a large-diameter portion **12d** having a relatively large diameter and providing the second surface **12b**, and the large-diameter portion **12d** and the small-diameter portion **12c** form a step portion **12e**. The ceramic plate **12** having the shape is advantageous in terms of attachment easiness of a fixing member **30** described below.

[0042] The internal electrode **14** is an electrode embedded in the ceramic plate **12**, and includes a heater electrode or an ESC electrode or both. Although not particularly limited, for example, the heater electrode may be a conductive coil laid in a one-stroke manner over an entire surface of the ceramic plate **12**. Terminal rods **26** for power supply are connected to respective ends of the heater electrode, and the heater electrode is connected to a heater power supply (not illustrated) through the terminal rods **26**. The terminal rods **26** connected to the internal electrode **14** preferably extend in a direction away from the second surface **12b** across the second surface **12b**, the metal layer **16**, the heat transfer space **20**, and the cooling plate **18**. When power is supplied from the heater power supply, the heater electrode generates heat to heat the wafer placed on the top surface of the ceramic plate **12**. The heater electrode is not limited to the coil, and may be, for example, a ribbon (long thin plate), a mesh, or a print. The ESC electrode is an abbreviation for an electrostatic chuck (ESC) electrode, and is also referred to as an electrostatic electrode. The ESC electrode is preferably a circular thin layer electrode having a diameter slightly smaller than the diameter of the ceramic plate **12**, and may be, for example, a mesh-shaped electrode obtained by knitting thin metal wires to a mesh sheet. The terminal rods **26** for power supply are connected to the ESC electrode,

and the terminal rods may be connected to an external power supply (not illustrated). Even in this case, the terminal rods **26** connected to the internal electrode **14** as the ESC electrode preferably extend in the direction away from the second surface **12b** across the second surface **12b**, the metal layer **16**, the heat transfer space **20**, and the cooling plate **18**. When a voltage is applied from the external power supply, the ESC electrode chucks the wafer placed on the top surface of the ceramic plate **12** with Johnson Rahbeck force. The internal electrode **14** may include both the heater electrode and the ESC electrode. In this case, the heater electrode and the ESC electrode may be embedded as separate internal electrodes **14** at different depth positions in the ceramic plate **12**. Alternatively, only one of the heater electrode or the ESC electrode may be embedded as the internal electrode **14** in the ceramic plate **12**.

[0043] The metal layer **16** is provided as the RF electrode on an entirety or a part of the second surface **12b** of the ceramic plate **12**. A thickness of the metal layer **16** is preferably 3 μm to 500 μm , more preferably 20 μm to 300 μm , and further preferably 50 μm to 200 μm . Such a thin metal layer **16** is easily fitted to a surface shape of the second surface **12b** of the ceramic plate **12**, and accordingly, deformation such as undulation is less likely to occur. Therefore, it is possible to more effectively suppress the in-plane variation of the distance between the first surface **12a** of the ceramic plate **12** and the metal layer **16** (RF electrode). In that sense, the metal layer **16** is preferably a layer formed by printing or plating. Further, the metal layer **16** may be a metal sheet, and in this case, the metal sheet may be bonded to the second surface **12b** by an inexpensive method such as an adhesive.

[0044] A material of the metal layer **16** is not particularly limited as long as the metal layer **16** functions as the RF electrode, but the metal layer **16** is preferably made of a metal having a thermal expansion coefficient close to a thermal expansion coefficient of aluminum nitride or aluminum oxide, such as molybdenum, tungsten, and zirconium, or an alloy thereof.

[0045] The cooling plate **18** is a disc-shaped plate provided at a predetermined distance from the second surface **12b** of the ceramic plate **12**. The cooling plate **18** can have a configuration of a cooling plate generally used for a ceramic heater and electrostatic chuck. The cooling plate **18** is preferably made of a metal such as aluminum and an aluminum alloy in terms of RF supply, heat removal property, and a cost, but may be made of a metal matrix composite (MMC) such as SiSiCTi (composite material containing Si, SiC, and Ti). The typical cooling plate **18** includes an internal space providing a flow path **18a** for a cooling medium to flow inside the cooling plate **18**. For example, the flow path **18a** is connected to a refrigerant supply path and a refrigerant discharge path (not illustrated). The refrigerant discharged from the refrigerant discharge path is adjusted in temperature, and is then returned to the refrigerant supply path.

[0046] Preferably, the cooling plate **18** includes an opening hole through which the terminal rods **26** pass, and a surface of the opening hole is covered with an insulating member **28** to insulate the terminal rods **26** from the cooling plate **18** (made of, for example, metal).

[0047] The heat transfer space **20** is a space that is present between the metal layer **16** and the cooling plate **18** and enables heat transfer through gas. The typical heat transfer space **20** is a sealed space surrounded by the ceramic plate **12** including the metal layer **16** on the second surface **12b**, the cooling plate **18**, and the seal member **22**. In use, the heat transfer space **20** is filled with gas for heat transfer. Preferable examples of the gas filled in the heat transfer space **20** include helium (He).

[0048] The seal member **22** is provided along the outer peripheries of the ceramic plate **12** and the cooling plate **18** between the ceramic plate **12** and the cooling plate **18**, so as to impart airtightness to the heat transfer space **20**. Imparting airtightness to the heat transfer space **20** in such a manner makes it possible to prevent corrosive gas used for cleaning in the chamber from entering the heat transfer space **20**. As a result, it is possible to avoid corrosion of the metal layer **16** by the corrosive gas. The seal member **22** is not particularly limited as long as the seal member **22** has heat resistance necessary for the susceptor **10**, and a common inexpensive seal member such as an O-

ring and a metal seal can be used as the seal member **22**. Therefore, in the present invention, an expensive seal member having a special shape and/or made of a special material is not used as the seal member **22**, which is advantageous in terms of a cost.

[0049] The RF conduction member **24** is a member for securing electric connection between the metal layer **16** and the cooling plate **18**, and is provided at the position on the inner peripheral side of the seal member **22** between the ceramic plate **12** and the cooling plate **18**. To cause the metal layer **16** to function as the RF electrode, it is necessary to connect the metal layer **16** to an RF power supply (not illustrated) or to ground the metal layer **16**. However, since the heat transfer space **20** is present just below the metal layer **16** in the susceptor **10**, means for supplying RF to the metal layer **16** is necessary on the cooling plate **18** side. In this regard, since the RF conduction member **24** is interposed between the metal layer **16** and the cooling plate **18**, electric connection between the metal layer **16** and the cooling plate **18** is secured. Therefore, by connecting the cooling plate **18** to the RF power supply (not illustrated) or by grounding the cooling plate **18**, it is possible to cause the metal layer **16** to function as the RF electrode.

[0050] The RF conduction member **24** is not particularly limited as long as a member can secure electric connection between the metal layer **16** and the cooling plate **18**, but the RF conduction member **24** preferably includes an elongated metal part wound in a spiral shape as illustrated in FIG. **3**. The elongated metal part may have a plate shape, a rod shape, or other optional shape. As the elongated metal part wound in the spiral shape, a commercially-available spiral spring gasket is preferably used because of being inexpensively obtainable.

[0051] The susceptor **10** preferably further includes the fixing member **30** provided along the outer periphery of the susceptor **10**, and the fixing member **30** is preferably configured to fix the ceramic plate **12**, the metal layer **16**, the seal member **22**, the RF conduction member **24**, and the cooling plate **18** to be brought into contact with one another. For example, in a case where the ceramic plate **12** includes the small-diameter portion **12c** and the large-diameter portion **12d** to form the step portion **12e** as described above, the fixing member **30** is preferably configured to be engageable with the step portion **12e**. The fixing member **30** is not particularly limited as long as the fixing member **30** can fix the ceramic plate **12**, the metal layer **16**, the seal member **22**, the RF conduction member **24**, and the cooling plate **18** to be brought into contact with one another, and a well-known fixing member such as a clamp and a ring-shaped member (provided along outer periphery of ceramic plate **12**) may be used. In a case of the clamp, the ceramic plate **12** (for example, portion of large-diameter portion **12d** extending as step portion **12e**), the seal member **22**, the cooling plate **18**, and the like are sandwiched and fixed by a fixing mechanism of the clamp. In a case of the ring-shaped member, the ring-shaped member is placed on the ceramic plate **12** (for example, portion of large-diameter portion **12d** extending as step portion **12e**), and the ring-shaped member is fixed to the cooling plate **18** or the other apparatus member so as to be pressed against the cooling plate **18** by fixing means such as a screw.

Claims

1. A susceptor comprising: a ceramic plate having a disc shape and including a first surface and a second surface; an internal electrode embedded in the ceramic plate; a metal layer provided as an RF electrode on an entirety or a part of the second surface of the ceramic plate; a cooling plate having a disc shape and provided at a predetermined distance from the second surface of the ceramic plate; a heat transfer space present between the metal layer and the cooling plate, and configured to enable heat transfer through gas; a seal member provided along outer peripheries of the ceramic plate and the cooling plate between the ceramic plate and the cooling plate, to impart airtightness to the heat transfer space; and an RF conduction member provided at a position on an inner peripheral side of the seal member between the ceramic plate and the cooling plate, and configured to secure electric connection between the metal layer and the cooling plate.

2. The susceptor according to claim 1, wherein the metal layer has a thickness of 3 μm to 500 μm .
 3. The susceptor according to claim 1, wherein the metal layer is a layer formed by printing or plating, or a metal sheet.
 4. The susceptor according to claim 1, wherein the ceramic plate contains aluminum nitride and/or aluminum oxide.
 5. The susceptor according to claim 1, wherein the cooling plate is made of a metal or a metal matrix composite.
 6. The susceptor according to claim 1, wherein the RF conduction member includes an elongated metal part wound in a spiral shape.
 7. The susceptor according to claim 1, further comprising a terminal rod connected to the internal electrode, and configured to extend in a direction away from the second surface across the second surface, the metal layer, the heat transfer space, and the cooling plate.
 8. The susceptor according to claim 7, wherein the cooling plate includes an opening hole through which the terminal rod passes, and a surface of the opening hole is covered with an insulating member to insulate the terminal rod from the cooling plate.
 9. The susceptor according to claim 1, wherein the cooling plate includes an internal space for a cooling medium to flow inside the cooling plate.
 10. The susceptor according to claim 1, further comprising a fixing member provided along the outer periphery of the susceptor, the fixing member fixing the ceramic plate, the metal layer, the seal member, the RF conduction member, and the cooling plate to be brought into contact with one another.
 11. The susceptor according to claim 10, wherein the ceramic plate includes a small-diameter portion having a relatively small diameter and providing the first surface, and a large-diameter portion having a relatively large diameter and providing the second surface, such that the large-diameter portion and the small-diameter portion form a step portion, and wherein the fixing member is configured to be engageable with the step portion.
-