

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250286800

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

LEE; Hyun Yong et al.

MITIGATING JITTER IN COMMUNICATIONS

Abstract

Methods, systems, and devices for wireless communications are described. An application server (AS) may generate one or more packet data unit (PDU) sets of a first periodic burst transmission. The first periodic burst transmission may correspond to a first delivery deadline at a user equipment (UE) during a jitter window. The jitter window may span a time period prior to and after a first arrival time associated with the one or more PDU sets. The AS may buffer at least a portion of the one or more PDU sets for a first duration of the jitter window. The first duration may correspond to a threshold percentage of the jitter window. The AS may output the one or more PDU sets based on expiration of the first duration and prior to the first delivery deadline.

Inventors: LEE; Hyun Yong (San Diego, CA), TINNAKORNSRISUPHAP; Peerapol (San Diego, CA), HANDE; Prashanth Haridas (San Diego, CA), AGARWAL; Ravi (San Diego, CA), MONDET; Mickael (Louannec, FR), MAAMARI; Diana (San Diego, CA)

Applicant: QUALCOMM Incorporated (San Diego, CA)

Family ID: 1000008021226

Appl. No.: 18/759474

Filed: June 28, 2024

Related U.S. Application Data

us-provisional-application US 63563202 20240308

Publication Classification

Int. Cl.: H04L43/087 (20220101); H04L69/28 (20220101)

U.S. Cl.:

Background/Summary

CROSS REFERENCE [0001] The present Application for Patent claims the benefit of U.S. Provisional Patent Application No. 63/563,202 by LEE et al., entitled “MITIGATING JITTER IN COMMUNICATIONS,” filed Mar. 8, 2024, assigned to the assignee hereof, and expressly incorporated by reference herein.

FIELD OF TECHNOLOGY

[0002] The following relates to wireless communications, including mitigating jitter in communications.

BACKGROUND

[0003] Wireless communications systems are widely deployed to provide various types of communication content such as voice, video, packet data, messaging, broadcast, and so on. These systems may be capable of supporting communication with multiple users by sharing the available system resources (e.g., time, frequency, and power). Examples of such multiple-access systems include fourth generation (4G) systems such as Long Term Evolution (LTE) systems, LTE-Advanced (LTE-A) systems, or LTE-A Pro systems, and fifth generation (5G) systems which may be referred to as New Radio (NR) systems. These systems may employ technologies such as code division multiple access (CDMA), time division multiple access (TDMA), frequency division multiple access (FDMA), orthogonal FDMA (OFDMA), or discrete Fourier transform spread orthogonal frequency division multiplexing (DFT-S-OFDM). A wireless multiple-access communications system may include one or more base stations, each supporting wireless communication for communication devices, which may be known as user equipment (UE).

SUMMARY

[0004] The described techniques relate to improved methods, systems, devices, and apparatuses that support mitigating jitter in communications. For example, the described techniques provide for generating, at an application server (AS), one or more packet data unit (PDU) sets of a first periodic burst transmission. The first periodic burst transmission may correspond to a first delivery deadline at a user equipment (UE) during a jitter window. The jitter window may span a time period prior to and after a first arrival time associated with the one or more PDU sets. The AS may buffer at least a portion of the one or more PDU sets for a first duration of the jitter window. The first duration may correspond to a threshold percentage of the jitter window. The AS may output the one or more PDU sets based on expiration of the first duration and prior to the first delivery deadline.

[0005] A method for wireless communications by an AS is described. The method may include generating one or more PDU sets of a first periodic burst transmission, the first periodic burst transmission corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets, buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window, and outputting the one or more PDU sets upon expiration of the first duration and prior to the first delivery deadline.

[0006] An AS for wireless communications is described. The AS may include one or more memories storing processor executable code, and one or more processors coupled with the one or more memories. The one or more processors may individually or collectively be operable to execute the code to cause the AS to generate one or more PDU sets of a first periodic burst transmission, the first periodic burst transmission corresponding to a first delivery deadline at a UE

during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets, buffer at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window, and output the one or more PDU sets upon expiration of the first duration and prior to the first delivery deadline.

[0007] Another AS for wireless communications is described. The AS may include means for generating one or more PDU sets of a first periodic burst transmission, the first periodic burst transmission corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets, means for buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window, and means for outputting the one or more PDU sets upon expiration of the first duration and prior to the first delivery deadline.

[0008] A non-transitory computer-readable medium storing code for wireless communications is described. The code may include instructions executable by one or more processors to generate one or more PDU sets of a first periodic burst transmission, the first periodic burst transmission corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets, buffer at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window, and output the one or more PDU sets upon expiration of the first duration and prior to the first delivery deadline.

[0009] Some examples of the method, ASs, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for obtaining control signaling including assistance information associated with the UE, the assistance information indicating the first delivery deadline, a periodicity associated with the first periodic burst transmission, the jitter window, the first duration, or any combination thereof, where buffering at least the portion of the one or more PDU sets may be in accordance with the assistance information.

[0010] Some examples of the method, ASs, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for outputting a time sensitive communication (TSC) message including an indication of the jitter window based on generating the one or more PDU sets of the first periodic burst transmission. In some examples of the method, ASs, and non-transitory computer-readable medium described herein, buffering the portion of the one or more PDU sets may include operations, features, means, or instructions for starting a timer in response to generating the one or more PDU sets, the timer being set to the first duration, where buffering the portion of the one or more PDU sets may be based on starting the timer, and where outputting the one or more PDU sets may be based on expiration of the timer.

[0011] In some examples of the method, ASs, and non-transitory computer-readable medium described herein, buffering the portion of the one or more PDU sets may include operations, features, means, or instructions for identifying a start time associated with the one or more PDU sets in response to generating the one or more PDU sets and delaying the portion of the one or more PDU sets from the identified start time for the first duration, where outputting the one or more PDU sets may be based on the expiration of the first duration.

[0012] Some examples of the method, ASs, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for measuring a second jitter window associated with communication of a second periodic burst transmission, the second periodic burst transmission being prior to the first periodic burst transmission and estimating the jitter window associated with the first periodic burst transmission based on the second jitter window.

[0013] Some examples of the method, ASs, and non-transitory computer-readable medium

described herein may further include operations, features, means, or instructions for storing the second jitter window based on measuring the second jitter window, where estimating the jitter window may be based on the storing.

[0014] In some examples of the method, ASs, and non-transitory computer-readable medium described herein, the second jitter window may be stored according to an extended reality (XR) configuration in a memory of the AS.

[0015] Some examples of the method, ASs, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for measuring a respective jitter window associated with communication of one or more additional periodic burst transmissions, the one or more additional periodic burst transmissions being prior to the first periodic burst transmission and after the second periodic burst transmission and updating the second jitter window stored in the AS based on measuring the respective jitter windows of each of the one or more additional periodic burst transmissions, where estimating the jitter window may be based on updating the second jitter window.

[0016] In some examples of the method, ASs, and non-transitory computer-readable medium described herein, the second jitter window may be based on an operating condition of the AS, a data rate of the second periodic burst transmission, a periodicity of the second periodic burst transmission, or a combination thereof.

[0017] Some examples of the method, ASs, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for measuring a duration associated with generating the one or more PDU sets of the first periodic burst transmission and estimating the jitter window based on the duration associated with generating the one or more PDU sets.

[0018] Some examples of the method, ASs, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for estimating the jitter window using the duration may be based on the duration being less than a threshold duration.

[0019] In some examples of the method, ASs, and non-transitory computer-readable medium described herein, the duration associated with generating the one or more PDU sets of the first periodic burst transmission may be based on a data rate associated with the first periodic burst transmission, a periodicity of the first periodic burst transmission, or a combination thereof.

[0020] Some examples of the method, ASs, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for identifying a second jitter window associated with a second periodic burst transmission, the second periodic burst transmission being prior to the first periodic burst transmission, measuring a duration associated with generating the one or more PDU sets of the first periodic burst transmission, and estimating the jitter window based on the duration associated with generating the one or more PDU sets and the second jitter window associated with the second periodic burst transmission.

[0021] In some examples of the method, ASs, and non-transitory computer-readable medium described herein, generating the one or more PDU sets may include operations, features, means, or instructions for rendering at least a portion of a video frame associated with XR communications, encoding, based on the rendering, the portion of the video frame, and packetizing, based on the encoding, the portion of the video frame to obtain the one or more PDU sets of the first periodic burst transmission.

[0022] In some examples of the method, ASs, and non-transitory computer-readable medium described herein, the first arrival time may be an average arrival time measured across one or more periodic burst transmissions, the one or more periodic burst transmissions occurring prior to the first periodic burst transmission.

[0023] A method for wireless communications by a radio access network (RAN) is described. The method may include obtaining a TSC message indicating a jitter window associated with one or more PDU sets of a first periodic burst transmission, where the jitter window spans a time period

prior to and after a first arrival time associated with the one or more PDU sets, and where the one or more PDU sets of the first periodic burst transmission correspond to a first delivery deadline at a UE, obtaining at least a portion of the one or more PDU sets of the first periodic burst transmission at a first time, where the first time corresponds to at least a threshold percentage of the jitter window, and outputting the one or more PDU sets prior to the first delivery deadline.

[0024] A RAN for wireless communications is described. The RAN may include one or more memories storing processor executable code, and one or more processors coupled with the one or more memories. The one or more processors may individually or collectively be operable to execute the code to cause the RAN to obtain a TSC message indicating a jitter window associated with one or more PDU sets of a first periodic burst transmission, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets, and where the one or more PDU sets of the first periodic burst transmission correspond to a first delivery deadline at a UE, obtain at least a portion of the one or more PDU sets of the first periodic burst transmission at a first time, where the first time corresponds to at least a threshold percentage of the jitter window, and output the one or more PDU sets prior to the first delivery deadline.

[0025] Another RAN for wireless communications is described. The RAN may include means for obtaining a TSC message indicating a jitter window associated with one or more PDU sets of a first periodic burst transmission, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets, and where the one or more PDU sets of the first periodic burst transmission correspond to a first delivery deadline at a UE, means for obtaining at least a portion of the one or more PDU sets of the first periodic burst transmission at a first time, where the first time corresponds to at least a threshold percentage of the jitter window, and means for outputting the one or more PDU sets prior to the first delivery deadline.

[0026] A non-transitory computer-readable medium storing code for wireless communications is described. The code may include instructions executable by one or more processors to obtain a TSC message indicating a jitter window associated with one or more PDU sets of a first periodic burst transmission, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets, and where the one or more PDU sets of the first periodic burst transmission correspond to a first delivery deadline at a UE, obtain at least a portion of the one or more PDU sets of the first periodic burst transmission at a first time, where the first time corresponds to at least a threshold percentage of the jitter window, and output the one or more PDU sets prior to the first delivery deadline.

[0027] Some examples of the method, RANs, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for outputting control signaling indicating one or more parameters corresponding to a discontinuous reception (DRX) cycle associated with the UE based on the jitter window, where the one or more parameters include an offset and an on-duration.

[0028] In some examples of the method, RANs, and non-transitory computer-readable medium described herein, the offset may be based on the jitter window, a remaining jitter, a jitter associated with communications between the RAN and a user plane function (UPF), a first margin, or a combination thereof, the remaining jitter corresponding to a difference between the jitter window and the threshold percentage of the jitter window and the on-duration may be based on the remaining jitter, the jitter associated with the communications between the RAN and the UPF, a second margin, or a combination thereof.

[0029] In some examples of the method, RANs, and non-transitory computer-readable medium described herein, the TSC message further indicates the remaining jitter, the jitter associated with the communications between the RAN and the UPF, or both.

[0030] Some examples of the method, RANs, and non-transitory computer-readable medium described herein may further include operations, features, means, or instructions for measuring the remaining jitter, the jitter associated with the communications between the RAN and the UPF, or

both, where the DRX cycle may be based on the measuring.

[0031] A method for wireless communications by a UPF is described. The method may include obtaining one or more PDU sets of a first periodic burst transmission, the first periodic burst corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets, buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window, and outputting the one or more PDU sets upon based on expiration of the first duration and prior to the first delivery deadline.

[0032] A UPF for wireless communications is described. The UPF may include one or more memories storing processor executable code, and one or more processors coupled with the one or more memories. The one or more processors may individually or collectively be operable to execute the code to cause the UPF to obtain one or more PDU sets of a first periodic burst transmission, the first periodic burst corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets, buffer at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window, and output the one or more PDU sets upon based on expiration of the first duration and prior to the first delivery deadline.

[0033] Another UPF for wireless communications is described. The UPF may include means for obtaining one or more PDU sets of a first periodic burst transmission, the first periodic burst corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets, means for buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window, and means for outputting the one or more PDU sets upon based on expiration of the first duration and prior to the first delivery deadline.

[0034] A non-transitory computer-readable medium storing code for wireless communications is described. The code may include instructions executable by one or more processors to obtain one or more PDU sets of a first periodic burst transmission, the first periodic burst corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets, buffer at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window, and output the one or more PDU sets upon based on expiration of the first duration and prior to the first delivery deadline.

[0035] A method for wireless communications by a RAN is described. The method may include obtaining one or more PDU sets of a first periodic burst transmission, the first periodic burst corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets, buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window, and outputting the one or more PDU sets upon based on expiration of the first duration and prior to the first delivery deadline.

[0036] A RAN for wireless communications is described. The RAN may include one or more memories storing processor executable code, and one or more processors coupled with the one or more memories. The one or more processors may individually or collectively be operable to execute the code to cause the RAN to obtain one or more PDU sets of a first periodic burst transmission, the first periodic burst corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets, buffer at least a portion of the one or more PDU sets for

a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window, and output the one or more PDU sets upon based on expiration of the first duration and prior to the first delivery deadline.

[0037] Another RAN for wireless communications is described. The RAN may include means for obtaining one or more PDU sets of a first periodic burst transmission, the first periodic burst corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets, means for buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window, and means for outputting the one or more PDU sets upon based on expiration of the first duration and prior to the first delivery deadline.

[0038] A non-transitory computer-readable medium storing code for wireless communications is described. The code may include instructions executable by one or more processors to obtain one or more PDU sets of a first periodic burst transmission, the first periodic burst corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets, buffer at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window, and output the one or more PDU sets upon based on expiration of the first duration and prior to the first delivery deadline.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0039] FIG. 1 shows an example of a wireless communications system that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure.

[0040] FIG. 2 shows an example of a wireless communications system that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure.

[0041] FIG. 3 shows an example of a communications timeline that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure.

[0042] FIG. 4 shows an example of a communications timeline that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure.

[0043] FIG. 5 shows an example of a process flow that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure.

[0044] FIG. 6A shows an example of a buffering diagram that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure.

[0045] FIG. 6B shows an example of a buffering diagram that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure.

[0046] FIG. 7 shows an example of a process flow that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure.

[0047] FIG. 8 shows an example of a process flow that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure.

[0048] FIGS. 9 and 10 show block diagrams of devices that support mitigating jitter in communications in accordance with one or more aspects of the present disclosure.

[0049] FIG. 11 shows a block diagram of a communications manager that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure.

[0050] FIG. 12 shows a diagram of a system including a device that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure.

[0051] FIGS. 13 through 18 show flowcharts illustrating methods that support mitigating jitter in communications in accordance with one or more aspects of the present disclosure.

DETAILED DESCRIPTION

[0052] In some wireless communications systems, a user equipment (UE) may support extended reality (XR) communications, where, while operating an XR application, the UE may communicate with an application server (AS) of a network. For example, the AS may generate (e.g., render, encode, and packetize an XR frame) a periodic burst transmission (e.g., one or more packet data unit (PDU) sets) associated with the XR application at the UE. Accordingly, in response to generating the periodic burst transmission, the AS may transmit the periodic burst transmission to a user plane function (UPF) of the network, where the UPF may proceed to forward the periodic burst transmission to a radio access network (RAN) that is serving the UE. Based on receiving the periodic burst transmission, the RAN may forward the periodic burst transmission to the UE.

[0053] In some cases, the communication flow between the UE and the AS (e.g., AS to UPF to RAN to UE) may be associated with a jitter window (e.g., a time period during which a periodic burst transmission may arrive), where the jitter window may span a time period prior to and after an average arrival time associated with periodic burst transmissions across the communication flow (e.g., a minimum time period from the average arrival time and a maximum time period from the average arrival time). In such cases, however, if the jitter window spans a relatively large time period, the UE may operate in a connected mode (e.g., on mode) for an increased amount of time, thereby reducing power savings at the UE. Thus, techniques may be desired to reduce the effects of jitter during communications.

[0054] According to the techniques described herein, the AS may buffer (e.g., delay) a portion of the periodic burst transmission (e.g., one or more PDU sets) for a threshold percentage of the jitter window in order to mitigate the effects of the jitter during the communications, thereby enabling the UE to reduce the quantity of time operating in the connected mode and resulting in power savings at the UE. For example, the AS may generate one or more PDU sets of a first periodic burst transmission, where the first periodic burst transmission may be associated with a first delivery deadline at the UE during a jitter window. Accordingly, in some examples, the AS may buffer at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage (e.g., 90%, 99%, 100%) of the jitter window. That is, the AS may delay at least a portion of the one or more PDU sets (e.g., one or more PDU sets generated prior to a threshold time) such that the arrival time of the first periodic burst transmission may be deterministic.

[0055] In response to buffering the portion of the one or more PDU sets, the AS may output the one or more PDU sets to the UPF, where the UPF may forward the one or more PDU sets to the RAN. In such examples, the RAN may configure the UE with a discontinuous reception (DRX) cycle that includes an on-duration and an offset that is based on the jitter window and the buffering of the first periodic transmission. In such examples, the DRX cycle may include a relatively smaller on-duration, thereby enabling the UE to save power. In some cases, the UPF or RAN may buffer (e.g., delay) a portion of the periodic burst transmission (e.g., one or more PDU sets) for a threshold percentage of the jitter window in order to mitigate the effects of the jitter during the communications, thereby enabling the UE to reduce the quantity of time operating in the connected mode and resulting in power savings at the UE.

[0056] Aspects of the disclosure are initially described in the context of wireless communications systems. Additional aspects of the disclosure are described in the context of communications timelines, process flows, and block diagrams. Aspects of the disclosure are further illustrated by and described with reference to apparatus diagrams, system diagrams, and flowcharts that relate to mitigating jitter in communications.

[0057] FIG. 1 shows an example of a wireless communications system **100** that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure. The wireless communications system **100** may include one or more devices, such as one or more network devices (e.g., network entities **105**), one or more UEs **115**, and a core network **130**. In

some examples, the wireless communications system **100** may be a Long Term Evolution (LTE) network, an LTE-Advanced (LTE-A) network, an LTE-A Pro network, a New Radio (NR) network, or a network operating in accordance with other systems and radio technologies, including future systems and radio technologies not explicitly mentioned herein.

[0058] The network entities **105** may be dispersed throughout a geographic area to form the wireless communications system **100** and may include devices in different forms or having different capabilities. In various examples, a network entity **105** may be referred to as a network element, a mobility element, a RAN node, or network equipment, among other nomenclature. In some examples, network entities **105** and UEs **115** may wirelessly communicate via communication link(s) **125** (e.g., a radio frequency (RF) access link). For example, a network entity **105** may support a coverage area **110** (e.g., a geographic coverage area) over which the UEs **115** and the network entity **105** may establish the communication link(s) **125**. The coverage area **110** may be an example of a geographic area over which a network entity **105** and a UE **115** may support the communication of signals according to one or more radio access technologies (RATs).

[0059] The UEs **115** may be dispersed throughout a coverage area **110** of the wireless communications system **100**, and each UE **115** may be stationary, or mobile, or both at different times. The UEs **115** may be devices in different forms or having different capabilities. Some example UEs **115** are illustrated in FIG. 1. The UEs **115** described herein may be capable of supporting communications with various types of devices in the wireless communications system **100** (e.g., other wireless communication devices, including UEs **115** or network entities **105**), as shown in FIG. 1.

[0060] As described herein, a node of the wireless communications system **100**, which may be referred to as a network node, or a wireless node, may be a network entity **105** (e.g., any network entity described herein), a UE **115** (e.g., any UE described herein), a network controller, an apparatus, a device, a computing system, one or more components, or another suitable processing entity configured to perform any of the techniques described herein. For example, a node may be a UE **115**. As another example, a node may be a network entity **105**. As another example, a first node may be configured to communicate with a second node or a third node. In one aspect of this example, the first node may be a UE **115**, the second node may be a network entity **105**, and the third node may be a UE **115**. In another aspect of this example, the first node may be a UE **115**, the second node may be a network entity **105**, and the third node may be a network entity **105**. In yet other aspects of this example, the first, second, and third nodes may be different relative to these examples. Similarly, reference to a UE **115**, network entity **105**, apparatus, device, computing system, or the like may include disclosure of the UE **115**, network entity **105**, apparatus, device, computing system, or the like being a node. For example, disclosure that a UE **115** is configured to receive information from a network entity **105** also discloses that a first node is configured to receive information from a second node.

[0061] In some examples, network entities **105** may communicate with a core network **130**, or with one another, or both. For example, network entities **105** may communicate with the core network **130** via backhaul communication link(s) **120** (e.g., in accordance with an S1, N2, N3, or other interface protocol). In some examples, network entities **105** may communicate with one another via backhaul communication link(s) **120** (e.g., in accordance with an X2, Xn, or other interface protocol) either directly (e.g., directly between network entities **105**) or indirectly (e.g., via the core network **130**). In some examples, network entities **105** may communicate with one another via a midhaul communication link **162** (e.g., in accordance with a midhaul interface protocol) or a fronthaul communication link **168** (e.g., in accordance with a fronthaul interface protocol), or any combination thereof. The backhaul communication link(s) **120**, midhaul communication links **162**, or fronthaul communication links **168** may be or include one or more wired links (e.g., an electrical link, an optical fiber link) or one or more wireless links (e.g., a radio link, a wireless optical link), among other examples or various combinations thereof. A UE **115** may communicate with the core

network **130** via a communication link **155**.

[0062] One or more of the network entities **105** or network equipment described herein may include or may be referred to as a base station **140** (e.g., a base transceiver station, a radio base station, an NR base station, an access point, a radio transceiver, a NodeB, an eNodeB (eNB), a next-generation NodeB or giga-NodeB (either of which may be referred to as a gNB), a 5G NB, a next-generation eNB (ng-eNB), a Home NodeB, a Home eNodeB, or other suitable terminology). In some examples, a network entity **105** (e.g., a base station **140**) may be implemented in an aggregated (e.g., monolithic, standalone) base station architecture, which may be configured to utilize a protocol stack that is physically or logically integrated within one network entity (e.g., a network entity **105** or a single RAN node, such as a base station **140**).

[0063] In some examples, a network entity **105** may be implemented in a disaggregated architecture (e.g., a disaggregated base station architecture, a disaggregated RAN architecture), which may be configured to utilize a protocol stack that is physically or logically distributed among multiple network entities (e.g., network entities **105**), such as an integrated access and backhaul (IAB) network, an open RAN (O-RAN) (e.g., a network configuration sponsored by the O-RAN Alliance), or a virtualized RAN (vRAN) (e.g., a cloud RAN (C-RAN)). For example, a network entity **105** may include one or more of a central unit (CU), such as a CU **160**, a distributed unit (DU), such as a DU **165**, a radio unit (RU), such as an RU **170**, a RAN Intelligent Controller (RIC), such as an RIC **175** (e.g., a Near-Real Time RIC (Near-RT RIC), a Non-Real Time RIC (Non-RT RIC)), a Service Management and Orchestration (SMO) system, such as an SMO system **180**, or any combination thereof. An RU **170** may also be referred to as a radio head, a smart radio head, a remote radio head (RRH), a remote radio unit (RRU), or a transmission reception point (TRP). One or more components of the network entities **105** in a disaggregated RAN architecture may be co-located, or one or more components of the network entities **105** may be located in distributed locations (e.g., separate physical locations). In some examples, one or more of the network entities **105** of a disaggregated RAN architecture may be implemented as virtual units (e.g., a virtual CU (VCU), a virtual DU (VDU), a virtual RU (VRU)).

[0064] The split of functionality between a CU **160**, a DU **165**, and an RU **170** is flexible and may support different functionalities depending on which functions (e.g., network layer functions, protocol layer functions, baseband functions, RF functions, or any combinations thereof) are performed at a CU **160**, a DU **165**, or an RU **170**. For example, a functional split of a protocol stack may be employed between a CU **160** and a DU **165** such that the CU **160** may support one or more layers of the protocol stack and the DU **165** may support one or more different layers of the protocol stack. In some examples, the CU **160** may host upper protocol layer (e.g., layer 3 (L3), layer 2 (L2)) functionality and signaling (e.g., Radio Resource Control (RRC), service data adaptation protocol (SDAP), Packet Data Convergence Protocol (PDCP)). The CU **160** (e.g., one or more CUs) may be connected to a DU **165** (e.g., one or more DUs) or an RU **170** (e.g., one or more RUs), or some combination thereof, and the DUs **165**, RUs **170**, or both may host lower protocol layers, such as layer 1 (L1) (e.g., physical (PHY) layer) or L2 (e.g., radio link control (RLC) layer, medium access control (MAC) layer) functionality and signaling, and may each be at least partially controlled by the CU **160**. Additionally, or alternatively, a functional split of the protocol stack may be employed between a DU **165** and an RU **170** such that the DU **165** may support one or more layers of the protocol stack and the RU **170** may support one or more different layers of the protocol stack. The DU **165** may support one or multiple different cells (e.g., via one or multiple different RUs, such as an RU **170**). In some cases, a functional split between a CU **160** and a DU **165** or between a DU **165** and an RU **170** may be within a protocol layer (e.g., some functions for a protocol layer may be performed by one of a CU **160**, a DU **165**, or an RU **170**, while other functions of the protocol layer are performed by a different one of the CU **160**, the DU **165**, or the RU **170**). A CU **160** may be functionally split further into CU control plane (CU-CP) and CU user plane (CU-UP) functions. A CU **160** may be connected to a DU **165** via a midhaul communication

link **162** (e.g., F1, F1-c, F1-u), and a DU **165** may be connected to an RU **170** via a fronthaul communication link **168** (e.g., open fronthaul (FH) interface). In some examples, a midhaul communication link **162** or a fronthaul communication link **168** may be implemented in accordance with an interface (e.g., a channel) between layers of a protocol stack supported by respective network entities (e.g., one or more of the network entities **105**) that are in communication via such communication links.

[0065] In some wireless communications systems (e.g., the wireless communications system **100**), infrastructure and spectral resources for radio access may support wireless backhaul link capabilities to supplement wired backhaul connections, providing an IAB network architecture (e.g., to a core network **130**). In some cases, in an IAB network, one or more of the network entities **105** (e.g., network entities **105** or IAB node(s) **104**) may be partially controlled by each other. The IAB node(s) **104** may be referred to as a donor entity or an IAB donor. A DU **165** or an RU **170** may be partially controlled by a CU **160** associated with a network entity **105** or base station **140** (such as a donor network entity or a donor base station). The one or more donor entities (e.g., IAB donors) may be in communication with one or more additional devices (e.g., IAB node(s) **104**) via supported access and backhaul links (e.g., backhaul communication link(s) **120**). IAB node(s) **104** may include an IAB mobile termination (IAB-MT) controlled (e.g., scheduled) by one or more DUs (e.g., DUs **165**) of a coupled IAB donor. An IAB-MT may be equipped with an independent set of antennas for relay of communications with UEs **115** or may share the same antennas (e.g., of an RU **170**) of IAB node(s) **104** used for access via the DU **165** of the IAB node(s) **104** (e.g., referred to as virtual IAB-MT (vIAB-MT)). In some examples, the IAB node(s) **104** may include one or more DUs (e.g., DUs **165**) that support communication links with additional entities (e.g., IAB node(s) **104**, UEs **115**) within the relay chain or configuration of the access network (e.g., downstream). In such cases, one or more components of the disaggregated RAN architecture (e.g., the IAB node(s) **104** or components of the IAB node(s) **104**) may be configured to operate according to the techniques described herein.

[0066] In the case of the techniques described herein applied in the context of a disaggregated RAN architecture, one or more components of the disaggregated RAN architecture may be configured to support test as described herein. For example, some operations described as being performed by a UE **115** or a network entity **105** (e.g., a base station **140**) may additionally, or alternatively, be performed by one or more components of the disaggregated RAN architecture (e.g., components such as an IAB node, a DU **165**, a CU **160**, an RU **170**, an RIC **175**, an SMO system **180**).

[0067] A UE **115** may include or may be referred to as a mobile device, a wireless device, a remote device, a handheld device, or a subscriber device, or some other suitable terminology, where the “device” may also be referred to as a unit, a station, a terminal, or a client, among other examples. A UE **115** may also include or may be referred to as a personal electronic device such as a cellular phone, a personal digital assistant (PDA), a tablet computer, a laptop computer, or a personal computer. In some examples, a UE **115** may include or be referred to as a wireless local loop (WLL) station, an Internet of Things (IoT) device, an Internet of Everything (IoE) device, or a machine type communications (MTC) device, among other examples, which may be implemented in various objects such as appliances, vehicles, or meters, among other examples.

[0068] The UEs **115** described herein may be able to communicate with various types of devices, such as UEs **115** that may sometimes operate as relays, as well as the network entities **105** and the network equipment including macro eNBs or gNBs, small cell eNBs or gNBs, or relay base stations, among other examples, as shown in FIG. 1.

[0069] The UEs **115** and the network entities **105** may wirelessly communicate with one another via the communication link(s) **125** (e.g., one or more access links) using resources associated with one or more carriers. The term “carrier” may refer to a set of RF spectrum resources having a defined PHY layer structure for supporting the communication link(s) **125**. For example, a carrier used for the communication link(s) **125** may include a portion of an RF spectrum band (e.g., a

bandwidth part (BWP)) that is operated according to one or more PHY layer channels for a given RAT (e.g., LTE, LTE-A, LTE-A Pro, NR). Each PHY layer channel may carry acquisition signaling (e.g., synchronization signals, system information), control signaling that coordinates operation for the carrier, user data, or other signaling. The wireless communications system **100** may support communication with a UE **115** using carrier aggregation or multi-carrier operation. A UE **115** may be configured with multiple downlink component carriers and one or more uplink component carriers according to a carrier aggregation configuration. Carrier aggregation may be used with both frequency division duplexing (FDD) and time division duplexing (TDD) component carriers. Communication between a network entity **105** and other devices may refer to communication between the devices and any portion (e.g., entity, sub-entity) of a network entity **105**. For example, the terms “transmitting,” “receiving,” or “communicating,” when referring to a network entity **105**, may refer to any portion of a network entity **105** (e.g., a base station **140**, a CU **160**, a DU **165**, a RU **170**) of a RAN communicating with another device (e.g., directly or via one or more other network entities, such as one or more of the network entities **105**).

[0070] Signal waveforms transmitted via a carrier may be made up of multiple subcarriers (e.g., using multi-carrier modulation (MCM) techniques such as orthogonal frequency division multiplexing (OFDM) or discrete Fourier transform spread OFDM (DFT-S-OFDM)). In a system employing MCM techniques, a resource element may refer to resources of one symbol period (e.g., a duration of one modulation symbol) and one subcarrier, in which case the symbol period and subcarrier spacing may be inversely related. The quantity of bits carried by each resource element may depend on the modulation scheme (e.g., the order of the modulation scheme, the coding rate of the modulation scheme, or both), such that a relatively higher quantity of resource elements (e.g., in a transmission duration) and a relatively higher order of a modulation scheme may correspond to a relatively higher rate of communication. A wireless communications resource may refer to a combination of an RF spectrum resource, a time resource, and a spatial resource (e.g., a spatial layer, a beam), and the use of multiple spatial resources may increase the data rate or data integrity for communications with a UE **115**.

[0071] The time intervals for the network entities **105** or the UEs **115** may be expressed in multiples of a basic time unit which may, for example, refer to a sampling period of $T_{\text{sub.s}} = 1/(\Delta f_{\text{sub.max}} \cdot N_{\text{sub.f}})$ seconds, for which $\Delta f_{\text{sub.max}}$ may represent a supported subcarrier spacing, and $N_{\text{sub.f}}$ may represent a supported discrete Fourier transform (DFT) size. Time intervals of a communications resource may be organized according to radio frames each having a specified duration (e.g., 10 milliseconds (ms)). Each radio frame may be identified by a system frame number (SFN) (e.g., ranging from 0 to 1023).

[0072] Each frame may include multiple consecutively-numbered subframes or slots, and each subframe or slot may have the same duration. In some examples, a frame may be divided (e.g., in the time domain) into subframes, and each subframe may be further divided into a quantity of slots. Alternatively, each frame may include a variable quantity of slots, and the quantity of slots may depend on subcarrier spacing. Each slot may include a quantity of symbol periods (e.g., depending on the length of the cyclic prefix prepended to each symbol period). In some wireless communications systems, such as the wireless communications system **100**, a slot may further be divided into multiple mini-slots associated with one or more symbols. Excluding the cyclic prefix, each symbol period may be associated with one or more (e.g., $N_{\text{sub.f}}$) sampling periods. The duration of a symbol period may depend on the subcarrier spacing or frequency band of operation.

[0073] A subframe, a slot, a mini-slot, or a symbol may be the smallest scheduling unit (e.g., in the time domain) of the wireless communications system **100** and may be referred to as a transmission time interval (TTI). In some examples, the TTI duration (e.g., a quantity of symbol periods in a TTI) may be variable. Additionally, or alternatively, the smallest scheduling unit of the wireless communications system **100** may be dynamically selected (e.g., in bursts of shortened TTIs (sTTIs)).

[0074] Physical channels may be multiplexed for communication using a carrier according to various techniques. A physical control channel and a physical data channel may be multiplexed for signaling via a downlink carrier, for example, using one or more of time division multiplexing (TDM) techniques, frequency division multiplexing (FDM) techniques, or hybrid TDM-FDM techniques. A control region (e.g., a control resource set (CORESET)) for a physical control channel may be defined by a set of symbol periods and may extend across the system bandwidth or a subset of the system bandwidth of the carrier. One or more control regions (e.g., CORESETs) may be configured for a set of the UEs **115**. For example, one or more of the UEs **115** may monitor or search control regions for control information according to one or more search space sets, and each search space set may include one or multiple control channel candidates in one or more aggregation levels arranged in a cascaded manner. An aggregation level for a control channel candidate may refer to an amount of control channel resources (e.g., control channel elements (CCEs)) associated with encoded information for a control information format having a given payload size. Search space sets may include common search space sets configured for sending control information to UEs **115** (e.g., one or more UEs) or may include UE-specific search space sets for sending control information to a UE **115** (e.g., a specific UE).

[0075] In some examples, a network entity **105** (e.g., a base station **140**, an RU **170**) may be movable and therefore provide communication coverage for a moving coverage area, such as the coverage area **110**. In some examples, coverage areas **110** (e.g., different coverage areas) associated with different technologies may overlap, but the coverage areas **110** (e.g., different coverage areas) may be supported by the same network entity (e.g., a network entity **105**). In some other examples, overlapping coverage areas, such as a coverage area **110**, associated with different technologies may be supported by different network entities (e.g., the network entities **105**). The wireless communications system **100** may include, for example, a heterogeneous network in which different types of the network entities **105** support communications for coverage areas **110** (e.g., different coverage areas) using the same or different RATs.

[0076] The wireless communications system **100** may be configured to support ultra-reliable communications or low-latency communications, or various combinations thereof. For example, the wireless communications system **100** may be configured to support ultra-reliable low-latency communications (URLLC). The UEs **115** may be designed to support ultra-reliable, low-latency, or critical functions. Ultra-reliable communications may include private communication or group communication and may be supported by one or more services such as push-to-talk, video, or data. Support for ultra-reliable, low-latency functions may include prioritization of services, and such services may be used for public safety or general commercial applications. The terms ultra-reliable, low-latency, and ultra-reliable low-latency may be used interchangeably herein.

[0077] In some examples, a UE **115** may be configured to support communicating directly with other UEs (e.g., one or more of the UEs **115**) via a device-to-device (D2D) communication link, such as a D2D communication link **135** (e.g., in accordance with a peer-to-peer (P2P), D2D, or sidelink protocol). In some examples, one or more UEs **115** of a group that are performing D2D communications may be within the coverage area **110** of a network entity **105** (e.g., a base station **140**, an RU **170**), which may support aspects of such D2D communications being configured by (e.g., scheduled by) the network entity **105**. In some examples, one or more UEs **115** of such a group may be outside the coverage area **110** of a network entity **105** or may be otherwise unable to or not configured to receive transmissions from a network entity **105**. In some examples, groups of the UEs **115** communicating via D2D communications may support a one-to-many (1:M) system in which each UE **115** transmits to one or more of the UEs **115** in the group. In some examples, a network entity **105** may facilitate the scheduling of resources for D2D communications. In some other examples, D2D communications may be carried out between the UEs **115** without an involvement of a network entity **105**.

[0078] The core network **130** may provide user authentication, access authorization, tracking,

Internet Protocol (IP) connectivity, and other access, routing, or mobility functions. The core network **130** may be an evolved packet core (EPC) or 5G core (5GC), which may include at least one control plane entity that manages access and mobility (e.g., a mobility management entity (MME), an access and mobility management function (AMF)) and at least one user plane entity that routes packets or interconnects to external networks (e.g., a serving gateway (S-GW), a Packet Data Network (PDN) gateway (P-GW), or a UPF). The control plane entity may manage non-access stratum (NAS) functions such as mobility, authentication, and bearer management for the UEs **115** served by the network entities **105** (e.g., base stations **140**) associated with the core network **130**. User IP packets may be transferred through the user plane entity, which may provide IP address allocation as well as other functions. The user plane entity may be connected to IP services **150** for one or more network operators. The IP services **150** may include access to the Internet, Intranet(s), an IP Multimedia Subsystem (IMS), or a Packet-Switched Streaming Service. [0079] The wireless communications system **100** may operate using one or more frequency bands, which may be in the range of 300 megahertz (MHz) to 300 gigahertz (GHz). Generally, the region from 300 MHz to 3 GHz is known as the ultra-high frequency (UHF) region or decimeter band because the wavelengths range from approximately one decimeter to one meter in length. UHF waves may be blocked or redirected by buildings and environmental features, which may be referred to as clusters, but the waves may penetrate structures sufficiently for a macro cell to provide service to the UEs **115** located indoors. Communications using UHF waves may be associated with smaller antennas and shorter ranges (e.g., less than one hundred kilometers) compared to communications using the smaller frequencies and longer waves of the high frequency (HF) or very high frequency (VHF) portion of the spectrum below 300 MHz.

[0080] The wireless communications system **100** may utilize both licensed and unlicensed RF spectrum bands. For example, the wireless communications system **100** may employ License Assisted Access (LAA), LTE-Unlicensed (LTE-U) RAT, or NR technology using an unlicensed band such as the 5 GHz industrial, scientific, and medical (ISM) band. While operating using unlicensed RF spectrum bands, devices such as the network entities **105** and the UEs **115** may employ carrier sensing for collision detection and avoidance. In some examples, operations using unlicensed bands may be based on a carrier aggregation configuration in conjunction with component carriers operating using a licensed band (e.g., LAA). Operations using unlicensed spectrum may include downlink transmissions, uplink transmissions, P2P transmissions, or D2D transmissions, among other examples.

[0081] A network entity **105** (e.g., a base station **140**, an RU **170**) or a UE **115** may be equipped with multiple antennas, which may be used to employ techniques such as transmit diversity, receive diversity, multiple-input multiple-output (MIMO) communications, or beamforming. The antennas of a network entity **105** or a UE **115** may be located within one or more antenna arrays or antenna panels, which may support MIMO operations or transmit or receive beamforming. For example, one or more base station antennas or antenna arrays may be co-located at an antenna assembly, such as an antenna tower. In some examples, antennas or antenna arrays associated with a network entity **105** may be located at diverse geographic locations. A network entity **105** may include an antenna array with a set of rows and columns of antenna ports that the network entity **105** may use to support beamforming of communications with a UE **115**. Likewise, a UE **115** may include one or more antenna arrays that may support various MIMO or beamforming operations. Additionally, or alternatively, an antenna panel may support RF beamforming for a signal transmitted via an antenna port.

[0082] Beamforming, which may also be referred to as spatial filtering, directional transmission, or directional reception, is a signal processing technique that may be used at a transmitting device or a receiving device (e.g., a network entity **105**, a UE **115**) to shape or steer an antenna beam (e.g., a transmit beam, a receive beam) along a spatial path between the transmitting device and the receiving device. Beamforming may be achieved by combining the signals communicated via

antenna elements of an antenna array such that some signals propagating along particular orientations with respect to an antenna array experience constructive interference while others experience destructive interference. The adjustment of signals communicated via the antenna elements may include a transmitting device or a receiving device applying amplitude offsets, phase offsets, or both to signals carried via the antenna elements associated with the device. The adjustments associated with each of the antenna elements may be defined by a beamforming weight set associated with a particular orientation (e.g., with respect to the antenna array of the transmitting device or receiving device, or with respect to some other orientation).

[0083] In some examples of the wireless communications system **100**, the UE **115** may support XR communications, where, during such XR communications, the UE **115** may communicate with an AS. The AS may generate one or more PDU sets of a periodic burst (e.g., a video frame) that is associated with an application at the UE **115** (e.g., an XR application). In communications with XR applications, the jitter window (e.g., burst arrival time (BAT)) at a network (e.g., 5G network) may be quasi-periodic (e.g., periodic with jitter). For example, a communication flow between the UE **115-a** and the AS may be associated with a jitter window, where the jitter window may be a statistical calculation of arrival times of one or more periodic burst transmissions over the communication flow. Accordingly, the jitter window of the communication flow may be associated with a minimum arrival time of a periodic burst (e.g., the earliest time a periodic burst may arrive at the UE **115** over the communication flow), an average arrival time of a periodic burst transmission (e.g., when the average periodic burst may arrive at the UE **115** over the communication flow), and a maximum arrival time of a periodic burst transmission (e.g., the latest time a periodic burst may arrive at the UE **115** over the communication flow).

[0084] Further, the jitter window may be modeled according to a truncated gaussian distribution (e.g., a Gaussian distribution with mean: μ , standard deviation (STD)), where, as an illustrative example, the jitter window may be a range of $[-4, 4]$ milliseconds (ms) (baseline) or $[-5, 5]$ ms (optional) centered around an average arrival time for the periodic burst transmission.

[0085] For XR applications, the jitter window may be relatively large, as compared to other communication flows for other types of data or applications. For example, the range of jitter may use 48% of an XR message periodicity (e.g., jitter=8 ms vs. XR periodicity=16.666 ms (60 frames per second (fps))). As such, the jitter may significantly degrade the 5G system performance, including capacity and power consumption of the UE **115**, and therefore be unable to satisfy one or more quality of service (QoS) metrics of the periodic burst transmissions, such as being unable to satisfy a packet delay budget (PDB) or PDU set delay budget (PSDB) associated with the XR data. As a result, current system performance may suffer from the jitter associated with XR communications, for example, by being unable to configure extended connected mode DRX (eCDRX) modes for the UE **115** (e.g., resulting in a loss of power savings at the UE **115-a**), configure semi persistent scheduling (SPS) or configured grants (CG) (e.g., resulting in increased latency in the wireless communications).

[0086] As described herein, the jitter window associated with downlink XR traffic (e.g., periodic burst transmissions from the AS towards the UE) may be quasi-periodic (e.g., periodic with jitter). In such examples, the source of the jitter may be based on varying periodic burst (e.g., video frame) generation times at the AS. For example, to generate a periodic burst, the AS may render at least a portion of a video frame associated with an XR application at the UE, encode the render portion of the video frame, and perform real-time protocol (RTP) packetization on the encoded portion of the video frame, thereby producing one or more PDU sets that make up a periodic burst transmission. Accordingly, the varying frame generation times at the AS **215** may be based on a render time (e.g., render time may be scene dependent), an encoder time (e.g., encoder time based on complexity of a frame), and an RTP packetization time.

[0087] As such, because XR communications may include jitter, which may degrade communications and increase power consumption at the UE, techniques may be desired to

minimize the performance degradation of the jitter window, thereby enabling the configuration of an eCDRX cycle at the UE **115**, the configuration of SPS and CG scheduling at the UE **115**, or both.

[0088] According to the techniques described herein, a network entity **105**, such as an AS, may buffer (e.g., delay) a portion of a periodic burst transmission (e.g., one or more PDU sets) for a threshold percentage of a jitter window in order to mitigate the effects of the jitter during communications, thereby enabling the UE **115** to reduce the quantity of time operating in the connected mode and resulting in power savings at the UE **115**. For example, the AS may generate one or more PDU sets of a first periodic burst transmission, where the first periodic burst transmission may be associated with a first delivery deadline at the UE **115** during a jitter window. Accordingly, in some examples, the AS may buffer at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage (e.g., 90%, 99%, 100%) of the jitter window. That is, the AS may delay at least a portion of the one or more PDU sets (e.g., one or more PDU sets generated prior to a threshold time) such that the arrival time of the first periodic burst transmission may be deterministic.

[0089] In response to buffering the portion of the one or more PDU sets, the AS may output the one or more PDU sets to the UPF, where the UPF may forward the one or more PDU sets to the RAN. In such examples, the RAN may configure the UE **115** with a DRXD cycle that includes an on-duration and an offset that is based on the jitter window and the buffering of the first periodic transmission. In such examples, the DRX cycle may include a relatively smaller on-duration, thereby enabling the UE **115** to save power.

[0090] FIG. **2** shows an example of a wireless communications system **200** that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure. Aspects of the wireless communications system **200** may implement, or be implemented by, aspects of wireless communications system **100**. For example, the wireless communications system **200** may include a UE **115-a**, which may be an example of a UE **115**, as described with reference to FIG. **1**. The wireless communications system **200** may also include a RAN **202**, which may be an example of a network entity **105**, described with reference to FIG. **1**. The wireless communications system **200** may also include a UPF **205**, a data network (DN) **210**, and an AS **215**, which may be examples of corresponding entities operating in a core network **130**, as described with reference to FIG. **1**. The techniques described in the context of the wireless communications system **200** may enable the AS **215**, the UPF **205**, or the RAN **202** to delay one or more bursts **230** (e.g., periodic burst transmissions), thereby mitigating the effects of jitter during XR communications.

[0091] In some examples, the AS **215** may communicate, to the UE **115-a**, data associated with an XR application operating (e.g., running) at the UE **115-a**. In such examples, the XR application may consume (e.g., transmit or receive) data in one or more PDU sets **235** of a burst **230** (e.g., periodic burst transmission) rather than in singular IP packets **225**. That is, instead of transmitting singular IP packets **225** to the UE **115-a**, the AS **215** may transmit one or more PDU sets **235**, where a PDU set **235** includes a set of IP packets **225** (e.g., one or more IP packets **225**) and represents a unit of information associated with the XR application at the UE **115-a** (e.g., a slice or portion of a video frame, which can be forward error correction (FEC) protected). As described herein, a PDU set **235** may be referred to as an application data unit (ADU). A burst **230** (e.g., a periodic burst transmission) may include a set of PDU sets **235** (e.g., one or more PDU sets **235**), where each of the PDU sets **235** may be associated with a same delivery deadline at the UE **115-a**. In such examples, the burst **230** may carry all slices (e.g., portions) of an XR video frame or one or more slices of the XR video frame. In some examples, the XR application operating at the UE **115-a** may determine the transport layer parameters for the PDU sets **235**. Further, in 5G XR communications, the UE **115-a** and the AS **215** may utilize an enhanced RTP to indicate the metadata associated with each PDU set **235**.

[0092] In some examples, each of the PDU sets **235** may be associated with a QoS parameter, such

as PSDB, where the PSDB may be used in place of a PDB. The PSDB may define an upper bound for a delay that a PDU set **235** may experience for the transfer between the UE **115-a** and the UPF **205** (e.g., the N6 termination point at the UPF **205**). In downlink communications, the PSDB may be counted (e.g., started or valid) when the PDU sets **235** arrive at the UPF **205**. As such, each PDU set **235** within a burst **230** may be associated with a same PSDB or a respective PSDB.

[0093] As an illustrative example, the AS **215** may output, via a communication link **220-d**, one or more bursts **230** to the DN **210**, such as a burst **230-a**, a burst **230-b**, and a burst **230-c**. The burst **230-a** may include a PDU set **235-a** and PDU set **235-b**, where both the PDU set **235-a** and the PDU set **235-b** have a same delivery deadline at the UE **115-a**. The burst **230-b** may include a PDU set **235-c**, a PDU set **235-d**, and a PDU set **235-e**, where the PDU set **235-c**, the PDU set **235-d**, and the PDU set **235-e** have a same delivery deadline at the UE **115-a**. Similarly, the burst **230-c** may include the PDU set **235-f**. As described herein, each PDU set **235** may include one or more IP packets **225**.

[0094] Accordingly, in response to receiving the bursts **230** from the AS **215**, the DN **210** may forward the bursts **230** to the UPF via the communication link **220-c**, which may be referred to as an N6 interface. The UPF **205** may receive the bursts **230** from the DN **210** and proceed to forward the bursts **230** to the RAN **202** via the communication link **220-b**, which may be referred to as an N3 interface. In response to receiving the bursts **230**, the RAN may forward the bursts to the UE **115-a** over the communication link **220-a**, which may be referred to as a Uu interface. In this way, the UE **115-a** may obtain the data associated with the XR application.

[0095] In some examples, the communication flow between the AS **215** and the UE **115-a** may be associated with a jitter window, where the jitter window may be a statistical calculation of arrival times of one or more bursts **230** over the communication flow. Accordingly, the jitter window of the communication flow (e.g., BAT) may be associated with a minimum arrival time of a burst **230** (e.g., the earliest time a burst **230** may arrive at the UE **115-a** over the communication flow), an average arrival time of a burst **230** (e.g., when the average periodic burst may arrive at the UE **115** over the communication flow), and a maximum arrival time of a burst **230** (e.g., the latest time a burst **230** may arrive at the UE **115** over the communication flow).

[0096] The source of the jitter window (e.g., cause of the jitter in the BAT of the bursts **230**) may be based on jitter associated with generation of the bursts **230** at the AS **215** (e.g., rendering, encoding, and packetizing of a video frame), jitter of packet delivery over the communication link **220-c** (e.g., N6 interface), jitter of packet delivery over the communication link **220-b** (e.g., N3 interface), or a combination thereof. In such examples, jitter incurred during generation of the bursts **230** may be relatively larger (e.g., the major source of jitter) than the jitter incurred over the communication link **220-c** and the communication link **220-b**. In some examples, such as in edge computing, the jitter incurred over the communication link **220-c** (e.g., N6 interface) may be negligible due to the bursts **230** being delivered over a private network. Alternatively, for non-edge computing, the jitter incurred over the communication link **220-c** (e.g., N6 interface) may not be negligible due to the bursts **230** being delivered over a public network.

[0097] In some examples, the jitter incurred over the communication link **220-b** (e.g., N3 interface) may be relatively small, as compared to the jitter incurred over the communication link **220-c**, due to the burst **230** being delivered over a private network. In such examples, however, if the jitter window spans a relatively large time period, the UE **115-a** may operate in a connected mode (e.g., on mode) for an increased amount of time, thereby reducing power savings at the UE. Thus, techniques may be desired to reduce the effects of jitter during communications.

[0098] According to techniques described herein, the AS **215**, the UPF **205**, or the RAN **202** may delay delivering at least a portion of the bursts **230** (e.g., delay a portion of the one or more PDU sets **235**) for a first duration, where the first duration correspond to a threshold percentage of the jitter window. In one example, in response to generating the burst **230-a**, the AS **215** may delay the transmission of the burst **230-a** for a duration, where the duration corresponds to a threshold

percentage of the jitter window. Such techniques by the AS **215** may be further described herein with reference to FIG. 5.

[0099] In another example, in response to receiving the burst **230-a** from the DN **210**, the UPF **205** may delay the output of the burst **230-a** for a duration, where the duration corresponds to a threshold percentage of the jitter window. Such techniques by the UPF **205** may be further described herein with reference to FIG. 7. In another example, in response to receiving the burst **230-a** from the UPF **205**, the RAN **202** may delay the output of the burst **230-a** for a duration, where the duration corresponds to a threshold percentage of the jitter window. Such techniques by the UPF **205** may be further described herein with reference to FIG. 8.

[0100] Accordingly, by delaying the bursts **230**, the arrival time of the bursts **230** may become deterministic, such that the RAN **202** may be able to configure an eCDRX cycle based on the deterministic arrival time of the bursts **230**, such that an on-duration of the UE **115-a** may be reduced, thereby saving power at the UE **115-a**. Such techniques to configure the eCDRX cycle may be further described herein with reference to FIG. 4-8. Additionally, by having the arrival time of the bursts **230** be deterministic (e.g., known), the RAN **202** may allocate a single radio resource according to the arrival time of the bursts **230**, thereby reducing the quantity of resources allocated to cover the entire jitter window.

[0101] In some examples, although described in the context of 5G communications systems, the techniques described herein may be applied to other communication technologies, such as Wi-Fi target wake time (TWT) communications. Additionally, the techniques described herein may be implemented by RAN intelligence (e.g., RAN Intelligent Controller (RIC)), where the RIC may identify a jitter window of a communication flow and initiate the techniques described herein according to the identified jitter window and other parameters. Further, the techniques described herein may be applied to multiple users (e.g., one or more UEs **115**), where each UE **115** may have a relatively small jitter range based on buffering of the respective bursts **230**. Accordingly, the relatively small jitter window may reduce the chance of transmission periods overlapping for the UEs **115**.

[0102] Additionally, although described in the context of downlink communications, the techniques described herein may be applied to various other communication flows and types, such as applied to uplink bursts **230** originated from the UE **115**, applied for CG communications, applied for UE assistance information (UAI) uplink traffic patterns, applied for cross-layer application programming interface (API) to provide the related information, or a combination thereof.

[0103] FIG. 3 shows an example of a timing diagram **300** that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure. Aspects of the timing diagram **300** may implement, or be implemented by, aspects of the wireless communications system **100** and the wireless communications system **200**. For example, a UE **115**, a RAN **202**, a UPF **205**, a DN **210**, or an AS **215**, which may be examples of corresponding devices described with reference to FIGS. 1 and 2, may communicate according to the timing diagram **300**.

[0104] The timing diagram **300** may include a timeline corresponding to the arrival times of the bursts **230** at the UPF **205**, where the burst arrival times at the UPF **205** may be shown relative to the eCDRX cycle of the UE **115** and relative to the burst arrival times at the UE **115**. The timing diagram may include an eCDRX cycle at the UE **115**. The eCDRX cycle may include an off duration, where the UE **115** is operating in an idle mode, and an on-duration **330**, where the UE **115** is operating in an active mode. The on and off durations of the eCDRX cycle may be shown relative to the burst arrival time at the UPF **205** and the burst arrival times at the UE **115**. The timing diagram **300** may also include a timeline corresponding to the arrival times of the bursts **230** at the UE **115**, where the burst arrival times at the UE **115** may be shown relative to the eCDRX cycle at the UE **115** and the burst arrival times at the UPF **205**.

[0105] In the example of the timing diagram **300**, a UE **115** may receive bursts **230** from a RAN **202**, where the bursts **230** originated from an AS **215**. In such examples, each burst **230** may be

associated with a respective delivery deadline **305**. For example, a burst **230-a** may be associated with a delivery deadline **305-a**, a burst **230-b** may be associated with a delivery deadline **305-b**, and a burst **230-c** may be associated with a delivery deadline **305-c**. The delivery deadline **305** may represent a time at which an application (e.g., an XR application) at the UE **115** consumes the data included in the respective bursts **230**, otherwise the data included in the bursts **230** becomes invalid. That is, the delivery deadlines **305** may represent the upper-bound time by when a burst **230** should be delivered to meet a playtime time or display refresh time (e.g., delivery deadline=playout time–processing time) at the UE **115**. In such examples, the delivery deadlines **305** may be associated with a same application at the UE **115**, and be periodic since playout time may be periodic (e.g., the display refresh time of the application may be periodic).

[0106] Additionally, as described herein, each burst **230** may be associated with a PSDB **310**, for example, the burst **230-a** may be associated with a PSDB **310-a**, the burst **230-b** may be associated with a PSDB **310-b**, and the burst **230-c** may be associated with a PSDB **310-c**. As illustrated, and described herein, each of the PSDBs **310** may start relative to the arrival times of the bursts **230** at the UPF **205**. That is, the PSDBs **310** may start (e.g., begin or take effect) in response to the arrival of the bursts **230** at the UPF **205**.

[0107] The communication flow between the UE **115** and the AS **215** may be associated with jitter **320**, which may cause a jitter window **315**. The jitter window **315** may span a time period that includes an average arrival time **317** (e.g., average arrival time of the bursts **230** at the UPF **205**), a minimum arrival time **316** (e.g., a minimum arrival time of the bursts **230** at the UPF **205**) from the average arrival time **317**, and an average a maximum arrival time **318** (e.g., a maximum arrival time of the bursts **230** at the UPF **205**) from the average arrival time **317** (one or more of reference numbers **316**, **317**, and **318** may not be shown in FIG. 3 in connection with bursts **230-a**, **230-b**, and **230-c**, depending on context). For example, the jitter windows **315** may be a statistical calculation of the arrival times of one or more bursts **230** over a communication flow between the UE **115** and the AS **215**. In such examples, the jitter window **315** associated with each burst **230** may be relative to the generation time of the bursts **230** at the AS **215**, such that the minimum arrival time **316**, the average arrival time **317**, and the maximum arrival time **318** associated with a respective burst **230** may be identified relative to the start time of the generation of the respective burst **230** at the AS **215**.

[0108] In some examples, the bursts **230** may not be affected by jitter **320**, such that the bursts **230** may arrive at the UPF at the average arrival time **317** and subsequently arrive at the UE **115** prior to the delivery deadline **305** and within the PSDB **310**. For example, the burst **230-a** may arrive at the UPF **205** at a time corresponding to the average arrival time **317**, where the jitter **320-a** may be equal to 0. As such, the UPF **205** may transmit the burst **230-a** to the RAN **202**, where the RAN **202** may forward the burst **230-a** to the UE **115**. Accordingly, the UE **115** may receive the burst **230-a** within the PSDB **310-a** and prior to the delivery deadline **305-a**.

[0109] In some other examples, however, due to the jitter **320** associated with the bursts **230** and to meet the delivery deadlines **305** and PSDBs **310**, the RAN **202** may configure the UE **115** with an eCDRX configuration where an on-duration **330** of the eCDRX configuration may be longer than an off duration of the eCDRX configuration (referred to herein in some instances as an “aggressive eCDRX configuration”). For example, the RAN **202** may set an offset **325** of the eCDRX configuration to be prior to the minimum arrival time **316** and set the on-duration **330** to be greater than the jitter windows **315** associated with the bursts **230**, such that the on-duration **330** extends from before the minimum arrival times **316** to after the maximum arrival times **318** of the jitter windows **315**. As such, with the extended eCDRX configuration, the UE **115** may be awake in order to receive a burst **230-b** arriving prior to the average arrival time **317** (e.g., an early burst **230** associated with jitter **320-b**) or receive a burst **230-c** arriving after the average arrival time **317** (e.g., a later burst **230** associated with jitter **320-c**). Accordingly, due to the aggressive eCDRX configuration, the UE **115** may wake up relatively earlier and stay in an active connected mode for

longer, thereby reducing power savings at the UE 115.

[0110] To reduce the impact of the aggressive eCDRX cycle, the techniques described herein may enable the AS 215, the UPF 205, or the RAN 202 to delay the bursts 230 for a threshold percentage of the jitter window 315. Such techniques may be further described herein with reference to FIGS. 4-8.

[0111] FIG. 4 shows an example of a timing diagram 400 that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure. Aspects of the timing diagram 400 may implement, or be implemented by, aspects of the wireless communications system 100, the wireless communications system 200, and the timing diagram 300. For example, a UE 115, a RAN 202, a UPF 205, a DN 210, or an AS 215, which may be examples of corresponding devices described with reference to FIGS. 1 and 2, may communicate according to the timing diagram 400. The timing diagram 400 may include delivery deadlines 305 (e.g., a delivery deadline 305-a, a delivery deadline 305-b, and a delivery deadline 305-c) and PSDBs 310 (e.g., a PSDB 310-a, a PSDB 310-b, and PSDB 310-c), which may be examples of the delivery deadlines 305 and PSDBs 310, as described herein with reference to FIG. 3. The timing diagram 400 may also include a jitter window 315, a minimum arrival time 316, an average arrival time 317, and a maximum arrival time 318, which may be examples of corresponding times as described herein with reference to FIG. 3.

[0112] The timing diagram 400 may include a timeline corresponding to the arrival times of the bursts 230 at the UPF 205, where the burst arrival times at the UPF 205 may be shown relative to the eCDRX cycle of the UE 115 and relative to the burst arrival times at the UE 115. The timing diagram may include an eCDRX cycle at the UE 115. The eCDRX cycle may include an off duration, where the UE 115 is operating in an idle mode, and an on-duration 330, where the UE 115 is operating in an active mode. The on and off durations of the eCDRX cycle may be shown relative to the burst arrival time at the UPF 205 and the burst arrival times at the UE 115. The timing diagram 300 may also include a timeline corresponding to the arrival times of the bursts 230 at the UE 115, where the burst arrival times at the UE 115 may be shown relative to the eCDRX cycle at the UE 115 and the burst arrival times at the UPF 205.

[0113] In accordance with the techniques described herein, because there is no impact to the XR application at the UE 115 if the burst 230 arrives by the delivery deadlines 305 and because the PSDB 310 starts when the bursts 230 arrive at the UPF 205, the bursts 230 may be buffered by a delay 405, such that the arrival times of the bursts 230 at the UE 115 are deterministic and prior to the delivery deadlines 305. This may enable the RAN 202 to configure a less aggressive eCDRX cycle where the on-duration 330 of the eCDRX configuration does not have to be longer than an off duration of the eCDRX configuration, resulting in power savings at the UE 115. That is, because the arrival time of the bursts 230 at the UE 115 are deterministic, the RAN 202 may set the offset 325 based on the jitter window 315 (e.g., BAT), a remaining jitter (not shown), a margin (not shown), a jitter associated with the N6 interface, or a combination thereof. Additionally, the RAN 202 may set the on-duration 330 of the eCDRX cycle to be a relatively smaller value (e.g., less than the jitter window 315), for example, by setting the on-duration 330 based on the remaining jitter, the margin, the jitter associated with the N6 interface, or a combination thereof.

[0114] As an illustrative example, the burst 230-a may be buffered by a delay 405-a (e.g., a duration), where the delay 405-a may correspond to a first threshold percentage of the jitter window 315 (e.g., 90% of the jitter window). Accordingly, a remaining jitter may be equal to the difference between the jitter window 315 and the delay 405-a (e.g., 10% of the jitter window). As such, the on-duration 330 and offset 325 may be set accordingly, such that the UE 115 may experience power savings.

[0115] As another illustrative example, the burst 230-b may be buffered by a delay 405-b (e.g., a duration), where the delay 405-b corresponds to a second threshold percentage of the jitter window 315 (e.g., 99% of the jitter window). Accordingly, a remaining jitter may be equal to the difference

between the jitter window **315** and the delay **405-b** (e.g., 1% of the jitter window). As such, the on-duration **330** and offset **325** may be set accordingly, such that the UE **115** may experience power savings.

[0116] As another illustrative example, the burst **230-c** may be buffered for a duration that corresponds to a third threshold percentage of the jitter window **315** (e.g., greater than 99% of the jitter window or 100% of the jitter window). Accordingly, a remaining jitter may be equal to less than 1% of the jitter window. That is, there may be no remaining jitter or negligible remaining jitter. As such, the on-duration **330** and offset **325** may be set accordingly, such that the UE **115** may experience power savings.

[0117] In such examples, the bursts **230** may be delayed by an AS **215**, a UPF **205**, or a RAN **202** in accordance with the techniques described herein with reference to FIGS. **5-8**. Additionally, although three illustrative examples of the delay **405-a** are described, it should be understood that the bursts **230** may be delayed by any threshold percentage of the jitter window that results in a deterministic arrival time of the bursts **230**, thereby enabling the RAN **202** to set the offset **325** and the on-duration **330** for the eCDRX cycle accordingly.

[0118] In this way, by buffering the bursts **230** for the delays **405** (e.g., durations corresponding to a threshold percentage of the jitter window **315**), the UE **115** may receive the bursts **230** prior to the delivery deadlines **305** and within the PSDBs **310**, while also experiencing power savings. For example, because the RAN **202** may configure the on-duration **330** and the offset **325** according to jitter window **315**, delay **405**, remaining jitter, margin, or a combination thereof, the on-duration **330** of the UE **115** may be reduced (relative to the on-duration **330** of FIG. **3**), thereby saving power at the UE **115**.

[0119] FIG. **5** shows an example of a process flow **500** that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure. Aspects of the process flow **500** may implement, or be implemented by, aspects of the wireless communications system **100**, the wireless communications system **200**, the timing diagram **300**, and the timing diagram **400** as described herein with reference to FIGS. **1-3**. For example, the process flow **500** may include a UE **115-b**, a RAN **202-a**, a UPF **205-a**, and an AS **215-a** which may be examples of corresponding devices described with reference to FIGS. **1-3**. In the following description of the process flow **500**, the operations may be performed in a different order than the order shown. Specific operations also may be left out of the process flow **500**, or other operations may be added to the process flow **500**. Further, although some operations or signaling may be shown to occur at different times for discussion purposes, these operations may actually occur at the same time. The techniques described in the context of the process flow **500** may enable the AS **215-a** to delay a first periodic burst transmission, thereby mitigating the effects of jitter in the wireless communications system.

[0120] At **515**, the AS **215-a** may obtain control signaling that includes assistance information associated with the UE **115-b**, where the assistance information may indicate a delivery deadline (e.g., the delivery deadline **305**) associated with a first periodic burst transmission (e.g., bursts **230**), a periodicity associated with the first periodic burst transmission, a jitter window (e.g., jitter window **315**) associated with the first periodic burst transmission, a duration for which the first periodic burst transmission is to be delayed, a threshold percentage of the jitter window for which the first periodic burst transmission is to be delayed, or a combination thereof.

[0121] Additionally, in some examples, the assistance information may indicate one or more jitter measurements, or parameters, associated with the communication flow between the UE **115-b** and the AS **215-a** (e.g., flow for BAT de-jitter buffering). Further, assistance information may indicate whether the communication flow between the UE **115-b** and the AS **215-a** supports delaying (e.g., buffering) of the first periodic burst transmission (e.g., BAT de-jittering), whether to enable or disable the delaying of the first periodic burst transmission, or any combination thereof.

[0122] In such examples, the UE **115-b** may provide the assistance information directly to the AS

215-a. Alternatively, the UE **115-b** may provide the assistance information to the RAN **202-a**, where the RAN **202-a** may provide the assistance information to the AS **215-a** directly, or via the UPF **205-a**. In some other examples, the UE **115-b** may provide the assistance information to the UPF **205-a**, where the UPF **205-a** may forward the assistance information to the AS **215-a**. In some examples, the RAN **202-a**, the UPF **205-a**, or both, may generate the assistance information, and subsequently provide the assistance information to the AS **215-a**. Alternatively, in some examples, the AS **215-a** may have an indication of such parameters (e.g., delivery deadline, periodicity, jitter window, duration, or the like) based on monitoring the communication flow between the UE **115-b** and the AS **215-a**. That is, the AS **215-a** may have an indication of whether a flow (e.g., a flow associated with jitter) will be periodically consumed by a UE **115-b** (e.g., a client) regardless of jitter, whether the communication flow supports delaying of the first periodic burst transmission, or both.

[0123] At **520**, the AS **215-a** may estimate the jitter window associated with the communication flow (e.g., estimate or measure the jitter window for the communication flow between the UE **115-b** and the AS **215-a**).

[0124] In some examples, the AS **215-a** may utilize a static jitter estimation algorithm to estimate the jitter window, where the AS **215-a** may estimate the jitter window associated with the first periodic burst transmission according to previous statistical information (e.g., jitter windows) of the communication flow. For example, the AS **215-a** may store one or more previously measured jitter windows associated with previous periodic burst transmissions (e.g., a second jitter window associated with a send periodic burst transmission) in a reference table, where the previously measured jitter windows may be categorized, or stored, according to one or more operating conditions that were present during the transmission of the previous periodic burst transmissions.

[0125] Such operating conditions may include a workload of the AS **215-a**, a data rate of the previous periodic burst transmissions, a periodicity associated with the previous periodic burst transmissions, an XR configuration of the AS **215-a**, an XR configuration of the XR application at the UE **115-b**, or a combination thereof. As such, the AS **215-a** may utilize the stored jitter windows, measured from previous periodic burst transmissions, to estimate the jitter window associated with the first periodic burst transmission. Additionally, in such examples, the AS **215-a** may update the jitter window measurements after each periodic burst transmission (e.g., based on the traffic over the communication flow). That is, in response to estimating the jitter window associated with the first periodic burst transmission, the AS **215-a** may store the estimated jitter window in the reference table according to the operating conditions associated with the first periodic burst transmission.

[0126] In some other examples, the AS **215-a** may utilize a dynamic jitter estimation algorithm to estimate the jitter window, where the AS **215-a** may estimate the jitter window dynamically during the generation of the first periodic burst transmission (e.g., estimate the jitter window during ongoing frame generation). For example, for the first periodic burst generation (e.g., frame generation), the AS **215-a** may have an indication as to when the first periodic burst transmission is generated (e.g., knows a start time of generation). As such, based on the start time of the generation, the AS **215-a** may measure a duration associated with generating the first periodic burst transmission. Accordingly, after the first periodic burst transmission (e.g., frame) is generated, the AS **215-a** may estimate the jitter window associated with the first periodic burst transmission based on the measured duration (e.g., frame generation time). Techniques to dynamically estimate the jitter window may be further described herein with reference to FIGS. **6A** and **6B**.

[0127] In such examples, if the operating conditions during frame generation change (e.g., the data rate of the periodic burst transmissions, periodicity of the periodic burst transmissions, workload of the AS **215-a**, XR configurations, or the like), the AS **215-a** may restart the jitter window measurements. Additionally, in such examples, the AS **215-a** may update the jitter window measurements after each periodic burst transmission (e.g., based on the traffic over the

communication flow)). That is, in response to estimating the jitter window associated with the first periodic burst transmission using the dynamic jitter estimation algorithm, the AS **215-a** may store the estimated jitter window in the reference table according to the operating conditions associated with the first periodic burst transmission.

[0128] In some examples, the AS **215-a** may utilize a hybrid jitter estimation algorithm to estimate the jitter window. For example, the AS **215-a** may estimate the jitter window associated with the first periodic burst transmission using both previous jitter window measurements (e.g., previous statistical information) and using dynamic jitter window measurements during ongoing frame generation. For example, the AS **215-a** may begin the jitter window estimation by using the previously stored jitter windows (e.g., jitter statistics). Accordingly, while the AS **215-a** generates the one or more PDU sets of the first periodic burst transmission (e.g., XR frames), the AS **215-a** may update the jitter window estimation. That is, after obtaining the duration associated with generating the first periodic burst transmission, the AS **215-a** may utilize the measured duration and previously measured jitter durations to estimate the jitter window associated with the first periodic transmission. Additionally, in such examples, the AS **215-a** may update the jitter window measurements after each periodic burst transmission (e.g., based on the traffic over the communication flow). That is, in response to estimating the jitter window associated with the first periodic burst transmission using the hybrid jitter estimation algorithm, the AS **215-a** may store the estimated jitter window in the reference table according to the operating conditions associated with the first periodic burst transmission.

[0129] In some examples, the AS **215-a** may ignore abnormal jitter window estimations. For example, if the AS **215-a** estimates a jitter window that is greater than a threshold jitter window (e.g., spans a time period greater than a threshold), then the AS **215-a** may ignore the estimated jitter window, and refrain from storing the estimated jitter window in the reference table.

[0130] At **525**, in response to, or in conjunction with, estimating the jitter window, the AS **215-a** may generate one or more PDU sets of the first periodic burst transmission, where the generation of the first periodic burst transmission may incur a major source of jitter of the communication flow, as described herein with reference to FIG. 2. For example, to generate the first periodic burst transmission, the AS **215-a** may render at least a portion of a video frame associated with an XR application at the UE **115-b**. In response to the rendering, the AS **215-a** may encode the portion of the video frame and proceed to packetize the portion of the video frame to obtain the one or more PDU sets of the first periodic burst transmission. In such examples, the source of the jitter may be incurred during the rendering, encoding, and packetization of the first periodic burst transmission.

[0131] At **530**, the AS **215-a** may buffer at least a portion of the one or more PDU sets of the first periodic burst transmission for the first duration of the jitter window, where the first duration may correspond to a threshold percentage of the jitter window, as described herein with reference to FIG. 4. For example, the AS **215-a** may delay delivering at least a portion of the first periodic burst transmission (e.g., buffer at least a portion of the one or more PDU sets) to the UPF **205-a** (e.g., 5GS) until a threshold of the maximum arrival time of the jitter window (e.g., a threshold percentage of the jitter window).

[0132] In some examples, the AS **215-a** may delay the portion of the first periodic burst transmission (e.g., 90% of the one or more PDU sets) for a duration that corresponds to 90% of the jitter window, as described herein with reference to FIG. 4. In some other examples, the AS **215-a** may delay the portion of the first periodic burst transmission (e.g., 99% of the one or more PDU sets) for a duration that corresponds to 99% of the jitter window, as described herein with reference to FIG. 4. In some other examples, the AS **215-a** may delay all of the first periodic burst transmission (e.g., 100% or all of the one or more PDU sets) for a duration that corresponds to 100% of the jitter window, as described herein with reference to FIG. 4. In such examples, the portion of the first periodic burst transmission that is delayed may correspond to, or be based on, the delay duration (e.g., the threshold percentage of the jitter window). Techniques to delay the first

periodic burst transmission may be further described herein with reference to FIGS. 6A and 6B.

[0133] At **535**, in response to, prior to, or in conjunction with, delaying the first periodic burst transmission, the AS **215-a** may output, to the UPF **205-a**, a time sensitive communication (TSC) message including an indication of the jitter window. That is, the UPF **205-a** may receive an indication of the jitter window (e.g., BAT) via the TSC message. In some examples, the AS **215-a** may indicate, via the TSC message, that the delaying of the first periodic burst transmission is enabled (e.g., being performed), indicate the threshold percentage of the jitter window for which the first periodic burst transmission is delayed, or both. In some examples, the UPF **205-a** may receive the TSC message from an application function (AF) that is associated with AS **215-a** or the XR application of UE **115-b**.

[0134] At **540**, the AS **215-a** may output the one or more PDU sets of the first periodic burst transmission after expiration of the first duration and prior to the first delivery deadline. For example, the AS **215-a** may output the burst (e.g., one or more PDU sets) to the UPF **205-a** via an N6 interface (e.g., interface between the AS **215-a** and the UPF **205-a**).

[0135] At **545**, in response to receiving the first periodic burst transmission, the UPF **205-a** may estimate the jitter window, a remaining jitter, or both. For example, the UPF **205-a** may measure the jitter window (e.g., BAT) associated with the first periodic burst transmission according to the one of the static jitter estimation algorithm, the dynamic jitter estimation algorithm, or the hybrid jitter estimation algorithm as described herein. The UPF **205-a** may perform such measurements based on the jitter window received via the TSC message at **435** or perform such measurements independent of the TSC message received at **435**.

[0136] In some examples, the UPF **205-a** may measure the remaining jitter of the jitter window. In one example, the UPF **205-a** may add a jitter associated with the N6 interface (e.g., communication link **220-c** between the AS **215-a** and UPF **205-a**) on top of the measured remaining jitter. For example, the UPF **205-a** may identify the remaining jitter based on a difference between the jitter window and the threshold percentage of the jitter window (e.g., jitter window (100%)–threshold percentage of jitter window (x % tile jitter)). Based on identifying the remaining jitter, the UPF **205-a** may calculate a jitter associated with the N6 interface between the UPF **205-a** and the AS **215-a**. Accordingly, the UPF **205-a** may add the remaining jitter with the jitter associated with the N6 interface to obtain a remaining jitter that has the N6 jitter included.

[0137] In some other examples, the remaining jitter may be assumed to be a predetermined value. For example, because the jitter of the N6 interface between the UPF **205-a** and the AS **215-a** is consistent, the UPF **205-a** may utilize a predetermined value as the jitter for the N6 interface, such that the remaining jitter may be calculated according to a predetermined value of the jitter associated with the N6 interface (e.g., jitter window (100%)–threshold percentage of jitter window (x %)+predetermined value (%)). In some other examples, the UPF **205-a** may refrain from calculating the remaining (e.g., ignore the remaining jitter). For example, the UPF **205-a** may not support the calculations of the remaining jitter.

[0138] At **550**, in response to estimating the jitter window, the remaining jitter, or both, the UPF **205-a** may transmit a TSC message indicating the estimated jitter window, the remaining jitter, or both to the RAN **202-a**. In such examples, the UPF **205-a** may transmit respective TSC messages to indicate the estimated jitter window and the remaining jitter. Alternatively, the UPF **205-a** may include both the estimated remaining jitter and jitter window in a single TSC message. The TSC message may be an example of a TSC assistance information (TSCAI) message or a TSC assistance container (TSCAC) message. In some examples, the UPF **205-a** may indicate, via the TSC message, that the delaying of the first periodic burst transmission is enabled (e.g., being performed), indicate the threshold percentage of the jitter window for which the first periodic burst transmission is delayed, or both.

[0139] At **555**, in response to, prior to, or in conjunction with, transmitting the TSC message at **550**, the UPF **205-a** may output the first periodic burst transmission to the RAN **202-a**. At **560**, the

RAN **202-a** may estimate the jitter window, remaining jitter, or both (e.g., XR traffic patterns). In such examples, the RAN **202-a** may utilize the static, dynamic, or hybrid jitter estimation algorithms or use artificial intelligence or machine learning models to identify the jitter statistics. Such operations at **560** may be performed prior to or after reception of the periodic burst at **555**. [0140] At **565**, the RAN **202-a** may output control signaling indicating one or more parameters corresponding to a DRX cycle (e.g., eCDRX configuration) associated with the UE **115-b** based on the jitter window, the remaining jitter, or both, where the jitter window, the remaining jitter, or both are received via the TSC message from the UPF **205-a** at **550** or estimated by the RAN **202-a** at **560**. The one or more parameters of the DRX cycle may include an offset (e.g., offset **325**) and an on-duration (e.g., on-duration **330**). In such examples, the RAN **202-a** may set the offset based on the jitter window, the remaining jitter, a jitter associated with communications between the UPF **205-a** and the AS **215-a** (e.g., N6 interface jitter), a first margin, or a combination thereof (e.g., offset=jitter window-remaining jitter-N6 interface jitter-margin). The RAN **202-a** may set the on-duration based on the remaining jitter, the jitter associated with the communications between the UPF **205-a** and the AS **215-a**, a second margin, or a combination thereof (e.g., on-duration=remaining jitter+N6 interface jitter+margin).

[0141] At **570**, the RAN **202-a** may output the one or more PDU sets of the first periodic burst transmission prior to the first delivery deadline. For example, the RAN **202-a** may output the first periodic burst transmission to the UE **115-b**, such that the one or more PDU sets of the first periodic burst transmission are delivered by the respective PSDBs and prior to the delivery deadline.

[0142] FIG. 6A and FIG. 6B show examples of a buffering diagram **600** and a buffering diagram **601**, respectively, that support mitigating jitter in communications in accordance with one or more aspects of the present disclosure. One or more aspects of the buffering diagram **600** and buffering diagram **601** may be implemented by a network device, such as an AS **215**, a UPF **205**, or a RAN **202** as described with reference to FIGS. 1-5. The buffering diagram **600** may include rendering component **610-a**, an encoding component **615-a**, a packetization component **620-a**, a buffer component **625-a**, a measurement component **630-a**, a timer **635**, and a counter **640**. The buffering diagram **601** may include a rendering component **610-b**, an encoding component **615-b**, a packetization component **620-b**, a buffer component **625-b**, a measurement component **630-b**, a clock marking component **645**, and a clock **650**. The techniques described in the context of the buffering diagram **600** and the buffering diagram **601** may enable the network device (e.g., AS **215**, the UPF **205**, or the RAN **202**) to delay a burst **230** (e.g., a first periodic burst transmission).

[0143] With reference to the buffering diagram **600** of FIG. 6A, the network device may implement a local timer-based implementation for buffering the burst **230-a**. For example, when an event (e.g., generation of the burst **230-a** from the frame **605-a**) starts, the network device (e.g., AS **215**) may start the timer **635**, which has been set to an initial value (e.g., a duration corresponding to the threshold percentage of a jitter window). Additionally, the network device may initiate the counter **640**, which may start from zero. To generate the burst **230-a**, the network device (e.g., AS **215**) may begin to render the frame **605-a** using the rendering component **610-a**, encode the rendered frame **605-a** using the encoding component **615-a**, and packetize the encoded frame **605-a** using the packetization component **620-a** to obtain the burst **230-a**.

[0144] As such, during the rendering, encoding, and packetization, the timer **635** (e.g., duration corresponding to a threshold percentage of the jitter window) may decrease while the counter **640** may increase. In response to the completion of at least a portion of the burst **230-a**, the buffer component **625-a** may delay (e.g., hold) the generated portions of the burst **230-a** (e.g., generated frame) until the timer **635** expires (e.g., until expiration of the duration). When the timer **635** expires, the buffer component **625-a** of the network device may release the portion of the burst **230-a**, such that the network device may output the burst **230-a** (e.g., delivers the frame to UPF **205**). In this way, the network device may buffer at least a portion of the burst **230-a** for a threshold

percentage of the jitter window.

[0145] In such examples, the network device may utilize the value of the counter **640** to update the statistics regarding the jitter window using the measurement component **630-a**. For example, because the generation of the burst **230-a** (e.g., rendering, encoding, and packetizing) causes the majority of the jitter for the burst **230-a**, the network device may update the statistics regarding the jitter window according to the generation time of the burst **230-a** (e.g., the value of the counter **640**). The network device may update the minimum arrival time (e.g., minimum arrival time **316**) of the jitter window, the average arrival time of the jitter window (e.g., the average arrival time **317**), the maximum arrival time (e.g., the maximum arrival time **318**) of the jitter window, the mean of the jitter window, a variance of the jitter window, or a combination thereof, based on the value of the counter **640** (e.g., the duration associated with generating the burst **230-a**). Accordingly, the measurement component **630-a** may update the initial value of the timer **635** (e.g., the duration corresponding to the threshold percentage of the jitter window) according to the updated jitter statistics.

[0146] Such techniques may be utilized by the RAN **202** and the UPF **205**, where the rendering component **610-a**, the encoding component **615-a**, and the packetization component **620-a** may be skipped or replaced by reception of the one or more PDU sets of the burst **230-a**. For example, in response to reception of the burst **230-a**, the UPF **205** or the RAN **202** may initiate the timer **635** that is set to an initial value, and buffer the burst **230-a** until expiration of the timer **635** using the buffer component **625-a**.

[0147] With reference to the buffering diagram **601**, the network device (e.g., AS **215**) may implement a global timer-based implementation for buffering the burst **230-b**. For example, when an event starts (e.g., generation of the burst **230-b** from the frame **605-b**), the network device may mark (e.g., identify) a time associated with the start of the rendering of the frame **605-b**, where such a time may be referred to as a marked time. To generate the burst **230-b**, the network device (e.g., AS **215**) may begin to render the frame **605-b** using the rendering component **610-b**, encode the rendered frame **605-b** using the encoding component **615-b**, and packetize the encoded frame **605-b** using the packetization component **620-b** to obtain the burst **230-b**.

[0148] In response to the completion of at least a portion of the burst **230-b**, the buffer component **625-a** may delay (e.g., hold) the generated portions of the burst **230-b** (e.g., generated frame) until a duration (e.g., the duration corresponding to a threshold percentage of the jitter window) has expired. For example, in response to completion of the generated burst **230-b**, the clock **650** may indicate to the buffer component **625-b** a current time (e.g., a time at which the burst **230-b** was fully generated). Accordingly, the buffer component **625-b** may calculate a frame generation time (e.g., frame generation duration) associated with the burst **230-b** based on the marked time and the current time (e.g., frame generation time=current time-marked time). Accordingly, if the duration associated with the frame generation time (e.g., marked time+frame generation time) is below the duration corresponding to the threshold percentage of the jitter window, the buffer component **625-b** may delay the burst **230-b**. Alternatively, if the duration associated with the frame generation time (e.g., marked time+frame generation time) is greater than, or equal to, the duration corresponding to the threshold percentage of the jitter window, the buffer component **625-b** may release the burst **230-b**, such that the network device may transmit the burst **230-b** (e.g., to the UPF **205**).

[0149] In such examples, the network device may utilize the frame generation time to update the statistics regarding the jitter window using the measurement component **630-b**. For example, because the generation of the burst **230-b** (e.g., rendering, encoding, and packetizing) causes the majority of the jitter for the burst **230-b**, the network device may update the statistics regarding the jitter window according to the frame generation time of the burst **230-b**. The network device may update the minimum arrival time (e.g., minimum arrival time **316**) of the jitter window, the average arrival time of the jitter window (e.g., the average arrival time **317**), the maximum arrival time

(e.g., the maximum arrival time **318**) of the jitter window, the mean of the jitter window, a variance of the jitter window, or a combination thereof based on the frame generation time of the burst **230-b**. Accordingly, the measurement component **630-b** may update the duration corresponding to the threshold percentage of the jitter window according to the updated jitter statistics.

[0150] Such techniques may be utilized by the RAN **202** and the UPF **205**, where the rendering component **610-b**, the encoding component **615-b**, and the packetization component **620-b** may be skipped or replaced by reception of the one or more PDU sets of the burst **230-b**. For example, in response to reception of the burst **230-b**, the UPF **205** or the RAN **202** may identify the marked time using the clock marking component **645**, and buffer the burst **230-b** until expiration the duration corresponding to the threshold percentage of the jitter window using the buffer component **625-b**.

[0151] Although, the buffering diagram **600** and the buffering diagram **601** may be used delay the bursts **230**, it should be understood that any methodology by which the AS **215**, UPF **205**, or RAN **202** use to buffer the bursts **230** or restrict the jitter window may be applicable to the techniques described herein.

[0152] FIG. 7 shows an example of a process flow **700** that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure. Aspects of the process flow **700** may implement, or be implemented by, aspects of the wireless communications system **100**, the wireless communications system **200**, the timing diagram **300**, the timing diagram **400**, the process flow **500**, the buffering diagram **600**, and the buffering diagram **601** as described herein with reference to FIGS. 1-6B. For example, the process flow **700** may include a UE **115-c**, a RAN **202-b**, a UPF **205-b**, and an AS **215-b** which may be examples of corresponding devices described with reference to FIGS. 1-6B. In the following description of the process flow **700**, the operations may be performed in a different order than the order shown. Specific operations also may be left out of the process flow **700**, or other operations may be added to the process flow **700**. Further, although some operations or signaling may be shown to occur at different times for discussion purposes, these operations may actually occur at the same time. The techniques described in the context of the process flow **700** may enable the UPF **205-b** to delay a first periodic burst transmission, thereby mitigating the effects of jitter in the wireless communications system.

[0153] At **715**, the UPF **205-b** may receive control signaling indicating assistance information, where the assistance information may indicate a delivery deadline (e.g., the delivery deadline **305**) associated with the first periodic burst transmission (e.g., bursts **230**), a periodicity associated with the first periodic burst transmission, a jitter window (e.g., jitter window **315**) associated with the first periodic burst transmission, a duration for which the first periodic burst transmission is to be delayed, a threshold percentage of the jitter window for which the first periodic burst transmission is to be delayed, or a combination thereof. Additionally, in some examples, the assistance information may indicate one or more jitter measurements, or parameters, associated with the communication flow between the UE **115-c** and the AS **215-b** (e.g., flow for BAT de-jitter buffering). Further, assistance information may indicate whether the communication flow between the UE **115-c** and the AS **215-b** supports delaying (e.g., buffering) of the first periodic burst transmission (e.g., BAT de-jittering), whether to enable or disable the delaying of the first periodic burst transmission, or any combination thereof.

[0154] In some examples, the UPF **205-b** may receive the assistance information from session management function (SMF), where the SMF may receive the assistance information from a policy control function (PCF). In such examples, the UPF **205-b** may indicate the assistance information to the RAN **202-b** (e.g., the PCF indicates assistance information to the SMF, where the SMF forwards assistance information to UPF **205-b**, and the UPF **205-b** indicates assistance information to RAN **202-b**). In some other examples, the AS **215-b** may provide the UPF **205-b** with the assistance information via an AF or network exposure function (NEF) interface. For example, the AS **215-b** may provide the assistance information to the PCF via the AF or NEF interface, where

the PCF may forward the assistance information to the SMF, and the SMF may forward the assistance information to the UPF **205-b**.

[0155] In some other examples, the UPF **205-b** (e.g., 5GC) may receive the assistance information from the UE **115-c**, directly, via the non-access stratum (NAS) protocol. In some other examples, the UPF **205-b** may receive the assistance information from the UE **115-c** via the RAN **202-b**, where the RAN **202-b** may receive the assistance information from the UE **115-c** via RRC protocols (e.g., RRC messaging) and forward the assistance information to the UPF **205-b**.

[0156] Alternatively, the UPF **205-b** may have an indication of whether the communication flow between the AS **215-b** and the UE **115-c** will be periodically consumed by the UE **115-c** regardless of jitter, where the SMF may manage the traffic characteristics (e.g., jitter statistics, buffering, periodicity, or the like) for the communication flow) and indicate such characteristics to the UPF **205-b**.

[0157] At **720**, in response to, after, or in conjunction with the operations at **715**, the AS **215-b** may generate the first periodic burst transmission. For example, the AS **215-b** may generate one or more PDU sets of the first periodic burst transmission, where the generation of the first periodic burst transmission may incur a major source of jitter of the communication flow, as described herein with reference to FIG. 2. For example, to generate the first periodic burst transmission, the AS **215-b** may render at least a portion of a video frame associated with an XR application at the UE **115-c**. In response to rendering, the AS **215-b** may encode the portion of the video frame and proceed to packetize the portion of the video frame to obtain the one or more PDU sets of the first periodic burst transmission. In such examples, the source of the jitter may be incurred during the rendering, encoding, and packetization of the first periodic burst transmission.

[0158] In some examples, at **725**, the AS **215-b** may output, to the UPF **205-b** a TSC message including an indication of the jitter window associated with the first periodic burst transmission. That is, the UPF **205-b** may receive an indication of the jitter window (e.g., BAT) via the TSC message. In some examples, the AS **215-a** may indicate, via the TSC message, that the delaying of the first periodic burst transmission is enabled (e.g., being performed), indicate the threshold percentage of the jitter window for which the first periodic burst transmission is delayed, or both. In some examples, the UPF **205-b** may receive the TSC message from an AF that is associated with AS **215-b** or the XR application of UE **115-c**.

[0159] At **730**, the AS **215-b** may output the first periodic burst transmission via an N6 interface, where the jitter associated with the N6 interface may be added to the jitter window, the remaining jitter, or both. In such examples, the UPF **205-b** may identify the one or more PDU sets of the first periodic burst transmission according to metadata (e.g., RTP or static RTP (SRTP) headers) of the one or more PDU sets of the first periodic burst transmission. For example, each of the one or more PDU sets may have a same identifier in a header, such that the UPF **205-b** has an indication that the one or more PDU sets are associated with a same periodic burst transmission.

[0160] At **735**, the UPF **205-b** may estimate the jitter window, the remaining jitter, or both associated with the first periodic burst transmission. In such examples, the UPF **205-b** may estimate the jitter window in accordance with the techniques described herein with reference to the operations at **520** and **545** of FIG. 5. For example, the UPF **205-b** may utilize a static jitter estimation algorithm, a dynamic jitter estimation algorithm, or a hybrid jitter estimation algorithm to estimate the jitter window. In such examples, the UPF **205-b** may store the estimated jitter windows at a reference table of the UPF **205-b** according to one or more operation conditions, as described herein with reference to FIG. 5. In some examples, the AS **215-a** may ignore abnormal jitter window estimations. For example, if the UPF **205-b** estimates a jitter window that is greater than a threshold jitter window (e.g., spans a time period greater than a threshold), then the UPF **205-b** may ignore the estimated jitter window, and refrain from storing the estimated jitter window at the UPF **205-b**.

[0161] At **740**, the UPF **205-b** may buffer at least a portion of the one or more PDU sets of the first

periodic burst transmission for the first duration of the jitter window, where the first duration may correspond to a threshold percentage of the jitter window, as described herein with reference to FIG. 4. For example, the UPF 205-b may delay delivering at least a portion of the first periodic burst transmission (e.g., buffer at least a portion of the one or more PDU sets) to the RAN 202-b until a threshold of the maximum arrival time of the jitter window (e.g., a threshold percentage of the jitter window).

[0162] In some examples, the UPF 205-b may delay the portion of the first periodic burst transmission (e.g., 90% of the one or more PDU sets) for a duration that corresponds to 90% of the jitter window, as described herein with reference to FIG. 4. In some other examples, the UPF 205-b may delay the portion of the first periodic burst transmission (e.g., 99% of the one or more PDU sets) for a duration that corresponds to 99% of the jitter window, as described herein with reference to FIG. 4. In some other examples, the UPF 205-b may delay all of the first periodic burst transmission (e.g., 100% or all of the one or more PDU sets) for a duration that corresponds to 100% of the jitter window, as described herein with reference to FIG. 4. In such examples, the portion of the first periodic burst transmission that is delayed may correspond to, or be based on, the delay duration (e.g., the threshold percentage of the jitter window). The UPF 205-b may delay the first periodic burst transmission according to the techniques described herein with reference to FIGS. 6A and 6B.

[0163] At 745, in some examples, the UPF 205-b may update the jitter statistics stored at the UPF 205-b. For example, the UPF 205-b may store the jitter window estimated at 735 and update the jitter window associated with the communication flow accordingly. In some examples, the UPF 205-b may update the jitter statics according to the earliest arriving PDU, PDU set, or periodic burst transmission, according to the latest arriving PDU, PDU set, or periodic burst transmission, or both. For example, the UPF 205-b may identify the periodicity of the periodic bursts based on the average of the time intervals between two adjacent periodic burst transmission, identify the average arrival times (e.g., average arrival time 317 or nominal arrival time) based on the average of burst arrival times within the periodicity, and identify (e.g., measure) the jitter window based on the average arrival times. In this way, the UPF 205-b may maintain accurate jitter statistics (e.g., minimum arrival times 316, average arrival times 317, and a maximum arrival times 318) of the jitter windows over the communication flow.

[0164] At 750, the UPF 205-b may output a TSC message to the RAN 202-b, where the TSC message may include the jitter window (BAT), the remaining jitter, or both. The UPF 205-b may transmit the TSC message to the RAN 202-b according to the techniques described herein with reference to operations 550 of FIG. 5. For example, in response to estimating the jitter window, the remaining jitter, or both, the UPF 205-b may transmit a TSC message indicating the estimated jitter window, the remaining jitter, or both to the RAN 202-b. In such examples, the UPF 205-b may transmit respective TSC messages to indicate the estimated jitter window and the remaining jitter. Alternatively, the UPF 205-b may include both the estimated remaining jitter and jitter window in a single TSC message. The TSC message may be an example of a TSCAI message or a TSCAC message. In some examples, the UPF 205-b may indicate, via the TSC message, that the delaying of the first periodic burst transmission is enabled (e.g., being performed), indicate the threshold percentage of the jitter window for which the first periodic burst transmission is delayed, or both.

[0165] At 755, in response to, prior to, or in conjunction with, transmitting the TSC message at 750, the UPF 205-b may output the first periodic burst transmission to the RAN 202-b. As described herein, the one or more PDU sets of first periodic burst transmission may be associated a PDSB. Accordingly, an access network (AN) PSDB may be counted when the delayed periodic burst transmission arrives at the RAN 202-b, where the first periodic burst transmission may meet the associated delivery deadline. In such examples, the PSDB may be equal to the addition of a core network (CN) PSDB and the AN PSDB (e.g., $PSDB = CN-PSDB + AN-PSDB$). Further, the CN-PSDB may remain consistent regardless of the delay to the periodic burst transmission.

[0166] At **760**, the RAN **202-b** may estimate the jitter window, remaining jitter, or both (e.g., XR traffic patterns). In such examples, the RAN **202-b** may utilize the static, dynamic, or hybrid jitter estimation algorithms or use artificial intelligence or machine learning models to identify the jitter statistics. Such operations at **760** may be performed prior to or after reception of the periodic burst at **755**.

[0167] At **765**, the RAN **202-b** may output control signaling indicating one or more parameters corresponding to a DRX cycle (e.g., eCDRX configuration) associated with the UE **115-c** based on the jitter window, the remaining jitter, or both, where the jitter window, the remaining jitter, or both are received via the TSC message from the UPF **205-a** at **750**, estimated by the RAN **202-b** at **760**, or both. The one or more parameters of the DRX cycle may include an offset (e.g., offset **325**) and an on-duration (e.g., on-duration **330**). In such examples, the RAN **202-b** may set the offset based on the jitter window, the remaining jitter, a first margin, or a combination thereof (e.g., offset=jitter window-remaining jitter-margin). The RAN **202-b** may set the on-duration based on the remaining jitter, a second margin, or a combination thereof (e.g., on-duration=remaining jitter+margin). In such examples, the remaining jitter may account for the jitter associated with the N6 interface, as the UPF **205-b** may add the N6 jitter to the jitter window, remaining jitter, or both based on reception of the first periodic burst transmission.

[0168] At **770**, the RAN **202-b** may output the one or more PDU sets of the first periodic burst transmission prior to the first delivery deadline. For example, the RAN **202-b** may output the first periodic burst transmission to the UE **115-c**, such that the one or more PDU sets of the first periodic burst transmission are delivered by the respective PSDBs and prior to the delivery deadline.

[0169] FIG. **8** shows an example of a process flow **800** that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure. Aspects of the process flow **800** may implement, or be implemented by, aspects of the wireless communications system **100**, the wireless communications system **200**, the timing diagram **300**, the timing diagram **400**, the process flow **500**, the buffering diagram **600**, the buffering diagram **601**, and the process flow **700** as described herein with reference to FIGS. **1-7**. For example, the process flow **800** may include a UE **115-d**, a RAN **202-c**, a UPF **205-c**, and an AS **215-c**, which may be examples of corresponding devices described with reference to FIGS. **1-7**.

[0170] In the following description of the process flow **800**, the operations may be performed in a different order than the order shown. Specific operations also may be left out of the process flow **800**, or other operations may be added to the process flow **800**. Further, although some operations or signaling may be shown to occur at different times for discussion purposes, these operations may actually occur at the same time. The techniques described in the context of the process flow **800** may enable the RAN **202-c** to delay a first periodic burst transmission, thereby mitigating the effects of jitter in the wireless communications system.

[0171] At **815**, the RAN **202-c** may receive control signaling indicating assistance information, where the assistance information may indicate a delivery deadline (e.g., the delivery deadline **305**) associated with the first periodic burst transmission (e.g., bursts **230**), a periodicity associated with the first periodic burst transmission, a jitter window (e.g., jitter window **315**) associated with the first periodic burst transmission, a duration for which the first periodic burst transmission is to be delayed, a threshold percentage of the jitter window for which the first periodic burst transmission is to be delayed, or a combination thereof. Additionally, in some examples, the assistance information may indicate one or more jitter measurements, or parameters, associated with the communication flow between the UE **115-d** and the AS **215-c** (e.g., flow for BAT de-jitter buffering). Further, assistance information may indicate whether the communication flow between the UE **115-d** and the AS **215-c** supports delaying (e.g., buffering) of the first periodic burst transmission (e.g., BAT de-jittering), whether to enable or disable the delaying of the first periodic burst transmission, or any combination thereof.

[0172] In some examples, the RAN **202-c** may receive the assistance information from the UPF **205-c**, where the UPF **205-c** may receive the assistance information from the SMF, and where the SMF may receive the assistance information from the PCF (e.g., the PCF indicates assistance information to the SMF, where the SMF forwards assistance information to UPF **205-c**, and the UPF **205-c** indicates assistance information to RAN **202-c**). In some other examples, the AS **215-c** may generate and provide the UPF **205-b** with the assistance information via AF or NEF interface. For example, the AS **215-c** may provide the assistance information to the PCF via the AF or NEF interface, where the PCF may forward the assistance information to the SMF, and the SMF may forward the assistance information to the UPF **205-c**, where the UPF **205-c** may forward the assistance information to the RAN **202-c**.

[0173] In some other examples, the RAN **202-c** may receive the assistance information from the UE **115-d**, via, the UPF **205-c** (e.g., 5GC). For example, the UE **115-d** may provide the assistance information to the UPF **205-c** via the NAS protocol, where the UPF **205-c** may forward the assistance information to the RAN **202-c**. In some other examples, the RAN **202-c** may receive the assistance information from the UE **115-d** via the RRC protocol (e.g., RRC messaging).

[0174] Alternatively, the RAN **202-c** may have an indication of whether the communication flow between the AS **215-b** and the UE **115-d** will be periodically consumed by the UE **115-d** regardless of jitter, where the SMF may manage the traffic characteristics (e.g., jitter statistics, buffering, periodicity, or the like) for the communication flow) and indicate such characteristics to the RAN **202-c**.

[0175] At **820**, in response to, after, or in conjunction with the operations at **815**, the AS **215-c** may generate the first periodic burst transmission. For example, the AS **215-c** may generate one or more PDU sets of the first periodic burst transmission, where the generation of the first periodic burst transmission may incur a major source of jitter of the communication flow, as described herein with reference to FIG. 2. For example, to generate the first periodic burst transmission, the AS **215-c** may render at least a portion of a video frame associated with an XR application at the UE **115-d**. In response to rendering, the AS **215-c** may encode the portion of the video frame and proceed to packetize the portion of the video frame to obtain the one or more PDU sets of the first periodic burst transmission. In such examples, the source of the jitter may be incurred during the rendering, encoding, and packetization of the first periodic burst transmission.

[0176] At **825**, the AS **215-c** may output the first periodic burst transmission via an N6 interface, where the jitter associated with the N6 interface may be added to the jitter window. At **830**, the UPF **205-c** may output the first periodic burst transmission to the RAN **202-c**, where the jitter associated with the N3 interface may be added to the jitter window (e.g., the jitter associated with the communication link between the RAN **202-c** and the UPF **205-c**). In such examples, the RAN **202-c** may identify the one or more PDU sets of the first periodic burst transmission according to metadata (e.g., RTP or SRTP headers) of the one or more PDU sets of the first periodic burst transmission. For example, each of the one or more PDU sets may have a same identifier in a header, such that the RAN **202-c** has an indication that the one or more PDU sets are associated with a same periodic burst transmission.

[0177] As described herein, the one or more PDU sets of first periodic burst transmission may be associated a PDSB. Accordingly, an access network (AN) PSDB may be counted when the delayed periodic burst transmission arrives at the RAN **202-b**, where the first periodic burst transmission may meet the associated delivery deadline. In such examples, the PSDB may be equal to the addition of a core network (CN) PSDB and the AN PSDB (e.g., $PSDB = CN\text{-}PSDB + AN\text{-}PSDB$). Further, the CN-PSDB may remain consistent regardless of the delay. Alternatively, the AN-PDSB (or AN PDB) may start to in response to the UE **115-d** entering the on-duration of the DRX cycle.

[0178] At **835**, the RAN **202-c** may estimate the jitter window, the remaining jitter, or both associated with the first periodic burst transmission. In such examples, the RAN **202-c** may estimate the jitter window in accordance with the techniques described herein with reference to the

operations at **520**, **545**, or **560** of FIG. 5 or operations **735** or **760** of FIG. 7. For example, the RAN **202-c** may utilize a static jitter estimation algorithm, a dynamic jitter estimation algorithm, or a hybrid jitter estimation algorithm to estimate the jitter window or use artificial intelligence or machine learning models to identify the jitter statistics to identify the jitter window (e.g., obtain the XR traffic characteristics). In such examples, the RAN **202-c** may store the estimated jitter windows at a reference table of the RAN **202-c** according to one or more operation conditions, as described herein with reference to FIG. 5. In some examples, the RAN **202-c** may ignore abnormal jitter window estimations. For example, if the RAN **202-c** estimates a jitter window that is greater than a threshold jitter window (e.g., spans a time period greater than a threshold), then the RAN **202-c** may ignore the estimated jitter window, and refrain from storing the estimated jitter window at the RAN **202-c**.

[0179] At **840**, the RAN **202-c** may buffer at least a portion of the one or more PDU sets of the first periodic burst transmission for the first duration of the jitter window, where the first duration may correspond to a threshold percentage of the jitter window, as described herein with reference to FIG. 4. For example, the RAN **202-c** may delay delivering at least a portion of the first periodic burst transmission (e.g., buffer at least a portion of the one or more PDU sets) to the UE **115-d** until a threshold of the maximum arrival time of the jitter window (e.g., a threshold percentage of the jitter window).

[0180] In some examples, the RAN **202-c** may delay the portion of the first periodic burst transmission (e.g., 90% of the one or more PDU sets) for a duration that corresponds to 90% of the jitter window, as described herein with reference to FIG. 4. In some other examples, the RAN **202-c** may delay the portion of the first periodic burst transmission (e.g., 99% of the one or more PDU sets) for a duration that corresponds to 99% of the jitter window, as described herein with reference to FIG. 4. In some other examples, the RAN **202-c** may delay all of the first periodic burst transmission (e.g., 100% or all of the one or more PDU sets) for a duration that corresponds to 100% of the jitter window, as described herein with reference to FIG. 4. In such examples, the portion of the first periodic burst transmission that is delayed may correspond to, or be based on, the delay duration (e.g., the threshold percentage of the jitter window). The RAN **202-c** may delay the first periodic burst transmission according to the techniques described herein with reference to FIGS. 6A and 6B.

[0181] At **845**, in some examples, the RAN **202-c** may update the jitter statistics stored at the RAN **202-c**. For example, the RAN **202-c** may store the jitter window estimated at **835** and update the jitter window associated with the communication flow accordingly. In some examples, the RAN **202-c** may update the jitter statics according to the earliest arriving PDU, PDU set, or periodic burst transmission, according to the latest arriving PDU, PDU set, or periodic burst transmission, or both. For example, the RAN **202-c** may identify the periodicity of the periodic bursts based on the average of the time intervals between two adjacent periodic burst transmission, identify the average arrival times (e.g., average arrival time **317** or nominal arrival time) based on the average of burst arrival times within the periodicity, and identify (e.g., measure) the jitter window based on the average arrival times. In this way, the RAN **202-c** may maintain accurate jitter statistics (e.g., minimum arrival times **316**, average arrival times **317**, and a maximum arrival times **318**) of the jitter windows over the communication flow.

[0182] At **850**, the RAN **202-c** may output control signaling indicating one or more parameters corresponding to a DRX cycle (e.g., eCDRX configuration) associated with the UE **115-d** based on the jitter window, the remaining jitter, or both, where the jitter window, the remaining jitter, or both are estimated by the RAN **202-c** at **835**. The one or more parameters of the DRX cycle may include an offset (e.g., offset **325**) and an on-duration (e.g., on-duration **330**). In such examples, the RAN **202-c** may set the offset based on the jitter window, the remaining jitter, a first margin, or a combination thereof (e.g., jitter window–remaining jitter–margin). The RAN **202-c** may set the on-duration based on the remaining jitter, a second margin, or a both (e.g., remaining jitter+margin).

[0183] At **855**, the RAN **202-c** may output the one or more PDU sets of the first periodic burst transmission prior to the first delivery deadline. For example, the RAN **202-c** may output the first periodic burst transmission to the UE **115-d**, such that the one or more PDU sets of the first periodic burst transmission are delivered by the respective PSDBs and prior to the delivery deadline.

[0184] FIG. **9** shows a block diagram **900** of a device **905** that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure. The device **905** may be an example of aspects of a network entity **105**, an AS, a UPF, or a RAN, as described herein. The device **905** may include a receiver **910**, a transmitter **915**, and a communications manager **920**. The device **905**, or one or more components of the device **905** (e.g., the receiver **910**, the transmitter **915**, the communications manager **920**), may include at least one processor, which may be coupled with at least one memory, to, individually or collectively, support or enable the described techniques. Each of these components may be in communication with one another (e.g., via one or more buses).

[0185] The receiver **910** may provide a means for obtaining (e.g., receiving, determining, identifying) information such as user data, control information, or any combination thereof (e.g., I/Q samples, symbols, packets, protocol data units, service data units) associated with various channels (e.g., control channels, data channels, information channels, channels associated with a protocol stack). Information may be passed on to other components of the device **905**. In some examples, the receiver **910** may support obtaining information by receiving signals via one or more antennas. Additionally, or alternatively, the receiver **910** may support obtaining information by receiving signals via one or more wired (e.g., electrical, fiber optic) interfaces, wireless interfaces, or any combination thereof.

[0186] The transmitter **915** may provide a means for outputting (e.g., transmitting, providing, conveying, sending) information generated by other components of the device **905**. For example, the transmitter **915** may output information such as user data, control information, or any combination thereof (e.g., I/Q samples, symbols, packets, protocol data units, service data units) associated with various channels (e.g., control channels, data channels, information channels, channels associated with a protocol stack). In some examples, the transmitter **915** may support outputting information by transmitting signals via one or more antennas. Additionally, or alternatively, the transmitter **915** may support outputting information by transmitting signals via one or more wired (e.g., electrical, fiber optic) interfaces, wireless interfaces, or any combination thereof. In some examples, the transmitter **915** and the receiver **910** may be co-located in a transceiver, which may include or be coupled with a modem.

[0187] The communications manager **920**, the receiver **910**, the transmitter **915**, or various combinations or components thereof may be examples of means for performing various aspects of mitigating jitter in communications as described herein. For example, the communications manager **920**, the receiver **910**, the transmitter **915**, or various combinations or components thereof may be capable of performing one or more of the functions described herein.

[0188] In some examples, the communications manager **920**, the receiver **910**, the transmitter **915**, or various combinations or components thereof may be implemented in hardware (e.g., in communications management circuitry). The hardware may include at least one of a processor, a DSP, a CPU, an ASIC, an FPGA or other programmable logic device, a microcontroller, discrete gate or transistor logic, discrete hardware components, or any combination thereof configured as or otherwise supporting, individually or collectively, a means for performing the functions described in the present disclosure. In some examples, at least one processor and at least one memory coupled with the at least one processor may be configured to perform one or more of the functions described herein (e.g., by one or more processors, individually or collectively, executing instructions stored in the at least one memory).

[0189] Additionally, or alternatively, the communications manager **920**, the receiver **910**, the

transmitter **915**, or various combinations or components thereof may be implemented in code (e.g., as communications management software or firmware or processor-readable instructions) executed by at least one processor (e.g., referred to as a processor-executable code). If implemented in code executed by at least one processor, the functions of the communications manager **920**, the receiver **910**, the transmitter **915**, or various combinations or components thereof may be performed by a general-purpose processor, a DSP, a CPU, an ASIC, an FPGA, a microcontroller, or any combination of these or other programmable logic devices (e.g., configured as or otherwise supporting, individually or collectively, a means for performing the functions described in the present disclosure).

[0190] In some examples, the communications manager **920** may be configured to perform various operations (e.g., receiving, obtaining, monitoring, outputting, transmitting) using or otherwise in cooperation with the receiver **910**, the transmitter **915**, or both. For example, the communications manager **920** may receive information from the receiver **910**, send information to the transmitter **915**, or be integrated in combination with the receiver **910**, the transmitter **915**, or both to obtain information, output information, or perform various other operations as described herein.

[0191] In some examples, the device **905** may be an example of an AS, as described herein. In such examples, the communications manager **920** of the AS may support wireless communications in accordance with examples as disclosed herein. For example, the communications manager **920** is capable of, configured to, or operable to support a means for generating one or more PDU sets of a first periodic burst transmission, the first periodic burst transmission corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets. The communications manager **920** is capable of, configured to, or operable to support a means for buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window. The communications manager **920** is capable of, configured to, or operable to support a means for outputting the one or more PDU sets based on expiration of the first duration and prior to the first delivery deadline.

[0192] Additionally, or alternatively, the device **905** may be an example of a RAN, as described herein. Accordingly, the communications manager **920** of the RAN may support wireless communications in accordance with examples as disclosed herein. For example, the communications manager **920** is capable of, configured to, or operable to support a means for obtaining a TSC message indicating a jitter window associated with one or more PDU sets of a first periodic burst transmission, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets, and where the one or more PDU sets of the first periodic burst transmission correspond to a first delivery deadline at a UE. The communications manager **920** is capable of, configured to, or operable to support a means for obtaining at least a portion of the one or more PDU sets of the first periodic burst transmission at a first time, where the first time corresponds to at least a threshold percentage of the jitter window. The communications manager **920** is capable of, configured to, or operable to support a means for outputting the one or more PDU sets prior to the first delivery deadline.

[0193] Additionally, or alternatively, the device **905** may be an example of a UPF, as described herein. Accordingly, the communications manager **920** of the UPF may support wireless communications in accordance with examples as disclosed herein. For example, the communications manager **920** is capable of, configured to, or operable to support a means for obtaining one or more PDU sets of a first periodic burst transmission, the first periodic burst corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets. The communications manager **920** is capable of, configured to, or operable to support a means for buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window. The

communications manager **920** is capable of, configured to, or operable to support a means for outputting the one or more PDU sets based on expiration of the first duration and prior to the first delivery deadline.

[0194] Additionally, or alternatively, the device **905** may be an example of a RAN. Accordingly, the communications manager **920** of the RAN may support wireless communications in accordance with examples as disclosed herein. For example, the communications manager **920** is capable of, configured to, or operable to support a means for obtaining one or more PDU sets of a first periodic burst transmission, the first periodic burst corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets. The communications manager **920** is capable of, configured to, or operable to support a means for buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window. The communications manager **920** is capable of, configured to, or operable to support a means for outputting the one or more PDU sets based on expiration of the first duration and prior to the first delivery deadline.

[0195] By including or configuring the communications manager **920** in accordance with examples as described herein, the device **905** (e.g., at least one processor controlling or otherwise coupled with the receiver **910**, the transmitter **915**, the communications manager **920**, or a combination thereof) may support techniques for mitigating jitter in wireless communications systems, which may reduce power consumption at a UE.

[0196] FIG. **10** shows a block diagram **1000** of a device **1005** that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure. The device **1005** may be an example of aspects of a device **905**, an AS, a UPF, a RAN, or a network entity **105** as described herein. The device **1005** may include a receiver **1010**, a transmitter **1015**, and a communications manager **1020**. The device **1005**, or one or more components of the device **1005** (e.g., the receiver **1010**, the transmitter **1015**, the communications manager **1020**), may include at least one processor, which may be coupled with at least one memory, to support the described techniques. Each of these components may be in communication with one another (e.g., via one or more buses).

[0197] The receiver **1010** may provide a means for obtaining (e.g., receiving, determining, identifying) information such as user data, control information, or any combination thereof (e.g., I/Q samples, symbols, packets, protocol data units, service data units) associated with various channels (e.g., control channels, data channels, information channels, channels associated with a protocol stack). Information may be passed on to other components of the device **1005**. In some examples, the receiver **1010** may support obtaining information by receiving signals via one or more antennas. Additionally, or alternatively, the receiver **1010** may support obtaining information by receiving signals via one or more wired (e.g., electrical, fiber optic) interfaces, wireless interfaces, or any combination thereof.

[0198] The transmitter **1015** may provide a means for outputting (e.g., transmitting, providing, conveying, sending) information generated by other components of the device **1005**. For example, the transmitter **1015** may output information such as user data, control information, or any combination thereof (e.g., I/Q samples, symbols, packets, protocol data units, service data units) associated with various channels (e.g., control channels, data channels, information channels, channels associated with a protocol stack). In some examples, the transmitter **1015** may support outputting information by transmitting signals via one or more antennas. Additionally, or alternatively, the transmitter **1015** may support outputting information by transmitting signals via one or more wired (e.g., electrical, fiber optic) interfaces, wireless interfaces, or any combination thereof. In some examples, the transmitter **1015** and the receiver **1010** may be co-located in a transceiver, which may include or be coupled with a modem.

[0199] The device **1005**, or various components thereof, may be an example of means for

performing various aspects of mitigating jitter in communications as described herein. For example, the communications manager **1020** may include a frame generation manager **1025**, a packet buffering manager **1030**, a periodic burst manager **1035**, an TSC messaging manager **1040**, or any combination thereof. The communications manager **1020** may be an example of aspects of a communications manager **920** as described herein. In some examples, the communications manager **1020**, or various components thereof, may be configured to perform various operations (e.g., receiving, obtaining, monitoring, outputting, transmitting) using or otherwise in cooperation with the receiver **1010**, the transmitter **1015**, or both. For example, the communications manager **1020** may receive information from the receiver **1010**, send information to the transmitter **1015**, or be integrated in combination with the receiver **1010**, the transmitter **1015**, or both to obtain information, output information, or perform various other operations as described herein.

[0200] In some examples, the device **905** may be an example of an AS, as described herein.

Accordingly, the communications manager **1020** of the AS may support wireless communications in accordance with examples as disclosed herein. The frame generation manager **1025** is capable of, configured to, or operable to support a means for generating one or more PDU sets of a first periodic burst transmission, the first periodic burst transmission corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets. The packet buffering manager **1030** is capable of, configured to, or operable to support a means for buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window. The periodic burst manager **1035** is capable of, configured to, or operable to support a means for outputting the one or more PDU sets based on expiration of the first duration and prior to the first delivery deadline.

[0201] Additionally, or alternatively, the device **905** may be an example of a RAN, as described herein. Accordingly, the communications manager **1020** of the RAN may support wireless communications in accordance with examples as disclosed herein. The TSC messaging manager **1040** is capable of, configured to, or operable to support a means for obtaining a TSC message indicating a jitter window associated with one or more PDU sets of a first periodic burst transmission, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets, and where the one or more PDU sets of the first periodic burst transmission correspond to a first delivery deadline at a UE. The periodic burst manager **1035** is capable of, configured to, or operable to support a means for obtaining at least a portion of the one or more PDU sets of the first periodic burst transmission at a first time, where the first time corresponds to at least a threshold percentage of the jitter window. The periodic burst manager **1035** is capable of, configured to, or operable to support a means for outputting the one or more PDU sets prior to the first delivery deadline.

[0202] Additionally, or alternatively, the device **905** may be an example of a UPF, as described herein. Accordingly, the communications manager **1020** may support wireless communications in accordance with examples as disclosed herein. The periodic burst manager **1035** is capable of, configured to, or operable to support a means for obtaining one or more PDU sets of a first periodic burst transmission, the first periodic burst corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets. The packet buffering manager **1030** is capable of, configured to, or operable to support a means for buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window. The periodic burst manager **1035** is capable of, configured to, or operable to support a means for outputting the one or more PDU sets based on expiration of the first duration and prior to the first delivery deadline.

[0203] Additionally, or alternatively, may be an example of a RAN, as described herein.

Accordingly, the communications manager **1020** of the RAN may support wireless

communications in accordance with examples as disclosed herein. The periodic burst manager **1035** is capable of, configured to, or operable to support a means for obtaining one or more PDU sets of a first periodic burst transmission, the first periodic burst corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets. The packet buffering manager **1030** is capable of, configured to, or operable to support a means for buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window. The periodic burst manager **1035** is capable of, configured to, or operable to support a means for outputting the one or more PDU sets based on expiration of the first duration and prior to the first delivery deadline.

[0204] FIG. **11** shows a block diagram **1100** of a communications manager **1120** that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure. The communications manager **1120** may be an example of aspects of a communications manager **920**, a communications manager **1020**, or both, as described herein. The communications manager **1020** may be a component within an AS, a UPF, a RAN, or a network entity **105**, as described herein. The communications manager **1120**, or various components thereof, may be an example of means for performing various aspects of mitigating jitter in communications as described herein. For example, the communications manager **1120** may include a frame generation manager **1125**, a packet buffering manager **1130**, a periodic burst manager **1135**, an TSC messaging manager **1140**, an assistance information manager **1145**, a jitter measurement manager **1150**, a jitter estimation manager **1155**, a DRX manager **1160**, a jitter storage manager **1165**, or any combination thereof. Each of these components, or components or subcomponents thereof (e.g., one or more processors, one or more memories), may communicate, directly or indirectly, with one another (e.g., via one or more buses). The communications may include communications within a protocol layer of a protocol stack, communications associated with a logical channel of a protocol stack (e.g., between protocol layers of a protocol stack, within a device, component, or virtualized component associated with a network entity **105**, between devices, components, or virtualized components associated with a network entity **105**), or any combination thereof.

[0205] In some examples, the communications manager **1020** may be included within an AS, described herein. Accordingly, the communications manager **1120** of the AS may support wireless communications in accordance with examples as disclosed herein. The frame generation manager **1125** is capable of, configured to, or operable to support a means for generating one or more PDU sets of a first periodic burst transmission, the first periodic burst transmission corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets. The packet buffering manager **1130** is capable of, configured to, or operable to support a means for buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window. The periodic burst manager **1135** is capable of, configured to, or operable to support a means for outputting the one or more PDU sets based on expiration of the first duration and prior to the first delivery deadline.

[0206] In some examples, the assistance information manager **1145** is capable of, configured to, or operable to support a means for obtaining control signaling including assistance information associated with the UE, the assistance information indicating the first delivery deadline, a periodicity associated with the first periodic burst transmission, the jitter window, the first duration, or any combination thereof, where buffering at least the portion of the one or more PDU sets is in accordance with the assistance information.

[0207] In some examples, the TSC messaging manager **1140** is capable of, configured to, or operable to support a means for outputting a TSC message including an indication of the jitter window based on generating the one or more PDU sets of the first periodic burst transmission.

[0208] In some examples, to support buffering the portion of the one or more PDU sets, the packet

buffering manager **1130** is capable of, configured to, or operable to support a means for starting a timer in response to generating the one or more PDU sets, the timer being set to the first duration, where buffering the portion of the one or more PDU sets is based on starting the timer, and where outputting the one or more PDU sets is based on expiration of the timer.

[0209] In some examples, to support buffering the portion of the one or more PDU sets, the packet buffering manager **1130** is capable of, configured to, or operable to support a means for identifying a start time associated with the one or more PDU sets in response to generating the one or more PDU sets. In some examples, to support buffering the portion of the one or more PDU sets, the packet buffering manager **1130** is capable of, configured to, or operable to support a means for delaying the portion of the one or more PDU sets from the identified start time for the first duration, where outputting the one or more PDU sets is based on the expiration of the first duration.

[0210] In some examples, the jitter measurement manager **1150** is capable of, configured to, or operable to support a means for measuring a second jitter window associated with communication of a second periodic burst transmission, the second periodic burst transmission being prior to the first periodic burst transmission. In some examples, the jitter estimation manager **1155** is capable of, configured to, or operable to support a means for estimating the jitter window associated with the first periodic burst transmission based on the second jitter window.

[0211] In some examples, the jitter storage manager **1165** is capable of, configured to, or operable to support a means for storing the second jitter window based on measuring the second jitter window, where estimating the jitter window is based on the storing.

[0212] In some examples, the second jitter window is stored according to an XR configuration in a memory of the AS.

[0213] In some examples, the jitter measurement manager **1150** is capable of, configured to, or operable to support a means for measuring a respective jitter window associated with communication of one or more additional periodic burst transmissions, the one or more additional periodic burst transmissions being prior to the first periodic burst transmission and after the second periodic burst transmission. In some examples, the jitter estimation manager **1155** is capable of, configured to, or operable to support a means for updating the second jitter window stored in the AS based on measuring the respective jitter windows of each of the one or more additional periodic burst transmissions, where estimating the jitter window is based on updating the second jitter window.

[0214] In some examples, the second jitter window is based on an operating condition of the AS, a data rate of the second periodic burst transmission, a periodicity of the second periodic burst transmission, or a combination thereof.

[0215] In some examples, the jitter measurement manager **1150** is capable of, configured to, or operable to support a means for measuring a duration associated with generating the one or more PDU sets of the first periodic burst transmission. In some examples, the jitter estimation manager **1155** is capable of, configured to, or operable to support a means for estimating the jitter window based on the duration associated with generating the one or more PDU sets.

[0216] In some examples, estimating the jitter window using the duration is based on the duration being less than a threshold duration.

[0217] In some examples, the duration associated with generating the one or more PDU sets of the first periodic burst transmission is based on a data rate associated with the first periodic burst transmission, a periodicity of the first periodic burst transmission, or a combination thereof.

[0218] In some examples, the jitter measurement manager **1150** is capable of, configured to, or operable to support a means for identifying a second jitter window associated with a second periodic burst transmission, the second periodic burst transmission being prior to the first periodic burst transmission. In some examples, the jitter measurement manager **1150** is capable of, configured to, or operable to support a means for measuring a duration associated with generating the one or more PDU sets of the first periodic burst transmission. In some examples, the jitter

estimation manager **1155** is capable of, configured to, or operable to support a means for estimating the jitter window based on the duration associated with generating the one or more PDU sets and the second jitter window associated with the second periodic burst transmission.

[0219] In some examples, to support generating the one or more PDU sets, the frame generation manager **1125** is capable of, configured to, or operable to support a means for rendering at least a portion of a video frame associated with XR communications. In some examples, to support generating the one or more PDU sets, the frame generation manager **1125** is capable of, configured to, or operable to support a means for encoding, based on the rendering, the portion of the video frame. In some examples, to support generating the one or more PDU sets, the frame generation manager **1125** is capable of, configured to, or operable to support a means for packetizing, based on the encoding, the portion of the video frame to obtain the one or more PDU sets of the first periodic burst transmission.

[0220] In some examples, the first arrival time is an average arrival time measured across one or more periodic burst transmissions, the one or more periodic burst transmissions occurring prior to the first periodic burst transmission.

[0221] Additionally, or alternatively, the communications manager **1020** may be included within a RAN, as described herein. Accordingly, the communications manager **1120** of the RAN may support wireless communications in accordance with examples as disclosed herein. The TSC messaging manager **1140** is capable of, configured to, or operable to support a means for obtaining a TSC message indicating a jitter window associated with one or more PDU sets of a first periodic burst transmission, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets, and where the one or more PDU sets of the first periodic burst transmission correspond to a first delivery deadline at a UE. In some examples, the periodic burst manager **1135** is capable of, configured to, or operable to support a means for obtaining at least a portion of the one or more PDU sets of the first periodic burst transmission at a first time, where the first time corresponds to at least a threshold percentage of the jitter window. In some examples, the periodic burst manager **1135** is capable of, configured to, or operable to support a means for outputting the one or more PDU sets prior to the first delivery deadline.

[0222] In some examples, the DRX manager **1160** is capable of, configured to, or operable to support a means for outputting control signaling indicating one or more parameters corresponding to a DRX associated with the UE based on the jitter window, where the one or more parameters include an offset and an on-duration.

[0223] In some examples, the offset is based on the jitter window, a remaining jitter, a jitter associated with communications between the RAN and a UPF, a first margin, or a combination thereof, the remaining jitter corresponding to a difference between the jitter window and the threshold percentage of the jitter window, and the on-duration is based on the remaining jitter, the jitter associated with the communications between an AS and the UPF, a second margin, or a combination thereof.

[0224] In some examples, the TSC message further indicates the remaining jitter, the jitter associated with the communications between an AS and the UPF, or both.

[0225] In some examples, the DRX manager **1160** is capable of, configured to, or operable to support a means for measuring the remaining jitter, the jitter associated with the communications between an AS and the UPF, or both, where the DRX is based on the measuring.

[0226] Additionally, or alternatively, the communications manager **1020** may be included as part of a UPF, as described herein. Accordingly, the communications manager **1120** of the UPF may support wireless communications in accordance with examples as disclosed herein. In some examples, the periodic burst manager **1135** is capable of, configured to, or operable to support a means for obtaining one or more PDU sets of a first periodic burst transmission, the first periodic burst corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more

PDU sets. In some examples, the packet buffering manager **1130** is capable of, configured to, or operable to support a means for buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window. In some examples, the periodic burst manager **1135** is capable of, configured to, or operable to support a means for outputting the one or more PDU sets based on expiration of the first duration and prior to the first delivery deadline.

[0227] Additionally, or alternatively, the communications manager **1020** may be included as part of a RAN, as described herein. Accordingly, the communications manager **1120** of the RAN may support wireless communications in accordance with examples as disclosed herein. In some examples, the periodic burst manager **1135** is capable of, configured to, or operable to support a means for obtaining one or more PDU sets of a first periodic burst transmission, the first periodic burst corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets. In some examples, the packet buffering manager **1130** is capable of, configured to, or operable to support a means for buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window. In some examples, the periodic burst manager **1135** is capable of, configured to, or operable to support a means for outputting the one or more PDU sets based on expiration of the first duration and prior to the first delivery deadline.

[0228] FIG. **12** shows a diagram of a system **1200** including a device **1205** that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure. The device **1205** may be an example of or include components of a device **905**, a device **1005**, an AS, a UPF, a RAN, or a network entity **105** as described herein. The device **1205** may communicate with other network devices or network equipment such as one or more of the network entities **105**, UEs **115**, or any combination thereof. The communications may include communications over one or more wired interfaces, over one or more wireless interfaces, or any combination thereof. The device **1205** may include components that support outputting and obtaining communications, such as a communications manager **1220**, a transceiver **1210**, one or more antennas **1215**, at least one memory **1225**, code **1230**, and at least one processor **1235**. These components may be in electronic communication or otherwise coupled (e.g., operatively, communicatively, functionally, electronically, electrically) via one or more buses (e.g., a bus **1240**).

[0229] The transceiver **1210** may support bi-directional communications via wired links, wireless links, or both as described herein. In some examples, the transceiver **1210** may include a wired transceiver and may communicate bi-directionally with another wired transceiver. Additionally, or alternatively, in some examples, the transceiver **1210** may include a wireless transceiver and may communicate bi-directionally with another wireless transceiver. In some examples, the device **1205** may include one or more antennas **1215**, which may be capable of transmitting or receiving wireless transmissions (e.g., concurrently). The transceiver **1210** may also include a modem to modulate signals, to provide the modulated signals for transmission (e.g., by one or more antennas **1215**, by a wired transmitter), to receive modulated signals (e.g., from one or more antennas **1215**, from a wired receiver), and to demodulate signals. In some implementations, the transceiver **1210** may include one or more interfaces, such as one or more interfaces coupled with the one or more antennas **1215** that are configured to support various receiving or obtaining operations, or one or more interfaces coupled with the one or more antennas **1215** that are configured to support various transmitting or outputting operations, or a combination thereof. In some implementations, the transceiver **1210** may include or be configured for coupling with one or more processors or one or more memory components that are operable to perform or support operations based on received or obtained information or signals, or to generate information or other signals for transmission or other outputting, or any combination thereof. In some implementations, the transceiver **1210**, or the transceiver **1210** and the one or more antennas **1215**, or the transceiver **1210** and the one or more

antennas **1215** and one or more processors or one or more memory components (e.g., the at least one processor **1235**, the at least one memory **1225**, or both), may be included in a chip or chip assembly that is installed in the device **1205**. In some examples, the transceiver **1210** may be operable to support communications via one or more communications links (e.g., communication link(s) **125**, backhaul communication link(s) **120**, a midhaul communication link **162**, a fronthaul communication link **168**).

[0230] The at least one memory **1225** may include RAM, ROM, or any combination thereof. The at least one memory **1225** may store computer-readable, computer-executable, or processor-executable code, such as the code **1230**. The code **1230** may include instructions that, when executed by one or more of the at least one processor **1235**, cause the device **1205** to perform various functions described herein. The code **1230** may be stored in a non-transitory computer-readable medium such as system memory or another type of memory. In some cases, the code **1230** may not be directly executable by a processor of the at least one processor **1235** but may cause a computer (e.g., when compiled and executed) to perform functions described herein. In some cases, the at least one memory **1225** may include, among other things, a BIOS which may control basic hardware or software operation such as the interaction with peripheral components or devices. In some examples, the at least one processor **1235** may include multiple processors and the at least one memory **1225** may include multiple memories. One or more of the multiple processors may be coupled with one or more of the multiple memories which may, individually or collectively, be configured to perform various functions herein (for example, as part of a processing system).

[0231] The at least one processor **1235** may include one or more intelligent hardware devices (e.g., one or more general-purpose processors, one or more DSPs, one or more central processing units (CPUs), one or more graphics processing units (GPUs), one or more neural processing units (NPU) (also referred to as neural network processors or deep learning processors (DLP)), one or more microcontrollers, one or more ASICs, one or more FPGAs, one or more programmable logic devices, discrete gate or transistor logic, one or more discrete hardware components, or any combination thereof). In some cases, the at least one processor **1235** may be configured to operate a memory array using a memory controller. In some other cases, a memory controller may be integrated into one or more of the at least one processor **1235**. The at least one processor **1235** may be configured to execute computer-readable instructions stored in a memory (e.g., one or more of the at least one memory **1225**) to cause the device **1205** to perform various functions (e.g., functions or tasks supporting mitigating jitter in communications). For example, the device **1205** or a component of the device **1205** may include at least one processor **1235** and at least one memory **1225** coupled with one or more of the at least one processor **1235**, the at least one processor **1235** and the at least one memory **1225** configured to perform various functions described herein. The at least one processor **1235** may be an example of a cloud-computing platform (e.g., one or more physical nodes and supporting software such as operating systems, virtual machines, or container instances) that may host the functions (e.g., by executing code **1230**) to perform the functions of the device **1205**. The at least one processor **1235** may be any one or more suitable processors capable of executing scripts or instructions of one or more software programs stored in the device **1205** (such as within one or more of the at least one memory **1225**). In some examples, the at least one processor **1235** may include multiple processors and the at least one memory **1225** may include multiple memories. One or more of the multiple processors may be coupled with one or more of the multiple memories, which may, individually or collectively, be configured to perform various functions herein. In some examples, the at least one processor **1235** may be a component of a processing system, which may refer to a system (such as a series) of machines, circuitry (including, for example, one or both of processor circuitry (which may include the at least one processor **1235**) and memory circuitry (which may include the at least one memory **1225**)), or components, that receives or obtains inputs and processes the inputs to produce, generate, or obtain a set of outputs. The processing system may be configured to perform one or more of the functions described

herein. For example, the at least one processor **1235** or a processing system including the at least one processor **1235** may be configured to, configurable to, or operable to cause the device **1205** to perform one or more of the functions described herein. Further, as described herein, being “configured to,” being “configurable to,” and being “operable to” may be used interchangeably and may be associated with a capability, when executing code stored in the at least one memory **1225** or otherwise, to perform one or more of the functions described herein.

[0232] In some examples, a bus **1240** may support communications of (e.g., within) a protocol layer of a protocol stack. In some examples, a bus **1240** may support communications associated with a logical channel of a protocol stack (e.g., between protocol layers of a protocol stack), which may include communications performed within a component of the device **1205**, or between different components of the device **1205** that may be co-located or located in different locations (e.g., where the device **1205** may refer to a system in which one or more of the communications manager **1220**, the transceiver **1210**, the at least one memory **1225**, the code **1230**, and the at least one processor **1235** may be located in one of the different components or divided between different components).

[0233] In some examples, the communications manager **1220** may manage aspects of communications with a core network **130** (e.g., via one or more wired or wireless backhaul links). For example, the communications manager **1220** may manage the transfer of data communications for client devices, such as one or more UEs **115**. In some examples, the communications manager **1220** may manage communications with one or more other network devices, and may include a controller or scheduler for controlling communications with UEs **115** (e.g., in cooperation with the one or more other network devices). In some examples, the communications manager **1220** may support an X2 interface within an LTE/LTE-A wireless communications network technology to provide communication between network entities **105**.

[0234] In some examples, the device **1205** may be an example of an AS, as described herein. Accordingly, the communications manager **1220** of the AS may support wireless communications in accordance with examples as disclosed herein. For example, the communications manager **1220** is capable of, configured to, or operable to support a means for generating one or more PDU sets of a first periodic burst transmission, the first periodic burst transmission corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets. The communications manager **1220** is capable of, configured to, or operable to support a means for buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window. The communications manager **1220** is capable of, configured to, or operable to support a means for outputting the one or more PDU sets based on expiration of the first duration and prior to the first delivery deadline.

[0235] Additionally, or alternatively, the device **1205** may be an example of a RAN, as described herein. Accordingly, the communications manager **1220** of the RAN may support wireless communications in accordance with examples as disclosed herein. For example, the communications manager **1220** is capable of, configured to, or operable to support a means for obtaining a TSC message indicating a jitter window associated with one or more PDU sets of a first periodic burst transmission, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets, and where the one or more PDU sets of the first periodic burst transmission correspond to a first delivery deadline at a UE. The communications manager **1220** is capable of, configured to, or operable to support a means for obtaining at least a portion of the one or more PDU sets of the first periodic burst transmission at a first time, where the first time corresponds to at least a threshold percentage of the jitter window. The communications manager **1220** is capable of, configured to, or operable to support a means for outputting the one or more PDU sets prior to the first delivery deadline.

[0236] Additionally, or alternatively, the device **1205** may be an example of a UPF, as described

herein. Accordingly, the communications manager **1220** of the UPF may support wireless communications in accordance with examples as disclosed herein. For example, the communications manager **1220** is capable of, configured to, or operable to support a means for obtaining one or more PDU sets of a first periodic burst transmission, the first periodic burst corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets. The communications manager **1220** is capable of, configured to, or operable to support a means for buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window. The communications manager **1220** is capable of, configured to, or operable to support a means for outputting the one or more PDU sets based on expiration of the first duration and prior to the first delivery deadline.

[0237] Additionally, or alternatively, the device **1205** may be an example of a RAN, as described herein. Accordingly, the communications manager **1220** of the RAN may support wireless communications in accordance with examples as disclosed herein. For example, the communications manager **1220** is capable of, configured to, or operable to support a means for obtaining one or more PDU sets of a first periodic burst transmission, the first periodic burst corresponding to a first delivery deadline at a UE during a jitter window, where the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets. The communications manager **1220** is capable of, configured to, or operable to support a means for buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window. The communications manager **1220** is capable of, configured to, or operable to support a means for outputting the one or more PDU sets based on expiration of the first duration and prior to the first delivery deadline.

[0238] By including or configuring the communications manager **1220** in accordance with examples as described herein, the device **1205** may support techniques for mitigating jitter in wireless communications, which may reduce power consumption at a UE.

[0239] In some examples, the communications manager **1220** may be configured to perform various operations (e.g., receiving, obtaining, monitoring, outputting, transmitting) using or otherwise in cooperation with the transceiver **1210**, the one or more antennas **1215** (e.g., where applicable), or any combination thereof. Although the communications manager **1220** is illustrated as a separate component, in some examples, one or more functions described with reference to the communications manager **1220** may be supported by or performed by the transceiver **1210**, one or more of the at least one processor **1235**, one or more of the at least one memory **1225**, the code **1230**, or any combination thereof (for example, by a processing system including at least a portion of the at least one processor **1235**, the at least one memory **1225**, the code **1230**, or any combination thereof). For example, the code **1230** may include instructions executable by one or more of the at least one processor **1235** to cause the device **1205** to perform various aspects of mitigating jitter in communications as described herein, or the at least one processor **1235** and the at least one memory **1225** may be otherwise configured to, individually or collectively, perform or support such operations.

[0240] FIG. **13** shows a flowchart illustrating a method **1300** that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure. The operations of the method **1300** may be implemented by a network entity, such as an AS, or its components as described herein. For example, the operations of the method **1300** may be performed by a network entity as described with reference to FIGS. **1** through **12**. In some examples, a network entity may execute a set of instructions to control the functional elements of the network entity to perform the described functions. Additionally, or alternatively, the network entity may perform aspects of the described functions using special-purpose hardware.

[0241] At **1305**, the method may include generating one or more PDU sets (e.g., PDU sets **235** as described herein with reference to FIG. **2**) of a first periodic burst transmission (e.g., bursts **230** as described herein with reference to FIG. **2**), the first periodic burst transmission corresponding to a first delivery deadline (e.g., delivery deadlines **305** as described herein with reference to FIG. **3**) at a UE during a jitter window, (e.g., the jitter window **315** as described herein with reference to FIG. **3**), where the jitter window spans a time period prior to and after a first arrival time (e.g., the average arrival time **317** as described herein with reference to FIGS. **3** and **4**) associated with the one or more PDU sets. The operations of **1305** may be performed in accordance with examples as disclosed herein, such as disclosed in operation **525** of FIG. **5**. In some examples, aspects of the operations of **1305** may be performed by a frame generation manager **1125** as described with reference to FIG. **11**.

[0242] At **1310**, the method may include buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window. The operations of **1310** may be performed in accordance with examples as disclosed herein, such as disclosed in operation **530** of FIG. **5**. In some examples, aspects of the operations of **1310** may be performed by a packet buffering manager **1130** as described with reference to FIG. **11**.

[0243] At **1315**, the method may include outputting the one or more PDU sets based on expiration of the first duration and prior to the first delivery deadline. The operations of **1315** may be performed in accordance with examples as disclosed herein, such as disclosed in operation **540** of FIG. **5**. In some examples, aspects of the operations of **1315** may be performed by a periodic burst manager **1135** as described with reference to FIG. **11**.

[0244] FIG. **14** shows a flowchart illustrating a method **1400** that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure. The operations of the method **1400** may be implemented by a network entity, such as an AS, or its components as described herein. For example, the operations of the method **1400** may be performed by a network entity as described with reference to FIGS. **1** through **12**. In some examples, a network entity may execute a set of instructions to control the functional elements of the network entity to perform the described functions. Additionally, or alternatively, the network entity may perform aspects of the described functions using special-purpose hardware.

[0245] At **1405**, the method may include obtaining control signaling including assistance information associated with a UE, the assistance information indicating a first delivery deadline (e.g., the delivery deadlines **305** as described herein with reference to FIGS. **3** and **4**), a periodicity associated with a first periodic burst transmission (e.g., the bursts **230** as described herein with reference to FIG. **2**), a jitter window (e.g., the jitter window **315** as described herein with reference to FIG. **3**), a first duration, or any combination thereof. The operations of **1405** may be performed in accordance with examples as disclosed herein, such as disclosed in operation **515** of FIG. **5**. In some examples, aspects of the operations of **1405** may be performed by an assistance information manager **1145** as described with reference to FIG. **11**.

[0246] At **1410**, the method may include generating one or more PDU sets of the first periodic burst transmission, the first periodic burst transmission corresponding to the first delivery deadline at the UE during the jitter window, where the jitter window spans a time period prior to and after a first arrival time (e.g., the average arrival time **317** as disclosed herein with reference to FIGS. **3** and **4**) associated with the one or more PDU sets. The operations of **1410** may be performed in accordance with examples as disclosed herein, such as disclosed in operation **520** of FIG. **5**. In some examples, aspects of the operations of **1410** may be performed by a frame generation manager **1125** as described with reference to FIG. **11**.

[0247] At **1415**, the method may include buffering at least a portion of the one or more PDU sets for the first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window. The operations of **1415** may be performed in accordance with

examples as disclosed herein, such as disclosed in operation **530** of FIG. 5. In some examples, aspects of the operations of **1415** may be performed by a packet buffering manager **1130** as described with reference to FIG. 11.

[0248] At **1420**, the method may include outputting the one or more PDU sets based on expiration of the first duration and prior to the first delivery deadline. The operations of **1420** may be performed in accordance with examples as disclosed herein, such as in operation **540** of FIG. 5. In some examples, aspects of the operations of **1420** may be performed by a periodic burst manager **1135** as described with reference to FIG. 11.

[0249] FIG. 15 shows a flowchart illustrating a method **1500** that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure. The operations of the method **1500** may be implemented by a network entity, such as a RAN, or its components as described herein. For example, the operations of the method **1500** may be performed by a network entity as described with reference to FIGS. 1 through 12. In some examples, a network entity may execute a set of instructions to control the functional elements of the network entity to perform the described functions. Additionally, or alternatively, the network entity may perform aspects of the described functions using special-purpose hardware.

[0250] At **1505**, the method may include obtaining a TSC message indicating a jitter window (e.g., the jitter window **315** as described herein with reference to FIG. 3) associated with one or more PDU sets (e.g., PDU sets **235** as described herein with reference to FIG. 2) of a first periodic burst transmission (e.g., the burst **230** as described herein with reference to FIG. 2), where the jitter window spans a time period prior to and after a first arrival time (e.g., the average arrival time **317** as described herein with reference to FIGS. 3 and 4) associated with the one or more PDU sets, and where the one or more PDU sets of the first periodic burst transmission correspond to a first delivery deadline (e.g., the delivery deadline **305** as described herein with reference to FIGS. 3 and 4) at a UE. The operations of **1505** may be performed in accordance with examples as disclosed herein, such as disclosed in operation **550** of FIG. 5. In some examples, aspects of the operations of **1505** may be performed by an TSC messaging manager **1140** as described with reference to FIG. 11.

[0251] At **1510**, the method may include obtaining at least a portion of the one or more PDU sets of the first periodic burst transmission at a first time (e.g., such as the time of arrival of the bursts **230** as described herein with reference to FIGS. 3 and 4), where the first time corresponds to at least a threshold percentage of the jitter window. The operations of **1510** may be performed in accordance with examples as disclosed herein, such as disclosed in operation **555** of FIG. 5. In some examples, aspects of the operations of **1510** may be performed by a periodic burst manager **1135** as described with reference to FIG. 11.

[0252] At **1515**, the method may include outputting the one or more PDU sets prior to the first delivery deadline. The operations of **1515** may be performed in accordance with examples as disclosed herein, such as disclosed in operation **570** of FIG. 5. In some examples, aspects of the operations of **1515** may be performed by a periodic burst manager **1135** as described with reference to FIG. 11.

[0253] FIG. 16 shows a flowchart illustrating a method **1600** that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure. The operations of the method **1600** may be implemented by a network entity, such as a RAN, or its components as described herein. For example, the operations of the method **1600** may be performed by a network entity as described with reference to FIGS. 1 through 12. In some examples, a network entity may execute a set of instructions to control the functional elements of the network entity to perform the described functions. Additionally, or alternatively, the network entity may perform aspects of the described functions using special-purpose hardware.

[0254] At **1605**, the method may include obtaining a TSC message indicating a jitter window (e.g., the jitter window **315** as described herein with reference to FIG. 3) associated with one or more

PDU sets (e.g., PDU sets **235** as described herein with reference to FIG. 2) of a first periodic burst transmission (e.g., the burst **230** as described herein with reference to FIG. 2), where the jitter window spans a time period prior to and after a first arrival time (e.g., the average arrival time **317** as described herein with reference to FIGS. 3 and 4) associated with the one or more PDU sets, and where the one or more PDU sets of the first periodic burst transmission correspond to a first delivery deadline (e.g., the delivery deadline **305** as described herein with reference to FIGS. 3 and 4) at a UE. The operations of **1605** may be performed in accordance with examples as disclosed herein, such as disclosed in operation **550** of FIG. 5. In some examples, aspects of the operations of **1605** may be performed by an TSC messaging manager **1140** as described with reference to FIG. 11.

[0255] At **1610**, the method may include obtaining at least a portion of the one or more PDU sets of the first periodic burst transmission at a first time, where the first time corresponds to at least a threshold percentage of the jitter window. The operations of **1610** may be performed in accordance with examples as disclosed herein, such as disclosed in operation **555** of FIG. 5. In some examples, aspects of the operations of **1610** may be performed by a periodic burst manager **1135** as described with reference to FIG. 11.

[0256] At **1615**, the method may include outputting control signaling indicating one or more parameters corresponding to a DRX (e.g., the eCDRX as disclosed herein with reference to FIGS. 3 and 4) associated with the UE based on the jitter window, where the one or more parameters include an offset (e.g., the offset **325** as described herein with reference to FIG. 4) and an on-duration (e.g., the on-duration **330** as described herein with reference to FIG. 4). The operations of **1615** may be performed in accordance with examples as disclosed herein, such as disclosed in operation **565** of FIG. 5. In some examples, aspects of the operations of **1615** may be performed by a DRX manager **1160** as described with reference to FIG. 11.

[0257] At **1620**, the method may include outputting the one or more PDU sets prior to the first delivery deadline. The operations of **1620** may be performed in accordance with examples as disclosed herein, such as disclosed in operation **570** of FIG. 5. In some examples, aspects of the operations of **1620** may be performed by a periodic burst manager **1135** as described with reference to FIG. 11.

[0258] FIG. 17 shows a flowchart illustrating a method **1700** that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure. The operations of the method **1700** may be implemented by a network entity, such as a UPF, or its components as described herein. For example, the operations of the method **1700** may be performed by a network entity as described with reference to FIGS. 1 through 12. In some examples, a network entity may execute a set of instructions to control the functional elements of the network entity to perform the described functions. Additionally, or alternatively, the network entity may perform aspects of the described functions using special-purpose hardware.

[0259] At **1705**, the method may include obtaining one or more PDU sets (e.g., PDU sets **235** as described herein with reference to FIG. 2) of a first periodic burst transmission (e.g., the burst **230** as described herein with reference to FIGS. 2 and 3), the first periodic burst corresponding to a first delivery deadline (e.g., the delivery deadline **305** as described herein with reference to FIGS. 3 and 4) at a UE during a jitter window (e.g., the jitter window **315** as described herein with reference to FIG. 3), where the jitter window spans a time period prior to and after a first arrival time (e.g., the average arrival time **317** as described herein with reference to FIGS. 3 and 4) associated with the one or more PDU sets. The operations of **1705** may be performed in accordance with examples as disclosed herein, such as disclosed in operation **730** of FIG. 7. In some examples, aspects of the operations of **1705** may be performed by a periodic burst manager **1135** as described with reference to FIG. 11.

[0260] At **1710**, the method may include buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold

percentage of the jitter window. The operations of **1710** may be performed in accordance with examples as disclosed herein, such as disclosed in operation **740** of FIG. 7. In some examples, aspects of the operations of **1710** may be performed by a packet buffering manager **1130** as described with reference to FIG. 11.

[0261] At **1715**, the method may include outputting the one or more PDU sets based on expiration of the first duration and prior to the first delivery deadline. The operations of **1715** may be performed in accordance with examples as disclosed herein, such as disclosed in operation **755** of FIG. 7. In some examples, aspects of the operations of **1715** may be performed by a periodic burst manager **1135** as described with reference to FIG. 11.

[0262] FIG. 18 shows a flowchart illustrating a method **1800** that supports mitigating jitter in communications in accordance with one or more aspects of the present disclosure. The operations of the method **1800** may be implemented by a network entity, such as a RAN, or its components as described herein. For example, the operations of the method **1800** may be performed by a network entity as described with reference to FIGS. 1 through 12. In some examples, a network entity may execute a set of instructions to control the functional elements of the network entity to perform the described functions. Additionally, or alternatively, the network entity may perform aspects of the described functions using special-purpose hardware.

[0263] At **1805**, the method may include obtaining one or more PDU sets (e.g., PDU sets **235** as described herein with reference to FIG. 2) of a first periodic burst transmission (e.g., the burst **230** as described herein with reference to FIGS. 2 and 3), the first periodic burst corresponding to a first delivery deadline (e.g., the delivery deadline **305** as described herein with reference to FIGS. 3 and 4) at a UE during a jitter window (e.g., the jitter window **315** as described herein with reference to FIG. 3), where the jitter window spans a time period prior to and after a first arrival time (e.g., the average arrival time **317** as described herein with reference to FIGS. 3 and 4) associated with the one or more PDU sets. The operations of **1805** may be performed in accordance with examples as disclosed herein, such as disclosed in operation **830** of FIG. 8. In some examples, aspects of the operations of **1805** may be performed by a periodic burst manager **1135** as described with reference to FIG. 11.

[0264] At **1810**, the method may include buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, where the first duration corresponds to a threshold percentage of the jitter window. The operations of **1810** may be performed in accordance with examples as disclosed herein, such as disclosed in operation **840** of FIG. 8. In some examples, aspects of the operations of **1810** may be performed by a packet buffering manager **1130** as described with reference to FIG. 11.

[0265] At **1815**, the method may include outputting the one or more PDU sets based on expiration of the first duration and prior to the first delivery deadline. The operations of **1815** may be performed in accordance with examples as disclosed herein, such as disclosed in operation **850** of FIG. 8. In some examples, aspects of the operations of **1815** may be performed by a periodic burst manager **1135** as described with reference to FIG. 11.

[0266] The following provides an overview of aspects of the present disclosure:

[0267] Aspect 1: A method for wireless communications at an AS, comprising: generating one or more PDU sets of a first periodic burst transmission, the first periodic burst transmission corresponding to a first delivery deadline at a UE during a jitter window, wherein the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets; buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, wherein the first duration corresponds to a threshold percentage of the jitter window; and outputting the one or more PDU sets upon expiration of the first duration and prior to the first delivery deadline.

[0268] Aspect 2: The method of aspect 1, further comprising: obtaining control signaling comprising assistance information associated with the UE, the assistance information indicating the

first delivery deadline, a periodicity associated with the first periodic burst transmission, the jitter window, the first duration, or any combination thereof, wherein buffering at least the portion of the one or more PDU sets is in accordance with the assistance information.

[0269] Aspect 3: The method of any of aspects 1 through 2, further comprising: outputting a TSC message comprising an indication of the jitter window based at least in part on generating the one or more PDU sets of the first periodic burst transmission.

[0270] Aspect 4: The method of any of aspects 1 through 3, wherein buffering the portion of the one or more PDU sets comprises: starting a timer in response to generating the one or more PDU sets, the timer being set to the first duration, wherein buffering the portion of the one or more PDU sets is based at least in part on starting the timer, and wherein outputting the one or more PDU sets is based at least in part on expiration of the timer.

[0271] Aspect 5: The method of any of aspects 1 through 3, wherein buffering the portion of the one or more PDU sets comprises: identifying a start time associated with the one or more PDU sets in response to generating the one or more PDU sets; and delaying the portion of the one or more PDU sets from the identified start time for the first duration, wherein outputting the one or more PDU sets is based at least in part on the expiration of the first duration.

[0272] Aspect 6: The method of any of aspects 1 through 5, further comprising: measuring a second jitter window associated with communication of a second periodic burst transmission, the second periodic burst transmission being prior to the first periodic burst transmission; and estimating the jitter window associated with the first periodic burst transmission based at least in part on the second jitter window.

[0273] Aspect 7: The method of aspect 6, further comprising: storing the second jitter window based at least in part on measuring the second jitter window, wherein estimating the jitter window is based at least in part on the storing.

[0274] Aspect 8: The method of aspect 7, wherein the second jitter window is stored according to an XR configuration in a memory of the AS.

[0275] Aspect 9: The method of any of aspects 7 through 8, further comprising: measuring a respective jitter window associated with communication of one or more additional periodic burst transmissions, the one or more additional periodic burst transmissions being prior to the first periodic burst transmission and after the second periodic burst transmission; and updating the second jitter window stored in the AS based at least in part on measuring the respective jitter windows of each of the one or more additional periodic burst transmissions, wherein estimating the jitter window is based at least in part on updating the second jitter window.

[0276] Aspect 10: The method of any of aspects 6 through 9, wherein the second jitter window is based at least in part on an operating condition of the AS, a data rate of the second periodic burst transmission, a periodicity of the second periodic burst transmission, or a combination thereof.

[0277] Aspect 11: The method of any of aspects 1 through 10, further comprising: measuring a duration associated with generating the one or more PDU sets of the first periodic burst transmission; and estimating the jitter window based at least in part on the duration associated with generating the one or more PDU sets.

[0278] Aspect 12: The method of aspect 11, wherein estimating the jitter window using the duration is based at least in part on the duration being less than a threshold duration.

[0279] Aspect 13: The method of any of aspects 11 through 12, wherein the duration associated with generating the one or more PDU sets of the first periodic burst transmission is based at least in part on a data rate associated with the first periodic burst transmission, a periodicity of the first periodic burst transmission, or a combination thereof.

[0280] Aspect 14: The method of any of aspects 1 through 13, further comprising: identifying a second jitter window associated with a second periodic burst transmission, the second periodic burst transmission being prior to the first periodic burst transmission; measuring a duration associated with generating the one or more PDU sets of the first periodic burst transmission; and

estimating the jitter window based at least in part on the duration associated with generating the one or more PDU sets and the second jitter window associated with the second periodic burst transmission.

[0281] Aspect 15: The method of any of aspects 1 through 14, wherein generating the one or more PDU sets comprises: rendering at least a portion of a video frame associated with XR communications; encoding, based at least in part on the rendering, the portion of the video frame; and packetizing, based at least in part on the encoding, the portion of the video frame to obtain the one or more PDU sets of the first periodic burst transmission.

[0282] Aspect 16: The method of any of aspects 1 through 15, wherein the first arrival time is an average arrival time measured across one or more periodic burst transmissions, the one or more periodic burst transmissions occurring prior to the first periodic burst transmission.

[0283] Aspect 17: A method for wireless communications at a RAN, comprising: obtaining a TSC message indicating a jitter window associated with one or more PDU sets of a first periodic burst transmission, wherein the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets, and wherein the one or more PDU sets of the first periodic burst transmission correspond to a first delivery deadline at a UE; obtaining at least a portion of the one or more PDU sets of the first periodic burst transmission at a first time, wherein the first time corresponds to at least a threshold percentage of the jitter window; and outputting the one or more PDU sets prior to the first delivery deadline.

[0284] Aspect 18: The method of aspect 17, further comprising: outputting control signaling indicating one or more parameters corresponding to a DRX cycle associated with the UE based at least in part on the jitter window, wherein the one or more parameters comprise an offset and an on-duration.

[0285] Aspect 19: The method of aspect 18, wherein the offset is based at least in part on the jitter window, a remaining jitter, a jitter associated with communications between the RAN and a UPF, a first margin, or a combination thereof, the remaining jitter corresponding to a difference between the jitter window and the threshold percentage of the jitter window, and the on-duration is based at least in part on the remaining jitter, the jitter associated with the communications between the RAN and the UPF, a second margin, or a combination thereof.

[0286] Aspect 20: The method of aspect 19, wherein the TSC message further indicates the remaining jitter, the jitter associated with the communications between the RAN and the UPF, or both.

[0287] Aspect 21: The method of any of aspects 19, further comprising: measuring the remaining jitter, the jitter associated with the communications between the RAN and the UPF, or both, wherein the DRX cycle is based at least in part on the measuring.

[0288] Aspect 22: A method for wireless communications at a UPF, comprising: obtaining one or more PDU sets of a first periodic burst transmission, the first periodic burst corresponding to a first delivery deadline at a UE during a jitter window, wherein the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets; buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, wherein the first duration corresponds to a threshold percentage of the jitter window; and outputting the one or more PDU sets upon based at least in part on expiration of the first duration and prior to the first delivery deadline.

[0289] Aspect 23: A method for wireless communications at a RAN, comprising: obtaining one or more PDU sets of a first periodic burst transmission, the first periodic burst corresponding to a first delivery deadline at a UE during a jitter window, wherein the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets; buffering at least a portion of the one or more PDU sets for a first duration of the jitter window, wherein the first duration corresponds to a threshold percentage of the jitter window; and outputting the one or more PDU sets upon based at least in part on expiration of the first duration and prior to the first delivery

deadline.

[0290] Aspect 24: An AS for wireless communications, comprising one or more memories storing processor-executable code, and one or more processors coupled with the one or more memories and individually or collectively operable to execute the code to cause the AS to perform a method of any of aspects 1 through 16.

[0291] Aspect 25: An AS for wireless communications, comprising at least one means for performing a method of any of aspects 1 through 16.

[0292] Aspect 26: A non-transitory computer-readable medium storing code for wireless communications, the code comprising instructions executable by one or more processors to perform a method of any of aspects 1 through 16.

[0293] Aspect 27: A RAN for wireless communications, comprising one or more memories storing processor-executable code, and one or more processors coupled with the one or more memories and individually or collectively operable to execute the code to cause the RAN to perform a method of any of aspects 17 through 21.

[0294] Aspect 28: A RAN for wireless communications, comprising at least one means for performing a method of any of aspects 17 through 21.

[0295] Aspect 29: A non-transitory computer-readable medium storing code for wireless communications, the code comprising instructions executable by one or more processors to perform a method of any of aspects 17 through 21.

[0296] Aspect 30: A UPF for wireless communications, comprising one or more memories storing processor-executable code, and one or more processors coupled with the one or more memories and individually or collectively operable to execute the code to cause the UPF to perform a method of the aspect 22.

[0297] Aspect 31: A UPF for wireless communications, comprising at least one means for performing a method of the aspect 22.

[0298] Aspect 32: A non-transitory computer-readable medium storing code for wireless communications, the code comprising instructions executable by one or more processors to perform a method of the aspect 22.

[0299] Aspect 33: A RAN for wireless communications, comprising one or more memories storing processor-executable code, and one or more processors coupled with the one or more memories and individually or collectively operable to execute the code to cause the RAN to perform a method of the aspect 23.

[0300] Aspect 34: A RAN for wireless communications, comprising at least one means for performing a method of the aspect 23.

[0301] Aspect 35: A non-transitory computer-readable medium storing code for wireless communications, the code comprising instructions executable by one or more processors to perform a method of any of the aspect 23.

[0302] It should be noted that the methods described herein describe possible implementations. The operations and the steps may be rearranged or otherwise modified and other implementations are possible. Further, aspects from two or more of the methods may be combined.

[0303] Although aspects of an LTE, LTE-A, LTE-A Pro, or NR system may be described for purposes of example, and LTE, LTE-A, LTE-A Pro, or NR terminology may be used in much of the description, the techniques described herein are applicable beyond LTE, LTE-A, LTE-A Pro, or NR networks. For example, the described techniques may be applicable to various other wireless communications systems such as Ultra Mobile Broadband (UMB), Institute of Electrical and Electronics Engineers (IEEE) 802.11 (Wi-Fi), IEEE 802.16 (WiMAX), IEEE 802.20, Flash-OFDM, as well as other systems and radio technologies not explicitly mentioned herein.

[0304] Information and signals described herein may be represented using any of a variety of different technologies and techniques. For example, data, instructions, commands, information, signals, bits, symbols, and chips that may be referenced throughout the description may be

represented by voltages, currents, electromagnetic waves, magnetic fields or particles, optical fields or particles, or any combination thereof.

[0305] The various illustrative blocks and components described in connection with the disclosure herein may be implemented or performed using a general-purpose processor, a DSP, an ASIC, a CPU, a graphics processing unit (GPU), a neural processing unit (NPU), an FPGA or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor but, in the alternative, the processor may be any processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of computing devices (e.g., a combination of a DSP and a microprocessor, multiple microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration). Any functions or operations described herein as being capable of being performed by a processor may be performed by multiple processors that, individually or collectively, are capable of performing the described functions or operations.

[0306] The functions described herein may be implemented using hardware, software executed by a processor, firmware, or any combination thereof. If implemented using software executed by a processor, the functions may be stored as or transmitted using one or more instructions or code of a computer-readable medium. Other examples and implementations are within the scope of the disclosure and appended claims. For example, due to the nature of software, functions described herein may be implemented using software executed by a processor, hardware, firmware, hardwiring, or combinations of any of these. Features implementing functions may also be physically located at various positions, including being distributed such that portions of functions are implemented at different physical locations.

[0307] Computer-readable media includes both non-transitory computer storage media and communication media including any medium that facilitates transfer of a computer program from one location to another. A non-transitory storage medium may be any available medium that may be accessed by a general-purpose or special-purpose computer. By way of example, and not limitation, non-transitory computer-readable media may include RAM, ROM, electrically erasable programmable ROM (EEPROM), flash memory, compact disk (CD) ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other non-transitory medium that may be used to carry or store desired program code means in the form of instructions or data structures and that may be accessed by a general-purpose or special-purpose computer or a general-purpose or special-purpose processor. Also, any connection is properly termed a computer-readable medium. For example, if the software is transmitted from a website, server, or other remote source using a coaxial cable, fiber optic cable, twisted pair, digital subscriber line (DSL), or wireless technologies such as infrared, radio, and microwave, then the coaxial cable, fiber optic cable, twisted pair, DSL, or wireless technologies such as infrared, radio, and microwave are included in the definition of computer-readable medium. Disk and disc, as used herein, include CD, laser disc, optical disc, digital versatile disc (DVD), floppy disk, and Blu-ray disc. Disks may reproduce data magnetically, and discs may reproduce data optically using lasers. Combinations of the above are also included within the scope of computer-readable media. Any functions or operations described herein as being capable of being performed by a memory may be performed by multiple memories that, individually or collectively, are capable of performing the described functions or operations.

[0308] As used herein, including in the claims, “or” as used in a list of items (e.g., a list of items prefaced by a phrase such as “at least one of” or “one or more of”) indicates an inclusive list such that, for example, a list of at least one of A, B, or C means A or B or C or AB or AC or BC or ABC (i.e., A and B and C). Also, as used herein, the phrase “based on” shall not be construed as a reference to a closed set of conditions. For example, an example step that is described as “based on condition A” may be based on both a condition A and a condition B without departing from the

scope of the present disclosure. In other words, as used herein, the phrase “based on” shall be construed in the same manner as the phrase “based at least in part on.”

[0309] As used herein, including in the claims, the article “a” before a noun is open-ended and understood to refer to “at least one” of those nouns or “one or more” of those nouns. Thus, the terms “a,” “at least one,” “one or more,” and “at least one of one or more” may be interchangeable. For example, if a claim recites “a component” that performs one or more functions, each of the individual functions may be performed by a single component or by any combination of multiple components. Thus, the term “a component” having characteristics or performing functions may refer to “at least one of one or more components” having a particular characteristic or performing a particular function. Subsequent reference to a component introduced with the article “a” using the terms “the” or “said” may refer to any or all of the one or more components. For example, a component introduced with the article “a” may be understood to mean “one or more components,” and referring to “the component” subsequently in the claims may be understood to be equivalent to referring to “at least one of the one or more components.” Similarly, subsequent reference to a component introduced as “one or more components” using the terms “the” or “said” may refer to any or all of the one or more components. For example, referring to “the one or more components” subsequently in the claims may be understood to be equivalent to referring to “at least one of the one or more components.”

[0310] The term “determine” or “determining” encompasses a variety of actions and, therefore, “determining” can include calculating, computing, processing, deriving, investigating, looking up (such as via looking up in a table, a database, or another data structure), ascertaining, and the like. Also, “determining” can include receiving (e.g., receiving information), accessing (e.g., accessing data stored in memory), and the like. Also, “determining” can include resolving, obtaining, selecting, choosing, establishing, and other such similar actions.

[0311] In the appended figures, similar components or features may have the same reference label. Further, various components of the same type may be distinguished by following the reference label by a dash and a second label that distinguishes among the similar components. If just the first reference label is used in the specification, the description is applicable to any one of the similar components having the same first reference label irrespective of the second reference label or other subsequent reference label.

[0312] The description set forth herein, in connection with the appended drawings, describes example configurations and does not represent all the examples that may be implemented or that are within the scope of the claims. The term “example” used herein means “serving as an example, instance, or illustration” and not “preferred” or “advantageous over other examples.” The detailed description includes specific details for the purpose of providing an understanding of the described techniques. These techniques, however, may be practiced without these specific details. In some figures, known structures and devices are shown in block diagram form in order to avoid obscuring the concepts of the described examples.

[0313] The description herein is provided to enable a person having ordinary skill in the art to make or use the disclosure. Various modifications to the disclosure will be apparent to a person having ordinary skill in the art, and the generic principles defined herein may be applied to other variations without departing from the scope of the disclosure. Thus, the disclosure is not limited to the examples and designs described herein but is to be accorded the broadest scope consistent with the principles and novel features disclosed herein.

Claims

1. An application server, comprising: one or more processors; one or more memories coupled with the one or more processors; and one or more processor-readable instructions stored in the one or more memories and executable by the one or more processors individually or collectively to cause

the application server to: generate one or more packet data unit (PDU) sets of a first periodic burst transmission, the first periodic burst transmission corresponding to a first delivery deadline at a user equipment (UE) during a jitter window, wherein the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets; buffer at least a portion of the one or more PDU sets for a first duration of the jitter window, wherein the first duration corresponds to a threshold percentage of the jitter window; and output the one or more PDU sets based at least in part on expiration of the first duration and prior to the first delivery deadline.

2. The application server of claim 1, wherein the one or more processors are individually or collectively further operable to execute the one or more processor-readable instructions to cause the application server to: obtain control signaling comprising assistance information associated with the UE, the assistance information indicating the first delivery deadline, a periodicity associated with the first periodic burst transmission, the jitter window, the first duration, or any combination thereof, wherein buffering at least the portion of the one or more PDU sets is in accordance with the assistance information.

3. The application server of claim 1, wherein the one or more processors are individually or collectively further operable to execute the one or more processor-readable instructions to cause the application server to: output a time sensitive communication (TSC) message comprising an indication of the jitter window based at least in part on generating the one or more PDU sets of the first periodic burst transmission.

4. The application server of claim 1, wherein, to buffer the portion of the one or more PDU sets, the one or more processors are individually or collectively operable to execute the one or more processor-readable instructions to cause the application server to: start a timer in response to generating the one or more PDU sets, the timer being set to the first duration, wherein buffering the portion of the one or more PDU sets is based at least in part on starting the timer, and wherein outputting the one or more PDU sets is based at least in part on an expiration of the timer.

5. The application server of claim 1, wherein, to buffer the portion of the one or more PDU sets, the one or more processors are individually or collectively operable to execute the one or more processor-readable instructions to cause the application server to: identify a start time associated with the one or more PDU sets in response to generating the one or more PDU sets; and delay the portion of the one or more PDU sets from the identified start time for the first duration, wherein outputting the one or more PDU sets is based at least in part on the expiration of the first duration.

6. The application server of claim 1, wherein the one or more processors are individually or collectively further operable to execute the one or more processor-readable instructions to cause the application server to: measure a second jitter window associated with communication of a second periodic burst transmission, the second periodic burst transmission being prior to the first periodic burst transmission; and estimate the jitter window associated with the first periodic burst transmission based at least in part on the second jitter window.

7. The application server of claim 6, wherein the one or more processors are individually or collectively further operable to execute the one or more processor-readable instructions to cause the application server to: store the second jitter window based at least in part on measuring the second jitter window, wherein estimating the jitter window is based at least in part on the storing.

8. The application server of claim 7, wherein the second jitter window is stored according to an extended reality (XR) configuration in a memory of the application server.

9. The application server of claim 7, wherein the one or more processors are individually or collectively further operable to execute the one or more processor-readable instructions to cause the application server to: measure a respective jitter window associated with communication of one or more additional periodic burst transmissions, the one or more additional periodic burst transmissions being prior to the first periodic burst transmission and after the second periodic burst transmission; and update the second jitter window stored in the application server based at least in part on measuring the respective jitter windows of each of the one or more additional periodic burst

transmissions, wherein estimating the jitter window is based at least in part on updating the second jitter window.

10. The application server of claim 1, wherein the one or more processors are individually or collectively further operable to execute the one or more processor-readable instructions to cause the application server to: measure a duration associated with generating the one or more PDU sets of the first periodic burst transmission; and estimate the jitter window based at least in part on the duration associated with generating the one or more PDU sets.

11. The application server of claim 1, wherein the one or more processors are individually or collectively further operable to execute the one or more processor-readable instructions to cause the application server to: identify a second jitter window associated with a second periodic burst transmission, the second periodic burst transmission being prior to the first periodic burst transmission; measure a duration associated with generating the one or more PDU sets of the first periodic burst transmission; and estimate the jitter window based at least in part on the duration associated with generating the one or more PDU sets and the second jitter window associated with the second periodic burst transmission.

12. The application server of claim 1, wherein, to generate the one or more PDU sets, the one or more processors are individually or collectively operable to execute the one or more processor-readable instructions to cause the application server to: render at least a portion of a video frame associated with extended reality (XR) communications; encode, based at least in part on the rendering, the portion of the video frame; and packetizing, based at least in part on the encoding, the portion of the video frame to obtain the one or more PDU sets of the first periodic burst transmission.

13. A user plane function (UPF), comprising: one or more processors; one or more memories coupled with the one or more processors; and one or more processor-readable instructions stored in the one or more memories and executable by the one or more processors individually or collectively to cause the UPF to: obtain one or more packet data unit (PDU) sets of a first periodic burst transmission, the first periodic burst transmission corresponding to a first delivery deadline at a user equipment (UE) during a jitter window, wherein the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets; buffer at least a portion of the one or more PDU sets for a first duration of the jitter window, wherein the first duration corresponds to a threshold percentage of the jitter window; and output the one or more PDU sets based at least in part on expiration of the first duration and prior to the first delivery deadline.

14. The UPF of claim 13, wherein the one or more processors are individually or collectively further operable to execute the one or more processor-readable instructions to cause the UPF to: obtain control signaling comprising assistance information associated with the UE, the assistance information indicating the first delivery deadline, a periodicity associated with the first periodic burst transmission, the jitter window, the first duration, or any combination thereof, wherein buffering at least the portion of the one or more PDU sets is in accordance with the assistance information.

15. The UPF of claim 13, wherein the one or more processors are individually or collectively further operable to execute the one or more processor-readable instructions to cause the UPF to: obtain a time sensitive communication (TSC) message comprising an indication of the jitter window based at least in part on generating the one or more PDU sets of the first periodic burst transmission.

16. The UPF of claim 13, wherein, to buffer the portion of the one or more PDU sets, the one or more processors are individually or collectively operable to execute the one or more processor-readable instructions to cause the UPF to: start a timer in response to generating the one or more PDU sets, the timer being set to the first duration, wherein buffering the portion of the one or more PDU sets is based at least in part on starting the timer, and wherein outputting the one or more PDU sets is based at least in part on an expiration of the timer.

17. The UPF of claim 13, wherein, to buffer the portion of the one or more PDU sets, the one or more processors are individually or collectively operable to execute the one or more processor-readable instructions to cause the UPF to: identify a start time associated with the one or more PDU sets in response to generating the one or more PDU sets; and delay the portion of the one or more PDU sets from the identified start time for the first duration, wherein outputting the one or more PDU sets is based at least in part on the expiration of the first duration.

18. A radio access network (RAN), comprising: one or more processors; one or more memories coupled with the one or more processors; and one or more processor-readable instructions stored in the one or more memories and executable by the one or more processors individually or collectively to cause the RAN to: obtain one or more packet data unit (PDU) sets of a first periodic burst transmission, the first periodic burst transmission corresponding to a first delivery deadline at a user equipment (UE) during a jitter window, wherein the jitter window spans a time period prior to and after a first arrival time associated with the one or more PDU sets; buffer at least a portion of the one or more PDU sets for a first duration of the jitter window, wherein the first duration corresponds to a threshold percentage of the jitter window; and output the one or more PDU sets based at least in part on expiration of the first duration and prior to the first delivery deadline.

19. The RAN of claim 18, wherein the one or more processors are individually or collectively further operable to execute the one or more processor-readable instructions to cause the RAN to: output control signaling indicating one or more parameters corresponding to a discontinuous reception cycle associated with the UE based at least in part on the jitter window, wherein the one or more parameters comprise an offset and an on-duration.

20. The RAN of claim 18, wherein the one or more processors are individually or collectively further operable to execute the one or more processor-readable instructions to cause the RAN to: obtain control signaling comprising assistance information associated with the UE, the assistance information indicating the first delivery deadline, a periodicity associated with the first periodic burst transmission, the jitter window, the first duration, or any combination thereof, wherein buffering at least the portion of the one or more PDU sets is in accordance with the assistance information.
