

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250287152

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Zhou; Keyong et al.

SPEAKER

Abstract

A speaker includes a frame, a magnetic circuit system with a magnetic gap, and a vibration system, the vibration system includes a diaphragm assembly, a voice coil assembly, a first elastic wave assembly fixed, and a second elastic wave assembly, the diaphragm assembly includes a dome, a suspension, and a connecting wall extending from the dome to the voice coil assembly, the connecting wall includes a connecting portion connected with the dome the suspension, and a first suspension portion and a second suspension portion located at a side away from the dome, one end of the first elastic wave assembly away from the frame is connected with the first suspension portion, one end of the second elastic wave assembly away from the frame is connected with the second suspension portion. Compared with the related art, the speaker disclosed by the present disclosure could improve space utilization.

Inventors: Zhou; Keyong (Changzhou, CN), Mao; Yuanxiang (Changzhou, CN), Zhen; Guofang (Changzhou, CN), Yang; Hao (Changzhou, CN)

Applicant: AAC Microtech (Changzhou) Co., Ltd. (Changzhou, CN)

Family ID: 96949806

Appl. No.: 18/764346

Filed: July 04, 2024

Related U.S. Application Data

parent WO continuation PCT/CN2024/080708 20240308 PENDING child US 18764346

Publication Classification

Int. Cl.: H04R7/20 (20060101); H04R7/12 (20060101); H04R9/02 (20060101)

U.S. Cl.:

Background/Summary

FIELD OF THE INVENTION

[0001] The invention relates to the technical field of electro-acoustic transducers, in particular to speaker.

BACKGROUND

[0002] In the vehicle-mounted speaker industry, a traditional cone speaker is generally used. At present, the automobiles have higher requirements for high sound quality, flexible layout, low power consumption, and small vibration of speakers.

[0003] A vehicle-mounted speaker of the related art includes a frame, a vibration system fixed with the frame, and a magnetic circuit system with a magnetic gap. The magnetic circuit system drives the vibration system to vibrate and produce sounds, the vibration system includes a diaphragm fixed with the frame, and a voice coil assembly which is fixed with the diaphragm and inserted into the magnetic gap to drive the diaphragm to vibrate and produce sounds. However, this speaker has the problems of large structural size, low efficiency, and great low-frequency vibration.

[0004] Therefore, it is desired to provide a novel speaker to solve the above problems.

SUMMARY

[0005] The present disclosure is to provide an ultra-thin speaker that improves space utilization and has a well-balanced vibration system.

[0006] For achieving the object mentioned above, the disclosure provides a speaker comprising a frame, a magnetic circuit system with a magnetic gap, and a vibration system fixed with the frame, the vibration system includes a diaphragm assembly, a voice coil assembly driving the diaphragm assembly to vibrate and sound, a first elastic wave assembly fixed with the frame, and a second elastic wave assembly fixed with the frame and spaced apart from the first elastic wave assembly, the diaphragm assembly comprises a dome in a middle, a suspension surrounding the dome and fixed with the frame, and a connecting wall extending from the dome to the voice coil assembly, the connecting wall is integrally formed, the connecting wall comprises a connecting portion connected with the dome and the suspension, and a first suspension portion and a second suspension portion located at a side away from the dome, the first suspension portion and the second suspension portion are spaced apart from each other, one end of the first elastic wave assembly away from the frame is connected with the first suspension portion, one end of the second elastic wave assembly away from the frame is connected with the second suspension portion.

[0007] Further, the connecting portion is provided with an opening, the connecting portion is connected with the dome and the opening is covered by the dome, the first suspension portion and the second suspension portion are located symmetrically on opposite sides of the opening, respectively.

[0008] Further, the connecting wall further comprises a first fixing portion connected with the connecting portion and the first suspension portion, the first fixing portion comprises a first vertical segment extending from the connecting portion to the voice coil assembly and connected with the first suspension portion, and a first horizontal segment extending from the first vertical segment to the opening and connected with the connecting portion, a length of the first vertical segment is different from a length of the first horizontal segment.

[0009] Further, there is a plurality of first fixing portions, a first reinforce portion is formed between every two adjacent first fixing portions.

[0010] Further, the connecting wall further comprises a second fixing portion connected with the

connecting portion and the second suspension portion, the second fixing portion comprises a second vertical segment extending from the connecting portion to the voice coil assembly and connected with the second suspension portion, and a second horizontal segment extending from the second vertical segment to the opening and connected with the connecting portion, a length of the second vertical segment is different from a length of the second horizontal segment.

[0011] Further, there is a plurality of second fixing portions, a second reinforce portion is formed between every two adjacent second fixing portions.

[0012] Further, the voice coil assembly comprises a square voice coil movably accommodated in the magnetic gap and a skeleton connected with the square voice coil and the diaphragm assembly, a first outlet portion and a second outlet portion are provided on a side of the skeleton away from the square voice coil, the first outlet portion and the second outlet portion are symmetrical.

[0013] Further, the speaker further comprises a first external pad and a second external pad embedded in the frame and connected with an external circuit, a first braided wire connected with the first external pad and the first outlet portion, and a second braided wire connected with the second external pad and the second outlet portion, the first braided wire and the second braided wire are located in the frame.

[0014] Further, the magnetic circuit system comprises a magnetic bowl, a magnet accommodated in the magnetic bowl, and a pole plate attached to the magnet, the square voice coil is movably accommodated in the magnetic gap between the pole plate and the magnetic bowl.

[0015] Further, the frame is arranged in a rectangular shape, the frame comprises a main body with a receiving cavity for accommodating the magnetic circuit system, a first mounting portion formed in the receiving cavity and located at one side of the main body, and a second mounting portion formed in the receiving cavity and located on the other side of the main body, the first elastic wave assembly is mounted on the first mounting portion, the second elastic wave assembly is mounted on the second mounting portion.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0016] In order to explain the technical solutions of the embodiments of the present disclosure more clearly, accompanying drawings used to describe the embodiments are briefly introduced below. It is evident that the drawings in the following description are only concerned with some embodiments of the present disclosure. For those skilled in the art, in a case where no inventive effort is made, other drawings may be obtained based on these drawings.

[0017] FIG. 1 is an isometric view of a speaker of the present disclosure;

[0018] FIG. 2 is a partial isometric view of the speaker of the present disclosure;

[0019] FIG. 3 is an exploded view of the speaker of the present disclosure;

[0020] FIG. 4 is a cross-sectional view along the line A-A in FIG. 1;

[0021] FIG. 5 is an isometric view of a first view angle of a connecting wall; and

[0022] FIG. 6 is an isometric view of a second view angle of the connecting wall.

DESCRIPTION OF THE EMBODIMENTS

[0023] The present disclosure will be further illustrated with reference to the accompanying drawings. It shall be noted that the elements of similar structures or functions are represented by like reference numerals throughout the figures. The embodiments described herein are not intended as an exhaustive illustration or description of various other embodiments or as a limitation on the scope of the claims or the scope of some other embodiments that are apparent to one of ordinary skills in the art in view of the embodiments described in the Application. In addition, an illustrated embodiment need not have all the aspects or advantages shown.

[0024] As shown in the FIGS. 1-4, the present invention discloses a speaker, which includes a

frame **10**, a vibration system **20**, and a magnetic circuit system **30** with a magnetic gap **301**. The magnetic circuit system **30** is used for driving the vibration system **20** vibrate and produce sounds. The vibration system **20** and the magnetic circuit system **30** are fixed with the frame **10**.
[0025] As shown in the FIGS. **1-4**, the vibration system **20** includes a diaphragm assembly **21** fixed with the frame **10** and a voice coil assembly **22** driving the diaphragm assembly **21** to vibrate and produce sounds.

[0026] As shown in the FIGS. **2-4**, the diaphragm assembly **21** includes a dome **211** in a middle, a suspension **212** surrounding the dome **211** and fixed with the frame **10**, and a connecting wall **213** extending from the dome **211** to the voice coil assembly **22**. The connecting wall **213** is integrally formed, the connecting wall **213** includes a connecting portion **2131** connected the dome **211** to the suspension **212**, and a first suspension portion **2132** and a second suspension portion **2132** located at a side away from the dome **211**, the first suspension portion **2132** and the second suspension **2133** are spaced apart from each other.

[0027] As shown in the FIGS. **2-4**, the vibration system **20** further includes a first elastic wave assembly **23** fixed with the frame **10** and a second elastic wave assembly **24** fixed with the frame **10** and spaced apart from the first elastic wave assembly **23**. One end of the first elastic wave assembly **23** away from the frame **10** is connected with the first suspension portion **2132**, one end of the second elastic wave assembly **24** away from the frame **10** is connected with the second suspension portion **2133**.

[0028] In this embodiment, the first elastic wave assembly **23** and the second elastic wave assembly **24** make reasonable use of an internal space of the speaker, the height of the speaker is reduced, and thinning development is facilitated. Applying this speaker to the vehicle as an in-vehicle speaker can fulfil the parameter requirements of in-vehicle speakers for high sound quality of the horn, small size and flexible layout, low power consumption and small vibration. In addition, the first suspension portion **2132** cooperates with the first elastic wave assembly **23**, and the second suspension portion **2133** cooperates with the second elastic wave assembly **24**, which improve the balance of the vibration system and improve the acoustic performance of the speaker.

[0029] In some embodiments, as shown in the FIGS. **1-3**, the frame **10** is arranged in a rectangular shape, therefore, the speaker is arranged in a rectangular shape. The frame **10** includes a main body **12** with a receiving cavity **11** for accommodating the magnetic circuit system **30**, a first mounting portion **13** formed in the receiving cavity **11** and located at one side of the main body **12**, and a second mounting portion **14** formed in the receiving cavity **11** and located at the other side of the main body **12**, the first elastic wave assembly **23** is mounted on the first mounting portion **13**, the second elastic wave assembly **24** is mounted on the second mounting portion **14**. In this embodiment, the speaker reasonably utilizes the internal space of the speaker, has a compact layout, and thinning development is facilitated.

[0030] As shown in the FIG. **2** and FIG. **3**, the first elastic wave assembly **23** and the second elastic wave assembly **24** have the same structure which are in runway shape. The first elastic wave assembly **23** includes a first elastic wave fixing portion **231**, a first elastic wave edge portion **232**, a second elastic fixing portion **233**, a first elastic wave connection portion **234** for connecting the first elastic wave fixing portion **231** with the first elastic wave edge portion **232**, and a second elastic wave connection portion **235** for connecting the first elastic wave edge portion **232** and the second elastic fixing portion **233**, the first elastic fixing portion **231** is fixed with the frame **10**. The second elastic fixing portion **233** is connected with the first suspension portion **2132**. In one achievable embodiment, the second elastic wave assembly **24** includes a third elastic wave fixing portion **241**, a second elastic wave edge portion **242**, the fourth elastic fixing portion **243**, a third elastic wave connection portion **244** for connecting the third elastic wave fixing portion **241** with the second elastic wave edge portion **242**, and a fourth elastic wave connection portion **245** for connecting the second elastic wave edge portion **242** and the fourth elastic fixing portion **243**, the third elastic fixing portion **241** is fixed with the frame **10**. The fourth elastic fixing portion **243** is

connected with the second suspension portion **2133**.

[0031] As shown in the FIGS. **2-4**, a cross section of the first elastic connecting portion **234**, the second elastic connecting portion **235**, the third elastic connecting portion **244**, and the fourth elastic connecting portion **245** along vibration directions are both waved. The waved elastic wave assemblies have higher vibration attenuation performance, which are conducive to improve the stability of vibration of the vibration system **20**, thus improving the product performance of the speaker.

[0032] As shown in the FIG. **5** and FIG. **6**, the connecting portion **2131** is provided with an opening **201** configured to the dome **211**, the connecting portion **2131** is connected with the dome **211** and the opening **201** is covered by the dome **201**, the first suspension portion **2132** and the second suspension portion **2132** are located symmetrically on opposite sides of the opening.

[0033] The connecting wall **213** further includes a first fixing portion **2134** connected with the connecting portion **2131** and the first suspension portion **2132**, the first fixing portion **2134** includes a first vertical segment **1** extending from the connecting portion **2131** to the voice coil assembly **22** and connected with the first suspension portion **2132**, and a first horizontal segment **2** extending from the first vertical segment **1** to the opening **201** and connected with the connecting portion **2031**, a length of the first vertical segment **1** is different from a length of the first horizontal segment **2**. There is a plurality of first fixing portions **2134**, a first reinforce portion **2135** is formed between every two adjacent first fixing portions **2134**.

[0034] The connecting wall **213** further comprises a second fixing portion **2136** connected with the connecting portion **2131** and the second suspension portion **2133**, the second fixing portion **2136** comprises a second vertical segment **3** extending from the connecting portion **2131** to the voice coil assembly **22** and connected with the second suspension portion **2133**, and a second horizontal segment **4** extending from the second vertical segment **3** to the opening **2201** and connected with the connecting portion **2131**, a length of the second vertical segment **3** is different from a length of the second horizontal segment **4**. There is a plurality of second fixing portions **2136**, a second reinforce portion **2137** is formed between every two adjacent second fixing portions **2136**.

[0035] Cross-sections of the first fixing portion **2134** and the second fixing portion **2136** may be of regular shapes or irregular shapes, and the first reinforce portion **2135** and the second reinforcing portion **2137** may be sheet-like reinforcement bars, which are capable of providing good high-frequency structural strength, thereby improving acoustic performance of the speaker.

[0036] As shown in the FIGS. **2-4**, the voice coil assembly **22** includes a square voice coil **221** movably accommodated in the magnetic gap **301** and a skeleton **222** connected with the square voice coil **221** and the diaphragm assembly **21**, a first outlet portion **2221** and a second outlet portion **2222** are provided on a side of the skeleton **222** away from the square voice coil **221**, the first outlet portion **2221** and the second outlet portion **2222** are symmetrical. This embodiment exits the line from the upper side edge of the skeleton, which is conducive to the improvement of space utilization, and at the same time reduces the difficulty of wire management.

[0037] As shown in the FIG. **2** and FIG. **3**, the speaker further includes a first external pad **40** and a second external pad **50** embedded in the frame **10** and connected to an external circuit, a first braided wire **60** connecting with the first external pad **50** and the first outlet portion **2221**, and a second braided wire **70** connecting with the second external pad **50** and the second outlet portion **2222**, the first braided wire **60** and the second braided wire **70** are located in the frame **10**. The first braided wire **60** and the second braided wire **70** of this embodiment form a natural curvature on the upper side of the skeleton **222**, which is able to ensure that the braided wire does not interfere with the square voice coil **221** and the frame **10** during movement, and at the same time, the braided wires are provided inside the frame **10**, and the braided wires are guided to the outside through the external pads, so that the braided wires are not exposed to the outside, so as to improve the safety and service life of the speaker.

[0038] As shown in the FIG. **3** and FIG. **4**, the magnetic circuit system **30** includes a magnetic bowl

31, a magnet 32 accommodated in the magnetic bowl 31, and a pole plate 33 attached to the magnet 32, the square voice coil 221 is movably accommodated in the magnetic gap 301 between the pole plate 33 and the magnetic bowl 31. The square voice coil 221 of this embodiment moves up and down in the magnetic gap 301 between the pole plate 33 and the magnetic bowl 31, in conjunction with the square magnetic circuit, the internal space of the speaker could be fully utilized, a higher level of magnetic energy is provided compared to a circular magnetic circuit system, therefore, the sensitivity of the speaker could be increased.

[0039] It should be appreciated by those skilled in the art that various modifications are possible without departing from the spirit or scope of the present invention. The embodiments illustrated above should not be interpreted as limits to the present invention, and the scope of the invention is to be determined by reference to the claims that follow.

Claims

1. A speaker comprising: a frame; a magnetic circuit system with a magnetic gap; and a vibration system fixed with the frame, comprising a diaphragm assembly, a voice coil assembly driving the diaphragm assembly to vibrate and sound, a first elastic wave assembly fixed with the frame, and a second elastic wave assembly fixed with the frame and spaced apart from the first elastic wave assembly; wherein the diaphragm assembly comprises a dome in a middle, a suspension surrounding the dome and fixed with the frame, and a connecting wall extending from the dome to the voice coil assembly, the connecting wall is integrally formed, the connecting wall comprises a connecting portion connected with the dome and the suspension, and a first suspension portion and a second suspension portion located at a side away from the dome, the first suspension portion and the second suspension portion are spaced apart from each other, one end of the first elastic wave assembly away from the frame is connected with the first suspension portion, one end of the second elastic wave assembly away from the frame is connected with the second suspension portion.
2. The speaker as described in claim 1, wherein the connecting portion is provided with an opening, the connecting portion is connected with the dome and the opening is covered by the dome, the first suspension portion and the second suspension portion are located symmetrically on opposite sides of the opening, respectively.
3. The speaker as described in claim 2, wherein the connecting wall further comprises a first fixing portion connected with the connecting portion and the first suspension portion, the first fixing portion comprises a first vertical segment extending from the connecting portion to the voice coil assembly and connected with the first suspension portion, and a first horizontal segment extending from the first vertical segment to the opening and connected with the connecting portion, a length of the first vertical segment is different from a length of the first horizontal segment.
4. The speaker as described in claim 3, wherein there is a plurality of first fixing portions, a first reinforce portion is formed between every two adjacent first fixing portions.
5. The speaker as described in claim 2, wherein the connecting wall further comprises a second fixing portion connected with the connecting portion and the second suspension portion, the second fixing portion comprises a second vertical segment extending from the connecting portion to the voice coil assembly and connected with the second suspension portion, and a second horizontal segment extending from the second vertical segment to the opening and connected with the connecting portion, a length of the second vertical segment is different from a length of the second horizontal segment.
6. The speaker as described in claim 5, wherein there is a plurality of second fixing portions, a second reinforce portion is formed between every two adjacent second fixing portions.
7. The speaker as described in claim 1, wherein the voice coil assembly comprises a square voice coil movably accommodated in the magnetic gap and a skeleton connected with the square voice coil and the diaphragm assembly, a first outlet portion and a second outlet portion are provided on a

side of the skeleton away from the square voice coil, the first outlet portion and the second outlet portion are symmetrical.

8. The speaker as described in claim 7, wherein further comprises a first external pad and a second external pad embedded in the frame and connected with an external circuit, a first braided wire connected with the first external pad and the first outlet portion, and a second braided wire connected with the second external pad and the second outlet portion, the first braided wire and the second braided wire are located in the frame.

9. The speaker as described in claim 7, wherein the magnetic circuit system comprises a magnetic bowl, a magnet accommodated in the magnetic bowl, and a pole plate attached to the magnet, the square voice coil is movably accommodated in the magnetic gap between the pole plate and the magnetic bowl.

10. The speaker as described in claim 1, wherein the frame is arranged in a rectangular shape, the frame comprises a main body with a receiving cavity for accommodating the magnetic circuit system, a first mounting portion formed in the receiving cavity and located at one side of the main body, and a second mounting portion formed in the receiving cavity and located on the other side of the main body, the first elastic wave assembly is mounted on the first mounting portion, the second elastic wave assembly is mounted on the second mounting portion.
