

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250287703

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

KIM; Kyung Soo et al.

REUSABLE PHOTOVOLTAIC MODULE

Abstract

Proposed is a solar photovoltaic module that is easily recyclable. In the solar photovoltaic module disclosed herein, each component is coupled to each other in a physical manner. Therefore, since the solar photovoltaic module may be physically separated, recycling of the solar photovoltaic module may be very easily performed.

Inventors: KIM; Kyung Soo (Daejeon, KR), EO; Young Joo (Daejeon, KR), BAE; Soo Hyun (Daejeon, KR), KANG; Gi Hwa (Sejong-si, KR)

Applicant: KOREA INSTITUTE OF ENERGY RESEARCH (Daejeon, KR)

Family ID: 1000008020790

Assignee: KOREA INSTITUTE OF ENERGY RESEARCH (Daejeon, KR)

Appl. No.: 18/763926

Filed: July 03, 2024

Foreign Application Priority Data

KR

10-2024-0033228

Mar. 08, 2024

Publication Classification

Int. Cl.: H01L31/043 (20140101); H01L31/02 (20060101); H01L31/048 (20140101)

U.S. Cl.:

CPC H10F19/40 (20250101); H10F19/80 (20250101); H10F77/939 (20250101);

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION

[0001] The present application claims priority to Korean Patent Application No. 10-2024-0033228, filed Mar. 8, 2024, the entire contents of which are incorporated by reference herein for all purposes.

BACKGROUND OF THE INVENTION

Field of the Invention

[0002] The present disclosure relates to a photovoltaic module. Particularly, the present disclosure relates to a photovoltaic module in which each of configurations is easily separated and is capable of being recycled for a variety of purposes.

Description of the Related Art

[0003] Photovoltaic modules are devices that convert sunlight into electric energy, and are representative green energy devices. As the importance of environmental protection has emerged, the global photovoltaic power generation market has continuously grown since the mid-2010. As the solar photovoltaic power generation market continuously grows, the number of solar photovoltaic module installations has continuously increased.

[0004] Solar photovoltaic modules utilize an infinite amount of solar energy, but solar photovoltaic modules have limited lifespans. Solar photovoltaic modules that have reached the end of their lifespans are required to be collected and discarded. In addition, when damage occurs to solar photovoltaic modules due to a natural disaster, a fire, physical damage, and so on and the solar photovoltaic modules are in an unusable state, the solar photovoltaic modules are required to be discarded.

[0005] However, disposing of solar photovoltaic modules is an action contrary to the principle of protecting the environment. Recently, research has been conducted to recycle useful materials of solar photovoltaic modules without disposing of the solar photovoltaic modules.

[0006] Solar photovoltaic modules are devices in which frames, glass, sealing materials, solar cells, sealing materials, back sheets, junction boxes, and so on are coupled to each other. In order to separate the components, physical, chemical, thermal, optical, and electrical processes are required to be performed respectively. Aluminum, silicon, copper, and so on are recovered only when such a separation process is performed.

[0007] However, in this process, processes in different fields are respectively performed, so that complexity is increased.

Document of Related Art

[0008] (Patent Document 1) Japanese Patent No. 3245211 (Published on Dec. 27, 2023)

[0009] (Patent Document 2) Korean Patent Application Publication No. 2023-0100343 (Published on Jul. 5, 2023) (Patent Document 3) Japanese Patent No. 7022467 (Published on Feb. 9, 2022)

SUMMARY

[0010] This research was financially supported by national R&D programs through the Korea Institute of Energy Research (KIER) (grant no. C4-2414). This work was also partly supported by Korea Institute of Energy Technology Evaluation and Planning (KETEP) grant funded by the Korea government (MOTIE) (grant nos. 20208701010040 and RS-2023-00303745)

[0011] Accordingly, the present disclosure has been made keeping in mind the above problems occurring in the related art, and an objective of the present disclosure is to provide a solar photovoltaic module that is easily reusable.

[0012] According to an embodiment of the present disclosure, there is provided a solar photovoltaic module including: a base part on which a fixing part including a plurality of fixing parts that are not flat is formed; a solar cell part positioned on the fixing part; and a wire part disposed in contact with a first surface of the fixing part and disposed in contact with a first surface of the solar cell part.

[0013] The solar cell part may be positioned on the fixing part by being spaced apart from the

fixing part so that the fixing part is not positioned on a first side or a second side of the solar cell part.

[0014] The fixing part may protrude in a rounded manner.

[0015] The solar cell part may have a shape corresponding to the fixing part.

[0016] Point parts with the fixing part positioned therebetween may be formed on the base part, and the wire part may be disposed on the point parts with the fixing part positioned therebetween.

[0017] Tension parts may be spaced apart from each other between the fixing part, and the solar cell part disposed on the fixing part may have the first side and the second side in contact with the tension parts.

[0018] A length from the first side to the second side of the solar cell part may be longer than a length between the tension parts that are disposed in a corresponding manner, so that a shape of the solar cell part may be modified by being pressed due to a difference in length between the solar cell part and the tension parts when the solar cell part is disposed between the tension parts.

[0019] A cover part through which light is transmitted may be disposed on first surfaces of the base part and the solar cell part.

[0020] A plurality of alignment protrusions that protrudes and presses the wire part may be formed on a second surface of the cover part.

[0021] When the cover part is aligned and positioned, the alignment protrusions may be positioned between the point parts and the tension parts, and when the second surface of the cover part is positioned by being spaced apart by a predetermined distance from the first surface of the base part, the alignment protrusions may press the wire part and the wire part pressed by the alignment protrusions may not be in contact with the base part.

[0022] A sealing part may be disposed along a circumference of the base part.

[0023] A terminal part to which the wire part is connected may be provided on a first side of the base part, a connection groove may be provided in the terminal part, and a connection terminal electrically connected and fixed to the connection groove may be connected to and disposed in the connection groove.

[0024] According to an embodiment of the present disclosure, unlike an existing solar photovoltaic module, each component constituting the solar photovoltaic module of the present disclosure is physically formed and is physically coupled to each. Therefore, when recycling is performed, only a physical other process is performed, so that each component is conveniently separated and conveniently recycled.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0025] The above and other objectives, features, and other advantages of the present disclosure will be more clearly understood from the following detailed description when taken in conjunction with the accompanying drawings, in which:

[0026] FIG. 1 is a top view illustrating a solar photovoltaic module according to an embodiment of the present disclosure;

[0027] FIG. 2 is an enlarged view illustrating a fixing part and a point part of a base part according to an embodiment of the present disclosure;

[0028] FIG. 3 is a view illustrating a difference in length between a solar cell part and a space between the fixing parts according to an embodiment of the present disclosure;

[0029] FIG. 4 is a view illustrating the solar cell part disposed on the fixing part according to an embodiment of the present disclosure;

[0030] FIG. 5A is a view illustrating a state in which a cover part is positioned and aligned with the base part according to an embodiment of the present disclosure, and FIG. 5B is a view illustrating a

state in which the cover part is positioned by being spaced apart from the base part by a predetermined distance after the cover part is aligned with the base part according to an embodiment of the present disclosure;

[0031] FIG. 6 is a view illustrating a sealing part and the cover part according to an embodiment of the present disclosure;

[0032] FIG. 7 is a view illustrating the sealing part and the cover portion according to another embodiment of the present disclosure;

[0033] FIG. 8 is a view illustrating the sealing part and the cover part according to still another embodiment of the present disclosure; and

[0034] FIG. 9 is a view illustrating a terminal part according to an embodiment of the present disclosure.

DETAILED DESCRIPTION

[0035] Hereinafter, an embodiment of the present disclosure will be described in detail with reference to the accompanying drawings. However, this is not intended to limit the scope of the present disclosure.

[0036] In adding reference numerals to components throughout the drawings, it is to be noted that like or similar reference numerals designate like or similar components even though the components are illustrated in different drawings. In addition, in describing the present disclosure, when it is determined that a detailed description of a related known configuration or function may obscure the gist of the present disclosure, the detailed description thereof will be omitted.

[0037] In addition, the sizes, the shapes, and so on of components illustrated in the drawings may be exaggerated for convenience of understanding. In addition, terms specially defined by taking the configurations and functions of the present disclosure into consideration are provided only for illustrate embodiments of the present disclosure while not being limitative.

[0038] FIG. 1 is a top view illustrating a solar photovoltaic module according to an embodiment of the present disclosure.

[0039] A solar photovoltaic module in which each of components according to an embodiment of the present disclosure is physically connected and disposed may include a base part **100**, a solar cell part **200**, a wire part **300**, a sealing part **400**, and a terminal part **500**.

[0040] The base part **100** serves as a base plate of the solar photovoltaic module of the present disclosure. For example, the base part **100** may be formed in a rectangular shape, other components may be positioned on an upper surface of the base part **100**, and a lower surface of the base part **100** may be formed flat and may be disposed on a ground surface, a roof, a wall, and so on. A fixing part **110**, a point part **120**, and a tension part **130** are disposed on the base part **100**.

[0041] The fixing part **110** is formed on the upper surface of the base part **100**. The fixing part **110** is formed in a shape that protrudes upward. The fixing part **110** may be formed in a shape that smoothly protrudes from the left side and the right side toward the center. That is, the fixing part **110** may be formed in a shape of a portion of a circle having a large radius.

[0042] A plurality of fixing parts **110** is disposed. The plurality of fixing parts **110** is disposed to be spaced apart from each other. The fixing part **110** may electrically have a first pole. The fixing part **110** may have a +polarity.

[0043] The point parts **120** are disposed to be spaced apart from each other with the fixing part **110** therebetween. The point parts **120** are not formed corresponding to all fixing parts **110**, but are formed corresponding to some of the fixing parts **110**. As illustrated in FIG. 1, the point parts **120** are positioned corresponding to the fixing part **110** positioned at the top left side, are positioned corresponding to the fixing part **110** that is skipped one space to the right side (a third position from the left side) from the fixing part **110** positioned at the top left side, are positioned corresponding to the fixing part **110** positioned at the bottom right side, and are positioned corresponding to the fixing part **110** that is skipped one space to the left side from the fixing part **110** positioned at the bottom right side. The fixing part **110** is a point to which the wire part **300** is connected. The point

part **120** may serve to connect the left side and the right side of the wire part **300** conducting electricity.

[0044] The tension parts **130** are spaced apart from each other with the fixing part **110** therebetween. Similar to the point parts **120**, the tension parts **130** are formed corresponding to some of the fixing parts **110**. However, the tension parts **130** are formed corresponding to the fixing parts **110** on which the point parts **120** are not formed.

[0045] The tension parts **130** are formed on the fixing parts **110** other than the fixing parts **110** on which the point parts **120** described above are formed. The tension parts **130** are in contact with a left side and a right side of the solar cell part **200**, thereby being capable of bending the solar cell part **200**.

[0046] The solar cell part **200** is disposed on the fixing part **110**. The solar cell part **200** may be positioned corresponding to the fixing part **110** on which the tension parts **130** are formed. Therefore, in the present disclosure, when the upper surface of the present disclosure is observed from the left side to the right side, the present disclosure may be formed in the order of the fixing part **110**, the solar cell part **200**, the fixing part **110**, and the solar cell part **200**. When the solar cell part **200** receives sunlight, the solar cell part **200** generates energy. The energy may be moved through a wire. The solar cell part **200** has a second pole. The solar cell part **200** may have a – polarity. Therefore, the fixing part **110** and the solar cell part **200** may be + and – poles, respectively. Meanwhile, the solar cell part **200** may include a flexible film and is capable of being bent by external force.

[0047] The wire part **300** has a conductivity, and is configured to move energy generated in the solar cell part **200**.

[0048] The wire part **300** is alternately connected to the fixing part **110** and the solar cell part **200** in the order of the fixing part **110** and the solar cell part **200**, thereby allowing the electric energy generated in the solar cell part **200** to flow and move. Unlike a conventional solar photovoltaic module, the wire part **300** may be a wire having actual conductivity. The wire part **300** may be connected to the point part **120**.

[0049] Meanwhile, the wire part **300** may diverge from a portion thereof and may converge to other portion thereof.

[0050] The sealing part **400** is disposed along the circumference of the base part **100**. The sealing part **400** serves to seal a space between the base part **100** and a cover part **600** (see FIG. 5 that will be described later) when the cover part **600** is positioned on the upper surface of the base part **100**. Therefore, the sealing part **400** may prevent moisture, dust, and so on from being positioned in the space sealed by the base part **100** and the cover part **600**.

[0051] The terminal part **500** is connected to the wire part **300**. The wire part **300** forms an electrically closed circuit. The terminal part **500** may be connected to each end portion of the wire part **300**. A diode is disposed in the terminal part **500**, so that current flowing in a first direction is capable of being only allowed. The terminal part **500** may be connected to a battery that is not illustrated. Therefore, the energy that flows through the wire part **300** may be transferred to and stored in the battery through the terminal part **500**.

[0052] The solar photovoltaic module of the present disclosure formed in such a configuration is formed of physical components. Therefore, the installation of the present disclosure is also different from the installation of the existing solar photovoltaic module. In the present disclosure, the solar photovoltaic module may be formed in the following manner.

[0053] In the present disclosure, the base part **100** on which the fixing part **110** is formed is positioned, the terminal part **500** is positioned on the left side of the base part **100**, and the wire part **300** is connected first. When the wire part **300** is connected with respect to the point part **120**, the connection of the wire part **300** may be very easily performed.

[0054] Then, the solar cell part **200** is positioned between the wire part **300** and the fixing part **110**. The solar cell part **200** may be formed in a round shape since the left side and the right side of the

solar cell part **200** are in contact with the tension parts **130**.

[0055] Then, the cover part **600** is positioned on the upper surface of the base part **100** (not illustrated in detail in FIG. 1). By the cover part **600**, the solar cell part **200** and the wire part **300** are naturally pressed, so that the wire part **300** may be connected in the order of the fixing part **110**, the solar cell part **200**, the fixing part **110**, and the solar cell part **200** (the detailed description will be described later with reference to the drawings). Here, when the sealing part **400** is disposed in a shape in which a gap between the base part **100** and the cover part **600** is closed, the assembly of the solar photovoltaic module of the present disclosure may be completed.

[0056] When the solar photovoltaic module of the present disclosure is intended to be separated and recycled, all components of the solar photovoltaic module of the present disclosure may be separated by only removing the wire part **300** after the sealing part **400** is removed and then the cover part **600** is spaced apart from the base part **100**. Therefore, the solar photovoltaic module of the present disclosure may be very easily recyclable. The characteristics of the solar photovoltaic module of the present disclosure will be described below in detail.

[0057] FIG. 2 is an enlarged view illustrating the fixing part and the point part of the base part according to an embodiment of the present disclosure.

[0058] Referring to FIG. 2, the fixing part **110** may be formed on the upper surface of the base part **100** (see FIG. 1), and the cross-sectional shape of the fixing part **110** may be formed in a square shape having a round upper surface. The point parts **120** may be formed on the left side and the right side of the fixing part **110** with the fixing part **110** therebetween. The point part **120** is formed such that the end portion of the wire part **300** is connected to the point part **120**. The point part **120** serves as a connection point to which the wire part **300** is connected.

[0059] The wire part **300** may be formed such that the wire part **300** is in contact with the fixing part **110** between the point parts **120**. That is, as illustrated in FIG. 2, the wire part **300** may be disposed such that the left side and the right side of the wire part **300** are connected to the point parts **120** and the wire part **300** surrounds the fixing part **110**.

[0060] FIG. 3 is a view illustrating a difference in length between the solar cell part and a space between the fixing parts according to an embodiment of the present disclosure, and FIG. 4 is a view illustrating the solar cell part disposed on the fixing part according to an embodiment of the present disclosure.

[0061] As can be seen by referring to FIG. 3, in the present disclosure, a horizontal length **L1** of the solar cell part **200** may be formed longer than a horizontal length **L2** of the fixing part **110**.

Therefore, when the solar cell part **200** is positioned on the upper surface of the fixing part **110**, the solar cell part **200** may be disposed such that portions of the left side and the right side of the solar cell part **200** are not supported by the fixing part **110**. However, in the present disclosure, the tension parts **130** are disposed with the fixing part **110** therebetween.

[0062] As illustrated in FIG. 4, since the tension part **130** protrudes upward from the upper surface of the fixing part **110**, the solar cell part **200** positioned on the upper surface of the fixing part **110** may be disposed such that the left side and the right side of the solar cell part **200** are in contact with the tension parts **130** and the solar cell part **200** is disposed in the round shape.

[0063] In FIG. 5A and FIG. 5B, FIG. 5A is a view illustrating a state in which the cover part is positioned and aligned with the base part according to an embodiment of the present disclosure, and FIG. 5B is a view illustrating a state in which the cover part is positioned by being spaced apart from the base part by a predetermined distance after the cover part is aligned with the base part according to an embodiment of the present disclosure.

[0064] The wire part **300** is positioned such that the wire part **300** faces the upper surface of the solar cell part **200** by the point part **120** with the fixing part **110** therebetween, the fixing part **110** having the solar cell part **200** positioned on the upper surface of the fixing part **110**. At this time, as can be seen in FIG. 5A, since the wire part **300** has a long length, the wire part **300** may not be in contact with the solar cell part **200** when a specific external force is not applied to the wire part

300.

[0065] In the present disclosure, only by pressing the base part **100** by the cover part **600**, the wire part **300** may be aligned and may be connected to the solar cell part **200**. The cover part **600** may be a transparent glass. Therefore, light may transmit the cover part **600**. A plurality of alignment protrusions **610** may be formed on the cover part **600** corresponding to the tension parts **130**.

[0066] The alignment protrusion **610** protrudes downward from a lower surface of the cover part **600**. A length between the corresponding alignment protrusions **610** may be longer than a length between the corresponding tension parts **130**.

[0067] In addition, the length between the corresponding alignment protrusions **610** may be shorter than a length between the point parts **120** illustrated in FIG. 5A. Therefore, when the cover part **600** is aligned and positioned, the point part **120** and the tension part **130** may be positioned on opposite sides of the alignment protrusion **610** with respect to the alignment protrusion **610**.

[0068] As illustrated in FIG. 5B, when the cover part **600** is aligned and positioned close to the base part **100**, the alignment protrusion **610** is in contact with the wire part **300** so that the wire part **300** is moved downward. At the same time, the cover part **600** may press the solar cell part **200**. At this time, the wire part **300** is pressed again by the cover part **600**. Furthermore, due to the degree to which the wire part **300** is pressed by the cover part **600**, the wire part **300** may be in contact with the solar cell part **200** beyond an upper side of the tension part **130**. Therefore, the wire part **300** may only be in contact with the solar cell part **200**, not the fixing part **110**.

[0069] Meanwhile, to this end, the alignment protrusion **610** should not be in contact with the base part **100**, which may be realized by maintaining the gap through manual work of the worker or may be realized by the sealing part **400**.

[0070] As such, in the present disclosure, the solar cell part **200** is disposed, the cover part **600** is aligned, and the cover part **600** is disposed, so that each component is easily coupled to each other and convenience of manufacturing may be promoted.

[0071] FIG. 6 is a view illustrating the sealing part and the cover part according to an embodiment of the present disclosure.

[0072] The sealing part **400** is disposed between the base part **100** and the cover part **600**. Since the sealing part **400** is formed in a closed shape, the sealing part **400** serves to block the inner and outer sides of the sealing part **400**. Therefore, the sealing part **400** may prevent moisture, dust, and so on from being introduced between the base part **100** and the cover part **600**. As an example, the sealing part **400** may be formed in a shape of a bar having an elastic force, and may be formed in a shape in which the bar is disposed while having a specific shape. Here, the sealing part **400** may be connected to the cover part **600** and the base part **100** through an adhesive that is not illustrated.

[0073] FIG. 7 is a view illustrating the sealing part and the cover part according to another embodiment of the present disclosure.

[0074] The sealing part **400** may include a first sealing part **410**, a second sealing part **420**, and a third sealing part **430**. According to another embodiment, the sealing part **400** may be formed in a '[' shape. That is, the sealing part **400** may be formed in a shape in which each of the first sealing part **410** and the second sealing part **420** are spaced apart from each other and protrude upward. Here, the third sealing part **430** may connect the first sealing part **410** and the second sealing part **420** to each other. The first sealing part **410** may be disposed vertically, the second sealing part **420** may be disposed vertically, and the third sealing part **430** may be disposed horizontally.

[0075] A sealing protrusion **620** that protrudes downward may be formed on a lower surface of the cover part **600**. When the cover part **600** is aligned and positioned on the base part **100**, and the cover part **600** is disposed adjacent to the base part **100**, the sealing protrusion **620** may be disposed such that the left side of the sealing protrusion **620** is surrounded by the first sealing part **410**, the right side of the sealing protrusion **620** is surrounded by the second sealing part **420**, and the lower side of the sealing protrusion **620** is surrounded by the third sealing part **430**. In the present disclosure, since the sealing protrusion **620** of the cover part **600** is fixed by being in

contact with the sealing part **400**, moisture, dust, and so on may not be positioned between the cover part **600** and the base part **100**.

[0076] FIG. **8** is a view illustrating the sealing part and the cover part according to still another embodiment of the present disclosure.

[0077] According to still another embodiment, the sealing part **400** may include a first sealing part **410** and a second sealing part **420**.

[0078] The first sealing part **410** may be disposed along a vertical direction, and the second sealing part **420** may be disposed along a horizontal direction. According to still another embodiment, a difference between the sealing part **400** of the still another embodiment and the sealing part **400** described in FIG. **7** may be an arrangement relationship and a connection relationship between the first sealing part **410** and the second sealing part **420**, and may be the presence or absence of the third sealing part **430**.

[0079] However, as the basic principle of each embodiment is similar, sealing may be performed by fixing the sealing protrusion **620** after the sealing protrusion **620** is disposed on the sealing part **400**. Here, the second sealing part **420** may be telescoped by the sealing protrusion **620**, and may be closely connected to the cover part **600**. The first sealing part **410** may close a gap between the sealing protrusion **620** and the second sealing part **420** (the base part **100**).

[0080] FIG. **9** is a view illustrating the terminal part according to an embodiment of the present disclosure.

[0081] The terminal part **500** according to an embodiment may include a connection groove **510**.

[0082] That is, the terminal part **500** may include a first connection groove **511** on the left side, a second connection groove **512** on the right side, and a third connection groove **513** in the middle side. Respective connection terminals **310** may be electrically connected to each of the connection grooves **510**.

[0083] As an example, a first connection terminal **311** may be connected to a first side of the wire part **300**, and a second connection terminal **312** may be connected to a second side of the wire part **300**. In addition, the first connection terminal **311** of the wire part **300** may be connected to the first connection groove **511**, and the second connection terminal **312** of the wire part **300** may be connected to the second connection groove **512**. Since the terminal part **500** is electrically connected to the wire part **300**, energy generated from the solar cell part **200** may be transmitted to the terminal part **500** through the wire part **300**.

[0084] In addition, the battery that is not illustrated may be connected to the third connection groove **513** through the connection terminal **310**. Therefore, energy is supplied to the battery through the terminal part **500**, and the battery may store the energy.

[0085] In addition, when the present disclosure is configured as described above, the terminal part **500** and the wire part **300** are capable of being conveniently separated from each other, so that the present disclosure may be easily recycled.

[0086] Although exemplary embodiments of the present disclosure have been described herein, it is understood that the present disclosure should not be limited to these exemplary embodiments and that various changes and modifications can be made by one ordinary skilled in the art within the spirit and scope of the present disclosure.

Claims

1. A solar photovoltaic module comprising: a base part on which a fixing part comprising a plurality of fixing parts that are not flat is formed; a solar cell part positioned on the fixing part; and a wire part disposed in contact with a first surface of the fixing part and disposed in contact with a first surface of the solar cell part.
2. The solar photovoltaic module of claim 1, wherein the solar cell part is positioned on the fixing part by being spaced apart from the fixing part so that the fixing part is not positioned on a first

side or a second side of the solar cell part.

3. The solar photovoltaic module of claim 2, wherein the fixing part protrudes in a rounded manner.

4. The solar photovoltaic module of claim 3, wherein the solar cell part has a shape corresponding to the fixing part.

5. The solar photovoltaic module of claim 2, wherein point parts with the fixing part positioned therebetween are formed on the base part, and the wire part is disposed on the point parts with the fixing part positioned therebetween.

6. The solar photovoltaic module of claim 5, wherein tension parts are spaced apart from each other between the fixing part, and the solar cell part disposed on the fixing part has the first side and the second side in contact with the tension parts.

7. The solar photovoltaic module of claim 6, wherein a length from the first side to the second side of the solar cell part is longer than a length between the tension parts that are disposed in a corresponding manner, so that a shape of the solar cell part is modified by being pressed due to a difference in length between the solar cell part and the tension parts when the solar cell part is disposed between the tension parts.

8. The solar photovoltaic module of claim 6, wherein a cover part through which light is transmitted is disposed on first surfaces of the base part and the solar cell part.

9. The solar photovoltaic module of claim 8, wherein a plurality of alignment protrusions that protrudes and presses the wire part is formed on a second surface of the cover part.

10. The solar photovoltaic module of claim 9, wherein when the cover part is aligned and positioned, the alignment protrusions are positioned between the point parts and the tension parts, and when the second surface of the cover part is positioned by being spaced apart by a predetermined distance from the first surface of the base part, the alignment protrusions press the wire part and the wire part pressed by the alignment protrusions is not in contact with the base part.

11. The solar photovoltaic module of claim 8, wherein a sealing part is disposed along a circumference of the base part.

12. The solar photovoltaic module of claim 1, wherein a terminal part to which the wire part is connected is provided on a first side of the base part, a connection groove is provided in the terminal part, and a connection terminal electrically connected and fixed to the connection groove is capable of being connected to and disposed in the connection groove.
