

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412003
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Ramanasankaran; Rajiv et al.

Building data platform with digital twin based predictive recommendation visualization

Abstract

A building system of a building operates to store a digital twin of the building in the one or more storage devices, wherein the digital twin further includes an artificial intelligence configured to generate a plurality of inference values of a data point for a plurality of future times, the data point related to the building by the interrelationship of the digital twin. The building system operates to generate a recommendation based on the plurality of inference values for the data point for the plurality of future times, the recommendation recommending making one or more updates to the building, and cause a graphic representation of the building to display an indication of the recommendation.

Inventors: Ramanasankaran; Rajiv (San Jose, CA), Zhang; Chenlu (Milwaukee, WI), Shatdal; Ambuj (Madison, WI), Lee; Young (Milwaukee, WI), Douglas; Jonathan D. (Mequon, WI)

Applicant: Tyco Fire & Security GmbH (Neuhausen am Rheinfall, CH)

Family ID: 86500174

Assignee: TYCO FIRE & SECURITY GMBH (Neuhausen am Rheinfall, CH)

Appl. No.: 17/855561

Filed: June 30, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230169223 A1	Jun. 01, 2023

Related U.S. Application Data

continuation-in-part parent-doc US 17537046 20211129 US 11714930 child-doc US 17855561

Publication Classification

Int. Cl.: G06F30/13 (20200101); G05B15/02 (20060101); G06N5/04 (20230101)

U.S. Cl.:

CPC **G06F30/13** (20200101); **G05B15/02** (20130101); **G06N5/04** (20130101);

Field of Classification Search

CPC: G06F (30/13); G06F (30/27); G05B (15/02); G05B (17/02); G05B (2219/2642); G06N (5/04);
 G06N (3/044); G06N (3/0464); G06N (3/08); G06N (5/022)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5301109	12/1993	Landauer et al.	N/A	N/A
5446677	12/1994	Jensen et al.	N/A	N/A
5581478	12/1995	Cruse et al.	N/A	N/A
5812962	12/1997	Kovac	N/A	N/A
5960381	12/1998	Singers et al.	N/A	N/A
5973662	12/1998	Singers et al.	N/A	N/A
6014612	12/1999	Larson et al.	N/A	N/A
6031547	12/1999	Kennedy	N/A	N/A
6134511	12/1999	Subbarao	N/A	N/A
6157943	12/1999	Meyer	N/A	N/A
6285966	12/2000	Brown et al.	N/A	N/A
6363422	12/2001	Hunter et al.	N/A	N/A
6385510	12/2001	Hoog et al.	N/A	N/A
6389331	12/2001	Jensen et al.	N/A	N/A
6401027	12/2001	Xu et al.	N/A	N/A
6437691	12/2001	Sandelman et al.	N/A	N/A
6477518	12/2001	Li et al.	N/A	N/A
6487457	12/2001	Hull et al.	N/A	N/A
6493755	12/2001	Hansen et al.	N/A	N/A
6577323	12/2002	Jamieson et al.	N/A	N/A
6626366	12/2002	Kayahara et al.	N/A	N/A
6646660	12/2002	Patty	N/A	N/A
6704016	12/2003	Oliver et al.	N/A	N/A
6732540	12/2003	Sugihara et al.	N/A	N/A
6764019	12/2003	Kayahara et al.	N/A	N/A
6782385	12/2003	Natsumeda et al.	N/A	N/A
6813532	12/2003	Eryurek et al.	N/A	N/A
6816811	12/2003	Seem	N/A	N/A
6823680	12/2003	Jayanth	N/A	N/A
6826454	12/2003	Sulfstede	N/A	N/A
6865511	12/2004	Frerichs et al.	N/A	N/A
6925338	12/2004	Eryurek et al.	N/A	N/A
6986138	12/2005	Sakaguchi et al.	N/A	N/A
7031880	12/2005	Seem et al.	N/A	N/A
7401057	12/2007	Eder	N/A	N/A
7552467	12/2008	Lindsay	N/A	N/A
7627544	12/2008	Chkodrov et al.	N/A	N/A
7818249	12/2009	Lovejoy et al.	N/A	N/A
7889051	12/2010	Billig et al.	N/A	N/A
7996488	12/2010	Casabella et al.	N/A	N/A

8078330	12/2010	Brickfield et al.	N/A	N/A
8104044	12/2011	Scofield et al.	N/A	N/A
8229470	12/2011	Ranjan et al.	N/A	N/A
8401991	12/2012	Wu et al.	N/A	N/A
8495745	12/2012	Schrecker et al.	N/A	N/A
8516016	12/2012	Park et al.	N/A	N/A
8532808	12/2012	Drees et al.	N/A	N/A
8532839	12/2012	Drees et al.	N/A	N/A
8600556	12/2012	Nesler et al.	N/A	N/A
8635182	12/2013	Mackay	N/A	N/A
8682921	12/2013	Park et al.	N/A	N/A
8731724	12/2013	Drees et al.	N/A	N/A
8737334	12/2013	Ahn et al.	N/A	N/A
8738334	12/2013	Jiang et al.	N/A	N/A
8751487	12/2013	Byrne et al.	N/A	N/A
8788097	12/2013	Drees et al.	N/A	N/A
8805995	12/2013	Oliver	N/A	N/A
8843238	12/2013	Wenzel et al.	N/A	N/A
8874071	12/2013	Sherman et al.	N/A	N/A
8941465	12/2014	Pineau et al.	N/A	N/A
8990127	12/2014	Taylor	N/A	N/A
9070113	12/2014	Shafiee et al.	N/A	N/A
9116978	12/2014	Park et al.	N/A	N/A
9185095	12/2014	Moritz et al.	N/A	N/A
9189527	12/2014	Park et al.	N/A	N/A
9196009	12/2014	Drees et al.	N/A	N/A
9229966	12/2015	Aymeloglu et al.	N/A	N/A
9286582	12/2015	Drees et al.	N/A	N/A
9311807	12/2015	Schultz et al.	N/A	N/A
9344751	12/2015	Ream et al.	N/A	N/A
9354968	12/2015	Wenzel et al.	N/A	N/A
9507686	12/2015	Horn et al.	N/A	N/A
9524594	12/2015	Ouyang et al.	N/A	N/A
9558196	12/2016	Johnston et al.	N/A	N/A
9652813	12/2016	Gifford et al.	N/A	N/A
9753455	12/2016	Drees	N/A	N/A
9811249	12/2016	Chen et al.	N/A	N/A
9838844	12/2016	Emeis et al.	N/A	N/A
9886478	12/2017	Mukherjee	N/A	N/A
9948359	12/2017	Horton	N/A	N/A
10055114	12/2017	Shah et al.	N/A	N/A
10055206	12/2017	Park et al.	N/A	N/A
10116461	12/2017	Fairweather et al.	N/A	N/A
10169454	12/2018	Ait-Mokhtar et al.	N/A	N/A
10171297	12/2018	Stewart et al.	N/A	N/A
10171586	12/2018	Shaashua et al.	N/A	N/A
10187258	12/2018	Nagesh et al.	N/A	N/A
10514963	12/2018	Shrivastava et al.	N/A	N/A
10515098	12/2018	Park et al.	N/A	N/A
10534326	12/2019	Sridharan et al.	N/A	N/A
10536295	12/2019	Fairweather et al.	N/A	N/A
10564993	12/2019	Deutsch et al.	N/A	N/A
10705492	12/2019	Harvey	N/A	N/A
10708078	12/2019	Harvey	N/A	N/A

10760815	12/2019	Janakiraman et al.	N/A	N/A
10762475	12/2019	Song et al.	N/A	N/A
10824120	12/2019	Ahmed	N/A	N/A
10845771	12/2019	Harvey	N/A	N/A
10854194	12/2019	Park et al.	N/A	N/A
10862928	12/2019	Badawy et al.	N/A	N/A
10921760	12/2020	Harvey	N/A	N/A
10921972	12/2020	Park et al.	N/A	N/A
10969133	12/2020	Harvey	N/A	N/A
10986121	12/2020	Stockdale et al.	N/A	N/A
11016998	12/2020	Park et al.	N/A	N/A
11024292	12/2020	Park et al.	N/A	N/A
11038709	12/2020	Park et al.	N/A	N/A
11041650	12/2020	Li et al.	N/A	N/A
11054796	12/2020	Holaso	N/A	N/A
11070390	12/2020	Park et al.	N/A	N/A
11073976	12/2020	Park et al.	N/A	N/A
11108587	12/2020	Park et al.	N/A	N/A
11113295	12/2020	Park et al.	N/A	N/A
11216663	12/2021	Ettinger et al.	N/A	N/A
11229138	12/2021	Harvey et al.	N/A	N/A
11264140	12/2021	Tal et al.	N/A	N/A
11314726	12/2021	Park et al.	N/A	N/A
11314788	12/2021	Park et al.	N/A	N/A
11504011	12/2021	Jain	N/A	G06N 5/04
11556105	12/2022	Cooley et al.	N/A	N/A
11561522	12/2022	Cooley et al.	N/A	N/A
11561523	12/2022	Cooley et al.	N/A	N/A
11573551	12/2022	Cooley et al.	N/A	N/A
11586167	12/2022	Cooley et al.	N/A	N/A
11704011	12/2022	Jones et al.	N/A	N/A
11853938	12/2022	Muthusamy et al.	N/A	N/A
2002/0010562	12/2001	Schleiss et al.	N/A	N/A
2002/0016639	12/2001	Smith et al.	N/A	N/A
2002/0059229	12/2001	Natsumeda et al.	N/A	N/A
2002/0123864	12/2001	Eryurek et al.	N/A	N/A
2002/0147506	12/2001	Eryurek et al.	N/A	N/A
2002/0177909	12/2001	Fu et al.	N/A	N/A
2003/0005486	12/2002	Ridolfo et al.	N/A	N/A
2003/0014130	12/2002	Grumelart	N/A	N/A
2003/0073432	12/2002	Meade, II	N/A	N/A
2003/0158704	12/2002	Triginai et al.	N/A	N/A
2003/0171851	12/2002	Brickfield et al.	N/A	N/A
2003/0200059	12/2002	Ignatowski et al.	N/A	N/A
2004/0068390	12/2003	Saunders	N/A	N/A
2004/0128314	12/2003	Katibah et al.	N/A	N/A
2004/0133314	12/2003	Ehlers et al.	N/A	N/A
2004/0199360	12/2003	Friman et al.	N/A	N/A
2005/0055308	12/2004	Meyer et al.	N/A	N/A
2005/0108262	12/2004	Fawcett et al.	N/A	N/A
2005/0154494	12/2004	Ahmed	N/A	N/A
2005/0278703	12/2004	Lo et al.	N/A	N/A
2005/0283337	12/2004	Sayal	N/A	N/A
2006/0095521	12/2005	Patinkin	N/A	N/A

2006/0140207	12/2005	Eschbach et al.	N/A	N/A
2006/0184479	12/2005	Levine	N/A	N/A
2006/0200476	12/2005	Gottumukkala et al.	N/A	N/A
2006/0265751	12/2005	Cosquer et al.	N/A	N/A
2006/0271589	12/2005	Horowitz et al.	N/A	N/A
2007/0028179	12/2006	Levin et al.	N/A	N/A
2007/0203693	12/2006	Estes	N/A	N/A
2007/0208549	12/2006	Blevins et al.	N/A	N/A
2007/0219645	12/2006	Thomas et al.	N/A	N/A
2007/0261062	12/2006	Bansal et al.	N/A	N/A
2007/0273497	12/2006	Kuroda et al.	N/A	N/A
2007/0273610	12/2006	Baillot	N/A	N/A
2008/0034425	12/2007	Overcash et al.	N/A	N/A
2008/0094230	12/2007	Mock et al.	N/A	N/A
2008/0097816	12/2007	Freire et al.	N/A	N/A
2008/0186160	12/2007	Kim et al.	N/A	N/A
2008/0249756	12/2007	Chaisuparasmikul	N/A	N/A
2008/0252723	12/2007	Park	N/A	N/A
2008/0281472	12/2007	Podgorny et al.	N/A	N/A
2009/0195349	12/2008	Frader-Thompson et al.	N/A	N/A
2009/0315889	12/2008	Tognola	345/440	G06T 11/206
2010/0045439	12/2009	Tak et al.	N/A	N/A
2010/0058248	12/2009	Park	N/A	N/A
2010/0131533	12/2009	Ortiz	N/A	N/A
2010/0274366	12/2009	Fata et al.	N/A	N/A
2010/0281387	12/2009	Holland et al.	N/A	N/A
2010/0286937	12/2009	Hedley et al.	N/A	N/A
2010/0324962	12/2009	Nesler et al.	N/A	N/A
2011/0015802	12/2010	Imes	N/A	N/A
2011/0029341	12/2010	Muse et al.	N/A	N/A
2011/0047418	12/2010	Drees et al.	N/A	N/A
2011/0061015	12/2010	Drees et al.	N/A	N/A
2011/0071685	12/2010	Huneycutt et al.	N/A	N/A
2011/0077950	12/2010	Hughston	N/A	N/A
2011/0087650	12/2010	Mackay et al.	N/A	N/A
2011/0087988	12/2010	Ray et al.	N/A	N/A
2011/0088000	12/2010	Mackay	N/A	N/A
2011/0125737	12/2010	Pothering et al.	N/A	N/A
2011/0137853	12/2010	Mackay	N/A	N/A
2011/0153603	12/2010	Adiba et al.	N/A	N/A
2011/0154363	12/2010	Karmarkar	N/A	N/A
2011/0157357	12/2010	Weisensale et al.	N/A	N/A
2011/0178977	12/2010	Drees	N/A	N/A
2011/0191343	12/2010	Heaton et al.	N/A	N/A
2011/0205022	12/2010	Cavallaro et al.	N/A	N/A
2011/0218777	12/2010	Chen et al.	N/A	N/A
2012/0011126	12/2011	Park et al.	N/A	N/A
2012/0011141	12/2011	Park et al.	N/A	N/A
2012/0022698	12/2011	Mackay	N/A	N/A
2012/0062577	12/2011	Nixon	N/A	N/A
2012/0064923	12/2011	Imes et al.	N/A	N/A
2012/0083930	12/2011	Ilic et al.	N/A	N/A
2012/0100825	12/2011	Sherman et al.	N/A	N/A
2012/0101637	12/2011	Imes et al.	N/A	N/A

2012/0135759	12/2011	Imes et al.	N/A	N/A
2012/0136485	12/2011	Weber et al.	N/A	N/A
2012/0158633	12/2011	Eder	N/A	N/A
2012/0259583	12/2011	Noboa et al.	N/A	N/A
2012/0272228	12/2011	Marndi et al.	N/A	N/A
2012/0278051	12/2011	Jiang et al.	N/A	N/A
2013/0007063	12/2012	Kalra et al.	N/A	N/A
2013/0038430	12/2012	Blower et al.	N/A	N/A
2013/0038707	12/2012	Cunningham et al.	N/A	N/A
2013/0060820	12/2012	Bulusu et al.	N/A	N/A
2013/0086497	12/2012	Ambuhl et al.	N/A	N/A
2013/0096723	12/2012	Ludwig	N/A	N/A
2013/0097706	12/2012	Titonis et al.	N/A	N/A
2013/0103221	12/2012	Raman et al.	N/A	N/A
2013/0167035	12/2012	Imes et al.	N/A	N/A
2013/0170710	12/2012	Kuoch et al.	N/A	N/A
2013/0204836	12/2012	Choi et al.	N/A	N/A
2013/0246916	12/2012	Reimann et al.	N/A	N/A
2013/0247205	12/2012	Schrecker et al.	N/A	N/A
2013/0262035	12/2012	Mills	N/A	N/A
2013/0275174	12/2012	Bennett et al.	N/A	N/A
2013/0275908	12/2012	Reichard	N/A	N/A
2013/0297050	12/2012	Reichard et al.	N/A	N/A
2013/0298244	12/2012	Kumar et al.	N/A	N/A
2013/0331995	12/2012	Rosen	N/A	N/A
2013/0338970	12/2012	Reggetti	N/A	N/A
2014/0032506	12/2013	Hoey et al.	N/A	N/A
2014/0059483	12/2013	Mairs et al.	N/A	N/A
2014/0081652	12/2013	Klindworth	N/A	N/A
2014/0135952	12/2013	Maehara	N/A	N/A
2014/0152651	12/2013	Chen et al.	N/A	N/A
2014/0172184	12/2013	Schmidt et al.	N/A	N/A
2014/0189861	12/2013	Gupta et al.	N/A	N/A
2014/0207282	12/2013	Angle et al.	N/A	N/A
2014/0258052	12/2013	Khuti et al.	N/A	N/A
2014/0269614	12/2013	Maguire et al.	N/A	N/A
2014/0277765	12/2013	Karimi et al.	N/A	N/A
2014/0278461	12/2013	Artz	N/A	N/A
2014/0327555	12/2013	Sager et al.	N/A	N/A
2015/0019174	12/2014	Kiff et al.	N/A	N/A
2015/0042240	12/2014	Aggarwal et al.	N/A	N/A
2015/0105917	12/2014	Sasaki et al.	N/A	N/A
2015/0145468	12/2014	Ma et al.	N/A	N/A
2015/0156031	12/2014	Fadell et al.	N/A	N/A
2015/0168931	12/2014	Jin	N/A	N/A
2015/0172300	12/2014	Cochenour	N/A	N/A
2015/0178421	12/2014	Borrelli et al.	N/A	N/A
2015/0185261	12/2014	Frader-Thompson et al.	N/A	N/A
2015/0186777	12/2014	Lecue et al.	N/A	N/A
2015/0202962	12/2014	Habashima et al.	N/A	N/A
2015/0204563	12/2014	Imes et al.	N/A	N/A
2015/0235267	12/2014	Steube et al.	N/A	N/A
2015/0241895	12/2014	Lu et al.	N/A	N/A
2015/0244730	12/2014	Vu et al.	N/A	N/A

2015/0244732	12/2014	Golshan et al.	N/A	N/A
2015/0261863	12/2014	Dey et al.	N/A	N/A
2015/0263900	12/2014	Polyakov et al.	N/A	N/A
2015/0286969	12/2014	Warner et al.	N/A	N/A
2015/0295796	12/2014	Hsiao et al.	N/A	N/A
2015/0304193	12/2014	Ishii et al.	N/A	N/A
2015/0316918	12/2014	Schleiss et al.	N/A	N/A
2015/0324422	12/2014	Elder	N/A	N/A
2015/0341212	12/2014	Hsiao et al.	N/A	N/A
2015/0348417	12/2014	Ignaczak et al.	N/A	N/A
2015/0379080	12/2014	Jochimski	N/A	N/A
2016/0011753	12/2015	Mcfarland et al.	N/A	N/A
2016/0033946	12/2015	Zhu et al.	N/A	N/A
2016/0035246	12/2015	Curtis	N/A	N/A
2016/0065601	12/2015	Gong et al.	N/A	N/A
2016/0070736	12/2015	Swan et al.	N/A	N/A
2016/0078229	12/2015	Gong et al.	N/A	N/A
2016/0090839	12/2015	Stolarczyk	N/A	N/A
2016/0119434	12/2015	Dong et al.	N/A	N/A
2016/0127712	12/2015	Alfredsson et al.	N/A	N/A
2016/0132595	12/2015	Bliss et al.	N/A	N/A
2016/0139752	12/2015	Shim et al.	N/A	N/A
2016/0163186	12/2015	Davidson et al.	N/A	N/A
2016/0170390	12/2015	Xie et al.	N/A	N/A
2016/0171862	12/2015	Das et al.	N/A	N/A
2016/0173816	12/2015	Huenerfauth et al.	N/A	N/A
2016/0179315	12/2015	Sarao et al.	N/A	N/A
2016/0179342	12/2015	Sarao et al.	N/A	N/A
2016/0179990	12/2015	Sarao et al.	N/A	N/A
2016/0181967	12/2015	Nojima	N/A	N/A
2016/0195856	12/2015	Spero	N/A	N/A
2016/0212165	12/2015	Singla et al.	N/A	N/A
2016/0239660	12/2015	Azvine et al.	N/A	N/A
2016/0239756	12/2015	Aggour et al.	N/A	N/A
2016/0247129	12/2015	Song et al.	N/A	N/A
2016/0253679	12/2015	Venkatraman et al.	N/A	N/A
2016/0260063	12/2015	Harris et al.	N/A	N/A
2016/0292625	12/2015	Curtland	N/A	G06F 3/04847
2016/0313751	12/2015	Risbeck et al.	N/A	N/A
2016/0313752	12/2015	Przybylski	N/A	N/A
2016/0313902	12/2015	Hill et al.	N/A	N/A
2016/0350364	12/2015	Anicic et al.	N/A	N/A
2016/0357521	12/2015	Zhang et al.	N/A	N/A
2016/0357828	12/2015	Tobin et al.	N/A	N/A
2016/0358432	12/2015	Branscomb et al.	N/A	N/A
2016/0363336	12/2015	Roth et al.	N/A	N/A
2016/0370258	12/2015	Perez	N/A	N/A
2016/0377309	12/2015	Abiprojo et al.	N/A	N/A
2016/0378306	12/2015	Kresl et al.	N/A	N/A
2016/0379326	12/2015	Chan-Gove et al.	N/A	N/A
2017/0006135	12/2016	Siebel	N/A	N/A
2017/0011318	12/2016	Vigano et al.	N/A	N/A
2017/0017221	12/2016	Lamparter et al.	N/A	N/A
2017/0039255	12/2016	Raj et al.	N/A	N/A

2017/0052536	12/2016	Warner et al.	N/A	N/A
2017/0053441	12/2016	Nadumane et al.	N/A	N/A
2017/0063894	12/2016	Muddu et al.	N/A	N/A
2017/0068409	12/2016	Nair	N/A	N/A
2017/0070775	12/2016	Taxier et al.	N/A	N/A
2017/0075984	12/2016	Deshpande et al.	N/A	N/A
2017/0084168	12/2016	Janchookiat	N/A	N/A
2017/0090437	12/2016	Veeramani et al.	N/A	N/A
2017/0093700	12/2016	Gilley et al.	N/A	N/A
2017/0098086	12/2016	Hoernecke et al.	N/A	N/A
2017/0103327	12/2016	Penilla et al.	N/A	N/A
2017/0103403	12/2016	Chu et al.	N/A	N/A
2017/0123389	12/2016	Baez et al.	N/A	N/A
2017/0134415	12/2016	Muddu et al.	N/A	N/A
2017/0177715	12/2016	Chang et al.	N/A	N/A
2017/0180147	12/2016	Brandman et al.	N/A	N/A
2017/0188216	12/2016	Koskas et al.	N/A	N/A
2017/0212482	12/2016	Boettcher et al.	N/A	N/A
2017/0212668	12/2016	Shah et al.	N/A	N/A
2017/0220641	12/2016	Chi et al.	N/A	N/A
2017/0230930	12/2016	Frey	N/A	N/A
2017/0235817	12/2016	Deodhar et al.	N/A	N/A
2017/0251182	12/2016	Siminoff et al.	N/A	N/A
2017/0270124	12/2016	Nagano et al.	N/A	N/A
2017/0277769	12/2016	Pasupathy et al.	N/A	N/A
2017/0278003	12/2016	Liu	N/A	N/A
2017/0294132	12/2016	Colmenares	N/A	N/A
2017/0314803	12/2016	Jacobson et al.	N/A	N/A
2017/0315522	12/2016	Kwon et al.	N/A	N/A
2017/0315697	12/2016	Jacobson et al.	N/A	N/A
2017/0322534	12/2016	Sinha et al.	N/A	N/A
2017/0323389	12/2016	Vavrasek	N/A	N/A
2017/0329289	12/2016	Kohn et al.	N/A	N/A
2017/0336770	12/2016	Macmillan	N/A	N/A
2017/0345287	12/2016	Fuller et al.	N/A	N/A
2017/0351957	12/2016	Lecue et al.	N/A	N/A
2017/0357225	12/2016	Asp et al.	N/A	N/A
2017/0357490	12/2016	Park et al.	N/A	N/A
2017/0357908	12/2016	Cabadi et al.	N/A	N/A
2018/0012159	12/2017	Kozloski et al.	N/A	N/A
2018/0013579	12/2017	Fairweather et al.	N/A	N/A
2018/0017407	12/2017	Dousse	N/A	N/A
2018/0024520	12/2017	Sinha et al.	N/A	N/A
2018/0039238	12/2017	Gaertner et al.	N/A	N/A
2018/0048485	12/2017	Pelton et al.	N/A	N/A
2018/0068034	12/2017	Zeifman et al.	N/A	N/A
2018/0069932	12/2017	Tiwari et al.	N/A	N/A
2018/0114140	12/2017	Chen et al.	N/A	N/A
2018/0137288	12/2017	Polyakov	N/A	N/A
2018/0157930	12/2017	Rutschman et al.	N/A	N/A
2018/0162400	12/2017	Abdar	N/A	N/A
2018/0176241	12/2017	Manadhata et al.	N/A	N/A
2018/0198627	12/2017	Mullins	N/A	N/A
2018/0203961	12/2017	Aisu et al.	N/A	N/A

2018/0239982	12/2017	Rutschman et al.	N/A	N/A
2018/0275625	12/2017	Park et al.	N/A	N/A
2018/0276962	12/2017	Butler et al.	N/A	N/A
2018/0277246	12/2017	Zhong et al.	N/A	N/A
2018/0292797	12/2017	Lamparter et al.	N/A	N/A
2018/0336785	12/2017	Ghannam et al.	N/A	N/A
2018/0340701	12/2017	Baughman et al.	N/A	N/A
2018/0349797	12/2017	Garvey et al.	N/A	N/A
2018/0356775	12/2017	Harvey	N/A	N/A
2018/0359111	12/2017	Harvey	N/A	N/A
2018/0364654	12/2017	Locke et al.	N/A	N/A
2019/0005025	12/2018	Malabarba	N/A	N/A
2019/0013023	12/2018	Pourmohammad et al.	N/A	N/A
2019/0025771	12/2018	Park et al.	N/A	N/A
2019/0037135	12/2018	Hedge	N/A	N/A
2019/0042988	12/2018	Brown et al.	N/A	N/A
2019/0088106	12/2018	Grundstrom	N/A	N/A
2019/0094824	12/2018	Xie et al.	N/A	N/A
2019/0095644	12/2018	Park et al.	N/A	N/A
2019/0096217	12/2018	Pourmohammad et al.	N/A	N/A
2019/0102840	12/2018	Perl et al.	N/A	N/A
2019/0121801	12/2018	Jethwa et al.	N/A	N/A
2019/0138512	12/2018	Pourmohammad et al.	N/A	N/A
2019/0147883	12/2018	Mellenthin et al.	N/A	N/A
2019/0158309	12/2018	Park et al.	N/A	N/A
2019/0163152	12/2018	Worrall et al.	N/A	N/A
2019/0268178	12/2018	Fairweather et al.	N/A	N/A
2019/0278777	12/2018	Malik et al.	N/A	N/A
2019/0310979	12/2018	Masuzaki et al.	N/A	N/A
2019/0353376	12/2018	Rigg et al.	N/A	N/A
2019/0377306	12/2018	Harvey	N/A	N/A
2020/0034622	12/2019	Thakurta et al.	N/A	N/A
2020/0051440	12/2019	Yousif et al.	N/A	N/A
2020/0133978	12/2019	Ramamurti et al.	N/A	N/A
2020/0142365	12/2019	Sharma	N/A	G06N 7/01
2020/0143313	12/2019	Ohlsson et al.	N/A	N/A
2020/0210923	12/2019	Palmer	N/A	G06Q 10/04
2020/0226156	12/2019	Borra et al.	N/A	N/A
2020/0234220	12/2019	Ma	N/A	G08G 1/148
2020/0285203	12/2019	Thakur et al.	N/A	N/A
2020/0336328	12/2019	Harvey	N/A	N/A
2020/0348632	12/2019	Harvey	N/A	N/A
2020/0387576	12/2019	Brett et al.	N/A	N/A
2020/0396208	12/2019	Brett et al.	N/A	N/A
2021/0042299	12/2020	Migliori	N/A	N/A
2021/0043221	12/2020	Yelchuru et al.	N/A	N/A
2021/0080915	12/2020	Yan et al.	N/A	N/A
2021/0133670	12/2020	Cella et al.	N/A	N/A
2021/0173969	12/2020	Abbey	N/A	G06F 30/13
2021/0200171	12/2020	Sridharan et al.	N/A	N/A
2021/0200174	12/2020	Sridharan et al.	N/A	N/A
2021/0200713	12/2020	Sridharan et al.	N/A	N/A
2021/0248289	12/2020	Fasano	N/A	N/A
2021/0248514	12/2020	Cella	N/A	G06V 20/20

2021/0272394	12/2020	Cella	N/A	N/A
2021/0279957	12/2020	Eder et al.	N/A	N/A
2021/0287521	12/2020	Stone et al.	N/A	N/A
2021/0325070	12/2020	Endel et al.	N/A	N/A
2021/0342961	12/2020	Winter et al.	N/A	N/A
2021/0350877	12/2020	Spurbeck	N/A	G16H 10/40
2021/0356153	12/2020	Nesler	N/A	F24F 11/46
2021/0366062	12/2020	Trundle	N/A	N/A
2021/0366608	12/2020	Podobas et al.	N/A	N/A
2021/0373509	12/2020	Borah et al.	N/A	N/A
2021/0373510	12/2020	Borah et al.	N/A	N/A
2021/0381711	12/2020	Harvey et al.	N/A	N/A
2021/0381712	12/2020	Harvey et al.	N/A	N/A
2021/0382445	12/2020	Harvey et al.	N/A	N/A
2021/0383041	12/2020	Harvey et al.	N/A	N/A
2021/0383042	12/2020	Harvey et al.	N/A	N/A
2021/0383200	12/2020	Harvey et al.	N/A	N/A
2021/0383219	12/2020	Harvey et al.	N/A	N/A
2021/0383235	12/2020	Harvey et al.	N/A	N/A
2021/0383236	12/2020	Harvey et al.	N/A	N/A
2021/0390498	12/2020	Ohlsson et al.	N/A	N/A
2021/0390807	12/2020	Chaurasia	N/A	G07C 9/27
2022/0004672	12/2021	Santarone et al.	N/A	N/A
2022/0028159	12/2021	Vincent et al.	N/A	N/A
2022/0066402	12/2021	Harvey et al.	N/A	N/A
2022/0066405	12/2021	Harvey	N/A	N/A
2022/0066415	12/2021	Miller et al.	N/A	N/A
2022/0066432	12/2021	Harvey et al.	N/A	N/A
2022/0066434	12/2021	Harvey et al.	N/A	N/A
2022/0066528	12/2021	Harvey et al.	N/A	N/A
2022/0066722	12/2021	Harvey et al.	N/A	N/A
2022/0066754	12/2021	Harvey et al.	N/A	N/A
2022/0066761	12/2021	Harvey et al.	N/A	N/A
2022/0067226	12/2021	Harvey et al.	N/A	N/A
2022/0067227	12/2021	Harvey et al.	N/A	N/A
2022/0067230	12/2021	Harvey et al.	N/A	N/A
2022/0069863	12/2021	Harvey et al.	N/A	N/A
2022/0070293	12/2021	Harvey et al.	N/A	N/A
2022/0082280	12/2021	Douglas et al.	N/A	N/A
2022/0090927	12/2021	Shear	N/A	G01C 21/3492
2022/0092418	12/2021	Liu et al.	N/A	N/A
2022/0121965	12/2021	Chatterji et al.	N/A	N/A
2022/0138684	12/2021	Harvey	N/A	N/A
2022/0147000	12/2021	Cooley et al.	N/A	N/A
2022/0150124	12/2021	Cooley et al.	N/A	N/A
2022/0187818	12/2021	Kondejkar et al.	N/A	N/A
2022/0215264	12/2021	Harvey et al.	N/A	N/A
2022/0277851	12/2021	Wellig	N/A	N/A
2023/0010757	12/2022	Preciado	N/A	N/A
2023/0071312	12/2022	Preciado et al.	N/A	N/A
2023/0076011	12/2022	Preciado et al.	N/A	N/A
2023/0083703	12/2022	Meiners	N/A	N/A
2023/0099791	12/2022	Ghosh et al.	N/A	N/A
2023/0101023	12/2022	Jin et al.	N/A	N/A

2023/0113095	12/2022	Dixit et al.	N/A	N/A
--------------	---------	--------------	-----	-----

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2019226217	12/2019	AU	N/A
2019226264	12/2019	AU	N/A
101415011	12/2008	CN	N/A
102136099	12/2010	CN	N/A
102136100	12/2010	CN	N/A
102650876	12/2011	CN	N/A
104040583	12/2013	CN	N/A
104603832	12/2014	CN	N/A
104919484	12/2014	CN	N/A
106204392	12/2015	CN	N/A
106406806	12/2016	CN	N/A
106960269	12/2016	CN	N/A
107147639	12/2016	CN	N/A
107598928	12/2017	CN	N/A
110046316	12/2018	CN	N/A
111860900	12/2019	CN	N/A
2 528 033	12/2011	EP	N/A
3 268 821	12/2017	EP	N/A
3 324 306	12/2017	EP	N/A
4 226 263	12/2022	EP	N/A
H10-049552	12/1997	JP	N/A
2003-162573	12/2002	JP	N/A
2007-018322	12/2006	JP	N/A
4073946	12/2007	JP	N/A
2008-107930	12/2007	JP	N/A
2012-108571	12/2011	JP	N/A
2013-152618	12/2012	JP	N/A
2014-044457	12/2013	JP	N/A
2016/0102923	12/2015	KR	N/A
20210063688	12/2020	KR	N/A
WO-2009/020158	12/2008	WO	N/A
WO-2011/100255	12/2010	WO	N/A
WO-2013/050333	12/2012	WO	N/A
WO-2015/106702	12/2014	WO	N/A
WO-2015/145648	12/2014	WO	N/A
WO-2017/035536	12/2016	WO	N/A
WO-2017/192422	12/2016	WO	N/A
WO-2017/194244	12/2016	WO	N/A
WO-2017/205330	12/2016	WO	N/A
WO-2017/213918	12/2016	WO	N/A
WO-2018/132112	12/2017	WO	N/A
WO-2020/061621	12/2019	WO	N/A
WO-2022/042925	12/2021	WO	N/A
WO-2022/103812	12/2021	WO	N/A
WO-2022/103813	12/2021	WO	N/A
WO-2022/103820	12/2021	WO	N/A
WO-2022/103822	12/2021	WO	N/A
WO-2022/103824	12/2021	WO	N/A
WO-2022/103829	12/2021	WO	N/A
WO-2022/103831	12/2021	WO	N/A

OTHER PUBLICATIONS

U.S. Appl. No. 17/566,029, Passivelogic, Inc. cited by applicant

U.S. Appl. No. 17/567,275, Passivelogic, Inc. cited by applicant

U.S. Appl. No. 17/722,115, Passivelogic, Inc. cited by applicant

Sinha, Sudhi and Al Huraimel, Khaled, "Reimagining Businesses with AI" John Wiley & Sons, Inc., Hoboken, NJ, USA, First ed. published 2020 (156 pages). cited by applicant

Balaji et al, "Brick: Metadata schema for portable smart building applications," Applied Energy, 2018 (20 pages). cited by applicant

Balaji et al, "Brick: Metadata schema for portable smart building applications," Applied Energy, Sep. 15, 2018, 3 pages, (Abstract). cited by applicant

Balaji et al, "Demo Abstract: Portable Queries Using the Brick Schema for Building Applications," BuildSys '16, Palo Alto, CA, USA, Nov. 16-17, 2016 (2 pages). cited by applicant

Balaji, B. et al., "Brick: Towards a Unified Metadata Schema For Buildings." BuildSys '16, Palo Alto, CA, USA, Nov. 16-17, 2016 (10 pages). cited by applicant

Bhattacharya et al., "Short Paper: Analyzing Metadata Schemas for Buildings—The Good, The Bad and The Ugly," BuildSys '15, Seoul, South Korea, Nov. 4-5, 2015 (4 pages). cited by applicant

Bhattacharya, A., "Enabling Scalable Smart-Building Analytics," Electrical Engineering and Computer Sciences, University of California at Berkeley, Technical Report No. UCB/EECS-2016-201, Dec. 15, 2016 (121 pages). cited by applicant

Brick, "Brick Schema: Building Blocks for Smart Buildings," URL: chrome-extension://efaidnbmnnnibpcajpcglclefindmkaj/https://www.memoori.com/wp-content/uploads/2016/06/Brick_Schema_Whitepaper.pdf, Mar. 2019 (17 pages). cited by applicant

Brick, "Brick: Towards a Unified Metadata Schema For Buildings," URL: chrome-extension://efaidnbmnnnibpcajpcglclefindmkaj/https://brickschema.org/papers/Brick_BuildSys_Presentation.pdf, Presented at BuildSys '16, Nov. 2016 (46 pages). cited by applicant

Brick, "Metadata Schema for Buildings," URL: <https://brickschema.org/docs/Brick-Leaflet.pdf>, retrieved from internet Dec. 24, 2019 (3 pages). cited by applicant

Chinese Office Action on CN Appl. No. 201780003995.9 dated Apr. 8, 2021 (21 pages with English language translation). cited by applicant

Chinese Office action on CN Appl. No. 201780043400.2 dated Apr. 25, 2021 (15 pages with English language translation). cited by applicant

Curry, E. et al., "Linking building data in the cloud: Integrating cross-domain building data using linked data." Advanced Engineering Informatics, 2013, 27 (pp. 206-219). cited by applicant

Digital Platform Litigation Documents Part 1, includes cover letter, dismissal of case DDE-1-21-cv-01796, IPR2023-00022 (documents filed Jan. 26, 2023-Oct. 7, 2022), and IPR2023-00085 (documents filed Jan. 26, 2023-Oct. 20, 2022) (748 pages total). cited by applicant

Digital Platform Litigation Documents Part 10, includes DDE-1-21-cv-01796 (documents filed Nov. 1, 2022-Dec. 22, 2021 (1795 pages total). cited by applicant

Digital Platform Litigation Documents Part 2, includes IPR2023-00085 (documents filed Oct. 20, 2022) (172 pages total). cited by applicant

Digital Platform Litigation Documents Part 3, includes IPR2023-00085 (documents filed Oct. 20, 2022) and IPR2023-00170 (documents filed Nov. 28, 2022-Nov. 7, 2022) (397 pages total). cited by applicant

Digital Platform Litigation Documents Part 4, includes IPR2023-00170 (documents filed Nov. 7, 2022) and IPR2023-00217 (documents filed Jan. 18, 2023-Nov. 15, 2022) (434 pages total). cited by applicant

Digital Platform Litigation Documents Part 5, includes IPR2023-00217 (documents filed Nov. 15, 2022) and IPR2023-00257 (documents filed Jan. 25, 2023-Nov. 23, 2022) (316 pages total). cited by applicant

Digital Platform Litigation Documents Part 6, includes IPR2023-00257 (documents filed Nov. 23, 2022) and IPR2023-00346 (documents filed Jan. 3, 2023-Dec. 13, 2022) (295 pages total). cited by applicant

Digital Platform Litigation Documents Part 7, includes IPR 2023-00346 (documents filed Dec. 13, 2022) and IPR2023-00347 (documents filed Jan. 3, 2023-Dec. 13, 2022) (217 pages total). cited by applicant

Digital Platform Litigation Documents Part 8, includes IPR2023-00347 (documents filed Dec. 13, 2022), EDTX-2-22-cv-00243 (documents filed Sep. 20, 2022-Jun. 29, 2022), and DDE-1-21-cv-01796 (documents filed Feb. 3, 2023-Jan. 10, 2023 (480 pages total). cited by applicant

Digital Platform Litigation Documents Part 9, includes DDE-1-21-cv-01796 (documents filed Jan. 10, 2023-Nov. 1, 2022 (203 pages total)). cited by applicant

El Kaed, C. et al., "Building management insights driven by a multi-system semantic representation approach," 2016 IEEE 3rd World Forum on Internet of Things (WF-IoT), Dec. 12-14, 2016, (pp. 520-525). cited by applicant

Ellis, C. et al., "Creating a room connectivity graph of a building from per-room sensor units." BuildSys '12, Toronto, ON, Canada, Nov. 6, 2012 (7 pages). cited by applicant

Extended European Search Report on EP Application No. 18196948.6 dated Apr. 10, 2019 (9 pages). cited by applicant

Fierro et al., "Beyond a House of Sticks: Formalizing Metadata Tags with Brick," BuildSys '19, New York, NY, USA, Nov. 13-14, 2019 (10 pages). cited by applicant

Fierro et al., "Dataset: An Open Dataset and Collection Tool for BMS Point Labels," Data'19, New York, NY, USA, Nov. 10, 2019 (3 pages). cited by applicant

Fierro et al., "Design and Analysis of a Query Processor for Brick," ACM Transactions on Sensor Networks, Jan. 2018, vol. 1, No. 1, art. 1 (25 pages). cited by applicant

Fierro et al., "Design and Analysis of a Query Processor for Brick," BuildSys '17, Delft, Netherlands, Nov. 8-9, 2017 (10 pages). cited by applicant

Fierro et al., "Mortar: An Open Testbed for Portable Building Analytics," BuildSys '18, Shenzhen, China, Nov. 7-8, 2018 (10 pages). cited by applicant

Fierro et al., "Why Brick is a Game Changer for Smart Buildings," URL: https://brickschema.org/papers/Brick_Memoori_Webinar_Presentation.pdf, Memoori Webinar, 2019 (67 pages). cited by applicant

Fierro, "Writing Portable Building Analytics with the Brick Metadata Schema," UC Berkeley, ACM E-Energy, 2019 (39 pages). cited by applicant

Fierro, G., "Design of an Effective Ontology and Query Processor Enabling Portable Building Applications," Electrical Engineering and Computer Sciences, University of California at Berkeley, Technical Report No. UCB/EECS-2019-106, June 27, 2019 (118 pages). cited by applicant

File History for U.S. Appl. No. 12/776,159, filed May 7, 2010 (722 pages). cited by applicant

Final Conference Program, ACM BuildSys 2016, Stanford, CA, USA, Nov. 15-17, 2016 (7 pages). cited by applicant

Gao et al., "A large-scale evaluation of automated metadata inference approaches on sensors from air handling units," Advanced Engineering Informatics, 2018, 37 (pp. 14-30). cited by applicant

Harvey, T., "Quantum Part 3: The Tools of Autonomy, How PassiveLogic's Quantum Creator and Autonomy Studio software works," URL: <https://www.automatedbuildings.com/news/jan22/articles/passive/211224010000passive.html>, Jan. 2022 (7 pages). cited by applicant

Harvey, T., "Quantum: The Digital Twin Standard for Buildings," URL: <https://www.automatedbuildings.com/news/feb21/articles/passivelogic/210127124501passivelogic.html>, Feb. 2021 (6 pages). cited by applicant

Hu, S. et al., "Building performance optimisation: A hybrid architecture for the integration of contextual information and time-series data," Automation in Construction, 2016, 70 (pp. 51-61). cited by applicant

International Search Report and Written Opinion for PCT Appl. Ser. No. PCT/US2017/013831 dated Mar. 31, 2017 (14 pages). cited by applicant

International Search Report and Written Opinion for PCT Appl. Ser. No. PCT/US2017/035524 dated Jul. 24, 2017 (14 pages). cited by applicant

International Search Report and Written Opinion on PCT/US2017/052060, mailed Oct. 5, 2017, 11 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2017/052633, mailed Oct. 23, 2017, 9 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2017/052829, mailed Nov. 27, 2017, 24 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/024068, mailed Jun. 15, 2018, 22 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/052971, dated Mar. 1, 2019, 19 pages. cited

by applicant

International Search Report and Written Opinion on PCT/US2018/052974, mailed Dec. 19, 2018, 13 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/052975, mailed Jan. 2, 2019, 13 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2018/052994, mailed Jan. 7, 2019, 15 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2019/015481, dated May 17, 2019, 78 pages. cited by applicant

International Search Report and Written Opinion on PCT/US2020/058381, dated Jan. 27, 2021, 30 pages. cited by applicant

Japanese Office Action on JP Appl. No. 2018-534963 dated May 11, 2021 (16 pages with English language translation). cited by applicant

Koh et al., "Plaster: An Integration, Benchmark, and Development Framework for Metadata Normalization Methods," BuildSys '18, Shenzhen, China, Nov. 7-8, 2018 (10 pages). cited by applicant

Koh et al., "Scrabble: Transferrable Semi-Automated Semantic Metadata Normalization using Intermediate Representation," BuildSys '18, Shenzhen, China, Nov. 7-8, 2018 (10 pages). cited by applicant

Koh et al., "Who can Access What, and When?" BuildSys '19, New York, NY, USA, Nov. 13-14, 2019 (4 pages). cited by applicant

Li et al., "Event Stream Processing with Out-of-Order Data Arrival," International Conferences on Distributed Computing Systems, 2007, (8 pages). cited by applicant

Nissin Electric Co., Ltd., "Smart power supply system (SPSS)," Outline of the scale verification plan, Nissin Electric Technical Report, Japan, Apr. 23, 2014, vol. 59, No. 1 (23 pages). cited by applicant

Passivelogic, "Explorer: Digital Twin Standard for Autonomous Systems. Made interactive." URL: <https://passivelogic.com/software/quantum-explorer/>, retrieved from internet Jan. 4, 2023 (13 pages). cited by applicant

Passivelogic, "Quantum: The Digital Twin Standard for Autonomous Systems, A physics-based ontology for next-generation control and AI." URL: <https://passivelogic.com/software/quantum-standard/>, retrieved from internet Jan. 4, 2023 (20 pages). cited by applicant

Quantum Alliance, "Quantum Explorer Walkthrough," 2022, (7 pages) (screenshots from video). cited by applicant

Results of the Partial International Search for PCT/US2018/052971, dated Jan. 3, 2019, 3 pages. cited by applicant

Sinha, Sudhi and Al Huraimel, Khaled, "Reimagining Businesses with AI" John Wiley & Sons, Inc., Hoboken, NJ, USA, 2021 (156 pages). cited by applicant

Sinha, Sudhi R. and Park, Youngchoon, "Building an Effective IoT Ecosystem for Your Business," Johnson Controls International, Springer International Publishing, 2017 (286 pages). cited by applicant

Sinha, Sudhi, "Making Big Data Work For Your Business: A guide to effective Big Data analytics," Impactt Publishing Ltd., Birmingham, UK, Oct. 2014 (170 pages). cited by applicant

The Virtual Nuclear Tourist, "Calvert Cliffs Nuclear Power Plant," URL: <http://www.nucleartourist.com/us/calvert.htm>, Jan. 11, 2006 (2 pages). cited by applicant

University of California at Berkeley, EECS Department, "Enabling Scalable Smart-Building Analytics," URL: <https://www2.eecs.berkeley.edu/Pubs/TechRpts/2016/EECS-2016-201.html>, retrieved from internet Feb. 15, 2022 (7 pages). cited by applicant

Van Hoof, Bert, "Announcing Azure Digital Twins: Create digital replicas of spaces and infrastructure using cloud, AI and IoT," URL: <https://azure.microsoft.com/en-us/blog/announcing-azure-digital-twins-create-digital-replicas-of-spaces-and-infrastructure-using-cloud-ai-and-iot/>, Sep. 24, 2018 (11 pages). cited by applicant

W3C, "SPARQL: Query Language for RDF," located on The Wayback Machine, URL: <https://web.archive.org/web/20161230061728/http://www.w3.org/TR/rdf-sparql-query/>), retrieved from internet Nov. 15, 2022 (89 pages). cited by applicant

Wei et al., "Development and Implementation of Software Gateways of Fire Fighting Subsystem Running on EBI," Control, Automation and Systems Engineering, IITA International Conference on, IEEE, Jul. 2009 (pp. 9-12). cited by applicant

White et al., "Reduce building maintenance costs with AWS IoT TwinMaker Knowledge Graph," The Internet of

Things on AWS—Official Blog, URL: <https://aws.amazon.com/blogs/iot/reduce-building-maintenance-costs-with-aws-iot-twinmaker-knowledge-graph/>, Nov. 18, 2022 (10 pages). cited by applicant
Zhou, Q. et al., “Knowledge-infused and Consistent Complex Event Processing over Real-time and Persistent Streams,” *Further Generation Computer Systems*, 2017, 76 (pp. 391-406). cited by applicant

Primary Examiner: Poudel; Santosh R

Attorney, Agent or Firm: Foley & Lardner LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation-in-part of U.S. patent application Ser. No. 17/537,046 filed Nov. 29, 2021, the entirety of which is incorporated by reference herein.

BACKGROUND

(1) This application relates generally to a building system of a building. This application relates more particularly to a system for managing and processing data of the building system.

(2) A building may aggregate and store building data received from building equipment and/or other data sources. The building data can be stored in a database. The building can include a building system that operates analytic and/or control algorithms against the data of the database to control the building equipment. However, the development and/or deployment of the analytic and/or control algorithms may be time consuming and require a significant amount of software development. Furthermore, the analytic and/or control algorithms may lack flexibility to adapt to changing circumstances in the building. In some cases, the output data of the analytic and/or control algorithms may be hard for a user to conceptualize and relate to the physical components of the building for which the information is generated for.

SUMMARY

(3) Predictive Visualization

(4) One implementation of the present disclosure is a building system of a building. The building system includes one or more storage devices storing instructions thereon that, when executed by one or more processors, cause the one or more processors to store a digital twin of the building in the one or more storage devices, the digital twin comprising a virtual representation of the building with an entity of the building, a data point, and an interrelationship between the entity of the building and the data point, wherein the digital twin further includes an artificial intelligence configured to generate a plurality of inference values of the data point for a plurality of future times, the data point related to the building by the interrelationship of the digital twin, generate a recommendation based on the plurality of inference values for the data point for the plurality of future times, the recommendation recommending making one or more updates to the building, and cause a graphic representation of the building to display an indication of the recommendation at a location within the graphic representation of the building associated with the entity based on the digital twin indicating the data point being related to the entity.

(5) In some implementations, the instructions cause the one or more processors to receive a plurality of data point values for the data point from building equipment, the building equipment generates the data point values based on operation to control an environmental condition of the building, identify the data point based on the digital twin by identifying the interrelationship between the entity and the data point, the entity representing the building equipment, and store the plurality of data points, or a link to the plurality of data points, in the data point of the digital twin.

(6) In some implementations, the plurality of inference values include predicted future values of the data point. In some implementations, the instructions cause the one or more processors to generate the inference values by identifying the data point of the digital twin and retrieving the plurality of data values based on the data point of the digital twin and executing the artificial intelligence to generate the plurality of inference values based on the plurality of data values. In some implementations, the plurality of inference values are predicted future values of a virtual indicator, wherein the virtual indicator is at least one of a clean air virtual indicator indicating a level of air quality of a building space, an occupancy

number indicating a number of occupants in the building space, or a reproduction number indicating a spread of an infectious disease in a population.

(7) In some implementations, the digital twin includes a building graph data structure including a plurality of nodes representing a plurality of entities of the building and a plurality of edges between the plurality of nodes representing a plurality of relationships between the plurality of entities of the building. In some implementations, the instructions cause the one or more processors to cause the graphic representation of the building to display the indication of the recommendation through the plurality of future times. In some implementations, the recommendation includes a recommendation to update operating settings of building equipment of the building, the operating settings updating operation of the building equipment. In some implementations, the instructions cause the one or more processors to cause the graphic representation of the building to display updated operation of the building equipment through the plurality of future times.

(8) In some implementations, the recommendation to update operating settings of the building equipment includes at least one of a recommendation to make a command for an air handling unit to change an air flow through the building, a recommendation to command the air handling unit to change an air filtration setting for the building, a recommendation to command one or more disinfectant lights to activate, or a recommendation to command building security mechanisms to restrict access to one or more portions of the building. In some implementations, the recommendation includes a status of the actuation on the physical asset. In some implementations, the inference value includes at least one of a disease reproduction number indicating a rate at which an infectious disease spreads in a population, an energy consumption value indicating a level of energy consumed by building equipment of the building, or a clean air score indicating a quality of air in the building. In some implementations, the instructions further cause the one or more processors to generate diagnostics for at least one of a reproduction number, an energy consumption value, and a clean air score, wherein the diagnostic includes text indicating a cause of values of the reproduction number, an energy consumption value, or a clean air score.

(9) Another implementation of the present disclosure is a method. The method includes storing a digital twin of the building in the one or more storage devices, the digital twin comprising a virtual representation of the building with an entity of the building, a data point, and an interrelationship between the entity of the building and the data point, wherein the digital twin further includes an artificial intelligence configured to generate a plurality of inference values of the data point for a plurality of future times, the data point related to the building by the interrelationship of the digital twin, generating a recommendation based on the plurality of inference values for the data point for the plurality of future times, the recommendation recommending making one or more updates to the building, and causing a graphic representation of the building to display an indication of the recommendation at a location within the graphic representation of the building associated with the entity based on the digital twin indicating the data point being related to the entity.

(10) In some implementations, the method further includes receiving a plurality of data point values for the data point from building equipment, the building equipment generates the data point values based on operation to control an environmental condition of the building, identifying the data point based on the digital twin by identifying the interrelationship between the entity and the data point, the entity representing the building equipment, and storing the plurality of data points, or a link to the plurality of data points, in the data point of the digital twin. In some implementations, the plurality of inference values include predicted future values of the data point. In some implementations, the method generates the plurality of inference values by identifying the data point of the digital twin and retrieving the data values based on the data point of the digital twin and executing the artificial intelligence to generate the plurality of inference values based on the data values.

(11) In some implementations, the plurality of inference values are predicted future values of a virtual indicator, wherein the virtual indicator is at least one of a clean air virtual indicator indicating a level of air quality of a building space, an occupancy number indicating a number of occupants in the building space, or a reproduction number indicating a spread of an infectious disease in a population. In some implementations, the method further includes generating diagnostics for at least one of a reproduction number, an energy consumption value, and a clean air score, wherein the diagnostic includes text indicating a cause of values of the reproduction number, an energy consumption value, or a clean air score. In some implementations, the recommendation includes a recommendation to update operating settings of building equipment of the building, the operating settings updating operation of the building equipment. In

some implementations, the recommendation to update operating settings of the building equipment includes at least one of a recommendation to make a command for an air handling unit to change an air flow through the building, a recommendation to command the air handling unit to change an air filtration setting for the building, a recommendation to command one or more disinfectant lights to activate, or a recommendation to command building security mechanisms to restrict access to one or more portions of the building.

(12) Another implementation of the present disclosure is a non-transitory computer readable media containing program instructions that, when executed by one or more processors, cause the one or more processors to perform operations. The operations include storing a digital twin of the building in the one or more storage devices, the digital twin comprising a virtual representation of the building with an entity of the building, a data point, and an interrelationship between the entity of the building and the data point, wherein the digital twin further includes an artificial intelligence configured to generate a plurality of inference values of the data point for a plurality of future times, the data point related to the building by the interrelationship of the digital twin, generating a recommendation based on the plurality of inference values for the data point for the plurality of future times, the recommendation recommending making one or more updates to the building, and causing a graphic representation of the building to display an indication of the recommendation at a location within the graphic representation of the building associated with the entity based on the digital twin indicating the data point being related to the entity.

(13) Infectious Disease Management

(14) Another implementation of the present disclosure is a building system of a building. The building system includes one or more storage devices storing instructions thereon that, when executed by one or more processors, cause the one or more processors to store a digital twin of the building in the one or more storage devices, the digital twin comprising a virtual representation of the building with an entity of the building, a data point, and an interrelationship between the entity of the building and the data point, wherein an infectious disease indicator of an infectious disease is related to the entity of the building by the digital twin, receive building data for the entity and generate the infectious disease indicator based on the building data, generate a recommendation for reducing a spread of the infectious disease within the building based on the infectious disease indicator, and cause a graphic representation of the building to display an indication of the recommendation at a location within the graphic representation of the building associated with the entity based on the digital twin indicating the infectious disease indicator being related to the entity.

(15) In some implementations, the recommendation includes at least one of updating operation of an air handling unit to change an air flow through the building, updating operation of the air handling unit to change an air filtration setting for the building, operating one or more disinfectant lights to go from an off position to an on position, and operating one or more building security mechanisms to restrict access to one or more portions of the building. In some implementations, the recommendation includes occupant behavior policies for the building, wherein the occupant behavior policies includes at least one or a remote work policy, a mask wearing policy, an occupant social distancing policy, and an occupant limit for one or more spaces. In some embodiments, the infectious disease indicator is a disease reproductive number. In some embodiments, the entities of the building includes at least one of a building space, a floor of the building, a piece of building equipment, and the building occupant.

(16) In some implementations, the recommendation to update operating settings of the building equipment includes at least one of a recommendation to make a command for an air handling unit to change an air flow through the building, a recommendation to command the air handling unit to change an air filtration setting for the building, a recommendation to command one or more disinfectant lights to activate, or a recommendation to command building security mechanisms to restrict access to one or more portions of the building. In some implementations, the recommendation includes recommendations to implement or change a remote work policy, a mask wearing policy, an occupant social distancing policy, or an occupant limit for one or more spaces.

(17) In some implementations, the infectious disease indicator is a disease reproductive number indicating a spread of an infectious disease in a population. In some implementations, the infection disease indicator is generated for at least one of a building space, a floor of the building, a piece of building equipment, and the building occupant. In some implementations, the instructions cause the one or more processors to receive a plurality of data point values for the data point from building equipment, the building equipment

generates the data point values based on operation to control an environmental condition of the building, identifies the data point based on the digital twin by identifying the interrelationship between the entity and the data point, the entity representing the building equipment, and stores the plurality of data points, or a link to the plurality of data points, in the data point of the digital twin.

(18) In some implementations, the plurality of inference values include predicted future values of the data point. In some implementations, the instructions cause the one or more processors to generate the plurality of inference values by identifying the data point of the digital twin and retrieving the plurality of data values based on the data point of the digital twin executing the artificial intelligence to generate the plurality of inference values based on the plurality of data values. In some implementations, the digital twin includes a building graph data structure including a plurality of nodes representing the plurality of entities of the building and a plurality of edges between the plurality of nodes representing the interrelationship between the plurality of entities of the building. In some implementations, the instructions cause the one or more processors to perform a comparison of the infectious disease indicator to a threshold and determine an appearance of the infectious disease indicator based on the comparison. In some implementations, the instructions further cause the one or more processors to generate diagnostics for at least one of a reproduction number, an energy consumption value, and a clean air score, wherein the diagnostic provides a reasoning for why the reproduction number, an energy consumption value, and a clean air score are what they are.

(19) Another implementation of the present disclosure is a method. The method includes storing a digital twin of the building in the one or more storage devices, the digital twin comprising a virtual representation of the building with an entity of the building, a data point, and an interrelationship between the entity of the building and the data point, wherein an infectious disease indicator of an infectious disease is related to the entity of the building by the digital twin, receiving building data for the entity and generate the infectious disease indicator based on the building data, generating a recommendation for reducing a spread of the infectious disease within the building based on the infectious disease indicator, and causing a graphic representation of the building to display an indication of the recommendation at a location within the graphic representation of the building associated with the entity based on the digital twin indicating the infectious disease indicator being related to the entity.

(20) In some implementations, the recommendation to update operating settings of the building equipment includes at least one of a recommendation to make a command for an air handling unit to change an air flow through the building, a recommendation to command the air handling unit to change an air filtration setting for the building, a recommendation to command one or more disinfectant lights to activate, or a recommendation to command building security mechanisms to restrict access to one or more portions of the building. In some implementations, the recommendation includes recommendations to implement or change a remote work policy, a mask wearing policy, an occupant social distancing policy, or an occupant limit for one or more spaces. In some implementations, the infectious disease indicator is a disease reproductive number indicating a spread of an infectious disease in a population. In some implementations, the infection disease indicator is generated for at least one of a building space, a floor of the building, a piece of building equipment, and the building occupant. In some implementations, the method further includes receiving a plurality of data point values for the data point from building equipment, the building equipment generates the data point values based on operation to control an environmental condition of the building, identifying the data point based on the digital twin by identifying the interrelationship between the entity and the data point, the entity representing the building equipment, and storing the plurality of data points, or a link to the plurality of data points, in the data point of the digital twin.

(21) In some implementations, the method includes generating the plurality of inference values by identifying the data point of the digital twin, retrieving the plurality of data values based on the data point of the digital twin, and executing the artificial intelligence to generate the plurality of inference values based on the plurality of data values. In some implementations, the method includes performing a comparison of the infectious disease indicator to a threshold, and determining an appearance of the infectious disease indicator based on the comparison. In some implementations, the digital twin includes a building graph data structure including a plurality of nodes representing the plurality of entities of the building and a plurality of edges between the plurality of nodes representing the interrelationship between the plurality of entities of the building.

(22) Another implementation of the present disclosure is a non-transitory computer readable media containing program instructions that, when executed by one or more processors, cause the one or more processors to perform operations. The operations include storing a digital twin of the building in the one or more storage devices, the digital twin comprising a virtual representation of the building with an entity of the building, a data point, and an interrelationship between the entity of the building and the data point, wherein an infectious disease indicator of an infectious disease is related to the entity of the building by the digital twin, receiving building data for the entity and generate the infectious disease indicator based on the building data, generating a recommendation for reducing a spread of the infectious disease within the building based on the infectious disease indicator, and causing a graphic representation of the building to display an indication of the recommendation at a location within the graphic representation of the building associated with the entity based on the digital twin indicating the infectious disease indicator being related to the entity.

(23) Contact Tracing

(24) Another implementation of the present disclosure is a building system of a building. The building system includes one or more storage devices storing instructions thereon that, when executed by one or more processors, cause the one or more processors to: store a digital twin of the building in the one or more storage devices, the digital twin comprising a virtual representation of the building with a plurality of entities of the building and interrelationships between the plurality of entities of the building, wherein the digital twin further includes an artificial intelligence configured to simulate an airflow through the building and predict whether one or more occupants are potentially infected with an infectious disease, receive building data for the building from one or more pieces of equipment of the building, receive an indication of a location of an occupant and one or more indications of locations of one or more other occupants of the building, receive an indication that the occupant is infected with an infectious disease, and execute the artificial intelligence causing the artificial intelligence to simulate the air flow through the building based on the virtual representation of the building with the entities of the building and the interrelationships and the building data and predict whether the one or more other occupants of the building are potentially infected with the infectious disease based on the airflow, the location of the occupant, and the locations of the one or more other occupants.

(25) In some implementations, the instructions further cause the one or more processors to animate a graphic representation of the building to display the simulated airflow through the building. In some implementations, the instructions further cause the one or more processors to generate a user notification and push the user notification to a user device based on the prediction that the one or more other occupants of the building are potentially infected with the infectious disease. In some implementations, the instructions further cause the one or more processors to perform a comparison of the simulated airflow to a level, determine a characteristic of the airflow based on the comparison of the simulated airflow to the level, and display a representation of the characteristic of the airflow in the graphic representation. In some implementations, the characteristic of the airflow is a speed of the airflow. In some implementations, the representation of the characteristic is a color of one or more arrows representing a speed and direction of the simulated airflow. In some implementations, the digital twin includes a building graph data structure including a plurality of nodes representing the plurality of entities of the building and a plurality of edges between the nodes representing the interrelationship between the plurality of entities of the building.

(26) In some implementations, an infectious disease indicator of an infectious disease is related to an entity of the plurality of entities of the building by the digital twin. In some implementations, the instructions further cause the one or more processors to receive building data for the entity and generate the infectious disease indicator based on the building data, generate a recommendation for reducing a spread of the infectious disease within the building based on the infectious disease indicator, and cause a graphic representation of the building to display an indication of the recommendation at a location within the graphic representation of the building associated with the entity based on the digital twin indicating the infectious disease indicator being related to the entity. In some implementations, the recommendation to update operating settings of the building equipment includes at least one of a recommendation to make a command for an air handling unit to change an air flow through the building, a recommendation to command the air handling unit to change an air filtration setting for the building, a recommendation to command one or more disinfectant lights to activate, or a recommendation to command building security mechanisms to restrict access to one or more portions of the building. In some implementations, the

recommendation includes recommendations to implement or change a remote work policy, a mask wearing policy, an occupant social distancing policy, or an occupant limit for one or more spaces. In some implementations, the infection disease indicator is generated for at least one of a building space, a floor of the building, a piece of building equipment, and the building occupant.

(27) Another implementation of the present disclosure is a method. The method includes storing a digital twin of the building in the one or more storage devices, the digital twin comprising a virtual representation of the building with a plurality of entities of the building and interrelationships between the plurality of entities of the building, wherein the digital twin further includes an artificial intelligence configured to simulate an airflow through the building and predict whether one or more occupants are potentially infected with an infectious disease, receiving building data for the building from one or more pieces of equipment of the building, receiving an indication of a location of an occupant and one or more indications of locations of one or more other occupants of the building, receiving an indication that the occupant is infected with an infectious disease, and executing the artificial intelligence causing the artificial intelligence to simulate the air flow through the building based on the virtual representation of the building with the entities of the building and the interrelationships and the building data and predict whether the one or more other occupants of the building are potentially infected with the infectious disease based on the airflow, the location of the occupant, and the locations of the one or more other occupants.

(28) In some implementations, the method further includes comprising animating a graphic representation of the building to display the simulated airflow through the building. In some implementations, the method includes generating a user notification and push the user notification to a user device based on the prediction that the one or more other occupants of the building are potentially infected with the infectious disease. In some implementations, the method includes performing a comparison of the simulated airflow to a level, determining a characteristic of the airflow based on the comparison of the simulated airflow to the level, and displaying a representation of the characteristic of the airflow in the graphic representation. In some implementations, the digital twin includes a building graph data structure including a plurality of nodes representing the plurality of entities of the building and a plurality of edges between the plurality of nodes representing the interrelationship between the plurality of entities of the building. In some implementations, an infectious disease indicator of an infectious disease is related to an entity of the plurality of entities of the building by the digital twin. In some implementations, the method includes receiving building data for the entity and generate the infectious disease indicator based on the building data, generating a recommendation for reducing a spread of the infectious disease within the building based on the infectious disease indicator, and causing a graphic representation of the building to display an indication of the recommendation at a location within the graphic representation of the building associated with the entity based on the digital twin indicating the infectious disease indicator being related to the entity.

(29) In some implementations, the recommendation to update operating settings of the building equipment includes at least one of a recommendation to make a command for an air handling unit to change an air flow through the building, a recommendation to command the air handling unit to change an air filtration setting for the building, a recommendation to command one or more disinfectant lights to activate, or a recommendation to command building security mechanisms to restrict access to one or more portions of the building. In some implementations, the recommendation includes recommendations to implement or change a remote work policy, a mask wearing policy, an occupant social distancing policy, or an occupant limit for one or more spaces. In some implementations, the infection disease indicator is generated for at least one of a building space, a floor of the building, a piece of building equipment, and the building occupant.

(30) Another implementation of the present disclosure is a non-transitory computer readable media containing program instructions that, when executed by one or more processors, cause the one or more processors to perform operations. The operations include storing a digital twin of the building in the one or more storage devices, the digital twin comprising a virtual representation of the building with a plurality of entities of the building and interrelationships between the plurality of entities of the building, wherein the digital twin further includes an artificial intelligence configured to simulate an airflow through the building and predict whether one or more occupants are potentially infected with an infectious disease, receiving building data for the building from one or more pieces of equipment of the building, receiving an indication of a location of an occupant and one or more indications of locations of one or more other

occupants of the building, receiving an indication that the occupant is infected with an infectious disease, and executing the artificial intelligence causing the artificial intelligence to simulate the air flow through the building based on the virtual representation of the building with the entities of the building and the interrelationships and the building data and predict whether the one or more other occupants of the building are potentially infected with the infectious disease based on the airflow, the location of the occupant, and the locations of the one or more other occupants.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) Various objects, aspects, features, and advantages of the disclosure will become more apparent and better understood by referring to the detailed description taken in conjunction with the accompanying drawings, in which like reference characters identify corresponding elements throughout. In the drawings, like reference numbers generally indicate identical, functionally similar, and/or structurally similar elements.
- (2) FIG. 1 is a block diagram of a building data platform including an edge platform, a cloud platform, and a twin manager, according to an exemplary embodiment.
- (3) FIG. 2 is a graph projection of the twin manager of FIG. 1 including application programming interface (API) data, capability data, policy data, and services, according to an exemplary embodiment.
- (4) FIG. 3 is another graph projection of the twin manager of FIG. 1 including application programming interface (API) data, capability data, policy data, and services, according to an exemplary embodiment.
- (5) FIG. 4 is a graph projection of the twin manager of FIG. 1 including equipment and capability data for the equipment, according to an exemplary embodiment.
- (6) FIG. 5 is a block diagram of a system for managing a digital twin where an artificial intelligence agent can be executed to infer information for an entity of a graph, according to an exemplary embodiment.
- (7) FIG. 6 is a flow diagram of a process for executing an artificial intelligence agent to infer and/or predict information, according to an exemplary embodiment.
- (8) FIG. 7 is a diagram of a digital twin including a connector and a database, according to an exemplary embodiment.
- (9) FIG. 8 is a block diagram of a digital twin including triggers, connectors, actions, and a graph, according to an exemplary embodiment.
- (10) FIG. 9 is a block diagram of a people counter digital twin, an HVAC digital twin, and a facility manager digital twin that have triggers and actions that are interconnected, according to an exemplary embodiment.
- (11) FIG. 10 is a block diagram of an employee digital twin, a calendar digital twin, a meeting room digital twin, and a cafeteria digital twin that have triggers and actions that are interconnected, according to an exemplary embodiment.
- (12) FIG. 11 is a flow diagram an agent of a digital twin executing a trigger rule and an action rule, according to an exemplary embodiment.
- (13) FIG. 12 is a block diagram of a trigger rule of a thermostat digital twin where parameters of the trigger rule is trained, according to an exemplary embodiment.
- (14) FIG. 13 is a flow diagram of a process for identifying values for the parameters of the trigger rule of FIG. 12, according to an exemplary embodiment.
- (15) FIG. 14 is a minimization that can be performed to identify the values for the parameters of the trigger rule of FIGS. 12-13, according to an exemplary embodiment.
- (16) FIG. 15 is a block diagram of an action rule of a thermostat digital twin where parameters of the action rule is trained, according to an exemplary embodiment.
- (17) FIG. 16 is lists of states of a zone and of an air handler unit that can be used to train the parameters of the trigger rule and the action rule of the thermostat digital twins of FIGS. 12-15, according to an exemplary embodiment.
- (18) FIG. 17 is a block diagram of a trigger rule of a chemical reactor digital twin where parameters of the trigger rule are trained, according to an exemplary embodiment.
- (19) FIG. 18 is a flow diagram of a process for identifying values for the parameters of the trigger rule of

FIG. 17, according to an exemplary embodiment.

(20) FIG. 19 is a minimization that can be performed to identify the values for the parameters of the trigger rule of FIGS. 17-18, according to an exemplary embodiment.

(21) FIG. 20 is a block diagram of an action rule of a chemical reactor digital twin where parameters of the action rule are trained, according to an exemplary embodiment.

(22) FIG. 21 is lists of states of a reactor and a feed of a reactor that can be included in the trigger rule and the action rule of FIGS. 12-15, according to an exemplary embodiment.

(23) FIG. 22 is a block diagram of triggers and actions that can be constructed and learned for a digital twin, according to an exemplary embodiment.

(24) FIG. 23 is a flow diagram of a process for constructing triggers and actions for a digital twin, according to an exemplary embodiment.

(25) FIG. 24 is a block diagram of metadata sources being integrated with the building data platform of FIG. 1, according to an exemplary embodiment.

(26) FIG. 25 is another block diagram of metadata sources being integrated with the building data platform of FIG. 1 and including AI agents, according to an exemplary embodiment.

(27) FIG. 26 is a block diagram of a system where a clean air optimization (CAO) AI service 2604 and an energy prediction model (EPM) AI service operate to make inferences and predictions based on data of a knowledge graph is shown, according to an exemplary embodiment.

(28) FIG. 27 is a block diagram of a CAO AI agent and an EPM AI agent operating against the knowledge graph of FIG. 26 to generate inferences and predictions, according to an exemplary embodiment.

(29) FIG. 28 is a block diagram of inferences and predictions of the CAO AI agent and the EPM AI agent being presented in a graphic interface, according to an exemplary embodiment.

(30) FIG. 29 is an example interface that shows inferences and predictions within a graphical model, according to some embodiments.

(31) FIG. 30 is a schematic drawing of a three-dimensional graphical building, according to an exemplary embodiment.

(32) FIG. 31 is a schematic drawing of a floor of the three-dimensional graphical building of FIG. 30, according to an exemplary embodiment.

(33) FIG. 32 is a block diagram of a system ingesting data of a knowledge graph into the floor of FIG. 31, according to an exemplary embodiment.

(34) FIG. 33 is a schematic drawing of a floor of a building including indicators for a clean air score and a reproductive number, according to an exemplary embodiment.

(35) FIG. 34 is a table of information for ingesting the clean air score and the reproductive number into the floor of FIG. 33, according to an exemplary embodiment.

(36) FIG. 35 is a schematic drawing of a floor of a building including animated arrows indicating air flow, according to an exemplary embodiment.

(37) FIG. 36 is a table of information for ingesting a clean air delivery rate into the floor of FIG. 35, according to an exemplary embodiment.

(38) FIG. 37 is a schematic drawing of a floor of a building including indications of clean air score alarms and reproductive number alarms, according to an exemplary embodiment.

(39) FIG. 38 is a table of information for ingesting the clean air score and the reproductive number into the floor of the building of FIG. 37 and generating alarms based on the clean air score and the reproductive number for display within the floor of the building of FIG. 37, according to an exemplary embodiment.

(40) FIG. 39 is a block diagram of a facility manager interacting with a low clean air score displayed in a floor of a building and viewing diagnostic and action information, according to an exemplary embodiment.

(41) FIG. 40 is a schematic drawing of a block diagram of an occupant interacting with a high reproductive number displayed in a floor of a building and viewing diagnostic and action information, according to an exemplary embodiment.

(42) FIG. 41 is a table indicating information that could be displayed within a graphical building, according to an exemplary embodiment.

(43) FIG. 42 is a schematic drawing of an element for viewing future predictions of information in a floor of a building, according to an exemplary embodiment.

(44) FIG. 43 is a schematic drawing of an element for viewing an occupancy level and a clean air score in a floor of a building, according to an exemplary embodiment.

- (45) FIG. **44** is a schematic drawing of an element for viewing a predicted occupancy score and a predicted clean air score for a future time in a floor of a building, according to an exemplary embodiment.
- (46) FIG. **45** is a flow diagram of a process for generating and displaying, via a digital twin, a recommendation for updating a building, according to an exemplary embodiment.
- (47) FIG. **46** is a flow diagram of a process for generating and displaying, via a digital twin, a virtual indicator of an entity of a building based on telemetry data, according to an exemplary embodiment.
- (48) FIG. **47** is a flow diagram of a process for generating and displaying, via a digital twin, a recommendation for reducing the spread of an infection disease within a building, according to an exemplary embodiment.
- (49) FIG. **48** is a flow diagram of a process for using the artificial intelligence stored in the digital twin of FIG. **5** to simulate the air flow through the building and predict infectious disease values, according to an exemplary embodiment.
- (50) FIG. **49** is a flow diagram of a process for generating and displaying, via a digital twin, a graphic representation of a building with multiple states at one or more future times or one or more historical times, according to an exemplary embodiment.
- (51) FIG. **50** is a flow diagram of a process for generating and displaying, via a digital twin, a graphic representation of one or more predicted values at one or more future times of a building, according to an exemplary embodiment.
- (52) FIG. **51** is a flow diagram of a process for generating and displaying, via a digital twin, a graphic representation of a building at a historical time based on one or more historical operating scenarios, according to an exemplary embodiment.
- (53) FIG. **52** is a schematic drawing of viewing user interface including a predicted and actual occupancy score and a predicted and actual clean air score for a historical time in a floor of a building and running a simulation of the building at a historical time, according to an exemplary embodiment.

DETAILED DESCRIPTION

(54) Overview

(55) Referring generally to the FIGURES, systems and methods for digital twins of a building that integrate inferences and predictions with graphical building models are shown, according to various exemplary embodiments. In some embodiments, the graphical building models may be two-dimensional or three-dimensional graphical representation of the building. A digital twin can be a virtual representation of a building and/or an entity of the building (e.g., space, piece of equipment, occupant, etc.). Furthermore, the digital twin can represent a service performed in a building, e.g., facility management, clean air optimization, energy prediction, equipment maintenance, etc.

(56) A digital twin can be a virtual representation of a building and/or an entity of the building (e.g., space, piece of equipment, occupant, etc.). A virtual representation of a building could be a graph data structure. The virtual representation could be a graphic model, e.g., a building information model (BIM). The virtual representation of the building could be a hierarchical model, in some embodiments. Furthermore, the digital twin can represent a service performed in a building, e.g., facility management, equipment maintenance, etc. The digital twin can be displayed via virtual reality (VR) or augmented reality (AR) systems, in some embodiments.

(57) In some embodiments, the digital twin can include an information data store and a connector. The information data store can store the information describing the entity that the digital twin operates for (e.g., attributes of the entity, measurements associated with the entity, control points or commands of the entity, etc.). In some embodiments, the data store can be a graph including various nodes and edges. The connector can be a software component that provides telemetry from the entity (e.g., physical device) to the information store. Furthermore, the digital twin can include artificial intelligence (AI), e.g., an AI agent. The AI can be one or more machine learning algorithms and/or models that operate based on information of the information data store and outputs information. The AI agent can run against a common data model, e.g., BRICK, and can be easily implemented in various different buildings, e.g., against various different building models. Running against BRICK can allow for the AI agent to be plug-and-play and reduce AI design and/or deployment time. In some embodiments, the digital twin including the artificial intelligence may store the machine learning algorithms and/or models within the stored data structures (e.g., graph **526**). In some embodiments, the digital twin including the artificial intelligence may store a link to the machine learning algorithms and/or models within the data storage/graph where the

machine learning algorithms and/or model is stored and executed remotely to where the twin data is stored in the digital twin. In some embodiments, the digital twin including the artificial intelligence may store an identifier of the machine learning algorithms and/or model algorithm to be executed.

(58) In some embodiments, the AI agent for the digital twin can call an AI service to determine inferences and/or predict future data values. In some embodiments, the predictions are potential future states. In some embodiments, the predictions predict a timeseries of a data point into the future. The predictions could be predicted indoor temperature for an hour, inferred future air quality from 15 minute air quality readings, etc. In some embodiments, the digital twin can store predicted and/or inferred information in a graph data store as a node in the graph data store related to an entity that the digital twin represents or otherwise operates for. In some embodiments, the digital twin, or other digital twins, can operate against the predicted and/or inferred data, e.g., operate to construct and implement control algorithms for operating equipment of a building based on predicted future data points of the building.

(59) Furthermore, the AI agent can include various triggers and/or actions, conditions that define when and how command and control occurs for an entity. The triggers and actions can be rule based conditional and operational statements that are associated with a specific digital twin, e.g., are stored and executed by an AI agent of the digital twin. In some embodiments, the building system can identify actions and/or triggers (or parameters for the actions and/or triggers) through machine learning algorithms. In some embodiments, the building system can evaluate the conditions/context of the graph and determine and/or modify the triggers and actions of a digital twin.

(60) In some embodiments, the building system can implement and manage a three-dimensional (or two-dimensional) building model. The building system can cause the model to render in a user interface of a user device and allow a user to view the model, view information associated with the components of the model, and/or navigate throughout the model. The model can include information for various physical components, e.g., data for VAVs, data for thermostats, data for sensors, data for spaces, etc. In some embodiments, the information for the various physical components is generated based on a digital twin for those physical components, e.g., inferences or predictions generated for the physical components by one or more AI agents. The inferred and/or predicted information of the digital twin can be presented to the user in the three-dimensional and/or two-dimensional building model.

(61) Furthermore, in some embodiments, a user can provide commands and/or inputs into the digital twin via the building model. Various buttons and/or other input elements can be provided within the building model that a user can interact with via their user device. The inputs can be ingested into a graph of the digital twin and various agents of the digital twin can operate based on the ingested input. For example, a command or analysis request for data could be made via the building model. The command or analysis request could cause an agent to run to operate the building equipment based on the command and/or derive data for presentation in the building model. In some embodiments, the building model could be presented within a virtual reality (VR) view of the building configured to be presented on a virtual reality headset or other computing device. In some embodiments, the building model could be presented within an augmented reality (AR) view of the building configured to be presented on an augmented reality headset or other computing device configured to overlay the information on a live or real-world view of the building or a portion thereof. Furthermore, in some embodiments, the building model could be presented within a VR representation provided within a virtual metaverse.

(62) Referring now to FIG. 1, a building data platform **100** including an edge platform **102**, a cloud platform **106**, and a twin manager **108** are shown, according to an exemplary embodiment. The edge platform **102**, the cloud platform **106**, and the twin manager **108** can each be separate services deployed on the same or different computing systems. In some embodiments, the cloud platform **106** and the twin manager **108** are implemented in off premises computing systems, e.g., outside a building. The edge platform **102** can be implemented on-premises, e.g., within the building. However, any combination of on-premises and off-premises components of the building data platform **100** can be implemented.

(63) The building data platform **100** includes applications **110**. The applications **110** can be various applications that operate to manage the building subsystems **122**. The applications **110** can be remote or on-premises applications (or a hybrid of both) that run on various computing systems. The applications **110** can include an alarm application **168** configured to manage alarms for the building subsystems **122**. The applications **110** include an assurance application **170** that implements assurance services for the building subsystems **122**. In some embodiments, the applications **110** include an energy application **172**

configured to manage the energy usage of the building subsystems **122**. The applications **110** include a security application **174** configured to manage security systems of the building.

(64) In some embodiments, the applications **110** and/or the cloud platform **106** interacts with a user device **176**. In some embodiments, a component or an entire application of the applications **110** runs on the user device **176**. The user device **176** may be a laptop computer, a desktop computer, a smartphone, a tablet, and/or any other device with an input interface (e.g., touch screen, mouse, keyboard, etc.) and an output interface (e.g., a speaker, a display, etc.).

(65) The applications **110**, the twin manager **108**, the cloud platform **106**, and the edge platform **102** can be implemented on one or more computing systems, e.g., on processors and/or memory devices. For example, the edge platform **102** includes processor(s) **118** and memories **120**, the cloud platform **106** includes processor(s) **124** and memories **126**, the applications **110** include processor(s) **164** and memories **166**, and the twin manager **108** includes processor(s) **148** and memories **150**.

(66) The processors can be a general purpose or specific purpose processors, an application specific integrated circuit (ASIC), one or more field programmable gate arrays (FPGAs), a group of processing components, or other suitable processing components. The processors may be configured to execute computer code and/or instructions stored in the memories or received from other computer readable media (e.g., CDROM, network storage, a remote server, etc.).

(67) The memories can include one or more devices (e.g., memory units, memory devices, storage devices, etc.) for storing data and/or computer code for completing and/or facilitating the various processes described in the present disclosure. The memories can include random access memory (RAM), read-only memory (ROM), hard drive storage, temporary storage, non-volatile memory, flash memory, optical memory, or any other suitable memory for storing software objects and/or computer instructions. The memories can include database components, object code components, script components, or any other type of information structure for supporting the various activities and information structures described in the present disclosure. The memories can be communicably connected to the processors and can include computer code for executing (e.g., by the processors) one or more processes described herein.

(68) The edge platform **102** can be configured to provide connection to the building subsystems **122**. The edge platform **102** can receive messages from the building subsystems **122** and/or deliver messages to the building subsystems **122**. The edge platform **102** includes one or multiple gateways, e.g., the gateways **112-116**. The gateways **112-116** can act as a gateway between the cloud platform **106** and the building subsystems **122**. The gateways **112-116** can be the gateways described in U.S. Provisional Patent Application No. 62/951,897 filed Dec. 20, 2019, the entirety of which is incorporated by reference herein. In some embodiments, the applications **110** can be deployed on the edge platform **102**. In this regard, lower latency in management of the building subsystems **122** can be realized.

(69) The edge platform **102** can be connected to the cloud platform **106** via a network **104**. The network **104** can communicatively couple the devices and systems of building data platform **100**. In some embodiments, the network **104** is at least one of and/or a combination of a Wi-Fi network, a wired Ethernet network, a ZigBee network, a Bluetooth network, and/or any other wireless network. The network **104** may be a local area network or a wide area network (e.g., the Internet, a building WAN, etc.) and may use a variety of communications protocols (e.g., BACnet, IP, LON, etc.). The network **104** may include routers, modems, servers, cell towers, satellites, and/or network switches. The network **104** may be a combination of wired and wireless networks.

(70) The cloud platform **106** can be configured to facilitate communication and routing of messages between the applications **110**, the twin manager **108**, the edge platform **102**, and/or any other system. The cloud platform **106** can include a platform manager **128**, a messaging manager **140**, a command processor **136**, and an enrichment manager **138**. In some embodiments, the cloud platform **106** can facilitate messaging between the building data platform **100** via the network **104**.

(71) The messaging manager **140** can be configured to operate as a transport service that controls communication with the building subsystems **122** and/or any other system, e.g., managing commands to devices (C2D), commands to connectors (C2C) for external systems, commands from the device to the cloud (D2C), and/or notifications. The messaging manager **140** can receive different types of data from the applications **110**, the twin manager **108**, and/or the edge platform **102**. The messaging manager **140** can receive change on value data **142**, e.g., data that indicates that a value of a point has changed. The messaging manager **140** can receive timeseries data **144**, e.g., a time correlated series of data entries each

associated with a particular time stamp. Furthermore, the messaging manager **140** can receive command data **146**. All of the messages handled by the cloud platform **106** can be handled as an event, e.g., the data **142-146** can each be packaged as an event with a data value occurring at a particular time (e.g., a temperature measurement made at a particular time).

(72) The cloud platform **106** includes a command processor **136**. The command processor **136** can be configured to receive commands to perform an action from the applications **110**, the building subsystems **122**, the user device **176**, etc. The command processor **136** can manage the commands, determine whether the commanding system is authorized to perform the particular commands, and communicate the commands to the commanded system, e.g., the building subsystems **122** and/or the applications **110**. The commands could be a command to change an operational setting that control environmental conditions of a building, a command to run analytics, etc.

(73) The cloud platform **106** includes an enrichment manager **138**. The enrichment manager **138** can be configured to enrich the events received by the messaging manager **140**. The enrichment manager **138** can be configured to add contextual information to the events. The enrichment manager **138** can communicate with the twin manager **108** to retrieve the contextual information. In some embodiments, the contextual information is an indication of information related to the event. For example, if the event is a timeseries temperature measurement of a thermostat, contextual information such as the location of the thermostat (e.g., what room), the equipment controlled by the thermostat (e.g., what VAV), etc. can be added to the event. In this regard, when a consuming application, e.g., one of the applications **110** receives the event, the consuming application can operate based on the data of the event, the temperature measurement, and also the contextual information of the event.

(74) The enrichment manager **138** can solve a problem that when a device produces a significant amount of information, the information may contain simple data without context. An example might include the data generated when a user scans a badge at a badge scanner of the building subsystems **122**. This physical event can generate an output event including such information as “DeviceBadgeScannerID,” “BadgeID,” and/or “Date/Time.” However, if a system sends this data to a consuming application, e.g., Consumer A and a Consumer B, each customer may need to call the building data platform knowledge service to query information with queries such as, “What space, building, floor is that badge scanner in?” or “What user is associated with that badge?”

(75) By performing enrichment on the data feed, a system can be able to perform inferences on the data. A result of the enrichment may be transformation of the message “DeviceBadgeScannerId, BadgeId, Date/Time,” to “Region, Building, Floor, Asset, DeviceId, BadgeId, UserName, EmployeeId, Date/Time Scanned.” This can be a significant optimization, as a system can reduce the number of calls by $1/n$, where n is the number of consumers of this data feed.

(76) By using this enrichment, a system can also have the ability to filter out undesired events. If there are 100 buildings in a campus that receive 100,000 events per building each hour, but only 1 building is actually commissioned, only $1/10$ of the events are enriched. By looking at what events are enriched and what events are not enriched, a system can do traffic shaping of forwarding of these events to reduce the cost of forwarding events that no consuming application wants or reads.

(77) An example of an event received by the enrichment manager **138** may be:

(78) TABLE-US-00001 { “id”: “someguid”, “eventType”: “Device_Heartbeat”, “eventTime”: “2018-01-27T00:00:00+00:00” “eventValue”: 1, “deviceId”: “someguid” }

(79) An example of an enriched event generated by the enrichment manager **138** may be:

(80) TABLE-US-00002 { “id”: “someguid”, “eventType”: “Device_Heartbeat”, “eventTime”: “2018-01-27T00:00:00+00:00” “eventValue”: 1, “deviceId”: “someguid”, “buildingName”: “Building-48”, “buildingID”: “SomeGuid”, “panelID”: “SomeGuid”, “panelName”: “Building-48-Panel-13”, “cityID”: 371, “cityName”: “Milwaukee”, “stateID”: 48, “stateName”: “Wisconsin (WI)”, “countryID”: 1, “countryName”: “United States” }

(81) By receiving enriched events, an application of the applications **110** can be able to populate and/or filter what events are associated with what areas. Furthermore, user interface generating applications can generate user interfaces that include the contextual information based on the enriched events.

(82) The cloud platform **106** includes a platform manager **128**. The platform manager **128** can be configured to manage the users and/or subscriptions of the cloud platform **106**. For example, what subscribing building, user, and/or tenant utilizes the cloud platform **106**. The platform manager **128**

includes a provisioning service **130** configured to provision the cloud platform **106**, the edge platform **102**, and the twin manager **108**. The platform manager **128** includes a subscription service **132** configured to manage a subscription of the building, user, and/or tenant while the entitlement service **134** can track entitlements of the buildings, users, and/or tenants.

(83) The twin manager **108** can be configured to manage and maintain a digital twin. The digital twin can be a digital representation of the physical environment, e.g., a building. The twin manager **108** can include a change feed generator **152**, a schema and ontology **154**, a projection manager **156**, a policy manager **158**, an entity, relationship, and event database **160**, and a graph projection database **162**.

(84) The graph projection manager **156** can be configured to construct graph projections and store the graph projections in the graph projection database **162**. Examples of graph projections are shown in FIGS. **11-13**. Entities, relationships, and events can be stored in the database **160**. The graph projection manager **156** can retrieve entities, relationships, and/or events from the database **160** and construct a graph projection based on the retrieved entities, relationships and/or events. In some embodiments, the database **160** includes an entity-relationship collection for multiple subscriptions.

(85) In some embodiments, the graph projection manager **156** generates a graph projection for a particular user, application, subscription, and/or system. In this regard, the graph projection can be generated based on policies for the particular user, application, and/or system in addition to an ontology specific for that user, application, and/or system. In this regard, an entity could request a graph projection and the graph projection manager **156** can be configured to generate the graph projection for the entity based on policies and an ontology specific to the entity. The policies can indicate what entities, relationships, and/or events the entity has access to. The ontology can indicate what types of relationships between entities the requesting entity expects to see, e.g., floors within a building, devices within a floor, etc. Another requesting entity may have an ontology to see devices within a building and applications for the devices within the graph.

(86) The graph projections generated by the graph projection manager **156** and stored in the graph projection database **162** can be a knowledge graph and is an integration point. For example, the graph projections can represent floor plans and systems associated with each floor. Furthermore, the graph projections can include events, e.g., telemetry data of the building subsystems **122**. The graph projections can show application services as nodes and API calls between the services as edges in the graph. The graph projections can illustrate the capabilities of spaces, users, and/or devices. The graph projections can include indications of the building subsystems **122**, e.g., thermostats, cameras, VAVs, etc. The graph projection database **162** can store graph projections that keep up a current state of a building.

(87) The graph projections of the graph projection database **162** can be digital twins of a building. Digital twins can be digital replicas of physical entities that enable an in-depth analysis of data of the physical entities and provide the potential to monitor systems to mitigate risks, manage issues, and utilize simulations to test future solutions. Digital twins can play an important role in helping technicians find the root cause of issues and solve problems faster, in supporting safety and security protocols, and in supporting building managers in more efficient use of energy and other facilities resources. Digital twins can be used to enable and unify security systems, employee experience, facilities management, sustainability, etc.

(88) In some embodiments the enrichment manager **138** can use a graph projection of the graph projection database **162** to enrich events. In some embodiments, the enrichment manager **138** can identify nodes and relationships that are associated with, and are pertinent to, the device that generated the event. For example, the enrichment manager **138** could identify a thermostat generating a temperature measurement event within the graph. The enrichment manager **138** can identify relationships between the thermostat and spaces, e.g., a zone that the thermostat is located in. The enrichment manager **138** can add an indication of the zone to the event.

(89) Furthermore, the command processor **136** can be configured to utilize the graph projections to command the building subsystems **122**. The command processor **136** can identify a policy for a commanding entity within the graph projection to determine whether the commanding entity has the ability to make the command. For example, the command processor **136**, before allowing a user to make a command, determine, based on the graph projection database **162**, to determine that the user has a policy to be able to make the command.

(90) In some embodiments, the policies can be conditional based policies. For example, the building data

platform **100** can apply one or more conditional rules to determine whether a particular system has the ability to perform an action. In some embodiments, the rules analyze a behavioral based biometric. For example, a behavioral based biometric can indicate normal behavior and/or normal behavior rules for a system. In some embodiments, when the building data platform **100** determines, based on the one or more conditional rules, that an action requested by a system does not match a normal behavior, the building data platform **100** can deny the system the ability to perform the action and/or request approval from a higher level system.

(91) For example, a behavior rule could indicate that a user has access to log into a system with a particular IP address between 8 A.M. through 5 P.M. However, if the user logs in to the system at 7 P.M., the building data platform **100** may contact an administrator to determine whether to give the user permission to log in.

(92) The change feed generator **152** can be configured to generate a feed of events that indicate changes to the digital twin, e.g., to the graph. The change feed generator **152** can track changes to the entities, relationships, and/or events of the graph. For example, the change feed generator **152** can detect an addition, deletion, and/or modification of a node or edge of the graph, e.g., changing the entities, relationships, and/or events within the database **160**. In response to detecting a change to the graph, the change feed generator **152** can generate an event summarizing the change. The event can indicate what nodes and/or edges have changed and how the nodes and edges have changed. The events can be posted to a topic by the change feed generator **152**.

(93) The change feed generator **152** can implement a change feed of a knowledge graph. The building data platform **100** can implement a subscription to changes in the knowledge graph. When the change feed generator **152** posts events in the change feed, subscribing systems or applications can receive the change feed event. By generating a record of all changes that have happened, a system can stage data in different ways, and then replay the data back in whatever order the system wishes. This can include running the changes sequentially one by one and/or by jumping from one major change to the next. For example, to generate a graph at a particular time, all change feed events up to the particular time can be used to construct the graph.

(94) The change feed can track the changes in each node in the graph and the relationships related to them, in some embodiments. If a user wants to subscribe to these changes and the user has proper access, the user can simply submit a web API call to have sequential notifications of each change that happens in the graph. A user and/or system can replay the changes one by one to reinstitute the graph at any given time slice. Even though the messages are “thin” and only include notification of change and the reference “id/seq id,” the change feed can keep a copy of every state of each node and/or relationship so that a user and/or system can retrieve those past states at any time for each node. Furthermore, a consumer of the change feed could also create dynamic “views” allowing different “snapshots” in time of what the graph looks like from a particular context. While the twin manager **108** may contain the history and the current state of the graph based upon schema evaluation, a consumer can retain a copy of that data, and thereby create dynamic views using the change feed.

(95) The schema and ontology **154** can define the message schema and graph ontology of the twin manager **108**. The message schema can define what format messages received by the messaging manager **140** should have, e.g., what parameters, what formats, etc. The ontology can define graph projections, e.g., the ontology that a user wishes to view. For example, various systems, applications, and/or users can be associated with a graph ontology. Accordingly, when the graph projection manager **156** generates a graph projection for a user, system, or subscription, the graph projection manager **156** can generate a graph projection according to the ontology specific to the user. For example, the ontology can define what types of entities are related in what order in a graph, for example, for the ontology for a subscription of “Customer A,” the graph projection manager **156** can create relationships for a graph projection based on the rule: Region ← .fwdarw.Building ← .fwdarw.Floor ← .fwdarw.Space ← .fwdarw.Asset

(96) For the ontology of a subscription of “Customer B,” the graph projection manager **156** can create relationships based on the rule: Building ← .fwdarw.Floor ← .fwdarw.Asset

(97) The policy manager **158** can be configured to respond to requests from other applications and/or systems for policies. The policy manager **158** can consult a graph projection to determine what permissions different applications, users, and/or devices have. The graph projection can indicate various permissions that different types of entities have and the policy manager **158** can search the graph

projection to identify the permissions of a particular entity. The policy manager **158** can facilitate fine grain access control with user permissions. The policy manager **158** can apply permissions across a graph, e.g., if “user can view all data associated with floor 1” then they see all subsystem data for that floor, e.g., surveillance cameras, HVAC devices, fire detection and response devices, etc.

(98) The twin manager **108** includes a query manager **165** and a twin function manager **167**. The query manager **164** can be configured to handle queries received from a requesting system, e.g., the user device **176**, the applications **110**, and/or any other system. The query manager **165** can receive queries that include query parameters and context. The query manager **165** can query the graph projection database **162** with the query parameters to retrieve a result. The query manager **165** can then cause an event processor, e.g., a twin function, to operate based on the result and the context. In some embodiments, the query manager **165** can select the twin function based on the context and/or perform operations based on the context. In some embodiments, the query manager **165** is configured to perform the operations described with reference to FIGS. 5-10.

(99) The twin function manager **167** can be configured to manage the execution of twin functions. The twin function manager **167** can receive an indication of a context query that identifies a particular data element and/or pattern in the graph projection database **162**. Responsive to the particular data element and/or pattern occurring in the graph projection database **162** (e.g., based on a new data event added to the graph projection database **162** and/or change to nodes or edges of the graph projection database **162**, the twin function manager **167** can cause a particular twin function to execute. The twin function can execute based on an event, context, and/or rules. The event can be data that the twin function executes against. The context can be information that provides a contextual description of the data, e.g., what device the event is associated with, what control point should be updated based on the event, etc. The twin function manager **167** can be configured to perform the operations of the FIGS. 11-15.

(100) Referring now to FIG. 2, a graph projection **200** of the twin manager **108** including application programming interface (API) data, capability data, policy data, and services is shown, according to an exemplary embodiment. The graph projection **200** includes nodes **202-240** and edges **250-272**. The nodes **202-240** and the edges **250-272** are defined according to the key **201**. The nodes **202-240** represent different types of entities, devices, locations, points, persons, policies, and software services (e.g., API services). The edges **250-272** represent relationships between the nodes **202-240**, e.g., dependent calls, API calls, inferred relationships, and schema relationships (e.g., BRICK relationships).

(101) The graph projection **200** includes a device hub **202** which may represent a software service that facilitates the communication of data and commands between the cloud platform **106** and a device of the building subsystems **122**, e.g., door actuator **214**. The device hub **202** is related to a connector **204**, an external system **206**, and a digital asset “Door Actuator” **208** by edge **250**, edge **252**, and edge **254**.

(102) The cloud platform **106** can be configured to identify the device hub **202**, the connector **204**, the external system **206** related to the door actuator **214** by searching the graph projection **200** and identifying the edges **250-254** and edge **258**. The graph projection **200** includes a digital representation of the “Door Actuator,” node **208**. The digital asset “Door Actuator” **208** includes a “DeviceNameSpace” represented by node **207** and related to the digital asset “Door Actuator” **208** by the “Property of Object” edge **256**.

(103) The “Door Actuator” **214** has points and timeseries. The “Door Actuator” **214** is related to “Point A” **216** by a “has_a” edge **260**. The “Door Actuator” **214** is related to “Point B” **218** by a “has_A” edge **258**. Furthermore, timeseries associated with the points A and B are represented by nodes “TS” **220** and “TS” **222**. The timeseries are related to the points A and B by “has_a” edge **264** and “has_a” edge **262**. The timeseries “TS” **220** has particular samples, sample **210** and **212** each related to “TS” **220** with edges **268** and **266** respectively. Each sample includes a time and a value. Each sample may be an event received from the door actuator that the cloud platform **106** ingests into the entity, relationship, and event database **160**, e.g., ingests into the graph projection **200**.

(104) The graph projection **200** includes a building **234** representing a physical building. The building includes a floor represented by floor **232** related to the building **234** by the “has_a” edge from the building **234** to the floor **232**. The floor has a space indicated by the edge “has_a” **270** between the floor **232** and the space **230**. The space has particular capabilities, e.g., is a room that can be booked for a meeting, conference, private study time, etc. Furthermore, the booking can be canceled. The capabilities for the floor **232** are represented by capabilities **228** related to space **230** by edge **280**. The capabilities **228** are related to two different commands, command “book room” **224** and command “cancel booking” **226**

related to capabilities **228** by edge **284** and edge **282** respectively.

(105) If the cloud platform **106** receives a command to book the space represented by the node, space **230**, the cloud platform **106** can search the graph projection **200** for the capabilities for the **228** related to the space **230** to determine whether the cloud platform **106** can book the room.

(106) In some embodiments, the cloud platform **106** could receive a request to book a room in a particular building, e.g., the building **234**. The cloud platform **106** could search the graph projection **200** to identify spaces that have the capabilities to be booked, e.g., identify the space **230** based on the capabilities **228** related to the space **230**. The cloud platform **106** can reply to the request with an indication of the space and allow the requesting entity to book the space **230**.

(107) The graph projection **200** includes a policy **236** for the floor **232**. The policy **236** is a related set for the floor **232** based on a “To Floor” edge **274** between the policy **236** and the floor **232**. The policy **236** is related to different roles for the floor **232**, read events **238** via edge **276** and send command **240** via edge **278**. The policy **236** is set for the entity **203** based on has edge **251** between the entity **203** and the policy **236**.

(108) The twin manager **108** can identify policies for particular entities, e.g., users, software applications, systems, devices, etc. based on the policy **236**. For example, if the cloud platform **106** receives a command to book the space **230**. The cloud platform **106** can communicate with the twin manager **108** to verify that the entity requesting to book the space **230** has a policy to book the space. The twin manager **108** can identify the entity requesting to book the space as the entity **203** by searching the graph projection **200**. Furthermore, the twin manager **108** can further identify the edge has **251** between the entity **203** and the policy **236** and the edge **1178** between the policy **236** and the command **240**.

(109) Furthermore, the twin manager **108** can identify that the entity **203** has the ability to command the space **230** based on the edge **1174** between the policy **236** and the edge **270** between the floor **232** and the space **230**. In response to identifying the entity **203** has the ability to book the space **230**, the twin manager **108** can provide an indication to the cloud platform **106**.

(110) Furthermore, if the entity **203** makes a request to read events for the space **230**, e.g., the sample **210** and the sample **212**, the twin manager **108** can identify the edge **251** between the entity **203** and the policy **236**, the edge **1178** between the policy **236** and the read events **238**, the edge **1174** between the policy **236** and the floor **232**, the “has_a” edge **270** between the floor **232** and the space **230**, the edge **268** between the space **230** and the door actuator **214**, the edge **260** between the door actuator **214** and the point A **216**, the “has_a” edge **264** between the point A **216** and the TS **220**, and the edges **268** and **266** between the TS **220** and the samples **210** and **212** respectively.

(111) Referring now to FIG. 3, a graph projection **300** of the twin manager **108** including application programming interface (API) data, capability data, policy data, and services is shown, according to an exemplary embodiment. The graph projection **300** includes the nodes and edges described in the graph projection **200** of FIG. 2. The graph projection **300** includes a connection broker **354** related to capabilities **228** by edge **398a**. The connection broker **354** can be a node representing a software application configured to facilitate a connection with another software application. In some embodiments, the cloud platform **106** can identify the system that implements the capabilities **228** by identifying the edge **398a** between the capabilities **228** and the connection broker **354**.

(112) The connection broker **354** is related to an agent that optimizes a space **356** via edge **398b**. The agent represented by the node **356** can book and cancel bookings for the space represented by the node **230** based on the edge **398b** between the connection broker **354** and the node **356** and the edge **398a** between the capabilities **228** and the connection broker **354**.

(113) The connection broker **354** is related to a cluster **308** by edge **398c**. Cluster **308** is related to connector B **302** via edge **398e** and connector A **306** via edge **398d**. The connector A **306** is related to an external subscription service **304**. A connection broker **310** is related to cluster **308** via an edge **311** representing a rest call that the connection broker represented by node **310** can make to the cluster represented by cluster **308**.

(114) The connection broker **310** is related to a virtual meeting platform **312** by an edge **354**. The node **312** represents an external system that represents a virtual meeting platform **312**. The connection broker represented by node **310** can represent a software component that facilitates a connection between the cloud platform **106** and the virtual meeting platform represented by node **312**. When the cloud platform **106** needs to communicate with the virtual meeting platform represented by the node **312**, the cloud

platform **106** can identify the edge **354** between the connection broker **310** and the virtual meeting platform **312** and select the connection broker represented by the node **310** to facilitate communication with the virtual meeting platform represented by the node **312**.

(115) A capabilities node **318** can be connected to the connection broker **310** via edge **360**. The capabilities **318** can be capabilities of the virtual meeting platform represented by the node **312** and can be related to the node **312** through the edge **360** to the connection broker **310** and the edge **354** between the connection broker **310** and the node **312**. The capabilities **318** can define capabilities of the virtual meeting platform represented by the node **312**. The node **320** is related to capabilities **318** via edge **362**. The capabilities **318** may be an invite bob command represented by node **316** and an email bob command represented by node **314**. The capabilities **318** can be linked to a node **320** representing a user, Bob. The cloud platform **106** can facilitate email commands to send emails to the user Bob via the email service represented by the node **304**. The node **304** is related to the connect a node **306** via edge **398f**. Furthermore, the cloud platform **106** can facilitate sending an invite for a virtual meeting via the virtual meeting platform represented by the node **312** linked to the node **318** via the edge **358**.

(116) The node **320** for the user Bob can be associated with the policy **236** via the “has” edge **364**. Furthermore, the node **320** can have a “check policy” edge **366** with a portal node **324**. The device API node **328** has a check policy edge **370** to the policy node **236**. The portal node **324** has an edge **368** to the policy node **236**. The portal node **324** has an edge **323** to a node **326** representing a user input manager (UIM). The portal node **324** is related to the UIM node **326** via an edge **323**. The UIM node **326** has an edge **323** to a device API node **328**. The UIM node **326** is related to the door actuator node **214** via edge **372**. The door actuator node **214** has an edge **374** to the device API node **328**. The door actuator **214** has an edge **335** to the connector virtual object **334**. The device hub **332** is related to the connector virtual object via edge **380**. The device API node **328** can be an API for the door actuator **214**. The connector virtual object **334** is related to the device API node **328** via the edge **331**.

(117) The device API node **328** is related to a transport connection broker **330** via an edge **329**. The transport connection broker **330** is related to a device hub **332** via an edge **378**. The device hub represented by node **332** can be a software component that hands the communication of data and commands for the door actuator **214**. The cloud platform **106** can identify where to store data within the graph projection **300** received from the door actuator by identifying the nodes and edges between the points **216** and **218** and the device hub node **332**. Similarly, the cloud platform **308** can identify commands for the door actuator that can be facilitated by the device hub represented by the node **332**, e.g., by identifying edges between the device hub node **332** and an open door node **352** and a lock door node **350**. The door actuator node **214** has an edge “has mapped an asset” **280** between the node **214** and a capabilities node **348**. The capabilities node **348** and the nodes **352** and **350** are linked by edges **396** and **394**.

(118) The device hub **332** is linked to a cluster **336** via an edge **384**. The cluster **336** is linked to connector A **340** and connector B **338** by edges **386** and the edge **389**. The connector A **340** and the connector B **338** is linked to an external system **344** via edges **388** and **390**. The external system **344** is linked to a door actuator **342** via an edge **392**.

(119) Referring now to FIG. **4**, a graph projection **400** of the twin manager **108** including equipment and capability data for the equipment is shown, according to an exemplary embodiment. The graph projection **400** includes nodes **402-456** and edges **360-498f**. The cloud platform **106** can search the graph projection **400** to identify capabilities of different pieces of equipment.

(120) A building node **404** represents a particular building that includes two floors. A floor 1 node **402** is linked to the building node **404** via edge **460** while a floor 2 node **406** is linked to the building node **404** via edge **462**. The floor 2 includes a particular room **2023** represented by edge **464** between floor 2 node **406** and room **2023** node **408**. Various pieces of equipment are included within the room **2023**. A light represented by light node **416**, a bedside lamp node **414**, a bedside lamp node **412**, and a hallway light node **410** are related to room **2023** node **408** via edge **466**, edge **472**, edge **470**, and edge **468**.

(121) The light represented by light node **416** is related to a light connector **426** via edge **484**. The light connector **426** is related to multiple commands for the light represented by the light node **416** via edges **484**, **486**, and **488**. The commands may be a brightness setpoint **424**, an on command **425**, and a hue setpoint **428**. The cloud platform **106** can receive a request to identify commands for the light represented by the light **416** and can identify the nodes **424-428** and provide an indication of the commands represented by the node **424-428** to the requesting entity. The requesting entity can then send commands

for the commands represented by the nodes **424-428**.

(122) The bedside lamp node **414** is linked to a bedside lamp connector **481** via an edge **413**. The connector **481** is related to commands for the bedside lamp represented by the bedside lamp node **414** via edges **492**, **496**, and **494**. The command nodes are a brightness setpoint node **432**, an on command node **434**, and a color command **436**. The hallway light **410** is related to a hallway light connector **446** via an edge **498d**. The hallway light connector **446** is linked to multiple commands for the hallway light node **410** via edges **498g**, **498f**, and **498e**. The commands are represented by an on command node **452**, a hue setpoint node **450**, and a light bulb activity node **448**.

(123) The graph projection **400** includes a name space node **422** related to a server A node **418** and a server B node **420** via edges **474** and **476**. The name space node **422** is related to the bedside lamp connector **481**, the bedside lamp connector **444**, and the hallway light connector **446** via edges **482**, **480**, and **478**. The bedside lamp connector **444** is related to commands, e.g., the color command node **440**, the hue setpoint command **438**, a brightness setpoint command **456**, and an on command **454** via edges **498c**, **498b**, **498a**, and **498**.

(124) Referring now to FIG. 5, a system **500** for managing a digital twin where an artificial intelligence agent can be executed to infer and/or predict information for an entity of a graph is shown, according to an exemplary embodiment. The system **500** can be components of the building data platform **100**, e.g., components run on the processors and memories of the edge platform **102**, the cloud platform **106**, the twin manager **108**, and/or the applications **110**. The system **500** can, in some implementations, implement a digital twin with artificial intelligence.

(125) A digital twin (or a shadow) may be a computing entity that describes a physical thing (e.g., a building, spaces of a building, devices of a building, people of the building, equipment of the building, etc.) through modeling the physical thing through a set of attributes that define the physical thing. A digital twin can refer to a digital replica of physical assets (a physical device twin) and can be extended to store processes, people, places, systems that can be used for various purposes. The digital twin can include both the ingestion of information and actions learned and executed through artificial intelligence agents.

(126) In FIG. 5, the digital twin can be a graph **529** managed by the twin manager **108** and/or artificial intelligence agents **570**. In some embodiments, the digital twin is the combination of the graph **529** with the artificial intelligence agents **570**. In some embodiments, the digital twin enables the creation of a chronological time-series database of telemetry events for analytical purposes. In some embodiments, the graph **529** uses the BRICK schema.

(127) The twin manager **108** stores the graph **529** which may be a graph data structure including various nodes and edges interrelating the nodes. The graph **529** may be the same as, or similar to, the graph projections described herein with reference to FIGS. 1-4. The graph **529** includes nodes **510-526** and edges **528-546**. The graph **529** includes a building node **526** representing a building that has a floor indicated by the “has” edge **546** to the floor node **522**. The floor node **522** is related to a zone node **510** via a “has” edge **544** indicating that the floor represented by the node **522** has a zone represented by the zone **510**.

(128) The floor node **522** is related to the zone node **518** by the “has” edge **540** indicating that the floor represented by the floor node **522** has another zone represented by the zone node **518**. The floor node **522** is related to another zone node **524** via a “has” edge **542** representing that the floor represented by the floor node **522** has a third zone represented by the zone node **524**.

(129) The graph **529** includes an AHU node **514** representing an AHU of the building represented by the building node **526**. The AHU node **514** is related by a “supplies” edge **530** to the VAV node **512** to represent that the AHU represented by the AHU node **514** supplies air to the VAV represented by the VAV node **512**. The AHU node **514** is related by a “supplies” edge **536** to the VAV node **520** to represent that the AHU represented by the AHU node **514** supplies air to the VAV represented by the VAV node **520**. The AHU node **514** is related by a “supplies” edge **532** to the VAV node **516** to represent that the AHU represented by the AHU node **514** supplies air to the VAV represented by the VAV node **516**.

(130) The VAV node **516** is related to the zone node **518** via the “serves” edge **534** to represent that the VAV represented by the VAV node **516** serves (e.g., heats or cools) the zone represented by the zone node **518**. The VAV node **520** is related to the zone node **524** via the “serves” edge **538** to represent that the VAV represented by the VAV node **520** serves (e.g., heats or cools) the zone represented by the zone node **524**. The VAV node **512** is related to the zone node **510** via the “serves” edge **528** to represent that the VAV represented by the VAV node **512** serves (e.g., heats or cools) the zone represented by the zone node **510**.

(131) Furthermore, the graph **529** includes an edge **533** related to a timeseries node **564**. The timeseries node **564** can be information stored within the graph **529** and/or can be information stored outside the graph **529** in a different database (e.g., a timeseries database). In some embodiments, the timeseries node **564** stores timeseries data (or any other type of data) for a data point of the VAV represented by the VAV node **516**. The data of the timeseries node **564** can be aggregated and/or collected telemetry data of the timeseries node **564**.

(132) Furthermore, the graph **529** includes an edge **537** related to a timeseries node **566**. The timeseries node **566** can be information stored within the graph **529** and/or can be information stored outside the graph **529** in a different database (e.g., a timeseries database). In some embodiments, the timeseries node **566** stores timeseries data (or any other type of data) for a data point of the VAV represented by the VAV node **516**. The data of the timeseries node **564** can be inferred information, e.g., data inferred by one of the artificial intelligence agents **570** and written into the timeseries node **564** by the artificial intelligence agent **570**. In some embodiments, the timeseries **546** and/or **566** are stored in the graph **529** but are stored as references to timeseries data stored in a timeseries database.

(133) The twin manager **108** includes various software components. For example, the twin manager **108** includes a device management component **548** for managing devices of a building. The twin manager **108** includes a tenant management component **550** for managing various tenant subscriptions. The twin manager **108** includes an event routing component **552** for routing various events. The twin manager **108** includes an authentication and access component **554** for performing user and/or system authentication and granting the user and/or system access to various spaces, pieces of software, devices, etc. The twin manager **108** includes a commanding component **556** allowing a software application and/or user to send commands to physical devices. The twin manager **108** includes an entitlement component **558** that analyzes the entitlements of a user and/or system and grants the user and/or system abilities based on the entitlements. The twin manager **108** includes a telemetry component **560** that can receive telemetry data from physical systems and/or devices and ingest the telemetry data into the graph **529**. Furthermore, the twin manager **108** includes an integrations component **562** allowing the twin manager **108** to integrate with other applications.

(134) The twin manager **108** includes a gateway **506** and a twin connector **508**. The gateway **506** can be configured to integrate with other systems and the twin connector **508** can be configured to allow the gateway **506** to integrate with the twin manager **108**. The gateway **506** and/or the twin connector **508** can receive an entitlement request **502** and/or an inference request **504**. The entitlement request **502** can be a request received from a system and/or a user requesting that an AI agent action be taken by the AI agent **570**. The entitlement request **502** can be checked against entitlements for the system and/or user to verify that the action requested by the system and/or user is allowed for the user and/or system. The inference request **504** can be a request that the AI agent **570** generates an inference, e.g., a projection of information, a prediction of a future data measurement, an extrapolated data value, etc.

(135) The cloud platform **106** is shown to receive a manual entitlement request **586**. The request **586** can be received from a system, application, and/or user device (e.g., from the applications **110**, the building subsystems **122**, and/or the user device **176**). The manual entitlement request **586** may be a request for the AI agent **570** to perform an action, e.g., an action that the requesting system and/or user has an entitlement for. The cloud platform **106** can receive the manual entitlement request **586** and check the manual entitlement request **586** against an entitlement database **584** storing a set of entitlements to verify that the requesting system has access to the user and/or system. The cloud platform **106**, responsive to the manual entitlement request **586** being approved, can create a job for the AI agent **570** to perform. The created job can be added to a job request topic **580** of a set of topics **578**.

(136) The job request topic **580** can be fed to AI agents **570**. For example, the topics **580** can be fanned out to various AI agents **570** based on the AI agent that each of the topics **580** pertains to (e.g., based on an identifier that identifies an agent and is included in each job of the topic **580**). The AI agents **570** include a service client **572**, a connector **574**, and a model **576**. The model **576** can be loaded into the AI agent **570** from a set of AI models stored in the AI model storage **568**. The AI model storage **568** can store models for making energy load predictions for a building, weather forecasting models for predicting a weather forecast, action/decision models to take certain actions responsive to certain conditions being met, an occupancy model for predicting occupancy of a space and/or a building, etc. In some embodiments, the occupancy level may be a numerical value that indicates the amount of people within the building (e.g.,

total number, portion of the building capacity, scale between 1 (empty) and 10 (full), etc.). In some embodiments, the occupancy level may be a non-numerical indicator that indicates the amount of people within the building such as occupancy descriptors (e.g., “Empty”, “Half-Full”, “Full”). The models of the AI model storage **568** can be neural networks (e.g., convolutional neural networks, recurrent neural networks, deep learning networks, etc.), decision trees, support vector machines, and/or any other type of artificial intelligence, machine learning, and/or deep learning category. In some embodiments, the models are rule based triggers and actions that include various parameters for setting a condition and defining an action.

(137) The AI agent **570** can include triggers **595** and actions **597**. The triggers **595** can be conditional rules that, when met, cause one or more of the actions **597**. The triggers **595** can be executed based on information stored in the graph **529** and/or data received from the building subsystems **122**. The actions **597** can be executed to determine commands, actions, and/or outputs. The output of the actions **597** can be stored in the graph **529** and/or communicated to the building subsystems **122**.

(138) The AI agent **570** can include a service client **572** that causes an instance of an AI agent to run. The instance can be hosted by the artificial intelligence service client **588**. The client **588** can cause a client instance **592** to run and communicate with the AI agent **570** via a gateway **590**. The client instance **592** can include a service application **594** that interfaces with a core algorithm **598** via a functional interface **596**. The core algorithm **598** can run the model **576**, e.g., train the model **576** and/or use the model **576** to make inferences and/or predictions.

(139) In some embodiments, the core algorithm **598** can be configured to perform learning based on the graph **529**. In some embodiments, the core algorithm **598** can read and/or analyze the nodes and relationships of the graph **529** to make decisions. In some embodiments, the core algorithm **598** can be configured to use telemetry data (e.g., the timeseries data **564**) from the graph **529** to make inferences on and/or perform model learning. In some embodiments, the result of the inferences can be the timeseries **566**. In some embodiments, the timeseries **564** is an input into the model **576** that predicts the timeseries **566**.

(140) In some embodiments, the core algorithm **598** can generate the timeseries **566** as an inference for a data point, e.g., a prediction of values for the data point at future times. The timeseries **564** may be actual data for the data point. In this regard, the core algorithm **598** can learn and train by comparing the inferred data values against the true data values. In this regard, the model **576** can be trained by the core algorithm **598** to improve the inferences made by the model **576**.

(141) Referring now to FIG. 6, a process **600** for executing an artificial intelligence agent to infer and/or predict information is shown, according to an exemplary embodiment. The process **600** can be performed by the system **500** and/or components of the system **500**. The process **600** can be performed by the building data platform **100**. Furthermore, the process **600** can be performed by any computing device described herein.

(142) In step **602**, the twin manager **108** receives information from a physical device and stores the information, or a link to the information, in the graph **529**. For example, the telemetry component **560** can receive telemetry data from physical devices, e.g., the building subsystems **122**. The telemetry can be measured data values, a log of historical equipment commands, etc. The telemetry component **560** can store the received information in the graph **529** by relating a node storing the information to a node representing the physical device. For example, the telemetry component **560** can store timeseries data as the timeseries **566** along by identifying that the physical device is a VAV represented by the VAV node **516** and that an edge **537** relates the VAV node **516** to the timeseries node **566**.

(143) In step **604**, the twin manager **108** and/or the cloud platform **106** receives an indication to execute an artificial intelligence agent of an entity represented in the graph **529**, the AI agent being associated with a model. In some embodiments, the indication is created by a user and provided via the user device **176**. In some embodiments, the indication is created by an application, e.g., one of the applications **110**. In some embodiments, the indication is a triggering event that triggers the agent and is received from the building subsystems **122** and/or another agent (e.g., an output of one agent fed into another agent).

(144) In some embodiments, the AI agent is an agent for a specific entity represented in the graph **529**. For example, the agent could be a VAV maintenance agent configured to identify whether a VAV (e.g., a VAV represented by the nodes **512**, **530**, and/or **516**) should have maintenance performed at a specific time. Another agent could be a floor occupant prediction agent that is configured to predict the occupancy of a

particular floor of a building, e.g., the floor represented by the floor node 522.

(145) Responsive to receiving the indication, in step 606, the AI agent 570 causes a client instance 592 to run the model 576 based on the information received in step 602. In some embodiments, the information received in step 602 is provided directly to the AI agent 570. In some embodiments, the information is read from the graph 529 by the AI agent 570.

(146) In step 608, the AI agent 570 stores the inferred and/or predicted information in the graph 529 (or stores the inferred and/or predicted information in a separate data structure with a link to the graph 529). In some embodiments, the AI agent 570 identifies that the node that represents the physical entity that the AI agent 570 inferred and/or predicted information for, e.g., the VAV represented by the VAV 516. The AI agent 570 can identify that the timeseries node 566 stores the inferred and/or predicted information by identifying the edge 537 between the VAV node 516 and the timeseries node 566.

(147) In step 610, the AI agent 570 can retrieve the inferred or predicted information from the graph 529 responsive to receiving an indication to execute the model of the AI agent 570 of the inferred or predicted information, e.g., similar to the step 604. In step 612, the AI agent 570 can execute one or more actions based on the inferred and/or predicted information of the step 610 based the inferred and/or predicted information retrieved from the graph 529. In some embodiments, the AI agent 570 executes the model 576 based on the inferred and/or predicted information.

(148) In step 614, the AI agent 570 can train the model 576 based on the inferred or predicted information read from the graph 529 and received actual values for the inferred or predicted information. In some embodiments, the AI agent 570 can train and update parameters of the model 576. For example, the timeseries 564 may represent actual values for a data point of the VAV represented by the VAV node 516. The timeseries 566 can be the inferred and/or predicted information. The AI agent 570 can compare the timeseries 564 and the timeseries 566 to determine an error in the inferences and/or predictions of the model 576. The error can be used by the model 576 to update and train the model 576.

(149) Referring now to FIG. 7, a digital twin 700 including a connector and a database is shown, according to an exemplary embodiment. The digital twin 700 can be a software component stored and/or managed by the building data platform 100. The building data platform 100 includes connectors 702 and a database 704. The database 704 can store data attributes for a physical entity, e.g., a building, a VAV, etc. that describe the current state and/or operation of the physical entity. The connector 702 can be a software component that receives data from the physical device represented by the digital twin 700 and updates the attributes of the database 704. For example, the connector 702 can ingest device telemetry data into the database 704 to update the attributes of the digital twin 700.

(150) Referring now to FIG. 8, a digital twin 800 including triggers 802, connectors 804, actions 806, and a graph 808 is shown, according to an exemplary embodiment. The digital twin 800 can be a digital replica of physical assets (e.g., a physical device twin, sensor twin, actuator twin, building device twin, etc.) and can be used to store processes, people, places, systems that can be used for various purposes. The digital twins can be created, managed, stored, and/or operated on by the building data platform 100.

(151) In some cases, the devices can also be actuated on (told to perform an action). For example, a thermostat has sensors to measure temperature and humidity. A thermostat can also be asked to perform an action of setting the setpoint for an HVAC system. In this regard, the digital twin 800 can be configured so that information that the digital twin 800 can be made aware of can be stored by the digital twin 800 and there are also actions that the digital twin 800 can take.

(152) The digital twin 800 can include a connector 804 that ingests device telemetry into the graph 808 and/or update the digital twin attributes stored in the graph 808. In some embodiments, the connectors 804 can ingest external data received from external data sources into the graph 808. The external data could be weather data, calendar data, etc. In some embodiments, the connectors 804 can send commands back to the devices, e.g., the actions determined by the actions 806.

(153) The digital twin 800 includes triggers 802 which can set conditional logic for triggering the actions 706. The digital twin 800 can apply the attributes stored in the graph 808 against a rule of the triggers 802. When a particular condition of the rule of the triggers 802 involving that attribute is met, the actions 706 can execute. One example of a trigger could be a conditional question, “when the temperature of the zone managed by the thermostat reaches x degrees Fahrenheit.” When the question is met by the attributes stored in the graph 808, a rule of the actions 706 can execute.

(154) The digital twin 800 can, when executing the actions 806, update an attribute of the graph 808, e.g.,

a setpoint, an operating setting, etc. These attributes can be translated into commands that the building data platform **100** can send to physical devices that operate based on the setpoint, the operating setting, etc. An example of an action rule for the actions **806** could be the statement, “update the setpoint of the HVAC system for a zone to x Degrees Fahrenheit.”

(155) In some embodiments, the triggers **802** and/or the actions **806** are predefined and/or manually defined through user input of the user device **176**. In some cases, it may be difficult for a user to determine what the parameter values of the trigger rule should be (e.g., what values maximize a particular reward or minimize a particular penalty). Similarly, it may be difficult for a user to determine what the parameter values of the action rule should be (e.g., what values maximize the particular reward or minimize the particular penalty). Furthermore, even if the user is able to identify the ideal parameter values for the triggers **802** and the actions **806**, the ideal values for the parameters may not be constant and may instead change over time. Therefore, it would be desirable if the values of the attributes for the triggers **802** and the actions **806** are tuned optimally and automatically by the building data platform **100** by observing the responses from other related digital twins.

(156) Causal patterns between one or more digital twins having their triggering conditions satisfied and one or more digital twins (including the triggering digital twin) actuating by sending specific commands to their physical counterparts could be learned and defined by the building data platform **100**. Automated learning can be used by the building data platform **100** during real operations, by running simulations using digital twins, or using predicted inference within the digital twin. There may not even be the need for all standard operating procedures in building systems to be defined upfront by a user since patterns of interaction between digital twins can be learned by the building data platform **100** to define and recommend those to building and facility owners.

(157) Referring now to FIG. **9**, a system **900** of digital twins including a people counter digital twin **902**, an HVAC digital twin **904**, and a facility manager digital twin **906** that have triggers and actions that are interconnected is shown, according to an exemplary embodiment. In FIG. **9**, the people counter digital twin **902** is shown including triggers **908**, connectors **910**, actions **912**, and the graph **926**.

(158) The system **900** further includes an HVAC digital twin **904** that includes triggers **914**, connectors **916**, and actions **918**. The system **900** further includes the facility manager **906** that includes triggers **920**, connectors **922**, and actions **924**. In some embodiments, the graph **926**, the graph **928**, and the graph **930** are the same graph or different graphs. In some embodiments, the graphs **926-930** are the graph **529**.

(159) In the system **900**, the actions **912** are connected to the triggers **914** and the triggers **920**. In this regard, whatever action is taken by the people counter digital twin **902**, the result of the action will be provided to the HVAC digital twin **904** and the facility manager digital twin **906**. The people counter digital twin **902** can output a “low occupancy” attribute which can be stored in the graph **926** and/or provided to the HVAC digital twin **904** and/or the facility manager digital twin **906**. In some embodiments, if all of the digital twins use and/or have access to the same graph, if the people counter digital twin **902** stores the low occupancy indicator in the graph, the HVAC digital twin **904** and the facility manager digital twin **906** can read the attribute from the graph.

(160) In some embodiments, the trigger **908** is the logical condition, “when there are less than twenty people in a particular area.” Responsive to an occupancy count of the particular area is less than twenty, which the people counter digital twin **902** can determine from models and/or information of the graph **926**, a low occupancy indication can be generated by the actions **912**. The low occupancy indication can be provided to the HVAC digital twin **904**.

(161) In some embodiments, the trigger **914** of the HVAC digital twin **904** can be the logical condition, “if there is low occupancy.” Similarly, the trigger **920** of the facility manager digital twin **906** can be the logical condition, “if there is low occupancy.” Responsive to the trigger **914** being triggered, the actions **918** can execute to switch an HVAC mode to an economy mode. The economy mode status for an HVAC system can be stored in the graph **928** and/or communicated to an HVAC controller to execute on. Responsive to the trigger **920** being triggered, the actions **924** can execute to notify a facility manager of the low occupancy status, e.g., send a notification to a user device of the facility manager.

(162) In some embodiments, the digital twins of the system **900** can be solution twins, e.g., the people counter twin **902**, the HVAC digital twin **904**, the facility manager twin **906**, etc. The digital twin can be a solution twin because it represents a particular software solutions for the building. For example, in some embodiments, an occupancy sensor digital twin of a zone could be triggered with under-utilized criteria

(e.g., the triggering of the people counter digital twin **902** shown in FIG. **9**). The people counter digital twin **902** could be configured to identify what AHU is serving the zone that it has made an occupancy detection for based on the nodes and/or edges of the graph **926** relating a zone node for the zone and an AHU node for the AHU. In some embodiments, the AHU digital twin can evaluate the desired setting for the zone through running a simulation with one or more models. In some embodiments, an FM digital twin can evaluate space arrangement and/or purposing.

(163) Referring now to FIG. **10**, a system **1000** including an employee digital twin **1002**, a calendar digital twin **1006**, a meeting room digital twin **1004**, and a cafeteria digital twin **1008** that have triggers and actions that are interconnected is shown, according to an exemplary embodiment. The system **1000** includes a solution digital twin for an employee, a meeting room, a cafeteria, and a calendar. In the system **1000**, an employee digital twin **1002** and a calendar digital twin **1006** cause one or more associated digital twins, a meeting room digital twin **1004** and a cafeteria digital twin **1008** to execute. In FIG. **10**, the state of the digital twins **1002** and **1006** are provided to the digital twins **1004** and **1008** as conditions for the triggers **1020** and **1026**. The calendar digital twin **1006** can include a connector **1016**, the meeting room digital twin can include a connector **1022**, and the cafeteria digital twin **1008** can include a connector **1028** for ingesting information into the graphs **1034-1038**.

(164) In FIG. **10**, the employee digital twin **1002** includes a graph **1032**, the calendar digital twin **1006** includes a graph **1036**, the meeting room digital twin **1004** includes a graph **1034**, and the cafeteria digital twin **1008** includes a graph **1038**. The graphs **1032-1038** can be the same graphs and/or different graphs and can be the same as, or similar to, the graph **529**.

(165) The employee digital twin **1002** can generate an “occupant near office” indication via the actions **1012** responsive to the trigger **1010** triggering when a particular occupant is a particular instance (e.g., 250 meters) from their office. The digital twin **1002** can identify the occupant, the occupant's office, and the location of the office through analyzing the nodes and/or edge of the graph **1032**. The calendar digital twin **1006** determines, based on calendar data (e.g., calendar data stored in the graph **1036**), whether it is a work day via the trigger **1014** (e.g., is a day Monday through Friday). Responsive to determining that it is a work day, the calendar digital twin **1006** generates an indication that it is a work day via the actions **1018**.

(166) The meeting room digital twin **1004** can receive the work day indication from the calendar digital twin **1006** and can receive the occupant near office indication from the employee digital twin **1002**. The meeting room digital twin **1004** can take actions to reserve a meeting room via the actions **1024** responsive to the trigger **1020** indicating that the occupant is near their office and it is a work day. The cafeteria digital twin **1008** can receive the “occupant near office” indication from the employee digital twin **1002** and can receive the “it is a work day” indication from the calendar digital twin **1006**. The cafeteria digital twin **1008** can trigger the ordering of a coffee for the occupant via the trigger **1030** responsive to the trigger **1026** being triggered.

(167) Referring now to FIG. **11**, a process **1100** of an agent executing a trigger rule and an action rule is shown, according to an exemplary embodiment. The process **1100** can be performed by the system **500** and/or components of the system **500**. In some embodiments, the building data platform **100** can perform the process **1100**. Furthermore, the process **1100** can be performed by any computing device described herein.

(168) In step **1102**, the building data platform **100** can store the AI agent **570** in a data structure. The AI agent **570** can include a trigger rule indicating a condition for executing an action rule and an action rule indicating an action to be performed responsive to the condition being met. In some embodiments, the model **576** includes, or can be replaced with, the trigger rule and the action rule. The trigger rule and the action rule can be logical statements and/or conditions that include parameter values and/or create an output action. The parameter values can, in some embodiments, be identified through a learning process, e.g., as described through FIGS. **12-22**.

(169) In step **1104**, the AI agent **570** can receive information from at least one of a physical device and/or from the graph **529**. The information can be generated by a physical device, e.g., the building subsystems **122**. The building data platform **100** can, in some embodiments, receive the information from the physical device, ingest the information into the graph **529**, and the AI agent **570** can read the information from the graph **529**. In some embodiments, the AI agent **570** can check the information of the graph **529** against a trigger rule at a set period.

(170) In step **1106**, the agent **570** determines whether the information received in the step **1104** causes the

condition to be met. The agent **570** can apply the information to the trigger rule to determine whether the trigger rule is triggered, i.e., the condition of the trigger rule being met.

(171) In step **1108**, the AI agent **570** can perform the action responsive to the condition being met by the information determined in step **1106**. The action may cause a physical device to be operated or information be sent to another agent including another trigger rule and another action rule. In some embodiments, the action can be performed by executing the action rule of the AI agent **570**. The action rule can perform an action based on one or more parameter value of the action rule. In some embodiments, the action output of the action rule can be sent directly to the physical device, e.g., the building subsystems **122**. In some embodiments, the action output can be stored into the graph **529**. Another operating component of the building data platform **100**, e.g., the command processor **136**, can read the action from the graph **529** can communicate a corresponding command to the building subsystems **122**.

(172) Referring generally to FIGS. **12-23**, systems and methods for using artificial intelligence to determine triggers and actions for an agent is shown. The triggers can trigger autonomously based on received data and cause an action to occur. In some embodiments, multiple digital twins can interact with each other by identifying interrelationships between each other via the graph **529**, e.g., a VAV digital twin could interact with an AHU digital twin responsive to identifying that a VAV represented by the VAV digital twin is related to an AHU represented by the AHU digital twin via the graph **529**. The digital twins can in some embodiments, simulate the impact of triggers and/or actions to validate and learn triggers and/or actions.

(173) In some embodiments, the building data platform **100** can perform q-learning (Reinforcement Learning) to train and/or retrain the triggers and/or actions of the agents. In some embodiments, the data used to train and/or retrain the triggers and/or actions can be simulated data determined by another digital twin.

(174) One digital twin may have trigger conditions such as, “when the outside temperature is $x_{sub.0}$,” “when the inside humidity is $x\%$,” “when an AI-driven algorithm's threshold is reached,” and “when it is a certain day of the week.” In responsive to one or multiple triggers being met, the digital twin can perform actions (e.g., capabilities of a device either inherent and/or digital twin enhanced). The actions can include setting a setpoint to a value $x_{sub.0}$. The actions can be to run a fan for x minutes. The actions can be to start an AI-driven energy saving schedule. The actions can be to change a mode status to an away status. In some embodiments, the building data platform **100** can use other digital twins to simulate a reward for various values of the triggers and/or actions. The reward can be optimized to determine values for the parameters of the triggers and/or actions.

(175) In some embodiments, allowing the digital twin to learn and adjust the parameters of the triggers and/or rules allows the digital twin to optimize responses to internal and/or external events in real-time. In some embodiments, the digital twin performs operations with the correlation of contextual relationships to provide spatial intelligence. In some embodiments, the digital twin allows for AI-based self-learning solutions to operate on top of the digital twin. The digital twin can capture comprehensive data that drives rich analytics for security, compliance, etc. In some embodiments, the digital twin can enable and perform simulations.

(176) In some embodiments, the building data platform **100** can identify events and/or event patterns if the building data platform **100** identifies a pattern that suggests a trigger and/or action should be updated. For example, if the building data platform **100** identifies a pattern occurring in a building, the building data platform **100** can set triggers and/or actions in digital twins to allow the pattern to occur automatically. For example, if a user closes their blinds at 5:00 P.M. regularly on weekdays, this could indicate that the user desires the blinds to be closed at 5:00 P.M. each day. The building data platform **100** can set a blind control digital twin to trigger a blind closing action at 5:00 P.M. each day.

(177) In some embodiments, an agent of a digital twin can predict an inference in the future indicating that some action should be performed in the future. The building data platform **100** can identify that the action should be performed in the future and can set up a flow so that a prediction of one digital twin can be fed into another digital twin that can perform the action.

(178) Referring now to FIG. **12**, a system **1200** of a trigger rule **1202** of a thermostat digital twin where parameters of the trigger rule **1202** are trained is shown, according to an exemplary embodiment. In some embodiments, the system **1200** can implement a model that rewards triggers and/or actions of the thermostat digital twin using a neural network that is trained from data aggregated from a related digital

twin of the thermostat digital twin, an air handler unit digital twin.

(179) The building data platform **100** can perturb parameters, $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$ of the trigger rule **1202** of the thermostat digital twin. The trigger rule **1202** may be that if a number of occupants is greater than $\epsilon_{\text{sub.1}}$ and a zone temperature is less than $\epsilon_{\text{sub.2}}^{\circ}\text{C}$, the rule is triggered and a corresponding action be performed. The corresponding action can be to increase a supply air temperature setpoint of an AHU to 22°C . The perturbation of the parameters can be increasing or decreasing the parameters in set amounts from existing values. The perturbation of the parameters can be selecting a space of values for the parameters and/or randomizing the parameters and/or parameter space.

(180) With the perturbed values for $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$, the AHU digital twin **1204** can simulate the state of the AHU via the AHU digital twin **1204** for various conditions of occupant number and zone temperature. The result of the various states of the AHU digital twin **1204**. The simulation can be performed by the AI agent **570** via the model **576**. The output of the model **576** can be the simulated states, e.g., timeseries **566**.

(181) The building data platform **100** can analyze the states produced by the AHU digital twin **1204** to determine energy and comfort results from the states of the AHU digital twin **1204**. For example, an energy score can be generated for each state. For example, a power consumption level can be determined for each state. Similarly, a comfort violation score can be determined for each state. The comfort violation can indicate whether or not a temperature, humidity, or other condition of a physical space controlled by the AHU would be uncomfortable for a user (e.g., go below or above certain levels).

(182) The building data platform **100** can generate accumulated training data. The accumulated training data can include the values of the parameters $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$, the state of the AHU digital twin **1204** for each value of the parameters, and the energy score and comfort violation score for each state. In some embodiments, the triggers and/or actions that can be recommended for the thermostat digital twin can be determined by observing the responses of other digital twins on perturbed thresholds of existing triggers and/or actions.

(183) The building data platform **100** can generate neural networks **1210** for predicting an energy score based on the parameters $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$. Furthermore, the neural networks **1210** can indicate a comfort violation score for the parameters $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$. The neural networks **1210** can be trained by the building data platform **100** based on the accumulated training data **1208**.

(184) Based on the trained neural network models **1210**, the building data platform **100** can determine optimal values for the parameters $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$. The building data platform **100** can search a space of potential values for $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$ that consider predicted energy scores and/or comfort violation scores predicted by the trained neural network models **1210**. The optimization can be the relation **1400** shown in FIG. **14**. The optimization **1212** performed by the building data platform **100** can be a method of computing the optimal threshold of a trigger conditions using the neural network models **1210** of rewards (e.g., energy and comfort) and solving constrained optimization model. Similarly, the optimization **1212** performed by the building data platform **100** to determine the optimal threshold of action commands using the neural network models **1210** of rewards and solving constrained optimization.

(185) In some embodiments, the optimal values for the parameters found by the building data platform **100** can be presented to a user for review and/or approval via a user interface, e.g., via the user device **176**. In some embodiments, the recommendations produced by the building data platform **100** through the components **1202-1212** can be restricted by only looking at state/value changes of digital twins that are nearest neighbors in the graph **529**, e.g., two nodes are directed related by one edge, e.g., a thermostat node for the thermostat digital twin is directed to an AHU node for the AHU digital twin **1204**. In some embodiments, the building data platform **100** can use spatial correlation to assume contextual relationship between assets that can affect each other's attribute states/values.

(186) Referring now to FIG. **13**, a process **1300** for identifying values for the parameters of the trigger rule **1202** of FIG. **12** is shown, according to an exemplary embodiment. The process **1300** can be performed by the building data platform **100** and/or any component of the building data platform **100**. The process **1300** can be performed by the system **500** and/or components of the system **500**. Furthermore, the process **1300** can be performed by any computing device described herein.

(187) In step **1302**, the building data platform **100** can perturb a thermostat digital twin (e.g., the thermostat digital twin rule **1202**) with various value for thresholds and/or other parameters, E. The result of the perturbed parameters can result in various states, s. The states can be states predicted by the

thermostat digital twin or another digital twin that operates based on the thresholds and/or parameters ϵ , e.g., the AHU digital twin **1204**. The perturbations and simulated states can result in pairs (S, ϵ) . The pairs can be used to determine feedback for energy and/or comfort, e.g., (E, C) .

(188) In step **1304**, the building data platform **100** can build neural network models, e.g., the neural networks **1210** based on the data determined in step **1302**. The neural networks **1210** can predict energy rewards as a function of the state and the parameters, e.g., $E=f(s, \epsilon)$. Furthermore, the neural networks **1210** can predict comfort rewards as a function of the state and the parameters, e.g., $C=f(s, \epsilon)$.

(189) In step **1306**, the building data platform **100** can determine a value for the parameter, E that minimizes a relation, $(\alpha.\text{sub}.1.\text{Math}.E + \alpha.\text{sub}.2.\text{Math}.C)$. The minimization is shown in relation **1400** of FIG. **14**. The values of $\alpha.\text{sub}.1$ and $\alpha.\text{sub}.2$ can weigh the various rewards in the relation that is minimized, e.g., the energy reward and/or the comfort reward. In step **1308**, the building data platform **100** can periodically repeat the steps **1302-1306**. For example, the building data platform **100** can repeat the steps at a defined time period. In some embodiments, the building data platform **100** can compute rewards for the actions of the thermostat digital twin. If the rewards indicate that the thermostat digital twin need retraining, the building data platform **100** can repeat the steps **1302-1308**.

(190) Referring now to FIG. **15**, a system **1500** of components where an action rule **1502** of a thermostat digital twin is shown where parameters of the action rule **1502** are trained, according to an exemplary embodiment. The system **1500** can include similar and/or the same components of FIG. **14**. The process **1300** of FIG. **13** can be applied to the action rule **1502** to train the parameters of the action rule **1502**.

(191) The thermostat digital twin rule **1502** can be an action rule that if a trigger is met (e.g., the trigger **1402**), the action rule **1502** executes to command the AHU digital twin **1204**. The trigger rule may be to execute the action rule if an occupant count is greater than ten and a zone temperature is less than twenty degrees Celsius. The action rule **1502** may be to increase an AHU supply air temperature setpoint to a value, e.g., E . The value can, in some embodiments, be 22 degrees Celsius.

(192) The building data platform **100** can predict states resulting from perturbed values of E by executing the AHU digital twin **1204** to simulate the states. The building data platform **100** can collect rule feedback **1206** to construct accumulated training data **1208**. Furthermore, the building data platform **100** can train neural network models **1210** based on the accumulated training data **1208** and find optimal values for the parameter E based on the trained neural network models **1210**.

(193) Referring now to FIG. **16**, a list **1600** and a list **1602** of states of a zone and of an air handler unit that can be used to train the parameters of the trigger rule and the action rule of the thermostat digital twins of FIGS. **12-15** is shown, according to an exemplary embodiment. The list **1600** includes states for a zone. The states can be zone temperature, zone humidity, outdoor air temperature, outdoor air humidity, zone occupancy, etc. These states can be predicted and/or determined based on a digital twin for a space based on perturbed parameter values for a trigger rule, an action rule, weather forecasts, etc. In this regard, the rule feedback **1206**, in some embodiments, can be generated based on the digital twin for the space and used to tune the values of the parameters for the trigger rule **1402** and/or the action rule **1502**.

(194) The list **1602** includes states for an AHU. The states can be supply air temperature, supply air flow rate, return air temperature, return air flow rate, outdoor air flow rate, etc. These states can be predicted and/or determined based on a digital twin for an AHU (e.g., the AHU digital twin **1204**) based on perturbed parameter values for a trigger rule, an action rule, etc. In this regard, the rule feedback **1206** in some embodiments, can be generated based on the digital twin for the AHU and used to tune the values of the parameters for the trigger rule **1402** and/or the action rule **1502**.

(195) Referring now to FIG. **17**, a system **1700** of a trigger rule of a chemical reactor digital twin where parameters of a trigger rule are trained is shown, according to an exemplary embodiment. A reactor feed digital twin which may model the feed of a chemical reactor can include various trigger rules and/or action rules, e.g., the trigger rule **1702**. The trigger rule **1702** can be that if a chemical concentration of a first chemical A is less than $\epsilon.\text{sub}.1$ (e.g., 10 g/l) and a chemical concentration of a second chemical B is less than $\epsilon.\text{sub}.2$ (e.g., 20 g/l) then an action rule is triggered. The action rule may be increase a catalyst C feed amount to 300 g/s.

(196) The building data platform **100** can perturb the values for the parameters $\epsilon.\text{sub}.1$ and $\epsilon.\text{sub}.2$ of the reactor feed digital twin trigger rule **1702** (e.g., pseudo-randomly, increasing and/or decreasing in a particular number of predefined increments, etc.). A chemical reactor digital twin **1704** can simulate a state of the chemical reactor for the various perturbed parameters $\epsilon.\text{sub}.1$ and $\epsilon.\text{sub}.2$. The building data

platform **100** can determine a rule feedback **1706** for the state simulated by the chemical reactor digital twin **1704**. The rule feedback **1706** can identify scores for production throughput (P) and chemical property (C). (197) The building data platform **100** can accumulate training data **1708**. The accumulated training data **1708** can include the feedback **1706**, the state simulated by the chemical reactor digital twin **1704**, and/or the parameter values for $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$. The building data platform **100** can train neural network models **1710** to predict production throughput and/or chemical property for the various parameter and/or state pairs, e.g., the state resulting from the parameters of the trigger rule **1702**. The building data platform **100** can use the trained neural network models **1710** to identify optimal values for $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$. In element **1712**, the building data platform **100** can identify values for $\epsilon_{\text{sub.1}}$ and $\epsilon_{\text{sub.2}}$ that minimize the relation **1900** shown in FIG. **19**. In some embodiment, the optimization can optimize production throughput and/or chemical property.

(198) Referring now to FIG. **18**, a process **1800** for identifying values for the parameters of the trigger rule of FIG. **17** is shown, according to an exemplary embodiment. The process **1800** can be performed by the building data platform **100** and/or any component of the building data platform **100**. The process **1900** can be performed by the system **500** and/or components of the system **500**. Furthermore, the process **1800** can be performed by any computing device described herein. The steps **1802-1808** can be the same as or similar to the steps **1302-1308**. However, the steps **1802-1808** can be executed for a reactor digital twin and the reward for training the neural networks can be production throughput and chemical property.

(199) In step **1802**, the building data platform **100** can perturb a reactor digital twin **1704** with various values of a threshold E of a trigger rule **1702** with various values which cause the reactor digital twin to determine resulting states for the various values of the threshold, E. The states and the values for the threshold E can create state threshold pairs. The pairs can be used to determine feedback, e.g., production throughput and chemical property.

(200) In step **1804**, after some accumulation of feedback data, the building data platform **100** can build neural network models **1710** based on the pairs that predict production throughput and chemical property based on the values for the threshold E. In step **1806**, the building data platform **100** can determine a value for the threshold E that maximizes a reward and/or minimizes a penalty. The building data platform **100** can minimize the relation **1900** of FIG. **19**. In step **1808**, the building data platform **100** can periodically retrain the values for the threshold E for the trigger rule **1702**.

(201) Referring now to FIG. **20**, a system **2000** including an action rule **2002** of a chemical reactor digital twin where parameters of the action rule **2002** are trained is shown, according to an exemplary embodiment. The reactor feed twin rule **2002** can be an action rule to increase a catalyst C feed amount to $\epsilon_{\text{sub.1}}$ g/s in response to an trigger rule being triggered, e.g., the trigger rule **1702**. The building data platform **100** can perturb the values of the parameter $\epsilon_{\text{sub.1}}$ and the reactor digital twin **1704** can predict states resulting from the perturbed parameter. The building data platform **100** can determine rule feedback **1706** and generate accumulated training data **1708** based on the rule feedback **1706**. The building data platform **100** can train the neural network models **1710**. Based on the neural network models **1710**, the building data platform **100** can find optimal values for the parameter $\epsilon_{\text{sub.1}}$.

(202) Referring now to FIG. **21**, a list **2100** and a list **2102** of states of a feed of a reactor and a reactor that can be included in the trigger rule and the action rule of FIGS. **12-15** are shown, according to an exemplary embodiment. The list **2100** includes states for a feed of a chemical reactor. The states can be reactants feed amount, catalysts feed amount, feed stream temperature, etc. These states can be predicted and/or determined based on a digital twin for a space based on perturbed parameter values for a trigger rule, an action rule, etc. In this regard, the rule feedback **1706** in some embodiments, can be generated based on the digital twin for the space and used to tune the values of the parameters for the trigger rule **1702** and/or the action rule **2002**.

(203) The list **2102** includes states for a chemical reactor. The states can be product concentration, cooling coil temperature, product temperature, etc. These states can be predicted and/or determined based on a digital twin for a chemical reactor (e.g., the reactor digital twin **1704**) based on perturbed parameter values for a trigger rule, an action rule, etc. In this regard, the rule feedback **1706** in some embodiments, can be generated based on the digital twin for the chemical reactor and used to tune the values of the parameters for the trigger rule **1702** and/or the action rule **2002**.

(204) Referring now to FIG. **22**, a system **2200** where triggers and actions that can be constructed and learned for a digital twin is shown, according to an exemplary embodiment. Considering a building where

a room in the building has a thermostat, the building data platform **100** can construct triggers and/or actions of an agent of a digital twin or the room. The triggers and/or actions can be determined with an energy reduction reward function **2204** by a learning service **2206**. The energy reduction reward function **2204** can produce triggers and/or actions that have values that minimize energy usage.

(205) In some embodiments, the building data platform **100** can search the graph **529** to identify information related to the space, e.g., related pieces of equipment, spaces, people, etc. For example, the building data platform **100** can identify which entities of the graph **529** are related and operate to affect each other. The building data platform **100** can identify which actions each entity can perform and/or what measurements each entity can make, e.g., by identifying related data nodes for each entity. The identified entities, measurements, and/or commands can be combined into the rule **2202** by the building data platform **100**.

(206) In some embodiments, the learning service **2206**, which may be a component of the building data platform **100**, can run a learning process with the rule **2202** and/or one or more reward functions (e.g., comfort reward function, carbon footprint reduction reward function, the energy reduction reward function **2204**, etc.). The learning service **2206** can learn the rule **2208** from the rule **2202** and/or the energy reduction reward function **2204**.

(207) The learning service **2206** can run an optimization to determine combinations between measurements and actions triggered based on the measurements. The learning service **2206** can determine values for each measurement and/or action. Furthermore, the learning service **2206** can identify the relational operations for causing a trigger, e.g., equals to, greater than, less than, not equal to, etc. Furthermore, the learning service **2206** can identify action operations, e.g., increase by a particular amount, decrease by a particular amount, set an output equal to a value, run a particular algorithm, etc.

(208) Referring now to FIG. **23**, a process **2300** for constructing triggers and actions for a digital twin is shown, according to an exemplary embodiment. In some embodiments, the process **2300** can be performed by the building data platform **100**. In some embodiments, the process **2300** can be performed by the learning service **2206**.

(209) In step **2302**, the building data platform **100** can determine actions that a particular entity can take and data that the entity can measure by analyzing a graph **529**. The entity can be a thermostat, an air handler unit, a zone of a building, a person, a VAV unit, and/or any other entity. For example, if the entity is a thermostat the building data platform **100** could identify room temperature measurements for a thermostat and/or a cooling stage command, a heating stage command, a fan command, etc. that the thermostat can perform. Responsive to identifying data that the entity can measure, the building data platform **100** can generate a trigger condition based on the data type, e.g., when the temperature is equal to, less than, greater than, and/or not equal to some parameter value, trigger an action.

(210) In step **2304**, the building data platform **100** identifies, based on the graph **529**, entities related to the entity and actions that the entities can take and data that the entities can measure. For example, if the entity is for a thermostat for a zone, the building data platform **100**, could identify a shade control system for controlling a shade of the zone, an air handler unit that serves the zone, a VAV that serves the zone, etc. For example, the building data platform **100** can identify, based on the building graph **529**, that a blinds node is associated with a zone node which the thermostat node is related to. The building data platform **100** can identify a list of actions that the entities can perform, e.g., setting blind position from 0% (fully open) to 100% (fully closed).

(211) In some **2306**, the building data platform **100** can simulate various combinations of triggers that are based on the data that the entity and/or entities can measure and actions that are based on the actions that the entity and/or entities can make. The building data platform **100** can simulate various combinations, trigger operations, action operations, and/or parameters.

(212) In step **2308**, the building data platform **100** can identify a combination of triggers and actions that maximizes a reward. The building data platform **100** can search the simulated combinations of triggers and/or actions to identify a trigger and/or action that maximizes a reward and/or minimizes a reward. In some embodiments, the building data platform **100** uses a policy gradient and value function instead of brute force to try out combinations of the triggers and/or actions in the steps **2306-2308**.

(213) In some embodiments, the building data platform **100** can identify the operations for the triggers and/or actions. For example, the operation could be comparing a measurement to a threshold, determining whether a measurement is less than a threshold, determining whether a measurement is greater than the

threshold, determining whether the measurement is not equal to the threshold, etc.

(214) In step **2310**, the building data platform **100** can generate a digital twin for the entity. The entity can include (or reference) the graph **529** and include an agent that operates the triggers and/or actions. The triggers and/or actions can operate based on the graph **529** and/or based on data received building equipment, e.g., the building subsystems **122**.

(215) In step **2312**, the building data platform **100** can run a building system of a building and monitor the behavior of the entity and entities of the building. In some embodiments, the building system can be the building subsystems **122**. In step **2314**, the building data platform **100** can identify relationships between the measurements and actions of the entity and/or the entities based on the monitored behavior. The building data platform **100** can discover existing relationships by identifying how the measurements are currently affecting actions based on the monitored behavior. In step **2316**, the building data platform **100** can optimize the identified relationships between the measurements and the actions by maximizing a reward or minimizing a penalty.

(216) Referring now to FIG. **24**, a system **2400** where metadata sources **2406** are integrated with the building data platform **100** is shown, according to an exemplary embodiment. The system **2400** can be implemented on one or more processing circuits, e.g., as instructions stored on one or more memory devices and executed on one or more processors. The memory devices and processors may be the same as or similar to the memory devices and processors described with reference to FIG. **1**.

(217) The system **2400** includes a schema infusing tool **2404**. The schema infusing tool can infuse a particular schema, the schema **2402**, into various systems, services, and/or equipment in order to integrate the data of the various systems, services, and/or equipment into the building data platform **100**. The schema **2402** may be the BRICK schema, in some embodiments. In some embodiment, the schema **2402** may be a schema that uses portions and/or all of the BRICK schema but also includes unique class, relationship types, and/or unique schema rules. The schema infusing tool **2404** can infuse the schema **2402** into systems such as systems that manage and/or produce building information model (BIM) data **2418**, building automation system (BAS) systems that produce BAS data **2420**, and/or access control and video surveillance (ACVS) systems that produce ACVS data **2422**. In some embodiments, the BIM data **2418** can be generated by BIM automation utilities **2501**.

(218) The BIM data **2418** can include data such as Revit data **2424** (e.g., Navisworks data), industrial foundation class (IFC) data **2426**, gbxml data **2428**, and/or CoBie data **2430**. The BAS data **2420** can include Modelica data **2432** (e.g., Control Description Language (CDL) data), Project Haystack data **2434**, Bacnet data **2436**, Metasys data **2438**, and/or Easy IO data **2440**. All of this data can utilizing the schema **2402** and/or be capable of being mapped into the schema **2402**.

(219) The BAS data **2420** and/or the ACVS data **2422** may include timeseries data **2408**. The timeseries data **2408** can include trends of data points over time, e.g., a time correlated set of data values each corresponding to time stamps. The timeseries data can be a timeseries of data measurements, e.g., temperature measurements, pressure measurements, etc. Furthermore, the timeseries data can be a timeseries of inferred and/or predicted information, e.g., an inferred temperature value, an inferred energy load, a predicted weather forecast, identities of individuals granted access to a facility over time, etc. The timeseries data **2408** can further indicate command and/or control data, e.g., the damper position of a VAV over time, the setpoint of a thermostat over time, etc.

(220) The system **2400** includes a schema mapping toolchain **2412**. The schema mapping toolchain **2412** can map the data of the metadata sources **2406** into data of the schema **2402**, e.g., the data in schema **2414**. The data in schema **2414** may be in a schema that can be integrated by an integration toolchain **2416** with the building data platform **100** (e.g. ingested into the databases, graphs, and/or knowledge bases of the building data platform **100**) and/or provided to the AI services and applications **2410** for execution).

(221) The AI services and applications **2410** include building control **2442**, analytics **2444**, microgrid management **2446**, and various other applications **2448**. The building control **2442** can include various control applications that may utilize AI, ML, and/or any other software technique for managing control of a building. The building control **2442** can include auto sequence of operation, optimal supervisory controls, etc. The analytics **2444** include clean air optimization (CAO) applications, energy prediction model (EPM) applications, and/or any other type of analytics.

(222) Referring now to FIG. **25**, a system **2500** including metadata sources **2406** being integrated with the building data platform **100** and including AI agents is shown, according to an exemplary embodiment. The

system **2500** can be implemented on one or more processing circuits, e.g., as instructions stored on one or more memory devices and executed on one or more processors. The memory devices and processors may be the same as or similar to the memory devices and processors described with reference to FIG. 1.

(223) The system **2500** includes various tools for converting the metadata sources **2406** into the data in schema **2414**. Various mapping tools **2502-2512** can map data from an existing schema into the schema **2402**. For example, the mapping tools **2502-2512** can utilize a dictionary that provides mapping rules and syntax substitutions. In some embodiments, that data sources can have the schema **2402** activated, e.g., schema enable **2518-2522**. If the schema **2402** is enabled for a Metasys data source, an easy **10** data source, or an ACVS data sources, the output data by said systems can be in the schema **2402**. Examples of schema mapping techniques can be found in U.S. patent application Ser. No. 16/663,623 filed Oct. 25, 2019, U.S. patent application Ser. No. 16/885,968 filed May 28, 2020, and U.S. patent application Ser. No. 16/885,959 filed May 28, 2020, the entireties of which are incorporated by reference herein.

(224) For the EasyIO data **2440**, the EasyIO controller objects could be tagged with classes of the schema **2402**. For the Revit data **2424**, the metadata of a REVIT model could be converted into the schema **2402**, e.g., into a resource description format (RDF). For the Metasys data **2438**, Metasys SCT data could be converted into RDF. An OpenRefine aided mapping tool **2514** and/or a natural language aided mapping tool **2516** could perform the schema translation for the Bacnet data **2436**.

(225) The schema data output by the tools **2502-2522** can be provided to a reconciliation tool **2530**. The reconciliation tool **2530** can be configured to merge complementary or duplicate information and/or resolve any conflicts in the data received from the tools **2502-2522**. The result of the reconciliation performed by the reconciliation tool **2530** can be the data in schema **2414** which can be ingested into the building data platform **100** by the ingestion tool **2532**. The ingestion tool **2532** can generate and/or update one or more graphs managed and/or stored by the twin manager **108**. The graph could be the graphs described with reference to FIGS. 1-5 and further the graph shown in FIG. 26.

(226) The system **2500** includes agents that perform operations on behalf of the AI services and applications **2410**. For example, as shown in the system **2500**, the analytics **2444** are related to various agents, a CAO AI agent **2524**, an EPM AI agent **2526**, and various other AI agents **2528**. The agents **2524-2528** can receive data from the building data platform **100**, e.g., the data that the ingestion tool **2532** ingests into the building data platform **100**, and generate analytics data for the analytics **2444**.

(227) Referring now to FIG. 26, a system **2600** where a clean air optimization (CAO) AI service **2604** and an energy prediction model (EPM) AI service **2606** operate to make inferences and predictions based on data of a knowledge graph **2602** is shown, according to an exemplary embodiment. The knowledge graph **2602** includes various nodes and edges. The nodes may be the nodes **2608-2642**. The edges may be the edges **2644-2678**.

(228) The nodes may represent various entities of a building and/or buildings. The entities may be a campus, a building, a floor, a space, a zone, a piece of equipment, a person, a control point, a data measurement point, a sensor, an actuator, telemetry data, a piece of timeseries data, etc. The edges **2644-2678** can interrelate the nodes **2608-2642** to represent the relationships between the various entities of the building. The edges **2644-2678** can be semantic language based edges **2644-2678**. The edges can include words and/or phrases that represent the relationship. The words and/or phrases can include at least one predicate, in some cases.

(229) The knowledge graph **2602** includes a building node **2636** representing a building. The building can include floors, represented by the building node **2636** being related to a floor 1 node **2640** via a “hasPart” edge **2670** and the building node **2636** being related to a floor 3 node **2638** via a “feeds” edge **2668**. The building includes an energy prediction, e.g., a value or a timeseries of values indicating energy usage of the building. This can be represented by the building node **2636** being related to an energy prediction node **2630** via the edge **2672**.

(230) The floor 1 includes zones, indicated by the floor 1 node **2640** being related to a zone1-1 node **2608** via a “hasPart” edge **2644** and the floor 1 node **2640** being related to a zone1-2 node **2642** via a “hasPart” edge **2645**. Furthermore, the floor 1 can be fed by a particular AHU, AHU1. This is indicated by an AHU1 node **2622** being related to the floor 1 node **2640** via the “feeds” edge **2660**. The zone1-2 can include a VAV1-2 that feeds air to it. This can be indicated by the VAV1-2 node **2610** being related to the zone1-2 node **2642** by the “feeds” node **2662**. The AHU1 can feed the VAV1-2, indicated by the AHU1 node **2622** being related to the VAV1-2 node **2610** by the “feeds” edge **2658**.

(231) An AHU 3 can feed air to the floor 3, indicated by the “AHU3” node **2634** being related to the “floor 3” node **2638** by the “feeds” edge **2666**. The “AHU3” node **2634** is related to a CAO inference **2628** via an edge **2674** representing that the AHU has a clean air optimization inference that could be determined by the CAO AI service **2604**. The knowledge graph **2602** includes an AHU2 node **2632**. The AHU2 **2632** is related to a floor 2 node **2641** via a “feeds” edge **2664** indicating that the AHU2 feeds air to the floor 2. The AHU2 node **2632** is related to a CAO inference **2626** via the edge **2676**. The CAO inference **2626** can indicate an inference made by the CAO AI service **2604** for the AHU2. The AHU1 **2622** is related to a CAO inference **2624** via edge **2678**. The CAO inference **2624** can indicate a clean air optimization inference made by the CAO AI service **2604** for the AHU1.

(232) The knowledge graph **2602** includes a VAV1-1 node **2612** indicating a VAV1-1. The VAV1-1 node **2612** is related to the zone1-1 node **2608** via a “feeds” edge **2646** indicating that the VAV1-1 feeds air to the zone1-1. The AHU1 can feed air to the VAV1-1 indicated by the AHU1 node **2622** being related to the VAV1-1 node **2612** via the “feeds” edge **2656**. The VAV1-1 node **2612** includes various points, e.g., a zone temperature point (represented by the VAV1.ZN-T node **2614**) and a zone relative humidity point (represented by the VAV1.ZN-RH node **2616**). The VAV1-1 node **2612** is related to the VAV1.ZN-T node **2614** via the “hasPoint” edge **2648**. The VAV1-1 node **2612** is related to the VAV1.ZN-RH node **2616** via the “hasPoint” edge **2654**.

(233) The VAV1.ZN-T point includes a timeseries node **2618** representing and/or storing a timeseries for the zone temperature, indicated by the timeseries node **2618** being related to the VAV1.ZN-T node **2614** via the “hasTimeseriesID” node **2650**. The VAV1.ZN-RH point includes a timeseries node **2620** representing and/or storing a timeseries for the zone humidity, indicated by the timeseries node **2620** being related to the VAV1.ZN-RH node **2616** via the “hasTimeseriesID” node **2652**. In some embodiments, the timeseries node **2618** and the timeseries node **2620** are identifiers of a particular timeseries stored in a separate timeseries database, the identifier uniquely identifying the location of the timeseries so a system can consult the knowledge graph **2602** and use the identifiers to retrieve the timeseries data from the separate timeseries database.

(234) The system **2600** includes a CAO AI service **2604**. The CAO AI service **2604** can be configured to identify timeseries that it needs to execute on. For example, if the CAO AI service **2604** is executing for the AHU1, the CAO AI service **2604** could identify timeseries data linked to the AHU1. The CAO AI service **2604** can generate CAO inferences, e.g., can infer ideal settings for clean air. The ideal settings could be an AHU supply air temperature setpoint, an AHU minimum ventilation rate, etc. The ideal settings can be ingested into the knowledge graph **2602**, e.g., as the CAO inferences **2624-2630**.

(235) In some embodiments, the CAO AI service **2604** (or an agent for the CAO AI service **2604**) operates on behalf of a particular entity, e.g., the AHU 1. The CAO AI service **2604** can generate inferences with data of the AHU 1, e.g., by identifying timeseries data of the AHU 1 by identifying timeseries nodes of the knowledge graph **2602** via an edge. The inferences can be ingested into the knowledge graph **2602** by generating a new node and/or adding an edge between the new node and the node of the AHU 1, AHU 1 node **2622**. Similarly, the inferences can be added to the knowledge graph **2602** by updating an existing node related to the AHU 1 node **2622** via an existing edge. In some embodiments, the inferences of the CAO AI service **2604** can generate a recommendation, e.g., a control setting for improving or optimizing air quality, which can be reviewed and approved by a user via the user device **176**.

(236) The EPM AI service **2606** can generate energy predictions for various buildings, spaces, or devices of a building, e.g., entities of the knowledge graph **2602**. For example, the EPM AI service **2606** could predict a future energy consumption level of the building **2636**, e.g., a future energy demand. The energy prediction can be a node **2630** related to the building node **2636** via the edge **2672**. In some embodiments, the EPM AI service **2606** can generate the energy prediction node **2630** responsive to generating the future building energy consumption and cause the node **2630** to include a value for the future building energy consumption. The node **2630** can be added to the graph **2602** and the edge **2672** can be generated by the EPM AI service **2606** and added between the building node **2636** and the energy prediction **2630**.

(237) In some embodiments, the energy prediction node **2630** already exists within the knowledge graph **2602**. In this example, the EPM AI service **2606** can identify the energy prediction node **2630** by identifying an edge **2672** between the building **2636** and the energy prediction node **2630**. The EPM AI service **2606** can then ingest the energy prediction into the node **2630**.

(238) Referring now to FIG. 27, a system **2700** including a CAO AI agent **2524** and an EPM AI agent

2526 operating against the knowledge graph **2602** to generate inferences and predictions is shown, according to an exemplary embodiment. The system **2700** can be implemented on one or more processing circuits, e.g., as instructions stored on one or more memory devices and executed on one or more processors. The memory devices and processors may be the same as or similar to the memory devices and processors described with reference to FIG. 1.

(239) The CAO AI agent **2524** can operate on behalf of the CAO AI service **2604**. Similarly, the EPM AI agent **2526** can operate on behalf of the EPM AI service **2606**. Furthermore a service bus **2714** can interface with the agent **2524** and/or the agent **2526**. A user can interface with the agents **2524-2526** via the user device **176**. The user can provide an entitlement request, e.g., a request that the user is entitled to make and can be verified by the AI agent manager **2716**. The AI agent manager **2716** can send an AI job request based on a schedule to the service bus **2714** based on the entitlement request. The service bus **2714** can communicate the AI job request to the appropriate agent and/or communicate results for the AI job back to the user device **176**.

(240) In some embodiments, the CAO AI agent **2524** can provide a request for generating an inference to the CAO AI service **2604**. The request can include data read from the knowledge graph **2602**, in some embodiments.

(241) The CAO AI agent **2524** includes a client **2702**, a schema translator **2704**, and a CAO client **2706**. The client **2702** can be configured to interface with the knowledge graph **2602**, e.g., read data out of the knowledge graph **2602**. The client **2702** can further ingest inferences back into the knowledge graph **2602**. For example, the client **2702** could identify timeseries nodes related to the AHU1 node **2622**, e.g., timeseries nodes related to the AHU1 node **2622** via one or more edges. The client **2702** can then ingest the inference made by the CAO AI agent **2524** into the knowledge graph **2602**, e.g., add the CAO inference **2624** or update the CAO inference **2624**.

(242) The client **2702** can provide data it reads from the knowledge graph **2602** to a schema translator **2704** that may translate the data into a specific format in a specific schema that is appropriate for consumption by the CAO client **2706** and/or the CAO AI service **2604**. The CAO client **2706** can run one or more algorithms, software components, machine learning models, etc. to generate the inference and provide the inference to the client **2702**. In some embodiments, the client **2706** can interface with the EPM AI service **2606** and provide the translated data to the EPM AI service **2606** for generating an inference. The inference can be returned by the EPM AI service **2606** to the CAO client **2706**.

(243) The EPM AI agent **2526** can operate in a similar manner to the CAO AI agent **2524**, in some embodiments. The client **2708** can retrieve data from the knowledge graph **2602** and provide the data to the schema translator **2710**. The schema translator **2710** can translate the data into a readable format by the CAO AI service **2604** and can provide the data to the EPM client **2712**. The EPM client **2712** can provide the data along with a prediction request to the CAO AI service **2604**. The CAO AI service **2604** can generate the prediction and provide the prediction to the EPM client **2712**. The EPM client **2712** can provide the prediction to the client **2708** and the client **2708** can ingest the prediction into the knowledge graph **2602**.

(244) In some embodiments, the knowledge graph **2602** includes data necessary for the inferences and/or predictions that the agents **2524** and **2526** generate. For example, the knowledge graph **2602** can store information such as the size of a building, the number of floors of the building, the equipment of each floor of the building, the square footage of each floor, square footage of each zone, ceiling heights, etc. The data can be stored as nodes in the knowledge graph **2602** representing the physical characteristics of the building. In some embodiments, the EPM AI agent **2526** makes the predictions based on the characteristic data of the building and/or physical areas of the building.

(245) Referring now to FIG. 28, inferences and/or predictions of the CAO AI agent **2524** and the EPM AI agent **2526** being presented in a graphic interface is shown, according to an exemplary embodiment. The system **2800** can be implemented on one or more processing circuits, e.g., as instructions stored on one or more memory devices and executed on one or more processors. The memory devices and processors may be the same as or similar to the memory devices and processors described with reference to FIG. 1.

(246) The system **2800** includes a client **2802**. The client **2802** can integrate with the knowledge graph **2602** and also with a graphical building model **2804** that can be rendered on a screen of the user device **176**.

(247) The client **2802** can retrieve information from the knowledge graph **2602**, e.g., an inference

generated by the CAO AI agent **2524**, a prediction made by the EPM AI agent **2526**, and/or operational data stored in the knowledge graph **2602**. The client **2802** can ingest the values of the retrieved information into the graphical building model **2804** which can be displayed on the user device **176**. In some embodiments, when a particular visual component is being displayed on the user device **176** for the virtual model **2804**, e.g., a building, the corresponding information for the building can be displayed in the interface, e.g., inferences, predictions, and/or operational data.

(248) For example, the client **2802** could identify a node of the building in the knowledge graph **2602**, e.g., the building node **2636**. The client **2802** could identify information linked to the building node **2636** via edges, e.g., the energy prediction **2630** related to the building node **2636** via edge **2672**. The client **2802** can cause the energy prediction **2630** to be displayed in the graphical building model **2804**.

(249) In some embodiments, a user can provide input through the graphical building model **2804**. The input may be a manual action that a user provides via the user device **176**. The manual action can be ingested into the knowledge graph **2602** and stored as a node within the knowledge graph **2602**. In some embodiments, the manual action can trigger one of the agents **2524-2526** causing the agent to generate an inference and/or prediction which is ingested into the knowledge graph **2602** and presented for user review in the model **2804**.

(250) In some embodiments, the agents **2524-2526** are the same as, or similar to, the agents described with reference to FIGS. 5-23. For example, the agents **2524-2526** combined with the knowledge graph **2602** can create a digital twin. In some embodiments, the agents **2524-2526** are implemented for a specific node of the knowledge graph **2602**, e.g., on behalf of some and/or all of the entities of the knowledge graph **2602**. In some embodiments, the digital twin includes trigger and/or actions as discussed with reference to FIGS. 5-23. In this regard, the agents can trigger based on information of the knowledge graph **2602** (e.g., building ingested data and/or manual commands provide via the model **2804**) and generate inferences and/or predictions with data of the knowledge graph **2602** responsive to being triggered. The resulting inferences and/or predictions can be ingested into the knowledge graph **2602**. The inferences and/or predictions can be displayed within the model **2804**.

(251) In some embodiments, the animations of the model **2804** can be based on the inferences and/or predictions of the agents **2524-2526**. In some embodiments, charts or graphs can be included within the model **2804**, e.g., charting or graphing timeseries values of the inferences and/or predictions. For example, if an inference is an inference of a flow rate of a fluid (e.g., water, air, refrigerant, etc.) through a conduit, the speed at which arrows moving through the virtual conduit can be controlled based on the inferred flow rate inferred by an agent. Similarly, if the model **2804** provides a heat map indicating occupancy, e.g., red indicating high occupancy, blue indicating medium occupancy, and green indicating low occupancy, an agent could infer an occupancy level for each space of the building and the color coding for the heat map of the model **2804** could be based on the inference made by the agent.

(252) In some embodiments, the graphical building model **2804** can be a three-dimensional or two-dimensional graphical representation of the building. The graphical building model **2804** can be a building information model (BIM), in some embodiments. The BIM can be generated and viewed based on the knowledge graph **2602**. An example of rendering graph data and/or BIM data in a user interface is described in greater detail in U.S. patent application Ser. No. 17/136,752 filed Dec. 29, 2020, U.S. patent application Ser. No. 17/136,768 filed Dec. 29, 2020, and U.S. patent application Ser. No. 17/136,785 filed Dec. 29, 2020, the entirety of which is incorporated by reference herein.

(253) In some embodiments, the graphical building model **2804** includes one or multiple three-dimensional building elements **2806**. The three-dimensional building elements **2806** can form a building when combined, e.g., can form a building model of a building or a campus model of a campus. The building elements **2806** can include floors of a building, spaces of a building, equipment of a building, etc. Furthermore, each three-dimensional building element **2806** can be linked to certain data inferences **2808**, predictions **2810**, and/or operational data **2812**. The data **2808-2812** can be retrieved from the knowledge graph **2602** for display in an interface via the user device **176**.

(254) Referring now to FIG. 29, an interface **2900** that shows inferences and predictions within a three-dimensional model is shown, according to some embodiments. The interface **2900** provides a view of the graphical building model **2804**. The graphical building model **2804** provides graphical representations of a building, floors of a building, rooms and zones of a building, equipment of the building, etc. The interface **2900** provides a three-dimensional graphical representation of the graphical building model **2804**, e.g., the

graphical building model **2804** may be a three-dimensional model in the example of FIG. **29**.

(255) In FIG. **29**, a user interacts with a graphical element in the interface **2900**, e.g., by clicking on, touching, or otherwise interacting with the AHU graphical element **2902**. The AHU graphical element **2902** includes ducts and is connected to VAV elements, VAV element **2904** and **2906**. Responsive to receiving an interaction with the AHU graphical element, the interface **2900** can display an element **2908** which can include operational data and/or inferred and/or predicted data generated by a digital twin of the AHU and/or the building.

(256) For example, the digital twin could be the knowledge graph **2602** combined with one or more agents, e.g., the CAO AI agent **2524** and/or the EPM AI agent **2526**. The agents can generate inferred and/or predicted information for the AHU based at least in part on operational data stored in the knowledge graph **2602** (e.g., operational data of the AHU).

(257) For example, the CAO AI agent **2524** could be configured to generate a minimum ventilation rate of the AHU, e.g., 29 CFM/occupant. The CAO AI agent **2524** can ingest the minimum ventilation rate into the knowledge graph **2602**, e.g., into a node of the knowledge graph **2602** related by a relationship to a node for the AHU. The client **2802** can provide the minimum ventilation rate to the graphical building model **2804** which can be displayed in the element **2908** of the interface **2900**. Similarly, EPM AI agent **2526** could generate the energy usage prediction for the AHU, e.g., 10 kWh. The energy prediction can be ingested into the knowledge graph **2602** and then provided to a user via the user interface **2900** in the element **2908**.

(258) In some embodiments, a user may provide an input to the interface **2900**, e.g., a command, a manual action, a new data value, etc. The input can cause the digital twin to generate new inferences and/or predictions which can be ingested into the knowledge graph **2602** and then displayed in the interface **2900**. In some embodiments, the input is a new occupancy value input via the element **2908**. The new occupancy value can be ingested into the knowledge graph **2602** into a node related to a node for the AHU. The CAO AI agent **2524** can trigger (e.g., if it includes a trigger rule to execute based on a change in occupancy).

(259) The CAO AI agent **2524** can re-compute the minimum ventilation rate based on the new occupancy value for clean air and can store the updated value in the knowledge graph **2602**, thus updating the value displayed in the element **2908**. Similarly, the energy usage displayed in the element **2908** could be reproduced by the EPM AI agent **2526**.

(260) Referring generally to the FIGS. **30-31**, systems and methods for displaying information derived by an AI agent in building models is shown, according to various exemplary embodiments. In some embodiments, the building models may be a two-dimensional or three-dimensional graphical representation of the building. In some embodiments, the building model can be a graphic representation of the building **3000** and/or a particular floor of the building **3000**, e.g., floor **3100**. In some embodiments, the building **3000**, the floor **3100**, and/or any of the other building or floor shown in FIGS. **32-33** can be rendered within a user interface and displayed on a display device of the user device **176**. The various three-dimensional buildings and/or floors shown in FIGS. **31-44** can be the same as or similar to the graphical building model **2804** and/or any of the other graphic building models shown and described herein. The various graphical building models can all be displayed in a display device of the user device **176** and a user can interact with the building model viewing information of the graphical building models and/or navigating through various spaces and/or views of the graphical building model.

(261) In some embodiments, past information and/or future predictions can be ingested into the knowledge graph **2602** (e.g., into a digital twin or twins). In this regard, past, present, and/or future information can be displayed and/or visualized within a graphical building model. Furthermore, the client **2802** can, in some embodiments, provide a recorder and/or playback element (e.g., a widget) that allows a user to view past, present, and/or future states and values of the building within the graphical representation of the building.

(262) In some embodiments, actionable insights can be included within the graphical representation of the building. These actionable insights can aid a user in reviewing and understanding what issues may be affecting the building and what actions could be taken to resolve the issues. In some embodiments, the actionable insights can be acted on (e.g., approved and/or disapproved). The graphical representation of the building can further display the status of the actionable insights and/or results of implementing the actionable insights, e.g., if the actions resolved the issues.

(263) In some embodiments, the graphical representation of the building can include indications of alerts. Furthermore, the graphical representation of the building can indicate virtual zones for occupancy and/or

monitoring of a group of individuals for a particular metric. In some embodiments, an integration can exist (e.g., the client **2802**) that can integrate any AI service output into the graphic representation of the building. The client **2802** may abstract the integration and store a template/configuration for integrating information of the knowledge graph **2602** into the graphic representation of the building.

(264) In some embodiments, the user interface can display entity data for various spaces, assets, solutions, people, etc. The entity data can be data collected and ingested into a digital twin and/or inferred, derived, and/or predicted information generated by an agent running against the digital twin. The data could be live telemetry flowing from various entities and attributes of the entities stored in the digital twin. In some embodiments, the entity data can be a predicted telemetry stored as an event stream with future timestamps for a space, asset, person, etc. in the digital twin. In some embodiments, the entity data can be actionable insight and/or recommendations with future timestamps for spaces, assets, people, etc. In some embodiments, the entity data can include actionable insights for present and/or future times for spaces, assets, and/or people of a digital twin. The actionable insights can have present timestamps and/or future timestamps. The entity data can further indicate an actionable insight status view indicating status of a space, asset, and/or solution after a particular recommendation is accepted. The status could indicate submitted, confirmed, applied, etc.

(265) In some embodiments, information for addressing an infectious disease (e.g., COVID-19, influenza, smallpox, etc.) can be displayed within the graphic representation of the building. The information could be performance information, actionable information, indoor air quality, reproductive number, energy consumption, etc. The information can further indicate diagnosis information and/or actionable insights derived by an AI service for resolving an issue (fault, poor performance, etc.) for a space, piece of equipment, or user.

(266) The graphic representation of the building **3000** can represent a building with settings, rooms, cabins rooms, AHUs, VAVs, ACs, etc. The graphical representation of the building **3000** can include the floor **3100**. The building **3000** and/or the floor **3100** can be updated with information based on time-series data (e.g., zone temperatures, supply fan outputs, maximum supply air flows, etc.) received from a building management system managing and/or operating the rooms, AHUs, VAVs, ACs, etc. The timeseries data can be ingested into a digital twin of the building. An agent can operate against the digital twin to derive predictions or inferences, and display information within the graphical representation of the building **3000** based on the derived predictions or inferences.

(267) Referring now to FIG. **32**, a system **3200** ingesting data of the knowledge graph **2602** into the floor **3100** is shown, according to an exemplary embodiment. The client **2802** can be configured to query the knowledge graph **2602** for inferences, predictions, current data values, historical values, etc. The queries can be made for the various entities (e.g., equipment, spaces, people, points, etc.) being viewed on the floor **3100** by a user via the user device **176**. The data formatter **3202** can format the data queried from the knowledge graph **2602** into a format that can be displayed in the graphical floor **3100**. In some embodiments, the data needs to be translated from a JSON format to a BIM format. The data formatter **3202** can further generate graphics and configure the display of the graphics on the floor **3100** based on the values queried from the knowledge graph **2602**. The formatter **3202** can set color, flow animations, historical trends, shapes, sizes, etc. of various data elements. In some embodiments, a digital twin provided by the knowledge graph **2602** and/or agents that run against the knowledge graph **2602** can drive the three-dimensional visualization of the floor **3100**. The digital twin can provide inferences recommendations and/or predictions for visual representation within the floor **3100**.

(268) Referring now to FIG. **33**, a floor **3300** of a building including indicators for a clean air score and a reproductive number is shown, according to an exemplary embodiment. In some embodiments, the clean air score can be a score generated by an AI agent for various spaces of a building based on air quality measurements made for the various spaces of the building and/or operating settings of equipment of the various areas of the building. The clean air score can be generated by the AI agent based on telemetry stored in the knowledge graph **2602** for the various spaces of the building. In other embodiments, the clean air score may be generated using artificial intelligence executed by algorithms and/or software within the building data platform **100** (e.g., executed by an AI layer of the building data platform **100**). The clean air scores generated by the AI agent can be ingested by the AI agent into the knowledge graph **2602**. In some embodiments, the floor **330** displays a disease risk score that indicates a risk level of a disease spreading through a population. In some embodiments, a disease risk score can be determined with a Wells-Riley

equation. Examples of the Wells-Riley equation and determining the disease risk score can be found in U.S. patent application Ser. No. 17/476,351 filed Sep. 15, 2021. The disease risk score can, in some embodiments, be the reproductive number. The various determinations or display of a reproductive number can, in some embodiments, be replaced with a disease risk score.

(269) Similarly, in some embodiments, the reproductive number can be a value generated by an AI agent for various spaces of a building based on measurements made for the various spaces of the building and/or operating settings of equipment of the various areas of the building. In other embodiments, the reproductive number may be generated using artificial intelligence executed by algorithms and/or software within the building data platform **100** (e.g., executed by an AI layer of the building data platform **100**). The reproductive number may be the expected number of cases directly generated by one case in a population where all individuals are susceptible to infection. The reproductive number can be generated by the AI agent based on telemetry stored in the knowledge graph **2602** for the various spaces of the building. The clean air scores generated by the AI agent can be ingested by the AI agent into the knowledge graph **2602**. The client **2802** and/or data formatter **3202** can read out the clean air score and/or reproductive number for the various spaces of the building and display indications of the clean air scores and/or reproductive numbers in the various spaces of the building within the floor **3300**.

(270) Referring now to FIG. **34**, a table **3400** of information for ingesting the clean air score and the reproductive number into the floor **3300** of FIG. **33** is shown, according to an exemplary embodiment. The table can be stored by the client **2802** and/or the data formatter **3202**, in some embodiments. The table **3400** can provide a display name for displaying information within the floor **3300**. The table **3400** can further indicate a variable name stored within a digital twin, e.g., within the knowledge graph **2602**.

Furthermore, the table **3400** can include a color coding rule that compares the clean air score and/or the reproductive number to various ranges to determine whether a certain color indicator should be displayed within the floor **3300** along with the particular value of the clean air score and/or reproductive number. In some embodiments, each clean air score and/or reproductive number is displayed in the floor **3300** for a particular AHU zone. In some embodiments, tags such as minimum energy, equal priority, and maximum disinfection can be displayed in the floor **3300**.

(271) Referring now to FIG. **35**, a floor **3500** of a building including animated arrows indicating air flow is shown, according to an exemplary embodiment. In the floor **3500**, arrows representing airflow through a building can be animated moving in a particular path. This can represent the airflow through the building. In some embodiments, the speed and/or color of the arrows can be based on an air delivery rate in the building. The arrows can animate on pipes or ducts of the building, in some embodiments.

(272) Referring now to FIG. **36**, a table **3600** of information for ingesting a clean air delivery rate into the floor **3500** is shown, according to an exemplary embodiment. The clean air delivery rate for every AHU zone of the building **3600** (e.g., each area served by a particular AHU) can be stored within a digital twin, e.g., the knowledge graph **2602**. The client **2802** and/or **3202** can store the table **3600**, in some embodiments, and use the table **3600** to retrieve the clean air delivery rate from the knowledge graph **2602** and/or animate the arrows within the floor **3500** based on the retrieved clean air delivery rates. The table indicates a name of the parameter, a variable name stored in a twin, and an arrow animation rule. The speed at which the arrows move in the floor **3500** can be based on the rate value. Furthermore, the color of the arrows can be set to a particular color, e.g., blue.

(273) Referring now to FIG. **37**, a floor **3700** of a building including indications of clean air score alarms and reproductive number alarms is shown, according to an exemplary embodiment. In some cases, if the clean air score goes too low for a space (e.g., the clean air score goes below a threshold), or the reproduction number goes too high for a space (e.g., the reproduction number goes above a threshold), an alarm can be generated and/or displayed within the floor **3700**. The alarm can be generated based on an agent reviewing clean air scores and/or reproduction numbers of spaces stored in the knowledge graph **2602**. In some embodiments, the alarms can be generated by the client **2802** and/or the data formatter **3202** reviewing clean air scores and/or reproduction numbers received from the knowledge graph **2602**.

(274) Referring now to FIG. **38**, a table **3800** of information for ingesting the clean air score and the reproductive number into the floor **3700** and generating alarms based on the clean air score and the reproductive number for display within the floor of the building **3700** is shown, according to an exemplary embodiment. The table **3800** can be stored by the client **2802** and/or the data formatter **3202** and used to read information from the graph **2602** and/or render alarms within the floor **3700**, in some embodiments.

The table **3800** can indicate display name, variable name inside the digital twin, and a condition for whether an alarm should be triggered. A clean air alarm can be triggered if the clean air score is less than thirty. A reproductive number alarm can be raised if the reproductive number is greater than three.

(275) Referring now to FIG. **39**, is a block diagram **3900** of a facility manager **3902** interacting with a low clean air score displayed in a floor **3904** of a building and viewing diagnostic and action information is shown, according to an exemplary embodiment. The facility manager **3902** may be an individual that manages a building and/or floor. The facility manager **3902** can view the floor **3904** on a display device of the user device **176**. In some embodiments, the facility manager **3902** can interact with an element displayed in the floor **3904**, a low clean air score, via the user device **176**.

(276) Responsive to interacting with the low clean air score, the client **2802** can provide diagnostic information at **3906** and/or provide action information at **3912**. The diagnostic information and/or the action information can be information identified by an agent and ingested into the knowledge graph **2602**. The client **2802** can read the diagnostic information and/or action information out of the knowledge graph **2602** and display the information in the floor **3904** or in a user interface element on the above, below, or on the side of the floor **3904** within a user interface. The diagnostic information can provide a reason for the clean air score, e.g., an indication **3908** that the ventilation rate is too low or an indication **3910** that a filter is not in use. The action information can include an indication **3914** that a supply air temperature setpoint could be adjusted (e.g., to a particular value), an indication **3916** that a minimum ventilation rate could be adjusted (e.g., to a particular value), and/or an indication **3918** that a particular filter could be added to an AHU to improve the clean air score. A user can interact with the provided action information to cause the settings to automatically update and/or a work order to be generated to replace the filter.

(277) Referring now to FIG. **40**, a block diagram **4000** of an occupant **4002** interacting with a high reproductive number displayed in a floor **4004** of a building and viewing diagnostic and action information is shown, according to an exemplary embodiment. The occupant **4002** may be an individual that occupies a building and/or floor of the building. The occupant **4002** can view the floor **4004** on a display device of the user device **176**. In some embodiments, the occupant **4002** can interact with an element displayed in the floor **4004**, a high reproductive number, via the user device **176**.

(278) Responsive to interacting with the high reproductive number, the client **2802** can provide diagnostic information at **4006** and/or provide action information at **4012**. The diagnostic information and/or the action information can be information identified by an agent and ingested into the knowledge graph **2602**. The client **2802** can read the diagnostic information and/or action information out of the knowledge graph **2602** and display the information in the floor **4004** or in a user interface element on the above, below, or on the side of the floor **4004** within a user interface. The diagnostic information can provide a reason for the high reproductive number, e.g., an indication **4008** that the ventilation rate is too low or an indication **4010** that an occupant density level is too high. The action information can include an indication **4014** to stay at home and work remotely, an indication **4016** to wear a mask, and/or an indication **4018** to maintain social distancing.

(279) Referring now to FIG. **41**, a table **4100** indicating information that could be displayed within a graphical representation of the building is shown, according to an exemplary embodiment. For example, if a user interacts with the high reproductive number of the floor **4004**, the table **4100** could be displayed to illustrate the occupant density by AHU zone. In some cases, the table **4100** could further display minimum ventilation rate for each AHU, supply air temperature setpoint for each AHU, a duct filter recommendation (e.g., MERV13) for each AHU, etc.

(280) Referring now to FIG. **42**, an element **4202** for viewing future predictions of information in a floor **4200** of a building is shown, according to an exemplary embodiment. The elements **4200** and **4202** can be combined within a single user interface and/or displayed on a display device of the user device **176**, in some embodiments. The element **4202** can be a slider that allows a user to select past, present, and/or future times. In some embodiments, the element **4202** could be a drop down that provides past, present, or future times that can be selected directly, e.g., 8:00 AM, 9:00 AM, 10:00 AM, etc. The client **2802** can query the knowledge graph **2602** for information (e.g., data with a timestamp as selected in the element **4202**) and display the information within the element **4200**. The information displayed in the element **4200** can be alerts, data values, animations, trends, etc. In some embodiments a user can select times in a one hour interval.

(281) In some embodiments, the element **4202** allows a user to view “what if” scenarios by moving back

and forth in time and testing various settings and configurations for equipment of the building and/or the building. In some embodiments, for various settings and/or configurations provided by a user, an agent can infer future states for various future times. The user can provide various settings and view the varying results for each set of settings or configuration.

(282) In some embodiments, via the element **4200** various recommended action can be displayed to resolve a future predicted issue (e.g., fault, poor air quality, high reproduction rate, etc.). A user can set, via the element **4200**, approval to automatically generate a ticket for maintenance, update operating settings of equipment, etc. The element **4200** can allow a user to approve a trigger to automatically perform an action if a scenario simulated and displayed in the element **4200** does in fact occur.

(283) Referring now to FIG. **43**, an element **4300** and an element **4302** for viewing an occupancy score and a clean air score in a floor of a building are shown, according to an exemplary embodiment. The elements **4300** and **4302** can be combined within a single user interface and/or displayed on a display device of the user device **176**, in some embodiments. The element **4300** can be a graphical representation of a floor of a building that displays an occupancy level and a clean air score for a space of the building. The space can be highlighted by a particular color, e.g., green, blue, or red, based on the occupancy level and/or clean air score.

(284) The element **4300** can allow a user to view states of the building at a current time, one or more days into the future, and/or one or more days into the past. The element **4303** can be a slider allowing a user to flip through the states of the building at historical, current, or future times. The elements **4300** and **4302** can provide a “Building Player” allowing a user to “play” the building view the past statuses of the building (e.g., stored in a timeseries database and/or a digital twin), present statuses of the building, and/or future statuses of the building (e.g., simulated and/or inference/predictions generated by a digital twin). The predicted future statuses can be generated by an agent based on past and/or current data for the building, in some embodiments.

(285) Referring now to FIG. **44**, an element **4400** and an element **4402** for viewing a predicted occupancy score and a predicted clean air score for a future time in a graphical representation of a floor of a building is shown, according to an exemplary embodiment. The elements **4400** and **4402** may be the same as or similar to the elements **4300** and **4302** shown in FIG. **43**. However, the elements **4400** and **4402** can display a status of the building four days into the future as compared to the building illustrated in FIG. **43**. Various AHU digital twins can run to make predictions for occupancy and/or air quality four days into the future and cause the predictions to be displayed in the element **4400**.

(286) In some embodiments, the occupancy is predicted from schedules and/or calendars and/or predicted from historical occupancy trends. In some embodiments, the predicted occupancy could be fed into a clean air optimization model to predict the air quality. In some embodiments, the element **4400** can display actions for avoiding the future poor air quality scenario. The user can provide approval to perform the action and/or allow an agent to automatically operate to avoid the poor air scenario. In some cases, the poor air quality scenario may be unavoidable. In such a case, the element **4400** can include an indication that the scenario is unavoidable.

(287) Referring now to FIG. **45**, a flow diagram of a process **4500** for generating and displaying a recommendation for updating a building is shown, according to an exemplary embodiment. In some embodiments, the building data platform **100** can be configured to perform the process **4500**. In some embodiments, the learning service **2206** can be configured to perform the process **4500**. Any computing device or system described herein can be configured to perform the process **4500**.

(288) In step **4502**, the building data platform **100** stores a digital twin of a building in a data structure. The digital twin can include a virtual representation of one or more entities of the building, one or more data points, and the interrelationships between the one or more entities and one or more data points. The data structure can be a building graph (e.g., the graph **529**) as described in FIGS. **2-5**. For example, as shown in FIG. **5**, the one or more building entities may include a building zone, a building floor, an AHU of the building, and a VAV of the building. The one or more data points may include the data stored timeseries node **564** and timeseries node **566**. The building data platform **100** may store the building entities, the data points, and their interrelationship connections in twin manager **108**. The entities can be represented as nodes of a building graph. The interrelationships between the entities can be edges between the nodes. In some embodiments, the building data platform **100** may ingest outdoor air quality forecast data into the digital twin. Based on the outdoor air quality forecast data, the building data platform **100**

may be able to predict air quality and advise building occupants on their outdoor activities. Additionally, the building data platform **100** may control one or more building operations based on the air quality forecast data. For example, the building data platform **100** may pre-purge the building with fresh air when poor air quality is forecasted.

(289) In step **4504**, the building data platform **100** generates one or more inference values based on a data point of the one or more data points for one or more future times through an artificial intelligence of the digital twin. More specifically, the building data platform **100** may generate the one or more inference values by retrieving the inferred or predicted information stored in the graph **529** and generating one or more inference values based on the inferred or predicted information. As described above, the inferred or predicted information can be made based on the model **576**. In some embodiments, the model **576** may be stored in the digital twin as an attribute of the digital twin. For example, the model **576** can be a clean air model for predicting the air quality of a space, zone, and/or building or an occupancy model for predicting occupancy of a space, zone, and/or building. In some embodiments, an inference value may be in the form a score or number that describes a quality of a building entity. For example, an inference value may be an inferred or predicted air quality score ranging from 0-100 where a score between 0-60 may be a “poor” score, a score between 61-80 may be an “average” score, and a score between 81-100 may be a “good” score. As another example, an inference value may be an inferred and predicted reproductive number which describes the expected number of infection cases directly generated by one infection case in a population where all individuals are susceptible to infection. In some embodiments, a reproductive number of less than one may be considered “good”, a reproductive number between 1-2 may be considered “average”, and a reproductive number greater than 2 may be considered “poor.” The inference values can be inferred data values for a present time, e.g., a current clean air score or a current reproductive number. In some embodiments, the inference values are predicted values, e.g., a clean air score an hour into the future, a reproductive number an hour into the future, etc. The predicted values can be predicted by the model **576** based on current operating data of building equipment of the building, an operating schedule of the building equipment, current measured environmental conditions of the building measured by the building equipment, weather forecasts, current outdoor air conditions, etc.

(290) In step **4506**, the building data platform **100** generates a recommendation to make one or more updates to the building based on the one or more inference values as determined in step **4504**. For example, if the building data platform **100** determines an inference value that is “poor” (e.g., a building performance is less than a threshold, an energy consumption is greater than a threshold, a probability of infection for occupants of a building of an infectious disease is greater than a threshold, etc.), the building data platform **100** may determine one or more actions to improve this inference value and/or improve the functioning of the building. For example, if the building platform **100** determines a predicted clean air score of 50, the building platform **100** may determine certain actions (e.g., increase the ventilation rate, adjust the temperature setpoint, increase filtration, generate a maintenance request to replace an old filter and/or install a new filter, etc.) that can increase the predicted clean air score. Once the building data platform **100** has determined the action that may be implemented, the building data platform **100** may generate a recommendation to make one or more updates to the building based on the determined actions. In some implementations, the recommendation includes a recommendation to update operating settings of building equipment of the building, the operating settings updating operation of the building equipment by interacting with the digital twin of that building equipment or through an API or other integration with the building equipment or the building management system through which instructions can be sent to said equipment. In some embodiments, the recommendation may be implemented automatically by the building data platform **100**. In other embodiments, the recommendation may be implemented manually by a building technician.

(291) In step **4508**, the building data platform **100** displays the recommendation determined in step **4506** at a location within a graphical representation of the building. For example, the recommendation may be displayed at a location within the graphical representation of the building **3000** or within the floor **3100** of the graphical representation of the building **3000**. The recommendation may be displayed on a display device of the user device **176**. In some embodiments, a user may be able to interact with the user device **176** to implement the recommendations displayed on the user device. For example, if one of the recommendations is to increase the ventilation rate within a building, the user may be able to implement that action directly on the user device. In some embodiments, the building data platform **100** stores the

recommendation, or a link to the recommendation, in a node of a building graph. The node storing or linking the recommendation can be linked to a node representing a space (e.g., a floor, a room, a zone, etc.) of the building via an edge. Responsive to receiving a request to display the space in a user interface (e.g., a user navigating to the space), the building data platform **100** can query the graph for data of the space and identify the recommendation stored in the node based on the edge between the node storing or linking the recommendation and the node representing the space. The building data platform **100** can cause the recommendation to be displayed responsive to identifying the recommendation stored in the node.

(292) Referring now to FIG. **46**, a flow diagram of a process **4600** for generating and displaying a virtual indicator of an entity of a building based on telemetry data is shown, according to an exemplary embodiment. In some embodiments, the building data platform **100** can be configured to perform the process **4600**. In some embodiments, the learning service **2206** can be configured to perform the process **4600**. Any computing device or system described herein can be configured to perform the process **4600**.

(293) In step **4602**, the building data platform **100** stores a digital twin of a building in a data structure. The digital twin can include a virtual representation of one or more entities of the building, one or more data points, and the interrelationships between the one or more entities and one or more data points. The data structure can be a building graph (e.g., the graph **529**) as described in FIGS. **2-5**. For example, as shown in FIG. **5**, the one or more building entities may include a building zone, a building floor, an AHU of the building, and a VAV of the building. The one or more data points may include the data stored timeseries node **564** and timeseries node **566**. The building data platform **100** may store the building entities, the data points, and their interrelationship connections in twin manager **108**.

(294) In step **4604**, the building data platform **100** receives telemetry data for one or more pieces of equipment of the building for the one or more data points within the digital twin. More specifically, the telemetry component **560** can receive telemetry data from physical devices such as the building subsystems **122**. The telemetry can be measured data values, a log of historical equipment commands, etc. The telemetry component **560** can store the received information, or a link to the received information, in the graph **529** by relating a node storing or linking to the information to a node representing the physical device. In some embodiments, the telemetry component **560** can store timeseries data as the timeseries **566**.

(295) In step **4606**, the building data platform **100** generates a virtual indicator of an entity of the building from the telemetry data. The virtual indicator may be related by the digital twin to an entity of the one or more entities of the building. For example, a virtual indicator may be a temperature virtual indicator for a room or zone of the building by a thermostat digital twin or a temperature sensor digital twin. A virtual indicator may be described as virtual value that describes one or more states of a building entity. In some implementations, the virtual may be a non-measured characteristic of the building. As another example, the virtual indicator can be a reproductive number that describes the expected number of cases caused by a case in a population where all individuals are susceptible to infection. As another example, the virtual indicator can be an energy consumption associated with a building. As another example, the virtual indicator can be an air quality description associated with a building, building room, building space, or building zone. The virtual indicator is “virtual” because it can be derived from telemetry data or because the indicator may be created and stored remotely from the building associated with the building data platform **100**. For example, the building data platform **100** can store the virtual indicator in a building graph (e.g., graph **529**). For example, an agent or AI service (e.g., the AI agent **570**, the agent **2524** or the CAO AI service **2604**) in a virtual indicator node related to a space node via an edge of the building graph. The edge can connect the node to the space node. This relationship formed by the edge can indicate that the virtual indicator node stores or links to a virtual indicator for the space.

(296) In step **4608**, the building data platform **100** displays the virtual indicator determined in step **4606** at a location within a graphic representation of the building (e.g., the graphical building model **2804**, the floor **3300**, the floor **3700**, etc.) based on a request received from a user via the user device **176** that they would like to view the virtual indicator. For example, the user may interact with a user device to click, select, pan, highlight, etc. a portion of a building on a user interface to indicate that they would like to view a virtual indicator. Once the building data platform **100** receives the user indication as a request to display a virtual indicator, the building data platform **100** can display the virtual indicator at a location within a graphic representation of the building. More specifically, the building data platform **100** queries the digital twin to find an entity (e.g., a building floor, room, space, person, piece of equipment, etc.). The

entity may be related to a data object that stores a list of attributes related to the data entity (e.g., name, location, description, etc.). More specifically, a building model may include a set of names for entities and spaces associated with the building. The building data platform **100** queries and finds the entity node for the entity, and determines the location edge from the entity node to another node representing space within the building. Finally, the building data platform **100** compares the queried location name to the set of names to identify the specific building model object that represents that space and where to display the virtual indicator. If the virtual indicator is related to a particular room, zone, or part of a building, the virtual indicator may be displayed at or near that particular location. For example, the temperature virtual indicator **3102** related to conference room **3104** may be displayed in the graphical representation of the building. The virtual indicator may be displayed on a display device of the user device **176**.

(297) Referring now to FIG. **47**, a flow diagram of a process **4700** for generating and displaying a recommendation for reducing the spread of an infection disease within a building is shown, according to an exemplary embodiment. In some embodiments, the building data platform **100** can be configured to perform the process **4700** c. In some embodiments, the learning service **2206** can be configured to perform the process **4700**. Any computing device or system described herein can be configured to perform the process **4700**.

(298) In step **4702**, the building data platform **100** stores a digital twin of a building in a data structure. The digital twin can include a virtual representation of one or more entities of the building, one or more data points, and the interrelationships between the one or more entities and one or more data points. The data structure can be a building graph (e.g., the graph **529**) as described in FIGS. **2-5**. For example, as shown in FIG. **5**, the one or more building entities may include a building zone, a building floor, an AHU of the building, and a VAV of the building. The one or more data points may include the data stored timeseries node **564** and timeseries node **566**. The building data platform **100** may store the building entities, the data points, and their interrelationship connections in twin manager **108**. The entities can be represented as nodes of a building graph. The interrelationships between the entities can be edges between the nodes.

(299) In step **4704**, the building data platform **100** receives building data for an entity of the one or more entities of the building. In some embodiments, the entity may be a component associated with the building such as a piece of building equipment, a building device, a user, and/or a building space (e.g., a zone, a conference room, an office). In some embodiments, the building data platform **100** can receive this data from one or more building devices relating to the entities of the building. For example, the building data platform **100** can receive the number of occupants in a building and/or building space, the airflow of the building, the air changes for a building, the amount of infected individuals in a building, and the air quality of a building (e.g., temperature of the air, humidity of the air). This data may be used to determine a reproductive number for the building. In other embodiments, the building data platform may retrieve this data from the graph **529** or the knowledge graph **2602**.

(300) In step **4706**, the building data platform **100** generates an infectious disease indicator based on the building data. For example, the building data may include telemetry data and/or operating settings of equipment of the various areas of the building. In some embodiments, the infectious disease indicator may be generated by an AI agent for various spaces of a building based on the data received in step **4704**. More specifically, the building data platform **100** may use the model **576** to generate an infectious disease indicator. The model **576** is described in more detail above with respect to FIG. **5**. In some embodiments, the infectious disease indicator may be a reproductive number.

(301) In step **4708**, the building data platform **100** generates a recommendation for reducing a spread of an infectious disease within the building based on the infectious disease indicator determined at step **4706**. In some embodiments, the infectious disease indicator is a reproductive number, the building data platform **100** may determine that the reproductive number is “poor” (e.g., higher than 2) and may determine one or more actions for reducing the spread of an infectious disease and decreasing the reproductive number. For example, if the building data platform **100** determines a reproductive number of 4, the building data platform **100** may determine certain actions (e.g., implementing mask wearing policies, implementing social distance policies, implementing remote work policies, etc.) that may be implemented within the building to decrease the reproductive number. Once the building data platform **100** has determined the action that may be implemented, the building data platform **100** may generate a recommendation to make

one or more updates to the building based on the determined actions. The determined actions included in the recommendation may be changed based on the reproductive number. For example, if the reproductive number is lower (e.g., 1-2), then the recommendation may only include implementing a mask policy throughout the building. On the other hand, if the reproductive number is higher (e.g., 3-4), the recommendation may include implementing a mask policy, implementing a social distancing policy, and/or implementing a remote work policy.

(302) As another example, if the building data platform **100** determines a reproductive number of that is poor (e.g., higher than a certain threshold such as 2), the building data platform **100** can operate one or more building devices to change the indoor environmental quality to reduce the reproductive number and control the spread of a disease within a building. For example, the building data platform **100** may control the building subsystems **122** to increase air filtration within the building, activate or increase air treatment operations within the building, increase indoor air ventilation within the building, activate or increase the indoor water treatment within the building, change the temperature in the building, change the humidity in the building, and/or activate disinfectant lighting within the building. The building subsystem **122** can operate to improve the indoor air quality, reduce the reproductive number, and prevent the spread of an infectious disease by performing one or more of the techniques discussed in U.S. application Ser. No. 17/013,273 filed on Sep. 4, 2020 (published as U.S. Publication No. 2021/0356153 on Nov. 18, 2021), the entirety of which is incorporated by reference herein.

(303) In step **4710**, the building data platform **100** displays the recommendation determined in step **4708** at a location within a graphic representation of the building based on a request received from a user that they would like to view the recommendation. In some embodiments, a user via the user device **176** may interact with a user device to click, select, pan, highlight, etc. a portion of a building on a user interface to indicate which they would like to view a recommendation for. For example, if a certain space of the building has a high reproductive number (e.g., above 2, 3, or 4), the user, via the user device **176**, can select that portion or space of the building to receive a recommendation to lower the reproductive number. Once the building data platform **100** receives the user indication as a request to display a virtual indicator, the building data platform **100** displays the recommendation at a location within a graphic representation of the building. If the infectious disease indicator is related to a particular room, zone, or part of a building, the virtual indicator may be displayed at or near that particular location.

(304) Referring now to FIG. **48**, a flow diagram of a process **4800** for predicting whether a building occupant has been infected with an infectious disease is shown, according to an exemplary embodiment. In some embodiments, the building data platform **100** can be configured to perform the process **4800**. In some embodiments, the learning service **2206** can be configured to perform the process **4800**. Any computing device or system described herein can be configured to perform the process **4800**.

(305) In step **4802**, the building data platform **100** stores a digital twin of a building in a data structure. The digital twin can include a virtual representation of one or more entities of the building, one or more data points, and the interrelationships between the one or more entities and one or more data points. The data structure can be a building graph (e.g., the graph **529**) as described in FIGS. **2-5**. For example, as shown in FIG. **5**, the one or more building entities may include a building zone, a building floor, an AHU of the building, and a VAV of the building. The one or more data points may include the data stored timeseries node **564** and timeseries node **566**. The building data platform **100** may store the building entities, the data points, and their interrelationship connections in twin manager **108**. In some embodiments, the digital twin may include an analytical and/or artificial intelligence model/algorithm that simulates an airflow through the building and predicts whether one or more occupants are potentially infected with an infectious disease based on the artificial intelligence. The artificial intelligence can be the AI agent **570**. The AI agent **570** can execute against the graph **529** to simulate airflow. The AI agent **570** can analyze the edges between nodes representing AHUs, VAVs, zones, floors, etc. and the operating data (e.g., fan speeds of the AHUs, damper positions of the AHUs, etc.) to predict how air is flowing through the building. Furthermore, based on locations of occupants (which may be represented in the graph **529**) the AI agent **570** can be configured to determine whether the airflow is carrying particles (potentially disease particles) from a location where an infected occupant is to a location where another occupant is located. The entities can be represented as nodes of a building graph. The interrelationships between the entities can be edges between the nodes.

(306) In step **4804**, the building data platform **100** receives building data for the building from one or more

pieces of equipment of the building. The building data received in step **4804** may include air flow and air quality metrics, occupancy rates within one or more zones or areas of the building, identification of occupants within the building, and the temperature of one or more occupants within the building. This data may be collected by one or more pieces of equipment of the building including thermal imaging systems, one or more sensors structured to determine the air flow and air quality metrics (e.g., air temperature sensors, humidity sensor, indoor air quality sensors, etc.), and occupancy sensors. Additionally, the building data may also be collected through one or more sensors configured to determine the environmental quality of the building. The environmental quality of the building may describe conditions that may or may not facilitate the growth of infectious diseases and viruses. For example, these conditions may include the temperature of the building, air flow of the building, air quality of the building, and/or water temperature within the building. The building data received in step **4804** may be used as an input to the artificial intelligence (e.g., the AI agent **570**) within the digital twin to predict whether one or more occupants are potentially infected with an infectious disease.

(307) In some embodiments, the building data may be collected through one or more biological sensors. A biological sensor may be configured to monitor air quality or water quality to determine the presence of an infectious disease within a building. In some embodiments, the biological sensors may include pathogen detectors. In some embodiments, the pathogen detectors may be airborne and/or sewage-based pathogen detectors. More specifically, in some embodiments, one or more biological sensors can be placed in or near an air handling unit (AHU). The biological sensors may evaluate the air in or near the air handling unit to determine if the air contains any infectious diseases. The building data platform **100** can receive an input from the biological sensor indicating the presence of a particular biological agent such as an infectious disease. Biological sensors are described in more detail in U.S. Patent Application No. 63/252,050 filed Oct. 4, 2021, the entirety of which is incorporated by reference herein.

(308) In some embodiments, one or more airborne pathogen detectors may be used to sense the presence of one or more types of pathogens in the air, and/or one or more sewage pathogen detectors may be used to sense the presence of one or more pathogens in sewage. It should be understood that these are merely two examples of different types of pathogen detectors, and the present disclosure contemplates the use of any of a variety of different types of pathogen detectors in combination (e.g., airborne detectors, sewage detectors, water detectors configured to sense the presence of pathogens in water, surface detectors configured to sense the presence of pathogens on surfaces, patient sampling detectors configured to sense the presence of pathogens from samples taken from occupants/patients, etc.). For example, in some implementations, an airborne pathogen detector may be used to detect the presence of a pathogen in sewage (e.g., by placing the detector in or near the sewage, i.e., sensing the pathogen in the sewage or in the air proximate to the sewage). In some implementations, a sewage pathogen detector could be used to sense the presence of a pathogen in the sewage, and in response to detecting the presence of the pathogen, data from one or more airborne pathogen detectors could be obtained and/or analyzed to determine locations and/or severity of spread of the pathogen in a building. In some implementations, the airborne pathogen detectors could be activated responsive to detection of the presence of the pathogen by the sewage pathogen detectors. In some implementations, the sewage pathogen detectors and/or airborne pathogen detectors could obtain samples to be processed off-premises, and in some implementations, the sewage pathogen detectors and/or airborne pathogen detectors could process samples on-premises (e.g., at the location of the detectors or at a separate location within the building). Pathogen detectors are described in more detail in U.S. Patent Application No. 63/330,732 filed Apr. 13, 2022, the entirety of which is incorporated by reference herein.

(309) In step **4806**, the building data platform **100** determines the location of one or more occupants of the building within the building. The building data platform **100** may determine the location of one or more occupants of the building from the building data received by the building data platform **100** in step **4804**. As mentioned above, the building data may include occupancy data received from one or more occupancy sensors of the building. The occupancy sensors may include passive infrared sensors, ultrasonic sensors, infrared time-of-flight (ToF) sensors, infrared array sensors, ultrasonic sensors, microwave sensors, and occupant recognition cameras. One or more of the occupancy sensors may be able to determine the location of one or more occupants within the building.

(310) In step **4808**, the building data platform **100** receives an indication that the occupant is infected with an infectious disease. The indication that the occupant is infected with an infectious disease may be based

on the building data received in step **4804**. In some embodiments, the indication that the occupant is infected with an infectious disease may be based on a temperature measurement of the occupant. The temperature of the occupant may be determined by a thermal imaging system within the building or a temperature sensor within the building. In some embodiments, the indication that the occupant is infected with an infectious disease may be based on testing done either remotely or onsite within the building. For example, if a building implements periodic onsite testing for an infectious disease of each of the occupants, the results of the onsite testing may be used as an indication on whether the occupant is or is not infected with an infectious disease. In some embodiments, the onsite testing can be automatically performed in a building, building space, and/or building zone by one or more biological sensors within the building. The biological sensor may evaluate the air in the building to determine a presence of an infectious disease with one or more occupants of the building. The data received from the biological sensor may also be used to determine the reproductive number. In some embodiments, the indication that the occupant is infected with an infectious disease may be based on other data received by the building data platform **100**.

(311) In step **4810**, the building data platform **100** executes an artificial intelligence (e.g., the AI agent **570**) stored in the digital twin to simulate the air flow through the building based on the virtual representation of the building with the one or more entities of the building. For example, as shown in FIG. **35**, the building data platform **100** uses the artificial intelligence stored in the digital twin to simulate the air flow through the building as shown by the arrow **3502** in floor **3500**. The building data platform **100** executes the artificial intelligence by causing the client instance **592** to run the model **576** based on the virtual representation of the building with the one or more entities of the building and the interrelationships and the building data to simulate the air flow through the building.

(312) In step **4812**, the building data platform **100** executes the artificial intelligence stored in the digital twin to predict whether the one or more other occupants of the building are potentially infected with the infectious disease based on the airflow, the location of the occupant, and the locations of the one or more other occupants. The building data platform **100** can execute the artificial intelligence by causing the client instance **592** to run model **576** based on the building data received in step **4804**, the location of one or more occupants as determined in step **4806**, and/or an indication that the occupant has been infected with an infectious disease as received in step **4808**. For example, the building data platform **100** may receive building data for floor **3500** and the indication that an occupant on floor **3500** has been infected with an infectious disease, the building data platform **100** may simulate airflow through the building to create a prediction that one or more other occupants in the building who may have come in contact with the occupant infected with an infectious disease may also be potentially infected with an infectious disease. In some embodiments, the prediction can be ingested back into a graph (e.g., knowledge graph **2602**) by an artificial intelligence agent (e.g., AI agent **2524**, AI agent **2526**), etc.). For example, the building data platform **100** may identify a node tied to user (e.g., node **320**) via an edge and store the prediction that the user may be infected in the node tied to the user. In some embodiments, based on the location of the biological sensor detecting the infectious disease, the digital twin could be used to determine the building occupants most at risk and recommend supplemental testing. In some embodiments, if an infectious disease is detected in real-time, the building could operate building components (e.g., dampers, fire doors, etc.) to isolate parts of the building to prevent further infectious disease transmission.

(313) In some embodiments, the prediction determined at step **4812** may be used to control operation of the building and/or building equipment. For example, if an occupant is predicted to be infected with a disease, the building data platform **100** may control one or more building subsystems **122** to increase the ventilation in the portion of the building the user is predicted to occupy. As another example, if an occupant is predicted to be infected with a disease, the building data platform **100** may control one or more building subsystems **122** to increase the disinfectant light in a portion of the building the occupant is occupying. A disinfectant light may be a type of light that when exposed to a surface disinfects the surface. In some embodiments, a disinfectant light may be a classic UVC light (e.g., 254 nanometers) and a far UVC light (e.g., 205 nanometer-230 nanometers). As another example, if an occupant is predicted to be infected with a disease, the building data platform **100** may set a policy for one or more occupants in the building (e.g., requesting the occupant quarantine for a specified period of time, implementing a remote work policy, prompting the occupant to seek medical attention, etc.). In some embodiments, the method

4800 may be implemented within a plurality of buildings which may be part of a campus or community. For example, if a building is in an area where the general prevalence of infectious disease in the area is known (e.g., through waste water or air quality monitoring), the building data platform **100** may determine and display the risk of a first building relative to other buildings within a campus or the community. Furthermore, the building data platform **100** may be controlled to automatically switch into infection control mode when community transmission levels exceed predefined thresholds.

(314) Referring now to FIG. **49**, a flow diagram of a process **4900** for generating and displaying a graphic representation of the building with one or more states based on future data values is shown, according to an exemplary embodiment. In some embodiments, the building data platform **100** may be configured to perform the process **4900**. In some embodiments, the learning service **2206** may be configured to perform the process **4900**. Any computing device or system described herein can be configured to perform the process **4900**.

(315) In step **4902**, the building data platform **100** receives historical data values of one or more data points for one or more historical times. In some embodiments, the historical data values of the one or more data points may be associated with one or more devices, spaces, or systems within a building. For example, the historical data values may be associated with a heating, ventilation, and air conditioning system within a building. As another example, the historical data values may be associated with an occupancy sensor within a building. As a final example, the historical data values may be associated with a building floor or a building room within a building. The building data platform **100** may receive the historical data values from one or more devices or components configured to collect data. For example, the building data platform **100** may receive historical telemetry data values from the building subsystems **122**. The historical data values may include measured data values, a log of historical equipment commands, a log of historical building personnel commands, etc.

(316) In some embodiments, the building data platform **100** may store the historical data received in step **4902** in the twin manager **108**. More specifically, the historical data may be stored in graph **529**. In other embodiments, the historical data may be stored in one or more other memories within the building data platform **100** (e.g., memories **166**, memories **126**, memories **120**, and/or memories **150**).

(317) In step **4904**, the building data platform **100** executes an artificial intelligence agent to generate one or more inference values based on the one or more data points for one or more future times based on the historical data values. In some embodiments, the artificial agent is an agent for a specific entity represented in the graph **529**. For example, the agent could be a building history agent configured to evaluate the historical data of the building **526** and simulate a future data of the building **526** based on the historical data. Another agent could be a floor occupant prediction agent that is configured to predict the occupancy of a particular floor of a building, e.g., the floor represented by the floor node **522**. In some embodiments, the artificial intelligence agent may be coupled to (or included by) a digital twin associated with a specific entity. Furthermore, the building data platform **100** may determine the inference and/or prediction values based on the digital twin associated with the specific entity. For example, the building history agent may be associated with a building digital twin **526**, and the building history agent may determine one or more inference and/or prediction values for the building based on the building digital twin **526**.

(318) The building data platform **100** executes the artificial intelligence agent by causing the client instance **592** to run the model **576** based on the historical data values received at step **4902**. Based on the historical data values, the model **576** generates one or more inference and/or predicted values of the building. In some embodiments, the inference and/or predicted values may be combined to create a predicted future state of the building. For example, the inference and/or predicted values may be a predicted occupancy of a building or a floor, a predicted air quality of a building or floor, and/or a predicted reproductive number. These inferred or predicted values may be used to predict a future state of the building. For example, the building data platform **100** may be able to predict a future state of the building one or more days in the future (e.g., one day, two days, three days, four days, etc.) based on the predicted occupancy, air quality, and/or reproductive number. In some embodiments, the inference and/or predicted values are stored in the digital twin as attributes of the digital twin. In some embodiments, the building data platform **100** is also able to determine a past state of the building based on the historical values received at step **4902**. For example, the building data platform **100** may be able to determine a past state of the building one or more days in the past (e.g., one day, two days, three days, four days, etc.) based

on the historical occupancy, air quality, and/or reproductive number values as determined based on the historical values.

(319) In step **4906**, the building data platform **100** generates a user interface to display a graphic representation of the building based on the inference and/or prediction values determined at step **4904** on a user device. For example, the building data platform **100** may generate user interfaces including element **4300** and element **4400** at step **4906**. In some embodiments, the user interface may be displayed on a user device (e.g., a mobile device, a laptop, a computing device, etc.). The user interface may include one or more selectable elements which provide a selection of one or more historical times and/or future times. The user may be able to interact with the user device to manipulate the selected element to view one or more historical times and/or future times of the building. In some embodiments, the selectable element may be in the form of a sliding bar which the user may manipulate to view future or past states of the building. For example, the element **4300** may include selectable element **4302** which may be moved to the right to view future times of the building. Conversely, the selectable element **4302** may be moved to the left to view historical times of the building. In some embodiments, the selectable element may be a drop-down menu where the user may select which future or historical time of the building they wish to see. In some embodiments, the selectable element may be a text entry box where the user may enter which future or historical time of the building they wish to see. In some embodiments, the selectable element may be included in the user interface in a way not described herein. The building data platform **100** may generate the user interface based on the one or more predicted and/or inference values determined at step **4904**. In some embodiments, the user interface may include one or more space indicator elements that describe the state of a space in a graphical representation. For example, the space indicator element **4306** may highlight the space a certain color to indicate the state of that space. For example, as shown in FIG. **43**, the space indicator element **4306** may be green to indicate a positive state of the building (e.g., clean air score above a certain threshold, occupancy level below a certain threshold, etc.). As another example, as shown in FIG. **44**, the space indicator element **4406** may be red to indicate a predicted negative state of the building (e.g., clean score below a certain threshold, occupancy level above a certain threshold, etc.). In some embodiments, the space indicator element's color may be based on the infectious disease detected by one or more biological sensors. For example, a green space indicator may indicate that COVID-19 has been detected by the biological sensors while an orange space indicator may indicate that influenza has been detected by the biological sensors.

(320) In step **4908**, the building data platform **100** receives a selection from the user device via the selectable element of a time desired to be viewed by a user. As explained above, the user may interact with the user device (e.g., the user device **176**) to manipulate a selectable element on the user interface to indicate a future or historical time which they wish to view. By manipulating the selectable element, the user sends an indication to the building data platform **100** of the selection of times they wish to view. The building data platform **100** receives this indication at step **4908**. In step **4910**, the building data platform **100** displays the user interface of the graphic representation of the building generated in step **4906** based on the selection from the user device received in step **4908**.

(321) Referring now to FIG. **50**, a flow diagram of a process **5000** for generating and displaying one or more inference values of a building at one or more future times is shown, according to an exemplary embodiment. In some embodiments, the building data platform **100** may be configured to perform the process **5000**. In some embodiments, the learning service **2206** may be configured to perform the process **5000**. Any computing device or system described herein can be configured to perform the process **5000**.

(322) In step **5002**, the building data platform **100** receives historical data values of one or more data points for one or more historical times. In some embodiments, the historical data values of the one or more data points may be associated with one or more devices, spaces, or systems within a building. For example, the historical data values may be associated with a heating, ventilation, and air conditioning system within a building. As another example, the historical data values may be associated with an occupancy sensor within a building. As a final example, the historical data values may be associated with a building floor or a building room within a building. The building data platform **100** may receive the historical data values from one or more devices or components configured to collect data. For example, the building data platform **100** may receive historical telemetry data values from the building subsystems **122**. The historical data values may include measured data values, a log of historical equipment commands, a log of historical building personnel commands, etc.

(323) In some embodiments, the building data platform **100** may store the historical data received in step **5002** in the twin manager **108**. More specifically, the historical data may be stored in graph **529**. In other embodiments, the historical data may be stored in one or more other memories within the building data platform **100** (e.g., memories **166**, memories **126**, memories **120**, and/or memories **150**).

(324) In step **5004**, the building data platform **100** receives a selection of a proposed update changing control of the building or physical characteristics of the building at a past time, a current time, or a future time to the building. In some embodiments, the proposed update may include changing the control of the air handling unit of the building to update the air flow and/or air quality within the building. More specifically, the control of the AHU may be updated to change the clean air score. In some embodiments, the proposed update may include changing the occupancy level of the building or different spaces of the building. The building data platform **100** may receive a selection of the proposed update through a user device which the user may interact with to input selection of the proposed update. For example, the user device may display a user interface with one or more selectable elements (e.g., text box, dialog box, drop down menu, etc.) by which the user may input their selection for a proposed update.

(325) In step **5006**, the building data platform **100** executes an artificial intelligence agent to generate one or more inference values based on the one or more data points for one or more historical times based on the historical data values and the proposed update. Based on the historical data values and the proposed update, the model **576** generates one or more inference and/or predicted values of the building. In some embodiments, the model **576** may be stored in the digital twin as an attribute of the digital twin. For example, if a user inputs a proposed update with a lower building occupancy level, the model **576** uses the proposed lower occupancy level and historical data values related to air quality as inputs to determine an inferred or predicted clean air score. In some embodiments, the inference and/or predicted values may be combined to create a predicted future state of the building. For example, the inference and/or predicted values may be a predicted occupancy of a building or a floor, a predicted air quality of a building or floor, and/or a predicted reproductive number for a building. These inferred or predicted values may be used to predict a future state of the building. For example, the building data platform **100** may be able to predict a future state of the building one or more days in the future (e.g., one day, two days, three days, four days, etc.) based on the predicted occupancy, air quality, and reproductive number. In some embodiments, the building data platform **100** is also able to determine or simulate a past state of the building that would have occurred if a change were made to the operation of the building based on the historical values received at step **5002** and the proposed update received at step **5004**. For example, the building data platform **100** may be able to simulate a past state of the building one or more days in the past (e.g., one day, two days, three days, four days, etc.) based on the historical occupancy, air quality, and/or reproductive number values as determined based on the historical values and a proposed update.

(326) In some embodiments, the building data platform **100** may generate recommendations for the building based on inference and/or predicted values determined at step **5006**. For example, the recommendations may include running new control algorithms to control portions of the building in order to improve the air quality of the building, better manage occupancy levels, and/or reduce the reproductive number within buildings. As another example, the recommendations may include purchasing and/or installing new equipment in the building. For example, a predicted low clean air score and/or a predicted high reproductive number may be a result of poor air ventilation within a building. In this case, the recommendation may include purchasing and/or installing new air filters within the building to increase the clean air score and/or lower the predicted high reproductive number. In step **5008**, the building data platform **100** generates a user interface to display a graphic representation of the building based on the one or more inference values generated at step **5006**. For example, a user interface **5200** as shown in FIG. **52** may be generated by the building data platform **100**.

(327) Referring now to FIG. **51**, a flow diagram of a process **5100** for generating and displaying a graphic representation of the building and a selectable element of a historical time of one or more historical times is shown, according to an exemplary embodiment. In some embodiments, the building data platform **100** can be configured to perform the process **5100**. In some embodiments, the learning service **2206** may be configured to perform the process **5100**. Any computing device or system described herein can be configured to perform the process **5100**.

(328) In step **5102**, the building data platform **100** receives historical data values of one or more data points for one or more historical times. In some embodiments, the historical data values of the one or more

data points may be associated with one or more devices, spaces, or systems within a building. For example, the historical data values may be associated with a heating, ventilation, and air conditioning system within a building. As another example, the historical data values may be associated with an occupancy sensor within a building. As another example, the historical data values may be associated with a building floor or a building room within a building. The building data platform **100** may receive the historical data values from one or more devices or components configured to collect data. For example, the building data platform **100** may receive historical telemetry data values from the building subsystems **122**. The historical data values may include measured data values, a log of historical equipment commands, a log of historical building personnel commands, etc.

(329) In step **5104**, the building data platform **100** executes an artificial intelligence agent to generate multiple different operating scenarios for operating equipment of the building for multiple historical times. More specifically, based on historical data values for the building, the model **576** generates multiple operating scenarios of the building. For example, the model **576** may generate an operating scenario that simulates one or more operations of the building. For example, the model **576** may generate an operating scenario of a piece of building equipment (e.g., installation and/or maintenance of building equipment), a control algorithm or schedule for the building, a building room or zone, or the operation of the building as a whole.

(330) In step **5106**, the building data platform **100** executes an artificial intelligence to simulate multiple performance values of the building for multiple historical times based on the multiple different operating scenarios and/or the historical data values. More specifically, the model **576** uses the historical data values to simulate performance values at multiple historical times (e.g., 1 day in the past, 2 days in the past, 1 week in the past, 2 weeks in the past, etc.). The performance values may indicate a performance of one or more operating scenarios determined at step **5104**. More specifically, in some embodiments, the building data platform **100** may analyze each operating scenario based on one or more performance values (e.g., clean air score, occupancy number, reproductive number, etc.). Furthermore, the building data platform **100** analyzes each operating scenario of the building to determine an operating scenario with the most favorable performance values.

(331) Referring now to FIG. **52**, a user interface **5200** for viewing one or more elements of a building in a graphic representation of a building is shown, according to an exemplary embodiment. For example, a user interface **5200** may include a selectable element **5206** which is configured to display an operating scenario of a building for multiple historical times (e.g., -1 day, -2 days, -3 days, etc.). As another example, the user interface **5200** may include inference values **5202** and **5204**. The user interface **5200** may also include a selectable element **5208** (e.g., learn more button **5208**), which when selected by a user, displays more information about the occupancy solution and the clean air solution. The user interface **5200** may also include a selectable element **5210** (e.g., simulate scenario button **5210**), which when selected by a user, simulates one or more building scenarios as shown in selectable element **5212**. More specifically, when a user selects the simulate scenario button **5210**, the building data platform **100** causes a user interface portion to be displayed which gives a user the ability to select a parameter (e.g., occupancy level, AHU configuration, air filtration, etc.) for simulation. The elements **5202**, **5204**, **5208**, **5210**, and **5212** can be combined within a single user interface and/or displayed on a display device of the user device **176**, in some embodiments. The user interface **5200** can be a floor of a building that displays an occupancy level and a clean air score for a space of the building. The space can be highlighted by a particular color, e.g., green, blue, or red, based on the occupancy level and/or the clean air score.

(332) The user interface **5200** can allow a user to view states of the building at a current time, one or more days into the future, and/or one or more days into the past. The element **5206** can be a slider allowing a user to flip through the states of the building at historical, current, or future times. The user interface **5200** can provide a “Building Player” allowing a user to “play” the building view of the past statuses of the building (e.g., stored in a timeseries database and/or a digital twin), present statuses of the building, and/or future statuses of the building (e.g., simulated and/or inference/predictions generated by a digital twin). The predicted future statuses can be generated by an agent based on past and/or current data for the building, in some embodiments.

(333) In some embodiments, the building data platform **100** displays a graphic representation of the building and/or a selectable element of a historical time of the multiple historical times on a user device at step **5108**. For example, a user interface **5200** as shown in FIG. **52** may be generated by the building data

platform 100. In some embodiments, the performance values may be used to indicate a simulated state of the building. The state of building may be demonstrated as color coordinated indicators. For example, the state of the building may be shown as being highlighted in red which may indicate a low simulated clean air score (e.g., 20) and/or occupancy score (e.g., 10).

Configuration of Exemplary Embodiments

(334) The construction and arrangement of the systems and methods as shown in the various exemplary embodiments are illustrative only. Although only a few embodiments have been described in detail in this disclosure, many modifications are possible (e.g., variations in sizes, dimensions, structures, shapes and proportions of the various elements, values of parameters, mounting arrangements, use of materials, colors, orientations, etc.). For example, the position of elements may be reversed or otherwise varied and the nature or number of discrete elements or positions may be altered or varied. Accordingly, all such modifications are intended to be included within the scope of the present disclosure. The order or sequence of any process or method steps may be varied or re-sequenced according to alternative embodiments. Other substitutions, modifications, changes, and omissions may be made in the design, operating conditions and arrangement of the exemplary embodiments without departing from the scope of the present disclosure.

(335) The present disclosure contemplates methods, systems and program products on any machine-readable media for accomplishing various operations. The embodiments of the present disclosure may be implemented using existing computer processors, or by a special purpose computer processor for an appropriate system, incorporated for this or another purpose, or by a hardwired system. Embodiments within the scope of the present disclosure include program products including machine-readable media for carrying or having machine-executable instructions or data structures stored thereon. Such machine-readable media can be any available media that can be accessed by a general purpose or special purpose computer or other machine with a processor. By way of example, such machine-readable media can comprise RAM, ROM, EPROM, EEPROM, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to carry or store desired program code in the form of machine-executable instructions or data structures and which can be accessed by a general purpose or special purpose computer or other machine with a processor. When information is transferred or provided over a network or another communications connection (either hardwired, wireless, or a combination of hardwired or wireless) to a machine, the machine properly views the connection as a machine-readable medium. Thus, any such connection is properly termed a machine-readable medium. Combinations of the above are also included within the scope of machine-readable media. Machine-executable instructions include, for example, instructions and data which cause a general purpose computer, special purpose computer, or special purpose processing machines to perform a certain function or group of functions.

(336) Although the figures show a specific order of method steps, the order of the steps may differ from what is depicted. Also two or more steps may be performed concurrently or with partial concurrence. Such variation will depend on the software and hardware systems chosen and on designer choice. All such variations are within the scope of the disclosure. Likewise, software implementations could be accomplished with standard programming techniques with rule based logic and other logic to accomplish the various connection steps, processing steps, comparison steps and decision steps.

(337) In various implementations, the steps and operations described herein may be performed on one processor or in a combination of two or more processors. For example, in some implementations, the various operations could be performed in a central server or set of central servers configured to receive data from one or more devices (e.g., edge computing devices/controllers) and perform the operations. In some implementations, the operations may be performed by one or more local controllers or computing devices (e.g., edge devices), such as controllers dedicated to and/or located within a particular building or portion of a building. In some implementations, the operations may be performed by a combination of one or more central or offsite computing devices/servers and one or more local controllers/computing devices. All such implementations are contemplated within the scope of the present disclosure. Further, unless otherwise indicated, when the present disclosure refers to one or more computer-readable storage media and/or one or more controllers, such computer-readable storage media and/or one or more controllers may be implemented as one or more central servers, one or more local controllers or computing devices (e.g.,

edge devices), any combination thereof, or any other combination of storage media and/or controllers regardless of the location of such devices.

Claims

1. A building system of a building comprising one or more non-transitory storage devices storing instructions thereon that, when executed by one or more processors, cause the one or more processors to: store a digital twin of the building in the one or more non-transitory storage devices, the digital twin comprising a virtual representation of the building with an entity of the building, a data point, and an interrelationship between the entity of the building and the data point, wherein the digital twin further includes an artificial intelligence configured to generate a plurality of inference values of the data point for a plurality of future times; generate a recommendation based on the plurality of inference values for the data point for the plurality of future times, the recommendation recommending making one or more updates to the building; store data for the recommendation in the digital twin, wherein the digital twin includes a representation of a location within the building and associates the location with the recommendation; and cause a graphic representation of the building to display an indication of the recommendation at the location within the graphic representation of the building associated with the entity based on the digital twin indicating the data point being related to the entity.
2. The building system of claim 1, wherein the instructions cause the one or more processors to: receive a plurality of data point values for the data point from building equipment, the building equipment generating the plurality of data point values by measuring an environmental condition of the building or recording operating decisions performed by the building equipment; identify the data point based on the digital twin by identifying the interrelationship between the entity and the data point, the entity representing the building equipment; and store the plurality of data point values, or a link to the plurality of data point values, in the data point of the digital twin.
3. The building system of claim 2, wherein the plurality of inference values include predicted future values of the data point; wherein the plurality of inference values are stored in the digital twin; and wherein the instructions cause the one or more processors to generate the plurality of inference values by: identifying the data point of the digital twin and retrieving the plurality of data point values based on the data point of the digital twin; and executing the artificial intelligence to generate the plurality of inference values based on the plurality of data point values.
4. The building system of claim 2, wherein the plurality of inference values are predicted future values of a virtual indicator, wherein the virtual indicator is at least one of: a clean air virtual indicator indicating a level of air quality of a building space; an occupancy value indicating an amount of occupants in the building space; or an infection risk value indicating a risk of spread of an infectious disease in a population.
5. The building system of claim 1, wherein the digital twin includes a building graph data structure including a plurality of nodes representing a plurality of entities of the building and a plurality of edges between the plurality of nodes representing a plurality of relationships between the plurality of entities of the building.
6. The building system of claim 1, wherein the instructions cause the one or more processors to: model a predicted state of the building at the plurality of future times based on implementing the recommendation; and cause the graphic representation of the building to display the modeled predicted state of the building at the plurality of future times.
7. The building system of claim 1, wherein the recommendation includes a recommendation to update operating settings of building equipment of the building.
8. The building system of claim 7, wherein the instructions cause the one or more processors to cause the graphic representation of the building to display updated operation of the building equipment through the plurality of future times.
9. The building system of claim 7, wherein the recommendation to update the operating settings of the building equipment includes at least one of: a recommendation to command an air handling unit to change an air flow through the building; a recommendation to change air filtration of air within or being supplied to a space of the building; a recommendation to command one or more disinfectant lights to activate; or a

recommendation to restrict access to one or more portions of the building.

10. The building system of claim 9, wherein the recommendation to change air filtration of air within or being supplied to the space of the building includes a recommendation to perform at least one of: changing operation of at least one of an air handling unit, a variable air volume device, or an in-zone air filtration device; or modifying or replacing a filter in the at least one of the air handling unit, the variable air volume device, or the in-zone air filtration device.

11. The building system of claim 10, wherein the recommendation to change the air filtration of air within or being supplied to the space of the building includes automatically implementing the recommendation within the building.

12. The building system of claim 9, wherein the recommendation includes a status of the building equipment.

13. The building system of claim 1, wherein the plurality of inference values include at least one of a predicted disease reproduction number indicating a predicted number of individuals that contract a disease from an infected individual, a predicted energy consumption value indicating a level of energy expected to be consumed by building equipment of the building, or a clean air score indicating a predicted measure of quality of air in the building.

14. The building system of claim 13, wherein the instructions further cause the one or more processors to generate diagnostics for at least one of the predicted disease reproduction number, the predicted energy consumption value, or the clean air score, wherein the diagnostics include text indicating a cause for the predicted disease reproduction number, the predicted energy consumption value, or the clean air score.

15. The building system of claim 1, wherein the instructions cause the one or more processors to: receive outdoor air quality forecast data from one or more outdoor air quality sensors; model a predicted state of the building at the plurality of future times based on the outdoor air quality forecast data; and cause the graphic representation of the building to display the modeled predicted state of the building at the plurality of future times.

16. The building system of claim 15, wherein the recommendation includes a recommendation to update operating settings of building equipment of the building in response to the predicted state of the building based on the one or more outdoor air quality sensors.

17. A method comprising: storing a digital twin of a building in one or more storage devices, the digital twin comprising a virtual representation of the building with an entity of the building, a data point, and an interrelationship between the entity of the building and the data point, wherein the digital twin further includes an artificial intelligence configured to generate a plurality of inference values of the data point for a plurality of future times; generating a recommendation based on the plurality of inference values for the data point for the plurality of future times, the recommendation recommending making one or more updates to the building; storing data for the recommendation in the digital twin, wherein the digital twin includes a representation of a location within the building and associated the location with the recommendation; and causing a graphic representation of the building to display an indication of the recommendation at the location within the graphic representation of the building associated with the entity based on the digital twin indicating the data point being related to the entity.

18. The method of claim 17, further comprising: receiving a plurality of data point values for the data point from building equipment, the building equipment generates the plurality of data point values based on operation to control an environmental condition of the building; identifying the data point based on the digital twin by identifying the interrelationship between the entity and the data point, the entity representing the building equipment; and storing the plurality of data point values, or a link to the plurality of data point values, in the data point of the digital twin.

19. The method of claim 18, wherein the plurality of inference values are stored in the digital twin; and wherein the plurality of inference values include predicted future values of the data point, wherein the method generates the plurality of inference values by: identifying the data point of the digital twin and retrieving the plurality of data point values based on the data point of the digital twin; and executing the artificial intelligence to generate the plurality of inference values based on the plurality of data point values.

20. The method of claim 18, wherein the plurality of inference values are predicted future values of a virtual indicator, wherein the virtual indicator is at least one of: a clean air virtual indicator indicating a level of air quality of a building space; an occupancy number indicating a number of occupants in the

building space; or an infection risk value indicating a risk of spread of an infectious disease in a population.

21. The method of claim 17, further comprising generating diagnostics for at least one of a predicted disease reproduction number, a predicted energy consumption value, or a clean air score, wherein the diagnostics include text indicating a cause for the predicted disease reproduction number, the predicted energy consumption value, or the clean air score.

22. The method of claim 17, wherein the recommendation includes a recommendation to update operating settings of building equipment of the building, the operating settings updating operation of the building equipment.

23. The method of claim 22, wherein the recommendation to update the operating settings of the building equipment includes at least one of: a recommendation to make a command for an air handling unit to change an air flow through the building; a recommendation to command the air handling unit to change an air filtration setting for the building; a recommendation to command one or more disinfectant lights to activate; or a recommendation to command building security mechanisms to restrict access to one or more portions of the building.

24. One or more non-transitory computer readable media containing program instructions that, when executed by one or more processors, cause the one or more processors to perform operations comprising: storing a digital twin of a building in one or more storage devices, the digital twin comprising a virtual representation of the building with an entity of the building, a data point, and an interrelationship between the entity of the building and the data point, wherein the digital twin further includes an artificial intelligence configured to generate a plurality of inference values of the data point for a plurality of future times; generating a recommendation based on the plurality of inference values for the data point for the plurality of future times, the recommendation recommending making one or more updates to the building; storing data for the recommendation in the digital twin, wherein the digital twin includes a representation of a location within the building and associates the location with the recommendation; and causing a graphic representation of the building to display an indication of the recommendation at the location within the graphic representation of the building associated with the entity based on the digital twin indicating the data point being related to the entity.
