

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412005
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Strader; Dennis J. et al.

Systems and methods to model a site

Abstract

Systems and methods are disclosed herein for generating and/or providing a model, such as may be utilized for designing and/or presenting a proposal for a project for a structure or site. The disclosed embodiments can include identifying installation surface faces, installation surface face benefit metrics, obstructions, obstacles affecting placement of elements of the project, and for providing an educational experience, comprising general information and at least one structure-specific installation proposal. A selected plan can be implemented from within a proposal platform of the disclosed systems and methods.

Inventors: Strader; Dennis J. (Eagle Mountain, UT), Nelson; Ryan H. (Highland, UT), Anderton; Landon J. (Cottonwood Heights, UT), Goodrick; Daniel S. (Saratoga Springs, UT), McKee; Merrill E. (Clearwater, FL), Zhang; Cheng (Lutz, FL), Van Orman; Matthew G. (Eagle Mountain, UT), Naylor; Orrin C. (Colorado City, AZ)

Applicant: Speed of Light Ops, LLC (Lehi, UT)

Family ID: 86500182

Assignee: Speed of Light OPS, LLC (Lehi, UT)

Appl. No.: 18/070367

Filed: November 28, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230169731 A1	Jun. 01, 2023

Related U.S. Application Data

us-provisional-application US 63264657 20211129

Publication Classification

Int. Cl.: **G06F30/20** (20200101); **G06F30/13** (20200101); **G06F119/12** (20200101); **G06T7/12** (20170101); **G06T7/13** (20170101); **G06T7/60** (20170101); **G06T7/73** (20170101); **G06T15/60** (20060101); **G06T17/05** (20110101); **G06T17/10** (20060101); **G06T17/20** (20060101); **G06V10/44** (20220101); **G06V10/82** (20220101); **G06V20/10** (20220101); **G06V20/17** (20220101)

U.S. Cl.:

CPC **G06F30/20** (20200101); **G06F30/13** (20200101); **G06T7/12** (20170101); **G06T7/13** (20170101); **G06T7/60** (20130101); **G06T7/73** (20170101); **G06T15/60** (20130101); **G06T17/05** (20130101); **G06T17/10** (20130101); **G06T17/20** (20130101); **G06V10/44** (20220101); **G06V10/82** (20220101); **G06V20/17** (20220101); **G06V20/176** (20220101); G06F2119/12 (20200101); G06T2200/08 (20130101); G06T2207/10012 (20130101); G06T2207/10028 (20130101); G06T2207/10032 (20130101); G06T2207/20084 (20130101); G06T2210/56 (20130101)

Field of Classification Search

CPC: G06F (30/20); G06F (30/13); G06F (2119/12); G06F (30/27); G06F (2119/06); G06F (2111/10); G06T (7/12); G06T (7/13); G06T (7/60); G06T (7/73); G06T (15/60); G06T (17/05); G06T (17/10); G06T (17/20); G06T (2200/08); G06T (2207/10012); G06T (2207/10028); G06T (2207/10032); G06T (2207/20084); G06T (2210/56); G06T (2207/30192); G06V (10/44); G06V (10/82); G06V (20/17); G06V (20/176); G01B (21/28); G06Q (10/06)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
8209152	12/2011	Pershing	N/A	N/A
9041915	12/2014	Earhart et al.	N/A	N/A
9589079	12/2016	Morse et al.	N/A	N/A
10140401	12/2017	Hoff	N/A	N/A
10409925	12/2018	Hoff	N/A	N/A
10528960	12/2019	Pershing et al.	N/A	N/A
10970591	12/2020	Ananthakrishnan et al.	N/A	N/A
11043026	12/2020	Fathi et al.	N/A	N/A
11238193	12/2021	Hoff	N/A	N/A
11537808	12/2021	Crouch et al.	N/A	N/A
12014433	12/2023	Pearson et al.	N/A	N/A
2012/0035887	12/2011	Augenbraun et al.	N/A	N/A
2014/0046627	12/2013	Pershing	702/156	G01B 21/28
2014/0188571	12/2013	Han et al.	N/A	N/A
2015/0066442	12/2014	Pryor	N/A	N/A
2016/0103160	12/2015	Chen et al.	N/A	N/A

2017/0206648	12/2016	Marra	N/A	B64D 47/08
2017/0228913	12/2016	Kogan et al.	N/A	N/A
2017/0302077	12/2016	Yabe et al.	N/A	N/A
2019/0156570	12/2018	Sanjurjo et al.	N/A	N/A
2019/0188337	12/2018	Keane	N/A	G06Q 50/16
2019/0234638	12/2018	Song et al.	N/A	N/A
2019/0279420	12/2018	Moreno et al.	N/A	N/A
2019/0303707	12/2018	Ananthakrishnan et al.	N/A	N/A
2020/0293773	12/2019	Loveland et al.	N/A	N/A
2021/0272358	12/2020	Stevens et al.	N/A	N/A
2022/0237858	12/2021	Dubost et al.	N/A	N/A
2022/0335176	12/2021	Haddock et al.	N/A	N/A
2022/0366646	12/2021	Lopez Gavilan	N/A	G06T 17/00

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO-2014/033511	12/2013	WO	N/A

OTHER PUBLICATIONS

Zhuang, Yixin et al. "A General and Efficient Method for Finding Cycles in 3D Curve Networks." ACM transactions on graphics 32.6 (2013): 1-10. Web. (Year: 2013). cited by examiner
MathWorks. "Release Notes R2021a MATLAB & Simulink" (Mar. 2021).
<https://www.mathworks.com/help/matlab/release-notes-R2021a.html> (Year: 2021). cited by examiner

Primary Examiner: Brier; Jeffery A

Attorney, Agent or Firm: Foley & Lardner LLP

Background/Summary

RELATED APPLICATIONS (1) The present application claims the benefit of priority under 35 U.S.C. Section 119(e) of U.S. Provisional Patent Application No. 63/264,657 entitled SYSTEMS AND METHODS TO PROPOSE AN INSTALLATION, filed Nov. 29, 2021, which is hereby incorporated by reference herein in its entirety.

TECHNICAL FIELD

(1) The present disclosure is directed to generating and/or presenting a model of a site.

SUMMARY

(2) The present disclosure is directed to systems and methods to generate and/or present or otherwise provide a model of a site. For example, the present disclosure is directed to systems and methods to generate highly accurate models, such as may be used to present sophisticated, dynamic and/or interactive proposals (e.g., through a sales representative to a potential customer). The model of a site can include one or more structures and/or landscape. The embodiments of the present disclosure and/or models generated therefrom can be utilized for site enhancement,

including but not limited to surveillance, security, maintenance, and improvement (e.g., installation). Similarly, the system and methods herein described may be used with regard to site clearing, modification, restoration, rejuvenation, etc. Similarly, models generated from embodiments of the present disclosure can be utilized, such as for simulation, gaming, research, presentation, and any other suitable purpose.

(3) Additional aspects and advantages will be apparent from the following detailed description of preferred embodiments, which proceeds with reference to the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) FIG. 1 is a diagram of a project proposal system (PPS), according to one embodiment of the present disclosure.

(2) FIGS. 2A-2H and 2J-2M are a diagram of a process of a PPS to generate and present an electronic interactive solar proposal (“proposal”) for a solar energy system, according to one embodiment of the present disclosure.

(3) FIG. 3 is a diagram of a PPS, according to one embodiment of the present disclosure, wherein a platform provided by the PPS is configured to deliver information in advance of a proposal (e.g., a Preposal™) and a digital interactive solar proposal for a solar energy system.

(4) FIG. 4 is a flow diagram of a method of a PPS, according to one embodiment of the present disclosure, to generate and present a digital interactive solar proposal for installation of a solar energy system.

(5) FIG. 5 diagrams an architecture of a PPS for generating a digital interactive project proposal for a structure, such as a solar energy system, according to an embodiment of the present disclosure.

(6) FIGS. 6A and 6B illustrate scenarios or models for interfacing with the platform of a system to propose a digital interactive proposal (a project proposal system “PPS”), such as the PPSs of FIGS. 1-5, according to an embodiment of the present disclosure.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

(7) Enhancement of a site can be facilitated by proposals communicating information about the site. The present disclosure also provides embodiments for generating a model of a site, such as may be utilized in generating a proposal for an installation or a variety of other applications benefited by a three-dimensional model. The model may be utilized in any suitable manner, such as for proposals for installations and/or projects at a site.

(8) The following description describes embodiments of the present disclosure with primary reference to systems and methods of generating and/or providing proposals directed toward solar electricity generation systems (“solar energy systems”). The reference to and focus on solar is only an example, as a matter of convenience, and not by way of limitation as other applications, e.g., roofing, etc., are also anticipated.

(9) Selling solar electricity generation systems can be aided by providing customized information to a potential customer that is specific to a property and/or potential installation site of the potential customer. Information such as potential placement of solar panels and/or ultimate generation of electricity as a result of such placement can help a potential customer understand the scope and/or weigh the factors that are considered in a decision to install a solar electricity generation system.

(10) Introducing and educating potential customers to solar electricity generation installation and ultimately closing a sale has traditionally been a multi-touch, time intensive sales cycle. Proposals to provide potential customers with customized information specific to a property and/or potential installation site are typically hard copies or static electronic documents (e.g., portable document format (.pdf)) that provide static information. When the potential customer raises an objection or concern that leads to a new proposal design, a sales rep is required to either leave (or otherwise

disengage from the potential customer) and create a new proposal or request that support staff (e.g., at a support office) generate the new proposal, thereby elongating the sales process. This repeated, time-consuming regenerating of proposals over the course of one or more meetings of the sales rep with the potential customer can be burdensome to the potential customer (and the sales rep) and often leads to a lost sale.

(11) The customized information of a proposal is more useful to a potential customer when it includes solar production and shading analysis specific to the property and/or potential installation site. Solar production and shading analysis can be generated from three-dimensional (“3D”) data. Presently, available 3D data is, in many urban areas, limited to what can be obtained by sophisticated instruments attached to planes that can be flown at low altitudes over population centers to survey the structures. (Contractors that conduct the flyovers typically focus mainly on high population centers.) Rural and smaller population centers are often excluded from high volume data collection (although they may be served by Unmanned Aerial System (“UAS”) (see US Code of Federal Regulation 14, CFR 107.3 (last updated Nov. 14, 2022)) equipment), or the available data is outdated or of low-quality. Alternatively, a 3D model can be manually created with market-available do-it-yourself (“DIY”) tools. However, low volume collection methods (UAS-served, for example) and, more particularly, manual DIY tools leave room for human error, subjective decisions, slower return times, and an increase in manual labor cost.

(12) Another shortcoming of the present approach and challenge is that generating a high quality and informative proposal depends heavily on the designer of the proposal document understanding solar design and the technical details of azimuth, tilts, panel orientation, shading analysis, equipment, utilities, and others. Because the designer is often also a sales rep (e.g., individual trying to make a sale), obvious disincentives to accurately portray solar best practices arise because the proposal designer/sales rep earns more commissions for larger systems.

(13) Prior to a sales representative pitching a bid for installation of a solar energy system, they also typically take time educating the potential customer and answering questions on nuances of solar electricity generation. Solar (e.g., including solar electricity generation generally and solar energy systems specifically) is a new, interesting topic for many homeowners but they often don't know where to start investigating or researching this buying decision.

(14) In view of the foregoing considerations and factors, the present disclosure provides improved systems and methods to generate and/or present a proposal (e.g., a digital interactive solar proposal) for a solar energy system (or similar proposal) to a potential customer. The systems and methods of the present disclosure provide for generating and presenting an interactive solar energy system proposal to a potential customer (potentially providing a wider footprint), without reliance on light detection and ranging (“LiDAR”) instruments while removing aspects involving a human element that are thus error prone.

(15) The disclosed systems and methods to generate and/or present a proposal for a solar energy system to a potential customer can be automated to quickly provide highly accurate solar production models and to deliver sophisticated and dynamic solar sales proposals to sales reps in substantially “live time” (e.g., while the sales rep remains engaged with the customer, within a few minutes).

(16) The disclosed systems and methods can also, prior to delivering a proposal, immediately or near immediately provide sales reps with a Preposal™ (e.g., information in a presentation format provided preparatory to, “pre-,” or in advance of a proposal) to use for educating a potential customer while they are waiting for their proposal to be completed. The sales rep and potential customer have an immediate opportunity to begin the sales conversation and experience a seamless transition into the solar design, pricing metrics, and checkout.

(17) The disclosed systems and methods can include one or more of: onboarding, automated ordering, Preposal™ delivery, generating a 3D Point Cloud, roof face identification, roof face optimization, roof face modeling, structure modeling, tree and perimeter object detection and

simulation, sun path simulations, roof obstacle and penetrations detection, roof lines and measurements, solar panel placement, energy production calculations; editing solar cell placement within design, manual 2D override to optimize 3D polygons, and delivery of 3D solar/roof design (e.g., in a web-based 3D display tool).

(18) As used herein, the term “solar maximum day” refers to a day of the year (e.g., typically the summer solstice) whereupon a greatest amount of solar radiation falls upon a particular location.

(19) As used herein, the term “solar minimum day” refers to a day of the year (e.g., typically the winter solstice) whereupon a least amount of solar radiation falls upon a particular location.

(20) As used herein, the term “site” refers to definable space at a location without reference to any feature of the location, e.g., a geolocation (a “pinpoint”) along with a threshold surrounding area, regardless of what may be at or near the site. A geolocation and threshold surrounding area may be represented, e.g., by a legal property description.

(21) As used herein, the term “structure” refers to a feature of a site without regard for the feature origin. A structure may be any improvement (e.g., a manmade feature) on a site, such as a building, a tower, a sign, a canal, etc.; a definable area of a site having some bounding feature (physical or logical); an area of a site bounded only by a definition of the site itself; and so forth without limitation.

(22) An object of interest can be any object at a site that can be identified from imagery. A structure can be an example of an object of interest at a site. In some embodiments, an object of interest can be a geographic feature (e.g., a hill, a gulch, a volcano, a body of water). In some embodiments, an object of interest can be a living organism, such as a plant (e.g., tree) or animal (e.g., an endangered species).

(23) As used herein, the term “GPS” refers to a global positioning system employing a constellation of satellites to determine, to reasonable degrees of accuracy and precision, a location at or near the surface of the earth (including above or below the earth's surface). The present disclosure anticipates an alternative (or successor) geolocation system; however, GPS is used throughout and is intended to cover any suitable geolocation system.

(24) As used herein, the term “obstruction” refers to a physical object which may not physically impede on a structure but nevertheless impairs some aspect of the structure such as, e.g., casting a shadow on/over the structure or a portion of the structure. Examples of obstructions include trees, adjacent structures, elevated terrain, etc.

(25) As used herein, the term “obstacle” refers to a physical or logical object which impedes on a structure or a portion of a structure. An obstacle may be any object disposed on, against, over, around, or adjacent to the structure. Examples of obstacles include penetrations (a vent, a fan, an antenna, a chimney, etc.), an electrical drop, an easement (such as a utility easement), etc.

(26) As used herein, the term “insolation” refers to exposure of a definable entity to solar radiation, regardless of how the solar radiation is measured, expressed, or described. The definable entity may be a surface of interest, such as a roof of a structure, a face of roof, an area of ground, etc.

(27) FIG. 1 is a diagram of a project proposal system (PPS) **100**, according to one embodiment of the present disclosure. The PPS **100** is a system configured to design a solar energy system and to provide a digital interactive solar proposal (hereafter, “proposal”) for a solar energy system. While the embodiment of FIG. 1 takes the form of providing an interactive digital proposal for installation of a solar energy system, the systems and methods herein disclosed include components and functionality that are similarly suitable for providing an interactive digital proposal for other purposes, e.g., building a sun shade, laying out a garden, generating a structural design, organizing property rehabilitation, etc., and the present disclosure anticipates such other purposes. More particularly, the present embodiment is directed toward a solar energy system installed to a roof **30**, any surface of interest could be used, such as, e.g., a roof face, a top surface of a structure, a surface with a skyward exposure (including a wall, a dome, an eccentric roof, etc.), an inferred surface (e.g., a pergola, a space defined by poles, etc.), a mount, a pole, etc., and may encompass a

ground-level project, or even an excavated project. In one embodiment, the PPS **100** determines solar production, e.g., of a surface at a site of a potential solar electrical generation system.

(28) The PPS **100** receives data for and/or information about a site **40**, which may include a structure **20** and/or additional features. The PPS **100** comprises a PPS server **140** and a tablet computer **150** (or other client and/or mobile computing device). The PPS **100** may implement or otherwise provide a platform accessible by one or more users and/or entities that provide data to or otherwise interface with the PPS **100** to enable design of solar energy systems and/or proposals for the same. For example, the platform provided by the PPS **100** may comprise a sales representative-facing platform that enables sales representatives to receive Preposal™ and/or proposal data and seamlessly present the Preposal™ and proposal data to potential customers (e.g., an owner of a site and/or structure of a site). The PPS **100** may further employ an aircraft **110a**, **110b** and a communication system **10** (or network), and may obtain or otherwise receive data from an electrical grid system (“EGS”) **60** and/or a solar energy equipment provider (“SEEP”) **70**. The communication system **10** may be the Internet, a public network, a private network, a virtual private network, or a combination of these and/or similar communication networks; and is hereafter referred to as the Internet **10**. The Internet **10** may comprise, permit, or facilitate bidirectional communication **12**, **13**, **14**, **15** with, respectively, the PPS server **140**, the tablet computer **150**, the EGS **60** (more particularly, with a server **62** of the EGS **60**) and the SEEP (more particularly, with a server **72** of the SEEP **70**).

(29) In FIG. **1**, the structure **20** is a residential building (hereafter, “structure” **20**). The structure **20** represents a residential building; however, this is only for convenience of the disclosure, and systems and methods herein described are equally applicable to any object of interest, structure, a site, or even to a defined ground surface. The structure **20** comprises a roof **30** and is positioned on or at a site **40** that may include features or objects in addition to the structure **20** that may be at least considerations when designing a solar energy system for the structure **20** and/or the site **40**. While reference herein is made to a roof **30**, in some instances, an analogous feature may be applicable, such as a concrete pad, an area of ground, etc. An object of interest can have a top surface, which can be analogous to a roof (i.e., a roof is an example of a top surface of an object of interest).

(30) The site **40** may include features such as a nearby tree **42**, towers, poles, a building or other structure, a chimney **44**, vents **46**, **48**, etc. Some features of the site **40** may affect the degree to which sunlight strikes the roof **30** (obstruct or partially obstruct) and/or may impinge on solar panel placement (as an obstacle).

(31) The reference label **110a** represents an aircraft in a first position, while **110b** represents an aircraft in a second position, and **110x** (not illustrated) refers to an aircraft generally. The aircraft **110x** may be a manned aircraft (a fixed wing or rotary wing aircraft) or a UAS. The aircraft **110x** may be configured to capture images of terrain and features at the earth's surface, including a plurality of sites. The images may take the form of photogrammetry source and/or output images, stereoscopic images (such as the stereoscopic images **202**, **202s** in FIG. **2A**), video frames, etc. The present disclosure refers to the use of stereoscopic images for convenience only and not by way of limitation, and use of other image types is anticipated. The aircraft **110a** may capture a first stereoscopic image of terrain and features over which the aircraft **110a** is flying. A capture angle **112a** for the first stereoscopic image is shown for reference. The aircraft **110a** may travel **114** an appropriate distance and capture a second stereoscopic image having a capture angle **112b**. In one embodiment, the first stereoscopic image may be captured by a first aircraft **110x** and the second stereoscopic image may be captured by a second aircraft **110x**. The structure **20** is within the capture angles **112a**, **112b** of the aircraft **110a**, **110b**. The first and second stereoscopic images may be subject to various computer-based algorithmic processing before being delivered **116** to the PPS server **140**.

(32) An owner (e.g., a potential customer or other appropriate individual) (hereafter, “owner”) may request a solar proposal for a solar energy system. A sales representative may request the proposal

on behalf of the owner. The tablet computer **150** may be used to initiate preparation of the proposal. The tablet computer **150** may communicate **12, 13** via the Internet **10** with the PPS server **140** to cause various computer-based processes (further discussed in conjunction with FIGS. **2A-3**) to occur whereby the proposal may be generated. The stereoscopic images are used to generate point cloud data including points of the structure **20** and the features of the site **40**. The PPS server **140** may use the point cloud data and one or more neural networks (further discussed below) to identify faces of the roof **30**, and to determine the insolation (e.g., irradiance, irradiation, total solar resource fraction (TSRF), solar access) of each face of the roof **30**, as described below. The PPS server **140** may access data provided by the server **72** of the SEEP **70** to acquire dimensions, etc., of solar energy equipment that may be installable to the structure **20**. The PPS server **140** may employ the calculated insolation of each face of the roof, the solar energy equipment dimensions, information of the features of the site **40** (in particular, of features such as the chimney **44** and the vents **46, 48**) to design a solar energy system and installation thereof for the roof **30** of the structure **20**. The PPS server **140** may access data of the server **62** of the EGS **60**, the data comprising or enabling derivation of actual or estimated cost of power from the EGS **60** to the structure **20**. The PPS server **140** may further provide time-value-of-money calculations (or other cost-benefit analyses) illustrating an investment cost to install a solar energy system to the structure **20**, maintenance costs, energy cost savings over time, property value impact, etc. The PPS server **140** may format the relevant data to generate a proposal providing detailed information regarding a proposed installation of solar energy equipment to the structure **20**. The PPS server **140** may provide a digital interactive proposal over a communication network to a client computing device such as the tablet computer **150**.

(33) The tablet computer **150** may be used to provide general and particularized solar energy information (Solo™ Preposal™) to the owner and/or a detailed solar energy proposal. The Preposal™ may comprise general information of an educational nature, along with a placeholder for a particularized proposal for the structure **20** and/or site **40**. While the educational material is presented, the proposal is generated by the PPS server **140** and delivered and may be integrated with or otherwise combined with the Preposal™ for presentation to the owner. The Preposal™ may seamlessly transition from general educational material about solar energy to the particularized proposal for the structure **20** and/or site **40**. Stated otherwise, the platform provided by the PPS **100** may provide for presenting both the Preposal™ and the proposal in a seamless manner, in one integrated presentation.

(34) The proposal may provide information regarding proposed solar energy equipment to install to the structure **20** and/or at the site **40**, such as, e.g., a particular solar panel arrangement for one or more faces of the roof **30**; expected solar energy production output for time frames ranging from hourly to annually and lifetime, etc. The proposal may include an interactive digital representation **120** of the structure **20**, and one or more panels **130** (or other interfaces) to display relevant information. The proposal may provide further information to assist in closing of a sale to acquire and install the solar energy equipment to the structure **20** (as a solar energy system), such as, e.g., identification of candidate equipment, installation details (disposition of solar panels and other equipment), etc. The platform provided by the PPS **100** may further enable acquiring (ordering) the needed solar energy equipment, assisting with permitting (if required), contracting an installer, providing for inspection and connection to the EGS **60** (for net metering or power sell-back, where enabled), etc. More particularly, the PPS **100** (e.g., via the tablet computer **150**) may be configured to accept an order from the owner and/or sales rep, to order the solar energy equipment, to schedule inspections, installation, and connections, and may process payments related to implementing the installation. In other words, the platform provided by the PPS **100** in conjunction with the tablet computer **150** and a seamless presentation of the Preposal™ and proposal, may function to support a single-point-single-contact sale of solar energy equipment, making for an informed sale and an organized, efficient installation.

(35) FIGS. 2A-2H and 2J-2M are a diagram a process of a project proposal system (PPS) **200** to generate and present an electronic interactive solar proposal (“proposal”) for a solar energy system, according to one embodiment of the present disclosure. The PPS **200** may be similar in some respects to the PPS **100** of FIG. 1. In FIG. 2A, the PPS **200** may receive stereoscopic imagery for the site. The PPS **200** may, additionally or alternatively, receive or generate an orthogonal composite image (see the orthogonal composite image **214** in FIG. 2B). An orthogonal image can be a digital aerial image of land produced using digital orthoimagery. An overhead image may be captured as a first stereoscopic image **202** of a site **204** that may, as shown, include a structure, to which the owner of a site **204** may wish to consider installing a solar energy system. Another overhead image may be captured as a second stereoscopic image **202s** of the site **204**. The PPS **200** generates (or receives) point cloud data for the site (or a definable space at a location). By way of non-limiting example, the PPS **200** may access or otherwise receive point cloud data for a site of a potential solar electrical generation system. The first stereoscopic image **202** and a second stereoscopic image **202s** and/or point cloud data may be processed **206** to generate a point cloud **208** for the site **204**.

(36) The point cloud **208** may be generated from a high confidence disparity map of common points within the two stereoscopic images, with each common point having a position relative to an arbitrary point near the center of the point cloud **208**. The point cloud **208** may be logically disposed within a global coordinate system whereby a user may rotate the point cloud **208** in three axes. The stereoscopic images **202**, **202s** may include amorphous entities **210**. An amorphous entity **210** may be an image artifact representing an object which lacks a fixed size, shape, volume, density, or other feature, such as a tree, a shrub, a flag, a banner, a temporarily placed object, etc. In other words, an amorphous entity may have substantially different representation in images taken at different times of a given day, on different days, at different seasons of the year, in different years, affected by weather (in particular, by wind, for example), etc. An amorphous entity **210a**, representing a tree, is identified for reference (hereafter, “tree **210a**”).

(37) In some embodiments, the image data may be high quality and/or precisely positioned and/or point cloud **208** generation from such image data may be quite accurate. In some embodiments the generated point cloud **208** may include substantial noise. Noise, or other error in the point cloud data may come from, among other things, the relatively small values produced by the disparity map and the large distances over which the disparities are calculated or a lack of distinct features or texture on matching areas of the stereo image. Noisy point cloud **208** data points can be low pass filtered and a dense point cloud can be produced representing at least the upper surfaces present in both stereoscopic images **202**, **202s**. Some of the algorithms used to process the point cloud **208** and identify salient structures of the environment include: K-Nearest Neighbors, K-Means Clustering, GMM (Gaussian Mixture Models), RANSAC (Random Sample Consensus), PCA (Primary Component Analysis), Histogram Binning, MLESAC (Maximum Likelihood Estimate Sample Consensus), Least Squares Multiple Regression, and/or combinations of the same.

(38) In FIG. 2B, an orthogonal composite image **214** may be generated **212** from a flattened version of the point cloud **208**. The tree **210a** is identified for reference. The dense point cloud **208** is further processed **216** to identify clusters or arrays of points in the point cloud **208** that relate to roof surfaces **220**, whereby points relating to non-roof surfaces of the site (e.g., the ground, trees, adjacent structures, etc.) can be filtered out. In one embodiment, a flattened version of the point cloud data is then fed to a neural network that has been trained to identify the vertices and edges of the roof planes on the building. These vertices and edges are then joined to become the polygons that represent the roof surfaces. The point clusters identified to the roof surfaces **220** are further refined to identify rough polygons (or other shapes) representing outlines of each face comprising the roof surface. A first roof surface **220a** is identified for reference. In FIG. 2B, each identified roof surface **220** is illustrated with a different cross hatch. Each rough polygon may comprise a side which abuts a side of another rough polygon (such as, e.g., at a peak, a valley, a hip, etc.) or an

edge of the roof. The point clusters and rough polygons are processed to refine the shape of each polygon to generate an azimuth and pitch segmentation map **218** of the roof surfaces wherein the roof is contiguous (e.g., noise in the point clouds resulting in breaks between adjoining sides of polygons is resolved). The azimuth and pitch segmentation map **218** is further processed **222**, as discussed in conjunction with FIG. 2C.

(39) In FIG. 2C, further processing **222** is directed toward detection **224** of an original footprint **228** of the structure. The tree **210a** is identified for reference. An original footprint may be described as a perimeter of a real-world feature which resulted in the particular point cloud (or portion of the point cloud). In other words, the original footprint is the perimeter of the real-world object represented by at least a portion of the point cloud. A vertex detection neural network (“VDN”) (see the VDN **545** in FIG. 5) may be employed to detect a first set of vertices (V1-V12) **226**, wherein the first set of vertices **226** is generally disposed about a perimeter of a structure (e.g., an entire roof). Said otherwise, the PPS **200** may identify perimeter points (e.g., vertices **226**) of one or more surfaces of interest of an object of interest. In one embodiment, the PPS **200** may identify perimeter points (e.g. vertices **226**) of one or more limits of a definable space at a location. One vertex (V10) **226a** is identified for reference. A member of the first set of vertices **226** is identified for reference. In one embodiment, a vertex may be a point (actual or theoretical) where three planes intersect as suggested by the normal directions of neighboring groups of points. In another embodiment, a vertex may be a point cloud point or feature where an array of next-neighbor points indicates an intersection of at least three planes wherein at least two planes are perimeter defining for the structure. In one embodiment, a vertex may be a point cloud point or feature where a plane of point clouds has a single point (or nuclear array of points) situated at a nexus of a region of points (present points) and a region absent of points (absent points) (a region of the plane of points free or substantially free of points) wherein the region of present points occupies less than a 180° contiguous arc and the region of absent points occupies greater than a 180° arc. The VDN may iteratively operate **230** to detect **232** additional vertices (V13-V18) **234** that may be located about a top surface or a portion of the structure (e.g., a roof face). One such vertex (V13) **234a** is identified for reference. A member of the additional vertices **334** represents a point cloud feature where an array of next-neighbor points indicates an intersection of at least three planes wherein at least two planes are not perimeter defining for the structure. The PPS **200** then generates **236** an edges map **238**, as discussed in conjunction with FIG. 2D.

(40) In FIG. 2D, the PPS **200** generates **236** an edges map **238**. The tree **210a** in the point cloud is identified for reference. An edge detection neural network (“EDN”) (see the edge detection neural network **550** in FIG. 5) constructs bounding boxes, each circumscribing an array of next-point neighbors that represent an intersection between two planes within the point cloud, and also containing two vertices **226**, **234**. The EDN may be an embodiment of a perimeter neural network that detects a perimeter of a surface of interest. In one embodiment, the PPS **200** algorithmically places a set of perimeter points (e.g., the vertices **226**) inside a bounding shape and connects the perimeter points within each bounding shape to find a perimeter of a definable area at a location. A line defining an edge is algorithmically established between the two vertices **226**, **234** along the intersection of the two planes. These lines represent edges **240** between vertices **226**, **234**. Stated otherwise, the PPS **200** identifies surface of interest edge types, such as edges defined or found at a roof ridge, eaves, hips, and valleys. One such edge **240a** (a roof ridge) is identified for reference. The PPS **200** processes **242** the edges **240** to detect roof faces **244**. The PPS **200** may employ a face detection engine (“FDE”) (see the face detection engine **555** in FIG. 5) to relate the edges **240** so as to construct digital (or electronic) representations of roof surfaces (F1-F5) **244**. In one embodiment, the FDE uses a Cycle Basis algorithm to detect the roof faces **244**. One such roof face (F4) **244a** is identified for reference. Further processing **246** is discussed in conjunction with FIG. 2E. At this stage, the roof faces **244** exist in a single plane.

(41) In one embodiment, the PPS **200** may generate a representation of each surface of interest

(e.g., a roof face, a patio, a water feature) of the one or more surfaces of interest, based on corresponding perimeter points (vertices **226**, **234**), perimeter, 2D face and 3D plane, and may join the representation of the one or more surfaces of interest to create a 3D model of at least a portion of an object (e.g., a structure, a geographic feature) of interest. In one embodiment, finding a perimeter of a definable space at the location may comprise determining a 2D face of one or more top surfaces, which may enable or assist the PPS **200** to generate a model of the definable space at the location.

(42) In FIG. **2E**, the further processing **246** is directed to modeling the point cloud data to generate a structure representation (e.g., a 3D model, a polyhedron model) (hereafter, “3D model”) **250** of the structure at the site through 3D planes detection **248**. In one embodiment, the PPS **200** models the point cloud data to generate a representation of an object of interest at the site, including one or more surfaces of interest for the project to be proposed. In one embodiment, the PPS **200** models the point cloud data to generate a representation of a definable space at a location. The structure representation **250**, in the present example, comprises one or more roof faces. The tree **210a** is identified for reference. The PPS **200** may employ a 3D planes detection engine (“3DE”) (see the 3D planes detection engine **560** in FIG. **5**) to transform the individual roof faces **244** into their respective 3D planes. The 3DE maps planar (x, y) coordinates (2D vertex locations) from the orthogonal composite image to planar (x, y) coordinates with the point cloud for the structure (see the orthogonal composite image **214** and the point cloud **208** in FIG. **2B**). This allows the 3DE to associate a collection of point cloud points to each defined roof surface at the single plane, then to employ the additional data (e.g., a z-coordinate or elevation component) of each point associated to the particular 2D roof surface in order to establish the 3D roof plane. The 3DE can use random sample consensus (“RANSAC”) to establish a 3D plane that is a “best fit” for the points associated to the particular 2D roof plane. The collection of 3D roof planes can be joined together to construct the representation **250** of the structure, such as a simplified 3D model of the roof of the structure. The representation **250** of the structure can be completed by adding a representation of each vertical wall extending from a roof face of the one or more roof faces to a ground plane. A 3D model, or modeling, provides a digital representation of an object (in the present example, a structure) in the physical world, along with digital representation of at least some physical features (shape, form, etc.) of the object. The structure representation **250** is used in simulations, as discussed below. A simulation, by contrast to a model, involves a translation (a motion or movement) of a digital representation of a physical thing. By way of example, movement of the sun relative to the 3D model **250** will be simulated.

(43) In FIG. **2F**, a wide area point cloud **252** is shown, including the site of the structure and at least minimal surrounding area (see the site **204** in FIG. **2A**). The relative point density throughout the point cloud indicates various physical entities represented in the wide area point cloud **252**. The roof structure **252a** is identified for reference. The point cloud data may be modeled to generate a site representation (e.g., in the form of a 3D mesh scene). The wide area point cloud **252** may be rendered in a global coordinate system whereby a user may rotate the wide area point cloud **252** in three axes. The wide area point cloud **252** can be processed to generate **254** a mesh scene **256** containing the roof structure **252a** and obstructions. In one embodiment, the PPS **200** models the point cloud data to generate a site representation (e.g., a 3D mesh) of the site that includes an object of interest and one or more objects adjacent to or otherwise around the object of interest. In one embodiment, the PPS **200** generates a visual representation, such as the 3D mesh, of an object of interest and any obstruction(s) that can be utilized to determine or otherwise indicate a shade metric of each point of the one or more surfaces of interest. In one embodiment, the PPS **200** models the point cloud data to generate a 3D mesh as a site representation of a definable space at a location. The 3D mesh can be a collection of vertices interconnected with edges to define polygons that form a model of an object. The 3D mesh may include one or more surfaces of interest and one or more objects at the site that are adjacent to or around the one or more surfaces of interest. By way of

non-limiting example, adjacent points (or next-neighbor points) may be grouped to form a collection of Delaunay triangles. In other words, wide points are collected and formed into Delaunay triangles, then a ray casting scene is created and the triangles inserted. The mesh is imposed on the scene by the nature of each triangle side being shared with exactly one other triangle. One obstruction **257** is identified. The obstruction **257** is an analog of the tree (see the tree **210a** in FIGS. 2A-2E). The mesh scene **256** is used to generate **258** an insolation potential map (see the insolation potential map in FIG. 2G).

(44) In FIG. 2G, an insolation potential map **260** is generated **258**. The PPS **200** may employ a simulation engine (“SIM”) (see the simulation engine **565** in FIG. 5) to simulate sunlight striking each roof plane free from any obstruction (shade casting entity). The SIM may simulate a path of the sun with respect to the structure representation **250** (from FIG. 2E) to identify areas of the roof surfaces that are shaded from the sun at any time due to an obstruction. This simulation may be run recursively based on a solar maximum day, a solar minimum day, a period of days, etc. The SIM may run the sun path simulation for any given point of time and/or span of time. The SIM may simulate a path of the sun with respect to a site representation of the site or definable space at a location to identify areas of an object of interest that are shaded from the sun by an object adjacent to the object of interest and that obstructs the sunlight from a surface of the object of interest. The SIM may gather or otherwise obtain sun positions (zenith and azimuth) for a plurality of points in time or time spans that represent phases (e.g., days, weeks, months, seasons, etc.) throughout (e.g., every second, every minute, every hour of) the year for the geolocation of the site. The PPS **200** then calculates potential insolation of each 3d roof plane free of any obstruction (shade casting entity) to produce the insolation potential map **260**. Insolation potential of each 3D roof plane is represented by a different cross hatch **262**.

(45) The wide area point cloud or the mesh scene, or both may be utilized to generate a less dense point cloud (obstruction point cloud) representing features previously filtered out, such as trees, adjacent structures, etc., that may affect insolation of the roof of the structure (see the wide area point cloud **252** in FIG. 2F). The obstruction point cloud is processed to generate a point cloud with insolation that includes shade from surrounding obstructions and insolation heat-mapped to the roof of the structure.

(46) The SIM may iterate through the sun path simulation, filtering the sun positions for a plurality of points in time to daytime sun positions, and further filtering to sun positions for multiple days of year representative of, e.g., summer and winter solstice (or solar maximum and solar minimum days). The SIM simulates the sun positions for the multiple days of the year to find shade on the one or more roof surfaces. Stated otherwise, the SIM runs the sun path simulation to represent the sun positions for the multiple days (or time points) of the year to simulate shade at any given point of the point cloud representing any portion of a roof surface. By way of non-limiting example, the SIM represents the sun positions for the multiple days of the year to simulate shade at a point per period (e.g., hour) of the year, on one or more roof surfaces. The point cloud with insolation can be further processed (possibly with the azimuth and pitch segmentation map **218** (from FIG. 2B) and/or the azimuth map **284** (of FIG. 2K)) to generate **264** a roof insolation map **266**. Said otherwise, the PPS **200** generates a visual representation (the roof insolation map **266**) of the roof surfaces that indicates the insolation (e.g., irradiance, irradiation, total solar resource fraction (TSRF), solar access) value of each of the roof surfaces. Processing to produce the roof insolation map **266** comprises relating the path of the sun relative to the site or the building (zenith and azimuth), in particular, at the solar maximum day and the solar minimum day to generate a sun path simulation. The sun path simulation provides a representation of the sun rays from the sun's point of view to a site. In one embodiment, an Euler transformation can be used to project theoretical sunlight from the sun's point-of-view. In another embodiment, a process of Ray Casting on Mesh can be utilized to project theoretical (or simulated) sunlight from the sun's point-of-view to the site. When applied to the obstruction point cloud, the azimuth and pitch segmentation map **218**, and the

azimuth map **284**, the sun path simulations for the solar maximum day and the solar minimum day produce hourly irradiation data points that are then used to annualize the insolation of the roof surfaces (e.g., estimate or otherwise calculate insolation throughout a year). The roof insolation map **266** can represent annual irradiation of the roof.

(47) One useful way of determining insolation is to measure or calculate yearly irradiance (and the present disclosure anticipates other ways). The following data values for calculating yearly irradiance for each point on the roof can be gathered by at least either of the two following options.

(48) Option 1. Determine one or more insolation values for each face (e.g., point, area, square unit, entire face, etc.) of the one or more faces of the structure for a time period (e.g., a single point in time, a span of time), considering areas of the one or more faces that may be shaded at one or more times within the time period. This can be accomplished by: masking (e.g., extracting, filtering, separating, etc.) face points of the point cloud (e.g., based on the one or more faces, or based on determining the points of the point cloud that are on the one or more faces); determining a (theoretical) maximum available irradiance (insolation) at each; determining a shade metric or value at each point of each face of the one or more faces for the time period; and determining the one or more insolation values based on the theoretical maximum available irradiance (or insolation) and shade metric at each point of each face of the one or more faces for the time period.

(49) Option 2. Determining an insolation value for each face of the one or more faces of the structure for a period of time (e.g., a single point in time, a span of time), considering areas of the one or more faces that are shaded at one or more times within the time period. This can be accomplished by: separating (e.g., extracting, filtering, masking) surface points of the point cloud for the given face from other points of the point cloud; determining a theoretical maximum available irradiance (or insolation) at each point of the points of the given face over the time period; determining a shaded irradiance (insolation) at each point of the given face, the shaded irradiance (insolation) based on the theoretical maximum available irradiance (insolation) and the shade value or metric at each point of the given face over the time period; and summing the shaded irradiances (insolation) of all the points of the given face.

(50) Either Option 1 or Option 2 may provide for determining a shade metric or value, which may be determined at each point of the one or more surfaces of interest for a time period; and/or identifying the objects at the site that are obstructions, based on the shade metric at each point of each of the one or more surfaces of interest.

(51) An annualized degree of shade map **268** represents the calculated effect of shade cast upon areas of the roof. A region of less-dense cross hatch **268a** represents a lesser degree of shade (a higher degree of insolation), while a region of more-dense cross hatch **268b** represents a higher degree of shade (a lower degree of insolation) on an annual basis. It should be noted that the PPS **200** may be configured to adjust the roof insolation map **266** to a particular period, such as, e.g., seasonal rather than annual. It should also be noted that insolation values for a roof may be calculated in various ways. In one embodiment, the PPS **200** calculates an insolation value for each point of the point cloud associated with a particular roof face. In one embodiment, the PPS **200** may calculate an insolation value based on an array of points of the point cloud, such as a definable measurable area (e.g., a square foot, a square meter, etc.) of a roof face, a definable fraction of a roof face (e.g., one-tenth, one-quarter, etc.), an entire roof face, or the entire roof.

(52) The roof insolation map **266** is further processed to generate **270**, in FIG. 2H, a filtered production estimate map **272**. The tree **210a** is identified for reference. The filtered production estimate map **272** considers the roof irradiation map **268** and the model **250** to estimate a potential for solar energy production across the roof. Cross hatch density indicates relative production estimate across the roof with less-dense cross hatch indicating higher production estimates (less shade), and more dense cross hatch indicating lower production estimates (more shade).

(53) The designation of “FIG. 2I” is not used for any drawing to avoid confusion.

(54) In FIG. 2J, the edges **240** (from FIG. 2D) are classified **274**. The vertices **226**, **234** and the

edges **240** have been previously identified (see FIGS. 2C and 2D). In one embodiment, the vertices **226**, **234** and/or edges **240** may be reidentified or re-located again, as by a reiteration of the operations of FIGS. 2C and 2D, or another operation. The vertex (**V10**) **226a** is identified for reference. The edges **240** are initially classified as actual edges **278**. One actual edge **278a** is identified for reference. The PPS **200** generates **280** an edge erosion map **282**. The edge erosion map **282** may consider local, state, or other regulatory requirements, such as fire codes, building codes, etc. For convenience of the disclosure, fire offsets **284** are referenced, however, any other requirement may be imposed. The fire offsets **284** impose a set back from a physical edge of a roof for the installation of at least some equipment, such as solar panels. A fire offset **284a** is identified adjacent to its corresponding physical edge **276a**. The PPS **200** generates **280** the edge erosion map **282** to identify roof areas available for use in the proposal in view of the fire offsets **284** (or other offset requirement). Determining roof areas available for use in the proposal entails determining dimensions (or measurements) of each of the one or more roof faces, adjusting for the fire offsets **284**, and obstacles (see the obstacles map **288** in FIG. 2L); and may further consider dimensions and other requirements for equipment to be installed.

(55) In FIG. 2K, the PPS **200** generates an azimuth map **286**. The azimuth map **286** may provide an azimuth for each roof face or other surface of interest. An azimuth in the azimuth map **286** indicates a direction of orientation of a roof face or other surface (without regard for inclination from horizontal). An azimuth is a compass-relative (cardinal) orientation. To illustrate, a structure may have a surface of interest comprising two faces, wherein the first face has an azimuth of 95° and the second face has an azimuth of 275° (i.e., 180° relative to the first face). In other words, the structure may have a general north-south longitudinal disposition with a general east-west orientation of the two faces of the surface of interest, and the two faces of interest are disposed in nearly opposite directions. In FIG. 2K, five azimuths **286a-286e** are identified—one for each roof face. Each azimuth **286a-286e** may indicate an orientation of an associated roof face relative to an adjoining roof face. Said otherwise, the azimuth **286a** may represent an orientation of its associated roof face relative to an adjacent roof face having the azimuth **286b**, and, conversely, the azimuth **286b** represents the orientation of its associated roof face relative to the roof face having the azimuth **286a**.

(56) In FIG. 2L, the PPS **200** generates an obstacles **288** map. The PPS **200** detects placement obstacles, e.g., protrusions, penetration (such as vents, fans, etc.) on the one or more roof faces of the structure using at least the overhead imagery. The orthogonal composite image **214** (of FIG. 2B), or one or both of the stereoscopic images **202** (of FIG. 2A) can be used to identify obstacles **288a-288d** to the installation of solar equipment on the roof of the structure, including features of the structure, such as penetrations (e.g., chimneys, vents, etc.), HVAC equipment, antennae, etc. Machine learning algorithms can be utilized to identify the obstacles **288a-288d** from the image(s) **202**, **214**. For example, training images can be used to develop and/or train one or more neural networks that can be used to process the image(s) **202**, **214** to identify the obstacles **288a-288d**. In the present example, the obstacles **288a-288d** impose limitations on the placement of solar panels on roof faces. In FIG. 2L, four obstacles **288a-288d** are identified. By way of non-limiting examples, the obstacles **288a**, **288b**, and **288c** may be penetrations, such as vents, fans, etc., and the obstacle **288d** may be an electrical service drop. In another embodiment having an application other than that of a solar power system, the obstacles **288a-288d** may represent any feature that affects the completion of the intended project.

(57) In FIG. 2M, the PPS **200** processes together **290** the 3D model **250**, the filtered production estimate map **272**, the edge erosion map **282**, the azimuth map **286**, and the obstacles map **288**, along with the data regarding solar energy equipment (e.g., dimensions, installation clearances and requirements, etc.) to produce a candidate map **292** for installation of solar energy equipment to the roof of the structure. In one embodiment, the PPS **200** determines proposed positioning (a candidate map **292**) of one or more elements of a proposed project, based on dimensions of the one

or more surfaces of interest. The candidate map provided considers various installation geometries for solar panels **294** to determine an optimal installation geometry **296** for the particular structure. Each candidate map **292** involves determining (or optimizing) proposed placement (e.g., location, positioning, orientation, inclination) of one or more solar panels of the potential solar electrical generation system on the one or more roof faces based on: the insolation values, the dimensions of the one or more roof faces, the placement obstacles on the one or more roof faces, and any AHJ requirements such as fire setbacks or other offsets.

(58) The candidate map **292** may be utilized to generate a digital interactive proposal to present the proposed placement of the one or more solar panels, such as for customer information and understanding. The candidate map **292** can be added to a structure representation and/or site representation (e.g., a model), which can be rendered to provide visualization of the placement of the solar panels. A visualization of the site representation can be achieved via taking labeled (labeled as belonging to the roof, or the vertical walls) three-dimensional (3D) vertices (or coordinates) and using an earcut (or ear clipping) polygon triangulation algorithm to generate the geometry for displaying the mesh of the house. In another embodiment, the candidate map **292** can be modeled to generate a representation (e.g., 3D model) to be rendered in or in conjunction with the digital interactive proposal. The digital interactive proposal can be provided over a communication network to a client computing device.

(59) FIG. **3** is a diagram of a project proposal system (PPS) **300**, according to one embodiment of the present disclosure, wherein a platform **330** provided in conjunction with the PPS **300** is configured to deliver a Preposal™ **340** and a digital interactive solar proposal **358** for a solar energy system. The Preposal™ **340** and proposal **358** can be two different deliverables consolidated by the PPS **300** to the platform **330**. According to one embodiment of the present disclosure, platform **330** may be configured such that the Preposal™ **340** and the proposal **358** appear as seamless presentation to a potential client. In other words, the PPS **300** generates a digital interactive proposal to present the proposed positioning of one or more elements of a proposed project, and any calculated benefits or results deriving from the proposed project. The ability to present the Preposal™ **340** and the proposal **358** seamlessly can facilitate both an education portion and a sales portion in presenting to the potential client, increasing a likelihood of a sales commitment. While a sales representative is presenting the Preposal™ **340**, the PPS **300** informs the platform **330** as to processing and delivery time for the proposal **358**, enabling the sales representative to effectively utilize time with the Preposal™ **340** and transitioning (apparently seamlessly) to the proposal **358**.

(60) The PPS **300** includes a PPS server **310** and a tablet computer **320**, as shown. In one embodiment, the tablet computer **320** may be supplanted by a laptop computer, a desktop computer, or any appropriate personal computing device. The PPS server **310** may be similar in some respects to the PPS server **140** of FIG. **1**. The tablet computer **320** may be similar in some respects to the tablet computer **150** of FIG. **1**. The tablet computer **320** can comprise an electronic memory, a processor, a communication system, and a display module. The platform **330** can include the Preposal™ **340** and a container **350** for the interactive proposal **358**. The platform **330** can be implemented, executed, or otherwise provided by the PPS **300** to render a presentation of the Preposal™ **340** and proposal **358** to the display module of the tablet computer **320**. The platform **330** is shown in a representational form extending beyond the tablet computer **350** for ease of description and not as an actual physical state. A preset content library **342** is shown, and comprises a plurality of preset content modules **344**. Each of the preset content modules **344** may contain text, graphics, and other data useful to educate a potential purchaser of a solar energy system on general terms regarding the process, the benefits, etc. of a solar energy system. A user of the tablet computer **320** may select one or more of the preset content modules **344** (selected preset content modules **348**) for insertion **346** into or inclusion in the Preposal™ **340**. The user may further order the selected preset content modules **348** as desired. In one embodiment, the user may

be able to edit one or more of the selected preset content modules **348**. In one embodiment, the user may be able to generate a custom preset content module to include with the selected preset content modules **348**.

(61) The platform **330** may be configured to accept input to identify a site (or a structure at a site) as a candidate for a solar energy system (or any suitable project, such as a roof installation, ground cover implementation, etc.), as well as to identify an owner or appropriate contact point (a potential client) for the site or structure. The platform **330** may be configured to deliver the site/structure information and the owner information to the PPS server **310**. The PPS server **310** may generate one or more proposals **358** for installation of a solar energy system to the structure or site.

Generation of a proposal **358** is described elsewhere herein. The PPS server **310** may generate the one or more proposals **358** at the same time that the user is using the platform **330** to render, present, or otherwise deliver the selected preset content modules **348** of the Preposal™ **340** to the potential client. In other words, while the user is showing the potential client the Preposal™ **340**, the PPS server **310** may be generating the proposal(s) **358**. Once the PPS server **310** generates the proposal(s) **358**, the proposal(s) **358** may be injected **356** into the proposal container **350** of the platform **330**. In a nominal situation, the proposal(s) **358** may be present in the platform **330** before the user and the potential client have finished reviewing or otherwise interacting with the Preposal™ **340**, such that transition from the Preposal™ **340** to the proposal(s) **358** appears seamless to the potential client. The proposal(s) **358** may each include images, interactive images, text, financial analysis/-es, and/or other relevant sections to enable the potential client to make an informed decision (e.g., a purchase decision), to arrange ordering of solar energy equipment, arrange payment (including a payment plan and/or financing options), schedule any necessary permits, the actual installation, inspections, connections, etc.

(62) FIG. **4** is a flow diagram of a method **400** of a project proposal system (PPS), according to one embodiment of the present disclosure, to generate and present a digital interactive solar proposal (proposal) for installation of a solar energy system. The method **400** may be employed by a PPS such as the PPS **100**, **200**, **300** of FIGS. **1-3**, respectively. The PPS may receive a request for a proposal of a project, such as for a solar energy system for a site or structure. The PPS receives **405** imagery, point cloud data, and/or GPS data for the site or structure for which a proposal may be requested. The imagery may comprise one or more of a nadir image, an orthographic composite image, stereoscopic images, video images, etc. In one embodiment, the PPS may generate the orthographic composite image. The point cloud data may be generated by the PPS, or may be provided by a vendor. In one embodiment, the PPS generates the point cloud based on the imagery. The point cloud comprises an arbitrary reference point located near a center of the structure or site, and from which all other points have a vector (direction and inclination) and a distance.

(63) The PPS generates **410** an azimuth and pitch map by identifying a surface of interest, such as a roof, an area of ground, a definable space (such as above a pad or deck), etc. The PPS refines the surface of interest to surface faces (e.g., roof faces, terrain variations, elevation changes, etc.) The PPS identifies **415** vertices. The PPS may algorithmically (e.g., by GMM, RANSAC, PCA, MLESAC, etc.) identify clusters of points within the point cloud that may each represent an intersection of at least three planes. By way of non-limiting example, the PPS distinguishes points of the point cloud which represent a point of a roof surface of the structure from points which represent points of non-roof entities, then clusters together points which share characteristics indicative of representing a particular surface of the roof. Such characteristics may include a direction, an angle, and/or a distance from the arbitrary reference point, which suggest a plurality of points represent points in the same surface.

(64) The PPS identifies **420** edges by constructing a bounding box circumscribing an array of next-point neighbors that represent an intersection between two planes within the point cloud, and also containing two vertices. A line defining an edge is algorithmically established between the two vertices along the intersection of the two planes. This line represents an edge extending between

the two vertices. The PPS iterates this process until all edges have been identified and mapped.

(65) The PPS detects **425** 2D surface faces by relating together edges that have a common vertex. A polygon is generated for each surface defined by these common vertices. Each such polygon presents a perimeter shape of a particular face on the surface. The PPS resolves gaps between adjacent polygons, overlaps of a polygon on an adjacent polygon, etc. An algorithm may be applied to remove noise from the data (aberrant points of the point cloud) which may be the source of gaps and overlaps.

(66) The PPS generates **430** a 3D model of the structure or site. Roof lines can be identified and classified based on how a given polygon relates to or interfaces with surrounding polygons. A footprint and walls of the structure may be combined with the polygons of the roof faces.

(67) The PPS generates **435** a site representation by implementing a wide area point cloud. The wide area point cloud can include the structure and/or site (as a dense point cloud) and an appropriate amount of surrounding area to capture relevant features, such as may affect the project to be proposed. For example, for a solar electrical generation system, the wide area point cloud can include any surrounding features—obstructions, such as trees, neighboring structures, etc., that may cast shade on the surface of interest. The site representation may take the form of a mesh scene. A visualization of the site representation can be achieved via taking labeled (labeled as belonging to the roof, or the vertical walls) three-dimensional (3D) vertices (or coordinates) and using an earcut (or ear clipping) polygon triangulation algorithm to generate the geometry for displaying the mesh of the house.

(68) The PPS generates **440** an insolation potential map, which describes the potential for insolation without regard for any intervening factors, such as, e.g., seasonal changes, obstructions, etc. In other words, the PPS generates **440** a map representing a maximum potential for insolation of the surface of interest with no interference.

(69) The PPS then runs **445** sun simulations. A sun simulation determines a position of the sun relative to the structure or site at a particular time, and may iterate through a definable period of time to determine, from the site representation, the effect of obstructions and other features on the insolation potential map. An Euler transformation or a Ray Casting Mesh may be used to logically position the sun. Sun positions are gathered in zenith and azimuth angles) for a plurality of hours that is representative of phases or cycles (e.g., days, weeks, months, seasons, etc.) throughout the entirety of the year for the structure or site. The sun positions are filtered to daytime sun positions. The sun positions may be further filtered to multiple days of the year (e.g., summer and winter solstices).

(70) The sun positions are simulated for the multiple days of the year to generate **450** a degree of shade map and/or find shade cast on one or more faces of the surface of interest. In other words, a digital sun is logically positioned relative to the site representation at a particular time (e.g., at a particular time of a particular day of the year) and the PPS determines the position of any shade cast on the surface of interest by any feature (obstruction) within the site representation. The PPS iterates through this digital sun logical positioning to obtain shade cast-data for meaningful periods of time, such as, e.g., for a solar maximum hour on a solar maximum day and a solar minimum hour on a solar minimum day wherein only daylight hours at the structure or site are considered. Any other meaningful time period may be employed, such as monthly, or weekly. The shade casting on the surface of interest is calculated for each point cloud point representing a location of the surface of interest. In one embodiment, the shade casting on the surface of interest may be calculated for a definable area, such as, e.g., a square foot, a square meter, an X-by-Y dimension, a fractional portion (e.g., one-quarter, one-eighth, etc.) of a face of the surface of interest, a face of the surface of interest, etc.

(71) The PPS generates **455** a filtered production estimate map. The PPS **400** may calculate a benefit of installing one or more elements of the project to the one or more surfaces of interest or a portion of a definable space at a location based on an appropriate metric (e.g., solar production,

cooling effect, etc.). In one embodiment, the PPS annualizes the solar hours per day. As discussed above, the imposition of shade at any position on the roof may be determined for each daylight hour of each day of the year to determine insolation while shaded for each daylight hour of each day. The insolation while shaded may be a diffuse insolation (e.g., 1%, 5%, 10%, 20%, etc.) of full insolation. By way of non-limiting example, the PPS may calculate an Insolation Value (“IV”) (for a single point, an area, a face, etc.) by masking to only points of the surface of interest (a roof of a structure) and for each point to be included in the IV, sum the irradiation values of the shaded areas of the surface of interest to obtain a Total Irradiance Subset Where Shaded (“TISWS”), and calculate a Total Irradiance Subset (“TIS”) minus TISWS, dividing by TIS, and multiplying by Total Yearly Irradiance (“TYI”) ($IV = (TIS - TISWS) / TIS * TYI$). The PPS may determine an annual insolation per roof point. For example, for each point of each face surface, the total insolation on the point is reduced by the total insolation when shaded, with the result divided by the total insolation, and that result is multiplied by the total yearly insolation. Stated otherwise, a point referenced solar access ratio ($Insolation_in_shade / Insolation_no_shade$) is calculated for each panel and summed across the whole system. By way of a non-limiting example, if 10% of the points inside a panel array are shaded such that the insolation transmitted to the panel is 80% less for those points, the summation that calculates the total transmitted insolation would contain an analog relationship between the reduction for each day of the year (instead of a generalized reduction as is currently being used for other solar access calculations).

(72) The PPS generates **460** an edge erosion map. An edge erosion map, essentially takes into consideration any requirement for allowance of space (a setback) at each edge of each face of the surface of interest such that the useable space within a face is defined by the collective setbacks for each edge of the face. For example, a building code may require a setback at each roof edge, at a ridge, a hip, a valley, etc. The PPS considers such setback requirements to make a first determination of area within each face that may be useable for the project to be proposed (e.g., a solar energy system).

(73) The PPS generates **465** an azimuth map. An azimuth relates a direction of a face of the surface of interest to a compass direction (i.e., an azimuth is a compass-relative (cardinal) orientation). In other words, in an ideal construction, two opposing roof faces may each have an azimuth relative to the opposite face of 180° (however, in practice, there may be a slight deviation such that the azimuth may be separated by something other than 180°). Furthermore, some esoteric surfaces may have pseudo-compound curves resulting in multiple faces to accomplish a turn of direction. Additionally, a surface of interest may have face orientations incidental to terrain or some other factor rather than as a result of construction.

(74) The PPS generates **470** an obstacles map. The PPS identifies obstacles on, at, or near the surface of interest, including penetrations through the roof. Obstacles and penetrations may arise from, e.g., chimneys, vents, cooling equipment, antennae, etc. Obstacles affect potential disposition of solar panels on the roof. The PPS determines the area of each face of the roof surface. A total area of a face may be reduced by the existence of an obstacle or penetration at the particular face. The PPS determines, from the total area of a face (in view of the edge erosion map) an area of the face that is useable for installation of solar energy equipment or other project.

(75) The PPS generates **475** at least one candidate installation map for the project to be proposed. The PPS acquires data related to the installation, erection, etc., of equipment to be implemented, such as, e.g., solar panel dimensions, connection requirements/limitations, costs, workmanship requirements, inspections, permits, etc. (equipment data). The equipment data comprises dimensions of the equipment, such as solar panels, that are candidates for installation to the surface of interest (a roof of the structure) or at the site. The PPS optimizes equipment placement for each appropriate roof face. For example, the PPS may consider each possible orientation of solar plans on each roof face. In other words, the PPS may consider orienting a longitudinal axis of the solar panels parallel to a side of roof surface, at a right angle to a side, or at any other suitable angle

whereby solar energy production is optimized. The PPS determines a power production of solar energy from each potential disposition of solar panels. Optimizing solar panel placement and determining solar energy production may proceed iteratively in order to achieve a best result. Optimizing may include determining a minimum or maximum of a function, such as representing one or more of a placement, production, and/or cost.

(76) According to one embodiment, the following approach can be used for calculating how many panels can be placed on a given roof face. The 3D point cloud polygon that represents the roof face can be converted to a 2D roof polygon using the dot product of the 3D polygon and a projection matrix that is calculated from the plane model's normal vector. From the 2D roof polygon, solar “panels” or “modules” can be placed onto the 2D roof polygon, using a bounding rectangle to place panels and “overflow” the roof face, as follows: 1. Create a “bounding rectangle” where the 4 points of that rectangle contain all 2D polygon points. 2. Determine based on the “bounding rectangle” length and “panel” length how many rows of panels we can fit. 3. Determine based on the “bounding rectangle” width and “panel” width how many columns of panels we can fit. 4. Iterate over the number of rows and columns to place a point for the center of each panel. 5. Remove any points where the panel will overlap the actual roof polygon and remove any points where there is an obstacle point that lies within the panel polygon. i. Convert numpy arrays to Python Shapely Polygons. ii. Iterate over each panel representing a Shapely Polygon to check for intersection between roof face edges and the panel. If intersected, remove the panel. Lastly convert the 2D panel polygon and 2D panel center points back to 3D using the inverse matrix dot product as explained above. Then the 3D location data for each panel is saved in a database.

(77) The PPS performs **480** time value of money (“TVM”) calculations for each potential proposal (arrangement of equipment, e.g., solar panels). The PPS may obtain cost data from a variety of sources, such as, e.g., a solar energy system equipment vendor, an installer, a local power provider, local inspection authority, etc. The local power cost may be based on one or more of an area in which the site is situated, like structures served by the same (or a similar cost) power provider, estimated power used at the structure, and actual power consumption. The PPS can calculate a net cost to install each potential proposal, and a net value of production to determine a return-on-investment (“ROI”), etc. The PPS can calculate seasonal cost differentials, such as may arise from a capacity to sell back power during peak solar production periods. The PPS calculates energy production from one or more solar panels based on the insolation values at the area of the roof face occupied by the one or more solar panels.

(78) The PPS may request or acquire equipment availability data. Said otherwise, the PPS may look at available inventory of solar panels so that a proposal may be based on equipment available within a definable time frame. The equipment availability data may comprise inventory-like data (equipment on hand at a supplier or suppliers), dimensional data, cost of acquisition, installation cost and scheduling, related fees (e.g., permitting, inspection(s), connection to grid, etc.), financing data, payment and payment options, and so forth. The TVM calculations **480** may provide a cost-benefit analysis for installing a solar energy system to the structure. The PPS renders output of the foregoing steps. The output may comprise one or more images of results of each step (e.g., a point cloud map, an insolation map, solar equipment disposition recommendation, etc.), cost analysis/-es. The output may be stored to a memory of the PPS server. The output may be formatted into a proposal. The proposal may be delivered for presentation to an owner of the structure or site.

(79) The PPS populates **485** proposal modules for presentation via the platform. The proposal modules may include at least a base set of Preposal™ modules and proposal modules for each potential proposal. Stated simply, the PPS generates a digital (e.g., electronic) interactive proposal to present a proposed placement of the one or more solar panels and the calculated energy production. The digital interactive proposal may be generated based on one or more of the candidate installation map and/or the TVM calculations. The PPS may facilitate closing of a sale

by, for example, enabling presentation of the proposal to a potential client (or customer) whereby the potential client becomes informed of one or more solar energy installation plans; and can provide a cost analysis for each installation plan, ordering components of a selected solar energy installation plan, scheduling (e.g., permit acquisition, inspections, connections, etc.), accepting or arranging payment (e.g., accepting a payment, arranging a payment schedule, arranging financing and coordinating distribution, etc.), and so forth. The PPS may enable presentation of the proposal by providing it over a communication network to a client computing device.

(80) Following installation, the PPS may perform automated reviews and quality control operations. The PPS may, at given intervals, acquire actual or estimated solar energy productions data regarding the installed solar energy equipment, ongoing associated costs, etc. These data may be used to refine calculations, computations, or other functions performed by the PPS to improve service to future clients.

(81) FIG. 5 diagrams an architecture of a project proposal system (PPS) **500**, such as the PPS **100**, **200**, **300** of FIGS. 1-3, respectively, for generating a digital interactive project proposal (proposal) for a structure, such as a solar energy system, according to an embodiment of the present disclosure. The PPS **500** includes a control server **510**, hereafter referred to as a computing system **510**, which may be similar in some respects to the PPS server **140** of FIG. 1. The PPS **500** comprises a network **505**, and the computing system **510**. The computing system **510** includes a system bus **525**, one or more processors **530**, an electronic memory **535**, an input/output interface (I/O interface) **520**, and a network interface **515**. The PPS **500** may include and/or connect with a client computing device over the network **505** via the network interface **515**. no

(82) The one or more processors **530** may include one or more general purpose devices, such as an Intel®, AMD®, or other standard microprocessor. The one or more processors **530** may include a special purpose processing device, such as ASIC, SoC, SiP, FPGA, PAL, PLA, FPLA, PLD, or other customized or programmable device. The one or more processors **530** may perform distributed (e.g., parallel) processing to execute or otherwise implement functionalities of the present embodiments. The one or more processors **530** may run a standard operating system and perform standard operating system functions. It is recognized that any standard operating systems may be used, such as, for example, Microsoft® Windows®, Apple® MacOS®, Disk Operating System (DOS), UNIX, IRIX, Solaris, SunOS, FreeBSD, Linux®, f/iM® OS/2® operating systems, and so forth.

(83) The electronic memory **535** may include static RAM, dynamic RAM, flash memory, one or more flip-flops, ROM, CD-ROM, DVD, disk, tape, or magnetic, optical, or other computer storage medium. The electronic memory **535** may include a plurality of program modules **545-570** and a program data **540**. The electronic memory **535** may be local to the computing system **510** or may be remote from the computing system **510** and/or distributed over the network **505**.

(84) The program modules **545-570** may include all or portions of other elements of the PPS **500**. The program modules **545-570** may run multiple operations concurrently or in parallel by or on the one or more processors **530**. In some embodiments, portions of the disclosed modules, components, and/or facilities are embodied as executable instructions embodied in hardware or in firmware, or stored on a non-transitory, machine-readable storage medium. The instructions may comprise computer program code that, when executed by a processor and/or computing device, cause a computing system to implement certain processing steps, procedures, and/or operations, as disclosed herein. The modules, components, and/or facilities disclosed herein, may be implemented and/or embodied as a driver, a library, an interface, an API, FPGA configuration data, firmware (e.g., stored on an EEPROM), and/or the like. In some embodiments, portions of the modules, components, and/or facilities disclosed herein are embodied as machine components, such as general and/or application-specific devices, including, but not limited to: circuits, integrated circuits, processing components, interface components, hardware controller(s), storage controller(s), programmable hardware, FPGAs, ASICs, and/or the like.

(85) The program data **540** stored on the electronic memory **535** may include data generated by the PPS **500**, such as by the program modules **545-570** or other modules. The stored program data **540** may be organized as one or more databases.

(86) The I/O interface **520** may facilitate interfacing with one or more input devices and/or one or more output devices. The input device(s) may include a keyboard, mouse, touch screen, light pen, tablet, microphone, sensor, or other hardware with accompanying firmware and/or software. The output device(s) may include a monitor or other display, printer, speech or text synthesizer, switch, signal line, or other hardware with accompanying firmware and/or software.

(87) The network interface **515** may facilitate communication with other computing devices and/or networks **505**, such as the Internet and/or other computing and/or communications networks. The network interface **515** may be equipped with conventional network connectivity, such as, for example, Ethernet (IEEE 802.3), Token Ring (IEEE 802.5), Fiber Distributed Datalink Interface (FDDI), or Asynchronous Transfer Mode (ATM). Further, the computer may be configured to support a variety of network protocols such as, for example, Internet Protocol (IP), Transfer Control Protocol (TCP), Network File System over UDP/TCP, Server Message Block (SMB), Microsoft® Common Internet File System (CIFS), Hypertext Transfer Protocols (HTTP), Direct Access File System (DAFS), File Transfer Protocol (FTP), Real-Time Publish Subscribe (RTPS), Open Systems Interconnection (OSI) protocols, Simple Mail Transfer Protocol (SMTP), Secure Shell (SSH), Secure Socket Layer (SSL), and so forth.

(88) The system bus **525** may facilitate communication and/or interaction between the other components of the PPS **500**, including the one or more processors **530**, the electronic memory **535**, the I/O interface **520**, and the network interface **515**.

(89) As noted, the PPS **500** includes various program modules **545-570** (or engines, elements, or components) (hereafter, “modules”) to implement functionalities of the PPS **500** and to generate, access, and/or manipulate the program data **540** stored in the electronic memory **535**. Each of the various modules **545-570** may comprise machine-readable instructions that may be read and used by the one or more processors **530** to perform various functions of the PPS **500**. The modules **545-570** can include a vertex detection neural network (“VDN”) **545**, an edge detection neural network (“EDN”) **550**, a face detection engine (“FDE”) **555**, a 3D planes detection engine (3DE) **560**, and other appropriate software modules **570**, etc. The other appropriate software modules (“other modules”) **570** may include disparate modules, such as an insolation analysis neural network (IAN), a placement geometry engine (“PGE”), a cost analysis module (“CAM”), a scheduling and monitoring module (“SMM”), etc. There may be more or fewer software modules **545-570** than shown in FIG. 5 and described herein.

(90) The processor **530** is configurable to enable the processor **530** to read and execute computer-executable instructions, such as computer-executable instructions to perform the methods described herein. The computer-executable instructions may be stored in the memory **535**, or in another memory accessible to the processor **530**. The I/O interface **520** and/or the network interface **515** may enable to processor **530** to communicate with the memory **535** and/or another memory, and to communicate with, for example, a tablet computer, such as the tablet computer **150**, **320** of, respectively, FIGS. 1 and 3, etc.

(91) The memory **535** may store computer-readable and executable instructions to enable the processor **530** to perform the methods described herein. More particularly, the memory **535** may store instructions to enable the processor **530** to operate the VDN module **545** to generate, manipulate, interpolate, etc. a point cloud to identify each vertex representing an intersection of at least three planes in the point cloud model. The VDN module **545** may further enable the processor **530** to activate or employ the EDN module **550**. The EDN module **550** may enable the processor **530** construct a bounding box around each array of next-neighbor points of the point cloud representing an intersection of two planes, and including two vertices. The EDN module **550** may further enable the processor **530** to define an edge of a polygon (representing an edge of a face of

the surface of interest) from each line so identified. The EDN 550 may enable the processor 530 to employ the FDE 555 to construct a face of the surface of interest based on edges detected by the EDN 550. The FDE 555 may enable the processor 530 to employ the 3DE 560 to identify 3D planes representing faces of the surface of interest. The 3DE 560, in turn, may enable the processor 530 to employ the SIM 565 to run sun simulations relative to the site. The SIM 565 may enable the processor 530 to IAN to generate insolation data (as described elsewhere herein) relative to one or more of: each point of the point cloud representing a location at a face of the surface of interest, an array of points representing a definable area of a face of the surface of interest, an array of points representing entire area of a face of the surface of interest, the entire area of the surface of interest, etc. The IAN may enable the processor 530 to employ the PGE to ascertain one or more physical dispositions for equipment to be proposed for the project. The PGE may consider physical dimensions and/or geometry of the equipment, availability of equipment, etc., along with limitations imposed by, e.g., obstacles, setbacks, etc. The PGE may be recursively called by the processor 530 based on data that may be generated via the CAM. The PGE may generate data to be populated into a Preposal™ and/or proposal, such as images, text, etc. The PGE may enable the processor 530 to employ the CAM to perform a variety of cost analyses, including cost of implementation, TVM, ROI, FV-forecast, etc. The CAM may generate a cost table, an inventory table, etc., and at least some of the data generated by the CAM may be included in a proposal. The CAM, or another financial module, may also enable the processor 530 to perform financial transactions, such as to accept payment from a client, to remit payment to a vendor, etc. The CAM may enable the processor 530 to employ the SMM to perform scheduling of work and equipment to implement a project. The SMM may enable the processor 530 to, via the network interface 515 and the network 505, interact with vendors, contractors, etc., to request scheduling of equipment, installers, inspectors, etc. The SMM may further enable the processor 530 to interact with the client for scheduling and reporting purposes. The SMM and the CAM may each iteratively enable the processor 530 to invoke the SMM or the CAM to update relevant data of either module, as well as to invoke other modules as may, from time to time, be needed to perform the functions of the PPS 500. Additional other modules 570 are anticipated by the present disclosure.

(92) The network interface 515 may enable communication of the results generated by the modules 545-570 to a memory for retention storage and/or to another system.

(93) FIGS. 6A and 6B illustrate scenarios or models for interfacing with the platform of a system to propose a digital interactive proposal (a project proposal system “PPS”), such as the PPSs of FIGS. 1-5, according to an embodiment of the present disclosure. Through an entity onboarding process an ideal structure for the entity can be identified for interfacing with the platform. Consider four example scenarios: Installer model, Sales Org model, Hybrid, and Standard. Each scenario can signal or otherwise indicate how the platform should clone proposal templates and allow templates to inherit certain attributes, including but not limited to logos, imagery, custom pages, design preferences, restrictions imposed by an authority having jurisdiction (AHJ restrictions), fire setbacks, orientations, roof plane requirements, equipment, equipment scenarios, pricing redlines, pricing ceilings & floors, adders and their accompanying pricing logic, discounts, incentives, lending options, API credentials, document management, and others.

(94) The above scenario (or model) structure allows a sales representative (“sales rep”) to log into sales rep facing interface to the platform and order a pre/proposal with basic information. Based on company structure, geolocation, or some combination the sales representative is able to receive an automated Preposal™ and proposal template that fits a present selling scenario of the sales rep. When the request is submitted, it may enter a sophisticated queue system. A proposal engine of the platform can automate the design and populate data into an automated template. A quality assurance person can review the contents and then finish the process by digitally delivering the proposal to the end user via the platform, as described above with reference to FIG. 3.

(95) In FIG. 6A, a relationship of data within or available to the PPS is **600** shown. A master account **610** may be accessed by an appropriate user, such as an administrator of an entity employing the PPS **600** to design and propose a project. A number of subordinate accounts (sub accounts) **620** are shown, with the sub account **622** representing a first sub account, and the sub account **624** representing a nth sub account. In other words, there may be any number of sub accounts **620** for the entity. Each sub account **620** is related to a collection of data and data structures. For example, each sub account **620** may be related to standard templates for use in designing and/or presenting a proposal, custom templates, users, a library of proposals (e.g., past proposals, current proposals, proposal shells, etc.), data related to each of these, etc. The templates, data, etc., may be used in conjunction with preset content for the platform, such as in conjunction with the preset content modules **344** of FIG. 3, to populate or configure a selected preset content module **348** (see FIG. 3), etc. In the context of FIGS. 6A and 6B, “related to” may mean any of the following: owns, controls, implements, uses, generates, receives, sends, etc. In other words, a user may access the first sub account **622** to interact with a proposal by using standard templates and custom templates, retrieving a current or past proposal, or a proposal shell, populating the proposal with data from various sources, transmit the proposal to, e.g., a sales rep, etc. The master account **610** has to all access of each of the sub accounts **620**.

(96) FIG. 6B depicts template access for the PPS **600**. The master account **610**, similar to having access to all sub accounts **620** of FIG. 6A, can access (including, creating, modifying, deleting, etc.) all templates **630** within the PPS **600**. The PPS **500** may employ any number of templates **630**. A first template **632** and a nth template **634** are identified. Each template **630** may relate to a particular vendor, supplier, installer, etc., that may be considered for a proposal being designed at the PPS **600**. By way of non-limiting example, the first template **632** may relate to a supplier of solar energy system equipment and installation service. The first template **632** may include logos, login data, tax tables, scheduling data, etc., related to the particular supplier such that the template, when used with or as a selected preset content module **348**, a presentation via the platform will display data related to the supplier, assisting in the apparent seam lessness of presenting the proposal to a potential client. The master account **610** may access, create, generate, edit, delete, etc., each template of the PPS **600**. Each template **630** may also be associated to one or more of the sub accounts **620** of FIG. 6A.

EXAMPLES

(97) Some examples of embodiments of the present disclosure are now provided.

(98) Example 1. A system to generate a model of a definable space (e.g., at a location), comprising: a network interface to couple to one or more client computing devices over a communication network; memory to store one or more of imagery, point cloud data, and computer-readable instructions that when executed by a processor cause the system to perform operations; and one or more processors to execute the computer-readable instructions to cause the system to perform operations to: identify, within a point cloud for a definable space, perimeter points of one or more top surfaces of an object of interest in the definable space, based on imagery of the definable space, wherein the perimeter points are points of the point cloud; determine a perimeter of each top surface of the one or more top surfaces (e.g., based on the perimeter points); determine a two-dimensional (2D) face of each top surface of the one or more top surfaces; determine a three-dimensional (3D) plane of each top surface of the one or top surfaces; generate a representation of each top surface of the one or more top surfaces, based on the corresponding perimeter points, perimeter, two-dimensional face, and three dimensional plane; and join the representations of the one or more top surfaces to create a three-dimensional (3D) model of at least a portion of the object.

(99) Example 2. The system of Example 1, wherein the one or more processors are further to execute the computer-readable instructions to cause the system to perform operations to receive point cloud data for the definable space, the point cloud data including the point cloud.

(100) Example 3. The system of Example 1, wherein the one or more processors are further to execute the computer-readable instructions to cause the system to perform operations to: receive a plurality of two-dimensional orthogonal images of the definable space; and generate the point cloud data from the plurality of two-dimensional orthogonal images. Alternatively, the operations can be to receive stereo pair images of the definable space; and generate the point cloud data from the stereo pair images.

(101) Example 4. The system of Example 1, wherein the one or more processors are further to execute the computer-readable instructions to cause the system to perform operations to add to the 3D model a representation of one or more vertical portions of the object of interest extending from the one or more top surfaces to one of a ground plane and another top surface of the one or more top surfaces.

(102) Example 5. The system of Example 1, wherein the one or more processors are further to execute the computer-readable instructions to cause the system to perform operations to model the point cloud data to generate a site representation of the definable space, wherein the site representation includes the object of interest and one or more objects adjacent to the object of interest.

(103) Example 6. The system of Example 1, wherein modeling the point cloud data to generate the site representation comprises generating a 3D mesh.

(104) Example 7. The system of Example 1, wherein identifying the perimeter points of the one or more top surfaces comprises processing the imagery of the definable space with a vertex neural network trained to recognize vertices of top surfaces of the object of interest within the imagery of the definable space.

(105) Example 8. The system of Example 1, wherein identifying the perimeter points of the one or more top surfaces comprises: processing the imagery of the definable space with a perimeter neural network trained to recognize a perimeter of a top surface; and identifying points of the point cloud that correspond to the perimeter.

(106) Example 9. The system of Example 1, wherein determining the perimeter of each top surface is based on connecting the perimeter points.

(107) Example 10. The system of Example 1, wherein determining the perimeter of each top surface comprises processing the imagery of the definable space with a perimeter neural network trained to recognize a perimeter of a top surface.

(108) Example 11. A computer-implemented method to generate a model (e.g., of a site, definable space at a location), comprising: identifying, within a point cloud for a definable space, perimeter points of one or more top surfaces of an object of interest in the definable space, based on imagery of the definable space, wherein the perimeter points are points of the point cloud; determining a perimeter of each top surface of the one or more top surfaces; determining a two-dimensional (2D) face of each top surface of the one or more top surfaces; determining a three-dimensional (3D) plane of each top surface of the one or more top surfaces; and generating a representation of each top surface of the one or more top surfaces, based on the corresponding perimeter points, perimeter, two-dimensional face, and three dimensional plane; and joining the representations of the one or more top surfaces to create a three-dimensional (3D) model of at least a portion of the object.

(109) Example 12. The method of Example 11, further comprising: receiving point cloud data for the definable space, the point cloud data including the point cloud.

(110) Example 13. The method of Example 11, further comprising: receiving a plurality of two-dimensional (e.g., orthogonal, stereo pair) images of the definable space; and generating the point cloud data from the plurality of two-dimensional images.

(111) Example 14. The method of Example 11, further comprising adding to the 3D model a representation of one or more vertical portions of the object of interest extending from the one or more top surfaces to one of a ground plane and another top surface of the one or more top surfaces.

(112) Example 15. The method of Example 11, further comprising modeling the point cloud data to

generate a site representation of the definable space, wherein the site representation includes the object of interest and one or more objects adjacent to the object of interest.

(113) Example 16. The method of Example 11, wherein modeling the point cloud data to generate the site representation comprises generating a 3D mesh.

(114) Example 17. The method of Example 11, wherein modeling the point cloud data to generate the representation comprises generating a three-dimensional polyhedron model.

(115) Example 18. The method of Example 11, wherein identifying the perimeter points of the one or more top surfaces comprises processing the imagery of the definable space with a vertex neural network trained to recognize vertices of top surfaces of the object of interest within the imagery of the definable space.

(116) Example 19. The method of Example 11, wherein identifying the perimeter points of the one or more top surfaces comprises: processing the imagery of the definable space with a perimeter neural network trained to recognize a perimeter of a top surface; and identifying points of the point cloud that correspond to the perimeter.

(117) Example 20. The method of Example 11, where in the imagery is one or more two-dimensional orthogonal composite images of the definable space.

(118) Example 21. The method of Example 20, where in the one or more two-dimensional orthogonal composite images are created from a flattened version of the point cloud.

(119) Example 22. The method of Example 11, wherein determining the perimeter of each top surface is based on connecting the perimeter points.

(120) Example 23. The method of Example 11, wherein determining the perimeter of each top surface comprises processing the imagery of the definable space with a perimeter neural network trained to recognize a perimeter of a top surface.

(121) Example 24. The method of Example 11, wherein determining the perimeter of each top surface comprises: processing the imagery of the definable space with a perimeter neural network trained to find a bounding shape for each top surface; algorithmically placing a set of the perimeter points inside of the bounding shape; and connecting perimeter points within each bounding shape to find the perimeter.

(122) Example 25. The method of claim 306B, wherein finding the perimeter comprises determining the 2D face of the one or more top surfaces.

(123) Example 26. The method of Example 11, wherein determining the two-dimensional (2D) face of each top surface comprises using a cycle basis algorithm.

(124) Example 27. The method of Example 11, wherein determining a 3D plane of the one or more top surfaces comprises: using the 2D face of a given top surface of the one or more top surfaces to segment out points of the point cloud that belong to the given top surface; and determining a plane that runs through the points of the given top surface.

(125) Example 28. The method of Example 27, wherein determining the plane comprises utilizing an iterative algorithm.

(126) Example 29. The method of Example 27, wherein determining the plane comprises utilizing a random sample consensus algorithm.

(127) While this specification contains many specific implementation details, these should not be construed as limitations on the scope of any inventions or of what may be claimed, but rather as descriptions of features specific to particular implementations of the systems and methods described herein. Certain features that are described in this specification in the context of separate implementations can also be implemented and/or arranged in combination in a single implementation. Conversely, various features that are described in the context of a single implementation can also be implemented and arranged in multiple implementations separately or in any suitable sub combination. Moreover, although features may be described above as acting in certain combinations and even initially claimed as such, one or more features from a claimed combination can in some cases be excised from the combination, and the claimed combination may

be directed to a subcombination or variation of a subcombination.

(128) Similarly, while operations are depicted in the drawings in a particular order, this should not be understood as requiring that such operations be performed in the particular order shown or in sequential order, or that all illustrated operations be performed, to achieve desirable results. In some cases, the actions recited in the claims can be performed in a different order and still achieve desirable results. In addition, the processes depicted in the accompanying figures do not necessarily require the particular order shown, or sequential order, to achieve desirable results.

(129) In certain circumstances, multitasking and parallel processing may be advantageous. Moreover, the separation of various system components in the implementations described above should not be understood as requiring such separation in all implementations, and it should be understood that the described program components and systems can generally be integrated together in a single software product or packaged into multiple software products.

(130) Having described some illustrative implementations, implementations, illustrative embodiments, and embodiments, it is apparent that the foregoing is illustrative and not limiting, having been presented by way of example. In particular, although many of the examples presented herein involve specific combinations of method acts or system elements, those acts and those elements may be combined in other ways to accomplish the same objectives. Acts, elements, and features discussed only in connection with one implementation are not intended to be excluded from a similar role in other implementations.

(131) The phraseology and terminology used herein is for the purpose of description and should not be regarded as limiting. The use of “including,” “comprising,” “having,” “containing,” “involving,” “characterized by,” “characterized in that,” and variations thereof herein, is meant to encompass the items listed thereafter, equivalents thereof, and additional items, as well as alternate implementations consisting of the items listed thereafter exclusively. In one implementation, the systems and methods described herein consist of one, each combination of more than one, or all of the described elements, acts, or components.

(132) Any references to implementations, arrangements, elements, or acts of the systems and methods herein referred to in the singular may also embrace implementations including a plurality of these elements, and any references in plural to any implementation, arrangement, element, or act herein may also embrace implementations including only a single element. References in the singular or plural form are not intended to limit the presently disclosed systems or methods, or their components, acts, or elements to single or plural configurations. References to any act or element being based on any information, act, or element may include implementations where the act or element is based at least in part on any information, act, or element.

(133) It should be understood that no claim element herein is to be construed under the provisions of 35 U.S.C. § 112(f) unless the element is expressly recited using the phrase “means for.”

(134) It should be noted that although the diagrams herein may show a specific order and composition of method steps, it is understood that the order of these steps may differ from what is depicted. For example, two or more steps may be performed concurrently or with partial concurrence. Also, some method steps that are performed as discrete steps may be combined, steps being performed as a combined step may be separated into discrete steps, the sequence of certain processes may be reversed or otherwise varied, and the nature or number of discrete processes may be altered or varied. The order or sequence of any element or apparatus may be varied or substituted according to alternative embodiments. Accordingly, all such modifications are intended to be included within the scope of the present disclosure as defined in the appended claims. Such variations will depend on the machine-readable media and hardware systems chosen and on designer choice. It is understood that all such variations are within the scope of the disclosure. Likewise, software and web implementations of the present disclosure could be accomplished with standard programming techniques with rule-based logic and other logic to accomplish the various database searching steps, correlation steps, comparison steps, and decision steps.

(135) It will be obvious to those having skill in the art that many changes may be made to the details of the above-described embodiments without departing from the underlying principles of the invention. The scope of the present invention should, therefore, be determined only by the following claims.

Claims

1. A system to generate a model, comprising: a network interface to couple to one or more client computing devices over a communication network; memory to store one or more of imagery, point cloud data, and computer-readable instructions that when executed by a processor cause the system to perform operations; and one or more processors to execute the computer-readable instructions to cause the system to perform operations to: identify, within a point cloud for a definable space, perimeter points of a plurality of top surfaces of an object of interest in the definable space, based on imagery of the definable space, wherein the perimeter points are points of the point cloud; determine a perimeter of each top surface of the plurality of top surfaces; determine a two-dimensional (2D) face of each top surface of the plurality of top surfaces; determine a three-dimensional (3D) plane of each top surface of the plurality of top surfaces; generate a representation of each top surface of the plurality of top surfaces, based on the corresponding perimeter points, perimeter, two-dimensional face, and three-dimensional plane; and join the representations of the plurality of top surfaces to create a three-dimensional (3D) model of at least a portion of the object.
2. The system of claim 1, wherein the one or more processors are further to execute the computer-readable instructions to cause the system to perform operations to receive point cloud data for the definable space, the point cloud data including the point cloud.
3. The system of claim 1, wherein the one or more processors are further to execute the computer-readable instructions to cause the system to perform operations to: receive a plurality of two-dimensional images of the definable space; and generate the point cloud data from the plurality of two-dimensional images.
4. The system of claim 1, wherein the one or more processors are further to execute the computer-readable instructions to cause the system to perform operations to add to the 3D model a representation of one or more vertical portions of the object of interest extending from the plurality of top surfaces to one of a ground plane and another top surface of the plurality of top surfaces.
5. The system of claim 1, wherein the one or more processors are further to execute the computer-readable instructions to cause the system to perform operations to model the point cloud to generate a site representation of the definable space, wherein the site representation includes the object of interest and one or more objects adjacent to the object of interest.
6. The system of claim 1, wherein to model the point cloud to generate the site representation, the one or more processors are further to execute the computer-readable instructions to cause the system to perform operations to generate a 3D mesh.
7. The system of claim 1, wherein to identify the perimeter points of the plurality of top surfaces, the one or more processors are further to execute the computer-readable instructions to cause the system to perform operations to process the imagery of the definable space with a vertex neural network trained to recognize vertices of top surfaces of the object of interest within the imagery of the definable space.
8. The system of claim 1, wherein to identify the perimeter points of the plurality of top surfaces, the one or more processors are further to execute the computer-readable instructions to cause the system to perform operations to: process the imagery of the definable space with a perimeter neural network trained to recognize a perimeter of a top surface; and identify points of the point cloud that correspond to the perimeter.
9. The system of claim 1, wherein to determine the perimeter of each top surface, the one or more

processors are further to execute the computer-readable instructions to cause the system to perform operations based on connecting the perimeter points.

10. The system of claim 1, wherein to determine the perimeter of each top surface, the one or more processors are further to execute the computer-readable instructions to cause the system to perform operations to process the imagery of the definable space with a perimeter neural network trained to recognize a perimeter of a top surface.

11. A computer-implemented method to generate a model, comprising: identifying, within a point cloud for a definable space, perimeter points of a plurality of top surfaces of an object of interest in the definable space, based on imagery of the definable space, wherein the perimeter points are points of the point cloud; determining a perimeter of each top surface of the plurality of top surfaces; determining a two-dimensional (2D) face of each top surface of the plurality of top surfaces; determining a three-dimensional (3D) plane of each top surface of the plurality of top surfaces; and generating a representation of each top surface of the plurality of top surfaces, based on the corresponding perimeter points, perimeter, two-dimensional face, and three dimensional plane; and joining the representations of the plurality of top surfaces to create a three-dimensional (3D) model of at least a portion of the object.

12. The method of claim 11, further comprising: receiving point cloud data for the definable space, the point cloud data including the point cloud.

13. The method of claim 11, further comprising: receiving a plurality of two-dimensional images of the definable space; and generating the point cloud from the plurality of two-dimensional images.

14. The method of claim 11, further comprising adding to the 3D model a representation of one or more vertical portions of the object of interest extending from the plurality of top surfaces to one of a ground plane and another top surface of the plurality of top surfaces.

15. The method of claim 11, further comprising modeling the point cloud to generate a site representation of the definable space, wherein the site representation includes the object of interest and one or more objects adjacent to the object of interest.

16. The method of claim 11, wherein modeling the point cloud to generate the site representation comprises generating a 3D mesh.

17. The method of claim 11, wherein identifying the perimeter points of the plurality of top surfaces comprises processing the imagery of the definable space with a vertex neural network trained to recognize vertices of top surfaces of the object of interest within the imagery of the definable space.

18. The method of claim 11, wherein determining the perimeter of each top surface is based on connecting the perimeter points.

19. The method of claim 11, wherein determining the two-dimensional (2D) face of each top surface comprises using a cycle basis algorithm.

20. The method of claim 11, wherein determining a 3D plane of the plurality of top surfaces comprises: using the 2D face of a given top surface of the plurality of top surfaces to segment out points of the point cloud that belong to the given top surface; and determining a plane that runs through the points of the given top surface.
