

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12412822
Kind Code	B2
Date of Patent	September 09, 2025
Inventor(s)	Lee; Yun Tae et al.

Semiconductor chip and semiconductor package including the same

Abstract

A semiconductor package includes: a semiconductor chip including a front end of line (FEOL) layer and a first back end of line (BEOL) layer disposed on the FEOL layer; and a printed circuit board including a wiring layer and a second BEOL layer disposed on the wiring layer, wherein the semiconductor chip is mounted on the printed circuit board so that the first and second BEOL layers are connected to each other while facing each other, and the second BEOL layer includes a wiring for power transmission.

Inventors:	Lee; Yun Tae (Suwon-si, KR), Lee; Jin Won (Suwon-si, KR)
Applicant:	SAMSUNG ELECTRO-MECHANICS CO., LTD. (Suwon-si, KR)
Family ID:	86992232
Assignee:	SAMSUNG ELECTRO-MECHANICS CO., LTD. (Suwon-si, KR)
Appl. No.:	17/743740
Filed:	May 13, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230215793 A1	Jul. 06, 2023

Foreign Application Priority Data

KR	10-2021-0194291	Dec. 31, 2021
KR	10-2022-0027234	Mar. 03, 2022

Publication Classification

Int. Cl.: H01L23/498 (20060101); H01L23/00 (20060101); H01L23/14 (20060101);
H01L23/522 (20060101); H01L23/528 (20060101)

U.S. Cl.:

CPC H01L23/49833 (20130101); H01L23/145 (20130101); H01L23/49816 (20130101);
H01L23/49822 (20130101); H01L23/49838 (20130101); H01L23/5226 (20130101);
H01L23/5283 (20130101); H01L23/5286 (20130101); H01L24/16 (20130101);
H01L2224/16013 (20130101); H01L2224/16227 (20130101); H01L2224/16237
(20130101)

Field of Classification Search

CPC: H01L (23/49833); H01L (23/145); H01L (23/49816); H01L (23/49822); H01L
(23/49838); H01L (23/5226); H01L (23/5283); H01L (23/5286); H01L (24/16); H01L
(2224/16013); H01L (2224/16227); H01L (2224/16237)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
11329047	12/2021	Wang	N/A	H10D 86/0212
2008/0277765	12/2007	Lane	257/E21.546	H01L 21/78
2015/0333004	12/2014	Jomaa	257/774	H01L 23/5226
2017/0338206	12/2016	Seo	N/A	H01L 23/53238
2018/0047756	12/2017	Yoshida	N/A	H01L 25/0657
2018/0102470	12/2017	Das	N/A	H01P 7/086
2019/0319626	12/2018	Dabral	N/A	G06F 13/4022
2020/0020610	12/2019	Lim	N/A	H01L 24/02
2021/0028061	12/2020	Farooq et al.	N/A	N/A
2021/0050339	12/2020	Yoo et al.	N/A	N/A
2022/0165669	12/2021	Yu	N/A	H01L 24/80
2022/0199517	12/2021	Dabral	N/A	H01L 23/522
2022/0317179	12/2021	Kwon	N/A	G01R 31/2856
2022/0359466	12/2021	Kim	N/A	H01L 25/50
2023/0069490	12/2022	Lee	N/A	H01L 23/49838
2023/0085890	12/2022	Dabral	257/621	H01L 24/18
2024/0128239	12/2023	Song	N/A	H01L 24/16
2024/0213109	12/2023	Ko	N/A	H01L 23/3178
2024/0222274	12/2023	Akkinepally	N/A	H01L 24/16

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
112530882	12/2020	CN	H01L 21/02516
112530906	12/2020	CN	H01L 23/495
117434317	12/2023	CN	G01R 1/06783
117729779	12/2023	CN	H01L 23/3107
118299373	12/2023	CN	H01L 21/76898
20130037550	12/2012	KR	N/A
20220016689	12/2021	KR	N/A
202201740	12/2021	TW	G11C 5/06

OTHER PUBLICATIONS

KR-20220016689-A, You Se Ho et al, Google Machine Language Translation (Year: 2024). cited by examiner

Primary Examiner: Lebentritt; Michael

Attorney, Agent or Firm: Morgan Lewis & Bockius LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S)

(1) This application claims benefit of priority to Korean Patent Applications Nos. 10-2021-0194291 filed on Dec. 31, 2021 and 10-2022-0027234 filed on Mar. 3, 2022 in the Korean Intellectual Property Office, the disclosures of which are incorporated herein by reference in its entirety.

TECHNICAL FIELD

(2) The present disclosure relates to a semiconductor package in which a semiconductor chip is mounted on a printed circuit board such as a package board and/or an interposer board, and a semiconductor chip included in the same.

BACKGROUND

(3) Recently, demand for high-performance semiconductors has increased. Due to a speed increase and performance improvement of such semiconductors, the number of layers of a semiconductor chip has increased or a circuit density of the semiconductor chip has increased, and accordingly, manufacturing costs of the semiconductor chip has significantly increased. In addition, a yield problem of the semiconductor chip has also occurred. For example, according to the manufacture of the high-performance semiconductors, the number of layers of a back end of line (BEOL) of the semiconductor chip may increase or a circuit density of the semiconductor chip may increase. Accordingly, manufacturing costs of the semiconductor chip may be significantly increased, and a cost problem may occur due to a decrease in yield of the semiconductor chip caused by the occurrence of a defect during manufacturing of the semiconductor chip.

SUMMARY

(4) An aspect of the present disclosure may provide a semiconductor chip of which a process cost may be decreased, and a semiconductor package including the same.

(5) An aspect of the present disclosure may also provide a semiconductor chip capable of solving a cost problem due to a decrease in yield of the semiconductor chip, and a semiconductor package including the same.

(6) According to an aspect of the present disclosure, a portion of a back end of line (BEOL) layer of a semiconductor chip including wirings for power transmission may be formed on a printed circuit

board such as a package board and/or an interposer board.

(7) According to an aspect of the present disclosure, a semiconductor package may include: a semiconductor chip including a front end of line (FEOL) layer and a first back end of line (BEOL) layer disposed on the FEOL layer; and a printed circuit board including a wiring layer and a second BEOL layer disposed on the wiring layer, wherein the semiconductor chip is mounted on the printed circuit board so that the first and second BEOL layers are connected to each other, and the second BEOL layer includes a wiring for power transmission.

(8) According to another aspect of the present disclosure, a semiconductor package may include: a semiconductor chip including a first BEOL layer; an interposer board including a second BEOL layer; and a package board including a wiring layer, wherein the semiconductor chip is mounted on the interposer board, the interposer board is mounted on the package board, the first and second BEOL layers are connected to each other, and the second BEOL layer includes a wiring for power transmission.

(9) According to another aspect of the present disclosure, a semiconductor chip may include: a FEOL layer including a plurality of circuit units each including a plurality of transistor elements; and a BEOL layer disposed on the FEOL layer and including a wiring unit electrically connected to the plurality of circuit units, wherein the wiring unit does not include a trace pattern for power transmission interconnecting at least two of the plurality of circuit units.

(10) According to another aspect of the present disclosure, a semiconductor package may include: a semiconductor chip including a FEOL layer and a first BEOL layer disposed on the FEOL layer, the FEOL layer including a first circuit unit including a plurality of first transistor elements and a second circuit unit including a plurality of second transistor elements, and the first BEOL layer including a first wiring unit electrically connected to the first and second circuit units; and a printed circuit board including a second BEOL layer including a second wiring unit electrically connected to the first wiring unit, wherein the semiconductor chip is mounted on the printed circuit board, the first wiring unit does not include a trace pattern for power transmission interconnecting the first and second circuit units within the first BEOL layer, and the second wiring unit includes a trace pattern for power transmission interconnecting the first and second circuit units within the second BEOL layer.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) The above and other aspects, features, and advantages of the present disclosure will be more clearly understood from the following detailed description taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a schematic block diagram illustrating an example of an electronic device system;

(3) FIG. 2 is a schematic perspective view illustrating an example of an electronic device;

(4) FIG. 3 is a schematic cross-sectional view illustrating a semiconductor package according to an exemplary embodiment in the present disclosure;

(5) FIG. 4 is a schematic cross-sectional view illustrating a semiconductor package according to another exemplary embodiment in the present disclosure;

(6) FIG. 5 is a schematic cross-sectional view illustrating a semiconductor package according to another exemplary embodiment in the present disclosure;

(7) FIG. 6 is a schematic cross-sectional view illustrating wirings for power transmission within a semiconductor package after applying a portion of a back end of line (BEOL) layer of a semiconductor chip to a printed circuit board;

(8) FIG. 7A is a schematic cross-sectional view illustrating a plurality of metal layers of a BEOL layer of a semiconductor chip before applying a portion of the BEOL layer of the semiconductor

chip to a printed circuit board;

(9) FIGS. 7B and 7C are schematic plan views illustrating an M1 layer and an M2 layer of the plurality of metal layers of FIG. 7A, respectively;

(10) FIG. 8A is a schematic cross-sectional view illustrating a plurality of metal layers of a BEOL layer of a semiconductor chip after applying a portion of the BEOL layer of the semiconductor chip to a printed circuit board;

(11) FIGS. 8B and 8C are schematic plan views illustrating an M1 layer and an M2 layer of the plurality of metal layers of FIG. 8A, respectively;

(12) FIGS. 9A and 9B are schematic cross-sectional views illustrating internal structures of a semiconductor chip before and after applying a portion of a BEOL layer of the semiconductor chip to a printed circuit board, respectively;

(13) FIG. 9C is a schematic cross-sectional view illustrating a modified example of the semiconductor chip of FIG. 9B;

(14) FIG. 10 is a schematic cross-sectional view illustrating a package board according to an exemplary embodiment in the present disclosure;

(15) FIG. 11 is a schematic cross-sectional view illustrating a package board according to another exemplary embodiment in the present disclosure;

(16) FIG. 12 is a schematic cross-sectional view illustrating an interposer board according to an exemplary embodiment in the present disclosure;

(17) FIG. 13 is a schematic cross-sectional view illustrating an interposer board according to another exemplary embodiment in the present disclosure;

(18) FIG. 14 is a schematic cross-sectional view illustrating an interposer board according to another exemplary embodiment in the present disclosure; and

(19) FIG. 15 is a schematic cross-sectional view illustrating an interposer board according to another exemplary embodiment in the present disclosure.

DETAILED DESCRIPTION

(20) Hereinafter, exemplary embodiments in the present disclosure will be described with reference to the accompanying drawings. In the accompanying drawings, shapes, sizes, and the like, of components may be exaggerated or shortened for clarity.

(21) Herein, the phrase “in cross section” may refer to a cross-sectional shape of a target when the target is vertically cut or a cross-sectional shape of the target when the target is viewed in side view. In addition, the phrase “in plan view” may refer to a shape of the target when the target is horizontally cut or a shape of the target when the target is viewed in top view or bottom view.

(22) Herein, a lower side, a lower portion, a lower surface, and the like, are used to refer to a direction toward a mounted surface of the semiconductor package including an organic interposer in relation to cross sections of the drawings, while an upper side, an upper portion, an upper surface, and the like, are used to refer to an opposite direction to the direction. However, these directions are defined for convenience of explanation, and the claims are not particularly limited by the directions defined as described above.

(23) The meaning of a “connection” of a component to another component in the description conceptually includes an indirect connection through an adhesive layer as well as a direct connection between two components. In addition, “electrically connected” conceptually includes a physical connection and a physical disconnection. It may be understood that when an element is referred to with terms such as “first” and “second”, the element is not limited thereby. They may be used only for a purpose of distinguishing the element from the other elements, and may not limit the sequence or importance of the elements. In some cases, a first element may be referred to as a second element without departing from the scope of the claims set forth herein. Similarly, a second element may also be referred to as a first element.

(24) The term “an exemplary embodiment” used herein does not refer to the same exemplary embodiment, and is provided to emphasize a particular feature or characteristic different from that

of another exemplary embodiment. However, exemplary embodiments provided herein are considered to be able to be implemented by being combined in whole or in part one with one another. For example, one element described in a particular exemplary embodiment, even if it is not described in another exemplary embodiment, may be understood as a description related to another exemplary embodiment, unless an opposite or contradictory description is provided therein.

(25) Terms used herein are used only in order to describe an exemplary embodiment rather than limiting the present disclosure. In this case, singular forms include plural forms unless interpreted otherwise in context.

(26) Electronic Device

(27) FIG. 1 is a schematic block diagram illustrating an example of an electronic device system.

(28) Referring to FIG. 1, an electronic device **1000** may accommodate a mainboard **1010** therein. The mainboard **1010** may include chip-related components **1020**, network related components **1030**, other components **1040**, and the like, physically or electrically connected thereto. These components may be connected to others to be described below to form various signal lines **1090**.

(29) The chip-related components **1020** may include a memory chip such as a volatile memory (for example, a dynamic random access memory (DRAM)), a non-volatile memory (for example, a read only memory (ROM)), a flash memory, or the like; an application processor such as a central processor (for example, a central processing unit (CPU)), a graphics processor (for example, a graphics processing unit (GPU)), a digital signal processor, a cryptographic processor, a microprocessor, a microcontroller, or the like; and a logic chip such as an analog-to-digital (ADC) converter, an application-specific integrated circuit (ASIC), or the like. However, the chip-related components **1020** are not limited thereto, and may also include other types of chip-related components. In addition, these chip-related components **1020** may be combined with each other. These chip-related components **1020** may have a package form including the chips or the electronic components described above.

(30) The network related components **1030** may include protocols such as wireless fidelity (Wi-Fi) (Institute of Electrical And Electronics Engineers (IEEE) 802.11 family, or the like), worldwide interoperability for microwave access (WiMAX) (IEEE 802.16 family, or the like), IEEE 802.20, long term evolution (LTE), evolution data only (Ev-DO), high speed packet access+ (HSPA+), high speed downlink packet access+ (HSDPA+), high speed uplink packet access+ (HSUPA+), enhanced data GSM environment (EDGE), global system for mobile communications (GSM), global positioning system (GPS), general packet radio service (GPRS), code division multiple access (CDMA), time division multiple access (TDMA), digital enhanced cordless telecommunications (DECT), Bluetooth, 3G, 4G, and 5G protocols, and any other wireless and wired protocols, designated after the abovementioned protocols. However, the network related components **1030** are not limited thereto, and may also include a variety of other wireless or wired standards or protocols. In addition, the network related components **1030** may be combined with each other, together with the chip-related components **1020** described above.

(31) Other components **1040** may include a high frequency inductor, a ferrite inductor, a power inductor, ferrite beads, a low temperature co-fired ceramic (LTCC), an electromagnetic interference (EMI) filter, a multilayer ceramic capacitor (MLCC), or the like. However, these other components **1040** are not limited thereto, and may also include chip component types of passive components used for various other purposes, or the like. In addition, other components **1040** may be combined with each other, together with the chip-related components **1020** or the network related components **1030** described above.

(32) Depending on a type of the electronic device **1000**, the electronic device **1000** may include other components that may or may not be physically or electrically connected to the mainboard **1010**. These other electronic components may include, for example, a camera **1050**, an antenna **1060**, a display **1070**, a battery **1080**, or the like. These other electronic components are not limited thereto, and may be an audio codec, a video codec, a power amplifier, a compass, an accelerometer,

a gyroscope, a speaker, a mass storage unit (for example, a hard disk drive), a compact disk (CD) drive, a digital versatile disk (DVD) drive, or the like. These other electronic components may also include other electronic components used for various purposes depending on a type of electronic device **1000**, or the like.

(33) The electronic device **1000** may be a smartphone, a personal digital assistant (PDA), a digital video camera, a digital still camera, a network system, a computer, a monitor, a tablet PC, a laptop PC, a netbook PC, a television, a video game machine, a smartwatch, an automotive component, or the like. However, the electronic device **1000** is not limited thereto, and may be any other electronic device processing data.

(34) FIG. 2 is a schematic perspective view illustrating an example of an electronic device.

(35) Referring to FIG. 2, an electronic device may be, for example, a smartphone **1100**. A motherboard **1110** may be accommodated in the smartphone **1100**, and various components **1120** may be physically or electrically connected to the motherboard **1110**. In addition, other components that may or may not be physically or electrically connected to the motherboard **1110**, such as a camera module **1130** and/or a speaker **1140**, may be accommodated in the smartphone **1100**. Some of the electronic components **1120** may be the above-described chip-related components, for example, a semiconductor package **1121**, and are not limited thereto. The semiconductor package **1121** may have a form in which a semiconductor chip or the like is surface-mounted on a printed circuit board such as a package board and/or an interposer board. Meanwhile, the electronic device is not necessarily limited to the smartphone **1100**, and may be other electronic devices as described above.

(36) Semiconductor Package

(37) FIG. 3 is a schematic cross-sectional view illustrating a semiconductor package according to an exemplary embodiment in the present disclosure.

(38) Referring to FIG. 3, a semiconductor package **500A** according to an exemplary embodiment may include a semiconductor chip **300** including a front end of line (FEOL) layer **310** and a first back end of line (BEOL) layer **320** disposed on the FEOL layer **310**; and a printed circuit board **100A** including a wiring layer **110A** and a second BEOL layer **120A** disposed on the wiring layer **110A**. The semiconductor chip **300** may be mounted on the printed circuit board **100A** so that the first and second BEOL layers **320** and **120A** are connected to each other. The second BEOL layer **120A** may include wirings for power transmission. The printed circuit board **100A** may be a package board, but is not limited thereto.

(39) Meanwhile, recently, the demand for high-performance semiconductors has increased. Due to a speed increase and performance improvement of the semiconductors, the number of layers of a semiconductor chip has increased or a circuit density of the semiconductor chip has increased, and accordingly, manufacturing costs of the semiconductor chip have significantly increased. In addition, a yield problem of the semiconductor chip has also occurred. For example, according to the manufacture of the high-performance semiconductors, the number of layers of a BEOL of the semiconductor chip may increase or a circuit density of the semiconductor chip may increase. Accordingly, manufacturing costs of the semiconductor chip may be significantly increased, and a cost problem may occur due to a decrease in yield of the semiconductor chip caused by the occurrence of a defect during manufacture of the semiconductor chip.

(40) On the other hand, in the semiconductor package **500A** according to an exemplary embodiment, a portion of an existing BEOL layer of the semiconductor chip **300**, more specifically, a metal layer including wirings for power transmission having a relatively great wiring pitch may be formed in the printed circuit board **100A**. In this case, the number of layers of the printed circuit board **100A** may be increased, but the number of layers of the existing BEOL layer of the semiconductor chip **300** having a relatively high process difficulty and cost may be decreased, and accordingly, a process cost may be significantly decreased in terms of the entire semiconductor package. In addition, it may be more advantageous in terms of cost to discard the printed circuit

board **100A** due to the occurrence of defects in the wirings for power transmission than to discard the semiconductor chip **300** due to the occurrence of defects in the wirings for power transmission, and thus, a cost problem due to a decrease in yield of the semiconductor chip **300** may also be solved.

(41) The semiconductor chip **300** may include an integrated circuit (IC) provided in an amount of several hundred to several million or more elements integrated in a single chip. In this case, the IC may be, for example, a logic chip such as a central processor (for example, a CPU), a graphic processor (for example, a GPU), a field programmable gate array (FPGA), a digital signal processor, a cryptographic processor, a microprocessor, a microcontroller, an application processor (for example, an AP), an analog-to-digital converter, an application-specific IC (ASIC), or the like. Alternatively, the semiconductor chip **300** may be a memory chip such as a volatile memory (for example, a DRAM), a non-volatile memory (for example, a ROM), a flash memory, a high bandwidth memory, or the like. Alternatively, the semiconductor chip **300** may be another type of chip such as a power management IC (PMIC).

(42) The FEOL layer **310** may include a semiconductor substrate, a transistor element formed on the semiconductor substrate, and a metal contact region formed on the transistor element. Here, the FEOL layer may include a middle end of line (MEOL) layer. For example, the metal contact region may include a contact hole and a plug connecting a metal layer and a p-n junction diffusion layer on a silicon substrate to each other or connecting the metal layer and a polycrystalline silicon electrode to each other.

(43) The first BEOL layer **320** may include a plurality of insulating layers and a plurality of metal layers. In this case, the plurality of insulating layers may include an inorganic insulating material. In addition, the plurality of metal layers may include a metal material. The plurality of metal layers may mainly include wirings for signal transmission, and may further include some wirings for power transmission and/or some wirings for ground transmission, if necessary. Here, the phrase “mainly include the wirings for signal transmission” may mean that a total area occupied by the wirings for signal transmission is greater than a total area occupied by the wirings for power transmission and/or the wirings for ground transmission in plan view. In the case of a plurality of layers, the sums of areas in plan view in respective layers may be compared with each other, and the areas in plan view in the respective layers may be determined with the exception of vias overlapping trace patterns of the respective layers. Each wiring may include a trace pattern, a via pattern, and the like. The trace pattern may include a pad pattern. The first BEOL layer **320** may be formed on a semiconductor substrate, for example, a silicon substrate, and accordingly, may be formed at a higher density.

(44) The wiring layer **110A** may include a plurality of insulating layers and a plurality of metal layers. In this case, the plurality of insulating layers may include an organic insulating material. In addition, the plurality of metal layers may include a metal material. In addition, the plurality of metal layers may include wirings for transmission of various wirings within the wiring layer **110A**, for example, wirings for power transmission, wirings for signal transmission, and/or wirings for ground transmission. Each wiring may include a trace pattern, a via pattern, and the like. The trace pattern may include a pad pattern and the like. The plurality of insulating layers and the plurality of wiring layers may be alternately stacked. The wiring layer **110A** may be formed on an organic substrate, and accordingly, may be more easily formed at a low cost.

(45) The second BEOL layer **120A** may include one or more insulating layers and one or more metal layers. In this case, one or more insulating layers may include an organic insulating material. In addition, one or more metal layers may include a metal material. One or more metal layers may mainly include wirings for power transmission, and may further include some wirings for signal transmission and/or some wirings for ground transmission, if necessary. Here, the wiring for power transmission may be a wiring for transmitting power to the semiconductor chip **300**. In addition, the phrase “mainly include the wirings for power transmission” may mean that a total area

occupied by the wirings for power transmission is greater than a total area occupied by the wirings for signal transmission and/or the wirings for ground transmission in plan view. In the case of a plurality of layers, the sums of areas in plan view in respective layers may be compared with each other, and the areas in plan view in the respective layers may be determined with the exception of vias overlapping trace patterns or the like of the respective layers. Each wiring may include a trace pattern, a via pattern, and the like. The trace pattern may include a pad pattern and the like. The second BEOL layer **120A** may be formed on an organic substrate, and accordingly, may be more easily formed at a low cost.

(46) In some embodiments, silicon may not be disposed between the first and second BEOL layers **320** and **120A**. The first BEOL layer **320** may be disposed adjacent to a bottom side of the semiconductor chip **300**. The second BEOL layer **120A** may be disposed adjacent to a top side of the printed circuit board **100A**. As such, the first and second BEOL layers **320** and **120A** may be disposed adjacent to each other and be connected to each other, and accordingly, a side effect due to separation of the existing BEOL layer of the semiconductor chip **300** may be significantly decreased. In some embodiments, the first BEOL layer **320** may be spaced apart from the second BEOL layer **120A**.

(47) A wiring pitch of the second BEOL layer **120A** may be greater than a wiring pitch of the first BEOL layer **320**. The second BEOL layer **120A** may mainly include wirings for power transmission having a relatively great pitch and formed in a greater size, and may be formed in the printed circuit board **100A**, and thus, a pitch of the second BEOL layer **120A** may be relatively greater. On the other hand, the first BEOL layer **320** may mainly include wirings for signal transmission having a relatively small pitch and formed to have a smaller size, and may be formed in the semiconductor chip **300**, and thus, a pitch of the first BEOL layer **320** may be relatively smaller. Meanwhile, the pitch may be measured using a scanning microscope or the like, and may refer to an approximately average numerical value. For example, the pitch may be an average value of the greatest numerical number and the smallest numerical number.

(48) The semiconductor package **500A** according to an exemplary embodiment may further include a plurality of connection conductors **330** disposed between the printed circuit board **100A** and the semiconductor chip **300** and connecting the printed circuit board **100A** and the semiconductor chip **300** to each other and/or a plurality of electrical connection conductors **130** disposed on the other surface of the printed circuit board **100A** opposing one surface of the printed circuit board **100A** on which the semiconductor chip **300** is mounted and connected to the printed circuit board **100A**.

(49) The plurality of connection conductors **330** may provide electrical connection paths between the printed circuit board **100A** and the semiconductor chip **300**. The plurality of electrical connection conductors **130** may provide electrical connection paths when the semiconductor package **500A** is mounted on another board, for example, a mainboard. Each of the plurality of connection conductors **330** may be a solder bump, but is not limited thereto. Each of the plurality of electrical connection conductors **130** may be a solder ball, but is not limited thereto.

(50) FIG. 4 is a schematic cross-sectional view illustrating a semiconductor package according to another exemplary embodiment in the present disclosure.

(51) Referring to FIG. 4, a semiconductor package **500B** according to another exemplary embodiment may include a semiconductor chip **300** including a FEOL layer **310** and a first BEOL layer **320** disposed on the FEOL layer **310**; an interposer board **200A** including a first wiring layer **210A** and a second BEOL layer **220A** disposed on the first wiring layer **210A**; and a package board **100B** including a second wiring layer **110B**. The semiconductor chip **300** may be mounted on the interposer board **200A** so that the first and second BEOL layers **320** and **220A** are connected to each other. The interposer board **200A** may be mounted on the package board **100B** so that the first and second wiring layers **210A** and **110B** are connected to each other. The interposer board **200A** may be an organic interposer in which wirings are formed on an insulating layer including an organic insulating material, for example, a coreless type board or be an inorganic interposer in

which wirings are formed on an insulating layer including an inorganic insulating material, for example, a silicon interposer, but is not limited thereto.

(52) In the semiconductor package **500B** according to another exemplary embodiment, a portion of an existing BEOL layer of the semiconductor chip **300**, more specifically, a metal layer including wirings for power transmission having a relatively great wiring pitch may be formed in the interposer board **200A**. In this case, the number of layers of the interposer board **200A** may be increased, but the number of layers of the existing BEOL layer of the semiconductor chip **300** having a relatively high process difficulty and cost may be decreased, and accordingly, a process cost may be significantly decreased in terms of the entire semiconductor package. In addition, it may be more advantageous in terms of cost to discard the interposer board **200A** due to the occurrence of defects in the wirings for power transmission than to discard the semiconductor chip **300** due to the occurrence of defects in the wirings for power transmission, and thus, a cost problem due to a decrease in yield of the semiconductor chip **300** may also be solved.

(53) The first wiring layer **210A** may include a plurality of insulating layers and a plurality of metal layers. In this case, the plurality of insulating layers may include an organic insulating material or an inorganic insulating material. In addition, the plurality of metal layers may include a metal material. In addition, the plurality of metal layers may include wirings for transmission of various wirings within the first wiring layer **210A**, for example, wirings for power transmission, wirings for signal transmission, and/or wirings for ground transmission. Each wiring may include a trace pattern, a via pattern, and the like. The trace pattern may include a pad pattern and the like. The plurality of insulating layers and the plurality of wiring layers may be alternately stacked.

(54) The second BEOL layer **220A** may include one or more insulating layers and one or more metal layers. In this case, one or more insulating layers may include an organic insulating material or an inorganic insulating material. In addition, one or more metal layers may include a metal material. One or more metal layers may mainly include wirings for power transmission, and may further include some wirings for signal transmission and/or some wirings for ground transmission, if necessary. Here, the wiring for power transmission may be a wiring for transmitting power to the semiconductor chip **300**. In addition, the phrase “mainly include the wirings for power transmission” may mean that a total area occupied by the wirings for power transmission is greater than a total area occupied by the wirings for signal transmission and/or the wirings for ground transmission in plan view. In the case of a plurality of layers, the sums of areas in plan view in respective layers may be compared with each other, and the areas in plan view in the respective layers may be determined with the exception of vias overlapping trace patterns or the like of the respective layers. Each wiring may include a trace pattern, a via pattern, and the like. The trace pattern may include a pad pattern and the like.

(55) The first BEOL layer **320** may be disposed adjacent to a bottom side of the semiconductor chip **300**. The second BEOL layer **220A** may be disposed adjacent to a top side of the interposer board **200A**. As such, the first and second BEOL layers **320** and **220A** may be disposed adjacent to each other and be connected to each other, and accordingly, a side effect due to separation of the existing BEOL layer of the semiconductor chip **300** may be significantly decreased.

(56) A wiring pitch of the second BEOL layer **220A** may be greater than a wiring pitch of the first BEOL layer **320**. The second BEOL layer **220A** may mainly include wirings for power transmission having a relatively great pitch and formed in a greater size, and may be formed in the interposer board **200A**, and thus, a pitch of the second BEOL layer **220A** may be relatively greater. On the other hand, the first BEOL layer **320** may mainly include wirings for signal transmission having a relatively small pitch and formed in a smaller size, and may be formed in the semiconductor chip **300**, and thus, a pitch of the first BEOL layer **320** may be relatively smaller. Meanwhile, the pitch may be measured using a scanning microscope or the like, and may refer to an approximately average numerical value. For example, the pitch may be an average value of the greatest numerical number and the smallest numerical number.

(57) The semiconductor package **500B** according to another exemplary embodiment may further include a plurality of connection conductors **330** disposed between the semiconductor chip **300** and the interposer board **200A** and connecting the semiconductor chip **300** and the interposer board **200A** to each other, a plurality of first electrical connection conductors **230** disposed between the interposer board **200A** of the package board **100B** and connecting the interposer board **200A** of the package board **100B** to each other, and/or a plurality of second electrical connection conductors **130** disposed on the other surface of the package board **100B** opposing one surface of the package board **100B** on which the interposer board **200A** is disposed and connected to the package board **100B**.

(58) The plurality of connection conductors **330** may provide electrical connection paths between the interposer board **200A** and the semiconductor chip **300**. The plurality of first electrical connection conductors **230** may provide electrical connection paths between the package board **100B** and the interposer board **200A**. The plurality of second electrical connection conductors **130** may provide electrical connection paths when the semiconductor package **500B** is mounted on another board, for example, a mainboard. Each of the plurality of connection conductors **330** may be a solder bump, but is not limited thereto. Each of the plurality of first and second electrical connection conductors **230** and **130** may be a solder ball, but is not limited thereto.

(59) Other contents, for example, the contents described in the semiconductor package **500A** according to the exemplary embodiment described above may be applied to the semiconductor package **500B** according to another exemplary embodiment described above as long as there is no contradiction, and a description of overlapping contents is omitted.

(60) FIG. 5 is a schematic cross-sectional view illustrating a semiconductor package according to another exemplary embodiment in the present disclosure.

(61) Referring to FIG. 5, a semiconductor package **500C** according to another exemplary embodiment may include a semiconductor chip **300** including a FEOL layer **310** and a first BEOL layer **320** disposed on the FEOL layer **310**; an interposer board **200B** including a second BEOL layer **220B**; and a package board **100B** including a wiring layer **110B**. The semiconductor chip **300** may be mounted on the interposer board **200B** so that the first and second BEOL layers **320** and **220B** are connected to each other. The interposer board **200B** may be mounted on the package board **100B** so that the second BEOL layer **220B** and the wiring layer **110B** are connected to each other. The interposer board **200B** may be an organic interposer in which wirings are formed on an insulating layer including an organic insulating material, for example, a coreless type board or be an inorganic interposer in which wirings are formed on an insulating layer including an inorganic insulating material, for example, a silicon interposer, but is not limited thereto.

(62) In the semiconductor package **500C** according to another exemplary embodiment, a portion of an existing BEOL layer of the semiconductor chip **300**, more specifically, a metal layer including wirings for power transmission having a relatively great wiring pitch may be formed in the interposer board **200B**. In this case, the number of layers of the interposer board **200B** may be increased, but the number of layers of the existing BEOL layer of the semiconductor chip **300** having a relatively high process difficulty and cost may be decreased, and accordingly, a process cost may be significantly decreased in terms of the entire semiconductor package. In addition, it may be more advantageous in terms of cost to discard the interposer board **200B** due to the occurrence of defects in the wirings for power transmission than to discard the semiconductor chip **300** due to the occurrence of defects in the wirings for power transmission, and thus, a cost problem due to a decrease in yield of the semiconductor chip **300** may also be solved.

(63) In the semiconductor package **500C** according to another exemplary embodiment, the interposer board **200B** may include the second BEOL layer **220B**, but may not include a separate additional wiring layer. Accordingly, the number of layers of the interposer board **200B** may be significantly decreased. Accordingly, a thickness may be decreased, process difficulty may be decreased, and a yield may be improved.

(64) The second BEOL layer **220B** may include one or more insulating layers and one or more metal layers. In this case, one or more insulating layers may include an organic insulating material or an inorganic insulating material. In addition, one or more metal layers may include a metal material. One or more metal layers may mainly include wirings for power transmission, and may further include some wirings for signal transmission and/or some wirings for ground transmission, if necessary. Here, the wiring for power transmission may be a wiring for transmitting power to the semiconductor chip **300**. In addition, the phrase “mainly include the wirings for power transmission” may mean that a total area occupied by the wirings for power transmission is greater than a total area occupied by the wirings for signal transmission and/or the wirings for ground transmission in plan view. In the case of a plurality of layers, the sums of areas in plan view in respective layers may be compared with each other, and the areas in plan view in the respective layers may be determined with the exception of vias overlapping trace patterns or the like of the respective layers. Each wiring may include a trace pattern, a via pattern, and the like. The trace pattern may include a pad pattern and the like. One or more insulating layers and one or more metal layers may be alternately stacked.

(65) Other contents, for example, the contents described in the semiconductor packages **500A** and **500B** described above may be applied to the semiconductor package **500C** according to another exemplary embodiment described above as long as there is no contradiction, and a description of overlapping contents is omitted.

(66) FIG. **6** is a schematic cross-sectional view illustrating wirings for power transmission within a semiconductor package after applying a portion of a BEOL layer of a semiconductor chip to a printed circuit board.

(67) Meanwhile, for convenience of explanation, other components except for transistor elements, wirings for power transmission, and the like, have been omitted in FIG. **6**, and such omitted components may be understood based on the contents described above or contents to be described later.

(68) Referring to FIG. **6**, a semiconductor package **5000** may include a printed circuit board **1000A** and a semiconductor chip **3000** mounted on the printed circuit board **1000A**. The semiconductor chip **3000** may include a FEOL layer **3100** and a first BEOL layer **3200** disposed on the FEOL layer **3100**. The FEOL layer **3100** may include a first circuit unit **3110** including a plurality of first transistor elements **3111**, **3112**, and **3113**, and a second circuit unit **3120** including a plurality of second transistor elements **3121**, **3122**, and **3123**. The first BEOL layer **3200** may include a first wiring unit **3201** electrically connected to the first and second circuit units **3110** and **3120**. A second BEOL layer **1200** may include a second wiring unit **1201** electrically connected to the first wiring unit **3201**.

(69) The first wiring unit **3201** may not include a trace pattern for power transmission interconnecting the first and second circuit units **3110** and **3120** within the first BEOL layer **3200**. For example, the first wiring unit **3201** may include wirings for power transmission, specifically, via patterns for power transmission, independently connected to the first and second circuit units **3110** and **3120** within the first BEOL layer **3200**. Each of the first and second circuit units **3110** and **3120** may be a unit circuit having a specific function or a block circuit of a greater unit than the unit circuit. The FEOL layer **3100** may include a greater number of such circuit units, and the first wiring unit **3201** may not include a trace pattern for power transmission interconnecting at least two of a plurality of circuit units. Such interconnection may be performed in the second BEOL layer **1200** of the printed circuit board **1000A**. Meanwhile, although not illustrated in FIG. **6**, the first wiring unit **3201** may further include wirings for signal transmission and/or wirings for ground transmission in addition to the wirings for power transmission, and trace patterns of the wirings for signal transmission and the wirings for ground transmission may interconnect the first and second circuit units **3110** and **3120** within the first BEOL layer **3200**, but are not limited thereto.

(70) The first wiring unit **3201** may not include a trace pattern for power transmission

interconnecting at least two of the plurality of first transistor elements **3111**, **3112**, and **3113** within the first BEOL layer **3200**, and may not include a trace pattern for power transmission interconnecting at least two of the second transistor elements **3121**, **3122**, and **3123** within the first BEOL layer **3200**. As such, if necessary, the first wiring unit **3201** may not include a trace pattern for power transmission for interconnection between elements of the smallest unit. Meanwhile, although not illustrated in FIG. 6, the first wiring unit **3201** may further include wirings for signal transmission and/or wirings for ground transmission in addition to the wirings for power transmission, and trace patterns of the wirings for signal transmission and the wirings for ground transmission may interconnect at least two of the plurality of first transistor elements **3111**, **3112**, and **3113** and/or may interconnect at least two of the second transistor elements **3121**, **3122**, and **3123** within the first BEOL layer **3200**, but are not limited thereto.

(71) The second wiring unit **1201** may include a trace pattern for power transmission interconnecting the first and second circuit units **3110** and **3120** within the second BEOL layer **1200**. For example, the second wiring unit **1201** may include the trace pattern for power transmission for interconnection between first and second circuit units **3110** and **3120** of the FEOL layer **3100**, which is omitted in the first wiring unit **3201** of the first BEOL layer **3200** of the semiconductor chip **3000**. The same may go for a case where the FEOL layer **3100** includes a greater number of circuit units. Meanwhile, although not illustrated in FIG. 6, the second wiring unit **1201** may further include wirings for signal transmission and/or wirings for ground transmission in addition to wirings for power transmission, and trace patterns of the wirings for signal transmission and the wirings for ground transmission may not interconnect the first and second circuit units **3110** and **3120** within the second BEOL layer **1200**, but are not limited thereto.

(72) The second wiring unit **1201** may also include a trace pattern for power transmission interconnecting at least two of the plurality of first transistor elements **3111**, **3112**, and **3113** within the second BEOL layer **1200**, and may also include a trace pattern for power transmission interconnecting at least two of the second transistor elements **3121**, **3122**, and **3123** within the second BEOL layer **1200**. As such, the second wiring unit **1201** may include a trace pattern for power transmission for interconnection between elements of the smallest unit as well as for a trace pattern interconnection between circuit units of a large unit. Meanwhile, although not illustrated in FIG. 6, a plurality of second wiring units **1201** may further include wirings for signal transmission and/or wirings for ground transmission in addition to the wirings for power transmission, and trace patterns of the wirings for signal transmission and the wirings for ground transmission may not interconnect at least two of the plurality of first transistor elements **3111**, **3112**, and **3113** and/or may not interconnect at least two of the second transistor elements **3121**, **3122**, and **3123** within the second BEOL layer **1200**, but are not limited thereto.

(73) Meanwhile, the printed circuit board **1000A** may be a package board, an interposer board, or the like, and accordingly, the contents described in the semiconductor packages **500A**, **500B**, and **500C** described above may also be applied to the semiconductor package **5000**. For example, the printed circuit board **1000A** may further include a separate wiring layer connected to the second wiring unit **1201**. In addition, when the printed circuit board **1000A** is the interposer board, a printed circuit board such as a separate package board including a wiring unit connected to the second wiring unit **1201** may be further disposed. In addition, as a specific structure of the printed circuit board **1000A**, a package board **100A-1** or **100A-2**, an interposer board **200A-1**, **200A-2**, **200B-1**, or **200B-2**, or the like, to be described later, may be applied. In addition, a structure of a BEOL layer **1320-2** or a structure of a semiconductor chip **300**, **300'**, or **300''** to be described later may be applied to the semiconductor chip **3000**. Overlapping descriptions thereof are omitted.

(74) FIG. 7A is a schematic cross-sectional view illustrating a plurality of metal layers of a BEOL layer of a semiconductor chip before applying a portion of the BEOL layer of the semiconductor chip to a printed circuit board.

(75) FIGS. 7B and 7C are schematic plan views illustrating an M1 layer and an M2 layer of the

plurality of metal layers of FIG. 7A, respectively.

(76) In FIGS. 7A through 7C, only some layers may be illustrated for convenience, and in order to indicate connections between patterns of an upper metal layer and patterns of a lower metal layer, some vias are illustrated together with the patterns for convenience of explanation even though they are positioned below the patterns of the upper metal layer.

(77) Referring to FIGS. 7A through 7C, a BEOL layer **1320-1** of a semiconductor chip may include a plurality of metal layers M1, M2, M3, M4, . . . M8, M9, The number of metal layers M1, M2, M3, M4, . . . M8, M9, . . . is not particularly limited, and may be various depending on a design. The metal layers M1, M2, M3, M4, . . . M8, M9, . . . may include trace patterns and via patterns. In this case, the trace patterns may include pad patterns connected to the via patterns. The metal layers M1, M2, M3, M4, . . . M8, M9, . . . may include a low-resistance conductive material such as copper (Cu), aluminum (Al), or tungsten (W).

(78) Metal layers M1, M2, M3, and M4 adjacent to a FEOL layer of the semiconductor chip, for example, first and second metal layers M1 and M2, among the plurality of metal layers M1, M2, M3, M4, . . . M8, M9, . . . may include trace patterns P1 and P2 for power transmission and trace patterns P3 for signal transmission. In addition, these metal layers may include via patterns V_P1 and V_P2 for power transmission connected to the trace patterns P1 and P2 for power transmission. In addition, although not illustrated in FIGS. 7A through 7C, these metal layers may also include via patterns for signal transmission connected to the trace patterns P3 for signal transmission.

(79) The first trace pattern P1 for power transmission may include a trace pattern for a positive supply voltage VDD. The first via pattern V_P1 for power transmission may include a via pattern for a positive supply voltage VDD. The second trace pattern P2 for power transmission may include a trace pattern for a negative supply voltage VSS. The second via pattern V_P2 for power transmission may include a via pattern for a negative supply voltage VSS. However, the present disclosure is not limited thereto, and the trace patterns P1 and P2 for power transmission and the via patterns V_P1 and V_P2 for power transmission may include patterns for different types of voltages. The trace pattern and the via pattern for a negative supply voltage VSS may be a ground pattern while being a voltage pattern. That is, if necessary, the voltage pattern may include the ground pattern.

(80) Meanwhile, the metal layers M1, M2, M3, and M4 adjacent to the FEOL layer of the semiconductor chip, for example, the first and second metal layers M1 and M2 may be layers with a high circuit density, and may require, for example, a fine pitch of the trace patterns P3 for signal transmission. In this case, when the trace patterns P1 and P2 for power transmission having a relatively large wiring pitch are designed together with the trace patterns P3 for signal transmission on the first and second metal layers M1 and M2, the process difficulty may become higher, as described above. Therefore, manufacturing costs of the semiconductor chip may be significantly increased, and a defect may occur in a manufacturing process of the semiconductor chip, which may cause a cost problem due to a decrease in yield of the semiconductor chip.

(81) FIG. 8A is a schematic cross-sectional view illustrating a plurality of metal layers of a BEOL layer of a semiconductor chip after applying a portion of the BEOL layer of the semiconductor chip to a printed circuit board.

(82) FIGS. 8B and 8C are schematic plan views illustrating an M1 layer and an M2 layer of the plurality of metal layers of FIG. 8A, respectively.

(83) In FIGS. 8A through 8C, only some layers may be illustrated for convenience, and in order to indicate connections between patterns of an upper metal layer and patterns of a lower metal layer, some vias are illustrated together with the patterns for convenience of explanation even though they are positioned below the patterns of the upper metal layer.

(84) Referring to FIGS. 8A through 7C, a BEOL layer **1320-2** of a semiconductor chip may include a plurality of metal layers M1, M2, M3, . . . M7, In this case, a portion of the BEOL layer **1320-2** of the semiconductor chip may be applied to the printed circuit board, and the number of

metal layers M1, M2, M3, . . . M7, . . . may thus be decreased as compared with the BEOL layer **1320-1** described above before a portion of the BEOL layer **1320-1** is applied to the printed circuit board. For example, metal layers M1, M2, and M3 adjacent to a FEOL layer of the semiconductor chip, for example, first and second metal layers M1 and M2, among the plurality of metal layers M1, M2, M3, . . . M7, . . . may include trace patterns P3 for signal transmission, but may not include the trace patterns P1 and P2 for power transmission described above. For example, the trace patterns P1 and P2 for power transmission described above may be separately designed as a BEOL layer in the printed circuit board. In this case, the first and second metal layers M1 and M2 may include only via patterns V_P1 and V_P2 for power transmission without the trace patterns P1 and P2 for power transmission described above. The via patterns V_P1 and V_P2 for power transmission may be electrically connected to wirings for power transmission of the BEOL layer designed in the printed circuit board including the trace patterns P1 and P2 for power transmission described above. If necessary, some of the trace patterns P1 and P2 for power transmission described above may be designed on metal layers M7, for example, a seventh metal layer M7, relatively far from the FEOL layer of the semiconductor chip among the plurality of metal layers M1, M2, M3, . . . M7, . . .

(85) As described above, when a portion of the BEOL layer **1320-2** of the semiconductor chip, for example, at least some of the trace patterns P1 and P2 for power transmission that have been designed on lower metal layers M1 and M2 are formed as a separate BEOL layer in the printed circuit board, the number of layer of the existing BEOL layer of the semiconductor chip having high process difficulty and cost may be reduced, and the trace pattern P3 for signal transmission may be designed at a greater pitch, and a process cost may thus be significantly decreased. In addition, a cost problem due to a decrease in yield of the semiconductor chip may be solved.

(86) Meanwhile, the contents described in the BEOL layer **1320-1** of the semiconductor chip described above may be applied to the BEOL layer **1320-2** of the semiconductor chip as long as there is no contradiction, and a description of overlapping contents is omitted. In addition, the contents described in the semiconductor packages **500A**, **500B**, **500C**, and **500D** described above and contents to be described in semiconductor chips **300**, **300'** and **300''** to be described later may also be applied to the BEOL layer **1320-2** of the semiconductor chip as long as there is no contradiction, and a description of overlapping contents is omitted.

(87) FIGS. **9A** and **9B** are schematic cross-sectional views illustrating internal structures of a semiconductor chip before and after applying a portion of a BEOL layer of the semiconductor chip to a printed circuit board, respectively.

(88) Meanwhile, an internal structure of a partial region of the semiconductor chip is enlarged and schematically illustrated in FIGS. **9A** and **9B**, and other regions may be understood based on such a partial region.

(89) Referring to FIGS. **9A** and **9B**, semiconductor chips **300** and **300''** may include FEOL layers **310** and **310''** and BEOL layers **320** and **320''**, respectively. In this case, before a portion of the BEOL layer **320''** is applied to the printed circuit board, the BEOL layer **320''** may include more metal layers **324**. Accordingly, manufacturing costs of the semiconductor chip **300''** may significantly increase, and when a defect occurs during manufacture of the semiconductor chip **300''**, the semiconductor chip **300''** needs to be discarded, which may cause a significant cost problem due to a decrease in yield of the semiconductor chip **300''**. On the other hand, when a portion of the BEOL layer is applied to the printed circuit board, the BEOL layer **320** includes fewer metal layers **324**. Accordingly, manufacturing costs of the semiconductor chip **300** may be significantly decreased, and a probability of the occurrence of a defect during manufacture of the semiconductor chip **300** may also be decreased, such that a yield of the semiconductor chip **300** may also be improved.

(90) However, the present disclosure is not limited thereto, and if necessary, the number of metal layers **324** may be similar to or the same as the number of metal layers **324''**, but a circuit density of

each of the metal layers **324** may become lower. For example, most of wirings for power transmission in each of the metal layers **324** may be omitted, so that wirings for signal transmission, and the like, may be formed more sparsely. Also in this case, manufacturing costs of the semiconductor chip **300** may be significantly decreased, and a probability of the occurrence of a defect during manufacture of the semiconductor chip **300** may also be decreased, such that a yield of the semiconductor chip **300** may also be improved.

(91) Meanwhile, the FEOL layers **310** and **310''** may include, respectively, semiconductor substrates **311** and **312**, and **311''** and **312''**, lower insulating layers **313** and **313''** each disposed on the semiconductor substrates **311** and **312**, and **311''** and **312''**, transistor elements **314** and **314''** each disposed on the semiconductor substrates **311** and **312**, and **311''** and **312''** and each surrounded by the lower insulating layers **313** and **313''**, insulating films **315** and **315''** each covering the transistor elements **314** and **314''** and the lower insulating layers **313** and **313''**, upper insulating layers **316** and **316''** each disposed on the insulating films **315** and **315''**, and/or plugs **317** and **317''** each penetrating through the upper insulating layers **316** and **316''**.

(92) The semiconductor substrate **311**, **312**, **311''**, and **312''** may include a semiconductor material, for example, a group IV semiconductor, a group III-V compound semiconductor, or a group II-VI compound semiconductor. For example, the group IV semiconductor may include silicon, germanium, or silicon-germanium. Each of the semiconductor substrates **311**, **312**, **311''**, and **312''** may also be provided as, for example, a bulk wafer, an epitaxial layer, a silicon on insulator (SOI) layer, a semiconductor on insulator (SeOI) layer, or the like, but is not limited thereto.

(93) Each of the transistor elements **314** and **314''** may include a gate insulating layer, a gate electrode, a capping layer, a spacer, and the like. Source and drain regions may be disposed on both sides of each of the transistor elements **314** and **314''**, respectively. The transistor elements **314** and **314''** may be positioned in a cell region, and may include, for example, a DRAM memory element, a flash memory element, or a complementary metal oxide semiconductor (CMOS) image sensor (CIS) element, and the like, but is not limited thereto, and may also include other logic element, power element, and the like.

(94) The plugs **317** and **317''** may be electrically connected to the transistor elements **314** and **314''** and the metal layers **324** and **324''**, respectively. The plugs **317** and **317''** may include copper (Cu), tungsten (W), or combinations thereof.

(95) In addition, the BEOL layers **320** and **320''** may include, respectively, interlayer insulating layers **321** and **321''**, first interlayer insulating films **322** and **322''** and the second interlayer insulating film **323** and **323''** each disposed between the interlayer insulating layers **321** and **321''**, metal layers **324** and **324''** each formed in the interlayer insulating layers **321** and **321''**, and/or protective layers **325** and **325''** disposed on the interlayer insulating layers **321** and **321''**.

(96) The interlayer insulating layers **321** and **321''** may include, for example, oxide, nitride, or oxynitride, and may include, for example, silicon oxide, silicon nitride, or silicon oxynitride, but is not limited thereto. Respective layers of the interlayer insulating layers **321** and **321''** may include the same material or include different materials.

(97) The metal layers **324** and **324''** may include a low-resistance conductive material such as copper (Cu), aluminum (Al), or tungsten (W). Respective layers of the metal layers **324** and **324''** may include the same material or include different materials. The respective layers of the metal layers **324** and **324''** may include trace patterns, via patterns, and the like. The trace pattern may include a pad pattern connected to the via pattern. Unlike the metal layer **324''**, the metal layer **324** may mainly include wirings for signal transmission. Here, the phrase "mainly include the wirings for signal transmission" may mean that a total area occupied by the wirings for signal transmission is greater than a total area occupied by the wirings for power transmission and/or the wirings for ground transmission in plan view. In the case of a plurality of layers, the sums of areas in plan view in respective layers may be compared with each other, and the areas in plan view in the respective layers may be determined with the exception of via patterns overlapping trace patterns or the like of

the respective layers.

(98) The metal layers **324** and **324''** may be surrounded by diffusion prevention layers. The diffusion prevention layer may include at least one selected from the group consisting of titanium (Ti), titanium nitride (TiN), tantalum (Ta), tantalum nitride (TaN), ruthenium (Ru), cobalt (Co), manganese (Mn), tungsten nitride (WN), nickel (Ni), and nickel boron (NiB).

(99) Meanwhile, sealing layers **340** and **340''** may be further disposed on the protective layers **325** and **325''**, respectively, and underbump metal layers **351** and **351''** and surface treatment layers **352** and **352''** may be further disposed in via holes penetrating through the protective layers **325** and **325''** and the sealing layers **340** and **340''**, respectively. Connection conductors **330** and **330''** may be further disposed on the surface treatment layers **352** and **352''**, respectively.

(100) The underbump metal layers **351** and **351''** and the surface treatment layers **352** and **352''** may improve reliability of connections with the connection conductors **330** and **330''**. Each of the underbump metal layers **351** and **351''** may include a chrome (Cr) layer and a copper (Cu) layer, and each of the surface treatment layers **352** and **352''** may include a nickel (Ni) layer, a gold (Au) layer, and the like, but the underbump metal layers **351** and **351''** and the surface treatment layers **352** and **352''** are not limited thereto.

(101) The connection conductors **330** and **330''** may be formed of a low-melting-point metal, for example, solder such as tin (Sn)-aluminum (Al)-copper (Cu) or tin (Sn)-silver (Ag), or the like. For example, the connection conductors **330** and **330''** may include a solder bump. However, this is only an example, and a material of the connection conductors **330** and **330''** is not particularly limited thereto.

(102) Meanwhile, the above-described structure is only an example of the semiconductor chips **300** and **300''**, and internal structures of the semiconductor chips **300** and **300''** may be modified.

(103) Other contents, for example, the contents described in the semiconductor packages **500A**, **500B**, and **500C** described above may be applied to the semiconductor chips **300** and **300''** as long as there is no contradiction, and a description of overlapping contents is omitted.

(104) FIG. **9C** is a schematic cross-sectional view illustrating a modified example of the semiconductor chip of FIG. **9B**.

(105) Meanwhile, an internal structure of a partial region of the semiconductor chip is enlarged and schematically illustrated in FIG. **9C**, and other regions may be understood based on such a partial region.

(106) Referring to FIG. **9C**, a semiconductor chip **300'** may further include a redistribution layer **370** disposed on the BEOL layer **320** in the semiconductor chip **300** described above.

(107) The redistribution layer **370** includes one or more insulating layers **371** and one or more metal layers **372**. In a case where the redistribution layer **370** is further disposed, when the semiconductor chip **300'** is applied to the semiconductor packages **500A**, **500B**, and **500C** described above, BEOL layers separated from each other may be connected to each other through the redistribution layer **370**. By further forming the redistribution layer **370**, a circuit scale for a connection with the substrate may be further expanded.

(108) One or more insulating layers **371** may include an inorganic insulating material, for example, oxide, nitride, or oxynitride, and may include, for example, silicon oxide, silicon nitride, or silicon oxynitride. However, a material of one or more insulating layers **371** is not limited thereto. One or more insulating layers **371** may include an organic insulating material, for example, a thermosetting resin such as an epoxy resin, a thermoplastic resin such as polyimide, Or a resin in which the thermosetting resin or the thermoplastic resin is mixed with an inorganic filler such as silica. The number of one or more insulating layers **371** is not particularly limited, and may be one or be plural. A boundary between the respective insulating layers **371** may be apparent, and in some cases, the respective insulating layers **371** may be integrated with each other without a boundary therebetween.

(109) One or more metal layers **372** may include a low-resistance conductive material such as

copper (Cu), aluminum (Al), or tungsten (W). One or more metal layers **372** may include wirings for power transmission, wirings for signal transmission, wirings for ground transmission, and the like. Each of these wirings may include a trace pattern, a via pattern, and the like. The trace pattern may include a pad pattern and the like. The number of one or more metal layers **372** is not particularly limited, and may be one or be plural. A boundary between the respective metal layers **372** may be apparent, and in some cases, the respective metal layers **372** may be integrated with each other without a boundary therebetween.

(110) Other contents, for example, the contents described in the semiconductor packages **500A**, **500B**, and **500C** described above and the semiconductor chips **300** and **300'** described above may be applied to the semiconductor chip **300'** as long as there is no contradiction, and a description of overlapping contents is omitted.

(111) FIG. **10** is a schematic cross-sectional view illustrating a package board according to an exemplary embodiment in the present disclosure.

(112) Referring to FIG. **10**, a package board **100A-1** according to an exemplary embodiment may include a wiring layer **110A-1** and a BEOL layer **120A-1** disposed on the wiring layer **110A-1**. The wiring layer **110A-1** may include a core insulating layer **111a**, core metal layers **112a** formed in the core insulating layer **111a**, first and second build-up insulating layers **111b** and **111c** built up on opposite surfaces of the core insulating layer **111a**, respectively, and first and second build-up metal layers **112b** and **112c** formed on the first and second build-up insulating layers **111b** and **111c**, respectively. The BEOL layer **120A-1** may include insulating layers **121** and metal layers **122** formed in the insulating layers **121**. If necessary, the package board **100A-1** may further include a first passivation layer **141** disposed on the wiring layer **110A-1** and having a plurality of openings each exposing at least portions of the lowermost first build-up metal layer **112b**, a second passivation layer **142** disposed on the BEOL layer **120A-1** and having a plurality of openings each exposing at least portions of the uppermost metal layer **122**, and/or a plurality of electrical connection conductors **130** each formed on the plurality of openings of the first passivation layer **141**.

(113) The core insulating layer **111a** may function as a core layer of the package board **100A-1**, and may provide rigidity. A material of the core insulating layer **111a** is not particularly limited. For example, an insulating material may be used as the material of the core insulating layer **111a**. In this case, the insulating material may be a thermosetting resin such as an epoxy resin, a thermoplastic resin such as a polyimide resin, a resin in which the thermosetting resin or the thermoplastic resin is mixed with an inorganic filler such as silica or is impregnated together with an inorganic filler in a core material such as a glass fiber (or a glass cloth or a glass fabric), for example, prepreg, Ajinomoto Build-up Film (ABF), FR-4, Bismaleimide Triazine (BT), or the like, but is not limited thereto. The core insulating layer **111a** may be introduced through a copper clad laminate (CCL) or the like, but is not limited thereto. The core insulating layer **111a** may be thicker than each of the first and second build-up insulating layers **111b** and **111c**.

(114) The first and second build-up insulating layers **111b** and **111c** may be introduced onto the opposite surfaces of the core insulating layer **111a** for build-up, respectively. A material of each of the first and second build-up insulating layers **111b** and **111c** is also not particularly limited. For example, an insulating material may be used as the material of each of the first and second build-up insulating layers **111b** and **111c**. In this case, the insulating material may be a thermosetting resin such as an epoxy resin, a thermoplastic resin such as a polyimide resin, a resin in which the thermosetting resin or the thermoplastic resin is mixed with an inorganic filler such as silica or is impregnated in a core material of an inorganic filler, for example, prepreg, ABF, FR-4, BT, or the like, but is not limited thereto. The first and second build-up insulating layers **111b** and **111c** may be introduced through resin coated copper (RCC) or the like, but are not limited thereto. The numbers of first and second build-up insulating layers **111b** and **111c** are not particularly limited, and may be variously modified depending on a design. Boundaries between the first and second

build-up insulating layers **111b** and **111c** may be apparent or the first and second build-up insulating layers **111b** and **111c** may be integrated with each other so that boundaries therebetween are not apparent.

(115) The core metal layers **112a** may perform various functions depending on designs of their corresponding layers. For example, the core metal layers **112a** may include wirings for ground transmission, wirings for power transmission, wirings for signal transmission, and the like. The wirings for signal transmission may include various signals other than the wirings for ground transmission and the wirings for power transmission, for example, a data signal and the like. Each of these wirings may include a trace pattern, a via pattern, and the like. The trace pattern may include a pad pattern and the like. The core metal layer **112a** may include a conductive material, specifically, a metal material, such as copper (Cu), aluminum (Al), silver (Ag), tin (Sn), gold (Au), nickel (Ni), lead (Pb), titanium (Ti), or alloys thereof. The core metal layer **112a** may include an electroless plating layer (or chemical copper) and an electroplating layer (or electrolytic copper). The via pattern of the core metal layer **112a** may be in the form of a through via, and may have an hourglass shape, a cylindrical shape, or the like, in cross section, but is not limited thereto.

(116) The first and second build-up metal layers **112b** and **112c** may perform various functions depending on designs of their corresponding layers. For example, the first and second build-up metal layers **112b** and **112c** may include wirings for ground transmission, wirings for power transmission, wirings for signal transmission, and the like. The wirings for signal transmission may include various signals other than the wirings for ground transmission and the wirings for power transmission, for example, a data signal and the like. Each of these wirings may include a trace pattern, a via pattern, and the like. The trace pattern may include a pad pattern and the like. The first and second build-up metal layers **112b** and **112c** may include a conductive material, specifically, a metal material, such as copper (Cu), aluminum (Al), silver (Ag), tin (Sn), gold (Au), nickel (Ni), lead (Pb), titanium (Ti), or alloys thereof. Each of the first and second build-up metal layers **112b** and **112c** may include an electroless plating layer (chemical copper) and an electroplating layer (or electrolytic copper). The via pattern of the first and second build-up metal layers **112b** and **112c** may have a shape in which it is tapered downward or upward on cross section, but is not limited thereto.

(117) The insulating layers **121** may be disposed on the second build-up insulating layer **111c** and may be built up in the same manner as the second build-up insulating layer **111c**. A material of each of the insulating layers **121** is also not particularly limited. For example, an insulating material may be used as the material of each of the insulating layers **121**. In this case, the insulating material may be a thermosetting resin such as an epoxy resin, a thermoplastic resin such as a polyimide resin, a resin in which the thermosetting resin or the thermoplastic resin is mixed with an inorganic filler such as silica or is impregnated in a core material of an inorganic filler, for example, prepreg, ABE, FR-4, BT, or the like, but is not limited thereto. The insulating layers **121** may also be introduced through RCC or the like, but is not limited thereto. The number of insulating layers **121** is not particularly limited, and may be variously modified depending on a design. A boundary between the insulating layers **121** may be apparent, or the insulating layers **121** may be integrated with each other so that a boundary therebetween is not apparent.

(118) The metal layers **122** may mainly include wirings for power transmission. However, the metal layers **122** may further include some wirings for signal transmission and/or some wirings for ground transmission, if necessary. Here, the wiring for power transmission may be a wiring for transmitting power to the semiconductor chip. In addition, the phrase “mainly include the wirings for power transmission” may mean that a total area occupied by the wirings for power transmission is greater than a total area occupied by the wirings for signal transmission and/or the wirings for ground transmission in plan view. In the case of a plurality of layers, the sums of areas in plan view in respective layers may be compared with each other, and the areas in plan view in the respective layers may be determined with the exception of vias overlapping pads or the like of the respective

layers. Each of these wirings may include a trace pattern, a via pattern, and the like. The trace pattern may include a pad pattern and the like. Each of the metal layers **122** may include a conductive material, specifically, a metal material, such as copper (Cu), aluminum (Al), silver (Ag), tin (Sn), gold (Au), nickel (Ni), lead (Pb), titanium (Ti), or alloys thereof. Each of the metal layers **122** may include an electroless plating layer (or chemical copper) and an electroplating layer (or electrolytic copper). The via pattern of the metal layer **122** may have a shape in which it is tapered downward on cross section, but is not limited thereto.

(119) The first and second passivation layers **141** and **142** may be disposed at both outermost sides of the package board **100A-1**, respectively, to protect internal components. A material of each of the first and second passivation layers **141** and **142** is not particularly limited. For example, an insulating material may be used as the material of each of the first and second passivation layers **141** and **142**. In this case, the insulating material may be a solder resist. However, a material of each of the first and second passivation layers **141** and **142** is not limited thereto, but may also be ABF or the like.

(120) The plurality of electrical connection conductors **130** may externally physically and/or electrically connect the package board **100A-1**. For example, the package board **100A-1** may be a ball grid array (BGA)-type board. Each of the plurality of electrical connection conductors **130** may include a low melting metal having a lower melting point than copper (Cu), such as tin (Sn) or alloys including tin (Sn). For example, each of the plurality of electrical connection conductors **130** may include a solder, but this is only an example, and a material of each of the electrical connection conductors **130** is not particularly limited thereto. The plurality of electrical connection conductors **130** may be lands, balls, pins, or the like. The plurality of electrical connection conductors **130** may be a single layer or multiple layers. When the plurality of electrical connection conductors **130** are formed as multilayer layers, the plurality of electrical connection conductors **130** may include a copper (Cu) pillar and a solder. When the plurality of electrical connection conductors **130** are formed as a single layer, the plurality of electrical connection conductors **130** may include a solder. However, this is only an example, and the plurality of electrical connection conductors **130** are not limited thereto.

(121) As such, the package board **100A-1** according to an exemplary embodiment may be a core-type multilayer board, and may be applied to the semiconductor package **500A** according to the exemplary embodiment described above when the package board **100A-1** includes the BEOL layer **120A-1** and be applied the semiconductor package **500B** according to another exemplary embodiment described above when the BEOL layer **120A-1** is replaced with the wiring layer **110A-1**.

(122) Other contents, for example, the contents described in the semiconductor packages **500A**, **500B**, and **500C** described above may be applied to the package board **100A-1** as long as there is no contradiction, and a description of overlapping contents is omitted.

(123) FIG. **11** is a schematic cross-sectional view illustrating a package board according to another exemplary embodiment in the present disclosure.

(124) Referring to FIG. **11**, a package board **100A-2** according to another exemplary embodiment may include a wiring layer **110A-2** and a BEOL layer **120A-2** disposed on the wiring layer **110A-2**. The wiring layer **110A-2** may include build-up insulating layers **111** and build-up metal layers **112** formed in the build-up insulating layers **111**. The BEOL layer **120A-2** may include insulating layers **121** and metal layers **122** formed in the insulating layers **121**. If necessary, the package board **100A-2** may further include a first passivation layer **141** disposed on the wiring layer **110A-2** and having a plurality of openings each exposing at least portions of the lowermost build-up metal layer **112**, a second passivation layer **142** disposed on the BEOL layer **120A-2** and having a plurality of openings each exposing at least portions of the uppermost metal layer **122**, and/or a plurality of electrical connection conductors **130** each formed on the plurality of openings of the first passivation layer **141**.

(125) As such, the package board **100A-2** according to another exemplary embodiment may be a coreless-type multilayer board, and may be applied to the semiconductor package **500A** according to the exemplary embodiment described above when the package board **100A-2** includes the BEOL layer **120A-2** and be applied the semiconductor package **500B** according to another exemplary embodiment described above when the BEOL layer **120A-2** is replaced with the wiring layer **110A-2**.

(126) Other contents, for example, the contents described in the semiconductor packages **500A**, **500B**, and **500C** described above and the package board **100A-1** described above may be applied to the package board **100A-2** as long as there is no contradiction, and a description of overlapping contents is omitted.

(127) FIG. **12** is a schematic cross-sectional view illustrating an interposer board according to an exemplary embodiment in the present disclosure.

(128) Referring to FIG. **12**, an interposer board **200A-1** according to an exemplary embodiment may be an organic interposer. For example, the interposer board **200A-1** may be a coreless-type organic multilayer board. For example, the interposer board **200A-1** according to an exemplary embodiment may include a wiring layer **210A-1** and a BEOL layer **220A-1** disposed on the wiring layer **210A-1**. The wiring layer **210A-1** may include a plurality of insulating layers **211a-1** and a plurality of metal layers **212a-1**. The BEOL layer **220A-1** may include one or more insulating layers **221a-1** and one or more metal layers **222a-1**. The interposer board **200A-1** may further include first and second passivation layers **241-1** and **242-1** and a plurality of electrical connection conductors **230**, if necessary.

(129) Each of the insulating layers **211a-1** and **221a-1** may include an organic insulating material. The organic insulating material may be a thermosetting resin such as an epoxy resin, a thermoplastic resin such as a polyimide resin, a resin in which the thermosetting resin or the thermoplastic resin is mixed with an inorganic filler such as silica or is impregnated in a core material of an inorganic filler, for example, prepreg, ABE, FR-4, BT, or the like, but is not limited thereto. The numbers of insulating layers **211a-1** and **221a-2** are not particularly limited, and may be variously modified depending on a design. Boundaries between the insulating layers **211a-1** and **221a-2** may be apparent, or the insulating layers **211a-1** and **221a-2** may be integrated with each other so that boundaries therebetween are not apparent.

(130) The metal layers **212a-1** may include wirings for power transmission, wirings for signal transmission, wirings for ground transmission, and the like. The wirings for signal transmission may include various signals other than the wirings for ground transmission and the wirings for power transmission, for example, a data signal and the like. Each of these wirings may include a trace pattern, a via pattern, and the like. The trace pattern may include a pad pattern and the like. Each of the metal layers **212a-1** may include a conductive material, specifically, a metal material, such as copper (Cu), aluminum (Al), silver (Ag), tin (Sn), gold (Au), nickel (Ni), lead (Pb), titanium (Ti), or alloys thereof. Each of the metal layers **212a-1** may include an electroless plating layer (or chemical copper) and an electroplating layer (or electrolytic copper). The via pattern of the metal layer **212a-1** may have a shape in which it is tapered downward on cross section, but is not limited thereto.

(131) The metal layers **222a-1** may mainly include wirings for power transmission. However, the metal layers **222a-1** may further include some wirings for signal transmission and/or some wirings for ground transmission, if necessary. Here, the wiring for power transmission may be a wiring for transmitting power to the semiconductor chip. In addition, the phrase “mainly include the wirings for power transmission” may mean that a total area occupied by the wirings for power transmission is greater than a total area occupied by the wirings for signal transmission and/or the wirings for ground transmission in plan view. In the case of a plurality of layers, the sums of areas in plan view in respective layers may be compared with each other, and the areas in plan view in the respective layers may be determined with the exception of vias overlapping pads or the like of the respective

layers. Each of these wirings may include a trace pattern, a via pattern, and the like. The trace pattern may include a pad pattern and the like. Each of the metal layers **222a-1** may include a conductive material, specifically, a metal material, such as copper (Cu), aluminum (Al), silver (Ag), tin (Sn), gold (Au), nickel (Ni), lead (Pb), titanium (Ti), or alloys thereof. Each of the metal layers **212a-1** may include an electroless plating layer (or chemical copper) and an electroplating layer (or electrolytic copper). The via pattern of the metal layer **222a-1** may have a shape in which it is tapered downward on cross section, but is not limited thereto.

(132) The first and second passivation layers **241-1** and **242-2** may be disposed at both outermost sides of the interposer board **200A-1**, respectively, to protect internal components. A material of each of the first and second passivation layers **241-1** and **242-2** is not particularly limited. For example, an insulating material may be used as the material of each of the first and second passivation layers **241-1** and **242-2**. In this case, the insulating material may be a solder resist. However, a material of each of the first and second passivation layers **241-1** and **242-2** is not limited thereto, but may also be ABF or the like.

(133) The plurality of electrical connection conductors **230** may externally physically and/or electrically connect the interposer board **200A-1**. For example, the interposer board **200A-1** may be a BGA-type board. Each of the plurality of electrical connection conductors **230** may include a low melting metal having a lower melting point than copper (Cu), such as tin (Sn) or alloys including tin (Sn). For example, each of the plurality of electrical connection conductors **230** may include a solder, but this is only an example, and a material of each of the electrical connection conductors **230** is not particularly limited thereto. The plurality of electrical connection conductors **230** may be lands, balls, pins, or the like. The plurality of electrical connection conductors **230** may be a single layer or multiple layers. When the plurality of electrical connection conductors **230** are formed as multilayer layers, the plurality of electrical connection conductors **230** may include a copper (Cu) pillar and a solder. When the plurality of electrical connection conductors **230** are formed as a single layer, the plurality of electrical connection conductors **230** may include a solder. However, this is only an example, and the plurality of electrical connection conductors **230** are not limited thereto.

(134) Other contents, for example, the contents described in the semiconductor packages **500A**, **500B**, and **500C** described above may be applied to the interposer board **200A-1** as long as there is no contradiction, and a description of overlapping contents is omitted.

(135) FIG. **13** is a schematic cross-sectional view illustrating an interposer board according to another exemplary embodiment in the present disclosure.

(136) Referring to FIG. **13**, an interposer board **200A-2** according to another exemplary embodiment may be an inorganic interposer. For example, the interposer board **200A-2** may be a silicon interposer. For example, the interposer board **200A-2** according to another exemplary embodiment may include a wiring layer **210A-2** and a BEOL layer **220A-2** disposed on the wiring layer **210A-2**. The wiring layer **210A-2** may include one or more insulating layers **211a-2** and one or more metal layers **212a-2**. The BEOL layer **220A-2** may include one or more insulating layers **221a-2** and one or more metal layers **222a-2**. The interposer board **200A-2** may further include first and second passivation layers **241-2** and **242-2** and a plurality of electrical connection conductors **230**, if necessary.

(137) The insulating layers **211a-2** and **221a-2** may provide a body of the interposer board **200A-2**. Each of the insulating layers **211a-2** and **221a-2** may include an insulating material. In this case, the insulating material may include silicon, more specifically, silicon dioxide. In this case, the interposer board **200A-2** may be formed by a semiconductor wafer process, and thus, the metal layers **212a-2** and **222a-2** may be easily designed at a high density. However, a material of each of the insulating layers **211a-2** and **221a-2** is not limited thereto, and may be other semiconductor materials. The numbers of insulating layers **211a-2** and **221a-2** are not particularly limited, and may be variously modified depending on a design. When the insulating layers **211a-2** and **221a-2** are

multilayer, boundaries between the insulating layers **211a-2** and **221a-2** may be apparent or may not be apparent.

(138) The metal layers **212a-2** may include wirings for signal transmission, wirings for power transmission, wirings for ground transmission, and the like. The wirings for signal transmission may include various signals other than the wirings for ground transmission and the wirings for power transmission, for example, a data signal and the like. Each of the metal layers **212a-2** may include a conductive material, specifically, a metal material, such as copper (Cu), aluminum (Al), silver (Ag), tin (Sn), gold (Au), nickel (Ni), lead (Pb), titanium (Ti), or alloys thereof. Each of the metal layers **212a-2** may be formed by a deposition process such as chemical vapor deposition (CVD), but is not limited thereto. The number of metal layers **212a-2** is also not particularly limited, and may be modified depending on a design. The metal layers **212a-2** may include vias **213a** for interlayer electrical connection, and the vias **213a** may be through silicon vias (TSVs), but are not limited thereto.

(139) The metal layers **222a-2** may mainly include wirings for power transmission. However, the metal layers **222a-2** may further include some wirings for signal transmission and/or some wirings for ground transmission, if necessary. Here, the wiring for power transmission may be a wiring for transmitting power to the semiconductor chip **300**. In addition, the phrase “mainly include the wirings for power transmission” may mean that a total area occupied by the wirings for power transmission is greater than a total area occupied by the wirings for signal transmission and/or the wirings for ground transmission in plan view. In the case of a plurality of layers, the sums of areas in plan view in respective layers may be compared with each other, and the areas in plan view in the respective layers may be determined with the exception of vias overlapping trace patterns or the like of the respective layers. Each of the metal layers **222a-2** may include a conductive material, specifically, a metal material, such as copper (Cu), aluminum (Al), silver (Ag), tin (Sn), gold (Au), nickel (Ni), lead (Pb), titanium (Ti), or alloys thereof. Each of the metal layers **222a-2** may be formed by a deposition process such as CVD, but is not limited thereto. The number of metal layers **222a-2** is also not particularly limited, and may be modified depending on a design. The metal layers **222a-2** may include vias **223a** for interlayer electrical connection, and the vias **223a** may be TSVs, but are not limited thereto.

(140) The first and second passivation layers **241-2** and **242-2** may be disposed at both outermost sides of the interposer board **200A-2**, respectively, to protect internal components. A material of each of the first and second passivation layers **241-2** and **242-2** is not particularly limited. For example, an insulating material may be used as the material of each of the first and second passivation layers **241-2** and **242-2**. In this case, the insulating material may include an oxide film, a nitride film or the like, but is not limited thereto.

(141) Other contents, for example, the contents described in the semiconductor packages **500A**, **500B**, and **500C** described above and the interposer board **200A-1** described above may be applied to the interposer board **200A-2** as long as there is no contradiction, and a description of overlapping contents is omitted.

(142) FIG. **14** is a schematic cross-sectional view illustrating an interposer board according to another exemplary embodiment in the present disclosure.

(143) Referring to FIG. **14**, an interposer board **200B-1** according to another exemplary embodiment may be an organic interposer in which the wiring layer is omitted from the interposer board **200A-1** described above and a BEOL layer **220B-1** includes a plurality of insulating layers **221b-1** and a plurality of metal layers **222b-1**.

(144) Each of the insulating layers **221b-1** may include an organic insulating material. The organic insulating material may be a thermosetting resin such as an epoxy resin, a thermoplastic resin such as a polyimide resin, a resin in which the thermosetting resin or the thermoplastic resin is mixed with an inorganic filler such as silica or is impregnated in a core material of an inorganic filler, for example, prepreg, ABF, FR-4, BT, or the like, but is not limited thereto. The number of insulating

layers **221b-2** is not particularly limited, and may be variously modified depending on a design. A boundary between the insulating layers **221b-1** may be apparent, or the insulating layers **221b-1** may be integrated with each other so that a boundary therebetween is not apparent.

(145) The metal layers **222b-1** may mainly include wirings for power transmission. However, the metal layers **222b-1** may further include some wirings for signal transmission and/or some wirings for ground transmission, if necessary. Here, the wiring for power transmission may be a wiring for transmitting power to the semiconductor chip **300**. In addition, the phrase “mainly include the wirings for power transmission” may mean that a total area occupied by the wirings for power transmission is greater than a total area occupied by the wirings for signal transmission and/or the wirings for ground transmission in plan view. In the case of a plurality of layers, the sums of areas in plan view in respective layers may be compared with each other, and the areas in plan view in the respective layers may be determined with the exception of vias overlapping pads or the like of the respective layers. Each of these wirings may include a trace pattern, a via pattern, and the like. The trace pattern may include a pad pattern and the like. Each of the metal layers **222b-1** may include a conductive material, specifically, a metal material, such as copper (Cu), aluminum (Al), silver (Ag), tin (Sn), gold (Au), nickel (Ni), lead (Pb), titanium (Ti), or alloys thereof. Each of the metal layers **222b-1** may include an electroless plating layer (or chemical copper) and an electroplating layer (or electrolytic copper). The via pattern of the metal layer **222b-1** may have a shape in which it is tapered downward on cross section, but is not limited thereto.

(146) Other contents, for example, the contents described in the semiconductor packages **500A**, **500B**, and **500C** described above and the interposer boards **200A-1** and **200A-2** described above may be applied to the interposer board **200B-1** as long as there is no contradiction, and a description of overlapping contents is omitted.

(147) FIG. **15** is a schematic cross-sectional view illustrating an interposer board according to another exemplary embodiment in the present disclosure.

(148) Referring to FIG. **15**, an interposer board **200B-2** according to another exemplary embodiment may be a silicon interposer in which the wiring layer is omitted from the interposer board **200A-2** described above and a BEOL layer **220B-2** includes one or more insulating layers **221b-2** and one or more metal layers **222b-2**.

(149) The insulating layers **221b-2** may provide a body of the interposer board **200B-2**. Each of the insulating layers **221b-2** may include an insulating material. In this case, the insulating material may include silicon, more specifically, silicon dioxide. In this case, the interposer board **200B-2** may be formed by a semiconductor wafer process, and thus, the metal layers **222b-2** may be easily designed at a high density. However, a material of each of the insulating layers **221b-2** is not limited thereto, and may be other semiconductor materials. The number of insulating layers **221b-2** is not particularly limited, and may be variously modified depending on a design. When the insulating layers **221b-2** are multilayer, a boundary between the insulating layers **221b-2** may be apparent or may not be apparent.

(150) The metal layers **222b-2** may mainly include wirings for power transmission. However, the metal layers **222b-2** may further include some wirings for signal transmission and/or some wirings for ground transmission, if necessary. Here, the wiring for power transmission may be a wiring for transmitting power to the semiconductor chip **300**. In addition, the phrase “mainly include the wirings for power transmission” may mean that a total area occupied by the wirings for power transmission is greater than a total area occupied by the wirings for signal transmission and/or the wirings for ground transmission in plan view. In the case of a plurality of layers, the sums of areas in plan view in respective layers may be compared with each other, and the areas in plan view in the respective layers may be determined with the exception of vias overlapping trace patterns or the like of the respective layers. Each of the metal layers **222b-2** may include a conductive material, specifically, a metal material, such as copper (Cu), aluminum (Al), silver (Ag), tin (Sn), gold (Au), nickel (Ni), lead (Pb), titanium (Ti), or alloys thereof. Each of the metal layers **222b-2** may be

formed by a deposition process such as CVD, but is not limited thereto. The number of metal layers **222b-2** is also not particularly limited, and may be modified depending on a design. The metal layers **222b-2** may include vias **223b** for interlayer electrical connection, and the vias **223b** may be TSVs, but are not limited thereto.

(151) Other contents, for example, the contents described in the semiconductor packages **500A**, **500B**, and **500C** described above and the interposer boards **200A-1**, **200A-2**, and **200B-1** described above may be applied to the interposer board **200B-2** as long as there is no contradiction, and a description of overlapping contents is omitted.

(152) As set forth above, according to an exemplary embodiment in the present disclosure, a semiconductor chip of which a process cost may be decreased, and a semiconductor package including the same may be provided.

(153) In addition, a semiconductor chip capable of solving a cost problem due to a decrease in yield of the semiconductor chip, and a semiconductor package including the same may be provided.

(154) While exemplary embodiments have been shown and described above, it will be apparent to those skilled in the art that modifications and variations could be made without departing from the scope of the present invention as defined by the appended claims.

Claims

1. A semiconductor package comprising: a semiconductor chip including a front end of line (FEOL) layer and a first back end of line (BEOL) layer disposed on the FEOL layer; and a printed circuit board including a wiring layer and a second BEOL layer disposed on the wiring layer, wherein the semiconductor chip is mounted on the printed circuit board so that the first and second BEOL layers are connected to each other, the second BEOL layer includes a wiring for power transmission, and the first BEOL layer is between the FEOL layer and the second BEOL layer.
2. The semiconductor package of claim 1, wherein the wiring for power transmission is a wiring for transmitting power to the semiconductor chip.
3. The semiconductor package of claim 1, wherein the first BEOL layer is disposed adjacent to a bottom side of the semiconductor chip, and the second BEOL layer is disposed adjacent to a top side of the printed circuit board.
4. The semiconductor package of claim 1, wherein the FEOL layer includes a first circuit unit including a plurality of first transistor elements and a second circuit unit including a plurality of second transistor elements, the first and second BEOL layers include first and second wiring units electrically connected to the first and second circuit units, respectively, the first wiring unit does not include a trace pattern for power transmission interconnecting the first and second circuit units within the first BEOL layer, and the second wiring unit includes a trace pattern for power transmission interconnecting the first and second circuit units within the second BEOL layer.
5. The semiconductor package of claim 4, wherein the first wiring unit does not include a trace pattern for power transmission interconnecting at least two of the plurality of first transistor elements and a trace pattern for power transmission interconnecting at least two of the second transistor elements within the first BEOL layer, and the second wiring unit includes a trace pattern for power transmission interconnecting at least two of the plurality of first transistor elements and a trace pattern for power transmission interconnecting at least two of the second transistor elements within the second BEOL layer.
6. The semiconductor package of claim 1, wherein the first BEOL layer includes a plurality of metal layers, and a first metal layer closest to the FEOL layer among the plurality of metal layers includes a trace pattern for signal transmission, but does not include a trace pattern for power transmission.
7. The semiconductor package of claim 6, wherein the trace pattern for power transmission that is not included in the first metal layer includes at least one of a trace pattern for a positive supply

voltage (VDD) and a trace pattern for a negative supply voltage (VSS).

8. The semiconductor package of claim 6, wherein the first metal layer includes a via pattern for power transmission electrically connected to the wiring for power transmission of the second BEOL layer.

9. The semiconductor package of claim 8, wherein the via pattern for power transmission that is included in the first metal layer includes at least one of a via pattern for a positive supply voltage (VDD) and a via pattern for a negative supply voltage (VSS).

10. The semiconductor package of claim 1, wherein the second BEOL layer includes one or more insulating layers and one or more metal layers, and the one or more insulating layers include an organic insulating material.

11. The semiconductor package of claim 1, wherein the semiconductor chip further includes a redistribution layer disposed on the first BEOL layer, and the first and second BEOL layers are connected to each other through the redistribution layer.

12. The semiconductor package of claim 1, further comprising: a plurality of connection conductors disposed between the printed circuit board and the semiconductor chip and connecting the printed circuit board and the semiconductor chip to each other; and a plurality of electrical connection conductors disposed on the other surface of the printed circuit board opposing one surface of the printed circuit board on which the semiconductor chip is mounted and connected to the printed circuit board, wherein each of the plurality of connection conductors includes a solder bump, and each of the plurality of electrical connection conductors includes a solder ball.

13. The semiconductor package of claim 1, wherein silicon is not disposed between the first and second BEOL layers.

14. The semiconductor package of claim 13, wherein a wiring pitch of the second BEOL layer is greater than a wiring pitch of the first BEOL layer.

15. The semiconductor package of claim 1, wherein the first BEOL layer is spaced apart from the second BEOL layer.

16. A semiconductor package comprising: a semiconductor chip including a first BEOL layer, and a FEOL layer; an interposer board including a second BEOL layer; and a package board including a wiring layer, wherein the semiconductor chip is mounted on the interposer board, the interposer board is mounted on the package board, the first and second BEOL layers are connected to each other, the second BEOL layer includes a wiring for power transmission, and the first BEOL layer is between the FEOL layer and the second BEOL layer.

17. The semiconductor package of claim 16, wherein the interposer board is an organic interposer or an inorganic interposer, the organic interposer includes a coreless-type board, and the inorganic interposer includes a silicon interposer.

18. The semiconductor package of claim 16, further comprising: a plurality of connection conductors disposed between the semiconductor chip and the interposer board and connecting the semiconductor chip and the interposer board to each other; and a plurality of first electrical connection conductors disposed between the interposer board and the package board and connecting the interposer board and the package board to each other; and a plurality of second electrical connection conductors disposed on the other surface of the package board opposing one surface of the package board on which the interposer board is disposed and connected to the package board, wherein each of the plurality of connection conductors includes a solder bump, and each of the plurality of first and second electrical connection conductors includes a solder ball.

19. A semiconductor chip comprising: a FEOL layer including a plurality of circuit units each including a plurality of transistor elements; and a BEOL layer disposed on the FEOL layer and including a wiring unit electrically connected to the plurality of circuit units, wherein the wiring unit does not include a trace pattern for power transmission interconnecting at least two of the plurality of circuit units.

20. The semiconductor chip of claim 19, wherein the wiring unit does not include a trace pattern

for power transmission interconnecting at least two of the plurality of transistor elements of at least one of the plurality of circuit units.

21. A semiconductor package comprising: a semiconductor chip including a FEOL layer and a first BEOL layer disposed on the FEOL layer, the FEOL layer including a first circuit unit including a plurality of first transistor elements and a second circuit unit including a plurality of second transistor elements, and the first BEOL layer including a first wiring unit electrically connected to the first and second circuit units; and a printed circuit board including a second BEOL layer including a second wiring unit electrically connected to the first wiring unit, wherein the semiconductor chip is mounted on the printed circuit board, the first wiring unit does not include a trace pattern for power transmission interconnecting the first and second circuit units within the first BEOL layer, the second wiring unit includes a trace pattern for power transmission interconnecting the first and second circuit units within the second BEOL layer, the first BEOL layer is between the FEOL layer and the second BEOL layer.

22. The semiconductor package of claim 21, wherein the first wiring unit does not include a trace pattern for power transmission interconnecting at least two of the plurality of first transistor elements within the first BEOL layer, and the second wiring unit includes a trace pattern for power transmission interconnecting at least two of the plurality of first transistor elements within the second BEOL layer.

23. The semiconductor package of claim 21, wherein the first wiring unit does not include a trace pattern for power transmission interconnecting at least two of the plurality of second transistor elements within the first BEOL layer, and the second wiring unit includes a trace pattern for power transmission interconnecting at least two of the plurality of second transistor elements within the second BEOL layer.
