

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12397237
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	DuPlessie; Matthew

Systems and methods for providing self-resetting games in interactive physical environments

Abstract

A self-resetting game provided by an interactive physical environment includes a plurality of game components, a room sensor, a control system and an indicator. The plurality of game components are repositionable within a game room provided by the interactive physical environment. The room sensor detects a first position of at least some of the plurality of game components. The control system receives, from the room sensors, the detected position and selects, responsive to the received position information, one of a plurality of game solutions requiring the plurality of game components to be rearranged into a second position different from the first position. The indicator detects the selected one of the game solutions.

Inventors:	DuPlessie; Matthew (Foxboro, MA)
Applicant:	Open World Entertainment LLC (Natick, MA)
Family ID:	1000008778993
Assignee:	Open World Entertainment LLC (Natick, MA)
Appl. No.:	17/877821
Filed:	July 29, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20240042329 A1	Feb. 08, 2024
US 20240325926 A9	Oct. 03, 2024

Related U.S. Application Data

division parent-doc US 17838141 20220610 US 11524244 20221213 child-doc US 17877821
division parent-doc US 17837972 20220610 US 11935171 20240319 child-doc US 17877821

Publication Classification

Int. Cl.: A63F13/77 (20140101); G07F17/32 (20060101); A63F9/24 (20060101)

U.S. Cl.:

CPC A63F13/77 (20140902); G07F17/3216 (20130101); G07F17/3227 (20130101); G07F17/3241 (20130101); A63F2009/2442 (20130101); A63F2009/246 (20130101); A63F2009/2489 (20130101)

Field of Classification Search

CPC: A63B (9/00); A63F (13/214); A63F (13/2145); A63F (13/216); A63F (13/217); A63F (13/235); A63F (13/45); A63F (13/53); A63F (13/533); A63F (13/537); A63F (13/70); A63F (13/79); A63F (13/80); A63F (13/90); A63F (2300/80)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
7749089	12/2009	Briggs et al.	N/A	N/A
11161050	12/2020	Schmidt	N/A	N/A
11452944	12/2021	Schmidt	N/A	N/A
11524244	12/2021	DuPlessie	N/A	N/A
11935171	12/2023	Duplessie	N/A	N/A
12165248	12/2023	DuPlessie	N/A	N/A
2013/0179779	12/2012	Sandler et al.	N/A	N/A
2016/0086500	12/2015	Kaleal, III	N/A	N/A
2017/0189815	12/2016	Tweedale et al.	N/A	N/A
2018/0078848	12/2017	Henrie	N/A	A63F 9/24
2019/0143223	12/2018	Tamiya et al.	N/A	N/A
2019/0220634	12/2018	Cossairt et al.	N/A	N/A
2020/0360826	12/2019	Schmidt	N/A	N/A
2021/0016185	12/2020	Linguanti et al.	N/A	N/A
2021/0042762	12/2020	Budano et al.	N/A	N/A
2021/0220688	12/2020	Schmidt	N/A	N/A
2021/0220714	12/2020	Schmidt	N/A	N/A
2021/0220725	12/2020	Schmidt	N/A	N/A
2021/0335072	12/2020	Caldwell et al.	N/A	N/A
2021/0339123	12/2020	Boudville	N/A	N/A
2022/0105436	12/2021	Schmidt	N/A	N/A
2022/0398799	12/2021	DuPlessie	N/A	N/A
2024/0185495	12/2023	DuPlessie	N/A	N/A
2024/0265611	12/2023	DuPlessie	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
------------	------------------	---------	-----

3064047	12/2019	CA	N/A
3064047	12/2019	CA	N/A
3068840	12/2020	CA	N/A
3068847	12/2020	CA	N/A
3068860	12/2020	CA	N/A

OTHER PUBLICATIONS

Andrew H. Rolter and Donna Abbott-Vlahos, “Dragonslaying as a Teambuilding Exercise: Inside Crossgates' New Live-Action Entertainment Center”, Albany Business Review, Dec. 5, 2016. cited by applicant

Andrew H. Rolter and Donna Abbott-Vlahos, Photo—Lobby, “Dragonslaying as a Teambuilding Exercise: Inside Crossgates' New Live-Action Entertainment Center”, Albany Business Review, Dec. 5, 2016. cited by applicant

Anonymous, “A grandparent's cheat sheet: Local places for fun with the grandkids”, www.townonline.com, retrieved on Oct. 17, 2006. cited by applicant

Anonymous, “At museum, die another day”, Washington Times, Aug. 3, 2007. cited by applicant

Anonymous, “AV Stumpfl Show Control Helps the Pharaoh Find His Tomb!”, AV Stumpfl USA Corp Application Note. cited by applicant

Anonymous, “AV Stumpfl Show Control Helps the Pharaoh Find His Tomb!”, www.stumpfl.com, retrieved Feb. 2, 2005. cited by applicant

Anonymous, “Boston Tomb”, Spirit—Southwest Airlines, Feb. 2008. cited by applicant

Anonymous, “Five Questions with Matthew DuPlessie” Saratogian Business, Feb. 7, 2017. cited by applicant

Anonymous, “Now Playing—Uptown & Downtown”, Post-Gazette, Jun. 2, 2006. cited by applicant

Anonymous, The Boston Parents' Paper 2005 Family Favorite Award—Favorite Adventure Place—Editor's Pick: 5Wits Tomb Adventure. cited by applicant

Anonymous, “The Future of Entertainment”, www.knowyourboston.com, retrieved on Feb. 10, 2005. cited by applicant

Anonymous, “The Future of Entertainment”, www.knowyourboston.com, retrieved on Feb. 10, 2005, Cover. cited by applicant

Anonymous, “The Games People Play”, Stuff@night, Nov. 19, 2007. cited by applicant

Anonymous, www.magazineblu.com. cited by applicant

Arthur Levine, “Tomb at 5WITS”, www.themeparks.about.com, retrieved Feb. 2, 2005. cited by applicant

Arthur Levine, “Tomb Much Fun”, www.themeparks.about.com, Oct. 25, 2004. cited by applicant

Ay-Leen the Peacemaker, “Puzzle Your Way Out of Nemo's Submarine in 5 Wits's “20,000 Leagues” Interactive Adventure”, www.tor.com, Sep. 7, 2011. cited by applicant

Camille Doder, “Battling the Pharaoh in the Fenway”, The Boston Phoenix, Feb. 2, 2005. cited by applicant

Channel 5 News Broadcast, Patriot Place WCVB, Jan. 19, 2011. cited by applicant

Channing Gray, “Patriot Games”, Journal Express, an edition of the Providence Journal, Feb. 14, 2013. cited by applicant

Channing Gray, “Patriot Games”, Providence Journal, Jan. 10, 2013. cited by applicant

Chikage Windler, “Great Escape: Unlock the Secrets of Egypt”, WHDH Channel 7 News Transcript, Mar. 10, 2005. cited by applicant

Christin Steding, “Checking out 5 Wits at Crossgates, and other Capital Region escape rooms”, All Over Albany, Sep. 21, 2017. cited by applicant

Christina Couch, “License to Thrill”, www.airtranmagazine.com, Jul. 2007. cited by applicant

Chronicle, Channel 5 News Broadcast, Nov. 6, 2007. cited by applicant

David A. Kelly, "Fun if by Land and Fun if by Sea in Boston", The New York Times, Aug. 21, 2005. cited by applicant

David L. Ryan, "Best of the New: Entertainment", www.boston.com, retrieved on Mar. 16, 2005. cited by applicant

Elizabeth Papp, AAA Horizons Press Release, Jan. 24, 2013. cited by applicant

Esther Fung, "Shopping Malls' New Product: Fun", The Wall Street Journal, Aug. 30, 2016. cited by applicant

Ethan Gilsdorf, "At this attraction, you're not just along for the ride", The Christian Science Monitor, Apr. 21, 2006. cited by applicant

Ethan Gilsdorf, "Spy Guy", The Boston Globe Magazine, Apr. 2, 2006, JPG. cited by applicant

Ethan Gilsdorf, "Spy Guy", The Boston Globe Magazine, Apr. 2, 2006, PDF. cited by applicant

Heather Crowell, "PREIT Introduces New Experiential Concepts as Part of Ongoing Evolution at Plymouth Meeting Mall", PREIT, Nov. 6, 2017. cited by applicant

Jenn Romatelli, "Tomb: A Review", The Larper, retrieved Feb. 2, 2005. cited by applicant

Jinnie Lee, "Use Your Wits", Panorama, Jun. 19, 2006. cited by applicant

Jody Feinberg, "Tomb raiders: Interactive game takes you on a sensory adventure", The Patriot Ledger, Feb. 2, 2005. cited by applicant

Joe O'Shea, "You'll Need Your Wits About You in Boston's Tomb Experience", AAA Horizons Southern New England, Oct. 2007. cited by applicant

Johnny Monsarat, "5-Wits is New England's Best Escape Room (5 stars)", bostoneventsinsider.com, Feb. 23, 2018. cited by applicant

Johnny Monsarrat, "5-Wits at Patriot Place is a Room Escape Challenge at Movie Set Quality", Events Insider, Apr. 2017. cited by applicant

Josh Young, "5 Wits Brings New Puzzle Solving Adventures to Themed Entertainment", Theme Park University, Jun. 13, 2013. cited by applicant

Josh Young, "5 Wits Entertainment Center Carves Out Unique Niche in the Themed Entertainment", Theme Park University, Aug. 17, 2017. cited by applicant

Julie Sloan, "Sales From the Crypt", Fortune Small Business, Dec. 2005. cited by applicant

Julie Sloan, "Sales From the Crypt", www.fortune.com, Dec. 2005. cited by applicant

Kassmin Williams, "Haunted Sub", Go—The Sun Chronicle, Oct. 24, 2013. cited by applicant

Kathy Ceceri, "Visit a Tomb in Boston", www.wired.com, Jul. 16, 2009. cited by applicant

Kayte Deidoma, "Rainy Day in Boston", www.rainydaytraveler.com, retrieved Aug. 2, 2005. cited by applicant

Kayte Deloma, "Boston Interactive", www.rainydaytraveler.com. retrieved on Aug. 2, 2005. cited by applicant

Kevin Tampone, "5 Wits sneak peek: Get ready for adventure at Destiny USA (video)", www.syracuse.com, Feb. 20, 2014. cited by applicant

Kevin Tampone, "Dive Into a Video Game", Syracuse Post Standard, Feb. 23, 2014. cited by applicant

Kim Foley MacKinnon, "Tomb will show you the mummy", Boston Herald, Jun. 15, 2006, JPG. cited by applicant

Kim Foley MacKinnon, "Tomb will show you the mummy", Boston Herald, Jun. 15, 2006, PDF. cited by applicant

Kim Knox Beckius, "Tomb: Boston Attraction Will Test Your Wits", www.GoNewEngland.com, retrieved Feb. 2, 2005. cited by applicant

Larry Claflin Jr., "Test your family's wits at Tomb", Sunday Eagle-Tribune, Nov. 26, 2006. cited by applicant

Lisa Neal, "Five Questions . . . for Matt DuPlessie", eLearn Magazine, Feb. 28, 2008. cited by applicant

Liza Weisstuch, "Tomb at 5W!Ts", The Boston Globe, Oct. 20, 2004. cited by applicant

Matt Albany, Photo of Grand Opening with Guides Standing in Front of One of Several Game Rooms. cited by applicant

Meredith Tibbetts, “Jules Verne meets Patriot Place”, www.thesunchronicle.com, Mar. 9, 2014. cited by applicant

Paul D. Lehrman, “Ancient Tomb Reveals Low-Cost Audio of Tomorrow!”, Insider Audio, Oct. 2004. cited by applicant

Peter Demarco, “Mummy Complex”, Globe Newspaper Company, Sep. 22, 2004. cited by applicant

Peter Demarco, “Mummy Complex”, The Boston Globe, Sep. 22, 2004, JPG. cited by applicant

Peter Demarco, “Mummy Complex”, The Boston Globe, Sep. 22, 2004, PDF. cited by applicant

Peter Demarco, “Mummy Complex”, www.boston.com, Sep. 22, 2004. cited by applicant

Regina Velazquez, 5 Wits before Wits' End, www.GraylockGlass.com, Jul. 2019. cited by applicant

Richard Pastore, “The New Pocket-Sized Theme Park Concept”, www.cio.com, Feb. 1, 2005, JPG. cited by applicant

Richard Pastore, “The New Pocket-Sized Theme Park Concept”, www.cio.com, Feb. 1, 2005, PDF. cited by applicant

Robert Perkin, “Your Chance to Fill Indiana Jones' Shoes”, www.gamevortex.com, retrieved on Jul. 24, 2006. cited by applicant

Sandra Giardi, “Kid Tested, Parent Approved”, Where, the Complete Guide to Go, www.wheretraveler.com, Jul. 2008. cited by applicant

Stephanie Ebbert, “Game for a Life-Size Puzzle?”, The Boston Globe, Mar. 2, 2013. cited by applicant

Stephanie Ebbert, Spy Kids Infiltrate Life-Size Video Game, the Boston Globe, Mar. 1, 2013. cited by applicant

Tenley Woodman, “Tomb opens doors to Indy-style adventures”, www.theedge.bostonherald.com, Sep. 22, 2004. cited by applicant

Teresa Mendez, “At some museums, you're now Exhibit A”, The Christian Science Monitor, Oct. 19, 2007. cited by applicant

Teresa Mendez, “At some museums, you're now Exhibit A”, The Christian Science Monitor, www.csmonitor.com, Oct. 19, 2007. cited by applicant

Various, Notable Quotations from Recent Tomb Press, 5W!TS, May 2008. cited by applicant

Various, Recent Press Praising Tomb, now showing at 5W!TS Boston, 5W!TS, Jul. 2009. cited by applicant

Non-final Office Action for U.S. Appl. No. 17/837,972 dated Nov. 2, 2023. cited by applicant

Activate-Louisville Facebook Posting, <https://www.facebook.com/activategameslouisville/videos/activate-games-now-open/2688323521235018>, published on Dec. 2, 2019. cited by applicant

Non-Final Office Action on U.S. Appl. No. 17/838,141 dtd Aug. 26, 2022. cited by applicant

Notice of Allowance for U.S. Appl. No. 17/837,972 dated Feb. 8, 2024. cited by applicant

Primary Examiner: Deodhar; Omkar A

Attorney, Agent or Firm: Foley Hoag LLP

Background/Summary

CROSS-REFERENCE TO RELATED PATENT APPLICATIONS (1) This application is a divisional application of U.S. patent application Ser. No. 17/838,141, filed Jun. 10, 2022 (now U.S.

Pat. No. 11,524,244), and U.S. patent application Ser. No. 17/837,972, filed Jun. 10, 2022 (now U.S. Pat. No. 11,935,171), both of which claim the benefit of and priority to U.S. Provisional Patent application No. 63/209,957, filed Jun. 11, 2021. The entire disclosures of U.S. patent application Ser. No. 17/838,141, U.S. patent application Ser. No. 17/837,972, and U.S. Provisional Patent Application No. 63/209,957 are incorporated by reference herein.

BACKGROUND

(1) The described technology relates generally to the field of interactive physical environments and, in particular, interactive physical environments that provide entertainment to patrons.

SUMMARY

(2) In one aspect, the described technology relates to an interactive physical environment providing entertainment to a patron. The interactive physical environment includes a room formed by modular walls coupled to one another. The room presents a game to a patron that has game components positionable in a first game configuration and a second game configuration. The first game configuration presents a first challenge to a patron of the room and the second game configuration presents a second challenge to the patron. The second game configuration representing a solution to the first challenge. A radio frequency identification (RFID) tag is associated with the patron, and a control system receives patron identification information from the RFID tag. The control system selectively modifies the game presented by the room responsive to the received patron identification information.

(3) In some embodiments, the room includes a door and the control system can operate the door to control ingress to the room. In other embodiments, the room includes a screen displaying patron status information received from the control system. In some of these other embodiments, the screen displays an avatar associated with the patron that is received from the control system. In others of these embodiments, the screen displays a hint for the game that is received from the control system.

(4) In other embodiments, the control system monitors patron performance while playing the game. In still other embodiments, the control system modifies an avatar associated with the patron responsive to the patron performance. In yet other embodiments, the control system awards a reward point to the patron responsive to the completion of the game by the patron. The interactive physical environment may also include a registration kiosk to receive information from the patron that is used to associate the RFID tag with the patron.

(5) In another aspect, the described technology relates to a method for providing entertainment to a patron in a physical environment. Modular walls are coupled to one another to form a room. A game is presented to a patron, in the formed room. The game has components positionable in a first game configuration and a second game configuration. The first game configuration presents a first challenge to a patron and the second game configuration presenting a second challenge to the patron. The second game configuration representing a solution to the first challenge. A radio frequency identification (RFID) tag is associated with the patron. Patron identification information from the RFID tag associated with the patron is received by a control system. The control system uses the received patron identification information to selectively modify the game presented by the room.

(6) In some embodiments, a door is provided to control ingress to the room. In other embodiments, patron status information is received from the control system and displayed on a screen. In still other embodiments, an avatar associated with the patron is received from the control system and displayed on a screen. In some of these still other embodiments the control system modifies the avatar associated with the patron responsive to the patron performance.

(7) In some other embodiments, a hint for the game is received from the control system and displayed on a screen. In yet other embodiments the control system monitors patron performance. In other embodiments, the control system awards a reward point to the patron responsive to the

completion of the game by the patron. Information from the patron can be received at a registration kiosk and used to associate the RFID tag with the patron.

(8) In another aspect, the described technology relates to an interactive physical environment providing entertainment to a patron. A scanner identifies a patron of the interactive physical environment and transmits patron identification information. A sensor determines and transmits patron game performance data. A control system receives patron identification information from the scanner and patron game performance data from the sensor and, responsive to the received patron identification information and patron game performance data, modifies an avatar associated with the patron.

(9) In some embodiments, the scanner is a radio-frequency identification (RFID) tag scanner. In other embodiments, the scanner is a QR code scanner, bar code scanner or biometric characteristic scanner. The scanner may transmit data via a wireless network. In some embodiments, the control system determines that a length of time taken by the patron to complete a game has exceeded a predetermined limit while in other embodiments the control system determines whether an objective of the game has been achieved by the patron. In further embodiments, the control system configures an avatar associated with the patron by: retrieving, from a data storage element, a data structure representing an avatar associated with the patron via the patron identifying information; updating the data structure responsive to the received game performance data; and storing the updated data structure in the data storage element.

(10) In another aspect, the described technology relates to a method for providing entertainment to a patron via an interactive physical environment. A scanner identifies a patron of the interactive physical environment and transmits patron identification information. A sensor determines and transmits patron game performance data. A control system receives the transmitted patron identification information and patron game performance data and modifies an avatar associated with the patron.

(11) In some embodiments, the scanner identifies the patron by scanning a radio-frequency identification (RFID) tag scanner associated with the patron. In other embodiments, the scanner identifies the patron by scanning a QR code, bar code, or biometric characteristic associated with the patron. In further embodiments, the scanner transmits patron identification information via a wireless network. In still further embodiments, the sensor transmits patron game performance data via a wireless network. In some embodiments, the control system determines that a length of time taken by the patron to complete a game exceeds a predetermined threshold while in other embodiments the control system determines whether an objective of the game has been achieved by the patron. In yet further embodiments, modifying the avatar includes retrieving, from a data storage element, a data structure representing an avatar associated with the patron via the patron identifying information, updating the data structure responsive to the received patron game performance data, and storing the updated data structure in the data storage element. In some of these yet further embodiments the data structure is updated to include a reward amount based on the patron game performance data.

(12) In another aspect, the described technology relates to a self-resetting game provided by an interactive physical environment that minimizes the need for physical intervention to set the game up for subsequent patrons. A plurality of game components are repositionable within a game room provided by the interactive physical environment. In a first game configuration, the game components present a first challenge, which requires reconfiguration of the game components into a first solution configuration. In a second game configuration, the game components present a second challenge requiring reconfiguration of the plurality of game components into a second solution configuration, the second game configuration is different from the second solution configuration. The first game configuration may be different from the first solution configuration. In some embodiments, the second presentation of the plurality of game components is the first solution configuration. In other embodiments the first presentation of the plurality of game

components is the second solution configuration.

(13) In another aspect, the described technology relates to a method for providing a self-resetting game in a game room provided by an interactive physical environment. A plurality of game components are provided that are repositionable within a game room provided by the interactive physical environment. A control system determines that the plurality of game components are in a first configuration presenting a first challenge, the first challenge requiring reconfiguration of the plurality of game components into a first solution configuration. A control system allows a first patron into the game room. The control system detects that the first patron has completed the game and that, after completion by the first patron, the plurality of game components are in second configuration presenting a second challenge, the second challenge requiring reconfiguration of the plurality of game components into a second solution configuration, the second game configuration different from the second solution configuration.

(14) In some embodiments, the control system determines that the first game configuration is different from the first solution configuration. In other embodiments, the control system determines that the second presentation of the plurality of game components is the first solution configuration. In still other embodiments, the control system determines that the first presentation of the plurality of game components is the second solution configuration. In still other embodiments, a second patron is allowed into the game room and the control system determines, after completion by the second patron, that the game components are in a third presentation of the plurality of game components presenting the first challenge. In further embodiments, the control system determines a completion of the game by the first patron by detecting the expiration of a predetermined time period or by detecting that the plurality of game components comprise the first solution configuration.

(15) This summary is illustrative only and is not intended to be in any way limiting. Other aspects, inventive features, and advantages of the devices or processes described herein will become apparent in the detailed description set forth herein, taking in conjunction with the accompanying figures, wherein like reference numerals refer to like elements.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The disclosure will become more fully understood from the following detailed description, taken in conjunction with the accompanying figures, wherein like reference numerals refer to like elements, in which:

(2) FIG. 1 is a perspective view of an interactive physical environment, according to an example embodiment.

(3) FIGS. 2-6 are various views of a check-in screen for a check-in process of a patron entering the interactive physical environment of FIG. 1, according to example embodiments.

(4) FIG. 7 is a perspective view of a modular room of the interactive physical environment of FIG. 1, according to an example embodiment.

(5) FIG. 8 is a view of a display screen of a hunt kiosk of the interactive physical environment of FIG. 1, according to an example embodiment.

(6) FIGS. 9 and 10 are example views of components for use in a game hunt of the interactive physical environment of FIG. 1, according to an example embodiment.

(7) FIG. 11 is another view of a display screen of a hunt kiosk of the interactive physical environment of FIG. 1, showing a locked screen, according to an example embodiment.

(8) FIG. 12 is another perspective view of the modular room of interactive physical environment of FIG. 1, according to an example embodiment.

(9) FIG. 13 is perspective view of a modular room of the interactive physical environment of FIG.

- 1**, showing an example wall configuration, according to an example embodiment.
- (10) FIG. **14** is a detailed view of the modular room of FIG. **13**, showing the linkage assemblies, according to an example embodiment.
- (11) FIGS. **15-19** are various perspective views of wall configurations for assembly into the modular room of FIG. **13**, according to example embodiments.
- (12) FIGS. **20-25** are various perspective views of linkage assemblies for assembly into the modular room of FIG. **13**, according to example embodiments.
- (13) FIG. **26** is a perspective view of the wall configuration of FIG. **15**, according to an example embodiment.
- (14) FIG. **27** is a perspective view of the wall configuration of FIG. **16**, according to an example embodiment.
- (15) FIG. **28** is a perspective view of the wall configuration of FIG. **18**, according to an example embodiment.
- (16) FIG. **29** is a detailed view of the linkage assembly of FIG. **16**, according to an example embodiment.
- (17) FIG. **30** is a detailed view of the linkage assembly of FIG. **17**, according to an example embodiment.
- (18) FIG. **31** is a detailed view of the linkage assembly of FIG. **19**, according to an example embodiment.
- (19) FIG. **32** is a top view of the modular room of FIG. **13**, showing the coupling between the wall configuration and the linkage assembly, according to an example embodiment.
- (20) FIG. **33** is a perspective view of a radio frequency identification (RFID) tag for use in the interactive physical environment of FIG. **1**, according to an example embodiment.
- (21) FIG. **34** is a block diagram depicting various aspects of a system for controlling the interactive physical environment of FIG. **1**, according to an example embodiment.
- (22) FIGS. **35-39** are various views of displays from a patron kiosk of the interactive physical environment of FIG. **1**, according to an example embodiment.
- (23) FIG. **40** is a diagram of a patron card data element for use in the interactive physical environment of FIG. **1**, according to an example embodiment.
- (24) FIGS. **41** and **42** are various views of patron cards from a patron kiosk of the interactive physical environment of FIG. **1**, according to an example embodiment.
- (25) FIGS. **43-47** are various views of displays from a patron kiosk of the interactive physical environment of FIG. **1**, according to an example embodiment.
- (26) FIG. **48** is a diagram of a patron avatar data element for use in the patron card of FIG. **40**, according to an example embodiment.
- (27) FIG. **49** is a front view of a patron avatar for association with a unique patron within the interactive physical environment of FIG. **1**, according to an example embodiment.
- (28) FIG. **50** shows various views of patron avatars corresponding to various patron levels for use in the patron card of FIG. **40**, according to an example embodiment.

DETAILED DESCRIPTION

- (29) Before turning to the FIGURES, which illustrate certain example embodiments in detail, it should be understood that the present disclosure is not limited to the details or methodology set forth in the description or illustrated in the figures. It should also be understood that the terminology used herein is for the purpose of description only and should not be regarded as limiting.
- (30) Referring now to FIG. **1**, and in overview, an interactive physical environment **100** is shown that includes a warehouse **130**, offices **140**, a taproom **150**, a tunnel **160**, restrooms **170**, a kitchen **180**, beer hall **190** and one or more modular game rooms **200**. In other embodiments, the interactive physical environment includes a subset of the elements depicted in FIG. **1**. For example, in one embodiment, the interactive physical environment includes a warehouse **130**, restrooms **170**

and one or more modular game rooms **200**. Although a specific orientation of rooms (e.g., entrances **110**, **120**, warehouse **130**, offices **140**, taproom **150**, tunnel **160**, restrooms **170**, kitchen **180**, beer hall **190**, and modular game rooms **200**) are depicted in FIG. **1**, it should be appreciated that the rooms can take on any configuration that would be suitable to provide a user experience.

(31) Still referring to FIG. **1**, and in greater detail, the interactive physical environment **100** may be configured as an entertainment environment. The interactive physical environment **100** may be defined, or otherwise positioned, within a building environment. In some embodiments, the interactive physical environment **100** may be defined within a stand-alone building, mall, or the like. In other embodiments, the interactive physical environment **100** may be a virtual room including one or more virtual environments. The interactive physical environment **100** may be configured to provide at least one of a gaming, food, or drink experiences to a user or patron.

(32) The interactive physical environment **100** may include one or more entrances, shown as first entrance **110** and second entrance **120**. The first entrance **110** and the second entrance **120** may be substantially similar to one another. In other embodiments, the first entrance **110** may be substantially different to the second entrance **120**. The entrances **110**, **120** may provide the user entry into the interactive physical environment **100**. As shown in FIG. **1**, the first entrance **110** may direct the user through a tunnel **160**. The tunnel **160** may provide a barrier, boundary, or the like about the user when the user is traveling through the tunnel **160**. In some embodiments, the tunnel **160** includes one or more stations at which the user may register themselves, such as by associating a user profile with a token. Accordingly, the second entrance **120** may permit the user access into the interactive physical environment **100**, without traveling through any tunnel. In some embodiments, the second entrance **120** may also include a tunnel **160**. Although only two entrances **110**, **120** are described above, the interactive physical environment **100** may include more than two entrances. The entrances **110**, **120** may include one or more doors that selectively open and close to permit the user access to the interactive physical environment **100**. The doors may be automatic doors, manual doors, or a combination thereof.

(33) The interactive physical environment **100** may further include a warehouse **130**. The warehouse **130** may be positioned opposite the first entrance **110**, as depicted in FIG. **1**. In some embodiments, the warehouse **130** may be positioned adjacent the first entrance **110**. The warehouse **130** may store and/or house components for use in the interactive physical environment **100**. For example, the warehouse **130** may include spare components for a modular game room **200**. In another example, the warehouse **130** may store a control system for the modular game rooms **200** present in the interactive physical environment **100**. The interactive physical environment **100** may include offices **140**. In some embodiments, the offices **140** may be positioned adjacent the warehouse **130**. The offices **140** may include one or more desks and/or office space where employees of the interactive physical environment **100** may have a desired space or choose a space to work and/or relax.

(34) The interactive physical environment **100** may further include a taproom **150**. The taproom **150** may be a room positioned adjacent the first entrance **110**, where a patron may go to for a beverage and/or to relax. In other embodiments, the taproom **150** may be positioned distal the first entrance **110**. Additionally or alternatively, the taproom **150** may include one or more tables, where a patron can sit and relax.

(35) The interactive physical environment **100** may include a restrooms **170**. The restroom **170** may include one or more restrooms for the patrons. The restroom **170** may be positioned adjacent the first entrance **110**, between the first entrance **110** and the second entrance **120**. The interactive physical environment **100** may include more than one restroom **170**. For example, the interactive physical environment **100** may include a first restroom **170** designated for patron and/or employee use and a second restroom **170** designated for employee use.

(36) The interactive physical environment **100** may include a kitchen **180**. The kitchen **180** may be positioned adjacent the taproom **150**. In other embodiments, the kitchen **180** may be positioned

distal the taproom **150**. In still other embodiments, the interactive physical environment **100** may include additional kitchens **180**. The kitchen **180** may be a room where patrons can order and/or eat food. According to one example embodiment, the kitchen **180** may include a menu where the patron can place a food/drink order off of the menu. Additionally or alternatively, the kitchen **180** may include a pre-made section where the patron can order food/drinks that are pre-made. The interactive physical environment **100** may include a beer hall **190**. The beer hall **190** may be positioned adjacent the kitchen **180**. Additionally or alternatively, the beer hall **190** may be positioned centrally within the interactive physical environment **100**. The patron may be able to order and/or drink a beverage (e.g., beer, etc.) within the beer hall **190**. The patron may otherwise order a beverage at the taproom **150** and enjoy the beverage at the beer hall **190**.

(37) The interactive physical environment **100** may include one or more modular game rooms **200**, where the patron can interact with games provided in the modular game rooms **200** to achieve challenges and receive a patron experience. As will be discussed in greater detail herein, a control system may control, track, or otherwise determine a game status within the modular game rooms **200**. The interactive physical environment **100** may include any number of modular game rooms **200**. In some embodiments, the interactive physical environment **100** includes more than 10 modular game rooms **200**. In other embodiments, the interactive physical environment **100** includes more than 25 modular game rooms **200**. In still other embodiments, the interactive physical environment **100** includes between 40 and 50 modular game rooms **200**. In still further embodiments, the interactive physical environment **100** includes more than 50 modular game rooms **200**. In further embodiments, the interactive physical environment **100** includes more than 100 modular game rooms **200**. The modular game rooms **200** may each include different games or challenges different from the other modular game rooms **200** present in the interactive physical environment. In other embodiments, certain ones of the modular game rooms **200** may provide similar games or challenges. In some of these embodiments, game rooms **200** may be grouped together based on theme, e.g., a cluster of rooms may provide outer space themed games. The different games may be a combination of physical and mental challenges, although other game types may be contemplated. The different challenges may require patrons to exercise a combination of strength, agility, skill, logic, memory, and communication, although other challenges may be contemplated.

(38) Upon entering the interactive physical environment **100**, the patron may need to check in. The check in may be a first time check in for a new patron, or an existing check-in for an existing patron. A new patron is required to create a new profile. One embodiment of a process for creating the new profile is shown in FIGS. 2-6. As shown in FIG. 2, upon entrance into the interactive physical environment **100**, the patron selects between registering an account or logging in to an existing account **195a**. When the patron selects to register a new account, the patron is asked to identify a name for the account **195b**, as shown in FIG. 3. As shown in FIG. 4, the patron may then input their birthday **195c**. After the birthday is entered, the patron may then enter in a phone number **195d**, as shown in FIG. 5. As shown in FIG. 6, the patron may then input a desired login name **195e**. Existing patrons may login using existing login credentials to access their profile. The kiosk allows a user profile to be associated with an RFID tag, QR code or bar code associated with the patron. Alternatively, the kiosk may be used to collect biometric characteristics for identifying the patron. In other embodiments, a patron's login at the kiosk may activate an applet on their mobile phone to be used to identify the patron in the environment **100**. Although a specific order of steps has been described for registering the patron, it can be appreciated that the steps may happen in any order and, in some embodiments, certain steps may be omitted. For example, in some embodiments, the patron may not be required to enter their birthday or phone number.

(39) Referring now to FIGS. 7 and 8, the modular game rooms **200** may include walls **210** and other physical structures. The walls **210** may create a physical boundary for a patron to be positioned within. According to one embodiment, a modular game room **200** may not include a

ceiling, such that the patrons positioned within the modular game room **200** may see outside of the modular game room **200**. The walls **210** may form interior rooms **220** within the modular game room **200**. The modular game rooms **200** may include interior rooms **220** for games having multiple steps and/or challenges. The interior rooms **220** may define any dimensions or configurations for the desired game. For example, the modular room **200** may include two interior rooms **220** for games having two steps and/or challenges. In another example, the modular room **200** may not include any interior rooms **220** for games having one step and/or challenge. According to one example embodiment, the modular game rooms **200** may be defined in open areas. In such an embodiment, the modular game rooms **200** may not include any walls **210**, where the modular game rooms **200** may instead be open world concepts.

(40) A patron may enter the modular room **200** through one or more entrances, shown as room entrance **230**. The room entrance **230** may permit the patron access within the modular game rooms **200**. By way of example, patrons may enter into the modular game rooms **200** via the room entrance **230** and additionally exit the modular game rooms **200** via the room entrance **230**. In other embodiments, the modular room **200** may include additional entrances, where the patrons can enter into the modular room **200** via the room entrance **230** and exit the modular room **200** via the additional entrance. The modular room **200** may be configured to a group size between two and six patrons. In other embodiments, the modular room **200** may be configured for group sizes exceeding six patrons. According to one example embodiment, the modular room **200** may include a game time of between 1 and 10 minutes. More specifically, the game time may be within 2 and 4 minutes. In other embodiments, the game time may exceed 10 minutes.

(41) The modular game rooms **200** may include a patron kiosk **212**. In some embodiments, the patron kiosk provides information to a patron regarding the game provided by the game room **200**. A patron may also use the patron kiosk **212** to access, edit, and/or otherwise manage a patron card. As will be discussed in greater detail herein, the patron card may be a unique patron card designated and customized for a specific patron. The patron card may be accessible and managed by the patron associated with a specific patron card. The patron may access the patron card via the patron kiosk **212** before or after the patron plays the game. In other embodiments, the patron may access the patron card during the game. The patron may access the patron card before entering the modular room **200** to see profile details, such as currency currently earned, level, achievement, currency needed to achieve a new level or purchase in-game or real-world elements, remaining time, a map of the space, or the like. In one embodiment, the patron may scan a radio-frequency identification (RFID) tag via the patron kiosk **212** to open and/or access the desired patron card. In other embodiments, the patron kiosk may accept alternate forms of identification to allow the patron to access the patron card (e.g., bar code, QR code, a Bluetooth device, retinal identification, facial identification, fingerprint, etc.).

(42) The modular game room **200** may include an exit monitor **214**. The exit monitor **214** may be positioned within the modular game room **200**, where patrons within the modular room **200** may see and/or access the exit monitor **214**. In some embodiments, the exit monitor **214** displays instructions or information to patrons in the room **200**. In other embodiments, the exit monitor **214** may display a status of the game, including a status level identifying the game status or level of award achieved. For example, the exit monitor **214** may display three stars, where each star resembles a level of award achieved (e.g., three stars being the highest award, etc.). The patrons may achieve additional challenges within the game to be awarded additional stars. Additionally or alternatively, the exit monitor **214** may display a random element, such as a prize wheel. The random element may be used after completion of the game to award additional prizes to the patron. For example, in one embodiment the random element is a wheel, and additional prizes may be awarded upon a successful spin of the wheel. The prizes may include in-game currency or reward points such as coins, keys, reward multiplier, power-ups, special abilities, upgrades to player avatar, etc., or real-world prizes such as apparel, merchandise, food, beverage, etc. In other embodiments,

the prizes may be redeemable tokens or passes for additional play time. In some embodiments, the random element may only be used upon successful completion of the game. In other embodiments, the random element may be used following every game, regardless of whether the patrons were successful or not.

(43) The modular room **200** may include external games, shown in FIG. 7 as game hunts **216**. Game hunts **216** may include an additional patron interface, referred to herein as hunt kiosk, coupled to an exterior of the modular game rooms **200**. The hunt kiosk may be substantially similar to the patron kiosk **212**. The patrons not playing the game within the modular room **200** may play the game hunts **216**. Additionally or alternatively, the hunt kiosk may not be coupled to the exterior of the modular game rooms **200** but may, instead, be freestanding or coupled to a wall of the environment **100**. The game hunts **216** may provide an additional patron experience other than the games within the modular game rooms **200**. The game hunts **216** may be games requiring the patrons to find and/or locate particular components (e.g., artifacts, art, technology, shapes, symbols, etc.). The game hunts **216** may include different systems other than the systems for the modular game room **200** such that the patrons may have more time or different awards for the game hunts **216**. In other embodiments, the game hunts **216** may include a substantially similar system to the system for the modular game room **200**.

(44) To check-in to the hunt kiosk, the patron may scan their associated RFID tag via the hunt kiosk. In other embodiments, the patron kiosk may accept alternate forms of identification to allow the patron to access the patron card (e.g., bar code, QR code, a Bluetooth device, retinal identification, facial identification, fingerprint, etc.). The game hunt **216** may define a game time within a maximum time of 20 minutes. The hunt kiosk may display a first screen, as shown in FIG. 8. The first screen may display the instructions and how to achieve the objective. In other embodiments, the game time may exceed 20 minutes. The game hunt **216** may include one or more correct components and one or more incorrect components. Examples of components are shown in FIGS. 9 and 10. The components may include, but not be limited to, glyphs (e.g., punny art, magic eye art, low poly art, overhead art, string art, shadow art, mural art, perspective illusions, etc.). The patron may identify the correct components to earn digital prizes or reward points (e.g., stars, rooms, apparel, merchandise, reward multipliers, gems, keys, etc.). Accordingly, identification of incorrect components may penalize the patron. For example, if the patron selects the incorrect component, the patron be locked out from the hunt kiosk for a period of time, as shown in FIG. 11. In one example, the patron may be locked out for 15 seconds. In another example, the time of which the patron is locked out increases with the number of incorrect component selections.

(45) The modular game room **200** may include one or more sensory effects, shown as lighting modules **218** and audio modules **219**. The lighting modules **218** may be configured to provide light to within the modular room **200**. As can be appreciated, the lighting modules **218** may be positioned anywhere within the room **200**, such as at a ceiling, or proximate the ceiling, of the modular room **200**, where the lighting modules **218** provides area lighting or effect lighting within. The lighting modules **218** may output lights having varying color, brightness, shape, pulse, etc. as such to enhance a patron experience. The lighting modules **218** may be controlled by the control system, and may be influenced by, or provide visual feedback on, the patron's performance or status in the room. In one example, the lighting modules **218** may provide light to game components within the modular room **200**. In other examples, the lighting modules **218** may provide light onto boundaries or structures within the modular room **200**. The modular room **200** may further include additional lighting modules **218** positioned proximate a floor of the modular room such to provide light to the floor. The audio modules **219** may be positioned proximate the lighting modules **218**, where the audio modules **219** provide audio to the modular room **200**. The audio modules **219** may be controlled by the control system. The audio may be one of music, sound effects, or status audio (e.g., vocal hint, time remaining, completion status, etc.). For example, the audio modules **219** may provide a time remaining status to the patrons to inform them of an amount

of time remaining in the game. In another example, the audio modules **219** may provide a game status to the patrons to inform them that the patrons have correctly or incorrectly performed a specific action. In another example, the audio modules **219** may be associated with a command speaker, where the audio modules **219** output a general statement outputted via an employee (e.g., closing soon, interactive physical environment **100** status, etc.).

(46) Referring generally to FIGS. **13-32**, the modular game room **200** may be defined by the walls **210** and/or other physical structures. In some embodiments, the physical structures may be game components, objects, obstacles, etc. The walls **210** further define the rooms **220**. As discussed above, the modular game room **200** may include any number of internal rooms **220** such to make up the game and/or challenge, where the internal rooms **220** are accessible by the patrons through the room entrance **230**. The internal rooms **220** may include any number of room entrances **230** (e.g., one room entrance **230**, two room entrances **230**, three room entrances **240**, etc.). The internal rooms **220** may have any dimensions (e.g., length, width, height, etc.) to permit the patrons accessibility and mobility within the rooms **220** to complete the challenge. In one example, the rooms **220** may define a room length within a range of 3 to 20 feet and a room width within a range of 3 to 20 feet. In another example, the room length and the room width may exceed 20 feet.

(47) As shown in FIG. **14**, the walls **210** may include one or more linkage assemblies, shown as linear linkage assembly **240** and angular linkage assembly **260**. The linkage assemblies **240**, **260** may be positioned along one or more top surfaces of the walls **210**. In some embodiments, the linkage assemblies **240**, **260** may be positioned along one or more bottom surfaces of the walls **210**. In other embodiments, the linkage assemblies **240**, **260** may be integrated into the walls **210** (e.g., joints, fasteners, interlocking mechanisms, etc.). By way of example, the linkage assemblies **240**, **260** may be coupled to, and extend from, the top surface of the walls **210** to define an enclosed space. Additionally or alternatively, the linkage assemblies **240**, **260** may include room hardware (e.g., lighting, speaker, wiring, etc.). As will be discussed in greater detail herein, the linkage assemblies **240**, **260** may include one or more receiver interfaces **380** that permit a quick connect and disconnect of the linkage assemblies **240**, **260** to the walls **210**.

(48) The walls **210** may include a covering, panel, or the like, shown as wall panels **212**. The wall panels **212** may be flat panels coupled to at least one of an exterior or interior of the walls **210**. In some embodiments, the wall panels **212** are not flat panels and instead include a protruding or curved structure. According to one embodiment, the wall panels **212** are coupled to both the exterior and the interior of the walls **210**. The wall panels **212** may be coupled to one or more structures (e.g., top wall support **270**, bottom wall support **280**, side wall support **290**, middle support **300**, and horizontal support **310** of FIG. **21**) via one or more fasteners (e.g., locating pin, bolt, bracket, adhesive, etc.). In some embodiments, the wall panels **212** may be fixedly coupled to the structures, where the wall panels **212** may not be removed from the structures. The wall panels **212** may define a panel height. The panel height may not extend along an entire height of the walls **210**. Instead, the wall panels **212** may abut a top portion of the walls **210** and include a gap proximate a bottom of the walls **210**. In other embodiments, the wall panel **212** may extend along the entire height of the walls **210**. The structure of wall panels **212** allow them to easily set up and removed, which allows the rooms **200** within the physical environment **100** to be changed easily and regularly to avoid patron boredom.

(49) As shown in FIGS. **15-19**, various wall configurations are depicted. The wall configurations may be at least one of a first linear wall **212a** (e.g., shown in FIG. **15**), a door wall **212b** (e.g., shown in FIG. **16**), a second linear wall **212c** (e.g., shown in FIG. **17**), a corner wall **212d** (e.g., shown in FIG. **18**), and a T-wall **212e** (shown in FIG. **19**). The linear walls **212a**, **212c** may be linear walls including flat wall panels **212**. The first linear wall **212a** may be substantially similar to the second linear wall **212b**, except for a wall length. According to one embodiment the first linear wall **212a** may define a wall length of four feet, and the second linear wall **212c** may define a wall length of 2 feet. In other embodiments, the linear walls **212a**, **212c** may include any wall length

that will create the room **220** (e.g., one foot, two feet, three feet, four feet, five feet, six feet, seven feet, eight feet, etc.). The door wall **212b** may be substantially similar to the first linear wall **212a** (e.g., similar wall length, etc.), although the door wall **212b** may further include a passage for the room entrance **230**. The passage for the room entrance **230** may define a substantially similar geometry to the room entrance **230**. In other embodiments, the door wall **212b** may have a different wall length compared to the first linear wall **212a** to permit various sizes of room entrances **230**.

(50) The corner wall **212d** may define an angular wall section (e.g., 15 degrees, 30 degrees, 45 degrees, 60 degrees, 75 degrees, 90 degrees, 105 degrees, 120 degrees, 135 degrees, 150 degrees, 165 degrees, etc.). The corner wall **212d** may be positioned where the room **220** has a bend or otherwise changes from a linear direction. For example, the corner wall **212d** may be positioned at a corner of the room **220** to join two linear walls **212a**, **212c**. In another example, the corner wall **212d** may be coupled to the T-wall **212e** to form a small room construction. The T-wall **212e** may define a structure having two linear portions, where the linear portions are positioned perpendicular to one another. In other embodiments, the T-wall **212e** may have a first linear portion angularly provided in relation to a second linear portion. Although the wall configurations **212a**, **212b**, **212c**, **212d**, **212e** have been described individually, it should be understood that the wall configurations may be coupled to, or otherwise used in any combination with, one another to form the room **220**.

(51) Referring now to FIGS. **26-28**, various views of the wall configurations **212a**, **212b**, **212d** are depicted. The wall configurations may include respective top and bottom members, shown as top wall support **270** and bottom wall support **280**. The top wall support **270** may be positioned proximate a top of the wall **210**, where the top wall support **270** extends horizontally along the wall **210**. Accordingly, the bottom wall support **270** may be positioned proximate a bottom of the wall **210**, where the bottom wall support **270** extends horizontally along the wall **210**. According to one embodiment, the top and bottom wall supports **270**, **280** may extend along an entire length of the wall **210**. In other embodiments, the top and bottom wall supports **270**, **280** may extend along a portion of a length of the wall **210**. The wall configurations may include one or more vertical extending members, shown as side wall supports **290** and middle support **300**. The side wall supports **290** may extend vertically from ends of the top and bottom wall supports **270**, **280**. The middle support **300** may be provided between each side wall support **290** and further extend vertically between the top wall support **270** and the bottom wall support **280**. The middle support **300** may be provided substantially parallel to the side wall supports **290**. The middle support **300** may extend vertically from a midpoint of the wall configuration. In other embodiments, the middle support **300** may extend vertically from a location offset the midpoint of the wall configuration. In still other embodiments, the middle support **300** may be angularly provided between the side wall supports **290**. In some examples, the wall configuration may not need any middle support **300**.

(52) The wall configuration may further include one or more horizontal supports **310**. The horizontal supports **310** may extend between the middle support **300** and the respective side wall supports **290**. In other embodiments, the horizontal supports **310** may extend between middle supports **300**. As can be appreciated, the horizontal supports **310** may rigidly hold the wall configuration and prevent side sway. The wall configuration may include any number of horizontal supports **310** that prevent side sway (e.g., two horizontal supports **310**, four horizontal supports **310**, six horizontal supports **310**, etc.).

(53) Referring specifically to FIG. **26**, a wall configuration for the first linear wall **212a** is shown. As shown, the wall configuration defines a substantially rectangular construction, having two side wall supports **290** defined between a top wall support **270** and a bottom wall support **280**. The wall configuration further includes a middle support **300** extending vertically between the side wall supports **290**. The wall configuration is rigidly held together via horizontal supports **310** positioned proximate the top wall support **270**. In other embodiments, the horizontal supports **310** may be positioned proximate the bottom wall support **280**.

(54) Referring specifically to FIG. **27**, a wall configuration for the door wall **212b** is shown. As

shown, the wall configuration defines a substantially rectangular construction having an open section for the room entrance **230**. The wall configuration includes two side wall supports **290** defined between a top wall support **270** and two bottom wall supports **280**. The wall configuration further includes two middle portions **300** extending vertically between the side wall supports **290** and offset from a midpoint of the wall configuration. The wall configuration is rigidly held together via a single horizontal support **310** positioned underneath the middle supports **310** and extending between the side wall supports **290**. In other embodiments, the wall configuration may include multiple horizontal supports **310**.

(55) Referring specifically to FIG. **28**, a wall configuration for the corner wall **212d** is shown. As shown, the wall configuration includes two linear wall configurations coupled together by a corner support **320**. Each linear wall configuration includes two side wall supports **290** extending between a top wall support **270** and a bottom wall support **280**. The linear wall configurations may further be rigidly held together via a single horizontal support **310** positioned proximate the top wall support **270**. In some embodiments, the horizontal support **310** may be positioned proximate the bottom wall support **280**. In other embodiments, the linear wall configuration may include multiple horizontal supports **310**.

(56) As shown in FIGS. **20-25**, various linkage assemblies are depicted. The linkage assemblies may be at least one of a first header linkage **240a** (e.g., shown in FIG. **20**), a second header linkage **240b** (e.g., shown in FIG. **21**), a third header linkage **240c** (e.g., shown in FIG. **22**), a fourth header linkage **240d** (e.g., shown in FIG. **23**), an inside corner linkage **260a** (e.g., shown in FIG. **24**), and an outside corner linkage **260b** (e.g., shown in FIG. **25**). The header linkages **240a-240d** may be linear linkages. The header linkages **240a-240d** may be positioned along linear wall configurations or linear portions thereof. The header linkages **240a-240d** may be substantially similar to one another but define varying lengths. For example, in one embodiment, the first header linkage **240a** may be 2 feet long, the second header linkage **240b** may be four feet long, the third header linkage **240c** may be six feet long, and the fourth header linkage **240d** may be eight feet long. In another example, the header linkages **240a-240d** may define different lengths than described herein. The corner linkages **260a, 260b** may be positioned along corners or angular wall configurations. The corner linkages **260a, 260b** may couple walls that may be angularly provided from one another. Additionally or alternatively the corner linkages **260a, 260b** are utilized for corners defined by the corner wall **240d** and the T-wall **240e**. By way of example, the inside corner linkage **260a** may be positioned along an inside of the walls **210** and the outside corner linkage **260b** may be positioned along an outside of the walls **210**. The walls **210** may utilize both the inside corner linkage **260a** and the outside corner linkage **260b** when simultaneously. In other embodiments, the walls **210** may only utilize one of the inside corner linkage **260a** and the outside corner linkage **260b**.

(57) Referring now to FIGS. **29-31**, various views of the linkage assemblies **240a, 240d, 260a** are depicted. The linkage assemblies may include side linkages, shown as first side linkage **330** and second side linkage **360**. The side linkages **330, 360** may define an outermost structure of the linkage assembly, where the side linkages **330, 360** are coupled together. The linkage assemblies may include second side linkages **360** positioned at ends of the linkage assemblies. Additionally or alternatively, multiple second side linkages **360** may be positioned internal the linkage assemblies. In such an embodiment, the internal second side linkages **360** may be configured to support the first side linkages **330**. The linkage assemblies may include one or more linkage side panels **340**. The linkage side panels **340** may be coupled to one of the first side linkages **330**. In other embodiments, the linkage side panels **340** may be coupled to the second linkage **360**. The linkage side panels **340** may be positioned proximate an end of the walls **210**, where the linkage side panels **340** create a smooth outer surface of the linkage assemblies. Similarly to the linkage side panels **340**, the linkage assemblies may further include one or more linkage bottom panels **350**. The linkage bottom panels **350** may be positioned proximate a top or a bottom of the linkage assemblies, where the linkage bottom panels **350** create a smooth outer surface of the linkage assemblies.

(58) The linkage assemblies may be coupled to the walls via one or more connecting linkages **370**. The connecting linkages **370** may be positioned internal the side linkages **330**, **360** where the connecting linkages **370** protrude outward from the first side linkage **330**. More specifically the connecting linkages **370** may include a receiver interface **380**. The receiver interface **380** may extend outward past the first side linkage **330**. In other embodiments, the receiver interface **380** may not extend past the first side linkage **330**. The receiver interface **380** may be a slot configured to receive a top of the top wall support **270**, such that the linkage assembly extends outward from walls. In other embodiments, the linkage assemblies may be positioned over top of the top wall support **270**. According to one embodiment, the receiver interface **380** may define a quick connect/disconnect for the linkage assembly to the wall configuration. In such an embodiment, the receiver interface **380** hooks onto the wall configuration to rigidly secure the linkage assembly to the wall. In other embodiments, the linkage assembly may be fastened to the wall configuration (e.g., bracket, bolt, adhesive, etc.). The linkage assembly permits a relatively quick construction and/or deconstruction of the walls **210**. As can be appreciated, when changing game types and/or traveling, the walls **210** may be quickly assembled or disassembled for the needs. Additionally or alternatively, the employees may be able to quickly reassemble new wall configurations for a new game type to provide an enhanced patron experience.

(59) Referring now to FIG. **33**, the interactive physical environment **100** may detect, or otherwise be communicably coupled to one or more radio frequency identification (RFID) tags, shown as RFID tags **400**. An RFID tag **400** may be associated with a single patron, where the RFID tag **400** transmits an RFID signal **410**. The RFID signal **410** may be unique for each RFID tag **400** such that the patron is identified by the unique RFID signal **410**. As shown in FIG. **33**, the RFID tag **400** may be a bracelet, where the patron wears the bracelet around a portion of the patron body. In other embodiments, the RFID tag **400** may be a badge or scannable device, where the badge is worn or otherwise associated with the patron. The RFID tag **400** may permit the user access to the patron's account. The environment **100** may include an account associated with each unique patron, where the RFID tag **400** may be scanned to permit the patron access to the account. In other embodiments, the patron is associated with a unique identification number (e.g., account number, customer number, patron number, etc.) allowing the patron to access their account via the unique identification number.

(60) In other embodiments, the interactive physical environment **100** may detect a patron using alternative methods from RFID tags **400**. In one example, the interactive physical environment **100** may detect the presence of a patron via a cellular device. In such an embodiment, the interactive physical environment **100** may detect the patron by Bluetooth within the cellular device, a cellular application in which the patron interfaces with the cellular application, an online website in which the patron interfaces with the website, or the like. In another example, the interactive physical environment **100** may detect the presence of the patron using biometric identification methods (e.g., facial recognition, retinal recognition, fingerprint, etc.). In still other embodiments, the interactive physical environment **100** may detect the patron via a QR code or bar code. In these embodiments, the codes may be printed on a badge associated with the patron or the codes may be printed directly on a patron's body, such as on their hand.

(61) Referring now to FIG. **34**, the interactive physical environment **100** a patron **530** may be associated with an identifier **535**, rooms **220**, and a control system **550**. The rooms **220** may include the patron kiosk **212** and one or more sensors, shown as room sensors **542**. In one embodiment, the patron **530** scans their identifier **535** at a scanner provided in connection with the patron kiosk **212**. The patron **530** may scan the identifier **535** to enter the room **220** or play a game within the room **220**. The games may include any one of a physical challenge, mental challenge, skill challenge, mystery challenge, communication challenge, or combination thereof. Control system **550** may be provided on site, deployed in the cloud, or deployed as a hybrid system in which certain machines are located on site and other resources are deployed in the cloud.

(62) The rooms **200** may include one or more room sensors **542**. The room sensors **542** may be one of proximity sensors, pressure sensors, temperature sensors, optical sensors, or the like. In a specific embodiment, room sensors may be provided as LIDAR sensors. The room sensors **542** may be positioned externally to the rooms **220** or internally to the rooms **220**. As will be discussed in greater detail herein, the room sensors **542** may provide data to the control system **550** to determine a status of the game.

(63) In one example game, the game may include a physical challenge, where the patrons **530** may complete the challenge by completing a physical objective. The physical objective may be to throw a ball into an area, to cross the room **220**, to climb an object, or otherwise perform any physical action to achieve the objective. As can be appreciated, the room **220** may include various types of sensors (e.g., temperature, proximity, accelerometer, infrared, light, ultrasonic, pressure, LIDAR, etc.) that detect at least one of the patron **530** or a game component.

(64) In one embodiment, a physical challenge may instruct patrons to stand on a small walkway around three sides of the room **220** in order to throw balls through an overhead target without touching the ground. Each ball thrown through the target earns a point. If the patrons fall, a sensor **542** registers the pressure from the patron on the floor and transmits that data to the control system **550** via the network **540**. The controls system **550** receives the sensor data and determines that the patron has failed. The control system transmits data back to the room **220** to, in some embodiments, cause a sound to be emitted or, in other embodiments, cause the exit monitor **214** to display a failure status to the patron. The game may permit patrons 75 seconds to complete the challenge. In other embodiments, the game may permit more time than 75 seconds to complete the objective. For embodiments in which there is a time limit to complete the challenge, the control system **550** receives data from the patron kiosk **212** that the patron has started the game. Processor **554** executes a countdown timer program and, if no data is received from the room sensors **542** that the challenge objective has been completed prior to the timer elapsing, control system **550** transmits data back to the room **220** to inform the patron they have failed, as described above.

(65) In another example game, the game may include a skill challenge, where patrons **530** may need to keep a game component moving. In such an example, the room **220** may include a single light emitted from a first device. The first device may include multiple illuminated paths that lead to one or more second devices. The objective may be to press the second device associated with the light to keep the light moving for the entirety of the game.

(66) In one embodiment, an example skill challenge permit patrons access into the room **220**. The room **220** may be dim with one LED light strip positioned above. The game may not begin until the patrons press a lighted button. A sensor **542** associated with the lighted button transmits data to the control system, **550** indicating that the button has been pressed and the control system begins a routine to animate lighting elements in the room **220** to make it appear that a “ball of light” is launched up into a tube leading away from the lighted button. Upon launch, the ball of light continues moving and eventually travels downward toward another button box. When the ball of light reaches the button box, the patron presses the button box to again launch the ball of light to reach another button box. As before, a sensor **542** associated the button box senses that the patron has depressed the button and transmits that data to the control system **550**, which again executes a routine to animate lighting elements in the room **220** to make it appear that the ball of light has been relaunched. The more button boxes that are pressed during the time period correspond to a higher score earned by the patron. Additionally or alternatively, speed of the ball, i.e., speed of the lighting animation, may increase after each button box is successfully pressed. If the ball drops all the way into a button box, that is, if a button is not depressed in time, the control system **550** determines that the game has completed and it ends immediately.

(67) In another example game, the game may include a mystery challenge, where patrons **530** may stand on blocks including pressure sensors **543**. Other patrons **530** not standing on blocks may then swing, via ropes, to sidewalls of the room **220** to press, or otherwise interact with, buttons

positioned on the sidewalls. The objective may be to press all the buttons while maintaining contact with the ropes and the blocks.

(68) In one embodiment, an example mystery challenge includes permitting patron's access into the room **220**. When the patrons access the room, all button lights will be lighted. When the control system **550** receives data from the patron kiosk **212** that the game is beginning, it sends data back to room **220** to cause some of the buttons to flicker. After a predetermined amount of time, if the control system **550** does not receive data from a sensor **542** indicating the flickering button has been pressed, the control system **550** will send data to room **220** to cause the lighted button to stop flickering, signifying that the button has died, and that button will then remain off for the remainder of the game. The objective of this game is to have the patrons swing or push one another to reach the flickering buttons. Upon interaction with a flickering button, a sensor **542** associated with the button transmits data to the control system **550** indicating that the button has been successfully pressed. The control system **550** transmits data to the room **220** to cause that button to remain lighted for the rest of the game. The game is over after a time period has ended or the patron has fallen off a platform in the room. As more patrons enter the room, the less time the game allots to the group. Additionally or alternatively, the more flickering buttons pressed equals more reward points.

(69) In another example game, the challenge may be a communication challenge, where patrons must communicate between one another to achieve the objective. In such an example, the patrons may include a designated number, where the sidewalls of the modular rooms include illuminated spots. The patrons may achieve the objective by pressing an exact amount of illuminated light spots corresponding to their designated number.

(70) In one embodiment, an example communication challenge permits patrons access into the room **220**. The room **220** includes a platform, where patrons stand on the platform and are prohibited from touching the floor. Instead, the patrons must stand on "spots" protruding upwards from the floor. The control system **550** begins the game when it receives data from the room that the door has closed. The control system **550** transmits data to the room **220** to display a number on a screen, such as exit monitor **214**, and to illuminate a corresponding number of spots on the floor and the walls of the room **220**. The control system **550** may also begin a countdown and may transmit information to the exit monitor **214** to cause it to display the current status of the countdown monitor. Concurrently, the control system **550** transmits information to the room **220** to cause the spots to change color. The objective of this game is to have the patrons interface with (e.g., press, cover, etc.) a number of illuminated spots corresponding to the number displayed on the screen of the exit monitor **214** before time runs out. If too many spots are covered, i.e., if too many sensors **542** report to the control system **550** that they have been pressed, the patrons do not get a point, i.e., the control system **550** determines that the number of spots does not equal the number displayed on the monitor and no point is awarded to the patrons. If too few spots are covered, i.e., if too few sensors **542** report to the control system **550** that they have been pressed, the patrons do not get a point, i.e., the control system **550** determines that the number of spots does not equal the number displayed on the monitor and no point is awarded to the patrons. If any off-limit spots are covered, i.e., sensors **542** associated with spots that should not be pressed report that they are pressed, the patrons fail out of the room, i.e., the control system **550** determines that the game should end immediately. In some embodiments, the patrons repeat this for five total rounds, where patrons can earn a maximum of five points.

(71) In one specific embodiment, a game room **200** may provide a self-resetting game, that is, the ending state in which a game room is left by a first patron serves as the starting state for the game when played by a second patron. These types of games allow a room to set to initial conditions without requiring venue staff to attend to the room **200**. In this embodiment, the game provides a first challenge to a first group of patrons. The first group of patrons leaves the game room in a physical state that presents a second challenge to a second group of patrons. Although described in

terms of a first challenge and a second challenge, any number of challenges may be enabled by such a room as will be described below. The game may be selectively adjustable between a first game configuration and a second game configuration. The first game configuration may include a first game components and a first challenge, and the second game configuration may include a second game components and a second challenge. The first challenge may be different than the second challenge. The first game configuration may present the first game components in a first presentation. Additionally or alternatively, the first game configuration may present the first game components in a third presentation. The second game configuration may present the second game components in a second presentation. Additionally or alternatively, the second game configuration may present the second game components in a fourth presentation. The objective of the first game configuration may be to move the first game components into a first solution configuration. The objective of the second game configuration may be to move the second game components into a second solution configuration. The first game configuration may define a different game component position than the first solution configuration, and the second game configuration may define a different game component than the second solution configuration. By way of example, the first challenge may present the first game components in a first presentation and the second challenge may present the second game components in a second presentation. The first presentation may be the second solution configuration, and the second presentation may be the first solution configuration.

(72) The control system **550** may further include the room sensors **542** that detect the first and second game components. The room sensors **542** may determine a position of the first and second game components in relation to one of the first solution configuration and the second solution configuration. For example, in a first status, the patron **530** may play the game when the game is in the first configuration. If the patron **530** does not complete the first challenge, the sensors may detect the position of the game components in relation to the first challenge. If the game components are proximate or partially received in relation to the first challenge, the control system **550** may automatically adjust the game. More specifically, the processor **554** may receive the sensor data and communicate the sensor feedback to the memory **552**. The memory **552** may compare the game components position to the first challenge or the second challenge to determine an appropriate game configuration. In response to the game components being proximate the second solution configuration, the memory **552** may provide a status back to the processor **554** to adjust the entertainment game to the second game configuration. Accordingly, if the game components are proximate the first solution configuration, the memory **552** may provide a status back to the processor **554** to adjust the entertainment game to the first game configuration. In another example, if the game components are not proximate either of the first or second solution configurations, the memory **552** may select between one of the first and second game configurations. In such an example, the memory **552** may automatically reset into the first game configuration. The control system **550** may determine that the game has ended. In one example, the control system **550** may determine that the game is over by successful completion of the objective, via the room sensors **542**. In another example, the control system **550** may determine that the game is over by completion of the game time. In such an example, the control system **550** may determine successful completion or unsuccessful incompletion of the objective. The control system **550** readjusts the game configuration after each game is played. The control system **550**, via the room sensors **542**, may determine successful or unsuccessful completion of the objective. In one example, the room sensors **542** may be proximity sensors that determine a location of either the first and second game components. In such an example, if the game components are correctly positioned, the control system **550** may determine, via the memory **552**, an amount of stars to reward the patron **530**. As can be appreciated, the control system **550** automatically resets between the game configurations, where the control system **550** requires minimal, if any, external support (e.g., employee support, etc.) to adjust the entertainment game **850** between games. If a game

challenge is completed successfully, the control system **550** may select a different challenge for the next patron or patron group to enter the room **220**.

(73) In brief overview, a method for providing the self-resetting game in the room **220** includes providing game components, determining a presentation of the game components, allowing the patron **530** into the room **220**, detecting a completion of the game, and determining a status of the game.

(74) Providing the game components includes at least one of the first game components and the second game components. The first and second game components are repositionable within the room **220** of the interactive physical environment **100**. In some embodiments, the game components include more than two game components (e.g., third game components, fourth game components, etc.).

(75) Determining a presentation of the game components includes utilizing the control system **550** to receive a position data from the room sensors **542**, the position data representing a position of either the first game components or the second game components. The room sensors **542** may be at least one of proximity sensors, pressure sensors, or the like. The control system **550** may receive position data from the room sensors **542** and determining if the first game components are within a first presentation or if the second game components are within the second presentation. By way of example, if the first game components are within the first presentation, the first game components may present the first challenge, and if the second game components are within the second presentation, the second game components may present the second challenge. In other embodiments, the first game components may be within a third presentation. In such an embodiment, the third presentation may define any position of the game components where the game components are not within the first presentation or the second presentation. The third presentation may present the first challenge.

(76) Allowing the patron **530** into the room **220** includes utilizing the control system **550** to determine if the patron **530** has scanned into the room **220**. The patron **530** may scan the identifier **535**, via the scanner at the patron kiosk **212**, to check-in to the room **220**. The identifier **535** may be one of the RFID tag, QR code, bar code, biometric characteristics, etc. By way of example, multiple patrons **530** may check-in to the patron kiosk **212** to check-in to the room **220** (e.g., two patrons **530**, four patrons **530**, six patrons **530**, etc.). If the room **220** is currently providing a game to patrons **530** positioned within the room **220**, the control system **550** may not permit the patrons **530** access into the room **220**. If the room **220** is not currently providing a game to patrons **530**, the control system **550** may permit the patrons **530** access to the room **220**.

(77) Detecting the completion of the game includes the control system **550** receiving a status, via the room sensors **542**, of the game. The room sensors **542** may detect a position of either the first and second game components, and provide the position data to the control system **550**. The control system **550** may compare the position data to an objective position data, via objective position data stored within the memory **552**, to determine successful or unsuccessful completion of the objective.

(78) Determining the status of the game includes the control system **550** determining the status. The control system **550** may compare the position data to a first solution configuration or a second solution configuration. The first solution configuration may present a solution to the first game configuration and the second solution configuration may present a solution to the second game configuration. The first solution configuration may be substantially different than the first solution configuration. Additionally, the first solution configuration may define the second presentation and the second solution configuration may define the first presentation.

(79) In one embodiment, a self-resetting game is provided as a dinner party-themed logic puzzle. The goal of the game is to move entrees, beverages, and name cards around the table to set the table for a dinner party. The control system **550** selects a set of RSVPs from a plurality of sets of RSVPs stored in memory **552**, a menu from a plurality of menus stored in memory **552** and a guest letter from a plurality of guest letters stored in memory **552**. The selected items are transmitted to

the room **220** for display on the exit monitor **214**. Patrons must set the table in accord with the displayed information within a predetermined time period.

(80) When starting the game for a patron, the control system **550** receives data from one or more sensors **542** identifying the location of the game components, such as dishes, utensils and name cards, as those game components were left by the prior patron. The control system **550** uses the received game component data to select one of a plurality of challenges for the incoming patron. In one embodiment, the control system **550** chooses a challenge that requires moving the largest number of game components from their starting positions reported to the control system **550**. In some embodiments, if the patron sets the entire table properly in under 4 minutes, they earn three stars, in under 4:30 minutes, 2 stars, and in under 5 minutes, 1 star. In these embodiments, if the control system **550** determines that 5 minutes have elapsed, it transmits data to the room **220** to cause the lighting elements, audio elements and exit monitor **214** to indicate failure.

(81) In one embodiment, the control system **550** selectively adjusts the difficulty level by awarding fewer reward points to larger groups requiring the same amount of time to complete the game as smaller groups. For example, following completion of the game, the control system **550** can cause processor **554** to access the following table structure from memory **552**:

(82) TABLE-US-00001 Group Size 1 Star 2 Star 3 Star 2 Players 5 min. 4:30 min 4 min 3 Players 5 min. 4 min. 3:30 min. 4 Players 5 min. 3:30 min. 3 min. 5 Players 5 min. 3 min. 2:30 min. 6 Players 5 min. 2 min. 1 min.

(83) The control system **550** can cause the processor **554** to lookup, using the number of players reported by the patron kiosk **212** and the elapsed time of the countdown timer to determine how many stars to award the patrons for completion of the game. For example, if 4 patron completed the game in 3 minutes and 15 seconds, the processor **554** would access the “4 Players” row in the table data structure. Since the elapsed time, in this example, is less than 3:30 minutes but more than 3 minutes, the processor add 2 stars to the patron card **430** associated with the patron. In some embodiment, each of the patrons would receive two stars and in other embodiments, the awarded stars would be distributed among the patrons.

(84) In some embodiments, the control system **550** can modify the difficulty of the game responsive to the size of the patron group playing. In these embodiments, the control system may apply a scaling factor to the time period in the table data structure to increase difficulty. For example, the control system may divide the time periods stored in the table by 2 if the patron group is six players. In this example, to achieve a three star performance, the patron group would need to complete the challenge in 30 seconds.

(85) Other games may be combinations of the various examples just described above. For example, a game may require both skill from, and communication between, the patrons playing the game.

(86) When the patron **530** scans the identifier **535**, the patron kiosk **212** sends a command, via a network **540**, to request information from the control system **550**. The control system **550** includes a memory **552** and a processor **554**. The member **550** stores information associated with the patron **530**, such as a patron avatar data structure **560** and a patron card data structure **430**.

(87) The memory **552** may store machine instructions that, when executed by the processor **554**, cause the processor **554** to perform one or more of computer operations. The processor **554** may include one or more microprocessors, application specific integrated circuits (ASICs), field programmable gate arrays (FPGAs), other forms of processing circuits, or combinations thereof. The memory **552** may include, but is not limited to, electronic, optical, magnetic, or any other storage or transmission device capable of providing the processor **554** with program instructions. The memory **552** may include storage devices such as a floppy disk, CD-ROM, DVD, magnetic disk, memory chip, ROM, RAM, EEPROM, EPROM, flash memory, optical media, or any other suitable memory from which the processor **554** can read instructions and/or data. The processor **554** and the memory **552** may form a processing module.

(88) The control system **550** may track and/or log the position of a patron **530** via the identifier **535**

associated with the patron **530**. The rooms **220** may include one or more room sensors **542**. The room sensors **542** may be at least one or more sensors positioned within the rooms **220** or on an outside of the rooms **220**. The room sensors **542** positioned within the rooms **220** may be motion sensors that detect the presence of the patron or the sensors may directly detect the identifier associated with the patron. Additionally or alternatively, the room sensors **542** positioned on the outside of the rooms **220** may detect the presence of the patron or the sensors may directly detect the identifier associated with the patron.

(89) In response to determining patron position, the room sensors **542** may send position data to a control system **550** identifying the patron position. More specifically, the processor **554** may receive the position data from the room sensors **542** and store the position data within the memory **552**. The memory **552** may create a log of patron position data for each patron **530**.

(90) Referring now to FIGS. **35-47**, the patron **530** may access the patron kiosk **212** to view one or more kiosk screens. The patron **530** may access the patron kiosk **212** for each room **220**. Upon scanning the identifier **535**, the patron **530** may access a first screen **600** at the patron kiosk **212**, as shown in FIG. **35**. The first screen **600** may identify a number of stars that the patron **530** has earned for a given day. In other embodiments, the first screen **600** may identify a total number of stars earned in a career. In further embodiments, the first screen **600** may always be displayed and the information provided may relate to the room itself, e.g., 3% of all patrons have earned three stars playing this game.

(91) In some embodiments, upon scanning the identifier **535**, the patron kiosk **212** may display a second screen **610**, as shown in FIG. **36**. In such an embodiment, the second screen **610** may identify a locked room **220**. The second screen **610** identifies an amount of gems, or other in-game or digital currency, needed to unlock the room **220**. Additionally or alternatively, the second screen **610** permits the patron **530** to trade coins for gems if the patron does not have enough gems to access the room **220**. In another embodiment, upon scanning the identifier **535**, the patron kiosk **212** may display a third screen **620**, as shown in FIG. **37**. The third screen **620** may be substantially similar to the second screen **610**, although the patron **530** does not have any coins to trade for gems. In such a screen, the third screen **620** directs the patron to play more rooms **220** to earn the gems.

(92) In some embodiments, upon scanning the identifier **535**, the patron kiosk **212** may display a fourth screen **630**, as shown in FIG. **38**, allowing the patron **530** to purchase access to the locked room **220** in examples where the patron **530** currently has a sufficient amount of currency. The patron may select between an agree button (e.g., check-mark, etc.) or a cancel button (e.g., x-button, etc.). The screens **610-630** may be optional for embodiments in which the rooms **220** are not locked.

(93) As shown in FIG. **39**, the patron kiosk **212** may display a fifth screen **640** in response to the patron **530** scanning the identifier **535**. The fifth screen **640** indicate a group of patrons registered to enter the room **220**. The fifth screen **640** may display a patron name and the patron avatar **560** associated with each registered patron **530**. By way of example, the fifth screen **640** may only display the number of patrons that are able to access the room **220** (e.g., between 2 and 6 patrons). The fifth screen **640** may further indicate a time limit for the room **220** (e.g., as shown in the top right corner of the fifth screen **640**, etc.). Although the fifth screen **640** identifies a time limit of 3 minutes, the room **220** may include any time limit needed to complete the existing challenge and grant access to patrons **530** waiting outside of the room **220**. In other embodiments, the fifth screen **640** may identify estimated time remaining until the patron will be provided access to the room **200**. The fifth screen **640** may further include a hint for the room **220** (e.g., as shown in the bottom right corner of the fifth screen **640**, etc.). As will be discussed in greater detail herein, the hint may be a selection from the patron **530** to access one or more hints associated with the room **220**.

(94) When at the fifth screen **640**, the patron **530** may select the specific patron avatar **560** to view a patron card **430**. The patron card **430** may be a unique account card associated with the unique

patron **530**. The patron **530** may access the patron card **430** to view statistics associated with the patron **530**. In other embodiments, the patron **530** may access the patron card **430** to view account settings. As shown in FIG. **40**, the patron **530** may access the patron card **430** to access a number of stars **440**, a number of coins **450**, a number of keys **460**, a status of achievements **470**, one or more glyphs **480**, a number of Easter Eggs **490** (e.g., hidden challenges, etc.), a selection of hints **500**, apparel **510**, etc. Stars **440** may designate a progress rank or level of the patron **530**. The coins **450** and keys **460** may be used as digital currency to purchase products within the interactive physical environment **100** (e.g., food, drinks, apparel **510**, play time, etc.).

(95) Referring now to FIGS. **41** and **42**, various examples of patron cards **430** are depicted. FIG. **41** depicts multiple patron cards **430a** on the patron kiosk **212**. The patron cards **430a** are displayed vertically from one another. In other embodiments, the patron cards **430a** may be displayed horizontally, vertically or angularly to one another. The patrons **530** may view multiple patron cards **430a** to compare statistics between individual patrons **530**. As shown in FIG. **42**, the patron kiosk **212** may display a single patron card **430b**. The patron card **430b** depicted displays the patron name, the stars **440**, the number of coins **450**, the status of achievements **470**, the patron level, and a number of gems. As shown on a left side of the patron card **430b**, the patron card **430b** may further include one or more tabs, where the patron **530** may interface with the one or more tabs to access different features within the patron card **430b**. For example, the patron **530** may access the one or more tabs to access the number of Easter Eggs **490**.

(96) If no patron **530** selects the patron avatar **560**, the patron kiosk **212** may display a sixth screen **650**, as shown in FIG. **43**. The sixth screen **650** may be substantially similar to the fifth screen **640**, except for now the patron may select a play button (e.g., arrow, etc.) to enter the room **220**.

(97) The control system **550** may determine whether to provide a hint or to not provide a hint. The patron **530** may interface with the patron kiosk **212** for a hint selection. The hint selection may be to select one of a hint. Alternatively, the patron **530** may interface with the patron kiosk to not have a hint. By way of example, the patron **530** may select a lightbulb symbol (e.g., lower right corner, etc.) on the patron kiosk **212**. In other embodiments, the patron **530** may select another symbol representing the hint selection.

(98) When the patron **530** wishes to access one or more hints, the patron **530** may interface with a hint button to display, via the patron kiosk **212**, an eighth screen **670**, as shown in FIG. **44**. The eighth screen **670** may represent a screen indicating that the patron has selected for the hint. As shown, the hint may include various levels of hints (e.g., tiny hint, better hint, 3-star hint, etc.). The patron **530** may select the desired hint in order to enhance the patron experience. In one example, the patron **530** may not choose a hint. In another example, the patron **530** may choose one or more of the sizes of hints. As can be appreciated, the more hints that are chosen may make the game challenge easier to complete. As shown in FIGS. **45** and **46**, the patron kiosk **212** may display a ninth screen **680** and a tenth screen **690**. The screens **680**, **690** may indicate that the patron has selected the desired hint. By way of example, the hints may be freely given to the patrons **530** to enhance patron experience. In some embodiments, as shown in FIG. **45**, the ninth screen **690** indicates that the hint may be purchased for an amount of coins, and may further identify an amount of coins that each patron has that are playing the challenge. As shown in FIG. **46**, the tenth screen **690** displays the hint to the patrons.

(99) More specifically, the control system **550** may receive the hint selection command, where the processor **554** communicates with the memory **552**. The memory **552** may include a lookup table corresponding to the hint selection. The lookup table may be a generic lookup table including hints for all the games. The lookup table may include various hint types (e.g., tiny hint, better hint, 3-star hint, etc.) associated with each game challenge. The memory **552** may provide a hint feedback to the processor **554**. In response to receiving the hint feedback, the processor **554** may send a command to provide the hint, or to not provide the hint. According to one example, the hint selection may display onto the patron kiosk **212** for the patron **530** to view. As can be appreciated,

the process for the hint selection may be repeated consecutively to provide the patron **530** with more than one hint.

(100) As shown in FIG. **47**, the patron kiosk **212** may display an eleventh screen **700**. The eleventh screen **700** may indicate that the room **220** is ready for the patrons **530** to play. In other embodiments, the eleventh screen **700** may automatically display onto the patron kiosk **512** indicating that the room **220** is empty and ready for play.

(101) Referring now to FIGS. **48** and **49**, each patron **530** may be associated with a patron avatar **560**. The patron avatar **560** may be displayed on the patron's unique patron card. As shown in FIG. **46**, the patron avatar **560** may include at least one of an animation **562**, a window **564**, an effect **566**, a star count **568**, a color **570**, a glow **572**, an icon **574**, a pattern **576**, and a map pin **578**. As discussed in greater detail herein, the patron avatar **560** may evolve to include more emblem features (e.g., animation **562**, effect **564**, window **564**, effect **566**, star count **568**, color **570**, glow **572**, icon **574**, pattern **576**, and map pin **578**) as the patron's level increases. According to one example, the patron may unlock access to the different emblem features by advancing levels. For example, the patron may include access to a set of one of the emblem features, and, as the patron levels up, the patron gains access to sets of the additional emblem features. As can be appreciated, the patron avatar **560** can advance in customization and complexity as the patron advances in levels (e.g., as shown in FIG. **38**).

(102) Referring specifically to FIG. **48**, the patron avatar **560** may be modified and customized by the control system **550**. The control system **550** may receive a command from the patron **530** to select or change one or more features of the patron avatar **560**. The features may include the animation **562**, the window **564**, the effect **566**, the star count **568**, the color **570**, the glow **572**, the icon **574**, the pattern **576**, and the map pin **578**. More specifically, the processor **554** may receive the command from the patron **530** to select or change elements of the patron avatar **560**. In response to receiving such a command, the processor **554** retrieves from memory **552** the data structure representing the patron avatar **560**. In some embodiments, the data structure may be an array of values, a linked list of values, or a lookup table. In still other embodiments, avatar data structures may be stored in a database. The requested changes may be made to the avatar data structure by the processor **554** and the updated data structure can be stored to memory **552**.

(103) In brief overview, a method for providing the patron avatar **560** includes identifying a patron **530**, transmitting patron **530** identification information, determining patron **530** performance, transmitting game performance data, receiving patron **530** identification information, receiving game performance data, and modifying the patron avatar **560** associated with the patron **530**.

(104) Identifying a patron **530** includes utilizing the control system **550** to determine if the patron **530** has scanned into the room **220**. The patron **530** may scan the identifier **535**, via the scanner at the patron kiosk **212**, to check-in to the room **220**. The identifier **535** may be one of the RFID tag, QR code, bar code, biometric characteristics, etc. By way of example, multiple patrons **530** may check-in to the patron kiosk **212** to check-in to the room **220** (e.g., two patrons **530**, four patrons **530**, six patrons **530**, etc.).

(105) Transmitting patron **530** identification information includes transmitting, from the scanner, associated patron identification information via the network **540**. The network **540** may be a wireless network (e.g., Wi-Fi, cloud based, Bluetooth, etc.) or could be a wired network. The patron identification information may be specific to the patron **530**, where the identifier **535** links the specific patron **530** to their associated identification information.

(106) Determining patron **530** performance includes utilizing the control system **550** to determine a status of the game. The control system **550** may receive status data from the room sensors **542**, where the room sensors **542** determine a status of objectives within the room **220**. The status may define a status of the patron **530** performance by comparing the status data to an objective data. The objective data may be a time data associated with an amount of time in which it takes the patron **530** to complete the objective. Additionally or alternatively, the objective data may be a count data

associated with a number of objectives reached during the game. Additionally or alternatively, the objective data may be a complete or incomplete objective data (e.g., objective achieved, objective not achieved, etc.).

(107) Transmitting game performance data includes transmitting, from the control system **550**, the game performance data via the network **540**. As discussed above, the network **540** may be a wireless network (e.g., Wi-Fi, cloud based, Bluetooth, etc.) or could be a wired network.

(108) Receiving patron **530** identification information includes the patron kiosk **212** receiving the patron **530** identification information from the control system **550**. The control system **550** may communicate through the network **540** to display the patron **530** identification information. The identification information could be the patron card **430**, patron avatar **560**, or the like.

(109) Receiving game performance data includes the patron kiosk **212** receiving the game performance data from the control system **550**. The control system **550** may communicate through the network **540** to display the game performance data. The game performance data may be a reward associated with the game. For example, the game performance data may display the reward earned from playing the game. In another example, the game performance data may display that the patron **530** has not earned the reward.

(110) Modifying the patron avatar **560** associated with the patron **530** includes receiving the patron avatar **560** or patron card **430** associated with the patron **530** from the control system **550**. The patron avatar **560** and/or patron card **430** may be displayed onto the patron kiosk **212**. The patron **530** may select the patron card **430** to access the patron avatar **560**. When viewing the patron avatar **560**, the patron **530** may select to change or add in the avatar features. In one embodiment, the patron avatar **560** and the patron card **430** are stored within a data storage element within the memory **552**. More specifically, the data storage element may store a patron identifying information, including the patron avatar **560** and the patron card **430**. Upon selection of new or changing avatar features, the memory **552** updates and stores the new patron avatar information within the patron identifying information. In some embodiments, the patron card data structure stored in memory **552** may be updated to permit the patron **530** access to and the ability to modify new sets of avatar features.

(111) Referring now to FIG. **50**, various examples of patron avatars **590** are shown. As shown, the patron avatars advance based upon level progression. For example, FIG. **50** shows a first level patron avatar **590a**, a second level patron avatar **590b**, a third level patron avatar **590c**, a fourth level patron avatar **590d**, a fifth level patron avatar **590e**, a sixth level patron avatar **590f**, a seventh level patron avatar **590g**, an eighth level patron avatar **590h**, and a ninth level patron avatar **590i**. The patron avatars **590a-590i** are shown to advance and/or evolve into more sophisticated patron avatars as the patron achieves a greater level. The patron avatar advancements and/or effects are described above with respect to FIGS. **48** and **49**.

(112) The control system **550** may determine an amount of digital currency needed to purchase real world items. Additionally or alternatively, the control system **550** may be a control system that determine the amount of digital currency to access new rooms. The patron **530** may purchase the real world items or access new spaces by using digital currency. The digital currency may be gems, coins, keys, tokens, or the like. The patron **530** may purchase the real world items or access new spaces via the patron kiosk **212**. Alternatively, an additional kiosk may be used to purchase real world items or access new spaces. The processor **554** may receive a command from the patron **530**, the command being at least one of to purchase the real world items **770** or access the new spaces **780**. The processor **554** may communicate the command to the memory **554**, where the memory **554** may include a lookup table. The lookup table may be a table defining all of the products available for purchasing and an associated digital currency amount for each. The memory **552** may pull the digital currency data associated with each item. When the patron **530** makes a purchase, the processor **554** determines the associated digital currency amount from the memory **552** and charges the associated digital currency amount from the patron **530**. After the processor **554** charges the

associated digital currency amount, the processor 554 determines a new digital currency for the unique patron 530.

(113) The control system 550 may automatically change a difficulty of a game challenge based on a number of patrons 530. The number of patrons 530 may be substantially equivalent or equal to a number of identifiers 535. Upon entrance into the room 220 the identifier 535 for each patron 530 is scanned. The game challenge may change in difficulty or change a reward based on the number of patrons 530. The control system 550 may detect the number of patrons 530 within the room 220 via scanning of the identifiers 535 and/or proximity sensors positioned within the room 220. In other embodiments, a QR code may be scanned, a physical feature of the patron 815 may be scanned (e.g., retinal, facial recognition, fingerprint, etc.), or an account number associated with the patron 815 may be inputted. In response to detecting the number of patrons 530, the control system 550 provides the information to the processor 554, where the processor 554 may communicate the number of patrons 530 to the memory 552. The memory 552 may include a lookup table. The lookup table may include information for the number of patrons 530 and the game challenge. An example lookup table is shown below in Table 1.

(114) TABLE-US-00002 Group Size 1 Star 2 Star 3 Star 2 Players 1 2 3 3 Players 2 4 7 4 Players 3 5 8 5 Players 4 6 9 6 Players 5 7 10

(115) Table 1 is an example lookup table for the game challenges.

(116) As shown in Table 1 above, the game challenges vary depending on the number of patrons 530. More specifically, a reward for completing the game challenges varies depending on the number of patrons 530. For example, if there are two patrons 530, the patrons 530 can earn a maximum of 3 stars for completing the game challenges by reaching an objective of 3. In another example, if there are six patrons 530, the patrons 530 can earn a maximum of 3 stars for completing the challenges by reaching an objective of 10. The status of the game challenge can be any status corresponding to the game challenges. The control system 550 may further be communicably coupled to the rooms 220. The control system 550 may receive a signal from the rooms 220 on a status of the game challenges while the patrons 530 are playing the entertainment game. Based on the feedback from the number of patrons 530 and the feedback from rooms 220, the processor 554 may determine an amount of stars to reward the patron 530 upon completion of the game challenges. Although a particular group size and reward are shown in Table 1, it can be appreciated that the lookup table can include any number of patrons and associated rewards for completing game challenges.

(117) Upon completion of the game challenge (e.g., objective, etc.), the control system 550 may reward the patron 530. More specifically, the processor 554 may determine a level of the challenge received based on the feedback from the room 220. The processor 554 may communicate the feedback to the memory 552, where the memory 552 determines, via the lookup table, an amount of stars to reward the patron 530. In association, the memory 552 communicates the reward back to the processor 554, where the processor 554 presents the reward back to the patron 530.

Additionally or alternatively, the memory 552 increases an amount of stars stored within a data storage element (e.g., patron card 430) for each patron 530. As can be appreciated, the memory 552 may access the data storage element for each patron 530, where the memory 552 adjusts an amount of digital currency (e.g., stars, coins, keys, tokens, points, etc.) based on a feedback from the processor 554.

(118) The control system 550 may provide a status for each patron 530 to enable play or disable play based on an in-game selection. When playing a game within the room 220, the patron 530 may make the in-game selection to advance or reach the objective. The in-game selection may permit or prevent the patron 530 from advancing through the room 220 based on the selection. For example, the patron 530 may make either one of a correct selection or an incorrect selection. Based on the selection, the patron 530 may be granted access to keep playing or advance within the room 220. The incorrect selection may further include one or more feedbacks, referred to herein as a number

of incorrect selections, successive incorrect selections, and difficulty of selection. In other embodiments, the one or more feedbacks may include more feedbacks than described above (e.g., number of patrons, level of patrons, etc.).

(119) The control system **550** may receive the in-game selection via the room sensors **542**. In one example, the room sensors **542** may be pressure sensors that detect the patron **530**. In another example, the room sensors **542** may be proximity sensors that detect movement of the patron **530**. The processor **554** may compare data from room sensors **542** with a lookup table or other data stored in memory **552** to determine whether to enable or continue play. In such an example, the patron **530** advances through the room **220** or onto the next challenge. In response to the incorrect in-game selection, the processor **554** disables play for the patron **530**. In such an example, the room **220** may provide a feedback to the patron **530** signifying that the objective has not been completed and the game is over. In one example, the lights may change brightness or color. In another example, the exit monitor **214** may provide a display. In another example, the room **220** may include audio to signify to the patron **530**. In some embodiments, the error selection may be scaled based on the number of incorrect selections, the number of incorrect successive selections, and the difficulty of the selection. When play for the patron **530** is disabled, it may be for a particular time limit, game duration, selection limit, etc. In some embodiments, if the patron **530** has made a first incorrect selection at an easy difficulty, the control system **550** may disable play for a short amount of time. In another example, if the patron **530** has made successive incorrect selections at a hard difficulty, the control system **550** may disable play for a greater amount of time.

(120) In brief overview, a method of entertaining the patron **530** includes coupling walls **210** to form the room **220**, presenting the game to the patron **530** including the identifier **535**, receiving patron identification information, and modifying the game presented in the room **220**.

(121) Coupling walls **210** to form the room **220** includes one or more wall configurations **212a-212e** are coupled together to form the room **220**. The wall configuration may form a structure corresponding to the room entrance **230**. The walls **210** may include the linkage assemblies **240a-240b**, **260a-260b**, the linkage assemblies extending outward from the wall configurations **212a-212e** to present an enclosed structure for the patrons **530**.

(122) Presenting the game to the patron **530** includes permitting the patron **530** access into the room **220**. The patron **530** may be permitted access into the room **220** via the room entrance **230**. The patron **530** may include the identifier **535**, where the identifier **535** is scanned at the patron kiosk **212** to check-in the patron **530** for the room **220**. Upon scanning into the patron kiosk **212**, the patron card **430** is displayed onto the screen. The screen may include all patron cards **430** associated with all the patrons **530** checked-in to the room **220**.

(123) In some embodiments, the game includes a plurality of game components positionable in a first game configuration and a second game configuration. The first game configuration may present a first challenge and the second game configuration may present a second challenge. The second game configuration may further present a solution to the first challenge. Accordingly, the first game configuration may present a solution to the second challenge.

(124) In some embodiments, the game includes a hint selection. The patron **530** may select for one or more hints associated with the game, via the patron kiosk **212**. The patron **530** may choose between varying levels of hints (e.g., tiny hint, better hint, 3-star hint, etc.). The patron kiosk **212** may send a command to the control system **550**, via the network **540**, to pull the desired hint from the memory **552**. The control system **550** may provide the hint information back to the patron kiosk **212**, where the patron kiosk **212** displays the hint onto the screen of the patron kiosk **212**.

(125) Receiving patron **530** identification information includes the patron kiosk **212** receiving the patron **530** identification information from the control system **550**. The control system **550** may communicate through the network **540** to display the patron **530** identification information. The identification information could be the patron card **430**, patron avatar **560**, or the like.

(126) Modifying the game presented in the room **220** includes changing, via the control system

550, the objectives of the room **220**. In one example, the control system **550** may change the room objectives based on group size. In such an example, the control system **550** may receive a status from the scanner, the status signifying an amount of patrons **530** checked-in to the room. In response to receiving the scanner status, the control system **550** may pull, from the lookup table within the memory **552**, objective information for the room **220** (e.g., as shown in Table 1). The control system **550** may automatically adjust the objective to scale to the group size. Accordingly, the room may require more objectives to be achieved in order to receive maximum reward, for large group sizes.

(127) In some embodiments, the control system **550** may receive status data from the room sensors **542**, where the room sensors **542** determine a status of objectives within the room **220**. The status may define a status of the patron **530** performance by comparing the status data to an objective data. The objective data may be a time data associated with an amount of time in which it takes the patron **530** to complete the objective. Additionally or alternatively, the objective data may be a count data associated with a number of objectives reached during the game. Additionally or alternatively, the objective data may be a complete or incomplete objective data (e.g., objective achieved, objective not achieved, etc.).

(128) In such an embodiment, the patron kiosk **212** receives the game performance data from the control system **550**. The control system **550** may communicate through the network **540** to display the game performance data. The game performance data may be a reward associated with the game. For example, the game performance data may display the reward earned from playing the game. In another example, the game performance data may display that the patron **530** has not earned the reward.

(129) In such an embodiment, the patron kiosk **212** receives the patron avatar **560** or patron card **430** associated with the patron **530** from the control system **550**. The patron avatar **560** and/or patron card **430** may be displayed onto the patron kiosk **212**. The patron **530** may select the patron card **430** to access the patron avatar **560**. When viewing the patron avatar **560**, the patron **530** may select to change or add in the avatar features. In one embodiment, the patron avatar **560** and the patron card **430** are stored within a data storage element within the memory **552**. More specifically, the data storage element may store a patron identifying information, including the patron avatar **560** and the patron card **430**. Upon selection of new or changing avatar features, the memory **552** updates and stores the new patron avatar information within the patron identifying information. In some embodiment, the memory **552** may be updated to permit the patron **530** access to new sets of avatar features.

(130) As utilized herein, the terms “approximately,” “about,” “substantially”, and similar terms are intended to have a broad meaning in harmony with the common and accepted usage by those of ordinary skill in the art to which the subject matter of this disclosure pertains. It should be understood by those of skill in the art who review this disclosure that these terms are intended to allow a description of certain features described and claimed without restricting the scope of these features to the precise numerical ranges provided. Accordingly, these terms should be interpreted as indicating that insubstantial or inconsequential modifications or alterations of the subject matter described and claimed are considered to be within the scope of the disclosure as recited in the appended claims.

(131) It should be noted that the term “exemplary” and variations thereof, as used herein to describe various embodiments, are intended to indicate that such embodiments are possible examples, representations, or illustrations of possible embodiments (and such terms are not intended to connote that such embodiments are necessarily extraordinary or superlative examples).

(132) The term “coupled” and variations thereof, as used herein, means the joining of two members directly or indirectly to one another. Such joining may be stationary (e.g., permanent or fixed) or moveable (e.g., removable or releasable). Such joining may be achieved with the two members coupled directly to each other, with the two members coupled to each other using a separate

intervening member and any additional intermediate members coupled with one another, or with the two members coupled to each other using an intervening member that is integrally formed as a single unitary body with one of the two members. If “coupled” or variations thereof are modified by an additional term (e.g., directly coupled), the generic definition of “coupled” provided above is modified by the plain language meaning of the additional term (e.g., “directly coupled” means the joining of two members without any separate intervening member), resulting in a narrower definition than the generic definition of “coupled” provided above. Such coupling may be mechanical, electrical, or fluidic.

(133) References herein to the positions of elements (e.g., “top,” “bottom,” “above,” “below”) are merely used to describe the orientation of various elements in the FIGURES. It should be noted that the orientation of various elements may differ according to other exemplary embodiments, and that such variations are intended to be encompassed by the present disclosure.

(134) The hardware and data processing components used to implement the various processes, operations, illustrative logics, logical blocks, modules and circuits described in connection with the embodiments disclosed herein may be implemented or performed with a general purpose single- or multi-chip processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA), or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general purpose processor may be a microprocessor, or, any conventional processor, controller, microcontroller, or state machine. A processor also may be implemented as a combination of computing devices, such as a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration. In some embodiments, particular processes and methods may be performed by circuitry that is specific to a given function. The memory (e.g., memory, memory unit, storage device) may include one or more devices (e.g., RAM, ROM, Flash memory, hard disk storage) for storing data and/or computer code for completing or facilitating the various processes, layers and modules described in the present disclosure. The memory may be or include volatile memory or non-volatile memory, and may include database components, object code components, script components, or any other type of information structure for supporting the various activities and information structures described in the present disclosure. According to an exemplary embodiment, the memory is communicably connected to the processor via a processing circuit and includes computer code for executing (e.g., by the processing circuit or the processor) the one or more processes described herein.

(135) The present disclosure contemplates methods, systems and program products on any machine-readable media for accomplishing various operations. The embodiments of the present disclosure may be implemented using existing computer processors, or by a special purpose computer processor for an appropriate system, incorporated for this or another purpose, or by a hardwired system. Embodiments within the scope of the present disclosure include program products comprising machine-readable media for carrying or having machine-executable instructions or data structures stored thereon. Such machine-readable media can be any available media that can be accessed by a general purpose or special purpose computer or other machine with a processor. By way of example, such machine-readable media can comprise RAM, ROM, EPROM, EEPROM, or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium which can be used to carry or store desired program code in the form of machine-executable instructions or data structures and which can be accessed by a general purpose or special purpose computer or other machine with a processor. Combinations of the above are also included within the scope of machine-readable media. Machine-executable instructions include, for example, instructions and data which cause a general purpose computer, special purpose computer, or special purpose processing machines to perform a certain function or group of functions.

(136) Although the figures and description may illustrate a specific order of method steps, the order of such steps may differ from what is depicted and described, unless specified differently above. Also, two or more steps may be performed concurrently or with partial concurrence, unless specified differently above. Such variation may depend, for example, on the software and hardware systems chosen and on designer choice. All such variations are within the scope of the disclosure. Likewise, software implementations of the described methods could be accomplished with standard programming techniques with rule-based logic and other logic to accomplish the various connection steps, processing steps, comparison steps, and decision steps.

(137) It is important to note that the construction and arrangement of the vehicle **10** and the systems and components thereof as shown in the various exemplary embodiments is illustrative only. Additionally, any element disclosed in one embodiment may be incorporated or utilized with any other embodiment disclosed herein. Although only one example of an element from one embodiment that can be incorporated or utilized in another embodiment has been described above, it should be appreciated that other elements of the various embodiments may be incorporated or utilized with any of the other embodiments disclosed herein.

Claims

1. A self-resetting game provided by an interactive physical environment, the game comprising: a plurality of game components repositionable within a game room provided by the interactive physical environment; a room sensor detecting a first position of at least some of the plurality of game components; a control system receiving from the room sensor the detected position, the control system determining that the detected position of the at least some of the plurality of game components is proximate one of a plurality of game solutions and selecting, responsive to the received position information, the one of the plurality of game solutions requiring the plurality of game components to be rearranged into a second position different from the first position; and an indicator conveying the selected one of the game solutions.
2. The game of claim 1, wherein the room sensor comprises pressure sensors.
3. The game of claim 1, wherein the room sensor comprises at least one of an optical sensor, a camera, an RFID sensor, or an infrared sensor.
4. The game of claim 1, wherein the room sensor detects a first position of at least some of the plurality of game components in relation to a first game solution.
5. The game of claim 4, wherein the control system determines that the detected position of the at least some of the plurality of game components is proximate one of a plurality of game solutions and selects, responsive to the received position information, the one of the plurality of game solutions.
6. The game of claim 4, wherein the control system determines that the detected position of the at least some of the plurality of game components matches a first one of a plurality of game solutions and selects, responsive to the received position information, a second one of the plurality of game solutions different from the first one of the plurality of game solutions.
7. The game of claim 1, wherein the control system allows a patron into the game room.
8. The game of claim 1, wherein the indicator is a monitor positioned within the game room, and wherein the monitor receives from the control system, and displays, the selected one of the game solutions.
9. A method for providing a self-resetting game in a game room provided by an interactive physical environment, comprising: providing a plurality of game components repositionable within a game room of the interactive physical environment; detecting, by a room sensor, a first position of at least some of the plurality of game components; receiving, by a control system, the detected first position of the at least some of the plurality of game components; determining, by the control system, that the detected position of the at least some of the plurality of game components is

proximate one of a plurality of game solutions; selecting, by the control system responsive to the received position information, the one of the plurality of game solutions requiring the plurality of game components to be rearranged into a second position different from the first position; transmitting, by the control system to monitor in the game room, the selected one of the plurality of game solutions; and indicating, by an indicator, the selected one of the plurality of game solutions.

10. The method of claim 9, further comprising the step of allowing a patron into the room.

11. The method of claim 9, wherein detecting a first position further comprises detecting a first position of at least some of the plurality of game components in relation to a first game solution.

12. The method of claim 9, wherein the control system determines that the detected position of the at least some of the plurality of game components is proximate one of a plurality of game solutions and selects, responsive to the received position information, the one of the plurality of game solutions.

13. The method of claim 12, further comprising determining, by the control system, that the received position information of the at least some of the plurality of game components matches a first one of a plurality of game solutions.

14. The method of claim 12, further comprising selecting, by the control system responsive to the determination, a second one of the plurality of game solutions different from the first one of the plurality of game solutions.

15. The method of claim 9, wherein the indicator is a monitor positioned within the game room, and wherein the monitor receives from the control system, and displays, the selected one of the game solutions.
