

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399191
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Sears; Gordon et al.

Histological tissue specimen processing

Abstract

A method of operating a tissue processor for processing tissue samples is provided. The tissue processor includes at least one retort for receiving tissue samples, at least one container for storing a reagent, and at least one sensor arranged for fluid communication with one or both of the at least one container and the at least one retort for measuring a measured purity level of a reagent. The method includes the steps of conducting reagent from the at least one container or the at least one retort to the at least one sensor, automatically measuring, by means of the at least one sensor, a measured purity level of the reagent, checking whether the measured purity level meets a predetermined purity level of the reagent associated with the at least one container, and automatically determining, based on a result of checking, whether the reagent is suitable for processing tissue samples in the tissue processor. A tissue processor for processing tissue samples is also provided. A container is also provided for storing tissue samples for processing in a tissue processor.

Inventors: Sears; Gordon (Victoria, AU), Drummond; Michael Houston (Victoria, AU), Oh-Ainle; Donnchadh (Victoria, AU)

Applicant: LEICA BIOSYSTEMS MELBOURNE PTY LTD (Mount Waverley, AU)

Family ID: 1000008778990

Assignee: LEICA BIOSYSTEMS MELBOURNE PTY LTD (Mount Waverley, AU)

Appl. No.: 17/872953

Filed: July 25, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230061034 A1	Mar. 02, 2023

Related U.S. Application Data

Publication Classification

Int. Cl.: **G01N1/31** (20060101); **G01N35/00** (20060101)

U.S. Cl.:

CPC **G01N35/00663** (20130101); **G01N1/31** (20130101); G01N2001/315 (20130101);
G01N2035/00673 (20130101)

Field of Classification Search

CPC: G01N (2035/00673); G01N (2001/315); G01N (1/31); G01N (35/00663); G01N (1/30);
B65D (2501/24057); B65D (2501/24); B65D (71/406)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3995803	12/1975	Uitz	294/142	B62J 9/21
5127537	12/1991	Graham	220/838	G01N 1/36
5427308	12/1994	Swift	229/114	B65D 5/68
6047976	12/1999	Wang	280/37	A45C 11/20
8288086	12/2011	Metzner et al.	N/A	N/A
8309037	12/2011	Erben et al.	N/A	N/A
2006/0148063	12/2005	Fauzzi et al.	N/A	N/A
2007/0243626	12/2006	Windeyer	422/292	G01N 35/0092
2008/0248560	12/2007	Drummond	N/A	N/A
2010/0099199	12/2009	Egle et al.	N/A	N/A
2010/0112624	12/2009	Metzner et al.	N/A	N/A
2010/0112625	12/2009	Erben et al.	N/A	N/A
2011/0041599	12/2010	Herrmann et al.	N/A	N/A
2013/0196339	12/2012	Dowling et al.	N/A	N/A
2015/0241325	12/2014	Webber	221/307	G01N 1/312
2016/0175173	12/2015	Higgs-Jackson	29/434	B65D 25/14
2019/0137532	12/2018	Temple et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
626268	12/1960	CA	N/A
101351153	12/2008	CN	N/A
2000028501	12/1999	JP	N/A
20160353 86	12/2015	JP	N/A
03029845	12/2002	WO	N/A
2005031312	12/2004	WO	N/A
2005116609	12/2004	WO	N/A

OTHER PUBLICATIONS

Extended European Search Report dated Feb. 5, 2021 from the European Patent Office in EP Application No. 18849016.3. cited by applicant

Haeckel et al., “Recommendations for definition and determination of carry-over effects”, Journal of Automatic Chemistry, vol. 10, No. 4, pp. 181-183, Oct. 1988, XP055767785 (4 pages total). cited by applicant

International Preliminary Report on Patentability with translation of Written Opinion dated Feb. 25, 2020, in International Application No. PCT/AU2018/050892. cited by applicant

International Search Report dated Oct. 29, 2018 in International Application No. PCT/AU2018/050892. cited by applicant

International Search Report for PCT/AU2018/050892, dated Oct. 29, 2018. cited by applicant

Written Opinion for PCT/AU2018/050892, dated Oct. 29, 2018. cited by applicant

Mettler-Toledo International Inc. all rights reserved. (Jul. 31, 2017). Mettler toledo balances & scales for Industry, Lab, Retail. Mettler Toledo Balances & Scales for Industry, Lab, Retail—Mettler Toledo,
<https://web.archive.org/web/20170808205100/https://www.mt.com/us/en/home.html>. (Year: 2017). cited by applicant

European Exam Report Article dated Nov. 16, 2022, in EP Application No. 18849016.3. cited by applicant

Japanese Office Action dated Aug. 9, 2022 in JP Application No. 2020-505829. cited by applicant

Chinese Office Action dated Nov. 3, 2022 in Chinese Application No. 201880045954.0. cited by applicant

Indian Office Action dated Mar. 25, 2022, in Indian Application No. 201917051291. cited by applicant

Office Action dated Jan. 17, 2023 issued by the Japanese Patent Office in Japanese Application No. 2020-505829. cited by applicant

Office Action issued Jul. 17, 2023 in Canadian Application No. 3,066,282. cited by applicant

Office Action issued Apr. 28, 2023 in Korean Application No. 10-2020-7001883. cited by applicant

Office Action issued May 24, 2023 in Australian Application No. 2018322484. cited by applicant

Communication issued Oct. 20, 2023 in European Application No. 18 849 016.3. cited by applicant

Australian Examination Report No. 1 for Australian Patent Application No. 2023270360, dated Sep. 6, 2024, 2 pages. cited by applicant

Communication pursuant to Article 94(3) EPC for European Patent Application No. 18849016.3, dated Dec. 19, 2024, 6 pages. cited by applicant

Extended European Search Report for European Patent Application No. 25169488.1, dated Jul. 10, 2025, 6 pages. cited by applicant

Primary Examiner: Robinson; Elizabeth A

Assistant Examiner: Shi; Tingchen

Attorney, Agent or Firm: Kinney & Lange, P.A.

Background/Summary

(1) This application is a continuation of U.S. application Ser. No. 16/621,362, filed Dec. 11, 2019, which is a National Stage of International Application No. PCT/AU2018/050892 filed Aug. 22,

TECHNICAL FIELD

(1) The present invention relates to a method of operating a tissue processor, and to the tissue processor. The tissue processor includes at least one retort for receiving tissue samples, and at least one container for storing a reagent. It relates more particularly but not exclusively to operating the tissue processor to determine whether a reagent is suitable for processing tissue samples in the tissue processor. The present invention also relates to a container for storing tissue samples for processing in a tissue processor.

BACKGROUND OF INVENTION

(2) Biological tissue samples, in particular histological tissue samples, are often required in the fields of human and veterinary medicine, in particular as microscopic prepared specimens for the assessment of cells and their environment. For microscopic inspection, thin sections of the tissue sample must be prepared for assessment under the microscope, in incident or transmitted light, by an expert.

(3) The production of thin sections, for example using a microtome, requires that the tissue sample have a certain strength so that thin, transparent sections having a thickness on the order of micrometres can be produced using a knife. For this purpose, the tissue sample must first pass through a treatment process in which it is fixed, dehydrated, cleared, and then infiltrated with a carrier material, preferably melted paraffin. These processes are often performed successively in a single unit called a “tissue processor”; this tissue processor includes for this purpose a closable process chamber called a “retort” that receives the various reagents, in particular process media, for carrying out the process steps at a suitable temperature and pressure.

(4) These processes for processing the tissue samples in the tissue processor are generally provided as a tissue processor workflow. The tissue processor workflow defines the processes to be applied by selected laboratory stations in the tissue processor, such as the retort. Also, where the tissue sample is to be analysed for histopathological or histological assessment, the tissue processor workflow forms part of a histopathology workflow.

(5) Successful processing of tissue samples using a tissue processor relies on immersing the tissue samples in reagents at temperature or ambient temperature in a sequence of reagent types and increasing concentrations. Processing of tissue samples with reagent of insufficient concentration before progressing to the next reagent type can result in contamination of the sample and poorly processed tissue. In worst case scenarios, the processed tissue cannot be used for diagnostic purposes resulting in patients requiring re-biopsy or where in instances when there is no more sample to excise, such as for melanomas, a failure to diagnose the biopsy.

(6) The reagent quality is dependent on a user to ensure that a sufficient concentration of reagent is provided in the tissue processor and that the concentration is accurately identified, which is susceptible to human error. For example, a user may inadvertently assume that a reagent is pure although dilution or contamination of the reagent has occurred during processing. Furthermore, a user may incorrectly re-fill a reagent container of the tissue processor with the incorrect reagent type, concentration or volume. Additionally, a user may replace an empty or partially full reagent container in the tissue processor to activate a sensor and overcome a system error of insufficient reagent for processing.

(7) Therefore, it would be desirable to provide a method of operating a tissue processor, and a tissue processor, that can verify reagent quality so as to avoid user error and potential suboptimal tissue processing, and which ameliorates and/or overcomes one or more problems or inconveniences of the prior art.

(8) Successful processing of tissue samples using a tissue processor also relies on design of the basket which is loaded into the tissue processor and stores the tissue samples for processing,

preferably within cassettes. The basket design is important to ensure that the reagents used in tissue processing flow to the cassettes and tissue samples to achieve optimal processing. However, baskets currently used in tissue processors can interfere with sensors for determining fluid level in the retort in which the basket is placed. This may result in incorrect volumes or types of processing fluid being used in tissue processing protocols, which may lead to poorly processed tissue samples. Furthermore, multiple baskets are usually stacked in the retort for efficient processing and/or are transported in a stacked configuration from grossing, where formalin soaked samples are prepared, to tissue processing stations of the tissue processor. However, the baskets currently used in tissue processors include a handle that may interfere with their stacking for these purposes.

(9) Therefore, it would also be desirable to provide a basket for a tissue processor that does not interfere with fluid sensors of the tissue processor and/or is able to be readily stacked, and which ameliorates and/or overcomes one or more problems or inconveniences of the prior art.

(10) A reference herein to a patent document or any other matter identified as prior art, is not to be taken as an admission that the document or other matter was known or that the information it contains was part of the common general knowledge as at the priority date of any of the claims.

SUMMARY OF INVENTION

(11) Viewed from one aspect of the present invention, there is provided a method of operating a tissue processor for processing tissue samples, the tissue processor including: at least one retort for receiving tissue samples; at least one container for storing a reagent; and at least one sensor arranged for fluid communication with one or both of the at least one container and the at least one retort for measuring a measured purity level of a reagent, the method including the steps of: a) conducting reagent from the at least one container or the at least one retort to the at least one sensor; b) automatically measuring, by means of the at least one sensor, a measured purity level of the reagent; c) checking whether the measured purity level meets a predetermined purity level of the reagent associated with the at least one container; and d) automatically determining, based on a result of the checking, whether the reagent is suitable for processing tissue samples in the tissue processor.

(12) In some embodiments, the method further includes the step of providing the predetermined purity level of the reagent based on reagent data for the at least one container. The reagent data preferably includes at least a concentration value of the reagent. The concentration value can be a percentage dilution of the reagent in water, such as 70%, 80% or 100%. The reagent data can also include one or more of a reagent type, a reagent name and a container number. The reagent type can include one or more of a dehydrating fluid, such as ethanol, methanol, isopropanol, butanol, ethylene glycol and various alcohols, a clearing reagent, such as xylene, di-pentene, D-limonene, 1,1,1, trichloroethane, toluene and dioxane, and an infiltrating material, such as paraffin wax, to name a few.

(13) The method can further include the step of receiving, at the tissue processor, the reagent data for the at least one container from a user. The tissue processor can further include an input device, and the receiving step can include receiving the reagent data by means of the input device. The input device can include a control interface of the tissue processor having, for example, a touchscreen display operable by a user. Additionally/alternatively, the tissue processor can include a controller configured to receive the reagent data from a server or computing system, such as through a wireless or hard-wired connection.

(14) The predetermined purity level of the reagent can be one of a threshold value or a tolerance range of values. Preferably, the predetermined purity level of the reagent is a concentration level determined based on the concentration value from the reagent data. The concentration level can be a threshold value, where the threshold value can be the concentration value from the reagent data. Where the concentration level is a tolerance range of values, the range can be determined based on the concentration value from the reagent data.

(15) Alternatively, the predetermined purity level can be a density level determined based on the

concentration value from the reagent data. The density level can be a threshold value, where the threshold value can be a density value derived from the concentration value from the reagent data, such as through a calculation based on the pure reagent concentration or using a look-up table for the reagent. Where the density level is a tolerance range of values, the range can be determined based on the derived density value.

(16) In some embodiments, the at least one sensor measures at step b) a density value that represents the measured purity level of the reagent. The at least one sensor is preferably a fluid sensor configured to measure the density value of the reagent. The fluid sensor can be a densitometer, and preferably an oscillating pipe density meter.

(17) The method can further include the steps of repeating the measuring step b) one or more times, and calculating an average of the measured density values, wherein the calculated average represents the measured purity level of the reagent. Preferably, the measuring step b) is repeated at least three times for calculating the average of the three measured density values. The measured purity level is preferably a concentration value derived from the measured density value or the average of the measured density values, such as through a calculation method based on the pure reagent density or using a look-up table for the reagent. Alternatively, the measured purity level can be the measured density value or the average of the measured density values.

(18) In some embodiments, the checking step c) of the method includes checking whether the measured purity level is (i) greater than the threshold value of the predetermined purity level, or (ii) within the tolerance range of values of the predetermined purity level. The checking step is preferably performed on the basis of a comparison of concentration values, where the measured purity level is the concentration value derived from the measured density value or average of measured density values, and the predetermined purity level is the concentration value from the reagent data or the tolerance range of values determined based on the concentration value from the reagent data. However, the checking step can be performed on the basis of a comparison of density values, such as when the predetermined purity level is a density level.

(19) In some embodiments, the automatically determining step d) includes: determining that the reagent is suitable for processing tissue samples when the measured purity level is greater than the threshold value or within the tolerance range of values; and determining that the reagent is unsuitable for processing tissue samples when the measured purity level is less than the threshold value or falls outside the tolerance range of values. When the reagent is determined to be unsuitable for processing tissue samples, the method can further include the step of flagging the at least one container for non-use by the tissue processor. The method can also further include the step of generating, at the tissue processor, a notification signal for a user to check the reagent in the flagged container. The notification signal can be provided to the user by the input device, such as a control interface having a user display. The notification signal can include a message and/or alarm displayed on the user display.

(20) The method can be performed prior to operating the tissue processor to perform a tissue processing protocol using the reagent. Accordingly, in some embodiments the tissue processor includes a dedicated line connecting the at least one container or the at least one retort to the at least one sensor, and the conducting step a) of the method includes conducting reagent in the dedicated line from the at least one container or the at least one retort to the at least one sensor. Preferably, the dedicated line is separate from a reagent line that connects the at least one container to the at least one retort. The conducting step a) can include the transfer or pumping of reagent from the at least one container or the at least one retort along the dedicated line to the at least one sensor for measuring the measured purity level of the reagent.

(21) In other embodiments, the method is performed when operating the tissue processor to perform a tissue processing protocol using the reagent. The tissue processor can include a reagent line connecting the at least one container and the at least one retort, wherein the at least one sensor is arranged for fluid communication with the reagent line, and wherein the conducting step a)

includes conducting reagent in the reagent line between the at least one container and the at least one retort. The at least one sensor can be one of: positioned in the reagent line; or positioned in a bypass line that receives a portion of the reagent when the reagent is conducted in the reagent line.

(22) The method can be performed on one or both of: filling of the at least one retort with reagent; and draining of the at least one retort to remove reagent. Accordingly, the method can be performed on starting and/or finishing of a tissue processing protocol during which the at least one retort is filled or drained, respectively. In some embodiments, the method further includes the step of operating the tissue processor to stop filling or draining of the at least one retort to perform at least method steps (b)-(d). The operating the tissue processor to stop filling or draining can include one or both of: operating the tissue processor to stop filling prior to reagent contacting tissue samples stored in the at least one retort; and operating the tissue processor to stop filling prior to reagent being delivered to the at least one container.

(23) When the reagent is determined to be suitable for processing tissue samples, the method can further include the step of operating the tissue processor to continue filling or draining of the at least one retort to complete the tissue processing protocol. Otherwise, when the reagent is determined to be unsuitable for processing tissue samples, the method can further include the step of operating the tissue processor to abandon the tissue processing protocol.

(24) In some embodiments, the tissue processor includes a first container for storing a first reagent and a second container for storing a second reagent. The method can further include the step of: operating the tissue processor to perform a tissue processing protocol using the first reagent and the second reagent; and automatically determining a carry over volume of the first reagent from the first container into the second reagent from the second container.

(25) In some embodiments, the step of automatically determining the carry over volume includes the steps of: providing an initial volume of the second reagent in the second container; and performing the measuring step b) to measure the following: a density value of the first reagent on draining of the at least one retort; a density value of the second reagent on filling of the at least one retort; and a density value of the second reagent on draining of the at least one retort, wherein the carry over volume is calculated according to:

$$(26) V_{CO} = \frac{C_{2out} - C_{2in}}{C_{1out} - C_{2out}} \times V$$

wherein: V_{CO} =volume of carry over (L), p_{C2out} =measured density value of the second reagent on draining of the at least one retort (kg/m³), p_{C2in} =measured density value of the second reagent on filling of the at least one retort (kg/m³), p_{C1out} =measured density value of the first reagent on draining of the at least one retort (kg/m³), and V =initial volume of the second reagent in the second container (L).

(27) Viewed from another aspect of the present invention, there is provided a computer program product including: a computer readable medium having computer readable program code and computer readable system code embodied on the medium for, operating a tissue processor, within a data processing system, the computer program product including: computer readable code within the computer readable medium for performing the method of operating a tissue processor as described above.

(28) Viewed from another aspect of the present invention, there is provided a tissue processor for processing tissue samples, including: at least one retort for receiving tissue samples; at least one container for storing a reagent; at least one sensor arranged for fluid communication with one or both of the at least one container and the at least one retort for measuring a measured purity level of a reagent; and a controller configured to: conduct reagent from the at least one container or the at least one retort to the at least one sensor; measure, by means of the at least one sensor, a measured purity level of the reagent; check whether the measured purity level meets a predetermined purity level of the reagent associated with the at least one container; and determine, based on a result of the checking, whether the reagent is suitable for processing tissue samples in the tissue processor.

(29) In some embodiments, the controller is further configured to provide the predetermined purity level of the reagent based on reagent data for the at least one container. The reagent data preferably includes at least a concentration value of the reagent. The concentration value can be a percentage dilution of the reagent in water, such as 70%, 80% or 100%. The reagent data can also include one or more of a reagent type, a reagent name and a container number. The reagent type can include one or more of a dehydrating fluid, such as ethanol, methanol, isopropanol butanol, ethylene glycol and various alcohols, a clearing reagent, such as xylene, di-pentene, D-limonene, 1,1,1, trichloroethane, toluene and dioxane, and an infiltrating material, such as paraffin wax, to name a few.

(30) The controller can be further configured to receive, at the tissue processor, the reagent data for the at least one container from a user. The tissue processor can further include an input device, and the controller can be configured to receive the reagent data by means of the input device. The input device can include a control interface of the controller having, for example, a touchscreen display operable by a user. Alternatively, the controller can be configured to receive the reagent data from a server or computing system, such as through a wireless or hard-wired connection.

(31) The predetermined purity level of the reagent can be one of a threshold value or a tolerance range of values. Preferably, the predetermined purity level of the reagent is a concentration level determined based on the concentration value from the reagent data. The concentration level can be a threshold value, where the threshold value can be the concentration value from the reagent data. Where the concentration level is a tolerance range of values, the range can be determined based on the concentration value from the reagent data.

(32) Alternatively, the predetermined purity level can be a density level determined based on the concentration value from the reagent data. The density level can be a threshold value, where the threshold value can be a density value derived from the concentration value from the reagent data, such as through a calculation based on the pure reagent concentration or using a look-up table for the reagent. Where the density level is a tolerance range of values, the range can be determined based on the derived density value.

(33) In some embodiments, the at least one sensor measures a density value that represents the measured purity level of the reagent. The at least one sensor is preferably a fluid sensor configured to measure the density value of the reagent. The fluid sensor can be a densitometer, and preferably an oscillating pipe density meter.

(34) The controller can be configured to measure, by means of the at least one sensor, the density value that represents the measured purity level of the reagent two or more times, and can be further configured to calculate an average of the measured density values, wherein the calculated average represents the measured purity level of the reagent. Preferably, the density value is measured at least three times for calculating the average of the three measured density values. Preferably, the measured purity level is a concentration value derived from the measured density value or the average of the measured density values, such as through a calculation method based on the pure reagent density or using a look-up table for the reagent. Alternatively, the measured purity level can be the measured density value or the average of the measured density values.

(35) In some embodiments, the controller checks whether the measured purity level is (i) greater than the threshold value of the predetermined purity level, or (ii) within the tolerance range of values of the predetermined purity level. The checking is preferably performed on the basis of a comparison of concentration values, where the measured purity level is the concentration value derived from the measured density value or average of measured density values, and the predetermined purity level is the concentration value from the reagent data or the tolerance range of values determined based on the concentration value from the reagent data. However, the checking step can be performed on the basis of a comparison of density values, such as when the predetermined purity level is a density level.

(36) In some embodiments, the controller determines that the reagent is suitable for processing

tissue samples when the measured purity level is greater than the threshold value or within the range of values; and wherein the controller determines that the reagent is unsuitable for processing tissue samples when the measured purity level is less than the threshold value or falls outside the range of values. When the reagent is determined to be unsuitable for processing tissue samples, the controller can be further configured to flag the at least one container for non-use by the tissue processor. The controller can also be further configured to generate, at the tissue processor, a notification signal for a user to check the reagent in the flagged container. The notification signal can be provided to the user by the input device, such as a control interface of the controller having a user display. The notification signal can include a message and/or alarm displayed on user display.

(37) The controller can determine whether the reagent is suitable for processing tissue samples prior to operating the tissue processor to perform a tissue processing protocol using the reagent. Accordingly, in some embodiments the tissue processor includes a dedicated line connecting the at least one container or the at least one retort to the at least one sensor, and the controller conducts reagent in the dedicated line from the at least one container or the at least one retort to the at least one sensor. Preferably, the dedicated line is separate from a reagent line that connects the at least one container to the at least one retort. Conducting reagent can include the transfer or pumping of reagent from the at least one container or the at least one retort along the dedicated line to the at least one sensor for measuring the measured purity level of the reagent.

(38) In other embodiments, the controller determines whether the reagent is suitable for processing tissue samples when operating the tissue processor to perform a tissue processing protocol using the reagent. The tissue processor can include a reagent line connecting the at least one container and the at least one retort, wherein the at least one sensor is arranged for fluid communication with the reagent line, and wherein the controller conducts reagent in the reagent line between the at least one container and the at least one retort. The at least one sensor can be one of: positioned in the reagent line; or positioned in a bypass line that receives a portion of the reagent when the reagent is conducted in the reagent line.

(39) The controller can determine whether the reagent is suitable for processing tissue samples during one or both of: filling of the at least one retort with reagent; and draining of the at least one retort to remove reagent. Accordingly, the controller can determine the suitability of the reagent on starting and/or finishing of a tissue processing protocol during which the at least one retort is filled or drained, respectively. In some embodiments, the controller is further configured to operate the tissue processor to stop filling or draining of the at least one retort to determine whether the reagent is suitable for processing tissue samples. The controller can operate the tissue processor to stop filling or draining by one or both of: operating the tissue processor to stop filling prior to reagent contacting tissue samples stored in the at least one retort; and operating the tissue processor to stop filling prior to reagent being delivered to the at least one container.

(40) When the controller determines that the reagent is suitable for processing tissue samples, the controller can be further configured to operate the tissue processor to continue filling or draining of the at least one retort to complete the tissue processing protocol. Otherwise, when the controller determines that the reagent is unsuitable for processing tissue samples, the controller can be further configured to operate the tissue processor to abandon the tissue processing protocol.

(41) In some embodiments, the tissue processor includes a first container for storing a first reagent and a second container for storing a second reagent. The controller can be further configured to: operate the tissue processor to perform a tissue processing protocol using the first reagent and the second reagent; and determine a carry over volume of the first reagent from the first container into the second reagent from the second container.

(42) In some embodiments, the controller is configured to determine the carry over volume by: receiving an initial volume of the second reagent in the second container; and measuring, by means of the at least one sensor, the following: a density value of the first reagent on draining of the at

least one retort; a density value of the second reagent on filling of the at least one retort; and a density value of the second reagent on draining of the at least one retort, wherein the controller calculates the carry over volume according to:

$$(43) V_{CO} = \frac{C_{2out} - C_{2in}}{C_{1out} - C_{2out}} \times V$$

wherein: V.sub.C0=volume of carry over (L), p.sub.C2.sub.out=measured density value of the second reagent on draining of the at least one retort (kg/m.sup.3), p.sub.C2.sub.in=measured density value of the second reagent on filling of the at least one retort (kg/m.sup.3), p.sub.C1.sub.out=measured density value of the first reagent on draining of the at least one retort (kg/m.sup.3), and V=initial volume of the second reagent in the second container (L).

(44) Viewed from another aspect of the present invention, there is provided a container for storing tissue samples for processing in a tissue processor, wherein the container is configured to be accommodated in a retort of the tissue processor and provide access to the stored tissue samples for processing with a process fluid in the retort, wherein the retort includes at least one sensor for detecting a level of the process fluid in the retort, and wherein the container is configured to minimise interference with the at least one sensor.

(45) In some embodiments, the container is a basket for storing the tissue samples. In some embodiments, the at least one sensor is an optical sensor, and the container includes at least one non-reflective surface for minimising interference with the optical sensor. Preferably, the at least one non-reflective surface includes an opaque material. The opaque material ideally minimises reflections that can occur during use of the optical sensor to detect the level of the process fluid.

(46) The container can be configured to releasably receive one or more clips having the at least one non-reflective surface. For example, the container can be a basket and the one or more clips can be releasably attached to openings in side portions of the basket. Additionally/alternatively, the container can include side portions having the at least one non-reflective surface.

(47) Viewed from another aspect of the present invention, there is provided a container for storing tissue samples for processing in a tissue processor, wherein the container is configured to be accommodated in a retort of the tissue processor and provide access to the stored tissue samples for processing with a process fluid in the retort, wherein the container includes a retractable handle to facilitate stacking of a plurality of the containers.

(48) In some embodiments, the container is a basket for storing the tissue samples. In some embodiments, the container further includes a receptacle having a central recess for receiving the handle in a retracted position. The handle is preferably integral with the receptacle. Integrating the handle into the receptacle can avoid any dependency on secure attachment of a lid, thereby reducing the risk of dropping the container during transport.

(49) The container can further include a lid having a slot through which the handle is extendable to an extended position. Ideally, the handle does not protrude or only partly protrudes through the slot of the lid in the retracted position. In some embodiments, the receptacle includes a base portion having a slot for receiving at least part of a handle of a corresponding container. The slot in the base portion can receive a partly protruded handle of a corresponding container for ease of stacking.

(50) Viewed from yet another aspect of the present invention, there is provided the tissue processor as described above and further including the container for storing tissue samples as described above.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) The invention will now be described in greater detail with reference to the accompanying drawings in which like features are represented by like numerals. It is to be understood that the

embodiments shown are examples only and are not to be taken as limiting the scope of the invention as defined in the claims appended hereto.

- (2) FIG. 1 is a simplified schematic block diagram of a prior art tissue processor showing the basic elements thereof;
- (3) FIG. 2 is a detailed schematic block diagram of the prior art tissue processor of FIG. 1 showing air and reagent lines;
- (4) FIG. 3 illustrates a perspective view of the prior art tissue processor of FIGS. 1 and 2;
- (5) FIG. 4 illustrates a perspective cut-away view of a retort of the prior art tissue processor shown in FIG. 3;
- (6) FIG. 5 illustrates a similar perspective cut-away view of the retort of FIG. 4 with cassette baskets in place;
- (7) FIG. 6 illustrates a front view of the retort shown in FIG. 4;
- (8) FIGS. 7a and 7b illustrate views of a reagent valve used in the prior art tissue processor of FIGS. 1 to 3;
- (9) FIG. 8 illustrates a rear view of the tissue processor shown in FIG. 3;
- (10) FIGS. 9a and 9b are simplified schematic block diagrams of a tissue processor according to embodiments of the invention, showing a reagent line connecting a container and a retort with a sensor arranged in the reagent line.
- (11) FIGS. 9c and 9d are simplified schematic block diagrams of a tissue processor according to embodiments of the invention, showing a reagent line connecting a container and a retort with a sensor arranged in a bypass line in FIG. 9c and in a dedicated line in FIG. 9d;
- (12) FIG. 10 is a simplified schematic block diagram of a tissue processor according to an embodiment of the invention, showing a plurality of containers connected by a reagent valve to two retorts with a sensor arranged in each reagent line;
- (13) FIG. 11 is a flow chart of a method of operating a tissue processor, that can be performed by a controller of a tissue processor, according to an embodiment of the invention;
- (14) FIG. 12 is a simplified flow chart of a workflow for reagent screening on retort filling incorporating the method of FIG. 11;
- (15) FIGS. 13a to 13c are more detailed flow charts of the workflow for reagent screening shown in FIG. 12;
- (16) FIGS. 14a and 14b are perspective views of a container for storing tissue samples with a retracted handle, showing top and bottom views, respectively, according to embodiments of the invention; and
- (17) FIGS. 15a and 15b are perspective views of the container for storing tissue samples of FIGS. 14a and 14b showing an extended handle, with and without a lid, respectively, according to embodiments of the invention.

DETAILED DESCRIPTION

(18) Embodiments of the invention are discussed herein by reference to the drawings which are not to scale and are intended merely to assist with explanation of the invention. The inventive method, tissue processor and computer program product have utility in the operation of a tissue processor for processing tissue samples for histological analysis. The inventive method, tissue processor and computer program product have particular utility in the operation of a tissue processor to determine whether a reagent is suitable for processing tissue samples in the tissue processor, either prior to or during operation of the tissue processor to perform a tissue processing protocol using the reagent. Furthermore, the inventive container for storing tissue samples has utility in minimising interference with fluid sensors of a tissue processor and/or is able to be readily stacked for ease of use.

(19) A prior art tissue processor 10 is described in International PCT Application No. PCT/AU02/01337, publication No. WO 03/029845, titled "Histological Tissue Specimen Treatment", published 10 Apr. 2003 and filed by Vision Biosystems Limited. The tissue processor

100 of preferred embodiments of the invention includes similar components to the prior art tissue processor **10** disclosed in WO 03/029845 and, therefore, it will be convenient to hereinafter describe the prior art tissue processor **10** disclosed in that application. It should be appreciated, however, that embodiments of the invention are not limited to having identical components or all of the components of the prior art tissue processor **10** disclosed in WO 03/029845 and as described herein. For example, embodiments of the invention may be directed to tissue processors or methods of operating tissue processors that differ from the prior art tissue processor **10** and that only comprise a single retort, as will be described herein.

(20) Description of Histological Tissue Processor

(21) In FIG. **1** an example of a general schematic of a prior art tissue processor **10** is shown, indicating major features such as retorts **12** and **14**, four infiltrating baths **16-22**, containers **26**, reagent valve **40**, manifold **38**, and air pump **44**. There are three main fluid sub-systems connecting the major elements, one sub-system being the air lines **30** from pump **44** to infiltrating baths **16-22** and retorts **12** and **14**. A second sub-system being infiltrating, lines **32** connects infiltrating, baths **16-22** to the retorts **12** and **14**. A third sub-system is reagent lines **34** connecting the containers **26** to the reagent valve **40** and the retorts **12** and **14**. Valving as shown in FIG. **2** ensures that fluid flows along the lines to the correct destination, and FIG. **2** shows a specific embodiment of fluid line connection and valve placement relative to the aforementioned elements. The electrical connections between the controller **25**, valves, pump **44** and other elements have been omitted from FIG. **2** for clarity, and are considered standard fittings. Also omitted from FIG. **2** are the numerous containers **26** (see for example, containers **27** and **29** of FIG. **2**) and their respective connections to the reagent valve **40**, to provide clarity. The omitted connections are identical to the connections shown in FIG. **2**.

(22) The schematic of FIG. **2** is embodied in the examples shown in FIGS. **3** and **8**. With reference to FIGS. **3** and **8**, the prior art tissue processor **10** includes control interface **24** that employs a graphical user interface to enable a user to operate the prior art tissue processor **10** by controller **25**. In the present embodiment, the controller **25** is located in cabinet **11**, however the interface **24** and controller **25** may be located separately, for example as part of a stand-alone personal computer. The controller **25** may include a personal computer processor such as a Celeron chip by Intel Corporation located on an ETX form factor PCB (not shown). The controller **25** may contain or store a number of predefined protocols (or steps) for processing tissue, the protocols being stored in a non-volatile memory such as a hard drive. Protocols may be programmable by the user to implement a number of steps for tissue processing, or they may be predefined. Typical protocol parameters include which reagents are to be applied to the samples, how long the reagents are to be applied, the temperature at which the reagents are applied, whether agitation is to take place, and whether ambient pressure in the retort is to be changed.

(23) In FIG. **3**, the retorts **12** and **14** can be seen in front of infiltrating baths **16-22**. The lids for the retorts **12** and **14** have been removed for clarity, as have the lids for the infiltrating baths **16-22**. An open lid **15** of retort **14** is shown, for example, in FIG. **8**. In the present embodiment, each retort **12** and **14** would have a lid (not shown), and each pair of infiltrating baths would also have a lid **17** and **19** (shown in FIG. **8**). The lids may seal with the retorts **12** and **14** and baths **16-22** when in a closed position. The containers **26** may be located under the retorts **12** and **14** so as to be accessible to a user. The controller interface **24** in FIGS. **3** and **8** employs a touch screen, however other input and display devices may be employed. Also located under the retorts **12** and **14** is a filter unit **52**, which typically includes a carbon filter to absorb vapours from air expelled from the processor **10**.

(24) In FIG. **8**, the various fluid lines such as reagent lines **34** from reagent containers **26** can be seen attached to a reagent valve **40**. The reagent valve **40** may have inputs from all containers **26**, and a single output to retorts **12** and **14**. A number of air lines can also be seen connecting manifold **38** to the reagent bottles **26**. The connections between various elements in FIG. **8** are shown schematically in FIG. **2**.

(25) One embodiment of retort **12** is shown in FIGS. **4-6**, including a receptacle **13** for receiving baskets **62** containing tissue samples. The receptacle **13** has a working capacity of 5.5 litres, however it may not necessarily be completely filled during each step of a protocol. When located in the processor **10**, the retort **12** may be rotated 10 degrees forward towards the front of the processor **10**. This allows easier access to the baskets **62**, as well as providing a drainage point, which is lowermost in the receptacle **13**, minimising residuals remaining in the retort **12** after draining.

(26) Sensors **52** are used to detect the level of fluid within the retort **12**, so that the controller **25** can ascertain when to turn the pump **44** on or off, or open and close the appropriate valves, as described below. In FIG. **6**, the placement of the three sensors **52** can be seen. The lowermost sensor **52** detects when the level of liquid, for example reagent or infiltrating fluid, is above a minimum level. The minimum level may represent a partially filled receptacle **13**, which is desirable when operating in economy mode. This is desirable when two or less baskets **62** are to be processed at once, whereupon only approximately 3.8 litres of fluid are required to cover the baskets **62** and samples contained therein. As the baskets may be various sizes, the level of the lowermost sensor **52** and therefore fill volume for economy mode can vary in different embodiments of the retort **12**. The middle sensor **52** detects when the level of liquid typically covers three baskets **62**, which is a normal full load. The top sensor **52** detects an overfill situation. In this particular embodiment, the sensors **52** are optically based relying on a change in refractive index when liquid comes into contact with a prism (not shown) of the sensor **52**. Each basket **62** may hold approximately 100 samples either in individual cassettes or placed directly into the basket **62**. Thus a full load for the embodiment of the retort **12** shown in FIGS. **4-6** is approximately 300 samples. The retorts **12** and **14** may be made larger or smaller depending on requirements.

(27) Also shown in FIG. **6** is a temperature sensor **53**, which is mounted directly to the retort **12**, and the temperature sensor **54**, which is mounted to a heating mat **55**. The retort **12** is heated to ensure correct reagent, or infiltrating fluid temperature. Placing a temperature sensor **53** directly on the retort **12** allows the fluid temperature within to be measured more accurately than by measuring the temperature of the heating mat **55**, especially where the fluid used may have low thermal conductivity. The temperature sensor **54** of the heating mat **55** may then be kept at a maximum while the temperature of the retort **12** is below the maximum processing temperature or more precisely, the desired operating temperature of the retort **12**, providing, more rapid heating than if only one temperature sensor **54** was employed.

(28) Port **56** shown in FIG. **6** allows connection of an air line **30** to the retort **12**. Retort manifold **57** also allows connection of infiltrating line **32** and reagent line **34** through a common entry point (not shown) at the bottom of the receptacle **13**. In FIG. **2**, retort manifold **57** incorporates valves **ret1-vrgt** and **ret1-vwax**, and is located at the front of the prior art tissue processor **10** so that the lean angle of 10 degrees of the retort **12** causes all fluid to drain towards the common entry point.

(29) In FIGS. **4** and **5**, the interior of the receptacle **13** is shown, including agitator **70**. Agitator **70** is magnetically coupled to an electric motor **58**, and may be driven at a number of speeds dictated by controller **25**. The baskets **62** each contain up to 100 tissue samples. The baskets **62** are supported clear of the agitator on posts **59** as shown in FIG. **4**.

(30) In the present example, retorts **12** and **14** are of identical construction, size and operation, however one retort may be larger or more voluminous than the other. Connections to and from retort **12** are duplicated on retort **14**.

(31) In FIG. **2**, pressure relief valves **48** are shown in fluid communication with air lines **30**, retorts **12** and **14**, and the infiltrating baths. Any overpressure in these lines will result in excess air being vented to waste through the manifold **38** and filter **47**. The pressure may be measured by pressure sensors **46** as shown in FIG. **2**.

(32) A list of valve functions is as follows with reference to FIG. **2**:

(33) Valves **ret1-vwst** and **ret2-vwst** connect retorts **12** and **14** to waste container **72**, when a waste cycle is required. Only one retort will be emptied at once and therefore these valves only open one

at a time. In another embodiment, the valves **ret1-vwst** and **ret2-vwst** may be omitted, and waste container **72** may be directly connected to the reagent valve **40**. To drain reagent to waste, the reagent valve **40** connects to the reagent line **34** connected to the waste container **72**, and the valve on the retort **12, 14** is opened to drain reagent directly to the waste container **72**.

(34) Valves **ret1-vrgt** and **ret2-vrgt** allow reagent flow into and out of their respective retorts during filling and draining of the retort. When draining a retort, these valves are open so that reagent may flow back down the reagent line **34** and back into the same reagent container **26** from whence it came. It can be seen that air valves **ret1-vfls** and **ret2-vfls** connect to the reagent line **34** between the **ret1-vrgt** and **ret2-vrgt** valves. These air valves are used to purge excess reagent from the reagent lines after filling one retort. This is desirable as using reduced pressure to draw fluid into a retort **12, 14** reduces fluid pressure along the whole reagent line **34**, and therefore when pressure is restored to the reagent line **34** some reagent may travel up the line of the retort **12, 14** that was not filled. Opening these valves, or opening the valves and pumping air down the air lines into the reagent lines clears excess reagent, preventing or reducing cross contamination.

(35) Valves **ret1-vwax** and **ret2-vwax** connect the retorts **12, 14** to the infiltrating baths **16-22**, via infiltrating lines **32** and valves **wb1-vwx** and **wb4-vwx**. Valves **ret1-vwax** opens when infiltrating fluid is to enter or drain from retort **12**, and **wb1-vwx** to **wb4-vwx** open one at a time depending on where the infiltrating fluid is being sourced. The infiltrating line **32** between the infiltrating baths **16-22** and retorts **12, 14** is heated to ensure that the infiltrating material does not harden in the lines.

(36) Valves **ret1-vair** and **ret2-vair** are used to control air from the air pump to the retorts. Air may be supplied either at a positive pressure to ambient, or withdrawn from the retorts **12, 14** so that pressure inside one or both retorts **12, 14** is below ambient pressure. These valves determine which retort **12, 14** is in fluid connection with the air pump **44**. Also **air-vprs** must be open to allow communication between the pump **44** and the valves, otherwise air is directed toward wax-air valve, connected to the infiltrating baths **16-22**.

(37) The reagent valve **40** is shown in FIGS. **7a** and **7b**, and includes connections between the reagent lines **34** from the reagent containers **26** on the input side, and outlet **35**, which is fluidly connected to the retorts **12** and **14**. The reagent valve **40** selects which reagent container **26** will be in fluid communication with the reagent line **34** connected to the retorts **12, 14**. In the present embodiment, the reagent lines **34** from the reagent containers **26** are arranged in a circle attached to the reagent valve housing **37**. In the present embodiment, the reagent valve **40** is in the form of a rotary valve, having two ceramic discs **39** and **41**, disc **39** having a single aperture **43a** aligned with aperture **43b** to form a conduit for reagent. The discs **39, 41** are mounted coaxially and adjacent each other and rotate together according to the position dictated by the controller **25**. Disc **45** has an aperture for each reagent line **34**, although in FIG. **7b** only one aperture is in the plane of the cross section. The rotating discs **39** and **41** rotate with respect to disc **45**, driven by stepper motor **49** such that the apertures align to provide a flow path from the outlet **35** (and therefore one retort) to a reagent container **26**. In order to assist with sealing between the discs **39, 41** and **45**, a plate **51** applies pressure to the discs. In this way, any reagent line **34** and therefore any reagent container **26** can be selected by the controller **25** to be in fluid communication with one of the retorts **12** or **14**. This type of valve has a small internal volume and therefore minimises cross contamination. Further, the reagents are drained back into the reagent containers **26** after each step and therefore little reagent remains to contaminate the subsequent reagent. It should be noted that the infiltrating fluid does not pass through the reagent valve **40**. This separation of fluid flow prevents the reagent valve **40** from clogging and reduces the amount of cleaning of the valve **40**.

(38) In use, the tissue samples to be processed are typically placed into cassettes (not shown) for placement into a basket **62**. Generally, tissue samples expected to have similar processing times and to be exposed to the same processing protocol are placed together in the same basket **62**. The basket **62** containing the tissue samples is then placed into one of the retorts **12** or **14**, and the lid

closed, forming a sealed enclosure. An operator may then enter data into the control interface **24** to instruct the controller **25** of the protocol to be followed. The protocol may be programmed step by step, for example indicating the time, temperature, pressure, agitation and reagent for each step, or a pre-programmed protocol encompassing all steps may be selected.

(39) The first step in a protocol, once the lid **17** of the retort **12** is secured, may be to fill the chosen retort (in this example retort **12** is chosen) with a fixing solution. A typical fixing solution is formalin, which may be held in one or more reagent containers **26**. In order to fill the retort **12** with fixing solution, the pump **44** is switched on and valves open the air lines from the retort **12** to the inlet side of the pump, pumping air from the retort **12** chamber. The reagent valve **40** is set to a position that fluidly connects the reagent line **34** of the retort **12** to the specified reagent container **26** for formalin. Other valves are opened along the reagent lines **34** from the retort **12** to the reagent valve **40**. The reduced pressure in the retort **12** is sufficient to draw fluid out of the reagent container **26**, through the reagent valve **40** into the reagent lines **34** and into the retort **12**. The retort is heated by heater pads to a predetermined temperature selected and controlled by the controller **25**. Sensors **53** and **54** may be used to control the temperature of the retort **12**, and therefore the tissue and any reagent contained therein. One or more sensors **52** in the retort as shown in FIGS. **4** and **6**, may be used to detect the reagent level. When the reagent level in the retort **12** is sufficient, typically to cover the baskets **62** as seen in FIG. **5**, the pump may be turned off or otherwise disengaged from the retort **12**, for example by closing valve *ret1-vrgt* shown in FIG. **2**.

(40) After a length of time determined by the controller **25** (typically as programmed by the user), the reagent may be removed from the retort **12**. This is accomplished by opening valve *ret1-vair* in the air line **30** and opening valve *ret1-vrgt* in the reagent line **34**. Reagent will then drain from the retort **12** back into the reagent container **26** from which it came, or back into a different reagent container **26**, or to waste, according to the position of the reagent valve **40** determined by the programmed protocol. To assist in draining, the retort **12** may be positively pressurised by air from the pump **44**, supplied along the air lines **30**. In the present embodiment the reagent drains back to its originating container **26**. If the reagent is contaminated, or has been used for the predetermined number of samples or washes, then it is drained to waste using a separate waste cycle.

(41) During the retort filling with reagent from a reagent container **26**, the air pumped from the retort **12** flows down an air line **30**, some of which flows back through manifold **38** and into the reagent container **26**, recirculating some of the air from the retort **12**. Excess air pumped from the retort **12** will flow out through a condensing mechanism such as a condensing coil **51**, and/or a carbon filter **47**, both of which are designed to remove volatile organic or other compounds from the air before it reaches the atmosphere. The processor **10** may have an outlet connection that allows the filtered air to be vented or further filtered by apparatus external to the processor **10**.

(42) The second step in tissue processing may be the dehydration step. The methodology employed to draw dehydrating reagent into the retort **12** may be the same as described above, as the dehydrating reagent will be stored in a reagent container **26**. The dehydrated fluid may contain a fluid such as an alcohol, for example ethanol. The dehydrating fluid may also contain some water, either intentionally added, or, where the dehydrating fluid has been re-used, water removed from the previous samples. There may be a number of steps of the protocol where dehydrating fluid is applied to the sample in the retort **12**, **14**, and at each step a different dehydrating fluid may be used. For example, a fluid may be used that has less water than a previous fluid, to draw out more moisture from the sample at each wash. The dehydrating fluid may additionally or alternatively contain isopropanol. Later washes with isopropanol provide properties that may be advantageous, as will be described below. Further additives commonly used in the tissue processor dehydration fluids may be used, as the prior art tissue processor **10** is intended to be compatible with known dehydration fluids.

(43) On a final wash with dehydrating fluid, the fluid is drained completely from the retort **12**, **14**. This is accomplished by opening valves from the air pump **44** as well as pumping air into the

reagent lines **34** to clear the reagent. A vapour flush may be employed where the pump **44** flushes fresh air into the retort **12, 14** to clear any vapour from the reagent, such as a dehydrating fluid. Significant vapour may be present as the dehydrating fluid may have high partial pressure at the retort operating temperature. After the dehydrating step, a drying step may be employed, where the retort **12, 14** is heated by the heating mats **55**, while air is pumped through the chamber by the air lines **30**. This removes excess dehydrating fluid. The drying step may take several minutes or more, and the retort **12, 14** may be heated to 85 degrees Celsius, depending on the dehydrating fluid chosen and the sensitivity of the tissue samples to heat.

(44) Another step in tissue processing is infiltrating of the samples. This is typically accomplished by an infiltrating material such as a paraffin wax. The wax is held in the infiltrating baths **16-22**, which are heated to the desired temperature above the waxes melting temperature, which is typically 54 degrees Celsius. Wax pellets are typically added to an infiltrating bath **16-22**, which heats the pellets until they melt and achieve a suitable temperature. Alternatively, pre-molten wax may be added directly to the baths **16-22**. The wax is held at the elevated temperature, typically 65 degrees Celsius, until required. The prior art tissue processor **10** shows four infiltrating baths **16-22**, however there may be more or less depending on retort and infiltrating bath volume. The infiltrating lines **32** run from the infiltrating baths **16-22** to both retorts **12** and **14**, and include valves such as *ret1-vwax* and *ret2-vwax*, that allow one, some, or all baths **16-22** to be fluidly connected to one of the retorts **12, 14**. The arrangement of the baths **16-22**, valves, and infiltrating material lines enables samples in one retort **12, 14** to be washed with up to four different infiltrating materials. Further, the infiltrating material may be heated in one or more baths **16-22** while the processor **10** is in operation and drawing infiltrating material from the remainder of the baths **16-22**.

(45) During the infiltrating step, the wax is drawn into the retort **12** by opening the valve between the retort **12** and appropriate infiltrating bath **16-22**, such as *ret1-vfls*, then reducing the pressure in the retort **12** using the pump **44** and opening valves *air-vprs* and *ret1-vair*. The reduced pressure in the retort **12** draws the wax into the retort **12**. Typically, the pressure may be -20 to -80 kpa gauge, however a wide variety of pressures may be used, and these are user programmable via the controller **25**. The wax may be heated to a temperature above or approximately the same as the boiling temperature of the dehydrating fluid used in the last or last few washes. If an isopropanol is used, the boiling temperature will be approximately 82 degrees Celsius at atmospheric pressure. Ethanol typically boils at 78 degrees Celsius. After the retort **12** has been draining of dehydrating fluid, some fluid remains on or absorbed by the tissue samples. The tissue samples may then be subjected to a drying stage as described above to remove further dehydrating fluid, and the retort **12** flushed with clean air. Wax is then drawn into the retort **12**. Upon contact with the heated wax, the remaining dehydrating fluid is evaporated or boiled off the tissue samples, and the wax replaces the dehydrating fluid, thus infiltrating the samples. The pump **44** may continue to draw off air or vapour from the retort **12** to reduce the pressure in the retort **12**, which will reduce the evaporation temperature of the dehydration fluid. As an example, the pressure in the retort **12** may be reduced by 50 kpa gauge, resulting in a boiling temperature of approximately 52 degrees Celsius for the isopropanol. Reducing temperatures of the wax contacting the tissue samples may provide an advantage, for example where certain types of tissues do not perform well when exposed to high temperatures. Typically the paraffin wax used (Paraplast+from Oxford Laboratories) melt at about 54 degrees Celsius. Other infiltrating materials may be used including resins used in histological processes for infiltrating tissue samples. In the present example, the alcohol used at the last stage, isopropanol, is not substantially miscible with paraffin wax. This means that infiltrating fluid is unlikely to penetrate the tissue sample if the previous fluid in the retort was immiscible with the infiltrating fluid. Boiling the volatile dehydrating material off therefore enables the omission of step whereby an intermediary fluid such as xylene, which is miscible in alcohol and paraffin wax, is required. Xylene has undesirable properties in a laboratory. However, xylene will also evaporate

when exposed to temperature around 80 degrees, especially when applying a vacuum as described herein has lowered the pressure inside the retort **12**. Thus the present example enables the tissue samples to be used without a xylene wash cycle, but also may be used with fluids such as xylene. There are advantages in not using xylene, including that xylene is miscible in wax, and therefore can be absorbed into the wax as a contaminant. However, in some instances it is desirable to use xylene, for example when the tissue requires clearing and the dehydrating fluid such as isopropanol is deemed to be insufficient. Further, xylene may be used after a processing cycle to clean excess wax from the retort **12**, and therefore xylene may be present in the prior art tissue processor **10**.

(46) It is possible to clean the infiltrating fluid of some of the volatile contaminants, such as dehydrating fluid, clearing fluids such as xylene, by holding the wax in the bath **16-22** and reducing the pressure in the bath **16-22**. This clean cycle is done with the bath lid closed, whereupon the reduced pressure and holding the infiltrating material at an elevated temperature such as between 60 degrees and 100 degrees Celsius. The temperature may be held between 65 degrees and 85 degrees Celsius. By volatile material, it is meant that at the temperatures mentioned herein, and/or at reduced pressure, the material will boil or evaporate.

(47) The vapour pressure of the dehydration fluid within the air line **30** in the container **26** may also be reduced, for example, by venting air in the retort **12**, either while maintaining a low pressure or cycling through pressure ranges. The infiltrating fluid may be held in the bath **16-22** at an elevated temperature for several hours to clean away contaminants.

(48) The use of two retorts **12, 14** allows two sets of baskets **62** to be processed either simultaneously or with an overlap. Thus one retort **12** can be loaded and a protocol begun while the other retort **14** is mid-way through the same or a different protocol. This provides additional flexibility in the prior art tissue processor **10**.

(49) The tissue samples referred to may be human or animal tissue samples, or samples from plant material.

(50) An example protocol for tissue samples, such as a **3mm** punch human biopsy sample, will now be described:

(51) TABLE-US-00001

Time	Temp	Retort	Step	Reagent	(min)	(c.)	Pressure	Agitation
1	Formalin	5						
60	Ambient	Yes	2	50/50 Ethanol water	25	60	Ambient	Yes
3	80/20 Ethanol water	35	60	Ambient	Yes	4	Isopropanol	30
60	Ambient	Yes	5	Paraffin Wax	40	60	Vacuum	Yes
6	Paraffin Wax	5	60	Vacuum	Yes	Total processing time	140	

(52) Another protocol is as follows:

(53) TABLE-US-00002

Time	Temp	Retort	Step	Reagent	(min)	(c.)	Pressure	Agitation
1	Formalin	5						
60	40 Ambient	Yes	2	80% Ethanol	45	40	Ambient	Yes
3	90% Ethanol	45	40	Ambient	Yes	4	100% Ethanol	60
40	Ambient	Yes	5	100% Ethanol	60	40	Ambient	Yes
6	100% Ethanol	60	40	Ambient	Yes	7	100% Ethanol	60
40	Ambient	Yes	8	Isopar or d-limonene	60	40	Ambient	Yes
9	Isopar or d-limonene	75	40	Ambient	Yes	10	Isopar or d-limonene	75
40	Ambient	Yes	11	Paraplast	70	60	Vacuum	Yes
12	Paraplast	60	60	Vacuum	Yes	13	Paraplast	60
60	Vacuum	Yes	Total processing time	790				

(54) From the above it can be seen that xylene is not required in this protocol, and that the protocol has few steps, saving time.

(55) A contamination detector **68** may be placed in the reagent line **34** to detect the presence of contaminants in the reagents. To drain the retort **12**, the pump may increase pressure in the retort **12** by pumping air along the same air lines **34** as used to draw reagent into the retort **12**. Waste reagent may be drained into a reagent container **26**, or be expelled to waste port **72**. Infiltrating fluid may also be drained from the retort **12** to waste **70** by this method, and similarly infiltrating fluid may be drained from the baths **16-22** using positive pressure.

(56) In the above examples the dehydrating fluid is immiscible with the infiltrating material. However, the above process offers advantages even if a clearing cycle is used, where the clearing fluid is miscible with the dehydrating fluid and the infiltrating material. Further, additives may be

used to increase the clearing properties of the dehydrating material, as well as increasing the miscibility of the fluids in the dehydrating and infiltrating steps.

(57) While raising the temperature of the infiltrating fluid above the boiling temperature of the dehydrating reagent (or clearing reagent) will result in faster removal of the reagent, reagent will still be removed at or around the boiling temperature provided the partial pressure in the retort **12** is lower than the partial pressure of the reagent at the given temperature. This can be accomplished by reducing the pressure in the retort **12**, then allowing some fresh air into the retort. Bringing fresh air into the retort **12** while removing air laden with vapour will reduce the partial pressure of reagent in the air in the retort **12** thus promoting more evaporation of the reagent. If the reagent is miscible with the infiltrating fluid it may not be necessary to remove all the reagent to obtain infiltration. However, if the samples can withstand the temperature it is preferable to raise the temperature of the infiltrating fluid within the retort **12** to a temperature above the boiling temperature of the reagent for the given pressure. A temperature about the boiling temperature of a reagent for a given pressure may be typically a few degrees, such as 5 degrees Celsius, of the boiling temperature.

(58) Other dehydrating fluids are contemplated as being able to be used with the prior art tissue processor **10**, such as: methanol, butanol, ethylene glycol, propylene glycol, industrial methylated spirits, denatured alcohol (including alcohol denatured with kerosene, benzene or brucine), reagent grade alcohols, acetone and combinations thereof, however this list is merely representative and is not intended to encompass an exhaustive list of reagents useful in the prior art tissue processor **10** described herein.

(59) Clearing reagents such as di-pentene, D-limonene, 1,1,1, trichloroethane, toluene, and dioxane are also contemplated, and again this list is meant to be indicative of the types of reagents that may be used, rather than an exhaustive list. The reagents above, and other reagents suitable for histological processes such as dehydrating, clearing or a combination thereof, may be used in the present apparatus with the step of evaporating the reagent from the sample using heating of the infiltrating fluid, provided the reagents evaporate without leaving a residue. While reagents such as butanol have a boiling point of approximately 118 degrees Celsius at atmospheric pressure, the boiling point drops dramatically with a reduction in ambient pressure. While it is believed preferable to not heat most tissues above 85 degrees Celsius, some types of well fixed tissue will survive this temperature without damage, and therefore higher temperatures may be used, increasing the range of reagents useful in the abovementioned processes. Accordingly, the upper temperature which may be used is dependent on the tissue, and therefore in well fixed tissue, temperatures may exceed 100 degrees Celsius. Reducing pressure in the retort **12** will assist in reducing temperatures in the retort **12** by reducing the boiling point of reagents.

(60) Infiltrating materials such as resins and other fluids used in histological tissue processing are also contemplated in the above examples, and prior art tissue processor **10** is not intended to be limited to the infiltrating materials mentioned herein. It is also contemplated that infiltrating material may be mixture of substances, such as mineral oils and paraffin wax.

(61) Improvements in Reagent Management

(62) The prior art tissue processor **10** disclosed in WO 03/029845 and as described herein can be operated by a reagent management system that controls reagent use for optimal tissue processing results. An exemplary reagent management system and method of managing resources of a histological tissue processor, such as the prior art tissue processor **10**, is described in International PCT Application No. PCT/AU2004/001337, publication No. WO 2005/031312, titled "System and Method for Histological Tissue Specimen Processing", published on 7 Apr. 2005 and filed by Vision Biosystems Limited.

(63) The reagent management system can include a concentration management module that preferably uses a calculation method to determine reagent concentration at each station/bottle of a tissue processor, such as prior art tissue processor **10**. The calculation method involves using an initial station concentration, which may be set to the reagent's default value, and tracking station

use to calculate an estimate of the current concentration of the reagent. Tracking station use can include calculating an estimate of reagent carry over from the retort walls, baskets and biopsy pads used by the tissue processor. The reagent management system then operates the tissue processor based on the calculated reagent station concentration level.

(64) The present invention provides improvements in reagent management by providing a tissue processor **100** that includes at least one sensor **74, 76** for measuring a measured purity level of a reagent. Ideally, the measured purity level is a concentration value of the reagent derived from a measured parameter value. The present invention further provides a method of operating the tissue processor **100**, which may be computer-implemented by a computer program product, and a controller **25** of the tissue processor **100** that is configured to perform the method.

(65) In contrast to the reagent management system of WO 2005/031312 and as described above, the inventive tissue processor **100** with controller **25** and method of operating the tissue processor **100** can measure the actual reagent concentration, by means of the at least one sensor **74, 76**, before or during operation of the tissue processor **100** to perform a tissue processing, protocol.

Accordingly, the reagent management system can control reagent use on the basis of the measured reagent concentration values instead of calculated reagent concentration values based on an estimate of reagent carry over. The present invention therefore provides greater accuracy and reliability in measuring reagent concentration due to the at least one sensor **74, 76**. Furthermore, the present invention enables the reagent management system to more readily control tissue processor workflows as the reagent quality can be validated before or during operation of the tissue processor **100**.

(66) For simplicity, the same reference numerals have been used for features of the tissue processor **100** according to embodiments of the invention that correspond to the same features of the prior art tissue processor **10**. It is intended that the above description of the prior art tissue processor **10** and disclosure of WO 03/029845 is relevant to the features of the tissue processor **100** with the same reference numerals. The tissue processor **100** can, in some embodiments, include one or more features of the prior art tissue processor **10**, although not explicitly mentioned in the following description of preferred embodiments of the invention. A person skilled in the art would appreciate how the features of the prior art tissue processor **10** could be implemented with respect to the tissue processor **100** according to embodiments of the invention. It should be appreciated, however, that embodiments of the invention are not limited to having identical components or all of the components of the prior art tissue processor **10** disclosed in WO 03/029845 and as described herein. For example, embodiments of the invention may be directed to tissue processors or methods of operating tissue processors that differ from the prior art tissue processor **10** and that only comprise a single retort, as will be described herein.

(67) The tissue processor **100** of the present invention includes at least one retort **12** for receiving tissue samples, at least one container **26** for storing a reagent, and at least one sensor **74** arranged for fluid communication with one or both of the at least one container **26** and the at least one retort **12** for measuring a measured purity level of a reagent.

(68) Embodiments of the tissue processor **100** are illustrated in simplified schematic block diagrams as shown in FIGS. **9a-d** and **10**. The electrical connections between the sensors **74, 76**, manifold **38**, reagent valve **40**, air pump **44**, controller **25**, and other elements have been omitted from the figures for clarity, and are considered as standard fittings known to a person skilled in the art, and understood with reference to the prior art tissue processor **10** as shown in FIGS. **1** to **8**.

(69) Referring to FIGS. **9a** and **9b**, the tissue processor **100** can include a reagent line **34** connecting the container **26** and the retort **12**. The sensor **74** can be arranged in the reagent line **34**, positioned between the container **26** and retort **12**. A valve mechanism **50** can be optionally included in the reagent line **34** to control flow of a reagent between the container **26** and retort **12**, depending on the direction of flow during a tissue processing protocol. For example, on filling of the retort **12**, reagent will be conducted from the container **26** to the retort **12** in the reagent line **34**.

Conversely, on draining of the retort **12**, the direction of flow will be reversed as controlled by the valve mechanism **50**. In some embodiments, the valve mechanism **50** may include the reagent valve **40** of the prior art tissue processor **10**. The sensor **74** can be positioned in the reagent line **34** between the valve mechanism **50** and retort **12** or between the container **26** and valve mechanism **50**, as shown respectively in FIGS. **9a** and **9b**. Preferably, the sensor **74** is positioned between the valve mechanism **50** and retort **12** as shown in FIG. **9a**.

(70) Alternatively, in the embodiment of FIG. **9c** the sensor **74** is arranged in a bypass line **42** that receives a portion of the reagent when the reagent is conducted in the reagent line **34**. The bypass line **42** is positioned between the optional valve mechanism **50** and the retort **12** as shown in FIG. **9c**. However, the bypass line **42** could be positioned between the container **26** and the optional valve mechanism **50**. Further, in other embodiments the bypass line **42** could connect to the reagent line **34** on either side of the valve mechanism **50**. Entry of reagent to the bypass line **42** from the reagent line **34** could also be valved to selectively control the amount of reagent that is conducted to the sensor **74** (not shown).

(71) FIG. **9d** illustrates another alternative embodiment of the tissue processor **100** in which the sensor **74** is arranged in a dedicated line **36** that is connected to the container **26** and/or retort **12**. The dedicated line **36** is shown in broken lines to illustrate that the dedicated line **36** could be fluidly connected to one or both of the container **26** and retort **12**. Reagent can be conducted from one of the container **26** or retort **12** in the dedicated line **36** to the sensor **74** for measuring the measured purity level of the reagent. In this regard, an air line **30** may be connected from the air pump **44** to the sensor **74** in order to pump reagent in the dedicated line **36** (not shown).

(72) FIGS. **9a-d** illustrates embodiments of the tissue processor **100** that include a single container **26**, retort **12** and sensor **74**. However, the tissue processor **100** may include a plurality of containers **26** for storing different reagents and/or the same reagent at different concentrations, as shown in FIG. **10**.

(73) A preferred embodiment of the tissue processor **100** is illustrated in FIG. **10**. The tissue processor **100** can include a plurality of containers **26** (six shown, although various numbers of containers can be provided), two retorts **12** and **14** and two sensors **74** and **76**. The arrangement is similar to that shown and described with reference to FIG. **9a** in which each sensor **74** and **76** is positioned in the reagent line **34** between the reagent valve **40** and retorts **12** and **14**. However, in other embodiments a single sensor **74** could be positioned between the reagent valve **40** and connecting to both of the retorts **12** and **14** (not shown).

(74) As shown in FIG. **10**, the tissue processor **100** can include the reagent valve **40** for selectively connecting each container **26** to the retorts **12** and **14** for conducting reagent therebetween. Further, the tissue processor **100** can include four infiltrating baths **16-22** connected to the retorts **12** and **14** by an infiltrating line **32**. The infiltrating baths **16-22** can include infiltrating material such as paraffin wax for use by the tissue processor **100** in performing a tissue processing protocol for infiltrating of tissue samples. The tissue processor **100** can also include the air pump **44** with air lines **30** and manifold **38**, which together with a controller **25** enable transport of various fluids, such as process fluids or waste, in the tissue processor **100**.

(75) The sensors **74** and **76** preferably are fluid sensors configured to measure the density value of the reagent when conducted thereto from the container(s) **26** or retorts **12** and **14** to the sensors **74** and **76**. The sensors **74** and **76** can be densitometers, and preferably, oscillating pipe density meters, which include an oscillating element and measure the damping effect of the reagent flow. Alternatively, the sensors **74** and **76** can be oscillating u-tube or “tuning fork” density meters, or other densitometers as known to a person skilled in the art. Where the sensors **74** and **76** include an oscillating tube, the manifold **38** of the tissue processor **100** shown in FIG. **10** is preferably inclined at an angle. The inclination is such that any air bubbles from the oscillating tube of the sensor **74**, **76** can be removed, thereby allowing density measurements to be taken during filling of the retorts **12** and **14**, which occur when conducting reagent from the container(s) **26** to the retorts **12** and **14**.

(76) Ideally, the sensors **74** and **76** provide minimal fluidic restriction on the fluid/reagent flow in the tissue processor **100**. For example, the sensors **74** and **76** may have large internal tube diameters that minimise fluidic restriction. This is particularly important when the sensors **74** and **76** are positioned in the reagent line **34** (see FIGS. **9a-b** and **10**), for which such restriction may impact on fill and drain times between the container(s) **26** and retorts **12** and **14**.

(77) Referring now to FIG. **11**, the present invention provides a method of operating the tissue processor **100** for processing tissue samples. FIG. **11** is a flow chart of the steps **80-86** of the method of the invention. The method includes at step **80**, conducting reagent from the at least one container **26** or the at least one retort **12** to the at least one sensor **74**. At step **82**, the method further includes automatically measuring, by means of the at least one sensor **74**, the measured purity level of the reagent. At step **84**, the method further includes checking whether the measured purity level meets a predetermined purity level of the reagent associated with the at least one container **26**. The method further includes at step **86** automatically determining, based on a result of checking, whether the reagent is suitable for processing tissue samples in the tissue processor **100**.

(78) The predetermined purity level of the reagent can be associated with the at least one container **26** by means of data or information of the reagent that is intended to be stored in the container **26**. For example, the container **26** may include an identifier for a specific reagent that is positioned on the physical container **26**, such as through use of a label. The identifier may be machine-readable and include a Radio Frequency Identification Device (RFID). The identifier can include information such as the type and/or concentration of the reagent that is to be stored in the container **26**.

(79) In some embodiments, the method further includes the step of providing the predetermined purity level of the reagent based on reagent data for the at least one container **26**. The reagent data for the at least one container **26** is preferably provided by a user or operator of the tissue processor **100**. The tissue processor **100** can further include an input device such as control interface **24**, which can include the control interface **24** shown in FIGS. **3** and **8** of the prior art tissue processor **10**. The control interface **24** can employ a graphical user interface, and may include a touchscreen display, keyboard and/or mouse, operable by a user to provide the reagent data. The control interface **24** can be connected to a controller **25** of the tissue processor **100**, which is configured to receive the reagent data from the control interface **24**.

(80) Additionally/alternatively, the tissue processor **100** can include a controller **25**, which can include the controller **25** shown in FIG. **8** of the prior art tissue processor **10**. The controller **25** can be configured to receive the reagent data from a server or computing system, such as through a wireless or hard-wired connection. The controller **25** may be located on the tissue processor **100** in a cabinet **11** as shown in FIG. **3** of the prior art tissue processor **10**, or may be part of a stand-alone computer that communicates with the tissue processor **100**. The controller **25** may include a personal computer processor such as a Celeron chip by Intel Corporation located on an ETX form factor PCB (not shown). The controller **25** may contain or store a number of predefined protocols (or steps) for processing tissue, the protocols being stored in a non-volatile memory such as a hard drive. Protocols may be programmable by the user to implement a number of steps for tissue processing, or they may be predefined. Typical protocol parameters include which reagents are to be applied to the samples, how long the reagents are to be applied, the temperature at which the reagents are applied, whether agitation is to take place, and whether ambient pressure in the retort **12**, **14** is to be changed.

(81) The reagent data preferably includes at least a concentration value of the reagent for the at least one container **26**. The user may provide the concentration value, using the control interface **24** or controller **25**, as a percentage dilution of the reagent in water, such as 70%, 80% or 100%, or provide a concentration in Molar (M), g/L, mg/mL, to name a few. The reagent data can also include one or more of a reagent type, a reagent name and a container number for the tissue processor **100**. For example, the reagent type can include a dehydrating fluid, such as ethanol,

methanol, isopropanol, butanol, ethylene glycol, and various alcohols, a clearing reagent, such as xylene, di-pentene, D-limonene, trichloroethane, toluene and dioxane, and an infiltrating material, such as paraffin wax, to name a few.

(82) In preferred embodiments of the invention, the predetermined purity level of the reagent is a concentration level determined based on the concentration value from the reagent data. The concentration level can include one of a threshold value or a tolerance range of values. The threshold value can be the concentration value of the reagent included in the reagent data from the user. Where the concentration level is a tolerance range of values, the range can be determined based on the concentration value included in the reagent data. The method may include determining the tolerance range depending on the reagent type, such as dehydrating fluid, clearing reagent or infiltrating material, and in some embodiments, through a calculation based on the pure reagent concentration or using, a look-up table for the reagent. For example, a smaller tolerance range may be required for reagents in which a variation in concentration level will detrimentally affect the quality of the processed tissue samples.

(83) In some embodiments, the method further includes repeating the measuring step **82** one or more times, preferably three times, and calculating an average of the measured values of a parameter that represents the measured purity level of the reagent. In this case, the calculated average represents the measured purity level of the reagent. The measuring step **82** may include measuring density values of the reagent using the at least one sensor **74**, **76**, which may be a fluid sensor or densitometer, and thus the calculated average can include an average density value for the reagent. The method may further include a step of deriving from the measured density value or the average of the measured density values, a concentration value of the reagent. The step of deriving the concentration value may include performing a calculation method based on using a look-up table for the pure reagent. The measured purity level of the reagent determined at measuring step **82** preferably includes the derived concentration value.

(84) Accordingly, the checking step **84** of FIG. **11** is preferably performed on the basis of a comparison of concentration values. Ideally, the measured purity level is the concentration value derived from the measured density value or average of measured density values, and the predetermined purity level is the concentration level, being the threshold value or tolerance range of values determined based on the concentration value from the reagent data. The checking step **84** can include checking whether the measured purity level is (i) greater than the threshold value of the predetermined concentration level, or (ii) within the tolerance range of values of the predetermined concentration level.

(85) In alternative embodiments, the predetermined purity level can be a density level determined based on the concentration value from the reagent data. The density level can be a threshold value, where the threshold value can be a density value derived from the concentration value from the reagent data, such as through a calculation based on the pure reagent concentration or using a look-up table for the reagent. Where the density level is a tolerance range of values, the range can be determined based on the derived density value. Furthermore, the measured purity level of the reagent can be, the measured density value or average of measured density values. Thus, in alternative embodiments, the checking step **84** of FIG. **11** is performed on the basis of a comparison of density values.

(86) In some embodiments, the determining step **86** of FIG. **11** includes determining that the reagent is suitable for processing tissue samples when the measured purity level is greater than the threshold value or within the tolerance range of values. Step **86** further includes determining that the reagent is unsuitable for processing tissue samples when the measured purity level is less than the threshold value or falls outside the tolerance range of values. When the reagent is determined to be unsuitable for processing tissue samples, the method can further include the step of flagging the at least one container **26** for non-use by the tissue processor **100**. The method can also further include the step of generating, at the tissue processor **100**, a notification signal for a user to check

the reagent in the flagged container **26**. The notification signal can be provided to the user by the input device, such as a control interface **24** having a user display. The notification signal can include a message and/or alarm displayed on the control interface **24** or user display.

(87) The method can be performed prior to operating the tissue processor **100** to perform a tissue processing protocol using the reagent. This method requires a dedicated tissue processor workflow to check the measured purity level of the reagent prior to use in a tissue processing protocol by the tissue processor **100**. Referring to FIG. **9d**, the tissue processor **100** includes a dedicated line **36** connecting the container **26** or the retort **12** to the sensor **74**. The dedicated line **36** is separate from the reagent line **34** that connects the container **26** and retort **12**. In some embodiments, the method includes at step **80**, conducting reagent in the dedicated line **36** from the container **26** or the retort **12** to the sensor **74**.

(88) The dedicated tissue processor workflow requires a specific action to fill and drain reagent to the dedicated line **36** to measure the purity level or concentration of the reagent. For example, reagent can be stored in the container **26** and conducted to the sensor **74** in order to screen the reagent and check its purity level or concentration prior to use by the tissue processor **100**. If the method determines at step **86** that the reagent is unsuitable for use, the container **26** associated with the reagent, i.e. the container **26** for storing, the reagent, can be flagged for non-use. The “flagging” may be software-implemented in a reagent management system that locks-out the container **26** for use in tissue processing protocols. The “flagging” may result in selection by the reagent management system of an alternative container **26** for use in a tissue processing protocol. Furthermore, the method can include generating a notification signal for a user to check the reagent in the flagged container **26**. The notification signal can be a message and/or alarm displayed on the control interface **24** or user display.

(89) In another example, reagent can be stored in the retort **12** and conducted to the sensor **74** in order to screen the reagent and check its purity level or concentration prior to conducting the reagent to its associated container **26**. If the method determines at step **86** that the reagent is unsuitable for use, the container **26** associated with the reagent, e.g. in this case the container **26** storing the reagent, can be flagged for non-use as above, and further, the reagent can be conducted to a waste line of the tissue processor **100** for removal therefrom so as to not contaminate or dilute any reagent currently in the associated container **26**.

(90) In other embodiments, the method is preferably performed when operating the tissue processor **100** to perform a tissue processing protocol using the reagent. This method can be implemented in two ways, (i) adapting a tissue processor workflow for a tissue processing protocol to check the reagent during use (e.g. filling/draining of the retort **12**, **14**) by the tissue processor **100**, and (ii) a monitoring tissue processor workflow for calculating contamination of the reagent from successive uses in tissue processing protocols. Advantageously, the adapted workflow and monitoring workflow minimises inefficiency in operation of the tissue processor **100** as it avoids additional checks and retort cleans that are required to perform the dedicated workflow described above.

(91) Referring to FIGS. **9a-c** and **10**, the tissue processor **100** can include a reagent line **34** connecting the at least one container **26** and the at least one retort **12**, **14**. The at least one sensor **74**, **76** is arranged in fluid communication with the reagent line **34**. The sensor **74**, **76** can be positioned in the reagent line **34** as shown in FIGS. **9a-b** and **10**, or alternatively, positioned in a bypass line **42** that receives a portion of the reagent when the reagent is conducted in the reagent line **34** as shown in FIG. **9c**. With these embodiments of the tissue processor **100**, the method can be performed on filling of the retort **12**, **14** with reagent at the start of a tissue processing protocol and/or on draining of the retort **12**, **14** to remove reagent at the end of a tissue processing protocol, since the reagent from reagent line **34** conducted between the container **26** and retorts **12** and **14**, will pass through the sensor **74**, **76** positioned in the reagent line **34** or bypass line **42**.

(92) For the adapted tissue processor workflow, the method further includes the step of operating the tissue processor **100** to stop filling or draining of the at least one retort **12**, **14** to perform at least

method steps **82-86** of FIG. **11**. On filling of the retort **12, 14**, the method can include operating the tissue processor **100** to stop filling prior to reagent contacting tissue samples stored in the at least one retort **12, 14**. On draining of the retort **12, 14**, the method can include operating the tissue processor **100** to stop filling prior to reagent being delivered to the at least one container **26** associated with the reagent. The stopping step advantageously enables the reagent purity level or concentration to be checked prior to potentially contaminating and/or destroying tissue samples on filling and then processing in the retort **12, 14**, and prior to potentially contaminating and/or diluting any reagent in the associated container **26** on draining of the reagent from the retort **12, 14**. This desirably enables the reagent quality to be verified before or during operation of the tissue processor to perform a tissue processing protocol using the reagent, which can thereby avoid user error and potential suboptimal tissue processing of the tissue samples.

(93) When the reagent is determined to be suitable for processing tissue samples at step **86** of FIG. **11**, the method can further include the step of operating the tissue processor **100** to continue filling or draining of the retort **12, 14** to complete the tissue processing protocol. Otherwise, when the reagent is determined to be unsuitable for processing tissue samples, the method can further include the step of operating the tissue processor **100** to abandon the tissue processing protocol.

(94) The adapted tissue processor workflow on filling of the retort **12, 14** is illustrated in a preferred embodiment of the invention as shown in the flow charts of FIGS. **12** and **13a-c**. FIG. **12** is a simplified flow chart of a workflow for reagent screening (i.e., checking reagent purity level, particularly concentration) on retort filling that incorporates the method of FIG. **11** and embodiments as described herein. The flow chart begins with slowly filling the retort **12, 14** with reagent from a container **26**. Preferably, the retort is filled for 10 seconds and the tissue processor **100** is operated to stop filling prior to reagent contacting tissue samples stored in the retort **12, 14**. The next step in the workflow is to wait for a stable reading from the density meter **74, 76**. Next, the reading from the density meter **74, 76** is checked, which involves performing method steps **82** and **84**. The workflow next determines if the reading is good, which involves performing method step **86**. If the reading is good, the retort **12, 14** is continued to be filled with the reagent and the processing protocol is completed. Otherwise, the container **26** associated with the reagent is locked-out for use by the tissue processor **100** and an alternative bottle/container **26** (in embodiments with a plurality of containers **26**) is selected for use in the tissue processing protocol. The user is notified regarding the locked-out or flagged container **26**, such as by the control interface **24**, and the option to use an alternative bottle/container **26**. The workflow then abandons the tissue processing protocol and waits for the user to take further action, e.g. replace the reagent in the flagged container **26** or select the alternative bottle/container **26**.

(95) Referring to FIGS. **13a-c**, more detailed flow charts of the workflow for reagent screening shown in FIG. **12** and described above are provided. In particular, FIG. **13a** shows additional steps in the workflow which checks if the density meter(s) **74, 76** is enabled by the tissue processor **100**, and otherwise logs a DM Fault (**125**). Once the density meters **74, 76** are enabled, the reagent valves (such as *ret1-vrgt* and *ret2-vrgt* from FIG. **2** of the prior art tissue processor **10**) are opened for filling of the retort **12, 14** with reagent. FIG. **13b** shows detail of the stopping of filling of the retort **12, 14** in order to take the density measurement and check the reagent purity level or concentration. The stopping can be achieved by implementing a “Paused” function in the tissue processor workflow as shown in FIG. **13b**, which pauses the tissue processing protocol and filling of the retort **12, 14** for a time period until the density measurement is performed and reagent purity level or concentration checked. FIG. **13c** shows detail of the method steps **82-86** being performed, in which three stable density readings are taken and the density meter (DM) reading (e.g. an average of the three density measurements) is checked to see if it matches the expected reagent density (e.g. predetermined value based on reagent data from user) to within an error or tolerance. If the DM reading does not match to within the error or tolerance, the workflow logs a Reagent not in expected Density Reagent Error (**121**), flags the bottle **26** against reuse, closes the reagent valves

and returns “Retry New Reagent”. This may involve a notification signal or message being generated for the user to view and take appropriate action, such as selecting an alternative bottle/container **26** or replacing the reagent in the container **26**.

(96) The adapted tissue processor workflow as described above can be implemented in a monitoring tissue processor workflow performed by the reagent management system. The monitoring tissue processor workflow includes performing the adapted tissue processor workflow one or more times, and preferably on both filling and draining of the retort **12**, **14** during a tissue processing protocol performed by the tissue processor **100**. This enables the reagent purity level or concentration to be validated before and after use of the reagent in a tissue processing protocol. Ideally, the monitoring tissue processor workflow performs the adapted tissue processor workflow each time a tissue processing protocol is performed by the tissue processor **100**, which enables data of the reagent purity level or concentration to be collected on successive uses of the reagent by the tissue processor **100**.

(97) In some embodiments, the tissue processor **100** includes a first container for storing a first reagent and a second container for storing a second reagent. The first and second containers may include reagent containers **26** as shown in FIGS. **9a-d** and **10**. However, the first container may include an infiltrating bath **16-22** or alternative container of the tissue processor **100** that stores a reagent or treatment fluid used by the tissue processor **100** to treat tissue samples in the retort **12**, **14**.

(98) For the monitoring tissue processor workflow, the method can further include the step of operating the tissue processor **100** to perform a tissue processing protocol using the first reagent and the second reagent. Preferably, the first reagent is used in the tissue processing protocol prior to the second reagent being used. The tissue processing protocol can include treating tissue samples in the retort **12**, **14** with the first reagent by conducting or pumping the first reagent to and/or from the first container to the retort **12**, **14** on filling and/or draining of the retort **12**, **14**. Ideally, the tissue processing protocol then includes the same steps of treating the tissue samples in the retort **12**, **14** with the second reagent.

(99) Advantageously, the method for the monitoring tissue processor workflow can include automatically determining a carry over volume of the first reagent from the first container into the second reagent from the second container. The carryover volume can be determined by firstly, providing an initial volume of the second reagent in the second container, which can be provided by the user via the input device **24** or controller **25**. Then the method includes performing the measuring step **82** to measure, using the sensor **74**, **76**, a density value of the first reagent on draining of the retort **12**, **14** and a density value of the second reagent on filling and draining of the retort **12**, **14**. The carry over volume can then be calculated automatically according to:

$$(100) V_{CO} = \frac{C_{2out} - C_{2in}}{C_{1out} - C_{2out}} \times V$$

wherein: V_{CO} =volume of carry over (L), ρ_{C2out} =measured density value of the second reagent on draining of the at least one retort (kg/m³), ρ_{C2in} =measured density value of the second reagent on filling of the at least one retort (kg/m³), ρ_{C1out} =measured density value of the first reagent on draining of the at least one retort (kg/m³), and V =initial volume of the second reagent in the second container (L).

(101) The carry over volume is representative of the volume of the first reagent that has contaminated the second reagent during successive uses by the tissue processor **100**. This information can be used by the reagent management system to control use of reagents by the tissue processor **100**, such as by selecting the specific reagents and their order of use in a tissue processing protocol. Further, the carry over volume can be used by the reagent management system to estimate the contamination levels of reagents/treatment fluids from other containers, such as the infiltrating baths **16-22**. This is particularly advantageous as the purity level or concentration of the infiltrating fluids such as paraffin wax from the infiltrating baths **16-22** is not measured by the

sensor **74**, **76** of the tissue processor **100**. Accordingly, this method of calculating the carry over volume using actual measured reagent concentration provides accuracy in the calculation of the purity level or concentration of infiltrating fluids or other fluids by the reagent management system.

(102) The present invention also provides a tissue processor **100** that includes at least one retort **12** for receiving tissue samples, at least one container **26** for storing a reagent and at least one sensor **74** arranged for fluid communication with one or both of the at least one container **26** and the at least one retort **12** for measuring a measured purity level of a reagent. The measured purity level is preferably a concentration value derived from a measured parameter value. The tissue processor **100** also includes a controller **25** configured to perform the method of operating a tissue processor according to steps **80-86** of FIG. **11**.

(103) In preferred embodiments of the invention, the controller **25** is also configured to perform any of the additional method steps described above and with reference to FIGS. **11**, **12** and **13a-c**. Accordingly, the method of operating the tissue processor **100** can be implemented through the controller **25** and further in software, firmware and/or hardware in a variety of manners as would be understood by a person skilled in the art.

(104) The present invention also provides a computer program product including a computer readable medium having computer readable program code and computer readable system code embodied on the medium for, operating a tissue processor (such as tissue processor **100**), within a data processing system, where the computer program product includes computer readable code within the computer readable medium for performing the method of operating a tissue processor according, to steps **80-86** of FIG. **11**.

(105) In preferred embodiments of the invention, the computer readable code can perform any of the additional method steps described above and with reference to FIGS. **11**, **12** and **13a-c**, Accordingly, the method of operating the tissue processor **100** can be implemented through the computer program product in software. The computer program code could be supplied in a number of ways, for example on a memory of the tissue processor **100**, or on a tangible computer readable medium, or communicated as a data signal or file for the tissue processor **100**.

(106) The inventive method, tissue processor and computer program product as described herein advantageously enable reagent quality to be verified before or during operation of a tissue processor to perform a tissue processing protocol with the reagent. The inventive tissue processor includes at least one sensor for measuring a measured purity level of the reagent, which is preferably a concentration value derived from the measured parameter value. Accordingly, the actual reagent concentration level can be determined, by means of the at least one sensor, before or during operation of the tissue processor **100** to perform the tissue processing protocol. The determined reagent concentration level can be used by a reagent management system to more readily control reagent use and tissue processor workflows for performing tissue processing protocols. The invention can therefore improve the likelihood of successful tissue processing by avoiding user error and potential suboptimal tissue processing through verifying reagent quality.

(107) Improvements in Basket Design

(108) The present invention also provides improvements in cassette basket design for tissue processors.

(109) Referring to FIGS. **4** to **6**, the retort **12** of the prior art tissue processor **10** includes three fluid level sensors **52** for detecting the level of process fluid, such as reagents, in the retort **12**. The fluid level sensors **52** are positioned at different heights of the retort **12** as best shown in FIG. **6**. Multiple baskets **62** are configured to be accommodated and stacked in the retort **12** as shown in FIG. **5**. The baskets **62** are sufficiently sized for positioning within the retort **12** and to maximise the volume capacity for storing tissue samples, which may be stored in the baskets **62** within cassettes. The prior art baskets **62** are usually made of a metallic material, and thus provide a reflective structure when exposed to light. Since the fluid level sensors **52** are typically optical sensors, the metallic

reflective structure can interfere with the optical sensors for use in determining the level of the process fluid.

(110) The present invention provides a container **110** for storing tissue samples for processing in a tissue processor (such as the prior art tissue processor **10** or inventive tissue processor **100**). The container **110** is configured to be accommodated in a retort **12, 14** of the tissue processor **10, 100** and provide access to the stored tissue samples for processing with a process fluid in the retort **12, 14**. The retort **12, 14** includes at least one sensor **52** for detecting a level of the process fluid in the retort **12, 14**. The container **110** is configured to minimise interference with the at least one sensor **52**.

(111) FIGS. **14a-b** and **15a-b** illustrate a container **110** for storing tissue samples for processing in a tissue processor according to a preferred embodiment of the invention. The container **110** can be sufficiently sized for positioning within a retort **12, 14**. Furthermore, the container **110** can be a basket as shown in FIGS. **14a-b** and **15a-b** or have a netted structure in order to provide fluid access to the stored tissue samples for processing.

(112) In some embodiments, the at least one sensor **52** is an optical sensor, and the container **110** includes at least one non-reflective surface for minimising interference with the optical sensor **52** (not shown). The non-reflective surface preferably includes an opaque material in order to minimise reflections that can occur during use of the optical sensor **52** (not shown). In other embodiments, the sensor **52** can be other sensors that are affected by interference from surface reflections as known to a person skilled in the art.

(113) The container **110** can be configured to releasably receive one or more clips having the at least one non-reflective surface (not shown). Where the container **110** is a basket, as shown in FIGS. **14a-b** and **15a-b**, the one or more clips can releasably attach to openings in side portions of the basket **110** (not shown). The side portions can include the four surfaces of the receptacle **60** of the basket **110** that exclude base portion **63**. Additionally/alternatively, the side portions of the container or basket **110** can each include the non-reflective surface, which may be integral with the container **110** (not shown). The side portions are preferably formed of a non-reflective or opaque material in these embodiments.

(114) The present invention also provides a container **110** for storing tissue samples for processing in a tissue processor **10, 100** that includes a retractable handle **65** to facilitate stacking of a plurality of the containers **110**.

(115) FIGS. **14a-b** and **15a-b** illustrate the container **110** for storing tissue samples according to a preferred embodiment of the invention, showing the retractable handle **65**. FIGS. **14a-b** show the handle **65** in the retracted position and FIGS. **15a-b** show the handle **65** in the extended position. The container **110** can be sufficiently sized for positioning within a retort **12, 14** and be a basket or have a netted structure in order to provide fluid access to the stored samples for tissue processing. The container or basket **110** as illustrated includes a receptacle **60** and lid **64**. As best shown in FIG. **15b**, the receptacle **60** can include a central recess **66** for receiving the handle **65** in the retracted position. The central recess **66** forms a longitudinal slot for receiving arms of the handle **65** at opposite ends of the slot in the retracted position.

(116) Preferably, the handle **65** is integral with the receptacle **60** as shown in FIGS. **14a-b** and **15a-b**. In particular, FIG. **15b** illustrates that the receptacle **60** can include brackets at opposite ends of the longitudinal slot **66** for receiving, in an opening of the bracket, each arm of the handle **65**. The handle **65** is extended and retracted by manually pushing and pulling the handle **65** with respect to the receptacle **60** so as to move the arms of the handle **65** relative to the openings of the brackets. Integrating the handle **65** into the receptacle **60** can avoid any dependency on secure attachment of a lid **64**, thereby reducing the risk of dropping the container **110** and/or tissue samples during transport.

(117) Referring to FIG. **14a**, the container or basket **110** can further include a lid **64** having a slot **61** through which the handle is extendable to the extended position shown in FIG. **15a**. The slot **61**

can be a longitudinal slot which is slightly longer than a length of the handle **65** in order to allow the handle **65** to pass through to the extended position while minimising the gap therebetween through which tissue samples could exit the receptacle **60**. The slot **61** is centrally positioned as shown in FIGS. **14a** and **15a** for stability of the container **110** when carried by the handle **65**. The slot **61** can also be shaped to include a wider portion in a centre part of the lid **64** for receiving a curved portion of the handle **65**.

(118) Referring to FIG. **14b**, the receptacle **60** can include a base portion **63** having a slot **69** in a central portion thereof. The slot **69** is sized for receiving at least part of a handle **65** of a corresponding container or basket **110**. For example, as shown in FIG. **14a**, part of the handle **65** may protrude through the slot **61** of the lid **64**, particularly in the centre part of the lid **64**, in the retracted position. The slot **69** of the receptacle **60** can receive the protruding part of the handle **65** to facilitate stacking of a plurality of the containers **110**. This advantageously enables the base portion **63** and lid **64** to sit substantially flush when a plurality of containers **110** are vertically stacked.

(119) The container **110** can also include an electronic identifier **79** for use in tracking the location of the container **110** during sample processing. The electronic identifier **79** can include a barcode, or more preferably, a Radio Frequency identification Device (RFID) tag as shown in FIGS. **14a-b** and **15a-b**. In some embodiments, the electronic identifier **79** is provided on a tag **78** which is attached to the receptacle **60** of the basket **110**. Preferably, the tag **78** is attached to a side portion of the receptacle **60** (excluding the base portion **63**) so as to minimise interference with the handle **65** and can be easily read when a plurality of containers **110** are vertically stacked.

(120) Advantageously, the inventive container **110** for storing tissue samples minimises interference with fluid sensors **52** of the tissue processor **10**, **100**, such as by preferably providing at least one non-reflective surface. Furthermore, the inventive container **110** provides a retractable handle so that a plurality of containers **110** can be readily stacked for transport or use in the tissue processor **10**, **100**.

(121) Additional non-limiting exemplary embodiments of the disclosure are set forth below.

Embodiment 1: A method of operating a tissue processor for processing tissue samples, the tissue processor including: at least one retort for receiving tissue samples; at least one container for storing a reagent; and at least one sensor arranged for fluid communication with one or both of the at least one container and the at least one retort for measuring a measured purity level of a reagent, the method including the steps of: a) conducting reagent from the at least one container or the at least one retort to the at least one sensor; b) automatically measuring, by means of the at least one sensor, a measured purity level of the reagent; c) checking whether the measured purity level meets a predetermined purity level of the reagent associated with the at least one container; and d) automatically determining, based on a result of the checking, whether the reagent is suitable for processing tissue samples in the tissue processor. Embodiment 2: The method according to Embodiment 1, further including the step of: providing the predetermined purity level of the reagent based on reagent data for the at least one container. Embodiment 3: The method according to Embodiment 2, further including the step of: receiving, at the tissue processor, the reagent data for the at least one container from a user. Embodiment 4: The method according to Embodiment 3, wherein the tissue processor further includes an input device, and the receiving step includes receiving the reagent data by means of the input device. Embodiment 5: The method according to any one of Embodiments 2 to 4, wherein the reagent data includes at least a concentration value of the reagent. Embodiment 6: The method according to Embodiment 5, wherein the predetermined purity level of the reagent is a concentration level determined based on the concentration value from the reagent data. Embodiment 7: The method according to Embodiment 6, wherein the concentration level is one of: a threshold value, wherein the threshold value is the concentration value from the reagent data; or a tolerance range of values determined based on the concentration value from the reagent data. Embodiment 8: The method according to any one of Embodiments 1

to 7, wherein the at least one sensor measures at step b) a density value that represents the measured purity level of the reagent. Embodiment 9: The method according to Embodiment 8, further including the steps of: repeating the measuring step b) one or more times; and calculating an average of the measured density values, wherein the calculated average represents the measured purity level of the reagent. Embodiment 10: The method according to Embodiment 9, wherein the measured purity level is a concentration value derived from the measured density value or the average of the measured density values. Embodiment 11: The method according to any one of Embodiments 7 to 10 when Embodiment 8 includes the method according to Embodiment 7, wherein the checking step c) includes checking whether the measured purity level is (i) greater than the threshold value, or (ii) within the tolerance range of values. Embodiment 12: The method according to Embodiment 11, wherein the automatically determining step d) includes: determining that the reagent is suitable for processing tissue samples when the measured purity level is greater than the threshold value or within the tolerance range of values; and determining that the reagent is unsuitable for processing tissue samples when the measured purity level is less than the threshold value or falls outside the tolerance range of values. Embodiment 13: The method according to any one of Embodiments 1 to 12, wherein when the reagent is determined to be unsuitable for processing tissue samples, the method further includes the step of: flagging the at least one container for non-use by the tissue processor. Embodiment 14: The method according to Embodiment 13, further including the step of: generating, at the tissue processor, a notification signal for a user to check the reagent in the flagged container. Embodiment 15: The method according to any one of Embodiments 1 to 14, which is performed prior to operating the tissue processor to perform a tissue processing protocol using the reagent. Embodiment 16: The method according to any one of Embodiments 1 to 15, wherein the tissue processor includes a dedicated line connecting the at least one container or the at least one retort to the at least one sensor, and wherein the conducting step a) includes conducting reagent in the dedicated line from the at least one container or the at least one retort to the at least one sensor. Embodiment 17: The method according to any one of Embodiments 1 to 14, which is performed when operating the tissue processor to perform a tissue processing protocol using the reagent. Embodiment 18: The method according to any one of Embodiments 1 to 14 and 17, wherein the tissue processor includes a reagent line connecting the at least one container and the at least one retort, wherein the at least one sensor is arranged for fluid communication with the reagent line, and wherein the conducting step a) includes conducting reagent in the reagent line between the at least one container and the at least one retort. Embodiment 19: The method according to Embodiment 18, wherein the at least one sensor is one of: positioned in the reagent line; or positioned in a bypass line that receives a portion of the reagent when the reagent is conducted in the reagent line. Embodiment 20: The method according to any one of Embodiments 1 to 14 and 17 to 19, which is performed on one or both of: filling of the at least one retort with reagent; and draining of the at least one retort to remove reagent. Embodiment 21: The method according to Embodiment 20, further including the step of: operating the tissue processor to stop filling or draining of the at least one retort to perform at least steps (b)-(d). Embodiment 22: The method according to Embodiment 21, wherein operating the tissue processor to stop filling or draining includes one or both of: operating the tissue processor to stop filling prior to reagent contacting tissue samples stored in the at least one retort; and operating the tissue processor to stop filling prior to reagent being delivered to the at least one container. Embodiment 23: The method according to Embodiment 21 or Embodiment 22, wherein when the reagent is determined to be suitable for processing tissue samples, the method further includes the step of: operating the tissue processor to continue filling or draining of the at least one retort to complete the tissue processing protocol. Embodiment 24: The method according to any one of Embodiments 21 to 23, wherein when the reagent is determined to be unsuitable for processing tissue samples, the method further includes the step of: operating the tissue processor to abandon the tissue processing protocol. Embodiment 25: The method according to any one of Embodiments

1 to 14 and 17 to 24, wherein the tissue processor includes a first container for storing a first reagent and a second container for storing a second reagent, and wherein the method further includes the steps of: operating the tissue processor to perform a tissue processing protocol using the first reagent and the second reagent; and automatically determining a carry over volume of the first reagent from the first container into the second reagent from the second container.

Embodiment 26: The method according to Embodiment 25, wherein automatically determining the carry over volume includes the steps of: providing an initial volume of the second reagent in the second container; and performing the measuring step b) to measure the following: a density value of the first reagent on draining of the at least one retort; a density value of the second reagent on filling of the at least one retort; and a density value of the second reagent on draining of the at least one retort, wherein the carry over volume is calculated according to;

$$(122) V_{CO} = \frac{\frac{C_{2out}}{C_{1out}} - \frac{C_{2in}}{C_{2out}}}{\frac{C_{2out}}{C_{1out}} - \frac{C_{2in}}{C_{2out}}} \times V$$

wherein: V_{CO} =volume of carry over (L), ρ_{C2out} =measured density value of the second reagent on draining of the at least one retort (kg/m³), ρ_{C2in} =measured density value of the second reagent on filling of the at least one retort (kg/m³),

ρ_{C1out} =measured density value of the first reagent on draining of the at least one retort (kg/m³), and V =initial volume of the second reagent in the second container (L). Embodiment

27: A computer program product including: a computer readable medium having computer readable program code and computer readable system code embodied on the medium for, operating a tissue processor, within a data processing system, the computer program product including: computer readable code within the computer readable medium for performing the method steps of any one of Embodiments 1 to 26. Embodiment 28: A tissue processor for processing tissue samples, including:

at least one retort for receiving tissue samples; at least one container for storing a reagent; at least one sensor arranged for fluid communication with one or both of the at least one container and the at least one retort for measuring a measured purity level of a reagent; and a controller configured to: conduct reagent from the at least one container or the at least one retort to the at least one sensor; measure, by means of the at least one sensor, a measured purity level of the reagent; check whether the measured purity level meets a predetermined purity level of the reagent associated with the at least one container; and determine, based on a result of the checking, whether the reagent is suitable for processing tissue samples in the tissue processor. Embodiment 29: The tissue processor according to Embodiment 28, wherein the controller is further configured to: provide the predetermined purity level of the reagent based on reagent data for the at least one container.

Embodiment 30: The tissue processor according to Embodiment 29, wherein the controller is further configured to: receive, at the tissue processor, the reagent data for the at least one container from a user. Embodiment 31: The tissue processor according to Embodiment 30, further including an input device, and wherein the controller is configured to receive the reagent data by means of the input device. Embodiment 32: The tissue processor according to any one of Embodiments 29 to 31, wherein the reagent data includes at least a concentration value of the reagent. Embodiment 33:

The tissue processor according to Embodiment 32, wherein the predetermined purity level of the reagent is a concentration level determined based on the concentration value from the reagent data. Embodiment 34: The tissue processor according to Embodiment 33, wherein the concentration level is one of: a threshold value, wherein the threshold value is the concentration value; or a tolerance range of values determined based on the concentration value. Embodiment 35: The tissue processor according to any one of Embodiments 28 to 34, wherein the at least one sensor measures a density value that represents the measured purity level of the reagent. Embodiment 36: The tissue processor according to Embodiment 35, wherein the controller is configured to measure, by means of the at least one sensor, the density value that represents the measured purity level of the reagent two or more times, and is further configured to: calculate an average of the measured density values, wherein the calculated average represents the measured purity level of the reagent.

Embodiment 37: The tissue processor according to Embodiment 36, wherein the measured purity level is a concentration value derived from the measured density value or the average of the measured density values. Embodiment 38: The tissue processor according to any one of Embodiments 34 to 37 when Embodiment 35 includes the method according to Embodiment 34, wherein the controller checks whether the measured purity level is (i) greater than the threshold value, or (ii) within the tolerance range of values. Embodiment 39: The tissue processor according to Embodiment 38, wherein the controller determines that the reagent is suitable for processing tissue samples when the measured purity level is greater than the threshold value or within the tolerance range of values, and wherein the controller determines that the reagent is unsuitable for processing tissue samples when the measured purity level is less than the threshold value or falls outside the tolerance range of values. Embodiment 40: The tissue processor according, to any one of Embodiments 28 to 39, wherein when the reagent is determined to be unsuitable for processing tissue samples, the controller is further configured to: flag the at least one container for non-use by the tissue processor. Embodiment 41: The tissue processor according to Embodiment 40, wherein the controller is further configured to: generate, at the tissue processor, a notification signal for a user to check the reagent in the flagged container. Embodiment 42: The tissue processor according, to any one of Embodiments 28 to 41, wherein the controller determines whether the reagent is suitable for processing tissue samples prior to operating the tissue processor to perform a tissue processing protocol using the reagent. Embodiment 43: The tissue processor according to any one of Embodiments 28 to 42, wherein the tissue processor includes a dedicated line connecting the at least one container or the at least one retort to the at least one sensor, and wherein the controller conducts reagent in the dedicated line from the at least one container or the at least one retort to the at least one sensor. Embodiment 44: The tissue processor according to any one of Embodiments 28 to 41, wherein the controller determines whether the reagent is suitable for processing tissue samples when operating the tissue processor to perform a tissue processing protocol using the reagent. Embodiment 45: The tissue processor according to any one of Embodiments 28 to 41 and 44, wherein the tissue processor includes a reagent line connecting the at least one container and the at least one retort, wherein the at least one sensor is arranged for fluid communication with the reagent line, and wherein the controller conducts reagent in the reagent line between the at least one container and the at least one retort. Embodiment 46: The tissue processor according to Embodiment 45, wherein the at least one sensor is one of: positioned in the reagent line; or positioned in a bypass line that receives a portion of the reagent when the reagent is conducted in the reagent line. Embodiment 47: The tissue processor according to any one of Embodiments 28 to 41 and 44 to 47, wherein the controller determines whether the reagent is suitable for processing tissue samples during one or both of: filling of the at least one retort with reagent; and draining of the at least one retort to remove reagent. Embodiment 48: The tissue processor according to Embodiment 47, wherein the controller is further configured to: operate the tissue processor to stop filling or draining of the at least one retort to determine whether the reagent is suitable for processing tissue samples. Embodiment 49: The tissue processor according to Embodiment 48, wherein the controller operates the tissue processor to stop filling or draining by one or both of: operating the tissue processor to stop filling prior to reagent contacting tissue samples stored in the at least one retort; and operating the tissue processor to stop filling prior to reagent being delivered to the at least one container. Embodiment 50: The tissue processor according to Embodiment 48 or Embodiment 49, wherein when the controller determines that the reagent is suitable for processing tissue samples, the controller is further configured to: operate the tissue processor to continue filling or draining of the at least one retort to complete the tissue processing protocol. Embodiment 51: The tissue processor according, to any one of Embodiments 48 to 50, wherein when the controller determines that the reagent is unsuitable for processing tissue samples, the controller is further configured to: operate the tissue processor to abandon the tissue processing protocol. Embodiment 52: The tissue processor according to any one of Embodiments 28 to 41 and 44 to 51,

wherein the tissue processor includes a first container for storing a first reagent and a second container for storing a second reagent, and wherein the controller is further configured to: operate the tissue processor to perform a tissue processing protocol using the first reagent and the second reagent; and determine a carry over volume of the first reagent from the first container into the second reagent from the second container. Embodiment 53: The tissue processor according to Embodiment 52, wherein the controller is configured to determine the carry over volume by: receiving an initial volume of the second reagent in the second container; and measuring, by means of the at least one sensor, the following: a density value of the first reagent on draining of the at least one retort; a density value of the second reagent on filling of the at least one retort; and a density value of the second reagent on draining of the at least one retort, wherein the controller calculates the carry over volume according to:

$$(123) V_{CO} = \frac{\frac{C2_{out}}{C1_{out}} - \frac{C2_{in}}{C2_{out}}}{\frac{C2_{out}}{C1_{out}} - \frac{C2_{in}}{C2_{out}}} \times V$$

wherein: V_{CO} =volume of carry over (L), $\rho_{C2.out}$ =measured density value of the second reagent on draining of the at least one retort (kg/m³), $\rho_{C2.in}$ =measured density value of the second reagent on filling of the at least one retort (kg/m³), $\rho_{C1.out}$ =measured density value of the first reagent on draining of the at least one retort (kg/m³), and V =initial volume of the second reagent in the second container (L). Embodiment 54: A container for storing tissue samples for processing in a tissue processor, wherein the container is configured to be accommodated in a retort of the tissue processor and provide access to the stored tissue samples for processing with a process fluid in the retort, wherein the retort includes at least one sensor for detecting a level of the process fluid in the retort, and wherein the container is configured to minimise interference with the at least one sensor. Embodiment 55: The container according to Embodiment 54, wherein the at least one sensor is an optical sensor; and the container includes at least one non-reflective surface for minimising interference with the optical sensor. Embodiment 56: The container according to Embodiment 55, wherein the container is configured to releasably receive one or more clips having the at least one non-reflective surface. Embodiment 57: The container according to any one of Embodiments 54 to 56, wherein the at least one non-reflective surface includes an opaque material. Embodiment 58: A container for storing tissue samples for processing in a tissue processor, wherein the container is configured to be accommodated in a retort of the tissue processor and provide access to the stored tissue samples for processing with a process fluid in the retort, wherein the container includes a retractable handle to facilitate stacking of a plurality of the containers. Embodiment 59: The container according to Embodiment 58, further including a receptacle having a central recess for receiving the handle in a retracted position. Embodiment 60: The container according to Embodiment 59, wherein the handle is integral with the receptacle. Embodiment 61: The container according to Embodiment 59 or Embodiment 60, wherein the receptacle includes a base portion having a slot for receiving at least part of a handle of a corresponding container. Embodiment 62: The container according to any one of Embodiments 58 to 61, further including a lid having a slot through which the handle is extendable to an extended position. Embodiment 63: The tissue processor according to any one of Embodiment 28 to 53, further including the container for storing tissue samples according to any one of Embodiments 54 to 62.

(124) Where any or all of the terms “comprise”, “comprises”, “comprised” or “comprising” are used in this specification (including the claims) they are to be interpreted as specifying the presence of the stated features, integers, steps or components, but not precluding the presence of one or more other features, integers, steps or components.

(125) It is to be understood that various modifications, additions and/or alternatives may be made to the parts previously described without departing from the ambit of the present invention as defined in the claims appended hereto.

(126) It is to be understood that the following claims are provided by way of example only, and are

not intended to limit the scope of what may be claimed in any future application. Features may be added to or omitted from the claims at a later date so as to further define or re-define the invention or inventions.

Claims

1. A tissue processor, comprising: at least one retort in which the tissue processor is configured to process tissue samples with a process fluid; and a container for storing the tissue samples to be processed in the retort of the tissue processor, the container being configured and sized to be accommodated in the at least one retort of the tissue processor and comprising: a receptacle having a central recess which includes a longitudinal slot, and a retractable handle configured to be retracted into an interior of the container, such that arms of the handle are received into respective distal ends of the longitudinal slot in the retracted position, the handle being retractable to facilitate stacking of a plurality of the containers; wherein the container has a netted structure providing fluid access to the tissue samples stored in the container when the container is accommodated in the at least one retort of the tissue processor.
2. The tissue processor according to claim 1, wherein the receptacle of the container includes a base portion, and the longitudinal slot is formed in the base portion, the longitudinal slot being configured for receiving at least part of a handle of a corresponding container.
3. The tissue processor according to claim 1, wherein the handle of the container is attached to the receptacle.
4. The tissue processor according to claim 3, wherein the receptacle of the container includes a base portion, and the longitudinal slot is formed in the base portion, the longitudinal slot being configured for receiving at least part of a handle of a corresponding container.
5. The tissue processor according to claim 1, wherein the container further comprises: a lid attached to and covering an opening of the container, wherein the lid comprises a slot that is aligned with the handle, and wherein the handle is configured to be retracted into the container through the slot of the lid.
6. The tissue processor according to claim 5, wherein the handle of the container is configured to be protruded through the slot of the lid while remaining attached to the container and while the lid is attached to and covering the opening of the container.
7. The tissue processor according to claim 1, wherein side portions of the container are formed of a non-reflective or opaque material.
8. A tissue processor, comprising: at least one retort in which the tissue processor is configured to process tissue samples with a process fluid; and a container for storing the tissue samples to be processed in the retort of the tissue processor, the container being configured and sized to be accommodated in the at least one retort of the tissue processor and comprising: a receptacle having a central recess which includes a longitudinal slot; and a retractable handle configured to be retracted into an interior of the container, such that arms of the handle are received into respective distal ends of the longitudinal slot in the retracted position, the handle being retractable to facilitate stacking of a plurality of the containers, wherein the container is a basket that provides fluid access to the tissue samples stored in the container when the container is accommodated in the at least one retort of the tissue processor.
9. The tissue processor according to claim 8, wherein the receptacle of the container includes a base portion, and the longitudinal slot is formed in the base portion, the longitudinal slot being configured for receiving at least part of a handle of a corresponding container.
10. The tissue processor according to claim 8, wherein the handle of the container is attached to the receptacle.
11. The tissue processor according to claim 10, wherein the receptacle of the container includes a base portion, and the longitudinal slot is formed in the base portion, the longitudinal slot being

configured for receiving at least part of a handle of a corresponding container.

12. The tissue processor according to claim 9, wherein the container further comprises: a lid attached to and covering an opening of the container, wherein the lid comprises a slot that is aligned with the handle, and wherein the handle is configured to be retracted into the container through the slot of the lid.

13. The tissue processor according to claim 12, wherein the handle of the container is configured to be protruded through the slot of the lid while remaining attached to the container and while the lid is attached to and covering the opening of the container.

14. The tissue processor according to claim 8, wherein side portions of the container are formed of a non-reflective or opaque material.
