

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12399532
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Morgan; Thomas Scott

Modular embedded compute appliance docking board, and methods and systems for the same

Abstract

A docking board removably coupled to a processor board that does not function when not operatively coupled to the docking board. The docking board sends power to and receive a control signal from the processor board when operatively coupled to the processor board and does not send power and does not receive a control signal when not operatively coupled to the processor board. The docking board is removably coupled to an expansion board that performs a computer function that is not performed by the processor board and the docking board. The docking board sends power and a control signal to the expansion board when the docking board is operatively coupled to the processor board and the expansion board, and does not send power and does not send a control signal to the expansion board when the docking board is not operatively coupled to the processor board and the expansion board.

Inventors:	Morgan; Thomas Scott (Virginia Beach, VA)
Applicant:	Management Services Group, Inc. (Virginia Beach, VA)
Family ID:	1000008778948
Assignee:	Management Services Group, Inc. (Virginia Beach, VA)
Appl. No.:	18/636767
Filed:	April 16, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240264631 A1	Aug. 08, 2024

Related U.S. Application Data

continuation parent-doc US 18185421 20230317 US 11994908 child-doc US 18636767
continuation parent-doc US 17466401 20210903 US 11619972 20230404 child-doc US 18185421
continuation parent-doc US 16896634 20200609 US 11126225 20210921 child-doc US 17466401
continuation parent-doc US 16788877 20200212 US 10712778 20200714 child-doc US 16896634
us-provisional-application US 62925789 20191025

Publication Classification

Int. Cl.: **G06F1/16** (20060101); **G06F1/18** (20060101); **G06F1/26** (20060101); **G06F13/40** (20060101); **G06F21/44** (20130101)

U.S. Cl.:

CPC **G06F1/1632** (20130101); **G06F1/189** (20130101); **G06F1/26** (20130101); **G06F1/266** (20130101); **G06F13/4081** (20130101); **G06F21/44** (20130101);

Field of Classification Search

CPC: G06F (1/1632); G06F (1/189); G06F (1/26); G06F (1/266); G06F (21/44)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5463742	12/1994	Kobayashi	N/A	N/A
5550710	12/1995	Rahamim et al.	N/A	N/A
5774330	12/1997	Melton et al.	N/A	N/A
5861873	12/1998	Kikinis	N/A	N/A
6052276	12/1999	Do et al.	N/A	N/A
6098131	12/1999	Unger et al.	N/A	N/A
6747878	12/2003	Hipp et al.	N/A	N/A
7139914	12/2005	Arnouse	N/A	N/A
7239509	12/2006	Roeske	N/A	N/A
7472275	12/2007	Arnouse	N/A	N/A
7516484	12/2008	Arnouse	N/A	N/A
7533408	12/2008	Arnouse	N/A	N/A
7593723	12/2008	Zarom	N/A	N/A
9010645	12/2014	Arnouse	N/A	N/A
10235323	12/2018	Arnouse	N/A	N/A
10712778	12/2019	Morgan	N/A	N/A
11126225	12/2020	Morgan	N/A	N/A
11619972	12/2022	Morgan	N/A	N/A
11994908	12/2023	Morgan	N/A	G06F 13/4081
2003/0125107	12/2002	Cannon	N/A	N/A
2003/0154291	12/2002	Ocheltree et al.	N/A	N/A
2003/0188067	12/2002	Okin	N/A	N/A
2005/0021870	12/2004	Carnahan et al.	N/A	N/A
2006/0136622	12/2005	Rouvelin et al.	N/A	N/A

2007/0239963	12/2006	Yao et al.	N/A	N/A
2021/0124394	12/2020	Morgan	N/A	N/A
2022/0050503	12/2021	Morgan	N/A	N/A
2023/0221764	12/2022	Morgan	N/A	N/A

Primary Examiner: Auve; Glenn A.

Attorney, Agent or Firm: COOLEY LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION (1) This application is a continuation of U.S. patent application Ser. No. 18/185,421, filed Mar. 17, 2023, entitled “Modular Embedded Compute Appliance Docking Board, and Methods and Systems for the Same”, now U.S. Pat. No. 11,994,908, which is a continuation of U.S. application Ser. No. 17/466,401, filed Sep. 3, 2021, entitled “Modular Embedded Compute Appliance Docking Board, and Methods and Systems for the Same”, now U.S. Pat. No. 11,619,972, which is a continuation of U.S. application Ser. No. 16/896,634, filed Jun. 9, 2020, entitled “Modular Embedded Compute Appliance Docking Board, and Methods and Systems for the Same”, now U.S. Pat. No. 11,126,225, which is a continuation of U.S. application Ser. No. 16/788,877, filed Feb. 12, 2020, entitled “Modular Embedded Compute Appliance Docking Board, and Methods and Systems for the Same”, now U.S. Pat. No. 10,712,788, which claims priority to and the benefit of U.S. Provisional Application No. 62/925,789, filed Oct. 25, 2019 and entitled “Modular Embedded Compute Appliance Docking Board,” each of which is incorporated herein by reference in its entirety.

TECHNICAL FIELD

(1) The present disclosure relates to the field of computers/digital processing systems, and in particular to methods and apparatus related to a docking board, to which portable expansion boards can be securely attached to form a modern computer.

BACKGROUND

(2) A modular compute appliance can be a useful form of a computer for a number of reasons. For example, a modular function-based compute appliance can be easier to produce by separately producing each function-based board. Moreover, a modular function-based compute appliance can be advantageously produced by specialized focus on design of each function-based board rather than a general effort on managing invasive complexity of a multifunctional dense computer boards.

(3) Dense computer boards generate greater electrical noise, thermal noise, and electromagnetic interference compared to less dense computer boards. Moreover, it can be invasive and expensive to improve a design of a dense computer board to reduce its electrical noise, thermal noise, electromagnetic interference, and other deficiencies from its initial stage design of the dense computer board. Therefore, design deficiencies of dense computer boards that lead to electrical noise, thermal noise, and electromagnetic interference often remain in the dense computer boards as persistent product defects.

(4) Design of dense computer boards typically involves planning about functions to be supported by the dense computer boards. Planning has been an effective approach in known design approaches for the dense computer boards that have large power supplies. In design of non-modular portable computers and embedded systems where design area of their board is limited, cost effectiveness and performance of the portable computers and the embedded systems are reduced.

(5) Known embedded computers each typically includes a processor, a memory, a storage, a

networking component(s), and other peripherals soldered on or directly connected to a main board (also called “the motherboard”). Increased noise levels in the form of an electrical noise, a thermal noise, an electromagnetic interference, and other deficiencies can manifest in degraded performance of embedded computers. Thus, a need exists for a cleaner and more modular approach, which allows for a different primary function for each function-based peripherals connected to that board.

SUMMARY

(6) A docking board is removably couplable to a processor board that does not function when not operatively coupled to the docking board. The docking board sends power to and receives a control signal from the processor board when operatively coupled to the processor board and does not send power and does not receive a control signal when not operatively coupled to the processor board. The docking board is removably couplable to an expansion board that performs a computer function that is not performed by the processor board and the docking board. The docking board sends power and a control signal to the expansion board when the docking board is operatively coupled to the processor board and the expansion board, and does not send power and does not send a control signal to the expansion board when the docking board is not operatively coupled to the processor board and the expansion board.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1A is a schematic description of a portable computer, according to an embodiment.
- (2) FIG. 1B is a schematic description of a portable computer, according to an embodiment.
- (3) FIG. 2 is a flowchart illustrating a method of operating a portable computer, according to an embodiment.
- (4) FIG. 3 is a flowchart illustrating a method of operating a portable computer, according to an embodiment.
- (5) FIG. 4 is a flowchart illustrating a method of operating a portable computer, according to an embodiment.

DETAILED DESCRIPTION

- (6) Non-limiting examples of various aspects and variations of the embodiments are described herein and illustrated in the accompanying drawings.
- (7) One or more embodiments described herein generally relate to embedded computers, and in particular, methods, apparatus, and systems that use a modular compute appliance to increase quality, simplicity of production, cost effectiveness, and engineering quality of the total system. Modular design reduces possible design requirements and reduces costs associated with designs of more complex systems. Modular design further enables a more specialized approach in designing expansion boards. Methods and systems of modular embedded compute appliance docking board are disclosed.
- (8) Described herein are modular compute appliances that are suitable for highly reliable and secure portable computer systems. Function-based boards of the compute appliance can be as small as a card (e.g., a credit card, an access key card, etc.) as to be easily carried in pockets or wallets. Function-based boards can be dependent on a docking board for power supply and control signals from a processor board. On the other hand, the modular compute appliances can be dependent on function-based boards for board specific functions such as networking, memory, encryption, virtual reality, and so forth. Function-based boards, given their compact form factor and function-specific design, can achieve high signal integrity (SI) for power and signals sent between the docking board and the function-based boards.
- (9) Embodiments described herein provide methods and systems for organizing a modular compute

appliance (also referred to herein as a portable computer) into function-based boards. Function-based boards can have different portable sizes (e.g., size of a credit card, size of a smartphone screen, etc.), can have different functions (e.g., networking, satellite communication, additional storage, etc.), and can be removably coupled to a docking board. Modularizing the portable computer allows manufacturers of each function-based board to have a specialized and flexible approach in design of a specific function of the function-based board, without redesigning the modular compute appliance for different computers.

(10) FIG. 1A is a schematic description of a modular compute appliance (also referred to herein as a “portable computer”) **100A**, according to an embodiment. The modular compute appliance **100A** can include the docking board **101A**, the processor board **104A**, the expansion board **110A**, and/or an expansion board **120A**. The docking board **101A** can be configured to be operatively coupled to the processor board **104A**, the expansion board **110A**, and/or the expansion board **120A** through a system bus (for example, address bus, data bus, and/or control bus, not shown). The docking board **101A** can be used to send power (e.g., a direct current (DC) electric power, an alternating current (AC) electric power, etc.) and receive a set of signals (e.g., a DC electric signal, an AC electric signal, an radio frequency (RF) signal etc.) in response to a processor board (e.g., a central processing unit (CPU) board, etc.) being coupled or in response to an expansion board (e.g., a memory board, etc.) being coupled. For example, the docking board **101A** can include a processor or controller (not shown) to control the sending of power, receiving signals, etc. as described herein. The modular compute appliance **100A** can include, in addition to the docking board **101A**, a set of function-based boards including a processor board **104A** and/or an expansion board **110A**. The modular compute appliance **100A** can be connected to a set of readers **180A** (also referred to herein as “the set of peripheral devices” and “peripherals”) via a connector(s) (not shown in FIG. 1A).

(11) The docking board **101A** can include a power supply or be removably coupled to a power supply. The docking board **101A** has full control of power distribution between the boards within the modular compute appliance **100A**. For example, a processor or controller of the docking board **101A** can send power to processor board **104A** and/or the expansion board **110A**. In some implementations, the docking board **101A** can send a first power to the processor board **104A** and/or the expansion board **110A** to authenticate the processor board **104A** and/or the expansion board **110A** (e.g., send the first power to an authentication circuit, such as an integrated circuit (IC) chip that performs the authentication). The first power can be sent in response to the processor board **104A** and/or the expansion board **110A** being operatively coupled to the docking board **101A**. The docking board **101A** can send a second power, different than the first power (e.g., different in power magnitude, in voltages, or in currents), to the processor board **104A** and/or the expansion board **110A** after and/or in response to authenticating the processor board **104A** and/or the expansion board **110A** to operate them in full capacity. For example, the first power can be 3vdc and used to authenticate the processor board and/or expansion board, and the second power can be 5vdc for operating the processor board and/or expansion board. For another example, the first power can 12 vdc and the second power can be 5 vdc. For yet another example, the first power can be 5 vdc at 400 ma current and the second power can be 5 vdc at 500 ma current. For yet another example, the first power can be 5vdc at 500 ma current and the second power can be 50 vdc at 500 ma current. Thus, the first power and the second power can differ by any of the voltage, current and/or wattage.

(12) In some other implementations, the docking board **101A** can send power to the processor board **104A** and/or the expansion board **110A** to authenticate the processor board **104A** and/or the expansion board **110A**. For example, the power can be sent to an authentication circuit such as an integrated circuit (IC) chip that performs the authentication. The power can be sent in response to the processor board **104A** and/or the expansion board **110A** being operatively coupled to the docking board **101A**. In such implementations, power is not sent to remaining portions of the

processor board **104A** and/or the expansion board **110A** until the authentication circuit has authenticated the respective board. After the authentication circuit has authenticated the respective board, the power can be sent to the remaining portions of the processor board **104A** and/or the expansion board **110A**.

(13) The docking board **101A** can include a first power filter **102A** and a second power filter **103A**. The docking board **101A** can supply power to the function-based boards (such as expansion boards **110A** and **120A**), and can be configured further to facilitate a set of peripheral boards (also referred to herein as “the set of readers”) via, for example, a set of memory buses, a set of signal receivers, a set of signal transmitters, a set of wired networking, a set of wireless networking, a set of optical networking, a set of video systems, a set of monitors, and/or the like (not shown in FIG. **1A**).

(14) The docking board **101A** can be configured to facilitate, instead of or in addition to the set of peripheral boards, a set of peripheral connectors such as for example, a universal serial bus (USB) connector(s), a USB 2.0 connector(s), a USB 3.0 connector(s), a mini USB connector(s), a micro USB connector(s), a USB-c connector(s), a high definition multimedia interface (HDMI) connector(s), a video graphics array connector(s), a general purpose input/output (GPIO) connector(s), a general purpose interface bus (GPIB or IEEE-488) connector(s), and/or the like. The set of peripheral connectors can be a power or signal medium that connects to a set of connector interfaces. The set of connector interfaces can be integrated in the docking board **101A** and/or can be integrated in a peripheral board from the set of peripheral boards. In one example, a peripheral connector (e.g., a copper wire having two ends and with one male USB connector at each end) can have a corresponding type A USB 3.0 receptacle (female connector) located at the docking board **101A** and a type A USB 3.0 receptacle at a peripheral such as a projector video system.

(15) The processor board **104A** can include, for example, a hardware-based integrated circuit (IC) or any other suitable processing device configured to run or execute a set of instructions or a set of codes. For example, the processor board **104A** can include a general purpose processor, a central processing unit (CPU), an accelerated processing unit (APU), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA), a programmable logic array (PLA), a complex programmable logic device (CPLD), a programmable logic controller (PLC), a graphics processing unit (GPU), and/or the like. The processor board **104A** can additionally include a memory, such as, for example, a CPU cache memory or a random-access memory (RAM).

Including the memory on the processor board **104A** can allow reduce average time and/or average energy used to process data. The general-purpose processor can be operatively coupled to the memory through a system bus (for example, address bus, data bus, and/or control bus, not shown).

(16) The expansion board **110A** and/or the expansion board **120A** can include a hardware-based IC or can be any other suitable electronic board configured to provide at least one functionally. In one embodiment, the expansion board **110A** or the expansion board **120A** can have one function such as, for example, networking, storage, and/or the like. In one embodiment, the expansion board **110A** and/or the expansion board **120A** can have multiple functions such as, for example, networking and streaming, storage and authenticating, and/or the like. The flexibility of having one or more functions on the expansion board **110A** and/or the expansion board **120A** allows flexibility in circuit and overall system design.

(17) The set of readers **180A** can be set of ancillary devices used to input information to the modular compute appliance **100A** or output information from the modular compute appliance **100A**. The set of readers **180A** can include, for example, a keyboard(s), a mouse(s), a monitor(s), a webcam(s), a microphone(s), a touch screen(s), a printer(s), a scanner(s), a virtual reality (VR) head-mounted display, a speaker(s), a headphone(s), a gamepad(s), a joystick(s), a biometric reader(s), and/or the like (not shown).

(18) The modular compute appliance **100A** can connect the docking board **101A**, via a set of high signal integrity (SI) power and signal connectors, to the processor board **104A**, the expansion board

110A, and/or the expansion board **120A**. A high SI power and signal connectors **151A** can connect the processor board **104A** to the docking board **101A**, a high SI power and signal connectors **152A** can connect the expansion board **110A** (e.g., additional networking board) to the docking board **101A**, and/or a high SI power and signal connectors **153A** can connect the expansion board **120A** (e.g., additional storage board and additional networking board) to the docking board **101A**.

(19) In some implementations, the high SI power and signal connectors **151A** can establish a connection between the processor board **104A** and the docking board **101A** for information processing and providing power to operate the processor board **104A**. The information processing can be done by, for example, a processor board that synchronizes and controls operations of the modular compute appliance **100A**, the expansion board **101A**, the expansion board **120A**, and/or the set of readers **180A**. When the connection between the processor board **104A** and the docking board **101A** is established, the processor board **104A** and the docking board **101A** are then operatively coupled in the sense that the docking board **101A** can send power to the processor board **104A** and the processor board **104A** can send a set of control signals to the docking board **101A**. The connection between the processor board **104A** and the docking board **101A** is removable in the sense that the processor board **104A**, when removed from the docking board **101A**, is not operatively coupled, does not receive power from the docking board **101A**, does not send control signal to the docking board **101A** and does not function. In one example, the docking board **101A** is the only source of power to the processor board **104A**, and removing the processor board **104A** from the docking board **101A** stops operation of the expansion board **104A** to an extent that the expansion board **110A** cannot operate alone without being removably connected to the docking board **101A**.

(20) In some implementations, the high SI power and signal connectors **152A** establish a connection between the expansion board **110A** to the docking board **101A**, such that the expansion board **110A** is removably coupled to the docking board **101A**. The expansion board **110A** can be added for example to provide networking function when the expansion board **110A** is operatively coupled to the docking board **101A**. The additional networking function can be, for example, a wireless router board that acts as a mobile Wi-Fi™ hotspot. When the connection between the expansion board **110A** and the docking board **101A** is established, the expansion board **110A** and the docking board **101A** are then operatively coupled, in the sense that the docking board **101A** can be configured to send power and direct a control signal from the processor board **104A** to the expansion board **110A** and the expansion board **110A** can send a set of networking signals to the docking board **101A**. The connection between the expansion board **110A** and the docking board **101A** is removable in the sense that the expansion board **110A**, when removed from the docking board **101A**, is not operatively coupled, does not receive power and/or control signal from the docking board **101A**, and does not send networking signals to the docking board **101A**. In one example, the docking board **101A** is the only source of power to the expansion board **110A** and removing the expansion board **110A** stops operation of the expansion board **110A** to an extent that the expansion board **110A** cannot operate alone without being removably connected to the docking board **101A**.

(21) In some implementations, the high SI power and signal connectors **153A** establish a connection between the expansion board **120A** to the docking board **101A**, such that the expansion board **120A** is removably coupled to the docking board **101A**. The expansion board **120A** can be added to provide storage function when the expansion board **120A** is operatively coupled to the docking board **101A**. The additional storage function can be, for example, a solid-state storage board that acts as a database. After the connection between the expansion board **120A** and the docking board **101A** is established, the expansion board **120A** and the docking board **101A** are then operatively coupled, in the sense that the docking board **101A** can send power and direct a control signal from the processor board **104A** to the expansion board **110A** and the expansion board **110A** can send a set of data transfer signals to the docking board **101A**. The connection between the

expansion board **120A** and the docking board **101A** is removable in the sense that the expansion board **120A**, when removed from the docking board **101A**, is not operatively coupled, does not receive power and/or control signal from the docking board **101A**, and does not send data transfer signals to the docking board **101A**. In one example, the docking board **101A** provides the only source of power to the expansion board **120A** and removing the expansion board **120A** stops operation of the expansion board **120A** to an extent that the expansion board **120A** cannot operate alone without being operably connected to the docking board **101A**.

(22) In one implementation, the expansion board **110A** or the expansion board **120A** can connect directly to a power supply for board-level functions. The board-level functions refer to electronic operation performed by the expansion board **110A** and in some instances do not include non-electronic operations (e.g., running a turbine engine) performed by the expansion board **110**. In one example, all power used to operate the expansion board **110A** can be provided directly by the power supply in form of the AC electric power and/or the DC electric power. In another example, a first part of the power used to operate the expansion board **120A** can be provided directly by the power supply in form of the AC electric power and/or the DC electric power, and a second part of the power used to operate the expansion board **120A** can be provided by an internal power supply (e.g., an energy harvesting device, a photovoltaic device, a lithium ion battery, an AC adaptor, etc.) integrated in the expansion board **120A**.

(23) In one implementation, the expansion board **110A** or the expansion board **120A** can be operatively couple to a peripheral device (e.g., a laser pointer, a GPS locator, etc.) from the set of peripheral devices **180A**. The docking board **101A** can be configured to send power in a first power configuration to the expansion board **110A** when the expansion board **110A** is connected to a first peripheral device (not shown). The docking board **101A** can be configured to send power in a second power configuration to the expansion board **110A** when the expansion board **110A** is connected to a second peripheral device. In an example, the docking board **101A** can be configured to send a 5 Volts DC electric power to the expansion board **110A** when connected to a laser pointer peripheral device. In another example, the docking board **101A** can be configured to send a 220 Volts AC electric power to the expansion board **110A** when connected to a light detection and ranging (LiDAR) peripheral device.

(24) In one implementation, the docking board **101A** can be configured to send power in the first power configuration to the expansion board **110A** when the expansion board **110A** is connected to a peripheral device of a type. The type can refer to, for example, a technical standard, a quality standard, a security standard, a set of functional and/or technical characteristics, and/or a manufacturer. Additionally, the docking board **101A** can be configured to send power in a second power configuration to the expansion board **110A** when the expansion board **110A** is connected to a peripheral device not of the type. In an example, the docking board **101A** can be configured to send a 10-milliwatt electric power to the expansion board **110A** when connected to a fifth generation (5G) type network board. In another example, the docking board **101A** can be configured to send a 200-milliwatt electric power to the expansion board **110A** when connected to a long term evolution (LTE) network board which is not of the 5G type network board.

(25) As shown in FIG. 1A, the docking board **101A** includes a first power filter **102A** and a second power filter **103A**. The docking board **101A** can include a power conditioner (not shown) to connect the first power filter **102A** to the expansion board **110A** when connected to a first peripheral device **180A**, and to connect the second power filter **103A** to the expansion board **110A** when connected to a second peripheral device **180A**. The first power filter **102A** and/or the second power filter **103A** can be a printed circuit board including circuitry for filtering and/or power conversion such as, for example, electromagnetic interference (EMI) filter, low-pass filter, high-pass filter, band-path filter, AC-to-DC converter, voltage converter, and/or any other suitable electric circuitry for adjusting electric power levels, electric power types, and/or lowering electric power noises. In one example, the docking board **101A** can be configured to select the first power

filter **102A** to send 12 Volts DC electric power to the expansion board **110A**, when the expansion board **110A** is not connected to any peripheral device. The docking board **101A** can be configured further to select the second power filter **103A** to send 110 Volts AC electric power to the expansion board **110A**, when the expansion board **110A** is connected to a peripheral device such as satellite communication receiver board.

(26) The docking board **101A** can receive a control signal from the expansion board **110A** and/or the expansion board **120A** and can send a control signal to the processor board **104A** based on the control signal received from the expansion board **110A** and/or **120A**. In one example, the expansion board **120A** can include a graphical processing unit (GPU) that performs a set of specialized modular arithmetic tasks faster than the CPU of the processor board **104A**. The CPU can be configured to send a first set of control signals and a first data to the GPU to perform a series of modular arithmetic tasks. The GPU can be configured to perform the series of modular arithmetic tasks on the first data based on the first set of control signals and send a second data and a second set of control signals from the GPU to the CPU.

(27) The docking board **101A** is configured to be operatively disposed between the processor board **104A** and the expansion board **110A** when operatively coupled to the processor board **104A** and operatively coupled to the expansion board **110A**, such that the processor board **104A** and the expansion board **110A** do not exchange a signal without passing through the docking board **101A**. In one example, the expansion board **110A** can be a wireless communication board that receives and transmits data via radio frequency electromagnetic signals during operations. The processor board **104A** send a set of signals, carrying data and/or control commands, to the docking board **101A** to be directed to the expansion board **110A**. The docking board **101A** can receive the set of signals from the processor board **104A** and direct the set of signals to the expansion board **110A** to transmit the data via radio frequency electromagnetic signals.

(28) The docking board **101A** can authenticate the expansion board **110A** in response to the expansion board **110A** being operatively coupled to the docking board **101A**. An authentication of the expansion board **110A** can include exchanging power and/or a set of tokens between the expansion board **110A** and the docking board **101A**. The set of tokens can be for example a set of passwords, a set of codes, a set of electric signals, a set of electromagnetic signals, and/or the like. The docking board **101A** can be configured to send a first power to the expansion board **110A** in response to being operatively coupled to the docking board **101A** and before authenticating the expansion board **110A**. The first power can be a small amount of power sufficient to operate an authentication circuit on the expansion board **110A** (e.g., an integrated circuit (IC) chip that performs the authentication). After authenticating the expansion board **110A**, the docking board **101A** can then send a second power to the expansion board **110A**. The second power can be different than the first power and sufficient to operate the remaining portions of the expansion board **110A**. The docking board **101A** can send a control signal to the expansion board **110A** after authenticating the expansion board **110A**. The docking board **101A** can further to not send the control signal to the expansion board before authenticating the expansion board **110A**.

(29) Similarly, the docking board **101A** can authenticate the processor board **104A** in response to the processor board **104A** being operatively coupled to the docking board **101A**. An authentication of the processor board **104A** can include exchanging power and/or a set of tokens between the processor board **104A** and the docking board **101A**. The set of tokens can be for example a set of passwords, a set of codes, a set of electric signals, a set of electromagnetic signals, and/or the like. The docking board **101A** can be configured to send a first power to the processor board **104A** in response to being operatively coupled to the docking board **101A** and before authenticating the processor board **104A**. The first power can be a small amount of power sufficient to operate an authentication circuit on the processor board **104A**. After authenticating the processor board **104A**, the docking board **101A** can then send a second power to the processor board **104A**. The second power can be greater than the first power and sufficient to operate the remaining portions of the

processor board **104A**. The docking board **101A** can further send a control signal to the processor board **104A** after authenticating the processor board **104A**. The docking board **101A** can further choose to not send the control signal to the expansion board before authenticating the processor board **104A**.

(30) FIG. 1B is a schematic description of a modular compute appliance (also referred to herein as a “portable computer”) **100B**, according to an embodiment. The modular compute appliance **100B** includes a docking board **101B** (similar to the docking board **101A** described above with respect to FIG. 1A) used to send power (e.g., a direct current (DC) electric power, an alternating current (AC) electric power, etc.) and receive a set of signals (e.g., a DC electric signal, an AC electric signal, an radio frequency (RF) signal etc.) in response to a processor board (e.g., a central processing unit (CPU) board, etc.) or an expansion board (e.g., a memory board, etc.). The modular compute appliance **100B** includes, in addition to the docking board **101B**, a set of function-based boards such as, for example, a processor board **110B** (similar to the processor board **104A** described above with respect to FIG. 1A), and a set of expansion boards **120B**. The modular compute appliance **100B** can be connected to a set of readers (not shown here and similar to the set of readers **180A** described above with respect to FIG. 1A) via a connector.

(31) The set of expansion boards **120B** can be, for example, a hardware based integrated circuit (IC) board, a printed circuit board (PCB), or any other suitable electronic board configured to provide at least one specialized functionally. In one embodiment, each expansion board from the set of expansion boards **120B** can have a single specialized function such as, for example, networking, storage, and/or the like. In one embodiment, each expansion board from the set of expansion boards **120B** can have multiple functions such as, for example, networking and streaming, both storage and authenticating, and/or the like. Having flexibility of having one or more functions on the set of expansion boards **120B** enables flexibility and cost effectiveness in circuit design and in system design. Each expansion board from the set of expansion boards **120B** can be configured to establish a connection to the docking board **101B** via a high SI power and signal connectors.

(32) One or more expansion boards from the set of expansion boards **120B** can be memory boards configured to be removably coupled to the docking board **101B**. Each memory board can be, for example, a memory buffer, a random access memory (RAM), a read-only memory (ROM), a hard drive, a flash drive, a secure digital (SD) memory card, a compact disk (CD), an external hard drive, an erasable programmable read-only memory (EPROM), an embedded multi-time programmable (MTP) memory, an embedded multi-media card (eMMC), a universal flash storage (UFS) device, and/or the like. Each memory board can store, for example, one or more software boards and/or code that includes instructions to cause a processor (such as the processor board **110B**) to perform control procedures, arithmetic procedures, and/or logical procedures.

(33) One or more expansion boards from the set of expansion boards **120B** can be communication interface boards configured to be removably coupled to the docking board **101B**, and configured to connect the docking board **101B** the processor board **110B**, and/or an expansion board from the set of expansion boards **120B** to a network. Each communication interface board can be, for example, a network interface card (NIC), a Wi-Fi™ board, a Bluetooth® board, an optical communication board, and/or any other suitable wired and/or wireless communication interface. In some instances, each communication interface board can facilitate receiving or transmitting data via the network. More specifically, in some implementations, each communication interface board can facilitate receiving or transmitting data through the network from or to a modular compute appliance.

(34) The network can be a digital telecommunication network of servers and/or compute devices. The servers and/or computes device on the network can be connected via one or more wired or wireless communication networks (not shown) to share resources such as, for example, data storage or computing power. The wired or wireless communication networks between servers and/or compute devices of the network can include one or more communication channels, for example, a

radio frequency (RF) communication channel(s), an extremely low frequency (ELF) communication channel(s), an ultra-low frequency (ULF) communication channel(s), a low frequency (LF) communication channel(s), a medium frequency (MF) communication channel(s), an ultra-high frequency (UHF) communication channel(s), an extremely high frequency (EHF) communication channel(s), a fiber optic communication channel(s), an electronic communication channel(s), a satellite communication channel(s), and/or the like. The network can be, for example, the Internet, an intranet, a local area network (LAN), a wide area network (WAN), a metropolitan area network (MAN), a worldwide interoperability for microwave access network (WiMAX®), a virtual network, any other suitable communication system and/or a combination of such networks.

(35) One or more expansion boards from the set of expansion boards **120B** can be sound interface boards configured to be removably coupled to the docking board **101B**, and configured to provide audio signals to and from the docking board **101B** the processor board **110B**, and/or an expansion board from the set of expansion boards **120B**. Each sound interface board can be, for example, a consumer-grade sound interface board, an environmental audio expansion, a sound interface board with analog-to-digital (AD) and digital-to-analog (DA) converters, a high-definition sound interface, and/or the like. In some instances, each sound interface board can facilitate receiving or transmitting audio signals via a peripheral device (e.g., a microphone, a speaker, etc.). More specifically, in some implementations, a sound interface board can receive and/or transmit audio signals from or to the docking board **101B** connected to the peripheral device configured to receive and/or transmit audio signals from or to the docking board **101B**. In some implementations, a sound interface board can include an integrated peripheral unit (e.g., a microphone, a speaker, etc.) to receive and/or transmit audio signals from or to a user, and further configured to receive and/or transmit the audio signals to the docking board **101B**.

(36) One or more expansion boards from the set of expansion boards **120B** can be graphic interface boards configured to be removably coupled to the docking board **101B**, and configured to provide signals to and from the docking board **101B** the processor board **110B**, and/or an expansion board from the set of expansion boards **120B**. Each graphic interface board can be connected to the docking board **101B** via, for example, an industry standard architecture (ISA), peripheral component interconnect (PCI), peripheral component interconnect extended (PCI-X), accelerated graphics port (AGP), and/or the like. Each graphic interface board can be connected to a peripheral device (e.g., a monitor, a projector, a television, etc.) via, for example, a video graphics array (VGA) connector, high-definition multimedia interface (HDMI) and/or the like. In some implementations, a graphic interface board can receive and/or transmit video signals from or to the docking board **101B** connected to a peripheral device configured to receive and/or transmit video signals from or to the docking board **101B**. In some implementations, a graphic interface board can include an integrated peripheral unit (e.g., a display, a camera, etc.) to receive and/or transmit video signals from or to a user, and further configured to receive and/or transmit the video signals to the docking board **101B**.

(37) One or more expansion boards from the set of expansion boards **120B** can be encryption boards configured to be removably coupled to the docking board **101B**, and configured to provide signals to and from the docking board **101B**, the processor board **110B**, and/or an expansion board from the set of expansion boards **120B**. In some implementation, an encryption board can be a hardware-based encryption board operatively connected to the docking board **101B**. In one example, the hardware-based encryption board can operate individually to encrypt a message received, via the docking board **101B**, from a processor board. In another example, the hardware-based encryption board can operate together with a set of software codes being executed at the processor board.

(38) One or more expansion boards from the set of expansion boards **120B** can be a sensor fusion board configured to be removably coupled to the docking board **101B**, and configured to provide signals to and from the docking board **101B**, the processor board **110B**, and/or an expansion board

from the set of expansion boards **120B**. In one example the sensor fusion board is light detection and ranging (LiDAR) board including a set of light emitters and a set of light sensors collectively configured to detect objects in the three dimensional space surrounding the LiDAR board. The sensor fusion board can be configured to send sensor data, via the docking board **101B**, to the processor board and further receive a set of instruction from the processor board.

(39) FIG. **2** is a flowchart illustrating a method **200** of operating a portable computer (e.g., portable computer **100A** described above with respect to FIG. **1A**), according to an embodiment. As shown in FIG. **2**, at **201**, power is sent from a docking board (similar to the docking board **101A** described above with respect to FIG. **1A**) to a processor board (similar to the processor board **104A** described above with respect to FIG. **1A**) when the docking board and the processor board are operatively coupled together. The processor board does not function and the docking board does not send power to the processor board when the docking board and the processor board are not operatively coupled together. At **202**, a control signal is received at the docking board from the processor board when the docking board and the processor board are operatively coupled together. The docking board does not receive a control signal when not operatively coupled to the processor board. At **203**, power and a control signal is sent from the docking board to an expansion board (similar to the expansion board **110A** and/or the expansion board **120A** described above with respect to FIG. **1A**) when the docking board and the processor board are operatively coupled together. The expansion board can perform a computer function that is not performed by the processor board and the docking board. At **204**, power and a control signal is not sent from the docking board to the expansion board when the docking board is not operatively coupled to the processor board and the expansion board. The docking board, the processor board, and the expansion board collectively define a portable computer when the docking board is operatively coupled to the processor board and the expansion board. Optionally, at **205**, a control signal can be received at the docking board from the expansion board. Also, optionally, at **206**, a control signal can be sent from the docking board to the processor board based on the control signal received from the expansion board. The method **200** is explained in greater detail below.

(40) At **201**, the docking board sends power to a processor board when the docking board and the processor board are operatively coupled together. The processor board does not function and the docking board does not send power to the processor board when the docking board and the processor board are not operatively coupled together. The docking board, when operatively coupled to the processor board, sends power to the processor board in a power configuration. The power configuration is defined by an electromagnetic medium requirement, a wattage requirement, a voltage requirement, and/or a current requirement. The power configuration can be for example, a direct current (DC) electric power requirement and 5 volts of voltage requirement, an alternating current (AC) electric power requirement with 100 milliwatts of wattage requirement, an electromagnetic induction power requirement, and/or the like. The docking board, when not operatively coupled to the processor board, does not send power to the processor board in a power configuration.

(41) In one example, the docking board and the processor board each includes a set of electrically conducting pins when the electrically conducting pins are not in physical contact to conduct electric current, the docking board and the processor board are not operatively coupled, the docking board does not direct electric power to the processor board, and the processor board does not function. When the docking board and the processor board are connected together via an electric medium (such as the pins), the docking board transmits a first token, via the electric medium, to the processor board, and the processor boards transmits a second token, via the electric medium, to the processor board. If the first token does not authenticate the docking board to the processor board and/or if the second token does not authenticate the processor board to the docking board, the processor board does not operatively connect to the docket board, and the docking board does not send power to the processor board.

(42) At **202**, the docking board receives a control signal from the processor board when the docking board and the processor board are operatively coupled together. The docking board does not receive a control signal when not operatively coupled to the processor board. In one example, the control signal can be a DC electric current or an AC electric current sent from the processor board to the docking board, so that the docking board performs an operation in response to receiving the control signal. In another example, the control signal can be a set of radio frequency (RF) electromagnetic (EM) waves sent from the processor board to the docking board to perform a set of operations in response to receiving the RF EM waves.

(43) At **203**, the docking board sends power and a control signal to the expansion board when the docking board and the processor board are operatively coupled together. The expansion board can perform a computer function that is not performed by the processor board and the docking board. The docking board provides power to operate the processor board and the expansion board, when the docking board is operatively coupled to the processor board and expansion board. The computer function performed by the expansion board can be, for example, a networking function, an additional storage function, an additional encryption function, a virtual reality function. The control signal sent from the docking board to the expansion board can be generated in the docking board or can be directed from the processor board to the expansion board through the docking board. In some implementations, power and the control signal can be sent from the docking board to the expansion board via a common connection medium (e.g., a USB connection, a thunderbolt connection, etc.).

(44) In some instances, the computer function performed by the expansion board can be a set of electrically driven circuit operations that are different from the operation of the processor board. For example, the computer function performed by the expansion board can generate sound signals in a sound interface board, generate graphic signals in a graphic interface board, encrypt data using a specialized encryption board, generate a representation of a three-dimensional space using a sensor fusion board, detect an object with high reliability and accuracy using a LiDAR board, and so forth. In some other instances, the computer function performed by the expansion board can be a set of electrically driven circuit operations that are the same as or similar to the operation of the processor board that further improves or expands performance of the processor board. For example, the compute function performed by the expansion board can be additional processing core that enhances the processing power of the processor board, additional memory that expands capacity of memory on the processor board, additional networking boards that enable transmitting and receiving new telecommunication standards (e.g. 5G, 6G, etc.), and so forth.

(45) At **204**, the docking board does not send power and a control signal to the expansion board when the docking board is not operatively coupled to the processor board and the expansion board. In one example, the docking board, the processor board, and the expansion board each includes a set of electrically conducting pins that are not in physical contact to conduct electric current when the boards are not connected together. Thus, the docking board and the processor board are not operatively coupled and/or the docking board and the expansion board are not operatively coupled when the boards are not connected together. As a result, the docking board does not send power and the control signal to the expansion board, and the expansion board does not work when the boards are not connected together.

(46) At **205**, the docking board optionally receives a control signal from the expansion board. The control signal can be, for example, a DC electric current or an AC electric current sent from the expansion board to the docking board to perform an operation, a set of radio frequency (RF) electromagnetic waves sent from the expansion board to the docking board to perform a set of operations, and/or the like. In one example, the expansion board can be a task-specific processor board to perform a series of arithmetic and/or logical operations of a specific task more quickly and/or cost effectively compared to the processor board. The specific task performed by the task-specific processor board can result in the generation of a specific task control signal. At **206**, the

docking board optionally sends a control signal to the processor board based on the control signal received from the expansion board. In one example, the expansion board can send the specific task control signal to the docking board, and the docking board can re-send the specific task control signal to the processor board or any other boards operatively connected to the docking board.

(47) The docking board, the processor board, and the expansion board collectively define a portable computer when the docking board is operatively coupled to the processor board and the expansion board. The portable computer can process information (e.g., using the processor board), can store information (e.g., using a storage expansion board), can receive and/or transmit information (e.g., using a networking expansion board), and perform any other additional computing operation via an additional expansion board(s) capable being operatively connected to the docking board. The expansion board(s) (also referred to herein as “function-based boards”) can have different portable sizes (e.g., size of a credit card, size of a smartphone screen, etc.) and can be removably coupled to the docking board.

(48) FIG. 3 is a flowchart illustrating a method **300** of operating a portable computer (e.g., portable computer **100A** described above with respect to FIG. 1A), according to an embodiment. As shown in FIG. 3, at **301**, power is sent from a docking board (similar to the docking board **101A** described above with respect to FIG. 1A) to a processor board (similar to the processor board **104A** described above with respect to FIG. 1A) when the docking board and the processor board are operatively coupled together. The processor board does not function and the docking board does not send power to the processor board when the docking board and the processor board are not operatively coupled together. The docking board sends power to the processor board for example via the method shown and described above with reference to FIG. 2. At **302**, a control signal is received at the docking board from the processor board when the docking board and the processor board are operatively coupled together. The docking board does not receive a control signal when not operatively coupled to the processor board. The docking board receives the control signal from the processor board, for example, via the method shown and described above with reference to FIG. 2. At **303**, power and a control signal is sent from the docking board to a first expansion board (e.g., expansion board **110A** described above with respect to FIG. 1A) when the docking board and the processor board are operatively coupled together. The first expansion board is configured to perform a computer function that is not performed by the processor board and the docking board. The docking board sends power and the control signal to the expansion board, for example, via the method shown and described above with reference to FIG. 2. At **304**, power and a control signal are not sent from the docking board to the first expansion board when the docking board is not operatively coupled to the processor board and the first expansion board. The docking board does not send power and the control signal from the docking board to the expansion board, for example, via the method shown and described above with reference to FIG. 2. The docking board, the processor board and the first expansion board collectively define a portable computer when the docking board is operatively coupled to the processor board and the first expansion board. At **305**, power and a control signal is sent from a docking board to a second expansion board (e.g., the expansion board **120A** described above with respect to FIG. 1A) when the docking board, the processor board, and the second expansion board are operatively coupled together. The second expansion board performs a second computer function that is not performed by the processor board, the docking board and the first expansion board. At **306**, power and a control signal are not sent from the docking board to the second expansion board when the docking board, the processor board and the second expansion board are not operatively coupled together. The docking board, the processor board, the first expansion board, and the second expansion board collectively defining the portable computer in a second configuration when the docking board, the processor board, the first expansion board and the second expansion board are operatively coupled together. The method **300** is explained in greater detail below.

(49) At **305**, the docking board sends power and a control signal to a second expansion board when

the docking board, the processor board, and the second expansion board are operatively coupled together. The second expansion board performs a second computer function that is not performed by the processor board, the docking board and the first expansion board. The docking board provides power to operate the processor board, the first expansion board, and the second expansion board when the docking board is operatively coupled to the processor board. The computer function performed by the expansion board can be, for example, a sound interface board, a graphic interface board, and/or the like. The control signal sent from the docking board to the second expansion board can be generated in the docking board or can be directed from the processor board, or the first expansion board to the second expansion board.

(50) At **306**, the docking board does not send power and a control signal to the second expansion board when the docking board, the processor board and the second expansion board are not operatively coupled together. In one example, the docking board, the processor board, the first expansion board, and the second expansion board each includes a set of electrically conducting pins that are not in physical contact when the docking board, the processor board are not couple together, the first expansion board and the second expansion board. Thus, the docking board and the processor board are not operatively coupled, the docking board and the first expansion board are not operatively coupled, and the docking board and the second expansion board are not operatively coupled. As a result, the docking board does not send power and the control signal to the second expansion board, and the second expansion board does not work.

(51) FIG. **4** is a flowchart illustrating a method **400** of operating a portable computer (e.g., portable computer **100A** described above with respect to FIG. **1A**), according to an embodiment. As shown in FIG. **4**, at **401**, power is sent from a docking board (e.g., docking board **101A** described above with respect to FIG. **1A**) to a processor board (e.g., processor board **104A** described above with respect to FIG. **1A**) when the docking board and the processor board are operatively coupled together. The processor board does not function, and the docking board does not send power to the processor board when the docking board and the processor board are not operatively coupled together. The docking board can send power to the processor board via, for example, the method shown and described above with reference to FIG. **2**. At **402**, receiving a control signal is received at the docking board from the processor board when the docking board and the processor board are operatively coupled together. The docking board not receiving a control signal when not operatively coupled to the processor board. The docking board receives the control signal from the processor board via, for example, the method shown and described above with reference to FIG. **2**. At **403**, power and a control signal are sent from the docking board to an expansion board (e.g., expansion board **110A** and/or the expansion board **120A** described above with respect to FIG. **1A**) when the docking board and the processor board are operatively coupled together. The expansion board is configured to perform a computer function that is not performed by the processor board and the docking board. The docking board sends power and the control signal to the expansion board via, for example, the method shown and described above with reference to FIG. **2**. At **404**, power and a control signal are not sent from the docking board to the expansion board when the docking board is not operatively coupled to the processor board and the expansion board. The docking board, the processor board, and the expansion board collectively define a portable computer when the docking board is operatively coupled to the processor board and the expansion board. The docking board does not send power and the control signal from the docking board to the expansion board via, for example, the method shown and described above with reference to FIG. **2**. At **405**, the expansion board is authenticated at the docking board in response to the expansion board being operatively coupled to the docking board. At **406**, the control signal is sent from the docking board to the expansion board after the expansion board is authenticated. At **407**, the control signal is not sent from the docking board to the expansion board before the expansion board is authenticated. At **455**, the processor board is authenticated at the docking board in response to the processor board being operatively coupled to the docking board. At **456**, the control signal is

sent from the docking board to the processor board after the processor board is authenticated. At **457**, the control signal is not sent from the docking board to the processor board before the processor board is authenticated. The method **400** is explained in greater detail below.

(52) At **405**, the docking board authenticates the expansion board in response to the expansion board being operatively coupled to the docking board. In one implementation, an authentication of the expansion board can include exchanging a set of tokens between the expansion board and the docking board. The set of tokens can be, for example, a set of passwords, a set of codes, a set of electric signals, a set of electromagnetic signals, and/or the like. At **406**, the docking board sends the control signal to the expansion board after the expansion board is authenticated. In one implementation, the docking board directs the control signal generated in the processor board to the expansion board, after the expansion board and the docking board exchange the set of token to confirm that the expansion board is authentic and is compatible with the docking board. At **407**, the docking board does not send the control signal to the expansion board before the expansion board is authenticated. In one example, the docking board does not send any signal to the expansion board or does not direct any signal from the processor board to the expansion board before the set of tokens authenticate the expansion board.

(53) At **455**, the docking board authenticates the processor board in response to the processor board being operatively coupled to the docking board. In one implementation, an authentication of the processor board can include exchanging a set of tokens between the processor board and the docking board. The set of tokens can be, for example, a set of passwords, a set of codes, a set of electric signals, a set of electromagnetic signals, and/or the like. At **456**, the docking board sends the control signal to the processor board after the processor board is authenticated. In one implementation, the docking board sends the control signal generated in the docking board or the expansion board to the processor board, after the processor board and the docking board exchange the set of token to confirm that the processor board is authentic and is compatible with the docking board. At **457**, the docking board does not send the control signal to the processor board before the processor board is authenticated. In one example, the docking board does not send signals to the processor board before the set of tokens authenticate the processor board.

(54) It should be understood that the disclosed embodiments are not representative of all claimed innovations. As such, certain aspects of the disclosure have not been discussed herein. That alternate embodiments may not have been presented for a specific portion of the innovations or that further undescribed alternate embodiments may be available for a portion is not to be considered a disclaimer of those alternate embodiments. Thus, it is to be understood that other embodiments can be utilized, and functional, logical, operational, organizational, structural and/or topological modifications may be made without departing from the scope of the disclosure. As such, all examples and/or embodiments are deemed to be non-limiting throughout this disclosure.

(55) Some embodiments described herein relate to methods. It should be understood that such methods can be computer implemented methods (e.g., instructions stored in memory and executed on processors). Where methods described above indicate certain events occurring in certain order, the ordering of certain events can be modified. Additionally, certain of the events can be performed repeatedly, concurrently in a parallel process when possible, as well as performed sequentially as described above. Furthermore, certain embodiments can omit one or more described events.

(56) All definitions, as defined and used herein, should be understood to control over dictionary definitions, definitions in documents incorporated by reference, and/or ordinary meanings of the defined terms.

(57) Examples of computer code include, but are not limited to, micro-code or micro-instructions, machine instructions, such as produced by a compiler, code used to produce a web service, and files containing higher-level instructions that are executed by a computer using an interpreter. For example, embodiments can be implemented using Python, Java, JavaScript, C++, and/or other programming languages and development tools. Additional examples of computer code include,

but are not limited to, control signals, encrypted code, and compressed code.

(58) The drawings primarily are for illustrative purposes and are not intended to limit the scope of the subject matter described herein. The drawings are not necessarily to scale; in some instances, various aspects of the subject matter disclosed herein can be shown exaggerated or enlarged in the drawings to facilitate an understanding of different features. In the drawings, like reference characters generally refer to like features (e.g., functionally similar and/or structurally similar elements).

(59) The acts performed as part of a disclosed method(s) can be ordered in any suitable way. Accordingly, embodiments can be constructed in which processes or steps are executed in an order different than illustrated, which can include performing some steps or processes simultaneously, even though shown as sequential acts in illustrative embodiments. Put differently, it is to be understood that such features may not necessarily be limited to a particular order of execution, but rather, any number of threads, processes, services, servers, and/or the like that may execute serially, asynchronously, concurrently, in parallel, simultaneously, synchronously, and/or the like in a manner consistent with the disclosure. As such, some of these features may be mutually contradictory, in that they cannot be simultaneously present in a single embodiment. Similarly, some features are applicable to one aspect of the innovations, and inapplicable to others.

(60) Where a range of values is provided, it is understood that each intervening value, to the tenth of the unit of the lower limit unless the context clearly dictates otherwise, between the upper and lower limit of that range and any other stated or intervening value in that stated range is encompassed within the disclosure. That the upper and lower limits of these smaller ranges can independently be included in the smaller ranges is also encompassed within the disclosure, subject to any specifically excluded limit in the stated range. Where the stated range includes one or both of the limits, ranges excluding either or both of those included limits are also included in the disclosure.

(61) The phrase “and/or,” as used herein in the specification and in the embodiments, should be understood to mean “either or both” of the elements so conjoined, i.e., elements that are conjunctively present in some cases and disjunctively present in other cases. Multiple elements listed with “and/or” should be construed in the same fashion, i.e., “one or more” of the elements so conjoined. Other elements can optionally be present other than the elements specifically identified by the “and/or” clause, whether related or unrelated to those elements specifically identified. Thus, as a non-limiting example, a reference to “A and/or B”, when used in conjunction with open-ended language such as “comprising” can refer, in one embodiment, to A only (optionally including elements other than B); in another embodiment, to B only (optionally including elements other than A); in yet another embodiment, to both A and B (optionally including other elements); etc.

(62) As used herein in the specification and in the embodiments, “or” should be understood to have the same meaning as “and/or” as defined above. For example, when separating items in a list, “or” or “and/or” shall be interpreted as being inclusive, i.e., the inclusion of at least one, but also including more than one, of a number or list of elements, and, optionally, additional unlisted items. Only terms clearly indicated to the contrary, such as “only one of” or “exactly one of,” or, when used in the embodiments, “consisting of,” will refer to the inclusion of exactly one element of a number or list of elements. In general, the term “or” as used herein shall only be interpreted as indicating exclusive alternatives (i.e., “one or the other but not both”) when preceded by terms of exclusivity, such as “either,” “one of,” “only one of,” or “exactly one of.” “Consisting essentially of,” when used in the embodiments, shall have its ordinary meaning as used in the field of patent law.

(63) As used herein in the specification and in the embodiments, the phrase “at least one,” in reference to a list of one or more elements, should be understood to mean at least one element selected from any one or more of the elements in the list of elements, but not necessarily including at least one of each and every element specifically listed within the list of elements and not

excluding any combinations of elements in the list of elements. This definition also allows that elements can optionally be present other than the elements specifically identified within the list of elements to which the phrase “at least one” refers, whether related or unrelated to those elements specifically identified. Thus, as a non-limiting example, “at least one of A and B” (or, equivalently, “at least one of A or B,” or, equivalently “at least one of A and/or B”) can refer, in one embodiment, to at least one, optionally including more than one, A, with no B present (and optionally including elements other than B); in another embodiment, to at least one, optionally including more than one, B, with no A present (and optionally including elements other than A); in yet another embodiment, to at least one, optionally including more than one, A, and at least one, optionally including more than one, B (and optionally including other elements); etc.

(64) In the embodiments, as well as in the specification above, all transitional phrases such as “comprising,” “including,” “carrying,” “having,” “containing,” “involving,” “holding,” “composed of,” and the like are to be understood to be open-ended, i.e., to mean including but not limited to. Only the transitional phrases “consisting of” and “consisting essentially of” shall be closed or semi-closed transitional phrases, respectively, as set forth in the United States Patent Office Manual of Patent Examining Procedures, Section 2111.03.

Claims

1. An apparatus, comprising: an expansion board that is configured to be removably coupled to a docking board that is configured to be removably coupled to a processor board, the expansion board during operation performs a computer function that is not performed by the processor board, the expansion board having an authentication circuit configured to receive a first power sent from the docking board when the docking board is operatively coupled to the expansion board, the authentication circuit configured to prevent at least a portion of the first power from being sent to remaining portions of the expansion board until the expansion board is authenticated, and the expansion board configured to receive a second power and a control signal from the docking board after the expansion board authenticates itself in response to receiving the first power, the expansion board configured to not receive power nor a control signal from the docking board when the expansion board is not operatively coupled to the docking board.
2. The apparatus of claim 1, wherein the expansion board is a first expansion board, the computer function is a first computer function, the apparatus further comprising: a second expansion board configured to be removably coupled to a docking board, the second expansion board configured to not perform the first computer function and configured to perform a second computer function that is not performed by the processor board, the docking board and the first expansion board.
3. The apparatus of claim 1, wherein the expansion board is a first expansion board, the computer function is a first computer function, the apparatus further comprising: a second expansion board configured to be removably coupled to a docking board, the second expansion board configured to not perform the first computer function and configured to perform a second computer function that is not performed by the processor board, the docking board and the first expansion board, the second expansion board configured to receive power and a control signal from the docking board when the docking board is operatively coupled to the processor board and the second expansion board, the second expansion board configured to not receive power and not receive a control signal from the docking board when the docking board is not operatively coupled to the processor board and the second expansion board, and the docking board, the processor board, the first expansion board and the second expansion board collectively defining the portable computer in a second configuration when the docking board is operatively coupled to the processor board, the first expansion board and the second expansion board.
4. The apparatus of claim 1, wherein: the expansion board configured to receive, via a first power filter of the docking board, the power in a first configuration from the docking board when the

expansion board is operatively coupled to a peripheral device of a type, the expansion board configured to receive, via a second power filter of the docking board, the power in a second configuration from the docking board when the expansion board is not operatively coupled to a peripheral device of the type.

5. The apparatus of claim 1, wherein the control signal received at the expansion board and sent from the docking board is based on the control signal received by the docking board from the processor board.

6. The apparatus of claim 1, wherein the expansion board, when operatively coupled to the docking board and when the docking board is coupled to the processor board, does not exchange a signal with the processing board without passing through the docking board.

7. An apparatus, comprising: an expansion board that is configured to be removably coupled to a docking board that is configured to be removably coupled to a processor board, the expansion board during operation performs a computer function that is not performed by the processor board, the expansion board configured to receive power sent from the docking board when the expansion board is operatively coupled to the docking board, the expansion board configured to receive a control signal from the docking board after the expansion board authenticates itself, the expansion board configured to not receive power nor a control signal from the docking board when the expansion board is not operatively coupled to the docking board, and the expansion board, the processor board and the docking board collectively defining a portable computer when the docking board is operatively coupled to the processor board and the expansion board.

8. The apparatus of claim 7, wherein: the expansion board is a first expansion board, the computer function is a first computer function, a second expansion board configured to receive power and a control signal from the docking board when the second expansion board is coupled to the docking board, the second expansion board does not perform the first computer function, the second expansion board configured to perform a second computer function that is not performed by the processor board, the docking board and the first expansion board, the second expansion board configured to not receive power and a control signal from the docking board when the second expansion board is operatively coupled to the docking board and the docking board is not operatively coupled to the processor board, and the docking board, the processor board, the first expansion board and the second expansion board collectively defining a portable computer when the docking board is operatively coupled to the processor board, the first expansion board and the second expansion board.

9. The apparatus of claim 7, wherein: the expansion board is configured to receive the power in a first configuration from the docking board in response to the docking board receiving a control signal from the processor board and when the expansion board is operatively coupled to a peripheral device of a type; the expansion board is configured to receive the power in a second configuration from the docking board in response to the docking board receiving a control signal from the processor board and when the expansion board is not operatively coupled to a peripheral device of the type.

10. The apparatus of claim 7, wherein the expansion board is configured to send a first control signal to the docking board to cause the docking board to send a second control signal to the processor board in response to the docking board receiving the first control signal from the expansion board.

11. The apparatus of claim 7, wherein the expansion board, when coupled to the docking board that is coupled to the processor board, does not exchange a signal with the processor board without passing through the docking board.

12. The apparatus of claim 7, wherein an authentication circuit of the expansion board is configured to receive from the docking board at least one token from a set of tokens and send to the docking board at least one token from the set of tokens.

13. The apparatus of claim 7, wherein: an authentication circuit of the expansion board is

configured to receive from the docking board at least one token from a set of tokens and send to the docking board at least one token from the set of tokens, the set of tokens including at least one of a set of passwords, a set of codes, a set of electric signals or a set of electromagnetic signals.

14. A method, comprising: receiving a first power at an expansion board from a docking board when the docking board is operatively coupled to the expansion board and a processor board, the expansion board not functioning and the docking board not sending power to the expansion board when the docking board is not operatively coupled to the expansion board and the docking board is not operatively coupled to the processor board; authenticating, at the expansion board, the expansion board in response to receiving the first power; receiving a second power at the expansion board from the docking board after the expansion board is authenticated, the second power being different than the first power; and sending a control signal from the expansion board to the docking board when the docking board and the expansion board are operatively coupled together, the expansion board not sending a control signal when not operatively coupled to the docking board.

15. The method of claim 14, wherein the expansion board, the docking board, and the processor board collectively defining the portable computer in a first configuration when the expansion board, the docking board, and the processor board are operatively coupled together.

16. The method of claim 14, wherein: the expansion board is a first expansion board, the computer function is a first computer function, the first expansion board, the docking board, and the processor board collectively defining the portable computer in a first configuration when the first expansion board, the docking board, and the processor board are operatively coupled together, the method further comprising: receiving, at a second expansion board, power and a control signal from the docking board when the docking board, the processor board and the second expansion board are operatively coupled together, the second expansion board configured to perform a second computer function that is not performed by the processor board, the docking board and the first expansion board; and not receiving, at the second expansion board, power and a control signal from the docking board when the docking board, the processor board and the second expansion board are not operatively coupled together, the docking board, the processor board, the first expansion board and the second expansion board collectively defining the portable computer in a second configuration when the docking board, the processor board, the first expansion board and the second expansion board are operatively coupled together.

17. The method of claim 14, wherein the expansion board, when coupled to the docking board that is coupled to the processor board, does not exchange a signal with the processor board without passing through the docking board.

18. The method of claim 14, further comprising: preventing at least a portion of the first power from being sent to remaining portions of the expansion board until the expansion board is authenticated by an authentication circuit.

19. The method of claim 14, wherein: the receiving the second power includes receiving, via a first power filter of the docking board, the second power in a first configuration from the docking board when the expansion board is operatively coupled to a peripheral device of a type, the receiving the second power includes receiving, via a second power filter of the docking board, the second power in a second configuration from the docking board when the expansion board is not operatively coupled to a peripheral device of the type.

20. The method of claim 14, wherein: the receiving the second power includes receiving the second power having a first magnitude from the docking board when the expansion board is operatively coupled to a peripheral device, the receiving the second power includes receiving the second power having a second magnitude from the docking board when the expansion board is not operatively coupled to a peripheral device of the type, the first magnitude of the second power being greater than the second magnitude of the second power.
