

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication	20250268375
Kind Code	A1
Publication Date	August 28, 2025
Inventor(s)	TINGLE; Bryan Keith et al.

PILASTER STORAGE SYSTEM

Abstract

A pilaster system includes a pilaster including a plurality of pins spaced apart from each other along a length of the pilaster, and a bracket including a hook and a notch. The hook is configured to engage with a first one of the plurality of pins and the notch is configured to engage with a second one of the plurality of pins.

Inventors: TINGLE; Bryan Keith (Shelbyville, KY), Chambers; Paul Franklin (Louisville, KY)

Applicant: Rev-A-Shelf Company, LLC (Louisville, KY)

Family ID: 1000008489288

Assignee: Rev-A-Shelf Company, LLC (Louisville, KY)

Appl. No.: 19/054084

Filed: February 14, 2025

Related U.S. Application Data

us-provisional-application US 63556701 20240222

Publication Classification

Int. Cl.: A47B57/38 (20060101); A47B88/407 (20170101)

U.S. Cl.:

CPC A47B57/38 (20130101); A47B88/407 (20170101);

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS [0001] This application claims priority from U.S. Provisional Application No. 63/556,701, filed Feb. 22, 2024, which is hereby fully incorporated by reference herein in its entirety.

TECHNICAL FIELD

[0002] This disclosure relates to storage systems and, in particular, to adjustable cabinet storage systems.

BACKGROUND

[0003] Present storage systems suffer from a variety of drawbacks, limitations, and disadvantages. Accordingly, there is a need for inventive systems, methods, components, and apparatuses described herein.

SUMMARY

[0004] Further areas of applicability will become apparent from the description provided herein. It should be understood that the description and specific examples are intended for purposes of illustration only and are not intended to limit the scope of the present disclosure.

[0005] In some implementations, a pilaster system may include a pilaster including a plurality of pins spaced apart from each other along a length of the pilaster; and a bracket including a hook and a notch. The hook is configured to engage with a first one of the plurality of pins and the notch is configured to engage with a second one of the plurality of pins.

[0006] In some other implementations, a pilaster system may include: a pilaster including a first pin and a second pin extending between two sidewalls of the pilaster; and a bracket including a first flange, a second flange connected to the first flange, a hook extending from an end of the first flange, and a notch disposed within the first flange. The hook is configured to engage with the first pin and the notch is configured to engage with the second pin.

[0007] In some other implementations, a pilaster system may include: a pilaster including a first pin and a second pin extending between two sidewalls of the pilaster; and a bracket including a hook extending from an end of the bracket, and a notch disposed within the bracket. The hook is configured to engage with the first pin and the notch is configured to engage with the second pin.

[0008] Other systems, methods, features and advantages will be, or will become, apparent to one with skill in the art upon examination of the following figures and detailed description. It is intended that all such additional systems, methods, features and advantages be included within this description, be within the scope of the invention, and the following claims.

[0009] The terms “about,” “substantially,” “generally,” and other terms of degree, when used with reference to any volume, dimension, proportion, or other quantitative or qualitative value, are intended to communicate a definite and identifiable value within the standard parameters that would be understood by one of skill in the art (e.g., equivalent to a mechanical engineer with experience in this field), and should be interpreted to include at least any legal equivalents, minor but functionally-insignificant variants, standard manufacturing tolerances, and including at least mathematically significant figures (although not required to be as broad as the largest range thereof), including a variance of up to, for example 5%, 2%, 1%, or less or more as would be deemed appropriate by one of skill in the art. In addition, the term “configured to” is used to describe structural limitations in a particular manner that requires specific construction to accomplish a stated function and/or to interface or interact with another component(s) and is not used to describe mere intended or theoretical uses.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] The embodiments may be better understood with reference to the following drawings and

description. The components in the figures are not necessarily to scale. Moreover, in the figures, like-referenced numerals designate corresponding parts throughout the different views.

[0011] FIG. 1 illustrates a perspective view of an example of a pilaster system;

[0012] FIG. 2 illustrates a perspective view of an example of a bracket;

[0013] FIGS. 3A-3B illustrate perspective views of an example of a bracket;

[0014] FIGS. 4A-4C illustrate perspective view of an example of a pilaster;

[0015] FIG. 5 illustrates a perspective view of a portion of an example of a pilaster system;

[0016] FIG. 6 illustrates a perspective view of a portion of an example of a pilaster system;

[0017] FIG. 7A illustrates a perspective view of an example of a bracket and pins;

[0018] FIG. 7B illustrates a side view of an example of a bracket and pins;

[0019] FIG. 7C illustrates a perspective view of an example of a bracket and pins;

[0020] FIG. 8 illustrates a perspective view of an example of a bracket and a portion of a rail;

[0021] FIG. 9 illustrates a perspective view of an example of brackets and a rail;

[0022] FIG. 10 illustrates a perspective front view of an example of a pilaster system, including pilasters and brackets, coupled to rails and arranged for utilization in a storage system;

[0023] FIG. 11 illustrates a perspective front view of an example of a pilaster system, including pilasters and brackets, coupled to rails and arranged for utilization in a storage system including a drawer; and

[0024] FIG. 12 illustrates a perspective front view of an example of a storage system including a cabinet, a drawer, and rails, and further including a pilaster system.

[0025] FIG. 13 illustrates a perspective front view of an example of a pilaster system, including pilasters and brackets, coupled to rails and arranged for utilization in a storage system including multiple drawers.

[0026] FIG. 14 illustrates a perspective rear view of an example of a pilaster system, including pilasters and brackets, coupled to rails and arranged for utilization in a storage system including multiple drawers.

[0027] FIG. 15A illustrates a perspective view of another example of a bracket;

[0028] FIG. 15B illustrates a perspective view of another example of a bracket;

[0029] FIG. 15C illustrates a side view of the bracket of FIG. 15A;

[0030] FIG. 16 illustrates a side view of the bracket of FIG. 15A coupled to a pin of an example of a pilaster system;

[0031] FIG. 17A illustrates a perspective view of another example of a bracket;

[0032] FIG. 17B illustrates a perspective view of another example of a bracket;

[0033] FIG. 17C illustrates a side view of the bracket of FIG. 17A;

[0034] FIG. 18 illustrates a side view of the bracket of FIG. 17A coupled to a pin of an example of a pilaster system;

[0035] FIG. 19 illustrates a perspective view of the bracket of FIG. 17A coupled to a pin of an example of a pilaster system;

[0036] FIG. 20 illustrates an enlarged perspective view of the bracket of FIG. 17A and a portion of an example of a pilaster system.

DETAILED DESCRIPTION

[0037] FIG. 1 illustrates an example of a pilaster system **100**. The pilaster system **100** may include a pilaster **102** and a bracket **104**. Example materials for the pilaster **102** may include wood or plastic, although other types of materials or combinations of materials are possible. Additionally, example materials for the bracket **104** include metal or plastic, although other types of materials and/or combinations of materials are possible. Additionally, various other embodiments of the pilaster system **100** may include multiple pilasters **102** and/or brackets **104**, as show in FIGS. 10-14.

[0038] FIGS. 2, 3A, and 3B illustrate additional views of an example of the bracket **104**. The bracket **104** may include a first flange **106**, a second flange **108**, a hook **110**, a notch **112**, a pin **114**,

and an aperture **116**.

[0039] The first flange **106** and the second flange **108** may form the body of the bracket **104**. The first flange **106** and the second flange **108** may be formed at an angle to each other. For example, the first flange **106** and the second flange **108** may be formed perpendicular or at a 90 degree angle to each other. Alternatively, the first flange **106** and the second flange **108** may be formed at an acute or obtuse angle to each other. The first **106** and second flange **108** may meet at a corner of the bracket, which may be, for example, a sharp corner or may be curved with a radius.

[0040] The hook **110** may extend from and/or form part of the first flange **106**. For example, the hook **110** may extend from an end and/or a top of the first flange **106**. For reference, the terms top and bottom may refer to the orientation of components when they are installed, for example, in a cabinet. Additionally or alternatively, it may refer to the orientation of the component as shown in the figures. The first flange **106** may have a different height on one side of the hook **110** vs the other side of the hook **110**. For example, the first flange **106** and the second flange **108** may have a first height H1 on one side of the hook **110**, for example, the side of the hook **110** where the first flange **106** and the second flange **108** meet. Additionally or alternatively, the first flange **106** may have a second height H2 on the other side of the hook **110**, for example, the side of the hook **110** opposite from where the first flange **106** and the second flange **108** meet. The first height H1 and the second height H2 may be different. Alternatively, the first height H1 and the second height H2 may be the same.

[0041] Referring particularly to FIG. 3B, additionally or alternatively, the hook **110** may have a width W1 that is greater than a width W2 and/or a width W3 of the first flange **106**. For example, a portion of the hook **110** defined by the width W1 may extend out past a portion of the first flange **106** defined by the width W2 and/or a portion of the first flange **106** defined by the width W3. Alternatively, the width W1 of the hook **110** may be the same as or less than the width W3. These dimensions, W1, W2, W3 (described further below), and the second height H2 may enable easier use of the bracket **104**, for example, easier installment and/or hooking of the bracket **104** onto the pilaster **102**. Additionally or alternatively, these dimensions may also provide greater support and stability for the bracket **104** and any accessories or components installed onto the bracket **104** and/or pilaster **102**.

[0042] The notch **112** may be disposed on the first flange **106**. The notch **112** may be closer in proximity to a bottom of the first flange **106** and/or an end of the first flange **106** opposite the end of the flange **106** with the hook **110**. The notch **112** may extend from an edge of the first flange **106** into to the flange **106** towards the corner where the first **106** and second flange **108** meet. The widths W2, W3 of the first flange **106** may extend on different sides of the notch **112**, and may be the same as or different from each other. For example, the width W2 of the first flange **106** between the hook **110** and the notch **112** may be shorter than the width W3 of the first flange **106** on the other side of the notch **112**, between the notch **112** and the end of the bracket **104**. As illustrated in FIGS. 2-3B, the notch **112** may have rounded edges with a radius.

[0043] The second flange **108** may include the pin **114**. Additionally, as shown in FIG. 2, the second flange **108** may include the aperture **116**. The aperture **116** may be, for example, threaded and/or sized to receive a screw. For example, FIGS. 3A and 3B show a screw (or other similar fastener) **118** in the aperture **116**. The pin **114** may be, for example, press fit or otherwise assembled with into the flange **108**. Additionally or alternatively, the pin **114** may be a single, unitary structure and formed with the flange **108** and/or the bracket **104**. The aperture **116** may be disposed near or closer to the top of the bracket **104** and/or the end of the bracket **104** with the hook **110** than the pin **114**. The pin **114** may be disposed near or closer to the bottom of the bracket **104** and/or the end of the bracket **104** opposite from the hook **110** than the aperture **116**. In some implementations, the pin **114**, the aperture **116**, and the screw **118** may be used to attach or couple the second flange **108** of the bracket **104** to a rail **132**, as shown and described in further detail below in FIGS. 8 and 9. Also, in some implementations as shown in FIGS. 2-3B, the second flange

108 (and/or the bracket **104** as a whole) includes only one pin **114** and only one aperture **116** configured to receive only one screw **118**, thereby providing a “one-screw” installation of the bracket **104**, which in turn may optimize materials and cost, and/or provide easier installation or assembly with other components of a storage system compared to “multi-screw” alternatives. [0044] FIGS. **4A-C** illustrate different views of the pilaster **102**. The pilaster **102** may include a base **120**, a first sidewall **122**, a second sidewall **124**, pins **126**, pin apertures **128**, and mounting apertures **130**.

[0045] The base **120**, first sidewall **122**, and second sidewall **124** may form the body of the pilaster **102**. The base **120**, first sidewall **122**, and second sidewall **124** may extend vertically upward when installed. The first **122** and second sidewall **124** may extend out from the base **120**, for example perpendicular to the base **120**, such that a cross section of the pilaster **102** forms a “C” or “U” shape. Alternatively, the first **122** and/or second sidewall **124** may extend from the base **120** at an acute or obtuse angle. The first **122** and second sidewall **124** may be opposite from each other and/or extend parallel to each other, with the base **120** extending between the first **122** and second sidewall **124**.

[0046] The pins **126** may extend between the first sidewall **122** and the second sidewall **124** and may, for example, extend parallel to the base **120**. Each of the first sidewall **122** and the second sidewall **124** may include an associated set of apertures or holes (also called pin holes and/or pin apertures). Additionally, each of the pins **126** may be secured or coupled to the first sidewall **122** and the second sidewall **124** by having one end inserted into a respective one of the holes/apertures of the first sidewall **122** and another end inserted or fit into a respective one of the holes/apertures of the second sidewall **124**. In some implementations, each of the ends are press fit and/or glued in respective holes/apertures of the first and second sidewalls **122**, **124**.

[0047] Further, on the first sidewall **122**, the holes are or include blind holes on an inner surface of the first sidewall **122** that faces the second sidewall **124**. The holes are referred to as blind holes in that they do not extending through to an outer surface of the first sidewall **122**, and thereby are hidden from view when viewing the outer surface of the first wall **122**. For example, FIG. **4A** shows the outer surface of the first sidewall **122** without showing any of the blind holes disposed on the inner surface of the first sidewall **122**. When installed in a storage system (examples of which are described in further detail below with respect to FIGS. **10-13**), some or all of the outer surfaces of the first sidewalls **122** may be visible to a user of the storage system, such as after the storage system is installed. Configuring the holes of the first sidewall **122** to be blind holes, and in turn the outer surface of the first sidewall **122** to be smooth, may provide a more aesthetically pleasing appearance compared to if the holes extended through to the outer surface of the first sidewall **122** and were resultingly visible.

[0048] Additionally or alternatively, the second sidewall **124** may include the pin apertures **128**, which may be through holes, extending completely through the second sidewall **124** from an outer surface to an inner surface facing the first sidewall **122**. Since the pin apertures **128** extend completely through the second sidewall **124**, then the pin apertures **128** may be visible from the outer surface of the second sidewall **124**. For example, FIG. **4C** shows the pin apertures **128** on the outer surface of the second sidewall **124**. However, when implemented in a storage system (such as described in further detail below in FIGS. **10-14**), the outer surfaces of the second sidewalls **124** may not be visible to a user, in turn rendering the visible appearance of the pin apertures **128** on the outer surfaces of the second sidewalls **124** no less visually appealing.

[0049] In order to couple a pin **126** to the first and second sidewalls **122**, **124** via the holes, the pin **126** may be inserted into a pin aperture **128** from an outer surface of the second sidewall **124**, through an inner surface of the second sidewall **124**, and through to a corresponding blind hole in the first sidewall **122**. As mentioned, the pins **126** may be, for example, press fit into place and/or may be secured with an adhesive such as glue in some implementations. The plurality of pins **126**, pin apertures **128**, and blind holes may be spaced apart along the pilaster **102** and sidewalls **122**,

124 from top to bottom at regular intervals. Additionally or alternatively, the pins **126**, pin apertures **128**, and blind holes may be spaced along the pilaster **102** and sidewalls **122**, **124** irregularly. As illustrated in more detail with respect to FIGS. **5** and **6**, the pins **126** may be spaced apart, for example, to receive a hook **110** and notch **112** of a bracket **104** such that one or more brackets **104** can be installed onto a pilaster **102** and used to mount an accessory component (shown in later figures).

[0050] The mounting apertures **130** may be, for example, through holes, and may be disposed in the base **120**, extending through the base and configured to receive a fastener such as a screw or nail. Multiple mounting apertures may be disposed in the base apart from each other to secure the entire length of the pilaster **102** to, for example, a cabinet wall (such as a wall of cabinet **136** shown in FIG. **12**).

[0051] FIGS. **5**, **6**, and **7A-7C** illustrate additional views of the bracket **104** assembled and mounted on to the pilaster **102**.

[0052] FIGS. **8** and **9** illustrate brackets **104** installed on a rail **132**. The brackets **104** may be mounted on the rail **132** and/or any sort of component used to mount an item on the pilaster **102**. Multiple brackets **104** may be installed on the rail **132**, for example, to provide points of contact and installation with multiple corresponding pilasters **102**. The rail **132**, for example, may be used to allow an additionally installed component or item (such as a drawer or a shelf as shown in later figures) to slide. The bracket **104** may be mounted to the rail **132** via the pin **114** and screw **118** and/or aperture **116**.

[0053] FIGS. **10-12** illustrates multiple brackets **104**, rails **132**, and pilasters **102** assembled together to form, for example, a storage system utilizing the pilaster system **100** to hang and arrange a drawer **134** in a cabinet **136**. As shown in FIGS. **10-12**, a symmetrical and/or reversed geometry of the bracket **104** and pilaster **102** shown in FIGS. **1-9** may be used to create two halves of the system. FIGS. **13** and **14** illustrate further configurations of multiple brackets, rails **132**, and pilasters **102** assembled together to form, for example, a storage system utilizing the pilaster system **100** to hang and arrange multiple drawers **138**, **140** in a cabinet, such as the cabinet **136** in FIG. **13**.

[0054] Additionally, of note, FIGS. **10-13** show front perspective views of example pilaster systems **100** integrated with one or more components of a storage system, such as rails **132**, drawers **134**, **138**, **140**, and/or cabinetry **136**. On the other hand, FIG. **14** shows a back or rear perspective view of a storage system, as previously described. In such front perspective views, the blind holes on the inner surfaces of the first sidewalls **122** are not visible, as illustrated in FIGS. **10-13**. In contrast, the pin apertures **128** on the outer surfaces of the second sidewalls **124** are visible from the back or rear view of the storage system, as illustrated in FIG. **14**.

[0055] FIGS. **15A-20** illustrate other examples of a bracket. For the sake of brevity, features similar to what has been discussed above may not be repeated. Also, a person of ordinary skill in the art will understand the features discussed below with respect to FIGS. **15A-20** may be incorporated, as desired and/or needed, into the examples of the bracket shown in FIGS. **1-14**, including, but not limited to, the locking structure of the notch **112**, the plurality of apertures **116** on the second flange **108**, and the arrangement of the first flange **106** relative to the second flange **108** (e.g., shown in FIGS. **15B** and **17B**) discussed in greater detail below.

[0056] As one non-limiting example, as shown in FIGS. **15A-15C**, the second flange **108** may have a plurality of apertures **116**, which may be threaded and/or sized to receive a screw and/or other components for securing an item on the pilaster **102**. Providing the second flange **108** with a plurality of apertures **116** is advantageous for allowing the second flange **108** to accommodate varying mounting requirements of different items. The number and arrangement of the plurality of apertures **116** may be varied, as desired and/or needed, without departing from the scope of the present disclosure.

[0057] In a first example arrangement as shown in FIGS. **15A**, **17A**, the first flange **106** is on the

left and the second flange **108** is on the right, from the perspective shown in the figures. In a second example arrangement as shown in FIGS. **15B**, **17B**, the first flange **106** is on the right and the second flange **108** is on the left, from the perspective shown in the figures. It will be appreciated that the arrangement/orientation of the first flange **106** relative to the second flange **108**, and their respective orientations may be varied, as desired and/or needed, without departing from the scope of the present disclosure, for different mounting requirements.

[0058] Referring to FIGS. **15A-20**, for example, the notch **112** of the bracket **104** has a locking structure configured for providing better/stable engagement between the bracket **104** and the pin **126** of the pilaster **102**, thereby providing stronger support for larger items (e.g., drawers) with more weight. As shown, the locking structure includes a curved portion **113** and a substantially flat portion **115**, with a transition edge **117** disposed between the curved portion **113** and the substantially flat portion **115**. The curved portion **113** may be configured to curve along a circumferential surface of the pin **126** of the pilaster **102** when the pin **126** is received in the notch **112** for coupling the bracket **104** to the pin **126**. The transition edge **117** is configured to be a stop that reduces the likelihood of disengagement of the notch **112** from the pin **126**. It will be appreciated that the configuration and location of the locking structure may be varied, as desired and/or needed, without departing from the scope of the present disclosure, as long as the locking structure is configured to reduce the likelihood of disengagement of the notch **112** from the pin **126** (e.g., the substantially flat portion **115** may be replaced with an uneven/sloped portion).

[0059] The example pilaster system **100** and/or storage systems shown in FIGS. **1-14** are merely examples. Other examples may include additional, different, or fewer components. Additionally, storage systems including a cabinet, one or more drawers, and/or one or more rails as illustrated in FIGS. **10-14** are just one type of application for which the pilaster systems **100** described herein may be utilized. Various other applications utilizing the pilaster system **100** are possible.

[0060] To clarify the use of and to hereby provide notice to the public, the phrases “at least one of <A>, , . . . and <N>” or “at least one of <A>, , . . . <N>, or combinations thereof” or “<A>, , . . . and/or <N>” are defined by the Applicant in the broadest sense, superseding any other implied definitions hereinbefore or hereinafter unless expressly asserted by the Applicant to the contrary, to mean one or more elements selected from the group comprising A, B, . . . and N. In other words, the phrases mean any combination of one or more of the elements A, B, . . . or N including any one element alone or the one element in combination with one or more of the other elements which may also include, in combination, additional elements not listed. Unless otherwise indicated or the context suggests otherwise, as used herein, “a” or “an” means “at least one” or “one or more.”

[0061] While various embodiments have been described, it will be apparent to those of ordinary skill in the art that many more embodiments and implementations are possible. Accordingly, the embodiments described herein are examples, not the only possible embodiments and implementations.

[0062] The subject-matter of the disclosure may also relate, among others, to the following aspects:

[0063] A first aspect includes a pilaster system that includes: a pilaster, the pilaster including a plurality of pins spaced apart from each other along a length of the pilaster; and a bracket, the bracket including a hook and a notch, wherein the hook is configured to engage with a first one of the plurality of pins and the notch is configured to engage with a second one of the plurality of pins.

[0064] A second aspect includes the first aspect, and further includes wherein the pilaster includes a base, a first sidewall, and a second sidewall, wherein the first sidewall and the second sidewall extend out from the base, the first sidewall extending parallel to the second sidewall.

[0065] A third aspect includes the second aspect, and further includes wherein the plurality of pins extend from the first sidewall to the second sidewall.

[0066] A fourth aspect includes any of the second or third aspects, and further includes wherein the

first sidewall includes a plurality of blind holes and the second sidewall includes a plurality of through holes, each one of the plurality of pins extending through one of the plurality of through holes and into one of the plurality of blind holes.

[0067] A fifth aspect includes any of the first through fourth aspects, and further includes wherein the bracket includes a first flange, and a second flange, wherein the first flange and the second flange are perpendicular to each other, the hook and notch disposed on the first flange.

[0068] A sixth aspect includes the fifth aspect, and further includes an accessory component, wherein the accessory component attaches to the second flange of the bracket.

[0069] A seventh aspect includes the sixth aspect, and further includes wherein the second flange includes an aperture and a pin, the accessory component attached to the second flange via the pin and a fastener extending through the accessory component and aperture of the bracket.

[0070] An eighth aspect includes the seventh aspect, and further includes wherein the accessory component is a shelf or drawer.

[0071] A ninth aspect includes the eighth aspect, and further includes a plurality of pilasters and a plurality of brackets, each one of the plurality of brackets attached to a different area of the accessory component and configured to engage with a corresponding one of the plurality of pilasters.

[0072] A tenth aspect includes any of the first through ninth aspects, and further includes wherein the hook is disposed at a first end of the bracket, the notch disposed closer to a second end of the bracket than the first end, wherein the first end and second end are opposite each other.

[0073] An eleventh aspect includes any of the first through tenth aspects, and further includes wherein the notch further comprises a locking structure configured for providing stable engagement between the bracket and the second one of the plurality of pins.

[0074] A twelfth aspect includes a pilaster system comprising: a pilaster, the pilaster including a first pin and a second pin extending between two sidewalls of the pilaster; and a bracket, the bracket including a first flange, a second flange connected to the first flange, a hook extending from an end of the first flange, and a notch disposed within the first flange, wherein the hook is configured to engage with the first pin and the notch is configured to engage with the second pin.

[0075] A thirteenth aspect includes the twelfth aspect, and further includes wherein the pilaster includes a base, a first sidewall, and a second sidewall, wherein the first sidewall and the second sidewall extend out from the base, the first sidewall extending parallel to the second sidewall.

[0076] A fourteenth aspect includes the thirteenth aspect, and further includes wherein the first pin and the second pin extend from the first sidewall to the second sidewall.

[0077] A fifteenth aspect includes any of the thirteenth or fourteenth aspects, and further includes wherein the first sidewall includes a plurality of blind holes and the second sidewall includes a plurality of through holes, each one of the first pin and second pin extending through one of the plurality through holes and into one of the plurality of blind holes.

[0078] A sixteenth aspect includes any of the twelfth through fifteenth aspects, and further includes wherein the first flange and the second flange are perpendicular to each other.

[0079] A seventeenth aspect includes the sixteenth aspect, and further includes an accessory component, wherein the accessory component attaches to the second flange of the bracket.

[0080] An eighteenth aspect includes the seventeenth aspect, and further includes wherein the second flange includes an aperture and a pin, the accessory component attached to the second flange via the pin and a fastener extending through the accessory component and aperture of the bracket.

[0081] A nineteenth aspect includes any of the seventeenth or eighteenth aspects, and further includes a wall, where the pilaster and bracket are configured to adjustably attach the accessory component to the wall.

[0082] A twentieth aspect includes any of the twelfth through nineteenth aspects, and further includes wherein the notch further comprises a locking structure configured for providing stable

engagement between the bracket and the second pin.

[0083] A twenty-first aspect includes a pilaster system comprising: a pilaster, the pilaster including a first pin and a second pin extending between two sidewalls of the pilaster; and a bracket, the bracket including a hook extending from an end of the bracket, and a notch disposed within the bracket, wherein the hook is configured to engage with the first pin and the notch is configured to engage with the second pin.

[0084] A twenty-second aspect includes the twenty-first aspect, and further includes a wall, where the pilaster and bracket are configured to adjustably attach an accessory component to the wall.

[0085] A twenty-third aspect includes any of the twenty-first or twenty-second aspects, and further includes wherein the notch further comprises a locking structure configured for providing stable engagement between the bracket and the second pin.

[0086] In addition to the features mentioned in each of the independent aspects enumerated above, some examples may show, alone or in combination, the optional features mentioned in the dependent aspects and/or as disclosed in the description above and shown in the figures.

Claims

1. A pilaster system comprising: a pilaster, the pilaster including a plurality of pins spaced apart from each other along a length of the pilaster; and a bracket, the bracket including a hook and a notch, wherein the hook is configured to engage with a first one of the plurality of pins and the notch is configured to engage with a second one of the plurality of pins.
2. The pilaster system of claim 1, wherein the pilaster includes a base, a first sidewall, and a second sidewall, wherein the first sidewall and the second sidewall extend out from the base, the first sidewall extending parallel to the second sidewall.
3. The pilaster system of claim 2, wherein the plurality of pins extend from the first sidewall to the second sidewall.
4. The pilaster system of claim 2, wherein the first sidewall includes a plurality of blind holes and the second sidewall includes a plurality of through holes, each one of the plurality of pins extending through one of the plurality of through holes and into one of the plurality of blind holes.
5. The pilaster system of claim 1, wherein the bracket includes a first flange, and a second flange, wherein the first flange and the second flange are perpendicular to each other, the hook and notch disposed on the first flange.
6. The pilaster system of claim 5 further comprising an accessory component, wherein the accessory component attaches to the second flange of the bracket.
7. The pilaster system of claim 6, wherein the second flange includes an aperture and a pin, the accessory component attached to the second flange via the pin and a fastener extending through the accessory component and aperture of the bracket.
8. The pilaster system of claim 7, wherein the accessory component is a shelf or drawer.
9. The pilaster system of claim 8, further comprising a plurality of pilasters and a plurality of brackets, each one of the plurality of brackets attached to a different area of the accessory component and configured to engage with a corresponding one of the plurality of pilasters.
10. The pilaster system of claim 1, wherein the hook is disposed at a first end of the bracket, the notch disposed closer to a second end of the bracket than the first end, wherein the first end and second end are opposite each other.
11. The pilaster system of claim 1, wherein the notch further comprises a locking structure configured for providing stable engagement between the bracket and the second one of the plurality of pins.
12. A pilaster system comprising: a pilaster, the pilaster including a first pin and a second pin extending between two sidewalls of the pilaster; and a bracket, the bracket including a first flange, a second flange connected to the first flange, a hook extending from an end of the first flange, and a

notch disposed within the first flange, wherein the hook is configured to engage with the first pin and the notch is configured to engage with the second pin.

13. The pilaster system of claim 12, wherein the pilaster includes a base, a first sidewall, and a second sidewall, wherein the first sidewall and the second sidewall extend out from the base, the first sidewall extending parallel to the second sidewall.

14. The pilaster system of claim 13, wherein the first pin and the second pin extend from the first sidewall to the second sidewall.

15. The pilaster system of claim 13, wherein the first sidewall includes a plurality of blind holes and the second sidewall includes a plurality of through holes, each one of the first pin and second pin extending through one of the plurality through holes and into one of the plurality of blind holes.

16. The pilaster system of claim 12, wherein the first flange and the second flange are perpendicular to each other.

17. The pilaster system of claim 16 further comprising an accessory component, wherein the accessory component attaches to the second flange of the bracket.

18. The pilaster system of claim 17, wherein the second flange includes an aperture and a pin, the accessory component attached to the second flange via the pin and a fastener extending through the accessory component and aperture of the bracket.

19. The pilaster system of claim 17 further comprising a wall, wherein the pilaster and bracket are configured to adjustably attach the accessory component to the wall.

20. The pilaster system of claim 12, wherein the notch further comprises a locking structure configured for providing stable engagement between the bracket and the second pin.

21. A pilaster system comprising: a pilaster, the pilaster including a first pin and a second pin extending between two sidewalls of the pilaster; and a bracket, the bracket including a hook extending from an end of the bracket, and a notch disposed within the bracket, wherein the hook is configured to engage with the first pin and the notch is configured to engage with the second pin.

22. The pilaster system of claim 21 further comprising a wall, wherein the pilaster and bracket are configured to adjustably attach an accessory component to the wall.

23. The pilaster system of claim 21, wherein the notch further comprises a locking structure configured for providing stable engagement between the bracket and the second pin.
