

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250269804

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

Atting Thorin; Samuel et al.

VERTICAL HANGING BICYCLE CARRIER

Abstract

A vehicle mounted load carrier can include a hub, a support member, a tilt release mechanism, and a tilt memory actuator. The support member rotatably can couple to the hub. The tilt release mechanism can couple to the support member. The tilt release mechanism can include a locking arm configured to move between a locked configuration and a released configuration. In the locked configuration the support member can be fixed relative to the hub. In the released configuration the support member can rotate between a first position and a second position. The tilt memory actuator can moveably couple to the hub or the support member. The tilt memory actuator can be configured to maintain the locking arm in the released configuration when the locking arm is actuated from the locked configuration to the released configuration.

Inventors: Atting Thorin; Samuel (Jönköping, SE), Saladi; Praveen (Jönköping, SE), Le; Tam (Värnamo, SE), Hjulfors; Jimmy (Jönköping, SE), Berg; Oliver (Värnamo, SE), AHMETSPAHC; Vanesa (Värnamo, SE)

Applicant: Thule Sweden AB (HILLERSTORP, SE)

Family ID: 1000008488840

Appl. No.: 19/060121

Filed: February 21, 2025

Foreign Application Priority Data

DE 20 2024 100 872.3

Feb. 23, 2024

Related U.S. Application Data

us-provisional-application US 63634143 20240415

Publication Classification

Int. Cl.: B60R9/10 (20060101); **B25H1/00** (20060101); **B60R9/06** (20060101); **B62H3/04** (20060101)

U.S. Cl.:

CPC B60R9/10 (20130101); **B25H1/0014** (20130101); **B60R9/06** (20130101); **B62H3/04** (20130101);

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS [0001] This application claims priority to U.S. Provisional Application No. 63/634,143, filed Apr. 15, 2024, and German Utility Model Patent Application No. 20 2024 100 872.3, filed Feb. 23, 2024, which is hereby incorporated herein in its entirety by reference.

BACKGROUND

Field

[0002] The present disclosure relates to load carriers. More specifically, embodiments of the present disclosure relate to vehicle mounted load carriers, for example, bicycle carriers.

Background

[0003] Devices for carrying equipment on a vehicle can be used to transport the equipment from one place to another. In some examples, the load carrier can be secured to the vehicle safely and conveniently via a hitch, typically attached to the rear of the vehicle. Various mechanisms can be used to secure a load (e.g., a bicycle) to the load carrier, for example, straps and securement arms. However, in certain cases these devices can be cumbersome, unstable, difficult to use, limit the capacity of the load carrier, limit the size of bicycle wheel that can be secured to the load carrier, or fail to securely fasten or balance the bicycle to the load carrier in a sufficient manner. Further, load carriers attached to the rear of a vehicle can block access to trunks or rear vehicle doors.

[0004] Other load carrier systems can include carrying arrangements for carrying, for example, a license plate or a lighting assembly. These load carrier systems may include foldable load support platforms on which the carrying arrangements are fastened. If the load support platform is transferred from a use position into a stowage position, this can lead to an object fastened on the carrying arrangement no longer being visible or protruding from the load support platform in an unfavorable manner.

BRIEF SUMMARY

[0005] Accordingly, there is a need to provide a load carrier to accommodate bicycle wheels of all sizes, assist in tilting between configurations, and improve user operation and safety of the tilt operation between in-use and loading configurations.

[0006] In some embodiments, a vehicle mounted load carrier includes a hub, a support member, a tilt release mechanism, and a tilt memory actuator. In some embodiments, the support member can be rotatably coupled to the hub. In some embodiments, the tilt release mechanism can couple to the support member. In some embodiments, the tilt release mechanism can include a locking arm configured to move between a locked configuration and a released configuration. In some embodiments, in the locked configuration the support member is fixed relative to the hub. In some embodiments, in the released configuration the support member can rotate between a first position and a second position. In some embodiments, the tilt memory actuator can moveably couple to the hub or the support member and configured to maintain the locking arm in the released configuration when the locking arm is actuated from the locked configuration to the released configuration.

[0007] In some embodiments, a plurality of recesses can be formed in the hub or the support member. In some embodiments, the tilt memory actuator can move between a closed configuration and an open configuration. In some embodiments, in the closed configuration the tilt memory actuator is disposed over at least a portion of a first recess of the plurality of recesses. In some embodiments, the tilt memory actuator can linearly translate between the closed configuration and the open configuration. In some embodiments, in the closed configuration, the tilt memory actuator entirely covers the first recess.

[0008] In some embodiments, the tilt memory actuator can be biased into the closed configuration. In some embodiments, the locking arm can be disposed in the first recess in the locked configuration. In some embodiments, the plurality of recesses can be formed in the hub.

[0009] In some embodiments, the tilt memory actuator can include an actuating surface and a platform surface. In some embodiments, the platform surface can be configured to maintain the locking arm in the released configuration. In some embodiments, the locking arm can be configured to contact the actuating surface of the tilt memory actuator when the support arm is rotated in a first direction to move the tilt memory actuator into the open configuration. In some embodiments, the platform surface can be configured to maintain the locking arm in the released configuration when the support arm is rotated in a second direction opposite the first direction. In some embodiments, the platform surface is spaced apart from and disposed above a hub surface of the hub.

[0010] In some embodiments, the tilt memory actuator can moveably couple to the hub. In some embodiments, the support member can be configured to rotate to a third position different from the first position and the second position. In some embodiments, the tilt memory actuator can include a plate and a protrusion. In some embodiments, the protrusion can be configured to maintain the locking arm in the released configuration. In some embodiments, a plurality of recesses can be formed in the hub. In some embodiments, the tilt memory actuator can move between a closed configuration and an open configuration. In some embodiments, in the closed configuration the protrusion is disposed above at least one recess of the plurality of recesses.

[0011] In some embodiments, a load carrier includes a hub, a support member, and a first cover. In some embodiments, the hub can include a channel formed in the hub. In some embodiments, the channel can have a first end and a second end. In some embodiments, the support member can moveably couple to the hub and be disposed in the channel. In some embodiments, the first cover can couple to the hub or the support member. In some embodiments, the first cover can be configured to cover a portion of the channel between the first end and the support member when the support member is rotated between a first support position and a second support position.

[0012] In some embodiments, a second cover can be configured to cover a portion of the channel between the second end and the support member. In some embodiments, the first cover can couple to the hub and biased towards the support member. In some embodiments, the first cover can contact the support member and can slide along the support member.

[0013] In some embodiments, the first cover can slide along the hub or the support member. In some embodiments, the first cover can slide along the support member. In some embodiments, the first cover can couple to the hub. In some embodiments, the first cover can include a first sidewall disposed on a first side of the support member and a second sidewall disposed on a second side of the support member opposite the first side.

[0014] In some embodiments, the first cover can rotatably couple to the hub. In some embodiments, movement of the support member from a first position to a second position can move the first cover. In some embodiments, the load carrier can be a bicycle carrier.

[0015] In some embodiments, a bicycle carrier includes a wheel hoop arm and a wheel insert. In some embodiments, the wheel hoop arm can include a first end and a second end. In some embodiments, the wheel hoop arm can be configured to receive and support a bicycle wheel. In some embodiments, the wheel insert can removably couple the first end of the wheel hoop arm and

be configured to reduce a wheel receiving length of the wheel hoop arm.

[0016] In some embodiments, the wheel insert can include a plurality of flanges configured to receive a perimeter rim of the wheel hoop arm. In some embodiments, a first flange of the plurality of flanges can couple with the perimeter rim of the wheel hoop arm. In some embodiments, an outer wall of the wheel insert can include a profile configured to match a perimeter rim profile of the wheel hoop arm.

[0017] In some embodiments, the wheel insert can include a first support edge configured to support a first wheel having a first diameter. In some embodiments, the wheel insert can include a second support edge configured to support a second wheel having a second diameter different from the first diameter. In some embodiments, a first wheel receiving length can extend from the first support edge to the second end of the wheel hoop arm. In some embodiments, a second wheel receiving length can extend from the second support edge to the second end of the wheel hoop arm. In some embodiments, the second wheel receiving length can be less than the first wheel receiving length.

[0018] In some embodiments, a wall can extend between the first support edge and the second support edge. In some embodiments, the wall, the first support edge, and a portion of the wheel hoop arm can form a wheel receiving channel for the bicycle wheel. In some embodiments, a second wheel insert can couple to the second end of the wheel hoop arm and be configured to further reduce the wheel receiving length of the wheel hoop arm.

[0019] In some embodiments, a vehicle mounted load carrier includes a hub, a support member, and a tilt-assist device. In some embodiments, the support member can rotatably couple to the hub. In some embodiments, the support member can be configured to rotate between a first position and a second position. In some embodiments, the tilt-assist device can couple to the hub and the support member. In some embodiments, the tilt-assist device can be configured to control a rate of rotation of the support member between the first position and the second position, to assist the support member moving from the second position to the first position, or both.

[0020] In some embodiments, the tilt-assist device can be arranged on a first side of the support member. In some embodiments, an aperture can be formed through the support member, and the tilt-assist device extends through the aperture.

[0021] In some embodiments, the tilt-assist device can include a damping unit and a spring unit. In some embodiments, the damping unit can be arranged parallel to the spring unit. In some embodiments, the damping unit can be arranged on a first side of the support member, and the spring unit can be arranged on a second side of the support member opposite the first side.

[0022] In some embodiments, the tilt-assist device can include a gas spring. In some embodiments, the gas spring can include an actuator. In some embodiments, the gas spring can assist rotation of the support member from the second position to the first position when the actuator is actuated.

[0023] In some embodiments, the tilt-assist device can include a sensor to detect a load on the support member. In some embodiments, the tilt-assist device can adjust the rate of rotation or a force provided to assist the support member moving from the second position to the first position based on the load.

[0024] In some embodiments, the tilt-assist device can be configured to reduce vibration in the support member during transportation by the vehicle.

[0025] In some embodiments, a bicycle carrier includes a support member and a wheel hoop arm. In some embodiments, the wheel hoop arm can couple to the support member and be configured to receive a bicycle wheel. In some embodiments, the wheel hoop arm can include an angled support, a first coupling portion, a second coupling portion, and a recess portion. In some embodiments, the angled support can extend away from the support member. In some embodiments, the first coupling portion and the second coupling portion can extend from the angled support and be configured to receive and support the bicycle wheel. In some embodiments, the recess portion can be opposite the angled support and extend between the first and second coupling portions.

[0026] In some embodiments, the wheel hoop arm can be formed from a single bar. In some embodiments, the angled support can include a coupling bracket configured to couple to the support member. In some embodiments, the coupling bracket can include a plurality of angle position apertures to adjust an angle of the wheel hoop arm relative to the support member.

[0027] In some embodiments, the first coupling portion and the second coupling portion can be tapered. In some embodiments, the angled support member can extend at an acute angle relative to the support member. In some embodiments, the angled support and the recess can receive the wheel hub, the wheel spokes, or both.

[0028] In some embodiments, a bicycle carrier can include a support member and a wheel hoop arm. In some embodiments, the wheel hoop arm can couple to the support member and be configured to receive a bicycle wheel. In some embodiments, the wheel hoop arm can include a coupling member configured to couple with the support member in a plurality of angular orientations.

[0029] In some embodiments, the coupling member can include a plurality of angle position apertures. In some embodiments, the wheel hoop arm can have a first orientation when a fastener extends through a first aperture of the plurality of angle position apertures to couple the wheel hoop arm with the support member. In some embodiments, the wheel hoop arm can have a second orientation different from the first orientation when the fastener extends through a second aperture of the plurality of angle position apertures to couple the wheel hoop arm with the support member.

[0030] In some embodiments, a protruding bolt can be configured to secure a fastening member to a support member. In some embodiments, the protruding bolt includes a coupling shaft, a spacing shaft, and a bolt head. In some embodiments, the coupling shaft can be configured to couple to the support member. In some embodiments, the spacing shaft can extend away from the coupling shaft. In some embodiments, the bolt head can be spaced apart from the coupling shaft by the spacing shaft. In some embodiments, the fastening member can be disposed around the spacing shaft when the fastening member is secured to the protruding bolt.

[0031] In some embodiments, a strap for securing equipment to an equipment carrier can include a first end, a second end, and a plurality of apertures. In some embodiments, the first end can include a coupling aperture. In some embodiments, the second end can include a grip portion. In some embodiments, the plurality of apertures can be formed through the strap. In some embodiments, each aperture of the plurality of apertures can include a countersunk surface.

[0032] In some embodiments, an assembly for securing equipment to an equipment carrier can include the protruding bolt and the strap.

[0033] In some embodiments, an assembly for securing equipment to an equipment carrier can include a support member, a protruding bolt, and a strap. In some embodiments, the protruding bolt can couple to the support member. In some embodiments, the protruding bolt can include a coupling shaft, a spacing shaft, and a bolt head spaced apart from the support member by the spacing shaft. In some embodiments, the strap can include a plurality of apertures. In some embodiments, at least one of the plurality of apertures can removably couple with the protruding bolt.

[0034] In some embodiments, the strap further can include a first end and a second end. In some embodiments, the first end can couple to the support member. In some embodiments, a coupling aperture can be formed through the first end of the strap and be configured to receive a bolt that couples the strap to the support member. In some embodiments, the second end can include a grip portion.

[0035] In some embodiments, each aperture of the plurality of apertures can include a countersunk surface. In some embodiments, the spacing shaft can be disposed within an aperture of the plurality of aperture of the strap and the strap can be disposed between the bolt head and the support member when the strap is removably coupled to the protruding bolt. In some embodiments, the spacing shaft can include a square cross-sectional shape.

[0036] In some embodiments, a bicycle carrier includes an upper support, a lower support, and a wheel cradle. In some embodiments, the upper support can be configured to secure a first bicycle wheel to the bicycle carrier. In some embodiments, the lower support can be disposed below the upper support. In some embodiments, the wheel cradle can couple to the lower support and be configured to secure a second bicycle wheel to the bicycle carrier. In some embodiments, the wheel cradle can be formed from bent wire.

[0037] In some embodiments, the wheel cradle can have triangular shape. In some embodiments, the wheel cradle can taper from a wheel receiving end to a coupling portion with the lower support.

[0038] In some embodiments, a vehicle mounted load carrier includes a hub, a support member, and a tilt-release mechanism. In some embodiments, the hub can include a plurality of recesses formed in the hub. In some embodiments, the support member can rotatably couple to the hub. In some embodiments, the tilt-release mechanism can be configured to engage a first recess of the plurality of recesses formed in the hub to lock a relative position between the support arm and the hub. In some embodiments, the tilt release mechanism can include an actuator coupled to the support member.

[0039] In some embodiments, the actuator can be a strap, a button, a knob, a lever, or a handle. In some embodiments, the support member can include a first end rotatably coupled to the hub and a second end opposite the first end. In some embodiments, the actuator can be disposed along the support member and be spaced apart from the first end and the second end. In some embodiments, the locking arm can be biased towards the hub.

[0040] In some embodiments, the tilt-release mechanism can include a locking arm configured to move between a locked configuration and a released configuration. In some embodiments, the tilt-release mechanism can include a linkage coupled to the actuator and the locking arm. In some embodiments, in the locked configuration the locking arm can be received in one of the plurality of recesses of the hub and prevents rotation of the support arm relative to the hub. In some embodiments, when the actuator is operated, the locking arm can translate out of the recess to the released configuration such that the support arm can rotate relative to the hub. In some embodiments, the linkage can be disposed within the support member.

[0041] In some embodiments, a vehicle mounted load carrier includes a support member and an equipment lock. In some embodiments, the support member can have a proximal end disposed toward a vehicle and a distal end disposed opposite the proximal end. In some embodiments, the equipment lock can couple to the support member and be configured to secure a cable to the support member. In some embodiments, the equipment lock can be disposed at the distal end of the support member.

[0042] In some embodiments, the lock can include a lock barrel, a lock protrusion coupled to the lock barrel, and a spring configured to bias the lock protrusion into a locked position. In some embodiments, a locking notch can be formed in an end of the cable. In some embodiments, the lock protrusion can engage the locking notch to secure the cable to the base when the lock is disposed in a locked position.

[0043] In some embodiments, a vehicle mounted load carrier includes a hub, a support member, and a safety pin. In some embodiments, the support member can rotatably couple to the hub and be configured to rotate between a first position and a second position. In some embodiments, the safety pin can be configured to be disposed through an aperture formed in the hub. In some embodiments, the safety pin can be configured to prevent rotation of the support member from the first position to the second position. In some embodiments, a pin cradle can couple to the hub and be configured to receive the safety pin and secure the safety pin to the base.

[0044] In some embodiments, the safety pin can be L-shaped. In some embodiments, the safety pin can include a shaft and a handle. In some embodiments, the handle can be received in the pin cradle to secure the handle to the hub. In some embodiments, the handle can be approximately perpendicular to the shaft.

[0045] In some embodiments, a safety wire can couple to the safety pin and the hub to secure the safety pin to the hub when the safety pin is not disposed through the aperture of the hub. In some embodiments, when the support member is in the second position, the support member can block the aperture in the hub. In some embodiments, the pin cradle can be configured to receive the safety pin when the safety pin is not disposed through the aperture of the hub.

[0046] In some embodiments, the bicycle carrier includes a support member and a bicycle work stand. In some embodiments, the support member can rotatably couple to a base. In some embodiments, the bicycle work stand can couple to the support member and be configured to support a bicycle.

[0047] In some embodiments, the support member can include a vertical arm and a horizontal arm. In some embodiments, the bicycle work stand can couple to the horizontal arm. In some embodiments, the bicycle work stand can rotatably couple to the support member and be moveable between a stowed position and an in-use position. In some embodiments, the bicycle work stand can extend away from the support member at an in-use angle such that a bicycle disposed on the work stand is disposed distally from the bicycle carrier.

[0048] In some embodiments, the bicycle work stand includes a support arm, a first support, and a second support. In some embodiments, the support arm can rotatably couple to the support member. In some embodiments, the first support can couple to a distal end of the support arm. In some embodiments, the second support can couple to the support arm below the first support. In some embodiments, the first support and the second support can be configured to contact the bicycle to support the bicycle.

[0049] In some embodiments, a groove can be formed in the first support to accommodate a seat component of the bicycle. In some embodiments, the second support can be configured to contact a seat post or a frame of the bicycle.

[0050] In some embodiments, a bicycle carrier includes a support member, a wheel hoop arm, and a wheel support. In some embodiments, the wheel hoop arm can couple to the support member and be configured to receive a bicycle wheel. In some embodiments, the wheel support can couple to the wheel hoop arm and contact the support member. In some embodiments, the wheel support can be configured to support the bicycle wheel.

[0051] In some embodiments, a vehicle mounted load carrier includes a base and a wheel assembly. In some embodiments, the base can be configured to transport a load. In some embodiments, the wheel assembly can couple to the base in at least one of a storage configuration and a transport configuration. In some embodiments, the wheel assembly can moveably couple to the base.

[0052] In some embodiments, the wheel assembly can include a wheel arm and a wheel. In some embodiments, the wheel arm can include a first end and a second end. In some embodiments, first end can rotatably couple to the base and the wheel can couple to the second end.

[0053] In some embodiments, a load carrier can include a carrying arrangement. In some embodiments, the carrying arrangement can be configured for carrying an object. In some embodiments, the object can be, for example, a license plate. In some embodiments, the object can be a lighting assembly. In some embodiments, the lighting assembly can include a tail light. In some embodiments, the carrying arrangement can be configured for carrying a plurality of objects, for example, for carrying a license plate and a lighting assembly. In some embodiments, the carrying arrangement can also be configured for carrying loads to be transported, for example a bicycle.

[0054] In some embodiments, the carrying arrangement includes a carrying portion for carrying the object and a supporting portion for supporting the carrying portion on the load carrier. In some embodiments, the supporting portion can be configured for supporting the carrying portion on a carrying frame of the load carrier or on a load support platform of the load carrier. In some embodiments, the carrying frame can be configured as described above in connection with other embodiments. In some embodiments, the load support platform can be configured as described

above in connection with other embodiments.

[0055] In some embodiments, the carrying portion can be arranged in an articulated manner on the supporting portion. In some embodiments, the carrying portion can, in relation to the supporting portion, be arranged pivotable in a first direction about an axis of rotation between a use position and a stowage position.

[0056] In some embodiments, the carrying arrangement includes a locking arrangement. In some embodiments, the locking arrangement can be configured such that the carrying portion is locked in a form-fitting manner at least in the use position and a pivoting movement of the carrying portion to or into the stowage position is only possible when the carrying portion is moved before and/or during the pivoting movement in a second direction which differs from the first direction.

[0057] In some embodiments, the second direction can be a direction along or parallel to the axis of rotation.

[0058] In some embodiments, the locking arrangement can be configured such that pivoting of the carrying portion in the first direction from the use position into the stowage position and/or vice versa is only possible by previous movement of the carrying portion into a release position. In some embodiments, on reaching the release position, a movement of the carrying portion in the first direction can be released.

[0059] In some embodiments, the carrying portion can be movable in relation to the supporting portion along the axis of rotation and/or translationally, and a movement of the carrying portion into the release position can take place by moving along the axis of rotation and/or a translational movement of the carrying portion relative to the supporting portion.

[0060] In some embodiments, the locking arrangement includes a first engaging portion and a second engaging portion. In some embodiments, the first engaging portion can be associated with the carrying portion. In some embodiments, the second engaging portion can be associated with the supporting portion. In some embodiments, the first engaging portion and the second engaging portion can be configured such that they can come into form-fitting engagement when the carrying portion is in the use position.

[0061] In some embodiments, the first engaging portion and the second engaging portion can be configured complementary.

[0062] In some embodiments, the first engaging portion or the second engaging portion includes a recess and the respective other engaging portion can include a projection, which can engage in a form-fitting manner.

[0063] In some embodiments, the first engaging portion and the second engaging portion can be configured in the manner of claws of a claw coupling. In some embodiments, the first engaging portion includes a recess, which extends in the radial direction with respect to the axis of rotation and is indented in the axial direction, and the second engaging portion includes a projection, which extends radially with respect to the axis of rotation and protrudes in the axial direction and/or which extends in the radial direction with respect to the axis of rotation.

[0064] In some embodiments, the locking arrangement can be configured such that the carrying portion is automatically locked when the use position is reached. In some embodiments, the locking arrangement can be configured such that the first engaging portion engages with the second engaging portion when the use position is reached. In some embodiments, the first engaging portion can be pretensioned by means of an urging member in the direction of the second engaging portion. In some embodiments, the urging member includes a spring, for example a spiral spring.

[0065] In some embodiments, a license plate holding arrangement includes a carrying arrangement and a license plate holder. In some embodiments, the carrying arrangement can be a carrying arrangement as described above. In some embodiments, the carrying arrangement includes one or more features as described herein in connection with carrying arrangements. In some embodiments, the license plate holder can be fastened to the carrying arrangement.

[0066] In some embodiments, a load carrier includes a carrying frame, a load support platform and

a carrying arrangement. In some embodiments, the supporting portion of the carrying arrangement can be attached to the load support platform. For example, the supporting portion can be attached to a rear portion of the load support platform.

[0067] Implementations of any of the techniques described above may include a system, a method, a process, a device, and/or an apparatus. The details of one or more implementations are set forth in the accompanying drawings and the description below. Other features will be apparent from the description and drawings, and from the claims.

[0068] Further features and advantages of the invention, as well as the structure and operation of various embodiments of the invention, are described in detail below with reference to the accompanying drawings. It is noted that the invention is not limited to the specific embodiments described herein. Such embodiments are presented herein for illustrative purposes only. Additional embodiments will be apparent to persons skilled in the relevant art(s) based on the teachings contained herein.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0069] The accompanying drawings, which are incorporated herein and form a part of the specification, illustrate the embodiments and, together with the description, further serve to explain the principles and to enable a person skilled in the relevant art(s) to make and use the embodiments. Objects and advantages of illustrative, non-limiting embodiments will become more apparent by describing them in detail with reference to the attached drawings.

[0070] FIG. 1 illustrates a perspective view of a bicycle carrier coupled to a vehicle and supporting bicycles, according to an embodiment.

[0071] FIG. 2 illustrates a perspective view of a bicycle carrier in an in-use configuration, according to an embodiment.

[0072] FIG. 3 illustrates a side view of a bicycle carrier rotatable between an in-use configuration and a loading configuration, according to an embodiment.

[0073] FIGS. 4A-4C illustrate perspective views of a hub for a load carrier including a tilt memory actuator, with the hub in a plurality of positions, according to an embodiment.

[0074] FIGS. 5A-5D illustrate side views of a hub for a load carrier including the tilt memory actuator of FIGS. 4A-4C, with the tilt memory actuator in a plurality of positions, according to an embodiment.

[0075] FIG. 6A illustrates a perspective view of a tilt memory actuator, according to an embodiment.

[0076] FIG. 6B illustrates a cutaway perspective view of the tilt memory actuator of FIG. 6A, according to an embodiment.

[0077] FIGS. 7A-7B illustrate perspective views of the tilt memory actuator of FIG. 6A, according to an embodiment.

[0078] FIGS. 8A-8B illustrate perspective views of a tilt memory actuator, according to an embodiment.

[0079] FIGS. 9A-9C illustrate perspective views of a hub for a load carrier including covers, according to an embodiment.

[0080] FIG. 10A illustrates a side view of a hub for a load carrier with covers in an open configuration, according to an embodiment.

[0081] FIGS. 10B-10C illustrate perspective views a hub for a load carrier with covers in an open configuration, according to an embodiment.

[0082] FIG. 11 illustrates a perspective view of a wheel hoop arm including a wheel insert, according to an embodiment.

[0083] FIG. **12** illustrates a perspective view of the wheel insert of FIG. **11**, according to an embodiment.

[0084] FIGS. **13A-13B** illustrate perspective views of different sized bicycle wheels supported by a wheel insert and a wheel hoop arm, according to an embodiment.

[0085] FIGS. **14A-14E** illustrate perspective views of wheel hoop arms, according to embodiments.

[0086] FIG. **15** illustrates a perspective view of a load carrier including a tilt-assist device, according to an embodiment.

[0087] FIGS. **16A-16B** illustrate side views of a load carrier including a tilt-assist device in an in-use configuration and a loading configuration, according to an embodiment.

[0088] FIG. **17** illustrates a front view of a load carrier including a tilt-assist device, according to an embodiment.

[0089] FIGS. **18A-18B** illustrate perspective views of a load carrier including a tilt-assist device in an in-use configuration and a loading configuration, according to an embodiment.

[0090] FIG. **19** illustrates a cutaway perspective view of a load carrier including a tilt-assist device, according to an embodiment.

[0091] FIGS. **20A-20C** illustrate perspective views of a load carrier including a tilt-assist device, according to embodiments.

[0092] FIGS. **21A-21D** illustrate wheel hoop arms, according to embodiments.

[0093] FIGS. **22A-22B** illustrate front views of wheel hoop arms at a first orientation relative to a support member, according to an embodiment.

[0094] FIGS. **23A-23B** illustrate front views of wheel hoop arms at a second orientation relative to a support member, according to an embodiment.

[0095] FIG. **24** illustrates an exploded view of a strap assembly, according to an embodiment.

[0096] FIG. **25** illustrates a perspective view of a strap assembly coupled to a support member, according to an embodiment.

[0097] FIG. **26** illustrates a perspective view of a wheel cradle with a strap assembly, according to an embodiment.

[0098] FIG. **27** illustrates a side view of a tilt-release actuator, according to an embodiment.

[0099] FIG. **28** illustrates an exploded perspective view of the tilt-release actuator of FIG. **27**, according to an embodiment.

[0100] FIG. **29** illustrates a cutaway side view of a tilt-release mechanism, according to an embodiment.

[0101] FIG. **30** illustrates a perspective view of a locking arm of the tilt-release mechanism of FIG. **29**, according to an embodiment.

[0102] FIG. **31** illustrates a perspective view of an equipment lock coupled to a support member with a cable secured to the equipment lock, according to an embodiment.

[0103] FIG. **32** illustrates a perspective view of an equipment lock, according to an embodiment.

[0104] FIG. **33** illustrates a perspective view of a hub with a safety pin for a load carrier in a release configuration, according to an embodiment.

[0105] FIGS. **34A-34B** illustrate perspective views of the safety pin of FIG. **33** in a blocking configuration, according to an embodiment.

[0106] FIG. **35** illustrates a perspective view of a bicycle work stand in an in-use configuration, according to an embodiment.

[0107] FIG. **36** illustrates a perspective view of a bicycle work stand hub, according to an embodiment.

[0108] FIG. **37** illustrates a perspective view of a bicycle supported in a standing position by a bicycle carrier, according to an embodiment.

[0109] FIG. **38** illustrates a perspective view of a bicycle supported in a standing position by a bicycle carrier, according to an embodiment.

[0110] FIG. **39** illustrates a perspective view of a wheel support, according to an embodiment.

[0111] FIG. **40** illustrates a cutaway perspective view of a wheel assembly for a load carrier, according to an embodiment.

[0112] FIG. **41** illustrates a perspective view of a wheel assembly for a load carrier, according to an embodiment.

[0113] FIG. **42** illustrates a perspective view of a wheel assembly for a load carrier, according to an embodiment.

[0114] FIG. **43** illustrates a perspective view of a load carrier system, according to an embodiment.

[0115] FIG. **44** illustrates a perspective view of a carrying arrangement, according to an embodiment.

[0116] FIG. **45** illustrates a perspective view of the carrying arrangement of FIG. **44**, showing the carrying arrangement arranged in a stowage position, according to an embodiment.

[0117] FIG. **46** illustrates a perspective view of an exemplary connection between a carrying portion and a supporting portion of the carrying arrangement of FIG. **44**.

[0118] FIG. **47** illustrates the components of FIG. **46** in an exploded view.

[0119] FIG. **48** illustrates a perspective view of a license plate holding arrangement, according to an embodiment.

[0120] FIG. **49** illustrates a side view of components of the license plate holding arrangement of FIG. **48**, showing a license plate holder is in a use position.

[0121] FIG. **50** illustrates a side view of components of the license plate holding arrangement of FIG. **48**, showing the license plate holder is in a stowage position.

[0122] FIG. **51** illustrates an exploded view of components of a carrying arrangement, according to an embodiment.

[0123] FIG. **52** illustrates a perspective view of a supporting portion of the carrying arrangement of FIG. **51**.

[0124] FIG. **53** illustrates a perspective view of the carrying arrangement of FIG. **51** partially in section.

[0125] FIGS. **54** to **56** illustrate an embodiment of a carrying arrangement.

[0126] The features and advantages of the embodiments will become more apparent from the detailed description set forth below when taken in conjunction with the drawings, in which like reference characters identify corresponding elements throughout. In the drawings, like reference numbers generally indicate identical, functionally similar, and/or structurally similar elements.

DETAILED DESCRIPTION

[0127] Embodiments of the present disclosure are described in detail with reference to embodiments thereof as illustrated in the accompanying drawings. References to “one embodiment,” “an embodiment,” “some embodiments,” etc., indicate that the embodiment(s) described may include a particular feature, structure, or characteristic, but every embodiment may not necessarily include the particular feature, structure, or characteristic. Moreover, such phrases are not necessarily referring to the same embodiment. Further, when a particular feature, structure, or characteristic is described in connection with an embodiment, it is submitted that it is within the knowledge of one skilled in the art to affect such feature, structure, or characteristic in connection with other embodiments whether or not explicitly described.

[0128] Spatially relative terms, such as “beneath,” “below,” “lower,” “above,” “on,” “upper,” “opposite” and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. The spatially relative terms are intended to encompass different orientations of the device in use or in operation in addition to the orientation depicted in the figures. The apparatus may be otherwise oriented (e.g., rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein may likewise be interpreted accordingly.

[0129] The term “about” or “substantially” as used herein indicates the value of a given quantity that can vary based on a particular technology. Based on the particular technology, the term “about”

or “substantially” can indicate a value of a given quantity that varies within, for example, 1-15% of the value (e.g., $\pm 1\%$, $\pm 2\%$, $\pm 5\%$, $\pm 10\%$, or $\pm 15\%$ of the value).

[0130] The following examples are illustrative, but not limiting, of the present embodiments. Other suitable modifications and adaptations of the variety of conditions and parameters normally encountered in the field, and which would be apparent to those skilled in the art, are within the spirit and scope of the disclosure.

[0131] Embodiment 1 of the description—A vehicle mounted load carrier includes a hub; a support member rotatably coupled to the hub; a tilt release mechanism coupled to the support member, the tilt release mechanism including a locking arm configured to move between a locked configuration and a released configuration such that in the locked configuration the support member is fixed relative to the hub and in the released configuration the support member can rotate between a first position and a second position; and a tilt memory actuator moveably coupled to the hub or the support member and configured to maintain the locking arm in the released configuration when the locking arm is actuated from the locked configuration to the released configuration.

[0132] Embodiment 2 of the description—The load carrier of embodiment 1, wherein a plurality of recesses are formed in the hub or the support member, and wherein the tilt memory actuator moves between a closed configuration and an open configuration, wherein in the closed configuration the tilt memory actuator is disposed over at least a portion of a first recess of the plurality of recesses.

[0133] Embodiment 3 of the description—The load carrier of embodiment 2, wherein the tilt memory actuator linearly translates between the closed configuration and the open configuration.

[0134] Embodiment 4 of the description—The load carrier of embodiment 2, wherein in the closed configuration, the tilt memory actuator entirely covers the first recess.

[0135] Embodiment 5 of the description—The load carrier of embodiment 2, wherein the tilt memory actuator is biased into the closed configuration.

[0136] Embodiment 6 of the description—The load carrier of embodiment 2, wherein the locking arm is disposed in the first recess in the locked configuration.

[0137] Embodiment 7 of the description—The load carrier of embodiment 2, wherein the plurality of recesses are formed in the hub.

[0138] Embodiment 8 of the description—The load carrier of embodiment 2, wherein the tilt memory actuator includes an actuating surface and a platform surface, and wherein the platform surface is configured to maintain the locking arm in the released configuration.

[0139] Embodiment 9 of the description—The load carrier of embodiment 8, wherein the locking arm is configured to contact the actuating surface of the tilt memory actuator when the support arm is rotated in a first direction to move the tilt memory actuator into the open configuration.

[0140] Embodiment 10 of the description—The load carrier of embodiment 9, wherein the platform surface is configured to maintain the locking arm in the released configuration when the support arm is rotated in a second direction opposite the first direction.

[0141] Embodiment 11 of the description—The load carrier of embodiment 8, wherein the platform surface is spaced apart from and disposed above a hub surface of the hub.

[0142] Embodiment 12 of the description—The load carrier of embodiment 1, wherein the tilt memory actuator is moveably coupled to the hub.

[0143] Embodiment 13 of the description—The load carrier of embodiment 1, wherein the support member is further configured to rotate to a third position different from the first position and the second position.

[0144] Embodiment 14 of the description—The load carrier of embodiment 1, wherein the tilt memory actuator includes a plate and a protrusion, and wherein the protrusion is configured to maintain the locking arm in the released configuration.

[0145] Embodiment 15 of the description—The load carrier of embodiment 14, wherein a plurality of recesses are formed in the hub, and wherein the tilt memory actuator moves between a closed configuration and an open configuration, wherein in the closed configuration the protrusion is

disposed above at least one recess of the plurality of recesses.

[0146] Embodiment 16 of the description—A load carrier includes a hub including a channel formed in the hub, the channel having a first end and a second end; a support member moveably coupled to the hub and disposed in the channel; and a first cover coupled to the hub or the support member, wherein the first cover is configured to cover a portion of the channel between the first end and the support member when the support member is rotated between a first support position and a second support position.

[0147] Embodiment 17 of the description—The load carrier of embodiment 16, further including a second cover configured to cover a portion of the channel between the second end and the support member.

[0148] Embodiment 18 of the description—The load carrier of embodiment 16, wherein the first cover is coupled to the hub and biased towards the support member.

[0149] Embodiment 19 of the description—The load carrier of embodiment 18, wherein the first cover contacts the support member and slides along the support member.

[0150] Embodiment 20 of the description—The load carrier of embodiment 16, wherein the first cover slides along the hub or the support member.

[0151] Embodiment 21 of the description—The load carrier of embodiment 20, wherein the first cover slides along the support member.

[0152] Embodiment 22 of the description—The load carrier of embodiment 16, wherein the first cover is coupled to the hub and the first cover includes a first sidewall disposed on a first side of the support member and a second sidewall disposed on a second side of the support member opposite the first side.

[0153] Embodiment 23 of the description—The load carrier of embodiment 16, wherein the first cover is rotatably coupled to the hub.

[0154] Embodiment 24 of the description—The load carrier of embodiment 16, wherein movement of the support member from a first position to a second position moves the first cover.

[0155] Embodiment 25 of the description—The load carrier of embodiment 16, wherein the load carrier is a bicycle carrier.

[0156] Embodiment 26 of the description—A bicycle carrier including a wheel hoop arm including a first end and a second end, wherein the wheel hoop arm is configured to receive and support a bicycle wheel; and a wheel insert removably coupled the first end of the wheel hoop arm and configured to reduce a wheel receiving length of the wheel hoop arm.

[0157] Embodiment 27 of the description—The bicycle carrier of embodiment 26, wherein the wheel insert includes a plurality of flanges configured to receive a perimeter rim of the wheel hoop arm.

[0158] Embodiment 28 of the description—The bicycle carrier of embodiment 27, wherein a first flange of the plurality of flanges couples with the perimeter rim of the wheel hoop arm.

[0159] Embodiment 29 of the description—The bicycle carrier of embodiment 26, wherein an outer wall of the wheel insert includes a profile configured to match a perimeter rim profile of the wheel hoop arm.

[0160] Embodiment 30 of the description—The bicycle carrier of embodiment 26, wherein the wheel insert includes a first support edge configured to support a first wheel having a first diameter, and a second support edge configured to support a second wheel having a second diameter different from the first diameter.

[0161] Embodiment 31 of the description—The bicycle carrier of embodiment 30, wherein a first wheel receiving length extends from the first support edge to the second end of the wheel hoop arm, and a second wheel receiving length extends from the second support edge to the second end of the wheel hoop arm.

[0162] Embodiment 32 of the description—The bicycle carrier of embodiment 31, wherein the second wheel receiving length is less than the first wheel receiving length.

[0163] Embodiment 33 of the description—The bicycle carrier of embodiment 30, wherein a wall extends between the first support edge and the second support edge, and wherein the wall, the first support edge, and a portion of the wheel hoop arm form a wheel receiving channel for the bicycle wheel.

[0164] Embodiment 34 of the description—The bicycle carrier of embodiment 26, further including a second wheel insert coupled to the second end of the wheel hoop arm and configured to further reduce the wheel receiving length of the wheel hoop arm.

[0165] Embodiment 35 of the description—A vehicle mounted load carrier including a hub; a support member rotatably coupled to the hub, wherein the support member is configured to rotate between a first position and a second position; and a tilt-assist device coupled to the hub and the support member, wherein the tilt-assist device is configured to: control a rate of rotation of the support member between the first position and the second position, to assist the support member moving from the second position to the first position, or both.

[0166] Embodiment 36 of the description—The load carrier of embodiment 35, wherein the tilt-assist device is arranged on a first side of the support member.

[0167] Embodiment 37 of the description—The load carrier of embodiment 35, wherein an aperture is formed through the support member, and the tilt-assist device extends through the aperture.

[0168] Embodiment 38 of the description—The load carrier of embodiment 35, wherein the tilt-assist device includes a damping unit and a spring unit.

[0169] Embodiment 39 of the description—The load carrier of embodiment 38, wherein the damping unit is arranged parallel to the spring unit.

[0170] Embodiment 40 of the description—The load carrier of embodiment 38, wherein the damping unit is arranged on a first side of the support member, and the spring unit is arranged on a second side of the support member opposite the first side.

[0171] Embodiment 41 of the description—The load carrier of embodiment 35, wherein the tilt-assist device includes a gas spring.

[0172] Embodiment 42 of the description—The load carrier of embodiment 41, wherein the gas spring includes an actuator, and wherein the gas spring assists rotation of the support member from the second position to the first position when the actuator is actuated.

[0173] Embodiment 43 of the description—The load carrier of embodiment 35, wherein the tilt-assist device includes a sensor to detect a load on the support member, and wherein the tilt-assist device adjusts the rate of rotation or a force provided to assist the support member moving from the second position to the first position based on the load.

[0174] Embodiment 44 of the description—The load carrier of embodiment 35, wherein the tilt-assist device is further configured to reduce vibration in the support member during transportation by the vehicle.

[0175] Embodiment 45 of the description—A bicycle carrier includes a support member; a wheel hoop arm coupled to the support member and configured to receive a bicycle wheel, the wheel hoop arm including: an angled support extending away from the support member, a first coupling portion and a second coupling portion extending from the angled support and configured to receive and support the bicycle wheel, and a recess portion opposite the angled support and extending between the first and second coupling portions.

[0176] Embodiment 46 of the description—The bicycle carrier of embodiment 45, wherein the wheel hoop arm is formed from a single bar.

[0177] Embodiment 47 of the description—The bicycle carrier of embodiment 45, wherein the angled support includes a coupling bracket configured to couple to the support member.

[0178] Embodiment 48 of the description—The bicycle carrier of embodiment 47, wherein the coupling bracket includes a plurality of angle position apertures to adjust an angle of the wheel hoop arm relative to the support member.

[0179] Embodiment 49 of the description—The bicycle carrier of embodiment 45, wherein the first coupling portion and the second coupling portion are tapered.

[0180] Embodiment 50 of the description—The bicycle carrier of embodiment 45, wherein the angled support member extends at an acute angle relative to the support member.

[0181] Embodiment 51 of the description—The bicycle carrier of embodiment 45, wherein the angled support and the recess receive the wheel hub, the wheel spokes, or both.

[0182] Embodiment 52 of the description—A bicycle carrier includes a support member; a wheel hoop arm coupled to the support member and configured to receive a bicycle wheel, wherein the wheel hoop arm includes a coupling member configured to couple with the support member in a plurality of angular orientations.

[0183] Embodiment 53 of the description—The bicycle carrier of embodiment 52, wherein the coupling member includes a plurality of angle position apertures.

[0184] Embodiment 54 of the description—The bicycle carrier of embodiment 53, wherein the wheel hoop arm has a first orientation when a fastener extends through a first aperture of the plurality of angle position apertures to couple the wheel hoop arm with the support member.

[0185] Embodiment 55 of the description—The bicycle carrier of embodiment 54, wherein the wheel hoop arm has a second orientation different from the first orientation when the fastener extends through a second aperture of the plurality of angle position apertures to couple the wheel hoop arm with the support member.

[0186] Embodiment 56 of the description—A protruding bolt configured to secure a fastening member to a support member, the protruding bolt including: a coupling shaft configured to couple to the support member; a spacing shaft extending away from the coupling shaft; and a bolt head spaced apart from the coupling shaft by the spacing shaft, wherein the fastening member is disposed around the spacing shaft when the fastening member is secured to the protruding bolt.

[0187] Embodiment 57 of the description—A strap for securing equipment to an equipment carrier, the strap including: a first end including a coupling aperture; a second end including a grip portion; and a plurality of apertures formed through the strap, wherein each aperture of the plurality of apertures includes a countersunk surface.

[0188] Embodiment 58 of the description—An assembly for securing equipment to an equipment carrier, the assembly including: the protruding bolt of embodiment 56; and the strap of embodiment 57.

[0189] Embodiment 59 of the description—An assembly for securing equipment to an equipment carrier, the assembly including: a support member; a protruding bolt coupled to the support member, wherein the protruding bolt including a coupling shaft, a spacing shaft, and a bolt head spaced apart from the support member by the spacing shaft; and a strap including a plurality of apertures, wherein at least one of the plurality of apertures removably couples with the protruding bolt.

[0190] Embodiment 60 of the description—The assembly of embodiment 59, wherein the strap further includes a first end and a second end, and wherein the first end is coupled to the support member.

[0191] Embodiment 61 of the description—The assembly of embodiment 60, wherein a coupling aperture is formed through the first end of the strap and configured to receive a bolt that couples the strap to the support member.

[0192] Embodiment 62 of the description—The assembly of embodiment 60, wherein the second end includes a grip portion.

[0193] Embodiment 63 of the description—The assembly of embodiment 59, wherein each aperture of the plurality of apertures includes a countersunk surface.

[0194] Embodiment 64 of the description—The assembly of embodiment 59, wherein the spacing shaft is disposed within an aperture of the plurality of aperture of the strap and the strap is disposed between the bolt head and the support member when the strap is removably coupled to the

protruding bolt.

[0195] Embodiment 65 of the description—The assembly of embodiment 59, wherein the spacing shaft includes a square cross-sectional shape.

[0196] Embodiment 66 of the description—A bicycle carrier includes an upper support configured to secure a first bicycle wheel to the bicycle carrier; a lower support disposed below the upper support; and a wheel cradle coupled to the lower support and configured to secure a second bicycle wheel to the bicycle carrier, wherein the wheel cradle is formed from bent wire.

[0197] Embodiment 67 of the description—The bicycle carrier of embodiment 66, wherein the wheel cradle has triangular shape.

[0198] Embodiment 68 of the description—The bicycle carrier of embodiment 66, wherein the wheel cradle tapers from a wheel receiving end to a coupling portion with the lower support.

[0199] Embodiment 69 of the description—A vehicle mounted load carrier includes: a hub including a plurality of recesses formed in the hub; a support member rotatably coupled to the hub; and a tilt-release mechanism configured to engage a first recess of the plurality of recesses formed in the hub to lock a relative position between the support arm and the hub, wherein the tilt release mechanism includes an actuator coupled to the support member.

[0200] Embodiment 70 of the description—The load carrier of embodiment 69, wherein the actuator is a strap, a button, a knob, a lever, or a handle.

[0201] Embodiment 71 of the description—The load carrier of embodiment 69, wherein the support member includes a first end rotatably coupled to the hub and a second end opposite the first end, and wherein the actuator is disposed along the support member and spaced apart from the first end and the second end.

[0202] Embodiment 72 of the description—The load carrier of embodiment 69, wherein the tilt-release mechanism further includes a locking arm configured to move between a locked configuration and a released configuration, and a linkage coupled to the actuator and the locking arm,

[0203] Embodiment 73 of the description—The load carrier of embodiment 72, wherein in the locked configuration the locking arm is received in one of the plurality of recesses of the hub and prevents rotation of the support arm relative to the hub.

[0204] Embodiment 74 of the description—The load carrier of embodiment 73, wherein when the actuator is operated, the locking arm translates out of the recess to the released configuration such that the support arm can rotate relative to the hub.

[0205] Embodiment 75 of the description—The load carrier of embodiment 72, wherein the linkage is disposed within the support member.

[0206] Embodiment 76 of the description—The load carrier of embodiment 69, wherein the locking arm is biased towards the hub.

[0207] Embodiment 77 of the description—A vehicle mounted load carrier includes a support member having a proximal end disposed toward a vehicle and a distal end disposed opposite the proximal end; and an equipment lock coupled to the support member and configured to secure a cable to the support member, wherein the equipment lock is disposed at the distal end of the support member.

[0208] Embodiment 78 of the description—The load carrier of embodiment 77, wherein the lock includes a lock barrel, a lock protrusion coupled to the lock barrel, and a spring configured to bias the lock protrusion into a locked position, wherein a locking notch is formed in an end of the cable, and wherein the lock protrusion engages the locking notch to secure the cable to the base when the lock is disposed in a locked position.

[0209] Embodiment 79 of the description—A vehicle mounted load carrier includes: a hub; a support member rotatably coupled to the hub and configured to rotate between a first position and a second position; a safety pin configured to be disposed through an aperture formed in the hub, wherein the safety pin is configured to prevent rotation of the support member from the first

position to the second position; and a pin cradle coupled to the hub and configured to receive the safety pin and secure the safety pin to the base.

[0210] Embodiment 80 of the description—The load carrier of embodiment 79, wherein the safety pin is L-shaped.

[0211] Embodiment 81 of the description—The load carrier of embodiment 79, wherein the safety pin includes a shaft and a handle, and wherein the handle is received in the pin cradle to secure the handle to the hub.

[0212] Embodiment 82 of the description—The load carrier of embodiment 81, wherein the handle is approximately perpendicular to the shaft.

[0213] Embodiment 83 of the description—The load carrier of embodiment 79, further including a safety wire coupled to the safety pin and the hub to secure the safety pin to the hub when the safety pin is not disposed through the aperture of the hub.

[0214] Embodiment 84 of the description—The load carrier of embodiment 79, wherein when the support member is in the second position, the support member blocks the aperture in the hub.

[0215] Embodiment 85 of the description—The load carrier of embodiment 79, wherein the pin cradle is configured to receive the safety pin when the safety pin is not disposed through the aperture of the hub.

[0216] Embodiment 86 of the description—A bicycle carrier includes a support member rotatably coupled to a base; and a bicycle work stand coupled to the support member and configured to support a bicycle.

[0217] Embodiment 87 of the description—The bicycle carrier of embodiment 86, wherein the support member includes a vertical arm and a horizontal arm, and wherein the bicycle work stand is coupled to the horizontal arm.

[0218] Embodiment 88 of the description—The bicycle carrier of embodiment 86, wherein the bicycle work stand is rotatably coupled to the support member and moveable between a stowed position and an in-use position.

[0219] Embodiment 89 of the description—The bicycle carrier of embodiment 86, wherein the bicycle work stand extends away from the support member at an in-use angle such that a bicycle disposed on the work stand is disposed distally from the bicycle carrier.

[0220] Embodiment 90 of the description—The bicycle carrier of embodiment 86, wherein the bicycle work stand includes a support arm rotatably coupled to the support member; a first support coupled to a distal end of the support arm; and a second support coupled to the support arm below the first support, wherein the first support and the second support are configured to contact the bicycle to support the bicycle.

[0221] Embodiment 91 of the description—The bicycle carrier of embodiment 90, wherein a groove is formed in the first support to accommodate a seat component of the bicycle.

[0222] Embodiment 92 of the description—The bicycle carrier of embodiment 91, wherein the second support is configured to contact a seat post or a frame of the bicycle.

[0223] Embodiment 93 of the description—A bicycle carrier includes a support member; a wheel hoop arm coupled to the support member and configured to receive a bicycle wheel; and a wheel support coupled to the wheel hoop arm and contacting the support member, wherein the wheel support is configured to support the bicycle wheel.

[0224] Embodiment 94 of the description—A vehicle mounted load carrier includes a base configured to transport a load; and a wheel assembly coupled to the base in at least one of a storage configuration; and a transport configuration, wherein the wheel assembly is moveably coupled to the base.

[0225] Embodiment 95 of the description—The load carrier of embodiment 94, wherein the wheel assembly includes a wheel arm and a wheel, wherein the wheel arm includes a first end and a second end, wherein the first end is rotatably coupled to the base and the wheel is coupled to the second end.

[0226] Embodiments of load carrier apparatuses, systems, and methods as discussed below can provide improved user operation for moving loads on a load carrier, improve safety by removing access to finger-trapping channels, increase versatility of the load carrier to accommodate different sized bicycle wheels, and assist and control tilting of a load carrier between different configurations.

Example Tilt Memory Actuator

[0227] FIGS. 1-5D illustrate a load carrier system **100** with a tilt memory actuator **200**, according to embodiments. Load carrier system **100** can be configured to secure and carry a load, for example, one or more bicycles **102**, **104**. Load carrier system **100** can be moved and/or tilted from a first position **10**, such as when load carrier **100** is in an in-use position, to a second position **20**, such as when load carrier **10** is being loaded or rotated away from a vehicle and in a loading position. Load carrier system **100** can include a tilt-release mechanism **900** that moves a locking arm **920** from a locked configuration **40** to a released configuration **50**. When locking arm **920** is in the released configuration **50**, load carrier system **100** can be moved from the first position **10** to the second position **20**. Tilt memory actuator **200** can be configured to maintain locking arm **920** in the released configuration **50** when locking arm **920** is actuated from the locked configuration **40** to the released configuration **50**. Although load carrier **100** with tilt memory actuator **200** is shown in FIGS. 1-5D as a stand-alone system, the embodiments of this disclosure can be used with other apparatuses and/or systems, such as, but not limited to the covers **300**, wheel hoop arm **400**, wheel insert **500**, tilt-assist device **600**, strap assembly **700**, wheel cradle **800**, tilt-release mechanism **900**, equipment lock **1000**, safety pin **1100**, bicycle work stand **1200**, wheel support **1300**, and/or transport wheel assembly **1400**.

[0228] In some embodiments, load carrier system **100** can include hub **110**, support member **112**, tilt-release mechanism **900**, and/or tilt memory actuator **200** as shown, for example, in FIGS. 1-5D. In the illustrative embodiment shown in FIG. 1, load carrier system **100** can be a bicycle carrier to secure a plurality of bicycles **102**, **104** in a vertical arrangement. In some embodiments, load carrier system **100** can be a bicycle carrier to secure bicycles in a horizontal arrangement. In some embodiments, load carrier system **100** can be any load carrying device that tilts or rotates between positions such as a cargo box, rooftop box, folding tent, foldable stroller, or other similar devices.

[0229] In the illustrative embodiment shown in FIGS. 1-3, support member **112** is coupled to hub **110** and configured to secure a plurality of bicycles **102**, **104** to load carrier system **100**. Support member **112** can move from first position **10** to a second position **20**, or vice versa, as shown, for example, in FIG. 3. In some embodiments, first position **10** can be an in-use position. In some embodiments, second position **20** can be a tilt-down position, a loading position, and/or a vehicle clearance position. In some embodiments, support member **112** can move to a third position relative to hub **110**, different from the first and second positions **10**, **20**.

[0230] In the illustrative embodiment shown in FIGS. 1-3, support member **112** can include a vertical support **150**, a first horizontal support **152**, and a second horizontal support **154**. In some embodiments, first and second horizontal supports **152**, **154** can be coupled to vertical support **150**. In some embodiments, first and second horizontal supports **152**, **154** extend perpendicularly to vertical support **150**. In some embodiments, first horizontal support **152** can be an upper support and second horizontal support **154** can be a lower support such that first horizontal support **152** can be disposed above second horizontal support **154**. In some embodiments, a plurality of wheel hoop arms **400** can couple to first horizontal support **152**. In some embodiments, a plurality of wheel cradles **800** can couple to second horizontal support **154**. In some embodiments, support member **112** can include a first side **156**, a second side **158** opposite first side **156**, a first end **160** moveably coupled with hub **110**, and a second end **162** opposite first end **160**.

[0231] As shown, for example, in FIGS. 1-4C, hub **110** can include vehicle attachment portion **120** that can couple load carrier system **100** to a vehicle. Hub **110** can include a hub body **122**, a channel **124** formed in hub body **122**, and a guide pin **128** coupled to and extending away from hub

body **122**. In some embodiments, guide pin **128** is received within a guide slot **216** of tilt memory actuator **200** to guide movement of tilt memory actuator **200**. In some embodiments, hub body **122** supports movement and/or rotation of support member **112** between first and second positions **10**, **20**. Support member **112** can be moveably coupled to hub **110** via hub body **122** and can be moveably disposed in channel **124**. In some embodiments, support member **112** rotates within and along channel **124** from first position **10** to second position **20** or vice versa. In some embodiments, channel **124** can include first end **140** and second end **142**. In some embodiments, support member **112** is closer to first end **140** in first position **10** than second end **142**. In some embodiments, support member **112** is closer to second end **142** in second position **20** than first end **140**.

[0232] In some embodiments, hub **110** interacts with tilt-release mechanism **900** to lock support member **112** in first position **10** or second position **20**, or unlock support member **112** so that support member **112** can move between first and second positions **10**, **20**. Hub body **122** can include a plurality of recesses **130** formed in an outwardly facing hub surface **126** as shown, for example, in FIGS. 4A-5D. In some embodiments, hub surfaces **126** can extend between first end **140** and second end **142** of channel **124** along the edges of channel **124**. Locking arm **920** of tilt-release mechanism **900** is configured to translate from a locked configuration **40** to a released configuration **50** or vice versa. In the locked configuration **40**, locking arm **920** can be disposed in one of the plurality of recesses **130**. In the released configuration **50**, locking arm **920** can be disposed externally to the plurality of recesses **130**. In the illustrative embodiment shown in FIG. 5A, locking arm **920** rests on hub surface **126** when support arm is moved between first position **10** and second position **20**. Hub surface **126** maintains locking arm **920** in the released configuration **50** during movement of the support member **112** between the first and second positions **10**, **20**. In some embodiments, locking arm **920** is biased (e.g., by a spring) towards the locked configuration **40**. When locking arm **920** approaches one of the plurality of recesses **130**, locking arm **920** moves into the recess **130** and into locked configuration **40**.

[0233] As shown, for example, in FIGS. 4A-5D, plurality of recesses **130** can include first recess **132** and second recess **134**. In the illustrative embodiment shown in FIG. 4A, when locking arm **920** is in locked configuration **40** and in first recess **132**, support member **112** is locked in first position **10**. In the illustrative embodiment shown in FIGS. 4B and 5C, when locking arm **920** is in locked configuration **40** and in second recess **134**, support member **112** is locked in second position **20**. In the illustrative embodiment shown in FIG. 5A, when support member **112** is moved between the first and second positions **10**, **20**, locking arm **920** is in released configuration **50** and moves and/or slides along hub surface **126**.

[0234] Tilt memory actuator **200** can be configured to maintain and/or temporarily hold locking arm **920** in the released configuration **50** after locking arm **920** has been actuated from locked configuration **40** to released configuration **50** as shown, for example in FIGS. 4C and 5D. In some embodiments, tilt memory actuator **200** can be at least partially disposed over one of the plurality of recesses **130** as shown, for example in FIGS. 4C, 5A, and 5D. In some embodiments, tilt memory actuator **200** can completely cover one of the plurality of recesses **130**. In some embodiments, tilt memory actuator **200** can be moveably coupled to hub body **122**. In some embodiments, tilt memory actuator **200** can couple to support member **112**. In some embodiments, tilt memory actuator **200** can couple to locking arm **920**. In some embodiments, tilt memory actuator **200** can move from a closed configuration **60** to an open configuration **70** or vice versa. In some embodiments, tilt memory actuator **200** can include guide slot **216**, and guide pin **128** of hub **110** can be received within guide slot **216** to guide movement of tilt memory actuator **200**. In some embodiments, tilt memory actuator **200** linearly translates from closed configuration **60** to open configuration **70** or vice versa. In some embodiments, tilt memory actuator **200** rotates from closed configuration **60** to open configuration **70** or vice versa. In some embodiments, tilt memory actuator **200** includes a spring **210** that biases tilt memory actuator **200** towards the closed configuration **60**. In some embodiments, spring **210** can couple with slots formed in tilt memory

actuator **200**. In some embodiments, spring **210** can be a torsional spring coupled between hub **110** and tilt memory actuator **200**.

[0235] Tilt memory actuator **200** can include actuating surface **212** and platform surface **214**, as shown, for example, in FIGS. 4A-5D. In the illustrative embodiment shown in FIGS. 5A-5D, when support member **112** is moved in a first direction **80** between first and second positions **10**, **20**, locking arm **920** moves along and contacts hub surface **126**, such that hub surface **126** maintains locking arm **920** in the released configuration **50**. As shown, for example, in FIGS. 5A and 5B, platform surface **214** is spaced apart from hub surface **126** such that locking arm **920** contacts actuating surface **212** when locking arm **920** approaches second recess **134**. As shown, for example, in FIGS. 5A and 5B, as support member **112** continues to move in first direction **80**, into second position **20**, locking arm **920** pushes tilt memory actuator **200** away from recess **134** and from closed configuration **60** to open configuration **70**.

[0236] As shown, for example, in FIGS. 5B and 5C, when tilt memory actuator **200** is in open configuration **70**, recess **134** is uncovered. As shown, for example, in FIG. 5C, when tilt memory actuator **200** is in open configuration **70**, locking arm **920** can move into recess **134** and into locking configuration **40** to lock support member **112** in second position **20**. In some embodiments, locking arm **920** is biased into locked configuration **40** and into recess **134**, or another one of the plurality of recesses **130**. As shown, for example, in FIGS. 4B and 5C, when locking arm is in locked configuration **40** and disposed in recess **134**, locking arm **920** maintains tilt memory actuator **200** in open configuration **70**.

[0237] When a user desires to move support member **112** in a second direction **90** from second position **20** to first position **10**, tilt memory actuator **200** maintains locking arm **920** in released configuration **50**. Accordingly, the user does not have to continually and manually actuate locking arm **920** in released configuration **50** as tilt memory actuator **200** automatically performs this function. As shown, for example, in FIGS. 4C and 5D, when locking arm **920** is actuated from locked configuration **40** to released configuration **50**, locking arm **920** moves above actuating surface **212** such that tilt memory actuator **200** can move from open configuration **70** to closed configuration **60**. As shown, for example, in FIGS. 4C and 5D, tilt memory actuator **200** at least partially covers recess **134** when locking arm **920** moves to released configuration **50**. As shown, for example, in FIGS. 4C and 5D, when the user releases actuation of locking arm **920**, locking arm **920** rests on and contact platform surface **214** of tilt memory actuator **200**. In some embodiments, when platform surface **214** supports locking arm **920** in released configuration **50**, support member **112** can freely move in second direction **90** towards first position **10**. In some embodiments, locking arm **920** slides over platform surface **214** and onto hub surface **126** before moving into first recess **132** when support member **112** reaches first position **10**.

[0238] In some embodiments, tilt memory actuator **200** can be positioned over recess **132** such that tilt memory actuator **200** supports locking arm **920** in released configuration **50** above recess **132**, and support member **112** can freely move in first direction **80** towards second position **20**. When support member **112** is moved in second direction **90** between first and second positions **10**, **20**, locking arm **920** moves along and contacts hub surface **126** and contacts actuating surface **212** when locking arm **920** approaches first recess **132**. In some embodiments, as support member **112** continues to move in second direction **90**, into first position **10**, locking arm **920** pushes tilt memory actuator **200** away from recess **132** and from closed configuration **60** to open configuration **70**.

[0239] In some embodiments, when tilt memory actuator **200** is in open configuration **70**, recess **132** is uncovered. In some embodiments, when tilt memory actuator **200** is in open configuration **70**, locking arm **920** can move into recess **132** and into locking configuration **40** to lock support member **112** in first position **10**. In some embodiments, locking arm **920** is biased into locked configuration **40** and into recess **132**. In some embodiments, when locking arm **920** is actuated from locked configuration **40** to released configuration **50**, locking arm **920** moves above actuating

surface **212** such that tilt memory actuator **200** can move from open configuration **70** to closed configuration **60**. In some embodiments, tilt memory actuator **200** at least partially covers recess **132** when locking arm **920** moves to released configuration **50**. In some embodiments, when the user releases actuation of locking arm **920**, locking arm **920** rests on and contact platform surface **214** of tilt memory actuator **200** above recess **132**. In some embodiments, when platform surface **214** supports locking arm **920** in released configuration **50**, support member **112** can freely move in first direction **80** towards second position **20**.

[0240] In some embodiments, tilt memory actuator plate **250** can be configured to maintain locking arm **920** in released configuration **50** after locking arm **920** has been actuated from locked configuration **40** to released configuration **50** as shown, for example in FIGS. **6**, **7A**, and **7B**. In some embodiments, tilt memory actuator plate **250** can couple to a side of hub body **122** and extend across the plurality of recesses **130**. Tilt memory actuator plate **250** can include plate **252** and protrusions **254**. In some embodiments, tilt memory actuator plate **250** can be moveably coupled to hub body **122** from a closed configuration **60'** to an open configuration **70'** or vice versa. In some embodiments, protrusions **254** can extend inwards towards support member **112**. In some embodiments, tilt memory actuator plate **252** can include two protrusions **254** disposed over both of recess **132** and recess **134** in closed configuration **60'**. As shown, for example, in FIGS. **7A** and **7B**, when locking arm **920** moves from locked configuration **40** to released configuration **50**, locking arm **920** contacts protrusion **254** to bias plate **252** outwardly away from hub **110** to open configuration **70'**. In some embodiments, plate **252** moves perpendicular to the movement of locking arm **920**. In some embodiments, locking arm **920** and/or protrusion **254** can include chamfers and/or angled edges to facilitate locking arm **920** urging plate **252** into open configuration **70'**.

[0241] As shown, for example, in FIG. **7B**, when locking arm **920** is actuated from locked configuration **40** to released configuration **50**, locking arm **920** moves above protrusion **254** such that tilt memory actuator plate **250** moves from open configuration **70'** to closed configuration **60'**. As shown, when the user releases actuation of locking arm **920**, locking arm **920** rests on and contacts protrusion **254** such that protrusion maintains locking arm **920** in released configuration **50**. In some embodiments, when protrusion **254** supports locking arm **920** in released configuration **50**, support member **112** can freely move from first position **10** to second position **20** or vice versa. In some embodiments, protrusions **254** can be disposed over recesses **132**, **134** to maintain locking arm **920** in released configuration **50** when support member **112** is in the first position **10** or second position **20**.

[0242] In some embodiments, tilt memory actuator arm **270** can be configured to maintain locking arm **920** in released configuration **50** after locking arm **920** has been actuated from locked configuration **40** to released configuration **50** as shown, for example in FIGS. **8A** and **8B**. In some embodiments, tilt memory actuator arm **270** can couple to a side of locking arm **920**. Tilt memory actuator arm **270** can include a biasing arm **272** and a holding arm **274** extending perpendicularly from biasing arm **272** toward hub body **122**. In some embodiments, biasing arm **272** can move holding arm **274** from a closed configuration **60''** to an open configuration **70''** or vice versa. In some embodiments biasing arm **272** can be coupled to locking arm **920** and include side flanges **273** that wrap around a portion of locking arm **920** to maintain the orientation of tilt memory actuator arm **270** relative to locking arm **920**. In some embodiments, when locking arm **920** moves to released configuration **50**, holding arm **274** is urged by biasing arm **272** into one of the plurality of recesses **130**. In some embodiments, holding arm **274** extends into one of the plurality of recesses **130** and contacts a bottom of the recess to maintain locking arm **920** in released configuration **50**. In some embodiments, holding arm **274** can include chamfers such that when support member **112** is moved between first and second positions **10**, **20**, holding arm **274** is urged into the open configuration **70''** by a side face of one of the plurality of recesses **130**. In some embodiments, when locking arm **920** is moved to be disposed over a different recess **134**, holding

arm **274** remains in contact with hub body **122** and in open configuration **70"** such that locking arm **920** can move into recess **134** and into locked configuration **40**.

Example Load Carrier with Hinge Covers

[0243] FIGS. **9A-10** illustrate a covers **300** coupled to load carrier system **100**, according to embodiments. Covers **300** can be configured to cover an open portion of channel **124** of hub **110** to prevent external objects, including user appendages, from becoming trapped or pinched in channel **124** when support member **112** is moved from first position **10** to second position **20** or vice versa. Although load carrier **100** and covers **300** are shown in FIGS. **9A-10** as a stand-alone system, the embodiments of this disclosure can be used with other apparatuses and/or systems, such as, but not limited to the tilt memory actuator **200**, wheel hoop arm **400**, wheel insert **500**, tilt-assist device **600**, strap assembly **700**, wheel cradle **800**, tilt-release mechanism **900**, equipment lock **1000**, safety pin **1100**, bicycle work stand **1200**, wheel support **1300**, and/or transport wheel assembly **1400**.

[0244] As described above, load carrier system **100** can include hub **110** and support member **112** moveably coupled to hub **110**. In some embodiments, hub **110** can include channel **124** formed in or by hub body **122**. In the illustrative embodiment in FIGS. **9A-9C**, support member **112** is disposed in channel **124**. In some embodiments, channel **124** can include first end **140** and second end **142**. In some embodiments, support member **112** is closer to first end **140** in first position **10** than second end **142**. In some embodiments, support member **112** is closer to second end **142** in second position **20** than first end **140**. In some embodiments, support member **112** can include first side **156** and second side **158** opposite first side **156**. First and second sides **156**, **158** extend parallel to the direction **80**, **90** of movement of support member **112**.

[0245] Covers **300** can be configured to cover a portion of channel **124** from support member **112** to first end **140** and from support member **112** to second end **142** as shown, for example, in FIGS. **9A-9C**. In some embodiments, covers **300** can prevent access to channel **124** for any position or angle of support member **112** relative to hub **110**. In some embodiments, covers **300** may reduce a pinching risk between support member **112** and channel **124**. In some embodiments, covers **300** may prevent dirt or debris entering hub **110** via channel **124**. In some embodiments, covers **300** can be opened to allow access to channel **124**, for example, for assembly of support member **112** to hub **110**, as shown, for example, in FIG. **10**. In some embodiments, covers **300** can include a protrusion **311** that engages hub **110** to hold covers **300** in the opened configuration (e.g. as shown in FIG. **10**). In some embodiments, hub **110** can include a protrusion that engages covers **300** to hold covers in the opened configuration. In some embodiments, covers **300** can be coupled to hub **110**. In some embodiments, covers **300** can be coupled to support member **112** and move therewith.

[0246] In some embodiments, covers **300** can include first cover **310** and second cover **320** as shown, for example, in FIGS. **9A-10**. In some embodiments, first cover **310** covers a first portion **330** of channel **124**. In some embodiments, first cover **310** extends from first end **140** of channel **124** to support member **112**. In some embodiments, first cover **310** is rotatably coupled to hub **110** at first end **140** of channel **124**. In some embodiments, first cover **310** includes an arc shaped slot for rotational movement relative to hub **110**. In some embodiments, first cover **310** can be fixedly coupled at first end **140** of channel **124** and translate into pockets formed in support member **112**. In some embodiments, first cover **310** can be fixedly coupled to support member **112** and translate into pockets formed in first end **140** of channel **124**. In some embodiments, first cover **310** can include a plurality of linearly translating plates, fixed to hub **110** and support member **112**, that overlap and slide relative to each other to cover the first portion **330** of channel **124**. In some embodiments, first cover **310** can be biased towards support member **112** by a biasing member such as a torsional spring. In some embodiments, first cover **310** can include first sidewall **312** and second sidewall **314** that extend on first and second sides **156**, **158** of support member **112** respectively. First and second sidewalls **312**, **314** may minimize gaps between first cover **310** and channel **124** as first cover **310** moves with support member **112**.

[0247] In some embodiments, second cover **320** covers a second portion **332** of channel **124** as shown, for example, in FIGS. **9A-9C**. In some embodiments, second cover **320** extends from second end **142** of channel **124** to support member **112**. In some embodiments, second cover **320** is rotatably coupled to hub **110** at second end **142** of channel **124**. In some embodiments, second cover **320** includes an arc shaped slot for rotational movement relative to hub **110**. In some embodiments, second cover **320** can be fixedly coupled at second end **142** of channel **124** and translate into pockets formed in support member **112**. In some embodiments, second cover **320** can be fixedly coupled to support member **112** and translate into pockets formed in second end **142** of channel **124**. In some embodiments, second cover **320** can include a plurality of linearly translating plates, fixed to hub **110** and support member **112**, that overlap and slide relative to each other to cover the second portion **332** of channel **124**. In some embodiments, second cover **320** can be biased towards support member **112** by a biasing member such as a torsional spring. In some embodiments, second cover **320** can include first sidewall **322** and second sidewall **324** that extend on first and second sides **156, 158** of support member **112** respectively. First and second sidewalls **322, 324** may minimize gaps between second cover **320** and channel **124** as second cover **320** moves with support member **112**.

[0248] In the illustrative embodiment shown in FIGS. **9A-9C**, support member **112** can move from first position **10** to second position **20**, or vice versa, resulting in movement of first and second covers **310, 320** to cover channel **124**. In some embodiments, as support member **112** rotates in first direction **80**, from first position **10** to second position **20**, support member **112** urges movement of second cover **320**, while first cover **310** maintains contact with support member **112** via a biasing force and/or gravity. In some embodiments, as support member **112** rotates in second direction **90**, from second position **20** to first position **10**, support member **112** urges movement of first cover **310**, while second cover **320** maintains contact with support member **112** via a biasing force and/or gravity. As shown, for example, in FIG. **9A**, first cover **310** is approximately perpendicular to a tangential plane at first end **140** of channel **124** when support member **112** is in first position **10**. As shown, second cover **320** is approximately parallel to a tangential plane at second end **142** of channel **124** when support member **112** is in first position **10**. As shown, for example, in FIG. **9C**, first cover **310** is approximately parallel to a tangential plane at first end **140** of channel **124** when support member **112** is in second position **20**. As shown, second cover **320** is approximately perpendicular to a tangential plane at second end **142** of channel **124** when support member **112** is in second position **20**. As shown, for example, in FIG. **9B**, first and second covers **310, 320** move between a plurality of orientations relative to respective tangential planes at first and second ends **140, 142** of channel **124** when support member is moving between first and second positions **10, 20**.

Example Wheel Hoop Arms and Wheel Inserts

[0249] FIGS. **11-13B** and **21A-23B** illustrate wheel hoop arms **400** coupled to load carrier system **100** and wheel hoop inserts **500** removably coupled to wheel hoop arms **400**, according to embodiments. Wheel hoop arms **400** can be configured to secure a first bicycle wheel **106** to load carrier system **100**. Wheel hoop inserts **500** can be configured to change (e.g., reduce) a wheel receiving length **434** of wheel hoop arm **400** to accommodate different sized (e.g., smaller) bicycle wheels **106**, for example, such as for children's bicycles. Although load carrier **100**, wheel hoop arms **400**, and wheel hoop inserts **500** are shown in FIGS. **11-13B** and **21A-23B** as a stand-alone system, the embodiments of this disclosure can be used with other apparatuses and/or systems, such as, but not limited to the tilt memory actuator **200**, covers **300**, tilt-assist device **600**, strap assembly **700**, wheel cradle **800**, tilt-release mechanism **900**, equipment lock **1000**, safety pin **1100**, bicycle work stand **1200**, wheel support **1300**, and/or transport wheel assembly **1400**.

[0250] As described above, load carrier system **100** can include support member **112** with vertical support **150**, first horizontal support **152**, and second horizontal support **154**. In the illustrative embodiment shown in FIG. **11**, wheel hoop arm **400** is coupled to first horizontal member **152** to

secure first bicycle wheel **106** to load carrier system **100**. In some embodiments, wheel hoop arm **400** can be coupled to second horizontal support **154** to secure second bicycle wheel **108** to load carrier system **100**. In some embodiments, wheel insert **500** can be removably coupled to wheel hoop arm **400** to adjust a wheel receiving length **424** of wheel hoop arm **400**. As shown, for example, in FIGS. **1** and **2**, a plurality of wheel hoop arms **400** can be coupled to first horizontal support **152**. In some embodiments, four wheel hoop arms **400** can be coupled to first horizontal support **152** such that load carrier system **100** can transport four bicycles. In some embodiments, six wheel hoop arms **400** can be coupled to first horizontal support **152** such that load carrier system **100** can transport six bicycles. In some embodiments, less than four or more than six wheel hoop arms **400** can be coupled to first horizontal support **152**.

[0251] As shown, for example, in FIG. **11**, wheel hoop arm **400** can include angled support **410**, first coupling portion **412**, second coupling portion **414**, and recess portion **416**. In some embodiments, wheel hoop arm **400** can be made from a continuous single bar, and formed and/or bent into shape. In some embodiments, first coupling portion **412**, second coupling portion **414**, and recess portion **416** form a perimeter rim **418** of wheel hoop arm **400**. In some embodiments, perimeter rim **418** can surround a portion of bicycle wheel **106** and be configured to secure bicycle wheel **106** to load carrier system **100**. In some embodiments, wheel hoop arm **400** can have a symmetrical shape.

[0252] In some embodiments, angled support **410** extends away from first horizontal support **152** at an acute angle with support **152** as shown, for example, in FIG. **12**. In some embodiments, angled support **410** can include two diverging support bars that can be configured to receive a bicycle wheel hub or spokes. In some embodiments, first coupling portion **412** extends away from angled support **410** approximately perpendicular to vertical support **150** and first horizontal support **152**. In some embodiments, first coupling portion **412** can include a first end **420** at a distal end from first horizontal support **152**. In some embodiments, second coupling portion **414** extends away from angled support **410** approximately perpendicular to vertical support **150** and first horizontal support **152** and opposite first coupling portion **412**. In some embodiments, second coupling portion **414** can include a second end **422** at a distal end from first horizontal support **152**. In some embodiments, first and second coupling portions **412**, **414** can be tapered, v-shaped, u-shaped, or have other appropriate shape for securing bicycle wheel **106**. In some embodiments, wheel hoop arm **400** can have wheel receiving length **424** extending from first end **420** of first coupling portion **412** to second end **422** of second coupling portion **414**. In some embodiments, wheel receiving length **424** is sized to accommodate a bicycle wheel for regular adult bicycle (e.g. 29", 27.5" 650b, 26", and other typical sizes). In some embodiments, wheel hoop arm **400** can be wider to accommodate a fat tire bicycle wheel. In some embodiments, recess portion **416** extends between first and second coupling portions **412**, **414** on an opposite side of wheel hoop arm **400** to angled support **410**. In some embodiments, recess portion **416** extends toward first horizontal support **152** to form a dipped portion of wheel hoop arm **400**. In some embodiments, recess portion **416** can be configured to provide space for a bicycle wheel hub or spokes, to avoid contact with these components against perimeter rim **418**.

[0253] Angled support **410** can couple to first horizontal support **152** at a plurality of angles **450**, **452** to adjust an angle and orientation of wheel hoop arm **400** relative to first horizontal support **152**. In some embodiments, angled support **410** can include coupling bracket **430** to couple with first horizontal support **152**. In the illustrative embodiment shown in FIGS. **22A-23B**, coupling bracket **430** can include a plurality of angle position apertures **432**. An angle and orientation **434**, **436** of wheel hoop arm **400** can be adjusted based on the apertures **432** used to couple coupling bracket **430** to first horizontal support **152**. As shown, for example, in FIGS. **22A** and **22B**, when first and second apertures **440**, **441** are used, wheel hoop arm **400** has first orientation **434** with first angle **450** relative to first horizontal support **152**. As shown, for example, in FIGS. **23A** and **23B**, when third and fourth apertures **442**, **443** are used, wheel hoop arm **400** has second orientation **436**

with second angle **452** relative to first horizontal support **152**. In some embodiments, combinations of first and fourth apertures **440**, **443**, or second and third apertures **441**, **442** may provide additional orientations of wheel hoop arm **400** relative to first horizontal support **152**.

[0254] Wheel hoop arm **400** can have different shapes and sizes. In some embodiments, wheel hoop arm **400** can have a wider profile without recess portion **416** as shown, for example, in FIG. **21A**. In some embodiments, first and second coupling portions **412**, **414** can be asymmetrical, for example, with first coupling portion **412** being wider than second coupling portion **414** as shown, for example, in FIG. **21B**. In some embodiments, recess portion **416** can extend to and couple with first horizontal support **152**, and wheel hoop arm **400** can be formed from a continuous bar through all portions **410**, **412**, **414**, **416** as shown, for example, in FIG. **21C**. In the illustrative embodiment shown in FIG. **21C**, angled support **410** and recess portion **416** can be slideably coupled to first horizontal support **152**. In some embodiments, angled support **410** and recess portion **416** can be moved relative to one another to change a size of wheel hoop arm **400**, for example, to widen or shorten wheel hoop arm **400**. In some embodiments, perimeter rim **418** can rotate relative to coupling bracket **430** to adjust an angle of wheel hoop arm **400** relative to first horizontal support **152**. In some embodiments, first or second coupling portions **412**, **414** can include slots such that first or second ends **420**, **422** can slide along perimeter rim **418** to adjust wheel receiving length **424** as shown, for example, in FIG. **21D**.

[0255] In some embodiments, wheel insert **500** can be removably coupled with wheel hoop arm **400**. In some embodiments, wheel insert **500** can be configured to reduce wheel receiving length **424** of wheel hoop arm **400**. As shown, for example, in FIGS. **11** and **12**, wheel insert **500** can include a plurality of flanges **510**, outer wall **520**, first support edge **530**, second support edge **540**, and/or wall **545** extending from first support edge **530** to second support edge **540**. In some embodiments, wheel insert **500** can be removably coupled to first coupling portion **412** of wheel hoop arm **400**. In some embodiments, wheel insert **500** can be removably coupled to second coupling portion **414** of wheel hoop arm **400**. In some embodiments, wheel insert **500** can be removably coupled to first coupling portion **412** and a second wheel insert **550** can be removably coupled to second coupling portion **414** of wheel hoop arm **400** as shown, for example, in FIG. **14A**.

[0256] In some embodiments, one or more of the plurality of flanges **510** are configured to receive and detachably couple with perimeter rim **418** of wheel hoop arm **400**. In some embodiments, plurality of flanges **510** can include first flange **512**, second flange **514**, and third flange **516** as shown, for example, in FIGS. **11** and **12**. In some embodiments, wheel insert **500** can include less than three flanges. In some embodiments, wheel insert **500** can include more than three flanges. In some embodiments, all flanges **512**, **514**, **516** form a snap-fit connection with wheel hoop arm **400**. In some embodiments, only one or two flanges of the plurality of flanges form a snap-fit connection with wheel hoop arm, while the remaining flanges rest on wheel hoop arm **400** to maintain positioning of wheel insert **500** relative to wheel hoop arm **400**. For example, flanges **514**, **516** can form a snap-fit connection with wheel hoop arm **400**, with flange **512** guiding or preventing rotation of wheel insert **500** relative to wheel hoop arm **400**. In some embodiments, outer wall **520** extends around a perimeter rim **418** facing portion of wheel insert **500**. In some embodiments, outer wall **520** can have a concave profile **522** that matches the profile of perimeter rim **418** to form a close fit therebetween. In some embodiments, outer wall **520** can include a different profile **522** to match the profile of perimeter rim **418**.

[0257] In some embodiments, first support edge **530** can extend inward toward the receiving space of wheel hoop arm **400** as shown, for example, in FIG. **11**. In some embodiments, first support edge **530** forms a first reduced wheel receiving length **532** less than wheel receiving length **424**. In some embodiments, first reduced wheel receiving length **532** extends from first support edge **530** to second end **422** of wheel hoop arm **400**. Wall **545** extends from first support edge **530** to second support edge **540**. In some embodiments, a wheel receiving channel **546** is formed between

perimeter rim **418**, first support edge **530**, and wall **545**. In some embodiments, a wheel receiving channel **546** is configured to receive a bicycle wheel **106'**. As shown, for example, in FIG. **13A**, first support edge **530** can be configured to secure bicycle wheel **106'** with a first reduced diameter (e.g. 24" children's bicycle wheel). In some embodiments, second support edge **540** can extend inward toward the receiving space of wheel hoop arm **400** as shown, for example, in FIG. **11**. In some embodiments, second support edge **540** is spaced further apart from first end **420** than first support edge **530**. In some embodiments, second support edge **540** forms a second reduced wheel receiving length **542** less than first reduced wheel receiving length **532** and wheel receiving length **424**. In some embodiments, second reduced wheel receiving length **542** extends from second support edge **540** to second end **422** of wheel hoop arm **400**. As shown, for example, in FIG. **13B**, second support edge **540** can be configured to secure a bicycle wheel **106''** with a second reduced diameter less than bicycle wheel **106'** with first reduced diameter (e.g. 20" children's bicycle wheel).

[0258] In some embodiments, wheel insert **500** can have different shapes and sizes. In some embodiments, wheel insert **500** can include two flanges that extend around an upper portion of perimeter rim **418** as shown, for example, in FIG. **14A**. In some embodiments, wheel insert **500** can be a linear bar that diagonally extends across first coupling portion **412** as shown, for example, in FIG. **14B**. In some embodiments, wheel insert **500** can include a flange that extend around an upper portion of perimeter rim **418** and around the u-shaped portion of first coupling portion **412** as shown, for example, in FIG. **14C**. In some embodiments, wheel insert **500** can be a reversible insert that provides first wheel receiving length when installed in a first direction, and provides a second wheel receiving length when installed in an opposite direction as shown, for example, in FIGS. **14D** and **14E**.

Example Tilt-Assist Device

[0259] FIGS. **15-20C** illustrate a tilt-assist device **600** coupled to load carrier system **100**, according to embodiments. Tilt-assist device **600** can be configured to control a rate of movement of support member **112** and/or assist in lifting support member **112** from second position **20** to first position **10**, or vice versa. Although load carrier **100** and tilt-assist device **600** are shown in FIGS. **15-20C** as a stand-alone system, the embodiments of this disclosure can be used with other apparatuses and/or systems, such as, but not limited to the tilt memory actuator **200**, covers **300**, wheel hoop arm **400**, wheel insert **500**, strap assembly **700**, wheel cradle **800**, tilt-release mechanism **900**, equipment lock **1000**, safety pin **1100**, bicycle work stand **1200**, wheel support **1300**, and/or transport wheel assembly **1400**.

[0260] As described above, load carrier system **100** can include hub **110** and support member **112** having first and second sides **156**, **158**. In some embodiments, support member **112** can be moveably coupled to hub **110** from first position **10** to second position **20** or vice versa. In the illustrative embodiment shown in FIG. **15**, tilt-assist device **600** can couple to hub **110** and support member **112**. In some embodiments, tilt-assist device **600** can be arranged on and coupled to second side **158** of support member **112**. In some embodiments, tilt-assist device **600** can be configured to support, control, and assist movement of support member **112** relative to hub **110**. In some embodiments, tilt-assist device **600** can reduce vibration in load carrier system **100** when load carrier system **100** is being transported, for example, on the back of a vehicle. In some embodiments, tilt-assist device **600** can provide bump control and suspension between hub **110** and support member **112** to suppress vibration in the load carrier system **100** when load carrier system **100** is transported.

[0261] In some embodiments, load carrier system **100** can secure heavy equipment, for example, a plurality of bicycles **102**, **104**. In some embodiments, gravity may assist in moving support member **112** from first position **10** to second position **20**. However, when the equipment secured to load carrier system **100** is heavy, it can overwhelm a user and support member **112** may move too quickly. Accordingly, tilt-assist device **600** can control the rate of movement or rotation of support

member **112** relative to hub **110**. Similarly, if the equipment secured to load carrier system **100** is heavy, a user may struggle to move support member **112** against gravity and the weight of the equipment from second position **20** to first position **10**. Accordingly, tilt-assist device **600** may assist the lifting operation to move support member **112** relative to hub **110**. In some embodiments, tilt-assist device **600** is in a compressed state when support member **112** is in first position **10**. In some embodiments, tilt-assist device **600** is in a compressed state when support member **112** is in second position **20** as shown, for example, in FIG. **16B**. In some embodiments, tilt-assist device **600** is in an extended state when support member **112** is in first position **10** as shown, for example, in FIG. **16A**. In some embodiments, tilt-assist device **600** is in an extended state when support member **112** is in second position **20**.

[0262] In some embodiments, tilt-assist device **600** can include a damping unit **610** and a spring unit **612**. In some embodiments, tilt-assist device **600** can include damping unit **610** or spring unit **612**. In some embodiments, damping unit **610** and spring unit **612** can be a single unit. In some embodiments, damping unit **610** can control a rate of movement or rotation of support member **112** relative to hub **110**. In some embodiments, damping unit **610** can be adjusted to change the rate of rotation of support member **112**. In some embodiments, damping unit **610** can be configured to slow rotation of support member **112** relative to hub **110**, for example, when support member **112** approaches first position **10** or second position **20**. In some embodiments, damping unit **610** can be configured to slow rotation of support member **112** relative to hub **110** when support member **112** is between about 5 degrees to 15 degrees from the first position **10** and/or the second position **20**. In some embodiments, damping unit **610** can be configured to not slow rotation of support member **112** relative to hub **110** until support member **112** is between about 5 degrees to 15 degrees from the first position **10** and/or the second position **20**.

[0263] In some embodiments, damping unit **610** can be adjusted based on the weight of the equipment secured to load carrier system **100**. In some embodiments, damping unit **610** can automatically adjusted based on the weight of the equipment or the speed of movement of the support member **112** from the first position **10** to the second position **20**. In some embodiments, damping unit **610** can be configured to adjust a rate of rotation of support member **112** at different positions between and including first position **10** and second position **20**. In some embodiments, damping unit **610** can be configured to adjust a time for support member **112** to travel between first and second positions **10**, **20**. For example, damping unit **610** may control movement of support member **112** to travel between first and second positions **10**, **20** about 5 seconds. In some embodiments, damping unit **610** may control movement of support member **112** to travel between first and second positions **10**, **20** in more than about 2 seconds and less than about 10 seconds. In some embodiments, damping unit **610** may control movement of support member **112** to travel between first and second positions **10**, **20** in more than about 3 seconds and less than about 7 seconds

[0264] In some embodiments, damping unit **610** can include user controls such that a user can adjust the damping properties of damping unit **610** to achieve desired rotation speeds throughout the movement of support member **112** between first and second positions **10**, **20**. In some embodiments, damping unit **610** and spring unit **612** can automatically adjust a damping rate or force based on the load (e.g., the weight) secured to load carrier system **100**. In some embodiments, tilt-assist device **600** can include an additional damping reservoir or chamber (e.g. a piggyback reservoir) to provide improved control and adjustability of damping unit **610** and spring unit **612**. In some embodiments, tilt-assist device **600** can include a sensor and/or processor configured to detect loads, vibration, and/or user inputs, and adjust properties of the damping unit **610** and spring unit **612** in response.

[0265] In some embodiments, spring unit **612** can provide a desired amount of force to assist moving support member **112** from second position **20** to first position **10**. In some embodiments, spring unit **612** can include a coil spring. In some embodiments, spring unit **612** can be a gas spring

614. In some embodiments, the amount of gas in gas spring **614** can be changed to adjust a force provided to assist movement of support member **112**. In some embodiments, gas spring **614** can include an actuator **616** that exerts force to assist movement of support member **112** when actuator **616** is operated. In some embodiments, damping unit **610** can work with spring unit **612** to control the rate of movement or rotation of support member **112** from second position **20** to first position **10**. In some embodiments, tilt-assist device **600** can include a sensor **620** that detects a weight of equipment secured to the load carrier system **100**, and adjusts damping unit **610** and/or spring unit **612** based on the detected load. In some embodiments, damping unit **610** and/or spring unit **612** can include a housing **630** and a rod **632** that extends within housing **630**. In some embodiments, housing **630** can couple to support member **112** and rod **632** can couple to hub **110**. In some embodiments, housing **630** can couple to hub **110** and rod **632** can couple to support member **112** as shown, for example in FIGS. **16A** and **16B**.

[0266] In some embodiments, spring unit **612** provides a force to support member **112** from the first position **10** to the second position **20** and vice versa. In some embodiments, damping unit **610** is only active in an action zone near the first position **10** and/or the second position **20**. In some embodiments, the action zone is between about 1 degrees and 20 degrees (e.g., between about 5 degrees and 15 degrees) from the first position **10** and/or the second position **20**. In some embodiments, the action zone near the first position **10** is equal to the action zone near the second position **20**. In some embodiments, the action zone near the first position **10** is different compared to the action zone near the second position **20**.

[0267] In some embodiments, damping unit **610** can be arranged on first side **156** of support member and spring unit **612** can be arranged on second side **158** of support member **112** as shown, for example, in FIG. **17**. In some embodiments, a separate damping unit **610** and separate spring unit **612** can be arranged in parallel on the same side **156**, **158** of support member **112**. In some embodiments, support member **112** can include an aperture formed through support member **112**, and tilt-assist device **600** can extend through support member **112** as shown, for example, in FIGS. **18A** and **18B**. In some embodiments, spring unit **612** can be a torsional spring and can be arranged within hub **110** as shown, for example, in FIG. **19**. In some embodiments, spring unit **612** can include a pair of springs disposed between plates and arranged in a plurality of positions on load carrier system **100** as shown, for example, in FIGS. **20A-20C**.

Example Strap Assembly

[0268] FIGS. **24-26** illustrate a strap assembly **700**, according to embodiments. Strap assembly **700** can be configured to secure a bicycle wheel **106** to load carrier system **100**. Although strap assembly **700** is shown in FIGS. **24-26** as a stand-alone system, the embodiments of this disclosure can be used with other apparatuses and/or systems, such as, but not limited to the tilt memory actuator **200**, covers **300**, wheel hoop arm **400**, wheel insert **500**, tilt-assist device **600**, wheel cradle **800**, tilt-release mechanism **900**, equipment lock **1000**, safety pin **1100**, bicycle work stand **1200**, wheel support **1300**, and/or transport wheel assembly **1400**.

[0269] In some embodiments, strap assembly **700** can include a protruding bolt **710** and a strap **720**. Strap assembly **700** can be coupled with support member **112** to secure bicycle wheel **106** and/or bicycles **102**, **104** to load carrier system **100**. In some embodiments, strap assembly **700** can be coupled to wheel hoop arm **400** or wheel cradle **800** as shown, for example, in FIGS. **25** and **26**. In the illustrative embodiment shown in FIG. **24**, protruding bolt **710** can include a coupling shaft **712**, a spacing shaft **714**, and a bolt head **716**. In some embodiments, spacing shaft **714** is disposed between coupling shaft **712** and bolt head **716**. In some embodiments, bolt head **716** is spaced apart from support member **112** by spacing shaft **714**. In some embodiments, coupling shaft **712** can couple to and be fixed with support member **112**. In some embodiments, coupling shaft **712** can be secured to support member **112** with a fastener **717**, such as a nut, or a hollow bolt with internal threads. In some embodiments, spacing shaft **714** and/or fastener **717** can have a square cross-sectional shape **718**. In some embodiments, spacing shaft **714** and bolt head **716** can be a separate

spacer component and secured to support member **112** with a fastener that extends through the spacer component.

[0270] In the illustrative embodiment shown in FIG. **24**, strap **720** can include a first end **722**, a second end **724** opposite first end **722**, and a plurality of apertures **730** formed through strap **720**. In some embodiments, first end **722** can include coupling aperture **726** formed through first end **722** and configured to couple with protruding bolt **710** and/or support member **112**. In some embodiments, second end **724** can include grip portion **728** for a user to pull. In some embodiments, one or more of the plurality of apertures **730** can include a counter sunk surface, edge, or flange. In some embodiments, one or more of the plurality of apertures **730** can be elongated with round corners. In some embodiments, strap **720** can be made from an elastic material (e.g., rubber, polymer(s), TPE, etc.) and can be stretched to be tightly pulled around equipment secured with strap assembly **700**. In some embodiments, strap **720** can be removably coupled with protruding bolt **710** such that an aperture of the plurality of apertures **730** is arranged around spacing shaft **714** and disposed between bolt head **716** and support member **112**.

Example Wheel Cradle

[0271] FIG. **26** illustrates a wheel cradle **800** coupled to support member **112**, according to embodiments. Wheel cradle **800** can be configured to secure a wheel (e.g., second wheel **108**) to load carrier system **100**. Wheel cradle **800** can work with wheel hoop arm **400** to secure bicycle **102** to load carrier system **100**. Although load carrier **100** and wheel cradle **800** are shown in FIG. **26** as a stand-alone system, the embodiments of this disclosure can be used with other apparatuses and/or systems, such as, but not limited to the tilt memory actuator **200**, covers **300**, wheel hoop arm **400**, wheel insert **500**, tilt-assist device **600**, strap assembly **700**, tilt-release mechanism **900**, equipment lock **1000**, safety pin **1100**, bicycle work stand **1200**, wheel support **1300**, and/or transport wheel assembly **1400**.

[0272] As described above, load carrier system **100** can include support member **112** having vertical support **150**, first horizontal support **152**, and second horizontal support **154**. In the illustrative embodiment shown in FIG. **26**, wheel cradle **800** can be coupled to second horizontal support **154** and be configured to secure bicycle wheel **108** to load carrier system **100**. In some embodiments, wheel cradle **800** can include wheel receiving end **810** and coupling portion **812**. In some embodiments coupling portion **812** can couple to second horizontal support **154** (e.g. with fastener(s) or by welding). In some embodiments, wheel cradle **800** can be formed or bent from a bar of material (e.g., metal). In some embodiments, wheel cradle **800** can have an approximately triangular shape. In some embodiments, wheel cradle **800** can taper from wheel receiving end **810** to coupling portion **812**.

Example Tilt-Release Mechanism

[0273] FIGS. **27-30** illustrate a tilt-release mechanism **900** coupled to load carrier system **100**, according to embodiments. Tilt-release mechanism **900** can be configured to lock support member **112** relative to hub **110** and unlock support member **112** so that support member **112** can move relative to hub **110**. Although load carrier **100** and tilt-release mechanism **900** are shown in FIGS. **27-30** as a stand-alone system, the embodiments of this disclosure can be used with other apparatuses and/or systems, such as, but not limited to the tilt memory actuator **200**, covers **300**, wheel hoop arm **400**, wheel insert **500**, tilt-assist device **600**, strap assembly **700**, wheel cradle **800**, equipment lock **1000**, safety pin **1100**, bicycle work stand **1200**, wheel support **1300**, and/or transport wheel assembly **1400**.

[0274] As described above, load carrier system **100** can include hub **110** and support member **112**. In some embodiments, hub **110** can include a plurality of recesses **130** formed in hub **110**. In some embodiments, support member **112** can include first end **160** moveably coupled to hub **110** and second end **162** opposite first end **160**. In some embodiments, hub **110** interacts with tilt-release mechanism **900** to lock support member **112** in first position **10** or second position **20**, or unlock support member **112** so that support member **112** can move from first position **10** to second

position **20** or vice versa. In some embodiments, tilt-release mechanism can include actuator **910**, locking arm **920**, and/or linkage **930** as shown, for example in FIGS. **27-30**. In some embodiments, linkage **930** can couple actuator **910** to locking arm **920** and transfer movement of actuator **910** to locking arm **920**. In some embodiments, linkage **930** can be disposed within vertical support **150** of support member **112**. In some embodiments, linkage **930** can be a wire, chain, cord, rod, elongated plate, or tube.

[0275] In the illustrative embodiment shown in FIG. **27**, actuator **910** can rotatably couple to support member **112**. In some embodiments, actuator **910** can be a lever, handle, wire, strap, or telescopic arm. In some embodiments, actuator **910** can be disposed along support member **112** between first end **160** and second end **162**. In some embodiments, actuator **910** can be spaced apart from first end **160** and second end **162**. In some embodiments, actuator **910** can be a button, lever, knob, or strap. In some embodiments, actuator **910** can be disassembled from support member **112** to reduce a footprint when transporting load carrier system **100** as shown, for example, in FIG. **28**. In some embodiments, cover **914** can be disposed around a coupling end **916** of actuator **910** to hide and protect mechanical linkages and couplings (e.g. with rivets or bolts) of tilt-release mechanism **900**. In some embodiments, when actuator **910** is operated, locking arm **920** moves (e.g., translates) out of one of the plurality of recesses **130** to released configuration **50** such that support member **112** can move relative to hub **110**.

[0276] In some embodiments, locking arm **920** can be configured to translate from a locked configuration **40** to a released configuration **50** or vice versa as shown, for example, in FIGS. **4A-5D**. In the locked configuration **40**, locking arm **920** can be disposed in one of the plurality of recesses **130**. In the released configuration **50**, locking arm **920** can be disposed externally to the plurality of recesses **130**. In some embodiments, locking arm **920** is biased towards the locked configuration **40**. When locking arm **920** approaches one of the plurality of recesses **130**, locking arm **920** moves into the recess **130** and into locked configuration **40**.

Example Equipment Lock

[0277] FIGS. **31** and **32** illustrate an equipment lock **1000**, which can be integrated into load carrier system **100**, according to embodiments. In some embodiments, equipment lock **1000** can be configured to lock a cable **1010** to load carrier system **100**. Cable **1010** can be arranged around or through components of bicycles **102**, **104** that are secured to load carrier system **100** to lock bicycles **102**, **104** to load carrier system **100**. In some embodiments, cable **1010** can be arranged around and/or through a load or sports equipment secured to a load carrier system **100**. Although equipment lock **1000** is shown in FIGS. **31** and **32** as a stand-alone system, the embodiments of this disclosure can be used with other apparatuses and/or systems, such as, but not limited to the tilt memory actuator **200**, covers **300**, wheel hoop arm **400**, wheel insert **500**, tilt-assist device **600**, strap assembly **700**, wheel cradle **800**, tilt-release mechanism **900**, safety pin **1100**, bicycle work stand **1200**, wheel support **1300**, and/or transport wheel assembly **1400**.

[0278] As described above, load carrier system **100** can include support member **112** having vertical support **150**, first horizontal support **152**, and second horizontal support **154**. In some embodiments, equipment lock **1000** can be integrated into a distal end of vertical support **150**, first horizontal support **152**, and/or second horizontal support **154** such that equipment lock **1000** can be easily accessible to a user when bicycles **102** or loads are secured to load carrier system **100**. In some embodiments, equipment lock **1000** can be integrated into first horizontal support **152** adjacent to wheel hoop arm **400**. In some embodiments, equipment lock **1000** can be integrated into second horizontal support **154** adjacent to wheel cradle **800**. In some embodiments, barrel aperture **1020** and locking device aperture **1022** are formed through first horizontal support **152** as shown, for example, in FIG. **31**.

[0279] Cable **1010** can be locked to equipment lock **1000**. Cable can include a loop on one end and a locking notch at the opposite end. In some embodiments, load carrier system **100** can include a storage bag for storing cable **1010** when not in use. In some embodiments, cable **1010** can be stored

in a hollow cavity within support member **112** when not in use. In some embodiments, cable **1010** can be coupled to a recoil device coupled to support member **112**. Recoil device can be configured to recoil cable **1010** to neatly store cable **1010** when not in use. In some embodiments, cable **1010** can be configured to extend around a portion of bicycle **102** or other load secured to load carrier system **100** to lock said bicycle **102** or load to load carrier system **100**.

Example Safety Pin

[0280] FIGS. **33-34B** illustrate a safety pin **1100** configured to prevent movement of support member **112** relative to hub **110**, according to embodiments. In some embodiments, safety pin **1100** can be secured to a pin cradle **1110** when load carrier system **100** is in transport to secure safety pin **1100** to hub **110**. Although safety pin **1100** is shown in FIGS. **33-34B** as a stand-alone system, the embodiments of this disclosure can be used with other apparatuses and/or systems, such as, but not limited to the tilt memory actuator **200**, covers **300**, wheel hoop arm **400**, wheel insert **500**, tilt-assist device **600**, strap assembly **700**, wheel cradle **800**, tilt-release mechanism **900**, equipment lock **1000**, bicycle work stand **1200**, wheel support **1300**, and/or transport wheel assembly **1400**.

[0281] As described above, load carrier system **100** can include hub **110** and support member **112**. In some embodiments, support member **112** can be moveably coupled to hub **110** from a first position **10** to second position **20** or vice versa. In some embodiments, when support member **112** is in first position **10**, safety pin **1100** can be inserted through an aperture **127** in hub **110** to prevent support member **112** from moving to second position **20**. This may be important when load carrier system **100** is being transported and support member **112** needs to be in first position **10** to avoid damaging equipment and the load carrier system **100**. In the illustrative embodiment shown in FIG. **33**, safety pin **1100** can include shaft **1102** and handle **1104**. In some embodiments, shaft **1102** can extend through aperture **127** in hub **110** to prevent support member **112** from moving. In some embodiments, handle **1104** can extend perpendicular to shaft **1102** and be disposed externally to hub **110**. In some embodiments, safety pin **1100** is L-shaped.

[0282] In the illustrative embodiment shown in FIGS. **33, 34A**, and **34B**, hub **110** can include pin cradle **1110**. In some embodiments, pin cradle **1110** can couple to hub **110** with fasteners. In some embodiments, pin cradle **1110** can be integrally formed with hub **110**. In some embodiments pin cradle **1110** can form at least a portion of a receiving space **1112** for safety pin **1100**. Receiving space **1112** can be configured to receive and secure safety pin **1100** when safety pin **1110** is inserted into aperture **127** of hub **110**. In some embodiments, safety pin **1100** can be inserted into hub **110** and safety pin **1110** can be rotated through 90 degrees and received in receiving space **1112** as shown, for example, in FIGS. **34A** and **34B**. In some embodiments, handle **1104** can couple with a snap-fit connection to pin cradle **1110**. In some embodiments, pin cradle **1110** can be configured to receive safety pin **1100** when safety pin is not disposed through aperture **127** of hub **110**. In some embodiments, safety pin **1100** can include a safety wire **1120** to fixedly couple safety pin **1100** to hub **110**.

Example Bicycle Work Stand

[0283] FIGS. **35** and **36** illustrate a bicycle work stand **1200** coupled to support member **112** on load carrier system **100**, according to embodiments. Bicycle work stand **1200** can be configured to support a bicycle **102** in an upright position when bicycle **102** is not secured to load carrier system **100** with wheel hoop arms **400**. Although load carrier **100** and bicycle work stand **1200** are shown in FIGS. **35** and **36** as a stand-alone system, the embodiments of this disclosure can be used with other apparatuses and/or systems, such as, but not limited to the tilt memory actuator **200**, covers **300**, wheel hoop arm **400**, wheel insert **500**, tilt-assist device **600**, strap assembly **700**, wheel cradle **800**, tilt-release mechanism **900**, equipment lock **1000**, safety pin **1100**, wheel support **1300**, and/or transport wheel assembly **1400**.

[0284] As described above, load carrier system **100** can include support member **112** having vertical support **150** and second horizontal support **154**. In some embodiments, bicycle work stand **1200** can be pivotally coupled to support member **112** as shown, for example, in FIGS. **35** and **36**.

In some embodiments, bicycle work stand **1200** can couple to vertical support **150**. In some embodiments, bicycle work stand **1200** can couple to second horizontal support **154**. Bicycle work stand **1200** can be pivoted from an in-use position **15** to a stowed position **25** (as shown in FIG. 2), or vice versa, and can include a base joint **1210**, a support arm **1212**, a first support **1220**, and/or a second support **1222**, as shown, for example, in FIG. 35. Support arm **1212** can be pivotally coupled to support member **112** via base joint **1210** and can extend away from support member at an in-use angle **1230** such that bicycle **102** is spaced apart from support member **112** when bicycle **102** is supported by bicycle work stand **1200**. In some embodiments, in-use angle **1230** is approximately 30 degrees. In some embodiments, in-use angle **1230** is between approximately 10 degrees and 60 degrees.

[0285] In some embodiments, base joint **1210** can couple to support member **112** and pivotally couple to support arm **1212**, as shown, for example, in FIGS. 35 and 36. In some embodiments, base joint **1210** can be removably coupled to support member **112**. In some embodiments, base joint **1210** can couple to second horizontal support **154** adjacent to vertical support **150**. In some embodiments, base joint **1210** can couple to a distal end of second horizontal support **154**. Base joint **1210** can include a housing **1214**, a tool tray **1216**, and a plurality of recesses **1218**. Housing **1214** can extend outwardly away from support member **112** in the direction support arm **1212** pivots and behind load carrier system **100**. An aperture can be formed through housing **1214** and be configured to receive support arm **1212**. Plurality of recesses **1218** can be formed in housing **1214** and configured to receive support arm protrusion **1226**. Engagement between protrusions **1226** and recesses **1218** can maintain bicycle work stand **1200** in either the in-use position **15** or the stowed position **25**. In some embodiments, tool tray **1216** can be an arm, a hook, a loop, or similar shape, such that a bag or tools can be hung from tool tray **1216**.

[0286] In some embodiments, first support **1220** couples to a distal end **1224** of support arm **1212** and can be configured to secure a saddle component of bicycle **102**. In the illustrative embodiment shown in FIG. 35, first support **1220** can include a stepped groove **1221** configured to accommodate different shapes and sizes of saddles and corresponding saddle rails and seat-post attachment flanges, or other suitable bicycle components. In some embodiments, first support **1220** can have U-shape, V-shape, or any other shape that corresponds to a component of a bicycle.

[0287] In some embodiments, second support **1222** can couple to support arm **1212** and can be spaced apart from first support **1220**. In the illustrative embodiment shown in FIG. 35, second support **1222** can be hingedly coupled to support arm **1212**. In some embodiments, a U-shaped groove can be formed in second support **1222** and configured to accommodate a seat-post or a seat tube of the frame of the bicycle **102**, or other suitable component or feature of a bicycle. In some embodiments, second support **1222** can have V-shape, square shape, or any other shape that corresponds to a component or frame feature of a bicycle.

[0288] In some embodiments, support arm **1212** translates and pivots around base joint **1210** to move bicycle work stand **1200** from the in-use position **15** to the stowed position **25** or vice versa. To move bicycle work stand **1200** from the in-use position **15** to the stowed position **25**, support arm **1212** can be pulled upward and outward from support member **112** such that a pivot pin translates along a slot in support arm **1212**. Movement of support arm **1212** can also translate protrusion **1226** out of a first recess of the plurality of recesses **1218**, such that support arm **1212** can pivot around pivot pin toward the stowed position **25**. When support arm **1212** reaches the stowed position **25**, support arm **1212** can be translated downward such that protrusion **1226** extends into a second recess of the plurality of recesses **1218** to hold support arm in the stowed position **25**.

[0289] In some embodiments, wheel cradle **800** can be used to support bicycle **102** in the upright position by securing bicycle wheel **108** in wheel cradle **800** when load carrier system **100** is in second position **20** as shown, for example, in FIG. 37. In some embodiments, wheel hoop arm **400** can be used to support bicycle **102** in the upright position by supporting a saddle of bicycle **102**

when load carrier system **100** is in second position **20** as shown, for example, in FIG. **38**.

Example Wheel Hoop Arm Corner Support

[0290] FIG. **39** illustrates a wheel hoop arm corner support **1300** coupled between wheel hoop arm **400** and support member **112**, according to embodiments. Corner support **1300** can be configured to provide additional support to bicycle wheel **106** when bicycle wheel **106** is secured in wheel hoop arm **400**. Although wheel hoop arm corner support **1300** is shown in FIG. **39** as a stand-alone system, the embodiments of this disclosure can be used with other apparatuses and/or systems, such as, but not limited to the tilt memory actuator **200**, covers **300**, wheel hoop arm **400**, wheel insert **500**, tilt-assist device **600**, strap assembly **700**, wheel cradle **800**, tilt-release mechanism **900**, equipment lock **1000**, safety pin **1100**, bicycle work stand **1200**, and/or transport wheel assembly **1400**.

[0291] As described above, load carrier system **100** can include support member **112** having first horizontal support **152** and wheel hoop arm **400** coupled to first horizontal support **152**. In the illustrative embodiment shown in FIG. **39**, wheel support **1300** can be releasably coupled to wheel hoop arm **400** and contact and/or rest on first horizontal support **152**. Wheel support **1300** can be angled towards perimeter rim **418** such that when bicycle wheel **106** is secured in wheel hoop arm **400**, bicycle wheel **106** is stabilized by wheel support **1300**. In some embodiments, wheel support **1300** can be wedge shaped or triangular shaped. In some embodiments, wheel support **1300** can be made from plastic and molded. In some embodiments, wheel support **1300** includes ribs **1310** to facilitate gripping with bicycle wheel **106**. In some embodiments, wheel support **1300** is removably coupled with a snap-fit connection to wheel hoop arm **400** to avoid movement of wheel support **1300**. In some embodiments, wheel support **1300** can be reversible such that when wheel hoop arm **400** is assembled at a different orientation **434**, **436**, wheel support **1300** can still releasably couple to wheel hoop arm **400**.

Example Transport Wheels

[0292] FIGS. **40-42** illustrate a transport wheel assembly **1400** coupled to load carrier system **100**, according to embodiments. Wheel assembly **1400** can be configured to position wheels **1420** in a transport position **45** and a storage position. Although load carrier **100** and transport wheel assembly **1400** are shown in FIGS. **40-42** as a stand-alone system, the embodiments of this disclosure can be used with other apparatuses and/or systems, such as, but not limited to the tilt memory actuator **200**, covers **300**, wheel hoop arm **400**, wheel insert **500**, tilt-assist device **600**, strap assembly **700**, wheel cradle **800**, tilt-release mechanism **900**, equipment lock **1000**, safety pin **1100**, bicycle work stand **1200**, and/or wheel support **1300**.

[0293] The wheel assembly **1400** shown in FIGS. **40-42** can include wheel arm **1410** and wheels **1420**. Wheels **1420** can be rotatably coupled to a first end **1412** of wheel arm **1410**. Wheels **1420** can support the load carrier system **100** to ease transport of load carrier system **100**, for example to and from a vehicle, or moving the load carrier system when not attached to a vehicle, etc. In some embodiments, wheel assembly **1400** includes one wheel **1420**. In some embodiments, wheel assembly **1400** includes more than two wheels **1420**. In the illustrative embodiment, shown in FIGS. **40-42**, wheel assembly **1400** includes two wheels **1420**. In some embodiments, wheel arm **1410** can couple to hub **110** at a second end **1414** of wheel arm **1410**. In some embodiments, wheel arm **1410** can be fixed to hub **110** with fasteners. In some embodiments, second end **1414** is moveably coupled to hub **110** such that wheel assembly can be moved from a transport position **45** to a storage position or vice versa. In some embodiments, second end **1414** is slideably coupled to slots formed in hub **110** as shown, for example, in FIG. **41**. In some embodiments, second end **1414** is rotatably coupled to hub **110** as shown, for example, in FIG. **42**.

Example License Plate Holder and Lighting Assembly

[0294] FIG. **43** shows a perspective view of a load carrier system **1501**, which is configured as a bicycle carrier. The load carrier system **1501** has a carrying frame **1507**. Carrying frame **1507** is configured for supporting a load supporting platform **1515** and a load attachment unit **1513**. The

load support platform **1515** is configured to support wheel trays **1514**. Wheel trays **1514** can support a bicycle from below.

[0295] In some embodiments, load support platform **1515** can be pivotably fastened to the carrying frame **1507**, for example, in such a way that it can be pivoted between a use position, as illustrated in FIG. **43**. As shown in FIG. **43**, the load support platform **1515** extends approximately perpendicularly to the support frame **1507**, and a not shown stowage position in which the load support platform **1515** is folded onto the support frame **1507**.

[0296] In some embodiments, load attachment unit **1513** is configured for attaching support arms **1516**, which can also be referred to as spacers. Such support arms **1516** are configured to secure bicycles supported on the load support platform **1515** against tilting away laterally.

[0297] In some embodiments, the carrying frame **1507** can have a load supporting platform coupling section **1508**, **1509** and a rear door coupling section **1511**, **1512**. Load supporting platform **1515** and load fastening unit **1513** can be fastened to the load supporting platform coupling section **1508**, **1509**. The rear door coupling section **1511**, **1512** can serve to fasten the carrying frame **1507** to a rear door, for example by means of holders. The rear door coupling section **1511**, **1512** can be formed by a transverse strut or by a section of a transverse strut of the carrying frame **1507**. In the configuration shown in FIG. **43**, an upper cross strut is used as the rear door coupling section **1511**. In some embodiments, the rear door coupling section **1511** is coupled to an elongated support profile **1505**, which serves as a fastening device **1502** and can be fastened to the rear door of a vehicle. Fastening clamps **1517** are provided at the ends of the elongated support profile **1505**. The fastening clamps **1517** are designed for engagement with a door edge of the rear door. At least one fastening clamp **1517** can be coupled to the elongated support profile **1505** in such a way that it can be tensioned in the longitudinal direction L of the elongated support profile **1505**. A door can be clamped between two fastening clamps **1517**.

[0298] In some embodiments, the carrying frame **1507** can have a vehicle pillar coupling portion **1510**. In some embodiments, the vehicle pillar coupling portion **1510** is to be understood as a portion which is coupled to the vehicle pillar or to a door hinge. In some embodiments, a fastening device **1503** can be used, as shown in FIG. **43**. The vehicle pillar coupling portion **1510** can be formed by a longitudinal strut of the support frame **1507** or can be a part of a longitudinal strut of the support frame **1507**. In the illustrative embodiment shown in FIG. **43**, two fastening devices **1503** are provided on the vehicle pillar coupling portion **1510**. The upper fastening device is provided in the region of an upper door hinge of a vehicle and the lower fastening device is provided in the region of a lower door hinge of a vehicle.

[0299] In some embodiments, the load supporting platform coupling sections **1508**, **1509** may be arranged in a first plane E1. At least one rear door coupling section **1511** and the vehicle pillar coupling portion **1510** can be arranged in a second plane E2. In some embodiments, the first plane E1 and the second plane E2 are spaced apart from one another. In the illustrative embodiment shown in FIG. **43**, the carrying frame **1507** is in a main extension direction formed symmetrically to an imaginary plane of symmetry S. The plane of symmetry S is perpendicular to the aforementioned planes E1 and E2 and divides the longitudinal struts into two parts of equal length.

[0300] In the illustrative embodiment shown in FIG. **44**, a carrying arrangement **1600** for a load carrier **1501** is shown. The carrying arrangement **1600** is configured for carrying an object. In the illustrative embodiment, a plurality of objects are carried by the carrying arrangement **1600**, for example, a license plate holder **1602** for carrying a motor vehicle license plate, and lighting assemblies **1633**, **1634**, for example rear lights. The license plate holder **1602** and the lighting assemblies **1633**, **1634** are held on the load carrier **1501** by means of the carrying arrangement **1600** such that the license plate holder **1602** and the lighting assemblies **1633**, **1634** can be moved by a user from a use position into a stowage position. The use position is a position in which the object, for example, the license plate holder **1602** or a license plate fastened thereto or a lighting assembly **1633**, **1634**, is arranged vertically and thus visible for following vehicles. FIG. **44**

illustrates, for example, a state in which the carrying arrangement **1600** is in a use configuration. FIG. **45** illustrates, for example, a state in which the carrying arrangement **1600** is in a stowage configuration. In the stowage configuration, the object can be folded onto the load carrier or a part of the load carrier, for example, onto the carrying frame **1507** or the load support platform **1515**. [0301] In some embodiments, the carrying arrangement **1600** includes a supporting portion **1612**. The supporting portion **1612** can be fastened to the load carrier **1501** via suitable fastening devices **1651**. In some embodiments, the fastening devices **1651** can be screws or bolts. In some embodiments, the supporting portion **1612** can be mounted on the load support platform **1515** of the load carrier **1501**, as illustrated in FIGS. **44** and **45**. The load support platform **1515** can be coupled to the carrying frame **1507** via a hinge arrangement. The load support platform **1515** can be pivotably fastened to the carrying frame **1507**, for example, such that it can be pivoted between a use position, as illustrated in FIG. **43**, in which the load support platform extends approximately perpendicularly to the carrying frame **1507**, and a stowage position, not illustrated in more detail, in which the load support platform **1515** is folded onto the carrying frame **1507**.

[0302] In some embodiments, the carrying arrangement **1600** includes a carrying portion **1614** for carrying the object. In some embodiments, the object can be a license plate holder **1602** or a lighting assembly **1633**, **1634**. In some embodiments, the carrying portion **1614** can be connected in an articulated manner to the supporting portion **1612**. In some embodiments, the carrying portion **1614** and the supporting portion **1612** can form a joint **1610**. In some embodiments, the carrying portion **1614** is arranged movable with respect to the supporting portion **1612**. The carrying portion **1614** is held on the supporting portion **1612** such that it is arranged pivotable in a first direction R about an axis of rotation D between a use position and a stowage position. In some embodiments, the stowage position can be a position in which the carrying portion **1614** is folded onto the load support platform **1515**, as illustrated in FIG. **45**. In some embodiments, the use position can be a position in which the carrying portion **1614** is arranged perpendicularly to the load support platform **1515**, as illustrated in FIG. **44**.

[0303] In some embodiments, the carrying portion **1614** can include a frame arrangement **1630**. In some embodiments, the frame arrangement **1630** can include a first frame portion **1631** and a second frame portion **1632**. In some embodiments, the frame arrangement **1630** can be formed from one or more tube portions. The first frame portion **1631** can be mounted rotatable about an axis of rotation D on the supporting portion **1612**. The second frame portion **1632** can be arranged spaced apart from the first frame portion **1631**. A license plate holder **1602** can be fastened to the first frame portion **1631** and to the second frame portion **1632**. The first frame portion **1631** and the second frame portion **1632** can be provided such that they extend in the transverse direction of the load carrier **1501**. Lighting assemblies **1633**, **1634** can be fastened to lateral end portions of the frame portions **1631** and **1632**. For example, free end portions of the frame portions **1631** and **1632** can be received in corresponding recesses of the lighting assembly **1633**, **1634**, as can be seen, for example, in FIG. **45**.

[0304] In some embodiments, the supporting portion **1612** can include a housing **1640**. An opening **1641** can be provided in mutually opposite housing walls. In some embodiments, the first frame portion **1631** can be configured straight. The first frame portion **1631** can be inserted into the opening **1641**. In some embodiments, the first frame portion **1631** and the opening **1641** are configured round, so that a first frame portion **1631** inserted in the opening **1641** is rotatably mounted in the opening **1641**.

[0305] In some embodiments, a recess **1642** is formed in the housing **1640**. Members of a locking arrangement are received in the recess **1642**. In some embodiments, the locking arrangement is configured such that it locks the carrying portion **1614** in the use position and the stowage position with respect to the supporting portion **1612** such that the carrying portion **1614** remains or can be locked in the use position and in the stowage position. The use position is shown, for example, in FIG. **44**. The stowage position is shown, for example, in FIG. **45**. In some embodiments, the

locking arrangement is configured to block a rotation of the carrying portion **1614** from the use position and the stowage position.

[0306] In some embodiments, the locking arrangement includes a first engaging portion **1650**. The first engaging portion **1650** may be associated with the carrying portion **1614**. In some embodiments, the carrying portion **1614** is coupled to the engaging portion **1650**. In some embodiments, the engaging portion **1650** is fastened to the frame portion **1631** such that the engaging portion **1650** and the frame portion **1631** move together. A rotation of the carrying portion **1614** or of the frame portion **1631** leads to a rotation of the engaging portion **1650**. Due to this operative connection, a rotation of the carrying portion **1614** is blocked when a rotational movement of the engaging portion **1650** is blocked. The engaging portion **1650** can be configured as a portion, which extends in the radial direction away from the frame portion **1631**. The engaging portion **1650** can be coupled directly to the frame portion **1631**. In some embodiments, the engaging portion **1650** is configured as a part of a ring-like attachment **1647**, through which the frame portion **1631** is passed. In some embodiments, the attachment is fastened to the frame portion **1631** with a suitable fastening device, for example, a screw **1648**, by screwing the screw **1648** into a threaded opening **1633** on the frame portion **1631**.

[0307] In some embodiments, the locking arrangement includes a second engaging portion **1643**. In some embodiments, the second engaging portion **1643** is associated with the supporting portion **1612**. In some embodiments, the second engaging portion **1643** is fastened to the supporting portion **1612**. In some embodiments, the second engaging portion **1643** can be a plate-like member. The second engaging portion **1643** can be received in the recess **1642** such that it cannot be rotated with respect to the housing **1640** about the axis of rotation D. In some embodiments, the second engaging portion **1643** includes an opening **1646** which, when the engaging portion **1643** is received in the recess **1642**, is aligned or brought into alignment with the opening **1641** in the housing. The frame portion **1631** can be passed through the opening **1641** and the opening **1646**, through the housing **1640** and the second engaging portion **1643**, and through an attachment **1647** provided therein. Although not shown, in some embodiments, the second engaging portion **1643** can also be formed integrally in the housing **1640** and does not have to be formed by a separate part which is inserted into the housing.

[0308] In some embodiments, the first engaging portion **1650** and the second engaging portion **1643** are configured such that they can form-fittingly engage when the carrying portion **1614** is in the use position. In some embodiments, the second engaging portion **1643** includes two recesses, a first recess **1644** and a second recess **1645**. The first recess **1644** and the second recess **1645** are arranged at a predetermined angle to each other. In some embodiments, the angle can be 90 degrees. In some embodiments, the first recess **1644** and the second recess **1645** are configured as recesses in the axial direction of the axis of rotation. The first engaging portion **1650** is configured to be selectively engaged, when the first engaging portion **1650** is aligned with the first recess **1644** or the second recess **1645**, by a movement along the axis of rotation D into the first recess **1644** or into the second recess **1645** in order to generate a positive engagement which blocks a rotation of the frame portion **1631** relative to the supporting portion **1612**.

[0309] In the illustrative embodiment in FIG. **46**, the first engaging portion **1650** is in positive mechanical engagement with the second engaging portion **1643**. In some embodiments, the carrying portion **1614** is positioned in the use position, as illustrated in FIG. **44**.

[0310] In some embodiments, the ring-like attachment **1647** also serves as a stop or supporting portion for an urging member **1618**, which may be configured as a spring **1649**. In some embodiments, between the ring-like attachment **1647** and a housing inner wall of the housing **1640** facing the ring-like attachment **1647**, the spring **1649** is provided such that it applies a force on the ring-like attachment **1647** which urges or pretensions the ring-like attachment **1647** and the first engaging portion **1650** in the direction of the second engaging portion **1643**. In some embodiments, an engagement between the first engaging portion **1650** and the second engaging portion **1643** can

thus only be released by moving the first engaging portion **1650** away from the second engaging portion **1643** in the direction of the axis of rotation. In some embodiments, this can be done by a user displacing the carrying portion **1614**, for example the frame arrangement **1630**, in the direction T along the axis of rotation D and relative to the supporting portion **1612** against the urging force, as indicated in FIG. **44**. In this way, the carrying portion **1614** can be moved into a release position in which the engagement between the first engaging portion **1650** and the second engaging portion **1643** is released and therefore a rotation of the carrying portion **1614** in the direction of rotation R relative to the supporting portion **1612** is possible. At the same time, the arrangement can be such that the engagement between the first engaging portion **1650** and the second engaging portion **1643** takes place automatically by the acting urging force as soon as the carrying portion **1614** reaches the use position or the stowage position. In some embodiments, the engaging portion **1650** is automatically engaged into the respective recess by the urging force of the urging member, so that a locking between the carrying portion **1614** and the supporting portion **1612** can take place automatically and without any action of the user.

[0311] In some embodiments, carrying arrangement **1600** is shown, for example, in FIGS. **48** to **53**. In some embodiments, the carrying arrangement **1600** is configured for carrying an object. In the illustrative embodiment shown in FIGS. **48** to **53**, the object is a license plate holder **1602**. The carrying arrangement **1600** includes a supporting portion **1612** and a carrying portion **1614**. As shown, for example, in FIGS. **51** and **52**, the supporting portion **1612** includes a recess **1613**. In some embodiments, the recess **1613** serves for fastening to the load carrier **1501**. In some embodiments, a part of the load support platform **1515** is received in the recess **1613**, as shown, for example, in FIGS. **49** and **50**. The supporting portion **1612** is fastened to the load support platform **1515** with a suitable fastening device, for example a screw.

[0312] In some embodiments, the carrying portion **1614** is coupled in an articulated manner to the supporting portion **1612**. In some embodiments, the carrying portion **1614** is rotatably coupled to the supporting portion **1612** via a pivot pin **1616** or bolt. Both portions form a joint **1610**. In some embodiments, the carrying portion **1614** includes a coupling portion **1617** and an attachment portion **1615**. In some embodiments, the fastening portion **1615** serves for carrying the license plate holder **1602**. In some embodiments, the attachment portion **1615** can be configured oblong. The coupling portion **1617** is provided on the attachment portion **1615**. In some embodiments, the coupling portion **1617** protrudes from the attachment portion **1615** in a direction which is transverse to the longitudinal direction of the attachment portion **1615** and faces away from the license plate holder **1602**. In some embodiments, the coupling portion **1617** and the attachment portion **1615** can be formed integrally. An opening for receiving the pivot pin **1616** is provided in a free end portion of the coupling portion **1617**. The free end portion of the coupling portion **1617** is received in a recess of the supporting portion **1612**. FIG. **53** illustrates, for example, how the free end portion of the coupling portion **1617** is received in the recess of the supporting portion **1612** and the pivot pin **1616** is passed through the supporting portion **1612** and the coupling portion **1617**.

[0313] In some embodiments, a first engaging portion **1622** is formed on a side of the free end portion of the coupling portion **1617**. In some embodiments, the engaging portion **1622** includes two recesses **1623**, **1624**. A second engaging portion **1620** is formed on an inner wall delimiting the recess of the supporting portion **1612**, which inner wall faces the engaging portion **1622** or the side of the coupling portion **1617**. In some embodiments, the second engaging portion **1620** includes a protrusion **1621**, which can engage in the recesses **1623**, **1624** when the carrying portion **1614** is correspondingly positioned. The coupling portion **1617** is pretensioned via an urging member **1618**, for example, a spring, such that the first engaging portion **1622** is urged in the direction of the second engaging portion **1620**. The urging member **218** is received, as shown in FIG. **53**, in a cup-shaped recess **1619** of the coupling portion **1617** and is supported on a base of the recess **1619** and on an inner wall of the supporting portion **1612**. The coupling portion **1617** is displaceably held on

the pivot pin **1616**, so that an engagement between the first engaging portion **1622** and the second engaging portion **1620** can be established or released by a movement of the coupling portion **1617** along the pivot pin **1616**. The urging member can be a spring, as illustrated, which is held on the pivot pin. In some embodiments, an engagement is automatically generated due to the action of the urging member **1618** when the engaging portions are positioned in alignment with each other. Such an engagement can then only be released by overcoming the urging force.

[0314] In some embodiments, a movement of the carrying portion **1614** along the axis of rotation releases the engagement. In some embodiments, the engaging portions can be configured such that a rotational movement of the carrying portion **1614** is at least partially translated into a movement along the axis of rotation. In some embodiments, the recesses and/or projections can be configured slanted in the direction of rotation, so that when a rotational force is applied on the carrying portion **1614**, a force is generated in the direction of the axis of rotation on the coupling portion **1617**, whereby the coupling portion is displaced in the lateral direction along the axis of rotation relative to the supporting portion **1612**. In some embodiments, the recesses can be configured with slanted side surfaces on which the projections can slide. The side surfaces are configured such that a relative rotation between the projection and the side surface leads to a movement of the coupling portion **1617** in the direction of the axis of rotation. In some embodiments, the projections and recesses can get out of engagement or the engagement can be released by applying a sufficiently high rotational force on the carrying portion **1614**. In some embodiments, the coupling portion **1617** includes recesses and the supporting portion **1612** includes protrusions, an inverse arrangement is also possible and provided according to an alternative embodiment.

[0315] In the illustrative embodiments shown in FIGS. **54** to **56**, a carrying portion **1614** is rotatably coupled to a supporting portion **1612** by means of a pivot pin **1616**. In some embodiments, the carrying portion **1614** is rotatably and displaceably received on the pivot pin **1616**. In some embodiments, the pivot pin **1616** is coupled to the supporting portion **1612** on one side of the carrying portion **1614**, for example, screwed into the supporting portion **1612**. In some embodiments, the pivot pin **1616** and the supporting portion **1612** form an integral unit. The supporting portion **1612** is attached to a load support platform **1515**. On the other side of the carrying portion **1614**, an urging member **1618** is provided between an end portion of the pivot pin **1616** and the carrying portion **1614** and pushes the carrying portion **1614** onto the supporting portion **1612** or urges the carrying portion **1614** in the direction of the supporting portion **1612**. In some embodiments, the carrying portion **1614** includes a first engaging portion with openings **1623**, **1624**. In some embodiments, the supporting portion **1612** includes a second engaging portion **1620** in the form of a protrusion, which can engage in one of the openings when the carrying portion **1614** is positioned in the use position or the stowage position.

[0316] FIG. **56** shows a state in which the protrusion **1621** is engaged into the opening **1623** and a rotational movement of the carrying portion **1614** is blocked, according to an embodiment. In some embodiments, for releasing the locking, the carrying portion **1614** or a license plate holder **1602** mounted thereon can be displaced by a user along the axis of rotation defined by the pivot pin such that the protrusion is moved out of the opening **1623**. The carrying portion **1614** and the license plate holder **1602** mounted thereon are moved into a release position in which a rotation of the carrying portion about the axis of rotation is possible. The carrying portion **1614** can then be rotated into the stowage position in which the second opening and the protrusion **1621** are aligned such that the protrusion **1621** can engage in the second opening. By the urging force acting on the carrying portion **1614**, the protrusion is securely held in the respective opening and a rotation of the carrying portion **1614** is securely blocked. A housing can be provided over the urging member and the pivot pin, as shown, for example, in FIGS. **54** and **55**.

[0317] It is to be appreciated that the Detailed Description section, and not the Brief Summary and Abstract sections, is intended to be used to interpret the claims. The Summary and Abstract sections may set forth one or more but not all embodiments of the load carrier system and

apparatus, and thus, are not intended to limit the present embodiments and the appended claims. [0318] The present disclosure has been described above with the aid of functional building blocks illustrating the implementation of specified functions and relationships thereof. The boundaries of these functional building blocks have been arbitrarily defined herein for the convenience of the description. Alternate boundaries can be defined so long as the specified functions and relationships thereof are appropriately performed.

[0319] The foregoing description of the specific embodiments will so fully reveal the general nature of the disclosure that others can, by applying knowledge within the skill of the art, readily modify and/or adapt for various applications such specific embodiments, without undue experimentation, without departing from the general concept of the present disclosure. Therefore, such adaptations and modifications are intended to be within the meaning and range of equivalents of the disclosed embodiments, based on the teaching and guidance presented herein. It is to be understood that the phraseology or terminology herein is for the purpose of description and not of limitation, such that the terminology or phraseology of the present specification is to be interpreted by the skilled artisan in light of the teachings and guidance.

[0320] The breadth and scope of the present disclosure should not be limited by any of the above-described exemplary embodiments, but should be defined only in accordance with the following claims and their equivalents.

Claims

1. A vehicle mounted load carrier, comprising: a hub; a support member rotatably coupled to the hub; a tilt release mechanism coupled to the support member, the tilt release mechanism comprising a locking arm configured to move between a locked configuration and a released configuration such that in the locked configuration the support member is fixed relative to the hub and in the released configuration the support member can rotate between a first position and a second position; and a tilt memory actuator moveably coupled to the hub or the support member and configured to maintain the locking arm in the released configuration when the locking arm is actuated from the locked configuration to the released configuration.
2. The load carrier of claim 1, wherein a plurality of recesses are formed in the hub or the support member, and wherein the tilt memory actuator moves between a closed configuration and an open configuration, wherein in the closed configuration the tilt memory actuator is disposed over at least a portion of a first recess of the plurality of recesses.
3. The load carrier of claim 2, wherein the tilt memory actuator linearly translates between the closed configuration and the open configuration.
4. The load carrier of claim 2, wherein in the closed configuration, the tilt memory actuator entirely covers the first recess.
5. The load carrier of claim 2, wherein the tilt memory actuator is biased into the closed configuration.
6. The load carrier of claim 2, wherein the locking arm is disposed in the first recess in the locked configuration.
7. The load carrier of claim 2, wherein the plurality of recesses are formed in the hub.
8. The load carrier of claim 2, wherein the tilt memory actuator comprises an actuating surface and a platform surface, and wherein the platform surface is configured to maintain the locking arm in the released configuration.
9. The load carrier of claim 8, wherein the locking arm is configured to contact the actuating surface of the tilt memory actuator when the support arm is rotated in a first direction to move the tilt memory actuator into the open configuration.
10. The load carrier of claim 9, wherein the platform surface is configured to maintain the locking arm in the released configuration when the support arm is rotated in a second direction opposite the

first direction.

11. The load carrier of claim 8, wherein the platform surface is spaced apart from and disposed above a hub surface of the hub.

12. The load carrier of claim 1, wherein the tilt memory actuator is moveably coupled to the hub.

13. The load carrier of claim 1, wherein the support member is further configured to rotate to a third position different from the first position and the second position.

14. The load carrier of claim 1, wherein the tilt memory actuator comprises a plate and a protrusion, and wherein the protrusion is configured to maintain the locking arm in the released configuration.

15. The load carrier of claim 14, wherein a plurality of recesses are formed in the hub, and wherein the tilt memory actuator moves between a closed configuration and an open configuration, wherein in the closed configuration the protrusion is disposed above at least one recess of the plurality of recesses.

16.-106. (canceled)
