

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250272973

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

Missotten; Bart M.A. et al.

SYSTEM AND METHOD FOR AN AGRICULTURAL VEHICLE

Abstract

A system for an agricultural vehicle includes a topper assembly including a cutting disk configured to sever an upper portion of a crop. A sensor system can include a first sensor having a first focal axis and a second sensor having a second focal axis. The second focal axis can intersect the first focal axis. A computing system can be configured to receive an input related to a defined offset, receive the data from the sensor system, determine an intermediate position of the cutting disk based on data from the second sensor, and position the cutting disk at a cutting position along the crop based on data from the first sensor. The cutting position can be the defined offset below the target.

Inventors: Missotten; Bart M.A. (Zedelgem, BE), Li; Yuanyuan (Zedelgem, BE), Seki; Andre Satoshi (Nova Lima, BR), de Oliveira; Rafael Gazeta (Nova Lima, BR), Marcolin Lucca; Joao Augusto (Nova Lima, BR), Ohira; Marcos Ikeguchi (Nova Lima, BR), Carvalho; Sidney Roberto Dias de (Florianópolis, BR), Salem; Feres Azevedo (Florianópolis, BR), d'Avila; Arthur Weschenfelder (Florianópolis, BR)

Applicant: CNH INDUSTRIAL BELGIUM N.V. (Zedelgem, BE); CNH Industrial Brasil Ltda. (Nova Lima, BR)

Family ID: 1000008487942

Appl. No.: 19/062733

Filed: February 25, 2025

Foreign Application Priority Data

BR

10 2024 003768 5

Feb. 26, 2024

Publication Classification

Int. Cl.: G06V20/10 (20220101); A01D45/10 (20060101)

Background/Summary

FIELD OF THE INVENTION

[0001] The present disclosure relates generally to agricultural vehicles, such as sugarcane vehicles, and, more particularly, to systems and methods for a toppler assembly of the agricultural vehicle.

BACKGROUND OF THE INVENTION

[0002] In some cases, agricultural vehicles include an assembly of processing components for processing harvested material. For instance, within a sugarcane vehicle, a toppler assembly can remove an upper portion of the sugar cane crop. The remaining sugarcane stalks may then be conveyed via a feed roller assembly to a chopper assembly that cuts or chops the sugarcane stalks into pieces or billets (e.g., six-inch cane sections). The processed harvested material discharged from the chopper assembly is then directed as a stream of billets and debris into a primary extractor, within which the airborne debris (e.g., dust, dirt, leaves, etc.) is separated from the sugarcane billets. The separated/cleaned billets then fall into an elevator assembly for delivery to an external storage device.

[0003] During the operation of the vehicle, the amount of harvested material that may be delivered to the external storage device is at least partially based on the amount of stalk that is severed by the toppler assembly. Accordingly, systems and methods for monitoring the toppler assembly would be welcomed in the technology.

BRIEF DESCRIPTION OF THE INVENTION

[0004] Aspects and advantages of the invention will be set forth in part in the following description, or may be obvious from the description, or may be learned through practice of the invention.

[0005] In some aspects, the present subject matter is directed to a system for an agricultural vehicle. The system includes a toppler assembly including a cutting disk configured to sever an upper portion of a crop. A sensor system includes a first sensor having a first focal axis and configured to capture data associated with the crop and a second sensor having a second focal axis and configured to capture data associated with the crop, the first focal axis offset from the second focal axis. A computing system includes one or more processors and one or more non-transitory computer-readable media that collectively store instructions that, when executed by the one or more processors, configure the computing system to perform operations. The operations include receiving an input related to a defined offset, detecting an object forward of the toppler assembly based at least partially on the data from the second sensor, determining a target of the crop based at least partially on the data from the second sensor, and positioning the cutting disk at a cutting position along the crop, wherein the cutting position is the defined offset below the target.

[0006] In some aspects, the present subject matter is directed to a computer-implemented method for agricultural harvesting. The computer-implemented method includes receiving, from an input device, an input related to a defined offset. The method further includes determining, with a computing system, a target of a crop based at least partially on data from a first sensor. The method also includes receiving, from a second sensor, data related to an object proximate to a vehicle. Lastly, the method includes positioning a cutting disk at a cutting position along the crop, wherein the cutting position is the defined offset below the target.

[0007] In some aspects, the present subject matter is directed to a system for an agricultural vehicle. The system includes a toppler assembly including a cutting disk configured to sever an

upper portion of a crop. A sensor system includes a first sensor having a first focal axis and a second sensor having a second focal axis, the second focal axis intersecting the first focal axis. A computing system including one or more processors and one or more non-transitory computer-readable media that collectively store instructions that, when executed by the one or more processors, configure the computing system to receive an input related to a defined offset, receive data from the sensor system, determine an intermediate position of the cutting disk based on data from the second sensor, determine a target on the crop based on data from the first sensor, and position the cutting disk at a cutting position along the crop based on data from the first sensor, wherein the cutting position is the defined offset below the target.

[0008] These and other features, aspects, and advantages of the present invention will become better understood with reference to the following description and appended claims. The accompanying drawings, which are incorporated in and constitute a part of this specification, illustrate embodiments of the invention and, together with the description, serve to explain the principles of the invention.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] A full and enabling disclosure of the present invention, including the best mode thereof, directed to one of ordinary skill in the art, is set forth in the specification, which makes reference to the appended figures, in which:

[0010] FIG. 1 illustrates a simplified, side view of an agricultural vehicle in accordance with aspects of the present subject matter;

[0011] FIG. 2 illustrates a side view of a portion of the vehicle having a topper assembly within a field in accordance with aspects of the present subject matter;

[0012] FIG. 3 illustrates a schematic view of a system for a harvesting operation in accordance with aspects of the present subject matter;

[0013] FIG. 4 illustrates a side view of the topper assembly in accordance with aspects of the present subject matter;

[0014] FIG. 5 illustrates a side view of the agricultural vehicle in accordance with aspects of the present subject matter;

[0015] FIG. 6 illustrates a side view of the agricultural vehicle in accordance with aspects of the present subject matter;

[0016] FIG. 7 illustrates a side view of the agricultural vehicle in accordance with aspects of the present subject matter; and

[0017] FIG. 8 illustrates a flow diagram of a method for a harvesting operation in accordance with aspects of the present subject matter.

[0018] Repeat use of reference characters in the present specification and drawings is intended to represent the same or analogous features or elements of the present technology.

DETAILED DESCRIPTION OF THE INVENTION

[0019] Reference now will be made in detail to embodiments of the invention, one or more examples of which are illustrated in the drawings. Each example is provided by way of explanation of the invention, not limitation of the invention. In fact, it will be apparent to those skilled in the art that various modifications and variations can be made in the present invention without departing from the scope or spirit of the invention. For instance, features illustrated or described as part can be used with another embodiment to yield a still further embodiment. Thus, it is intended that the present invention covers such modifications and variations as come within the scope of the appended claims and their equivalents.

[0020] In this document, relational terms, such as first and second, top and bottom, and the like, are

used solely to distinguish one entity or action from another entity or action, without necessarily requiring or implying any actual such relationship or order between such entities or actions. The terms “comprises,” “comprising,” or any other variation thereof, are intended to cover a non-exclusive inclusion, such that a process, method, article, or apparatus that comprises a list of elements does not include only those elements but may include other elements not expressly listed or inherent to such process, method, article, or apparatus. An element preceded by “comprises . . . a” does not, without more constraints, preclude the existence of additional identical elements in the process, method, article, or apparatus that comprises the element.

[0021] As used herein, the terms “first,” “second,” and “third” may be used interchangeably to distinguish one component from another and are not intended to signify a location or importance of the individual components. The terms “coupled,” “fixed,” “attached to,” and the like refer to both direct coupling, fixing, or attaching, as well as indirect coupling, fixing, or attaching through one or more intermediate components or features, unless otherwise specified herein. The terms “upstream” and “downstream” refer to the relative direction with respect to a harvested material within a fluid circuit. For example, “upstream” refers to the direction from which a harvested material flows, and “downstream” refers to the direction to which the harvested material moves. The term “selectively” refers to a component's ability to operate in various states (e.g., an ON state and an OFF state) based on manual and/or automatic control of the component.

[0022] Furthermore, any arrangement of components to achieve the same functionality is effectively “associated” such that the functionality is achieved. Hence, any two components herein combined to achieve a particular functionality can be seen as “associated with” each other such that the desired functionality is achieved, irrespective of architectures or intermedial components. Likewise, any two components so associated can also be viewed as being “operably connected” or “operably coupled” to each other to achieve the desired functionality, and any two components capable of being so associated can also be viewed as being “operably couplable” to each other to achieve the desired functionality. Some examples of operably couplable include, but are not limited to, physically mateable, physically interacting components, wirelessly interactable, wirelessly interacting components, logically interacting, and/or logically interactable components.

[0023] The singular forms “a,” “an,” and “the” include plural references unless the context clearly dictates otherwise.

[0024] Approximating language, as used herein throughout the specification and claims, is applied to modify any quantitative representation that could permissibly vary without resulting in a change in the basic function to which it is related. Accordingly, a value modified by a term or terms, such as “about,” “approximately,” “generally,” and “substantially,” is not to be limited to the precise value specified. In at least some instances, the approximating language may correspond to the precision of an instrument for measuring the value, or the precision of the methods or apparatus for constructing or manufacturing the components and/or systems. For example, the approximating language may refer to being within a ten percent margin.

[0025] Moreover, the technology of the present application will be described in relation to exemplary embodiments. The word “exemplary” is used herein to mean “serving as an example, instance, or illustration.” Any embodiment described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other embodiments. Additionally, unless specifically identified otherwise, all embodiments described herein will be considered exemplary.

[0026] As used herein, the term “and/or,” when used in a list of two or more items, means that any one of the listed items can be employed by itself, or any combination of two or more of the listed items can be employed. For example, if a composition or assembly is described as containing components A, B, and/or C, the composition or assembly can contain A alone; B alone; C alone; A and B in combination; A and C in combination; B and C in combination; or A, B, and C in combination.

[0027] In general, the present subject matter is directed to systems and methods for agricultural

vehicles. The system can include a topper assembly that can remove an upper portion of the sugar cane crop. The remaining sugarcane stalks may then be conveyed via a feed roller assembly to a chopper assembly that cuts or chops the sugarcane stalks into pieces or billets (e.g., six-inch cane sections). The processed harvested material discharged from the chopper assembly is then directed as a stream of billets and debris into a primary extractor, within which the airborne debris (e.g., dust, dirt, leaves, etc.) is separated from the sugarcane billets. The separated/cleaned billets then fall into an elevator assembly for delivery to an external storage device.

[0028] A sensor system can be operably coupled with the topper assembly and can include a first sensor having a first focal axis and a second sensor having a second focal axis. In some instances, the second focal axis can intersect the first focal axis.

[0029] A computing system can including one or more processors and one or more non-transitory computer-readable media that collectively store instructions that, when executed by the one or more processors, can configure the computing system to receive an input related to a defined offset, receive data from the sensor system, determine an intermediate position of the cutting disk based on data from the second sensor, and position the cutting disk at a cutting position along the crop based on data from the first sensor. In some examples, the cutting position is the defined offset below the target.

[0030] In various cases, the systems and methods described herein may lead to a reduction of harvest losses when removing an upper portion of the sugar cane crop, or any other crop as the system can be a proactive and non-reactive system. Moreover, the system provided herein may allow for the possibility of cutting the upper portion of the sugar cane crop on undulating terrain and on fallen crops, among other benefits of the disclosed system.

[0031] Referring now to the drawings, FIG. 1 illustrates a side view of an agricultural vehicle **10** in accordance with aspects of the present subject matter. As shown, the vehicle **10** is configured as a sugarcane vehicle. The sugarcane may include an upper portion C.sub.up that includes one or more leaves and a stalk C.sub.s below the upper portion C.sub.up. It will be appreciated that, in other examples, the vehicle **10** may correspond to any other suitable agricultural vehicle capable of harvesting any other crop without departing from the teachings provided herein.

[0032] As shown in FIG. 1, the vehicle **10** can include a frame **12**, a pair of front wheels **14**, a pair of rear wheels **16**, and an operator's cab **18**. The vehicle **10** may also include a power source **20** (e.g., an engine mounted on the frame **12**) that powers one or both pairs of wheels **14**, **16** via a driveline assembly **22** (e.g., a transmission) to traverse a field **24**. Alternatively, the vehicle **10** may be a track-driven vehicle and, thus, may include tracks driven by the power source **20** as opposed to the illustrated wheels **14**, **16**. The power source **20** may also drive a hydraulic fluid pump **26** to power various components of the vehicle **10**, including the driveline assembly **22**.

[0033] The vehicle **10** may also include a harvested material processing system **28** incorporating various components, assemblies, and/or sub-assemblies of the vehicle **10** for cutting, processing, cleaning, and discharging sugarcane as the stalk C.sub.s is harvested from an agricultural field **24**. For instance, the harvested material processing system **28** may include a topper assembly **30** positioned at the front-end portion of the vehicle **10** to intercept sugarcane as the vehicle **10** is moved in a forward direction. As shown, the topper assembly **30** may include a gathering disk **32** and/or a cutting disk **34**. The gathering disk **32** may be configured to gather the sugarcane stalks C.sub.s so that the cutting disk **34** may be used to cut off an upper portion C.sub.up of each stalk C.sub.s. The height of the topper assembly **30** may be adjustable, which may be raised and lowered by an adjustment assembly **35** that may be hydraulically powered by the hydraulic fluid pump **26** and/or through any other manner (e.g., electrically powered, mechanically powered, manually adjusted, etc.). In some examples, the adjustment assembly **35** may include a pair of arms **36** for adjusting a height of the topper assembly **30**. Additionally or alternatively, the adjustment assembly **35** may allow for the arms **36** and the topper assembly **30** to rotate relative to the frame **12** of the vehicle **10** and/or the topper assembly **30** to rotate relative to the arms **36**.

[0034] The harvested material processing system **28** may also include a sensor system **37** that is configured to capture data associated with the crop **C**. Based on the data, the adjustment assembly **35** may alter the height of the topper assembly **30**. For example, in some cases, the sensor system **37** may capture data indicative of a target **39** associated with the crop **C** and/or an object **41** proximate to the vehicle **10**. Based on the position of the target **39**, the adjustment assembly **35** may alter the height of the topper assembly **30** so that a generally common upper portion **C.sub.up** height may be removed from each of the crops **C** harvested by the vehicle **10**.

[0035] The harvested material processing system **28** may further include a harvested material divider **38**. In general, the harvested material divider **38** may include one or more spiral feed rollers **40**. Each feed roller **40** may include a ground shoe **42** at its lower end portion to assist the harvested material divider **38** in gathering the sugarcane stalks **C.sub.s** for harvesting.

[0036] Moreover, as shown in FIG. **1**, the harvested material processing system **28** may include a knock-down roller **44** positioned near the front wheels **14** and a fin roller **46** positioned behind the knock-down roller **44**. As the knock-down roller **44** is rotated, the sugarcane stalks **C.sub.s** being harvested are knocked down while the harvested material divider **38** gathers the stalks **C.sub.s** from agricultural field **24**. Further, as shown in FIG. **1**, the fin roller **46** may include a plurality of intermittently mounted fins **48** that assist in forcing the sugarcane stalks **C.sub.s** downward. As the fin roller **46** is rotated during the harvest, the sugarcane stalks **C.sub.s** that have been knocked down by the knock-down roller **44** are separated and further knocked down by the fin roller **46** as the vehicle **10** continues to be moved in the forward direction relative to the field **24**.

[0037] Referring still to FIG. **1**, the harvested material processing system **28** of the vehicle **10** may also include a base cutter assembly **50** positioned behind the fin roller **46**. The base cutter assembly **50** may include blades for severing the sugarcane stalks **C.sub.s** as the sugarcane is being harvested. The blades, which may be located on a periphery section of the base cutter assembly **50**, may be rotated by a hydraulic circuit. Additionally, in several examples, the blades may be angled downward to sever the base of the sugarcane as the cane is knocked down by the fin roller **46**.

[0038] Moreover, the harvested material processing system **28** may include a feed roller assembly **52** located downstream of the base cutter assembly **50** for moving the severed stalks **C.sub.s** of sugarcane from base cutter assembly **50** along the processing path of the harvested material processing system **28**. As shown in FIG. **1**, the feed roller assembly **52** may include a plurality of bottom rollers **54** and a plurality of opposed, top rollers **56**. The various bottom and top rollers **54**, **56** may be used to pinch the harvested sugarcane during transport. As the sugarcane is transported through the feed roller assembly **52**, debris (e.g., rocks, dirt, and/or the like) may be allowed to fall through bottom rollers **54** onto the field **24**.

[0039] In addition, the harvested material processing system **28** may include a chopper assembly **58** located at the downstream end section of the feed roller assembly **52** (e.g., adjacent to the rearward-most bottom roller **54** and the rearward-most top roller **56**). In general, the chopper assembly **58** may be used to cut or chop the severed sugarcane stalks **C.sub.s** into pieces or "billets" **60**, which may be, for example, six (6) inches long. The billets **60** may then be propelled towards an elevator assembly **62** of the harvested material processing system **28** for delivery to an external receiver or storage device.

[0040] The pieces of debris **64** (e.g., dust, dirt, leaves, etc.) separated from the sugarcane billets **60** may be expelled from the vehicle **10** through a primary extractor **66** of the harvested material processing system **28**, which may be located downstream of the chopper assembly **58** and may be oriented to direct the debris **64** outwardly from the vehicle **10**. Additionally, an extractor fan **68** may be mounted within an extractor housing **70** of the primary extractor **66** for generating a suction force or vacuum sufficient to force the debris **64** through the primary extractor **66**. The separated or cleaned billets **60**, which may be heavier than the debris **64** expelled through the extractor **66**, may then fall downward to the elevator assembly **62**.

[0041] As shown in FIG. **1**, the elevator assembly **62** may include an elevator housing **72** and an

elevator **74** extending within the elevator housing **72** between a lower, proximal end portion **76** and an upper, distal end portion **78**. In some examples, the elevator **74** may include a looped chain **80** and a plurality of flights or paddles **82** attached to and spaced on the chain **80**. The paddles **82** may be configured to hold the sugarcane billets **60** on the elevator **74** as the sugarcane billets **60** are elevated along a top span of the elevator **74** defined between its proximal and distal end portions **76**, **78**. Additionally, the elevator **74** may include lower and upper sprockets **84**, **86** positioned at its proximal and distal end portions **76**, **78**, respectively. As shown in FIG. **1**, an elevator motor **88** may be coupled to one of the sprockets (e.g., the upper sprocket **86**) for driving the chain **80**, thereby allowing the chain **80** and the paddles **82** to travel in a loop between the proximal and distal end portions **76**, **78** of the elevator **74**.

[0042] Moreover, in some examples, pieces of debris **64** (e.g., dust, dirt, leaves, etc.) separated from the elevated sugarcane billets **60** may be expelled from the vehicle **10** through a secondary extractor **90** of the harvested material processing system **28** coupled to the rear end portion of the elevator housing **72**. For example, the debris **64** expelled by the secondary extractor **90** may be debris **64** remaining after the billets **60** are cleaned and debris **64** expelled by the primary extractor **66**. As shown in FIG. **1**, the secondary extractor **90** may be located adjacent to the distal end portion **78** of the elevator **74** and may be oriented to direct the debris **64** outwardly from the vehicle **10**. Additionally, an extractor fan **92** may be mounted at the base of the secondary extractor **90** to generate a suction force or vacuum sufficient to force the debris **64** through the secondary extractor **90**. The separated, cleaned billets **60**, heavier than the debris **64** expelled through the primary extractor **66**, may then fall from the distal end portion **78** of the elevator **74**. In some instances, the billets **60** may fall downwardly into an elevator discharge opening **94** defined by the elevator assembly **62** into an external storage device, such as a sugarcane billet cart.

[0043] During operation, the vehicle **10** traverses the agricultural field **24** for harvesting sugarcane and receives data related to one or more targets **39** associated with the approaching crop C. Based at least partially on the one or more targets **39** (and/or any other input), the height of the topper assembly **30** is adjusted via the adjustment assembly **35**. With the topper assembly **30** positioned in a defined position, the gathering disk **32** on the topper assembly **30** may function to gather the sugarcane stalks C.sub.s as the vehicle **10** proceeds across the field **24**, while the cutting disk **34** severs the upper portions C.sub.up of the sugarcane crop C for disposal. As the stalks C.sub.s enter the harvested material divider **38**, the ground shoes **42** may set an operating width to determine the quantity of sugarcane entering a throat of the vehicle **10**. The spiral feed rollers **40** then gather the stalks C.sub.s into the throat to allow the knock-down roller **44** to bend the stalks C.sub.s downwardly in conjunction with the action of the fin roller **46**. Once the stalks C.sub.s are angled downward as shown in FIG. **1**, the base cutter assembly **50** may then sever the base of the stalks C.sub.s from field **24**. The severed stalks C.sub.s are then, by the movement of the vehicle **10**, directed to the feed roller assembly **52**.

[0044] The severed sugarcane stalks C.sub.s are conveyed rearwardly by the bottom and top rollers **54**, **56**, which compresses the stalks C.sub.s, making them more uniform, and shakes loose debris **64** to pass through the bottom rollers **54** to the field **24**. At the downstream end portion of the feed roller assembly **52**, the chopper assembly **58** cuts or chops the compressed sugarcane stalks C.sub.s into pieces or billets **60** (e.g., 6-inch cane sections). The processed harvested material discharged from the chopper assembly **58** is then directed as a stream of billets **60** and debris **64** into the primary extractor **66**. The airborne debris **64** (e.g., dust, dirt, leaves, etc.) separated from the billets **60** is then extracted through the primary extractor **66** using suction created by the extractor fan **68**. The separated/cleaned billets **60** may then be directed to an elevator hopper **96** into the elevator assembly **62** and travel upwardly via the elevator **74** from its proximal end portion **76** to its distal end portion **78**. Once the billets **60** reach the distal end portion **78** of the elevator **74**, the billets **60** fall through the elevator discharge opening **94** to an external storage device. If provided, the secondary extractor **90** (with the aid of the extractor fan **92**) blows out trash/debris **64** from the

vehicle **10**, similar to the primary extractor **66**.

[0045] Referring now to FIG. **2**, a side view of a portion of the vehicle **10** within a field **24** is illustrated in accordance with aspects of the present subject matter. As shown in FIG. **2**, the topper assembly **30** may include a frame **100** and a deflector **102**. The topper assembly **30** may further include a pair of gathering disks **32** and/or a cutting disk **34** positioned on an opposing side of the deflector **102** from the cab **18** of the vehicle **10**. The gathering disk **32** may be configured to gather the sugarcane stalks C.sub.s so that the cutting disk **34** may be used to cut off an upper portion C.sub.up of each stalk C.sub.s. As illustrated, each of the pair of gathering disks **32** and/or a cutting disk **34** may be operably coupled with an actuation device **104**, such as a motor, which may be hydraulically powered, pneumatically powered, electrically powered, and/or powered through any other source. Each pair of gathering disks **32** and/or a cutting disk **34** may be respectively coupled with independent actuation devices **104**. Alternatively, any pair of gathering disks **32** and/or a cutting disk **34** may share a common actuation device **104**.

[0046] The topper assembly **30** may be operably coupled with the remaining portions of the vehicle **10**, such as the frame **12**, through an adjustment assembly **35**. The adjustment assembly **35** may include one or more arms **36** and an actuation system **106**. The actuation system **106** may be hydraulically powered, pneumatically powered, electrically powered, and/or powered through any other source for moving the topper assembly **30** between a plurality of positions relative to the field **24**.

[0047] In some examples, the sensor system **37** may be associated with the topper assembly **30**. For example, the sensor system **37** may include one or more sensors **108** that may be operably coupled with the topper assembly **30**, the adjustment assembly **35**, and/or any other component of the vehicle **10** (e.g., the cab **18** of the vehicle **10**). For instance, the sensor system **37** can include first and second sensors **110**, **112** that are configured to capture data related to the field **24** and/or crops C within the field **24**, an operational sensor **114**, an adjustment assembly sensor **116**, and/or any other sensor. In general, the sensor system **37** may be configured to capture data associated with the operation of one or more components of the vehicle **10** and/or data associated with the field **24** surrounding the vehicle **10**. For instance, the sensor system **37** may include one or more sensors **108** that capture data related to the to-be-harvested crops C. In some cases, the data related to the harvested crop C can include a type of crop C to be harvested, a target **39** associated with the crops C, the location/position of the crops C, and/or any other information.

[0048] In various examples, a support **118** may be operably coupled with the frame **100** of the topper assembly **30**. Alternatively, the support **118** may be integrally formed with the support **118**, or any other component of the topper assembly **30**. As illustrated, the support **118** can include a first portion **120** and a second portion **122** that is offset from the first portion **120**. In some examples, the first sensor **110** can be operably coupled with the first portion **120**, and the second sensor **112** operably coupled with the second portion **122**. However, the first sensor **110** and the second sensor **112** may be operably coupled with a common portion of the support **118**, any other component of the topper assembly **30**, and/or any other component of the vehicle **10** without departing from the scope of the present disclosure.

[0049] In some examples, the first sensor **110** may have a first focal axis **124**, which may correspond to a vehicle vertical direction, as generally illustrated by arrow **126** in FIG. **2**. The second sensor **112** may have a second focal axis **128**, which may be perpendicular to the first focal axis **124** and parallel to a vehicle fore-aft axis, as generally illustrated by arrow **130** in FIG. **2**. In other examples, the first focal axis **124** and the second focal axis **128** may be parallel to one another or offset in any other manner without departing from the teachings provided herein. In some instances, the first sensor **110** may be configured to capture data indicative of a distance from a target **39** (e.g., an upper region or a tip of the leaves) of the crop C to the first sensor **110**. Additionally or alternatively, the second may be configured to capture data indicative of a distance from the second sensor **112** to an oncoming obstacle (e.g., taller crops C). Additionally or

alternatively, as shown in FIG. 2, the second sensor **112** may be installed on the cab **18** with a focal axis directed forwardly and/or laterally outward from the cab **18** to capture data forwardly of the cab. In several examples, each of the first sensor **110** and the second sensor **112** may be configured as vision-based or wave-based sensors, such as cameras/imagers, radar sensors, ultrasound sensors, LIDAR devices, etc.

[0050] Additionally or alternatively, the sensor system **37** can include one or more operational sensors **114** that are configured to capture operation-related data associated with the operating conditions of the topper assembly **30**. The operating conditions may include an operational status of the pair of gathering disks **32** and/or a cutting disk **34**, a height of the cutting disk **34**, a tilt angle of the topper assembly **30** relative to the field **24** and/or the frame **12** of the vehicle **10**, and/or any other operating condition. In some instances, the operational sensor **114** can be configured as a pressure sensor that may provide data indicative of a pressure with one or more of the motors, thereby indicating an operating condition of the gathering disk **32** and/or cutting disk **34** operably coupled with the motor.

[0051] Additionally or alternatively, the sensor system **37** can include an adjustment assembly sensor **116** that can be configured to monitor a position of the arms **36** and/or a component of the topper assembly **30**.

[0052] The topper assembly **30**, the adjustment assembly **35**, and/or the sensor system **37** may be operably coupled with a computing system **202**. The computing system **202** may further be configured to receive an input related to a defined offset. The defined offset may be a defined height of the upper portion C.sub.up of the to-be-harvested crop C that is to be severed from the remaining stalks C.sub.s.

[0053] In operation, the computing system **202** can determine a first distance from the target **39** (e.g., a tip of the leaves) to the first sensor **110** based on data captured from the first sensor **110**. Additionally or alternatively, the computing system **202** can determine a second distance from a forwardly located obstacle (e.g., taller plants). In turn, the computing system **202** may determine a cutting position of the cutting disk **34** to sever an upper portion C.sub.up of the crop C that is defined by a defined offset from the target **39** of the crop C. The computing system **202**, based on the determined cutting position, may activate the adjustment assembly **35** to set a height of the cutting disk **34** at the cutting position. As the vehicle **10** moves through the field **24**, the target **39** of subsequent to-be-harvested crops C is determined based on the data, which is then used to alter the position of the cutting disk **34**, such as when the to be harvested crop C is varied from the previously harvested crop C.

[0054] Referring now to FIG. 3, a schematic view of examples of a system **200** is illustrated in accordance with aspects of the present subject matter. In general, the system **200** will be described herein with reference to the vehicle **10** described above with reference to FIGS. 1 and 2. However, it will be appreciated that the disclosed system **200** may generally be utilized with vehicles having any suitable vehicle configuration.

[0055] In several examples, the system **200** may include a computing system **202** and various other components configured to be communicatively coupled to and/or controlled by the computing system **202**, such as various input devices **204** and/or various components of the vehicle **10**. In some examples, the computing system **202** can operate to determine a cutting position of the topper assembly **30** based at least partially on data captured by one or more sensors **108** and, further, to initiate one or more control actions associated with a vehicle **10**, such as by altering a height of a topper assembly **30** based on the defined cutting position. In various instances, the computing system **202** is physically coupled to the vehicle **10**. In other examples, the computing system **202** is not physically coupled to the vehicle **10** (e.g., the computing system **202** may be remotely located from the vehicle **10**) and instead may communicate with the vehicle **10** over a wireless network.

[0056] In general, the computing system **202** may correspond to any suitable processor-based device(s), such as a computing device or any combination of computing devices. Thus, as shown in

FIG. 3, the computing system **202** may generally include one or more processor(s) **206** and associated memory **208** configured to perform a variety of computer-implemented functions (e.g., performing the methods, steps, algorithms, calculations, and the like disclosed herein). As used herein, the term “processor” refers not only to integrated circuits referred to in the art as being included in a computer, but also refers to a controller, a microcontroller, a microcomputer, a programmable logic controller (PLC), an application-specific integrated circuit, and other programmable circuits. Additionally, the memory **208** may generally include memory element(s) including, but not limited to, computer-readable medium (e.g., random access memory (RAM)), computer-readable non-volatile medium (e.g., a flash memory), a floppy disk, a compact disc-read only memory (CD-ROM), a magneto-optical disk (MOD), a digital versatile disc (DVD) and/or other suitable memory elements. Such memory **208** may generally be configured to store information accessible to the processor(s) **206**, including data **210** that can be retrieved, manipulated, created, and/or stored by the processor(s) **206** and instructions **212** that can be executed by the processor(s) **206**.

[0057] In several examples, the data **210** may be stored in one or more databases. For example, the memory **208** may include an input database **214** for storing input data received from the one or more input devices **204**. In some examples, the one or more input devices **204** may include the sensor system **37**, one or more positioning device(s) **216** for generating position data associated with the location of the vehicle **10**, one or more user interfaces **218** for allowing operator inputs to be provided to the computing system **202** (e.g., buttons, knobs, dials, levers, joysticks, touch screens, and/or the like), one or more other internal data sources **220** associated with the vehicle **10** (e.g., other devices, databases, etc.), one or more external data sources **222** (e.g., a remote computing device or server, including, for instance, a machine-learning computing system **202**), and/or any other suitable one or more input devices. The data received from the one or more input devices **204** may, for example, be stored within the input database **214** for subsequent processing and/or analysis.

[0058] It will be appreciated that, in addition to being considered an one or more input devices **204** that allows an operator to provide inputs to the computing system **202**, the user interface **218** may also function as an output device. For example, the user interface **218** may be configured to allow the computing system **202** to provide feedback to the operator (e.g., visual feedback via a display or other presentation device, audio feedback via a speaker or other audio output device, and/or the like).

[0059] As shown in FIG. 3, the memory **208** may also include a crop-related database **224** for storing information or data associated with to-be-harvested crops **C** and/or the field **24**. For example, as indicated above, based on the data received from the one or more input devices **204**, the computing system **202** may be configured to estimate or calculate a type of crop **C** to be harvested, a target **39** of the crop **C**, an object **41** proximate to the vehicle **10**, and/or any other information. The target **39** of the crop **C**, which may be determined based on data from a first sensor **110**, and the position of an object **41** proximate to the vehicle **10**, which may be determined based on data from a second sensor **112**, may be used by the computing system **202** to determine the location/position of the crops **C**. The location/position of the crops **C** may include a height of the crops **C**, a position of the crops **C** relative to one another, a location of the crops **C** relative to a field **24**, a verticality of the crops **C** (e.g., whether crops are growing in a vertical duration and/or have fallen and are no longer in a generally vertical orientation). The data may then be stored within the crop-related database **224** for subsequent processing and/or analysis.

[0060] Additionally, as shown in FIG. 3, the memory **208** may include an operation-related database **226** for storing information or data associated with the harvest-related parameter(s) for the vehicle **10**. For example, as indicated above, based on the input data received from the one or more input devices **204**, the computing system **202** may be configured to estimate or calculate a position of the topper assembly **30** such that the cutting disk **34** is positioned at the cutting position, which

may be a defined offset from the top of the to be harvested crop C. The topper assembly **30** position may then be stored within the operation-related database **226** for subsequent processing and/or analysis.

[0061] Moreover, in several examples, the memory **208** may also include a location database **228** storing location information about the vehicle **10** and/or information about the field **24** being processed (e.g., a field map). Such location database **228** may, for example, correspond to a separate database or may form part of the input database **214**. As shown in FIG. **3**, the computing system **202** may be communicatively coupled to the positioning device(s) **216** installed on or within the vehicle **10**. For example, in some examples, the positioning device(s) **216** may be configured to determine the exact location of the vehicle **10** using a satellite navigation position system (e.g., a GPS, a Galileo positioning system, the Global Navigation satellite system (GLONASS), the BeiDou Satellite Navigation and Positioning system, and/or the like). In such an example, the location determined by the positioning device(s) **216** may be transmitted to the computing system **202** (e.g., in the form of coordinates) and subsequently stored within the location database **228** for subsequent processing and/or analysis.

[0062] Additionally, in several examples, the location data stored within the location database **228** may also be correlated to all or a portion of the input data stored within the input database **214**. For instance, in some examples, the location coordinates derived from the positioning device(s) **216** and the data received from the input devices **204** may both be time-stamped. In such an example, the time-stamped data may allow the data received from the input devices **204** to be matched or correlated to a corresponding set of location coordinates received from the positioning device(s) **216**, thereby allowing the precise location of the portion of the field **24** associated with the input data to be known (or at least capable of calculation) by the computing system **202**.

[0063] Moreover, by matching the input data to a corresponding set of location coordinates, the computing system **202** may also be configured to generate or update a corresponding field map associated with the field **24** being processed. For example, in instances in which the computing system **202** already includes a field map stored within its memory **208** that includes location coordinates associated with various points across the field **24**, the input data received from the input devices **204** may be mapped or correlated to a given location within the field map. Alternatively, based on the location data and the associated image data, the computing system **202** may be configured to generate a field map for the field **24** that includes the geo-located input data associated therewith.

[0064] Referring still to FIG. **3**, in several examples, the instructions **212** stored within the memory **208** of the computing system **202** may be executed by the processor(s) **206** to implement a data analysis module **230**. In general, the data analysis module **230** may be configured to analyze the data (e.g., a set of data received at a given time or within a given time period or a subset of the data, which may be determined through a pre-processing method) to determine the target **39** of the crop C using any algorithm. In some instances, the data analysis module **230** can cooperatively operate with or otherwise leverage a machine-learned model **232** to analyze the data **224** to determine the target **39** of the crop C. In some examples, a color-based algorithm may be utilized that relies on color differences to determine a target **39** (e.g., a maximum height) of the crop C and/or an object **41** proximate to the vehicle **10**. In further examples, the model may include an algorithm that identifies the differences in the reflectivity or spectral absorption between the upper portion C.sub.up of the crop C and the stalks C.sub.s contained within the data.

[0065] Additionally or alternatively, the data analysis module **230** may be configured to analyze the operation-related data (e.g., a set of operation-related data received at a given time or within a given time period or a subset of the operation-related data, which may be determined through a pre-processing method) to determine the position of the cutting disk **34** using any algorithm. In some instances, the data analysis module **230** can cooperatively operate with or otherwise leverage a machine-learned model **232** to analyze the operation-related data **226** to determine the position of

the cutting disk **34**.

[0066] Referring still to FIG. 3, the instructions **212** stored within the memory **208** of the computing system **202** may also be executed by the processor(s) **206** to implement a control module **234**. The control module **234** may be configured to adjust the position of the cutting disk **34** when the position of the cutting disk **34** is varied from a cutting position by controlling one or more components of the adjustment assembly **35**. In general, the cutting position is defined as a position along the crop C that is a defined offset below the target **39** of the crop C. Thus, the system **200** can detect a target **39** of the crop C and reactively adjust a position of the topper assembly **30** so that a generally common upper portion C.sub.up height is severed from the crop C.

[0067] Moreover, as shown in FIG. 3, the computing system **202** may also include a communications interface **236** to communicate with any of the various other system components described herein. For instance, one or more communicative links or interfaces (e.g., one or more data buses and/or wireless connections) may be provided between the communications interface **236** and the one or more input devices **204** to allow data transmitted from the one or more input devices **204** to be received by the computing system **202**. Additionally, as shown in FIG. 3, one or more communicative links or interfaces (e.g., one or more data buses and/or wireless connections) may be provided between the communications interface **236** and one or more electronically controlled components of the vehicle **10** to allow the computing system **202** to control the operation of such system components.

[0068] Referring now to FIGS. 3-7, in operation, as the vehicle **10** traverses a field **24**, a first sensor **110** may be installed on the topper assembly **30** (and/or any other location of the vehicle **10**) for capturing vision-based data of the to-be-harvested crop C (and/or previously harvested portions of the field **24**). The first sensor **110** may be configured to capture vision-based data relative to a first focal axis **124** of the first sensor **110**. In some cases, the first focal axis **124** may correspond to a vehicle vertical direction. In such instances, the first sensor **110** may be positioned vehicle forward of the cutting disk **34** and/or otherwise positioned relative to the cutting disk **34**. The computing system **202** may determine the target **39** of the crop C below the first sensor **110** based at least partially on the data captured by the first sensor **110**. Additionally or alternatively, the data can include a type of crop C to be harvested, a location/position of the crops C, and/or any other information.

[0069] In some instances, the first sensor **110** may be positioned at a fixed distance d from the cutting disk **34**. Moreover, a defined offset O may be a defined height of the upper portion C.sub.up of the to-be-harvested crop C that is to be severed from the remaining stalks C.sub.s. As such, a cutting height may be determined by the computing system **202** that is equal to a height difference hd between the fixed distance d from the cutting disk **34** to the first sensor **110** and the defined offset O . As such, in operation, the topper assembly **30** may be manipulated to maintain the first sensor **110** at a distance from the target **39** of the crop C that is equal to the height difference hd .

[0070] Additionally or alternatively, the second sensor **112** may be installed on the topper assembly **30** (and/or any other location of the vehicle **10**) for capturing vision-based data of the to-be-harvested crop C (and/or previously harvested portions of the field **24**). The second sensor **112** may be configured to capture vision-based data relative to a second focal axis **128** of the second sensor **112**. In some cases, the second focal axis **128** may be perpendicular to or otherwise intersect the first focal axis **124**. Additionally or alternatively, the second focal axis **128** may be parallel to a vehicle fore-aft axis. The computing system **202** may determine an object **41** proximate to the vehicle **10**, such as crop C, forwardly of the vehicle **10** based at least partially on the data captured by the second sensor **112**. Additionally or alternatively, the data can include a type of crop C to be harvested, a location/position of the crops C, and/or any other information.

[0071] In some examples, the second sensor **112** may have a second focal axis **128** that is offset from a horizontal axis **124** relative to the frame **12** of the vehicle **10** and/or parallel to a cutting axis **140** that extends vertically forward of the cutting position. In operation, the computing system **202**

may be configured to estimate a height of the crop C based on the data from the second sensor **112** before the first sensor **110** is positioned above the detected crop C. As such, the data from the second sensor **112** may be used to determine an intermediate position of the cutting disk **34** and a subsequent cutting position may be determined based on the data from the first sensor **110**.

[0072] In various examples, the second sensor **112** can capture data that may be used to generate a point cloud (or other representation of the captured data) of the canopy profile of the crop C. Based on the canopy profile, the adjustment assembly **35** may alter the position of the topper assembly **30**. In turn, the computing system **202** can determine a final cutting position C_p based on data from the first sensor **110**. In some examples, the second sensor **112** may also be configured to capture data related to crops C that will be harvested in an upcoming pass. In such instances, the data may be used to determine a canopy profile proactively so that one or more alterations of the topper assembly **30** may be preprogrammed prior to the crop C being the next to be harvested crop C. Additionally or alternatively, the canopy profile may be captured in conjunction with location data so that a canopy profile map may be created. The canopy profile map may be provided to one or more input devices **204** and/or other electronic devices to improve the productivity and yield of the field **24**.

[0073] With further reference to FIGS. 3-7, through the use of the sensor system **37** including the first sensor **110** and the second sensor **112** described herein, the vehicle **10** may be configured to detect various field conditions and/or crop conditions and proactively adjust the topper assembly **30** to accommodate the field conditions and/or crop conditions. For example, as shown in FIG. 5, the field **24** may include height variations in the form of raised sections **150**, and/or, as shown in FIG. 6, the field **24** may include height variations in the form of lowered sections **152**. In either case, the height variations may cause the crop C, which may be of generally similar height, to have upper portions that are vertically offset from one another. As such, the position of the first sensor **110** may be vertically adjusted to maintain the first sensor **110** in a position that is above the crop C based on data captured from the second sensor **112** and/or any other sensor within the sensor system **37**. In some instances, the second sensor **112** may capture vision-based data that is forward of the vision-based data of the first sensor **110**. As such, the data from the second sensor **112** may be used to determine an intermediate position of the cutting disk **34** and a subsequent cutting position may be determined based on the data from the first sensor **110**.

[0074] As shown in FIG. 7, the crop C may be in a fallen and/or otherwise non-vertical position. In such instances, the position of the first sensor **110** may be vertically lowered to maintain the first sensor **110** in a position that is above the crop C based on data captured from the second sensor **112** and/or any other sensor within the sensor system **37**. In some cases, the lowering of the first sensor **110** before the first sensor **110** is vertically above the to be cut crop may allow for increased clarity of the second sensor **112** for increased detection of the target **39** of the crop C. As provided herein, the second sensor **112** may capture vision-based data that is forward of the vision-based data of the first sensor **110**. As such, the data from the second sensor **112** may be used to determine an intermediate position of the cutting disk **34** and a subsequent cutting position may be determined based on the data from the first sensor **110**.

[0075] Additionally or alternatively, the sensor system **37** may further be configured to detect a vehicle **10**, such as a trailer, within the field **24**. Moreover, once a vehicle is detected, the location of the vehicle relative to the vehicle **10** and/or type of vehicle may be established. Furthermore, when the vehicle is detected within a defined zone proximate to the vehicle **10** and is identified as a trailer that is capable of retaining harvested crop, the vehicle **10** may automatically and/or within operator intervention, begin directing the harvested crop C into the vehicle.

[0076] Referring now to FIG. 8, a flow diagram of a method **300** for operating an agricultural vehicle is illustrated in accordance with aspects of the present subject matter. In general, the method **300** will be described herein with reference to the agricultural vehicle **10** and related components described with reference to FIGS. 1-7. It will be appreciated, however, that the

disclosed method **300** may be implemented with vehicles having any other suitable configurations and/or within systems having any other suitable system configuration. In addition, although FIG. **8** depicts steps performed in a particular order for purposes of illustration and discussion, the methods discussed herein are not limited to any particular order or arrangement. One skilled in the art, using the disclosures provided herein, will appreciate that various steps of the method disclosed herein can be omitted, rearranged, combined, and/or adapted in various ways without deviating from the scope of the present disclosure.

[0077] As shown in FIG. **8**, at **(302)**, the method **300** may include receiving, from an input device, an input related to a defined offset. The defined offset may be a defined height of the upper portion of the to-be-harvested crop that is to be severed from the remaining stalks.

[0078] At **(304)**, the method **300** can include determining a target of the crop based at least partially on data from a first sensor with a computing system. At **(306)**, the method can include receiving data related to an oncoming object from a second sensor. In various examples, a first focal axis of the first sensor is configured to align with a vehicle vertical direction, and a second focal axis of the second sensor is configured to intersect the first focal axis.

[0079] In some cases, the method **300**, at **(308)**, can further include determining one or more height variations of the field based on data from the first sensor or the second sensor.

[0080] At **(310)**, the method **300** can include positioning a cutting disk at a cutting position along the crop. In some instances, the cutting position is the defined offset below the target. In some cases, positioning the cutting disk at the cutting position along the crop can further include, at **(312)**, determining an intermediate position of the cutting disk based on the data provided by the second sensor before the first sensor is positioned above the target. In some examples, the cutting position is determined when a focal axis of the first sensor passes a target. Additionally or alternatively, the intermediate position is at least partially based on the detected one or more height variations positioning a cutting disk at a cutting position along the crop

[0081] At **(314)**, the method **300** can include activating an adjustment assembly to alter a position of the cutting disk relative to a frame of the vehicle. As provided herein, the cutting disk is configured to sever an upper portion of the crop that is defined by a defined offset from the target of the crop. The severed crop may then be harvested by a harvesting system of the vehicle.

[0082] In various examples, the method **300** may implement machine learning methods and algorithms that utilize one or several machine learning techniques including, for example, decision tree learning, including, for example, random forest or conditional inference trees methods, neural networks, support vector vehicles, clustering, and Bayesian networks. These algorithms may include computer-executable code that may be retrieved by the computing system and/or through a network/cloud and may be used to evaluate and update the boom deflection model. In some instances, the machine learning engine may allow for changes to the boom deflection model to be performed without human intervention.

[0083] It is to be understood that the steps of any method disclosed herein may be performed by a computing system upon loading and executing software code or instructions that are tangibly stored on a tangible computer-readable medium, such as on a magnetic medium, e.g., a computer hard drive, an optical medium, e.g., an optical disc, solid-state memory, e.g., flash memory, or other storage media known in the art. Thus, any of the functionality performed by the computing system described herein, such as any of the disclosed methods, may be implemented in software code or instructions that are tangibly stored on a tangible computer-readable medium. The computing system loads the software code or instructions via a direct interface with the computer-readable medium or via a wired and/or wireless network. Upon loading and executing such software code or instructions by the controller, the computing system may perform any of the functionality of the computing system described herein, including any steps of the disclosed methods.

[0084] The term “software code” or “code” used herein refers to any instructions or set of instructions that influence the operation of a computer or controller. They may exist in a computer-

executable form, such as vehicle code, which is the set of instructions and data directly executed by a computer's central processing unit or by a controller, a human-understandable form, such as source code, which may be compiled in order to be executed by a computer's central processing unit or by a controller, or an intermediate form, such as object code, which is produced by a compiler. As used herein, the term "software code" or "code" also includes any human-understandable computer instructions or set of instructions, e.g., a script, that may be executed on the fly with the aid of an interpreter executed by a computer's central processing unit or by a controller.

[0085] This written description uses examples to disclose the technology, including the best mode, and also to enable any person skilled in the art to practice the technology, including making and using any devices or systems and performing any incorporated methods. The patentable scope of the technology is defined by the claims, and may include other examples that occur to those skilled in the art. Such other examples are intended to be within the scope of the claims if they include structural elements that do not differ from the literal language of the claims, or if they include equivalent structural elements with insubstantial differences from the literal language of the claims.

Claims

1. A system for an agricultural vehicle, the system comprising: a topper assembly including a cutting disk configured to sever an upper portion of a crop; a sensor system including a first sensor having a first focal axis and configured to capture data associated with the crop and a second sensor having a second focal axis and configured to capture data associated with the crop, the first focal axis offset from the second focal axis; and a computing system including one or more processors and one or more non-transitory computer-readable media that collectively store instructions that, when executed by the one or more processors, configure the computing system to perform operations, the operations comprising: receiving an input related to a defined offset; detecting an object forward of the topper assembly based at least partially on the data from the second sensor; determining a target of the crop based at least partially on the data from the second sensor; and positioning the cutting disk at a cutting position along the crop, wherein the cutting position is the defined offset below the target.
2. The system of claim 1, wherein each of the first sensor and the second sensor is a vision-based sensor, and wherein the data is image data.
3. The system of claim 1, wherein the target is a maximum height of the crop.
4. The system of claim 1, wherein the first sensor is positioned at least partially vehicle forward of the cutting disk.
5. The system of claim 1, further comprising: an input device configured to provide the defined offset to the computing system.
6. The system of claim 1, wherein the first sensor is positioned vehicle forward of the second sensor.
7. The system of claim 6, wherein the data captured by the second sensor is at least partially forward of the first sensor.
8. The system of claim 1, wherein the first focal axis is configured to align with a vehicle vertical direction and the second focal axis is configured to intersect the first focal axis.
9. The system of claim 1, further comprising: an adjustment assembly configured to alter a position of the cutting disk relative to a frame of a vehicle.
10. A computer-implemented method for agricultural harvesting, the computer-implemented method comprising: receiving, from an input device, an input related to a defined offset; determining, with a computing system, a target of a crop based at least partially on data from a first sensor; receiving, from a second sensor, data related to an object proximate to a vehicle; and positioning a cutting disk at a cutting position along the crop, wherein the cutting position is the

defined offset below the target.

11. The computer-implemented method of claim 10, wherein positioning of the cutting disk at the cutting position along the crop further comprises determining an intermediate position of the cutting disk based on the data provided by the second sensor before the first sensor being positioned above the target.

12. The computer-implemented method of claim 11, wherein the cutting position is determined when a focal axis of the first sensor passes the target.

13. The computer-implemented method of claim 11, further comprising: determining, with the computing system, one or more height variations of a field, wherein the intermediate position is at least partially based on the one or more height variations.

14. The computer-implemented method of claim 10, wherein a first focal axis of the first sensor is configured to align with a vehicle vertical direction, and a second focal axis of the second sensor is configured to intersect the first focal axis.

15. The computer-implemented method of claim 14, wherein positioning the cutting disk at the cutting position along the crop further comprises activating an adjustment assembly to alter a position of the cutting disk relative to a frame of the vehicle.

16. A system for an agricultural vehicle, the system comprising: a topper assembly including a cutting disk configured to sever an upper portion of a crop; a sensor system including a first sensor having a first focal axis and a second sensor having a second focal axis, the second focal axis intersecting the first focal axis; and a computing system including one or more processors and one or more non-transitory computer-readable media that collectively store instructions that, when executed by the one or more processors, configure the computing system to: receive an input related to a defined offset; receive data from the sensor system; determine an intermediate position of the cutting disk based on data from the second sensor; determine a target on the crop based on data from the first sensor; and position the cutting disk at a cutting position along the crop based on data from the first sensor, wherein the cutting position is the defined offset below the target.

17. The system of claim 16, where the computing system is further configured to: generate a canopy map based on a maximum height of the crop.

18. The system of claim 17, wherein the computing system is further configured to: determine one or more height variations of a field, wherein the intermediate position is at least partially based on the one or more height variations.

19. The system of claim 16, wherein each of the first sensor and the second sensor is a vision-based sensor.

20. The system of claim 16, further comprising: an adjustment assembly configured to alter a position of the cutting disk relative to a frame of a vehicle.
