

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250273819

Kind Code

A1

Publication Date

August 28, 2025

Inventor(s)

HAYAKAWA; Isamu

POWER STORAGE APPARATUS AND BATTERY PACK STRUCTURE

Abstract

A power storage apparatus includes: a plurality of stacked metal plates; and a sealing body for sealing an interior space formed between two adjacent metal plates of the plurality of the metal plates, in which the plurality of the metal plates include a first metal plate which is a positive terminal electrode, a second metal plate which is a negative terminal electrode, and a plurality of third metal plates which are a plurality of bipolar electrodes provided between the first metal plate and the second metal plate, each of the plurality of the bipolar electrodes includes a voltage detection terminal, each of the plurality of the third metal plates includes a positive electrode formed on one surface of the third metal plate and a negative electrode formed on the other surface of the third metal plate, and a support member is provided in the interior space.

Inventors: HAYAKAWA; Isamu (Okazaki-shi Aichi-ken, JP)

Applicant: TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota-shi Aichi-ken, JP)

Family ID: 1000008490693

Assignee: TOYOTA JIDOSHA KABUSHIKI KAISHA (Toyota-shi Aichi-ken, JP)

Appl. No.: 19/049027

Filed: February 10, 2025

Foreign Application Priority Data

JP 2024-025746

Feb. 22, 2024

Publication Classification

Int. Cl.: H01M50/474 (20210101); H01M4/02 (20060101); H01M10/48 (20060101);
H01M50/204 (20210101); H01M50/477 (20210101); H01M50/486 (20210101)

U.S. Cl.:

CPC **H01M50/474** (20210101); **H01M4/02** (20130101); **H01M10/482** (20130101);
H01M50/204 (20210101); **H01M50/477** (20210101); **H01M50/486** (20210101);
H01M2004/029 (20130101)

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

[0001] This application is based upon and claims the benefit of priority from Japanese patent application No. 2024-025746, filed on Feb. 22, 2024, the disclosure of which is incorporated herein in its entirety by reference.

BACKGROUND

[0002] The present disclosure relates to a power storage apparatus and a battery pack structure.

[0003] Patent Literature 1 discloses a power storage module in which a plurality of bipolar electrodes are stacked. [0004] Patent Literature 1: Japanese Unexamined Patent Application Publication No. 2021-174632

SUMMARY

[0005] A bipolar electrode has a structure in which a positive electrode is formed on one side of a metal plate (a current collector) and a negative electrode is formed on the other side of the metal plate. A positive electrode and a negative electrode can be easily formed by coating a metal plate with an active material.

[0006] On the other hand, in the case where a metal plate has a region that is not coated (a non-coated part), buckling due to the own weight of the metal plate may occur in the non-coated part when a plurality of bipolar electrodes are stacked. In addition, in the case where a thermal stress is repeatedly applied to the power storage module due to temperature change, fracture may occur in the buckled metal plate.

[0007] The present disclosure has been made in order to solve the aforementioned problems, and it is an object of the present disclosure to provide a power storage apparatus and a battery pack structure that are resistant to a bending stress.

[0008] According to the present disclosure, a power storage apparatus includes: a plurality of stacked metal plates; and a sealing body for sealing an interior space formed between two adjacent metal plates of the plurality of the metal plates, in which the plurality of the metal plates include a first metal plate which is a positive terminal electrode, a second metal plate which is a negative terminal electrode, and a plurality of third metal plates which are a plurality of bipolar electrodes provided between the first metal plate and the second metal plate, each of the plurality of the bipolar electrodes includes a voltage detection terminal, each of the plurality of the third metal plates includes a positive electrode formed on one surface of the third metal plate and a negative electrode formed on the other surface of the third metal plate, and a support member is provided in the interior space. With this configuration, it is possible to provide a power storage apparatus resistant to a bending stress.

[0009] Further the support member may be an insulating flat plate having durability against a bending stress. With this configuration, it is possible to suppress buckling of the power storage apparatus.

[0010] Further, the support member may be an insulating dot print or a resin rectangular timber provided at the center of the interior space. With this configuration, it is possible to suppress buckling of the power storage apparatus.

[0011] Further, the support member is formed in a region of the third metal plate where the positive

electrode and the negative electrode are not formed. With this configuration, it is possible to suppress buckling of the power storage apparatus.

[0012] Furthermore, a battery pack structure according to the present disclosure is formed by stacking a plurality of the power storage apparatuses. With this configuration, it is possible to provide a battery pack structure that is resistant to a bending stress.

[0013] According to the present disclosure, it is possible to provide a power storage apparatus and a battery pack structure that are resistant to a bending stress.

[0014] The above and other objects, features and advantages of the present disclosure will become more fully understood from the detailed description given hereinbelow and the accompanying drawings.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0015] FIG. 1A is a diagram illustrating a power storage apparatus according to the present disclosure;

[0016] FIG. 1B is a diagram illustrating a power storage apparatus according to the present disclosure;

[0017] FIG. 2A is a diagram illustrating a support member of a power storage apparatus according to the present disclosure;

[0018] FIG. 2B is a diagram illustrating a support member of a power storage apparatus according to the present disclosure;

[0019] FIG. 3A is a diagram illustrating a related power storage apparatus;

[0020] FIG. 3B is a diagram illustrating a related power storage apparatus;

[0021] FIG. 4A is a diagram illustrating buckling and fracture occurring in a molding apparatus; and

[0022] FIG. 4B is a diagram illustrating buckling and fracture occurring in a molding apparatus.

DESCRIPTION OF EMBODIMENTS

[0023] Hereinafter, embodiments of the present disclosure will be described with reference to the drawings. FIG. 1A is a diagram illustrating a power storage apparatus **10** according to the present embodiment.

[0024] The power storage apparatus **10** includes a stacked body having a plurality of stacked metal plates **100**. The plurality of the metal plates **100** are classified into a first metal plate **100A** which is a positive electrode terminal, a second metal plate **100B** which is a negative terminal electrode, and a plurality of third metal plates **100C** constituting a plurality of bipolar electrodes **110** provided between the first metal plate and the second metal plate. In some embodiments, the metal plates are formed of Al, Cu, or the like. A battery pack structure is obtained by stacking a plurality of power storage apparatuses **10**.

[0025] In the configuration example shown in FIG. 1A, the stacked body is provided with the first metal plate **100A**, which is a positive terminal electrode, on an upper surface in the stacking direction, and the second metal plate **100B**, which is a negative terminal electrode, on a lower surface in the stacking direction. However, the configuration of the stacked body is not limited to that shown in FIG. 1A, and as regard the positional relationship of a positive electrode and a negative electrode in the stacking direction, a location of a positive terminal electrode and a location of a negative terminal electrode may be interchanged in the configuration shown FIG. 1A.

[0026] FIG. 1B illustrates an enlarged view of the bipolar electrode **110**. Each of the plurality of the bipolar electrodes **110** includes the third metal plate **100C**, a positive electrode **111** formed on one surface of the third metal plate **100C**, and a negative electrode **112** formed on the other surface of the third metal plate. The positive electrode **111** is formed by coating one surface of the third metal

plate **100C** with a positive electrode active material, and the negative electrode **112** is formed by coating the other surface of the third metal plate with a negative electrode active material.

[0027] In some embodiments, a voltage detection terminal (not shown) is provided in a region (non-coated part) of the bipolar electrodes **110** where the positive electrode **111** and the negative electrode **112** are not formed. This facilitates quality control.

[0028] An interior space **120** is formed between two adjacent metal plates of the plurality of the metal plates **100**. As an example, FIG. **1A** shows the interior space **120** formed between the first metal plate **100A** and the third metal plate **100C** adjacent to the first metal plate **100A**.

[0029] The power storage apparatus **10** according to the present disclosure includes sealing bodies **121** and **122** for sealing the interior space **120** and a spacer **123** for maintaining the thickness of the stacked body. In some embodiments, the sealing bodies **121** and **122** have chemical resistance against an electrolyte (not shown) to be filled in the interior space **120**, and a resin material such as polypropylene is used, for example.

[0030] The power storage apparatus **10** according to the present disclosure includes a support member **130** in the interior space **120**. In some embodiments, the support member **130** is provided in a region (a non-coated part) of the third metal plate **100C** where the positive electrode **111** and the negative electrode **112** are not formed.

[0031] In some embodiments, the support member **130** is an insulating flat plate having durability against a bending stress. As shown in FIGS. **2A** and **2B**, as the support member **130**, a dot print (see FIG. **2A**) or a resin rectangular timber (see FIG. **2B**) may be provided at the center of the interior space **120**. In some embodiments, the dot print and the resin rectangular timber have insulating properties.

[0032] With such a configuration, buckling of the third metal plate **100C** due to its own weight can be prevented, thereby providing a power storage apparatus that is resistant to a bending stress.

[0033] As a comparative example, FIG. **3A** shows a configuration of a power storage apparatus in which the support member **130** is not provided. In the third metal plate **100C** of the bipolar electrodes **110**, a buckling may occur in a region (non-coated part) where the positive electrode **111** and the negative electrode **112** are not formed, thereby causing fracture in the metal plate (see FIG. **3B**).

[0034] The mechanism of buckling and fracture will be described with reference to FIGS. **4A** and **4B**. FIGS. **4A** and **4B** show a plan view of the power storage apparatus shown in FIG. **3A** in which illustration of the first metal plate **100A** is omitted and the corner portion is enlarged. The moment of inertia of area of the region (the non-coated part) of the third metal plate **100C** where the positive electrode **111** and the negative electrode **112** are not formed is small. In addition, since the non-coated part extends in the longitudinal direction and the transverse direction in the plan view, buckling easily occurs in this region due to the own weight of the metal plate (see FIG. **4A**).

[0035] Since the sealing bodies **121** and **122** are made of a resin material, they easily expand and contract due to a change in the temperature of the power storage apparatus. For example, in the case where the temperature of the power storage apparatus in which buckling has occurred is set at a low temperature, a stress acts in the direction of the arrow shown in FIG. **4B**, and a fracture occurs due to buckling and shrinkage of the resin material.

[0036] In the power storage apparatus **10** according to the present disclosure, by providing an insulating flat plate having durability against a bending stress to the non-coated part, buckling due to the own weight of the metal plate can be prevented. In the power storage apparatus **10** according to the present disclosure, by providing an insulating dot print or a resin rectangular timber to the non-coated part, the moment of inertia of area of the metal plate can be compensated, and buckling due to the own weight of metal plate can be prevented.

[0037] In this way, a power storage apparatus and a battery pack structure that are resistant to a bending stress can be provided.

[0038] It should be noted that the present disclosure is not limited to the above embodiments, and

may be appropriately modified without departing from the purpose.

[0039] From the disclosure thus described, it will be obvious that the embodiments of the disclosure may be varied in many ways. Such variations are not to be regarded as a departure from the spirit and scope of the disclosure, and all such modifications as would be obvious to one skilled in the art are intended for inclusion within the scope of the following claims.

Claims

1. A power storage apparatus comprising: a plurality of stacked metal plates; and a sealing body for sealing an interior space formed between two adjacent metal plates of the plurality of the metal plates, wherein the plurality of the metal plates include a first metal plate which is a positive terminal electrode, a second metal plate which is a negative terminal electrode, and a plurality of third metal plates which are a plurality of bipolar electrodes provided between the first metal plate and the second metal plate, each of the plurality of the bipolar electrodes includes a voltage detection terminal, each of the plurality of the third metal plates includes a positive electrode formed on one surface of the third metal plate and a negative electrode formed on the other surface of the third metal plate, and a support member is provided in the interior space.
 2. The power storage apparatus according to claim 1, wherein the support member is an insulating flat plate having durability against a bending stress.
 3. The power storage apparatus according to claim 1, wherein the support member is an insulating dot print or a resin rectangular timber provided at a center of the interior space.
 4. The power storage apparatus according to claim 1, wherein the support member is formed in a region of the third metal plate where the positive electrode and the negative electrode are not formed.
 5. A battery pack structure formed by stacking a plurality of the power storage apparatuses according to claim 1.
-