

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402660
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Hawkes; Matthew

Handheld vaping implement

Abstract

A vaping device with quick release interchangeable cartridge is disclosed for atomizing and discharging a composition as a mist for inhalation. The detachable cartridge comprises an atomizer, a transparent reservoir and elongated conductors, and is adapted to quickly attach and detach from an ovoid body using a friction fit or magnetic fit.

Inventors:	Hawkes; Matthew (South Jordan, UT)
Applicant:	Curb Living, Inc. (South Jordan, UT)
Family ID:	88094792
Appl. No.:	17/701643
Filed:	March 22, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230301353 A1	Sep. 28, 2023

Publication Classification

Int. Cl.: A24F40/46 (20200101); A24F40/42 (20200101); A24F40/44 (20200101); A24F40/90 (20200101)

U.S. Cl.:

CPC A24F40/46 (20200101); A24F40/42 (20200101); A24F40/44 (20200101); A24F40/90 (20200101);

Field of Classification Search

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1775947	12/1929	Robinson	N/A	N/A
3200819	12/1964	Gilbert	N/A	N/A
9877505	12/2017	Cameron et al.	N/A	N/A
9936737	12/2017	Cameron et al.	N/A	N/A
10561803	12/2019	Liu et al.	N/A	N/A
10595562	12/2019	Freeman et al.	N/A	N/A
10709173	12/2019	Monsees	N/A	A24F 40/42
10737041	12/2019	Adelaar et al.	N/A	N/A
11083850	12/2020	Hatamian et al.	N/A	N/A
11090449	12/2020	Hatamian et al.	N/A	N/A
11399571	12/2021	Cameron	N/A	N/A
11450420	12/2021	Hatamian et al.	N/A	N/A
11571022	12/2022	Lahoud	N/A	A24B 15/167
11676438	12/2022	Hubbard et al.	N/A	N/A
11701479	12/2022	Robinson et al.	N/A	N/A
11771136	12/2022	Hejazi et al.	N/A	N/A
2014/0027384	12/2013	Little et al.	N/A	N/A
2015/0136158	12/2014	Stevens et al.	N/A	N/A
2015/0181945	12/2014	Tremblay	N/A	N/A
2016/0331022	12/2015	Cameron	N/A	N/A
2017/0209840	12/2016	Swallow et al.	N/A	N/A
2019/0167922	12/2018	Cole	N/A	N/A
2020/0170301	12/2019	Gallagher et al.	N/A	N/A
2020/0222644	12/2019	Mccullough	N/A	N/A
2020/0245692	12/2019	Cameron	N/A	B05B 17/0684
2020/0245694	12/2019	Cameron et al.	N/A	N/A
2020/0276607	12/2019	Aherne	N/A	B05B 17/0646
2021/0059301	12/2020	Hejazi	N/A	N/A
2022/0105284	12/2021	Lahoud et al.	N/A	N/A
2022/0132935	12/2021	Lahoud et al.	N/A	N/A
2022/0287365	12/2021	Alsayar et al.	N/A	N/A
2023/0200453	12/2022	Kilger et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2021101022	12/2020	AU	N/A
201572400	12/2009	CN	N/A
2004249208	12/2003	JP	N/A
WO 2020165777	12/2019	WO	N/A
WO 2022167856	12/2021	WO	N/A
WO 2023017506	12/2022	WO	N/A
WO 2023161645	12/2022	WO	N/A

OTHER PUBLICATIONS

“SyqeAir Inhaler,” webpage <<https://syqe.com/product/syqgear/>>, last accessed Nov. 8, 2023. cited by applicant

English abstract of CN 201572400 U obtained from Google Patents on Feb. 22, 2024. cited by applicant

English abstract of JP 2024-249208 A obtained from Google Patents on Feb. 22, 2024. cited by applicant

Geekvape Max100 Kit User Manual, pp. 1-6, 2023. cited by applicant

Search Report and Written Opinion in International Application No. PCT/US2023/033491, issued Sep. 22, 2023, 13 pages. cited by applicant

ZICOH demo videos [online], [retrieved on Nov. 15, 2023]. Retrieved from the Internet <URL: <https://zicoh.com/demo/>>. cited by applicant

Primary Examiner: Louie; Philip Y

Background/Summary

FIELD OF THE INVENTION

(1) This invention relates to a diffusing and vaping devices, and more particularly relates to vaping devices with quick release and/or interchangeable cartridge(s) which contain, atomize, and discharge a composition as a mist for inhalation of the misted or diffused substance.

BACKGROUND

Description of the Related Art

(2) Atomizers, generators, nebulizers and the like are designed for a wide variety of purposes such as medical, therapeutic, and cosmetic applications. Vaping using e-cigarettes have become a popular substitute for smoking. Using e-cigarettes, vapers can inhale a diffused liquid containing only the active ingredients instead of traditional substances like tobacco, which contain many toxins and tangential substances, including tar.

(3) Vapers cause small droplets of liquid to be suspended in air. Typically, a vaper is adapted to discharge a mist into the mouth. Traditional misters either are not refillable, or contain a reservoir, that while refillable, is inefficient. These reservoirs are often oil-based, diffusing oil which contaminates lung tissue.

(4) In traditional vaping devices, the atomizer can become clogged with residue, and different sized atomizers are needed for oils of different viscosities, making interchange of a plurality of liquids unfeasible as the atomizer is contaminated and not properly sized. Overcoming this problem in the prior art is desirable.

(5) These difficulties inherent in the devices known in the art tend to make the useful life of a vaper much shorter than would otherwise be desirable. Mistifiers are often discarded, perform less favorably than predicted, are not as efficient in terms of conserving expensive contents and/or not reused as commonly as they might otherwise be if improvements to the art were made and if various contents could be swapped out merely by interchanging cartridges or reservoirs or tanks.

(6) Traditional vaping devices do not provide a means for quickly and cleanly interchanging different types of compositions without residue contaminants. A misting device that is operable with water-based cartridges is desirable.

SUMMARY

(7) From the foregoing discussion, it should be apparent that a need exists for an improved handheld vaping implement. Accordingly, the present invention has been developed to provide a vaping apparatus for dispensing of a composition, the vaping apparatus comprising: an ovoid body

comprising a rechargeable battery and a depressible triggering mechanism, the ovoid body defining a hollow interior recess and open top end defining a track within which a protuberance travels; a detachable, ovoid interchangeable cartridge adapted to insert into the open top end, the cartridge detachably engageable with the body, the cartridge comprising: a transparent reservoir having reservoir exterior surfacing, the transparent reservoir defining two conductor channels running longitudinally; a base affixed to the transparent reservoir comprising a protuberance, the base having exterior surfacing recessed inwardly from the reservoir exterior surfacing, the base adapted to insert into the open top end; two elongated, metal conductors each positioned within one of the conductor channels; a ceramic wick adapted to direct fluid housed within the transparent housing to a piezo plate; the piezo plate disposed above the ceramic wick; and a frustoconical tip having an open top end positioned above the transparent reservoir.

(8) The vaping apparatus may further comprise a USB charging port. The vaping apparatus may further comprise a tray inserted into the hollow interior recess adapted to secure the power supply and a triggering mechanism, the tray having a planar top surface defining two or more apertures and a hollow cylindrical recess.

(9) The vaping apparatus may further comprise a plurality of magnets disposed across the top surface of the tray and the ovoid base adapted to form a magnetic fit between the tray and the detachable cartridge.

(10) The tray may further comprise a plurality of threaded protuberances adapted to affix the tray to other components.

(11) The body may be fabricated from a metal alloy. The outlet of the atomizer may comprise an atomizer nozzle.

(12) Reference throughout this specification to features, advantages, or similar language does not imply that all of the features and advantages that may be realized with the present invention should be or are in any single embodiment of the invention. Rather, language referring to the features and advantages is understood to mean that a specific feature, advantage, or characteristic described in connection with an embodiment is included in at least one embodiment of the present invention. Thus, discussion of the features and advantages, and similar language, throughout this specification may, but do not necessarily, refer to the same embodiment.

(13) Furthermore, the described features, advantages, and characteristics of the invention may be combined in any suitable manner in one or more embodiments. One skilled in the relevant art will recognize that the invention may be practiced without one or more of the specific features or advantages of a particular embodiment. In other instances, additional features and advantages may be recognized in certain embodiments that may not be present in all embodiments of the invention.

(14) These features and advantages of the present invention will become more fully apparent from the following description and appended claims, or may be learned by the practice of the invention as set forth hereinafter.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) In order that the advantages of the invention will be readily understood, a more particular description of the invention briefly described above will be rendered by reference to specific embodiments that are illustrated in the appended drawings. Understanding that these drawings depict only typical embodiments of the invention and are not therefore to be considered to be limiting of its scope, the invention will be described and explained with additional specificity and detail through the use of the accompanying drawings, in which:

(2) FIG. 1 is an isometric, perspective view illustrating one embodiment of a handheld vaping instrument in accordance with the present invention;

- (3) FIG. 2 is an exploded perspective view illustrating one embodiment of a detachable cartridge of a handheld vaping instrument in accordance with the present invention;
- (4) FIG. 3A is an exploded, side-perspective view illustrating one embodiment of a handheld vaping instrument in accordance with the present invention;
- (5) FIG. 3B is an exploded, side-perspective view illustrating one embodiment of a handheld vaping instrument in accordance with the present invention;
- (6) FIG. 4A is a top perspective view illustrating one embodiment of a handheld vaping instrument in accordance with the present invention;
- (7) FIG. 4B is a top perspective view illustrating one embodiment of a handheld vaping instrument in accordance with the present invention;
- (8) FIG. 5 is a side perspective view illustrating one embodiment of a handheld vaping instrument in accordance with the present invention;
- (9) FIG. 6 is an exploded, side-perspective view illustrating one embodiment of a detachable cartridge of a handheld vaping instrument in accordance with the present invention;
- (10) FIG. 7 is an exploded, side-perspective view illustrating one embodiment of a handheld vaping instrument in accordance with the present invention; and
- (11) FIGS. 8 and 9 are exploded, perspective views illustrating one embodiment of a handheld vaping instrument in accordance with the present invention.

DETAILED DESCRIPTION

- (12) Reference throughout this specification to “one embodiment,” “an embodiment,” or similar language means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment of the present invention. Thus, appearances of the phrases “in one embodiment,” “in an embodiment,” and similar language throughout this specification may, but do not necessarily, all refer to the same embodiment.
- (13) Furthermore, the described features, structures, or characteristics of the invention may be combined in any suitable manner in one or more embodiments. In the following description, numerous specific details are provided, such as examples of programming, software modules, user selections, network transactions, database queries, database structures, hardware modules, hardware circuits, hardware chips, etc., to provide a thorough understanding of embodiments of the invention. One skilled in the relevant art will recognize, however, that the invention may be practiced without one or more of the specific details, or with other methods, components, materials, and so forth. In other instances, well-known structures, materials, or operations are not shown or described in detail to avoid obscuring aspects of the invention.
- (14) It is an object of the present invention to provide a diffusing and vaping device with quick release interchangeable cartridge or reservoir.
- (15) For the purposes of this invention, the terms “cartridge,” “tank” and “reservoir” are synonymous and interchangeable.
- (16) FIGS. 1-4B illustrate various embodiment of a handheld vaping instrument in accordance with the present invention.
- (17) FIG. 1 depicts a vaping device or apparatus **100** with a quick release interchangeable cartridge **110**, adapted to discharge a composition as a uniform mist for inhalation. The composition may include, without limitation, a composition having nicotine. The composition may include THC for medicinal use. The composition may be water-based rather than oil-based.
- (18) The device **100** provides a quick-release interchangeable cartridge **110** to carry or formulate, contain, and discharge the composition as a uniform mist into the mouth of a user/vaper. In some embodiments, this cartridge **110** may be refillable, and may comprise means known to those of skill in the art for refilling a cartridge, including a screw-down cap, a stopper, a valve, and the like.
- (19) The composition may be formulated directly in an interchangeable cartridge **110** or may be pre-formulated and filled and then quickly loaded into an interior chamber of a container **102** (or base **102**) for one-handed vaping. The composition is atomized to enable formation of the uniform

mist. A base **102** maintains the interchangeable cartridge **110** in an upright or horizontal disposition.

(20) The cartridge **110** comprises an open end **202** (or misting nozzle), which may engages a cap.

(21) A triggering mechanism, or depressible button **104**, is triggered by a user to activate the device **100** on the base **102**, which expels atomized fluid from the misting nozzle **202** into a user's mouth after activating a piezo plate **208**.

(22) In various embodiments, the base **102** comprises an internal battery **306**, which is charged via a USB port **106**.

(23) The body **102**, or base **102**, may be cylindrical or oblong from a lower perspective (i.e., ovoid from a lower and upper perspective). The detachable cartridge **110** is also ovoid or oblong and of the same dimensions from a lower perspective view. A USB port **106** positions within a recess on the lower surface **112**.

(24) In various embodiments, the interchangeable cartridge **110** comprises a frustoconical **210** tip with an open end **202** (or nozzle **202**) from which atomized fluid or mist is dispensed. A piezo plate **208** positions between the nozzle **202** and a ceramic wick **206**. Fluid housed within a transparent housing **224** (or transparent reservoir **224**) is inducted up the wick **206** to the piezo plate **208** and atomized.

(25) Two elongated, metal conductors **214a-b** position within tracks **216** defined on one of a lower cartridge component **218** and the transparent housing **224**. These conductors **214a-b** conduct electricity to the piezo plate **208** upon activation of a tactile or depressible button **104**. These conductors **214a-b** may also traverse conductor channels **220**, or bores, in the transparent housing **202**.

(26) The conductors **114** may taper at a distal end **404**, or be more narrow at said distal ends **404**.

(27) The base **102** may be formed from polymeric or metal alloy materials, including aluminum.

(28) An ovoid base **204** affixes to the transparent housing **224**. In some embodiments, the ovoid base **204** is formed as a single integrated piece with the transparent housing **202**. The apparatus **200** may comprise or consist of all the shown components.

(29) The ovoid base **204** has exterior surfaces which is recessed inward from that of the transparent housing **224** such that the ovoid base may insert into the open top end **402** of the base **102**. A protuberance **222** rises from the ovoid base **204** which mates with a corresponding track **104** (or recess) on the base **102**.

(30) The base **102** defines a hollow interior recess in which a tray **304** is disposed.

(31) In various embodiments, a plurality of magnets **454** affix to the tray **304** and to the base **102** adapted to secure the interchangeable cartridge **110** in place by forming a magnetic fit with magnets affixed to the interchangeable cartridge **110**.

(32) The base **102** may comprise a spring **116**.

(33) The planar top surface **354** of the tray **304** may define two or more apertures **456**.

(34) The tray **304** comprises two sidewalls **308**. The tray secures the USB port **106** and various components relating to the button **104**, including the battery **306** and/or the button **104**. The tray **304** may comprise a planar top face **354** and planar rearward surface **356**. The tray **304** may comprise a plurality of threaded, cylindrical protuberances **352** adapted to affix to other components of the apparatus **300**. The top surface **354** of the tray **304** may also define a hollow cylindrical recess **358** having a bore **360**.

(35) FIGS. 5-8 illustrate various embodiments of a handheld vaping instrument in accordance with the present invention.

(36) As illustrated in FIG. 5, the device **100** comprises a cylindrical body **502** adapted for handheld operation and uniform dispensing of the composition into a mouth. In one embodiment, the body **102** comprises a generally cylindrical shape affixed to a housing **504**. Though in other embodiments, the body **102** may include, without limitation, a rectangular shape, a cubicle shape, and a spherical shape.

(37) The housing **504** provides a gripping surface for enhanced manipulation of the apparatus **500**. The interchangeable cartridge **110** is adapted for quickly loading with a hollow cylindrical recess defined by the body **502**.

(38) In one embodiment, the interchangeable cartridge **110** forms a friction fit engagement between an outer surface of the interchangeable cartridge **110** and the surface of the cavity **812**. In one possible embodiment, the coupling mechanism is a snap-fit connection. In another embodiment, the coupling mechanism is a pressurized twist connection having threaded surfaces **806**. In yet another embodiment, the coupling mechanism enables the interchangeable cartridge **110** to clip in and out of the interior chamber through one-handed manipulation.

(39) The interchangeable cartridge **110** inserts into a cavity **812**. The cavity **812** is sized and dimensioned to contour an exterior surface of the cartridge **110**. The cavity **812** forms an inlet for the detachable cartridge **110**.

(40) Two conductive connection points **604a-b** position on an exterior surface of the cartridge **110**, adapted to come into contact with corresponding connection points within the cavity **812**.

(41) The cartridge **110** may comprise a coupler **702** having an annular flange **710** and two threaded surfaces, one of which is adapted to mate with an interiorly threaded surface **806** on a cylindrical component **808**.

(42) In various embodiments, the cartridge **110** and/or cavity **812** into which the cartridge **110** inserts have one or more planar facets **810** adapted to ensure the cartridge **110** is properly oriented within the cavity **812**.

(43) In various embodiments, the atomizer **208** comprises an ultrasonic nozzle having one or more piezoelectric plates or transducers (including piezoelectric ceramic elements) for atomizing fluid in the container **110**.

(44) Manipulation of the button actuates the atomizer **208**. The button **104** may be either manually-operable or electrically operable. The button **104** may partially protrude from the side of the body **502** for facilitated manipulation. In one embodiment, the button (or trigger mechanism) **104** is a switch that is disposed centrally along the length of the body **502** or base **102** and operatively connected to a pump adapted to pump fluid in the detachable cartridge **110** to the atomizer **208**.

(45) The device **100-800** comprises substantially, a detachable cartridge **110**; a body (or base) **102**, **502**; and an atomizer **208**. The interchangeable cartridge **110** quickly loads and unloads into the interior chamber of the container **502** through a quick release coupling mechanism. An atomizer **208** atomizes eclectic types of compositions in the form of a mist for vaping purposes.

(46) The atomized liquid is dispelled from the misting nozzle **202**. In various embodiments, the detachable cartridge **110** comprises one or more conductive elements which engage (or come in contact with) one or more corresponding conductive elements in the body **502**, **102**. When the cartridge **100** is inserted into the body **502**, **110**, there is electrical conductivity between the triggering mechanism **104** and the atomizer **208**. The triggering mechanism **104** may be activated by depression. The atomizer **208** is in logical connectivity with the triggering mechanism **104** and/or a power supply such as a battery **306**.

(47) In various other embodiments of the present invention, the cartridge **110** and/or body **502**, **102** of the devices **100-800** may comprise circuitry which is configurable to adjust the rate at which the piezo plate atomizes fluid. The circuitry may include computer readable memory which stores historical data about user usage of the device, including which cartridge is used, how long it has been used, and how much liquid is remaining in the cartridge. The historical data may be analyzed by a DBMS (database management system) and historical reports displayed graphically. The historical data may also be used to automatically order replacement cartridges for the device **100**, and other purposes.

(48) The present invention may be embodied in other specific forms without departing from its spirit or essential characteristics. The described embodiments are to be considered in all respects only as illustrative and not restrictive. The scope of the invention is, therefore, indicated by the

appended claims rather than by the foregoing description. All changes which come within the meaning and range of equivalency of the claims are to be embraced within their scope.

Claims

1. A vaping apparatus for dispensing of a composition, the vaping apparatus comprising: body comprising a rechargeable battery and a depressible triggering mechanism, the body defining a hollow interior recess and an open top end defining a track within which a protuberance travels; a detachable, interchangeable cartridge adapted to insert into the open top end, the cartridge detachably engageable with the body, the detachable interchangeable cartridge comprising: a transparent reservoir having reservoir exterior surfacing, the transparent reservoir defining two conductor channels running longitudinally; a base affixed to the transparent reservoir comprising a protuberance, the base having exterior surfacing recessed inwardly from the reservoir exterior surfacing, the base adapted to insert into the open top end; two elongated, metal conductors each positioned within one of the conductor channels; a ceramic wick adapted to direct fluid housed within the transparent reservoir to a piezo plate; the piezo plate disposed above the ceramic wick; and a frustoconical tip having an open top end positioned above the transparent reservoir.
 2. The vaping apparatus of claim 1, further comprising a USB charging port.
 3. The vaping apparatus of claim 1, further comprising a tray inserted into the hollow interior recess adapted to secure the power supply and a triggering mechanism, the tray having a planar top surface defining two or more apertures and a hollow cylindrical recess.
 4. The vaping apparatus of claim 3, further comprising a plurality of magnets disposed across the top surface of the tray and the base adapted to form a magnetic fit between the tray and the detachable cartridge.
 5. The vaping apparatus of claim 3, wherein the tray further comprises a plurality of threaded protuberances adapted to affix the tray to other components.
 6. The vaping apparatus of claim 1, wherein the body is fabricated from a metal alloy.
 7. The vaping apparatus of claim 1, wherein an outlet of the vaping apparatus comprises an atomizer nozzle.
-