

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402760
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Velasquez; Simon

Towel warming assembly including fragrance door

Abstract

A towel warming assembly includes a housing that has an entry extending into an interior of the housing to facilitate one or more towels to be positioned within the housing. A blower is positioned in the housing to blow air into the housing such that the towels are exposed to the air blown by the blower. A heating unit is positioned in the housing to heat air blown by the blower thereby facilitating the towels to be warmed. A control unit is positioned in the electronics space in the housing and the control unit is in communication with the blower and the heating unit. The control unit includes an electronic timer and each of the blower and the heating unit is turned off when the electronic timer counts down the pre-determined duration of time.

Inventors:	Velasquez; Simon (Houston, TX)
Applicant:	Velasquez; Simon (Houston, TX)
Family ID:	87851574
Appl. No.:	17/564421
Filed:	December 29, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20230277016 A1	Sep. 07, 2023

Publication Classification

Int. Cl.: **A47K10/06** (20060101); **A61L2/04** (20060101)

U.S. Cl.:

CPC **A47K10/06** (20130101); **A61L2/04** (20130101);

Field of Classification Search

CPC: A47K (10/06); A61L (2/04); D06F (58/10)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3839622	12/1973	Mastin	219/508	A47K 10/06
D302460	12/1988	Gibson	N/A	N/A
5555640	12/1995	Ou	312/249.9	F26B 25/066
5840589	12/1997	Warner, Jr.	438/505	H01L 21/74
6046436	12/1999	Hunts	219/400	A47K 10/06
6667464	12/2002	Ellis	219/393	A47K 10/06
6840589	12/2004	Uri	N/A	N/A
8058588	12/2010	Gagas	219/400	H05B 3/0071
8481895	12/2012	Taylor	219/535	A47K 10/06
2002/0084730	12/2001	Uri	312/228.1	D06F 58/10
2003/0015513	12/2002	Ellis	219/393	A47K 10/06
2008/0210678	12/2007	Crane	219/392	A47K 10/06
2011/0259864	12/2010	Galietti	N/A	N/A
2018/0320303	12/2017	Valzelli	N/A	D06F 58/10
2018/0347102	12/2017	Um	N/A	D06F 58/10
2018/0347103	12/2017	Lee	N/A	D06F 29/005
2019/0024288	12/2018	Nam	N/A	D06F 37/26
2019/0085493	12/2018	Magnusson	N/A	D06F 18/00
2019/0100866	12/2018	Mangan	N/A	D06F 58/26
2019/0211497	12/2018	Kim	N/A	D06F 73/02
2019/0257025	12/2018	Park	N/A	D06F 71/36
2020/0080254	12/2019	Chang	N/A	D06F 39/083
2020/0375412	12/2019	Wallander	N/A	A61M 21/00
2021/0032797	12/2020	Shin	N/A	D06F 67/005
2021/0047772	12/2020	Jang	N/A	D06F 58/10
2021/0208590	12/2020	Cho	N/A	G07F 17/20
2021/0372030	12/2020	Kang	N/A	D06F 58/203
2022/0074123	12/2021	Jang	N/A	D06F 58/24
2022/0259794	12/2021	Kim	N/A	D06F 58/44
2023/0277016	12/2022	Velasquez	34/329	A61L 2/04
2023/0399789	12/2022	Aneladasu	N/A	D06F 58/26
2024/0167217	12/2023	Jang	N/A	D06F 71/34
2024/0301613	12/2023	Han	N/A	D06F 58/10
2025/0043501	12/2024	Chong	N/A	D06F 57/00
2025/0044026	12/2024	Wallander	N/A	F24H 3/0411
2025/0066976	12/2024	Lee	N/A	D06F 39/14
2025/0066980	12/2024	Park	N/A	D06F 39/083
2025/0066985	12/2024	Park	N/A	D06F 43/081
2025/0116057	12/2024	Kim	N/A	A61L 2/06

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS

(1) Not Applicable

STATEMENT REGARDING FEDERALLY SPONSORED RESEARCH OR DEVELOPMENT

(2) Not Applicable

THE NAMES OF THE PARTIES TO A JOINT RESEARCH AGREEMENT

(3) Not Applicable

INCORPORATION-BY-REFERENCE OF MATERIAL SUBMITTED ON A COMPACT DISC OR AS A TEXT FILE VIA THE OFFICE ELECTRONIC FILING SYSTEM

(4) Not Applicable

STATEMENT REGARDING PRIOR DISCLOSURES BY THE INVENTOR OR JOINT INVENTOR

(5) Not Applicable

BACKGROUND OF THE INVENTION

(1) Field of the Invention

(6) The disclosure relates to warming devices and more particularly pertains to a new warming device for warming towel and imparting a pleasing fragrance into the towels. The device includes a housing and hangers in the housing for suspending towels on the hangers. The device includes a blower and heating unit for blowing heated air into the housing. Additionally, the device includes a fragrance pad, infused with a chemical fragrance, for releasing the chemical fragrance into the towels.

(2) Description of Related Art Including Information Disclosed Under 37 CFR 1.97 and 1.98

(7) The prior art relates to warming devices a variety of towel warming chambers which each at least includes a blower and a heating element for blowing warmed air into the warming chamber for warming towels. The prior art discloses a towel warmer which includes a heating coil against which towels can be positioned for warming the towels. The prior art discloses a towel and garment warmer that includes a chamber for holding towels and garments, a heat source for warming the towels and garments and a cooling unit for cooling the towels and garments. The prior art discloses a towel warmer that includes a heating unit and a UV light emitter for warming towels.

BRIEF SUMMARY OF THE INVENTION

(8) An embodiment of the disclosure meets the needs presented above by generally comprising a housing that has an entry extending into an interior of the housing to facilitate one or more towels to be positioned within the housing. A blower is positioned in the housing to blow air into the housing such that the towels are exposed to the air blown by the blower. A heating unit is positioned in the housing to heat air blown by the blower thereby facilitating the towels to be warmed. A control unit is positioned in the electronics space in the housing and the control unit is in communication with the blower and the heating unit. The control unit includes an electronic timer and each of the blower and the heating unit is turned off when the electronic timer counts down the pre-determined duration of time.

(9) There has thus been outlined, rather broadly, the more important features of the disclosure in order that the detailed description thereof that follows may be better understood, and in order that the present contribution to the art may be better appreciated. There are additional features of the disclosure that will be described hereinafter and which will form the subject matter of the claims appended hereto.

(10) The objects of the disclosure, along with the various features of novelty which characterize the disclosure, are pointed out with particularity in the claims annexed to and forming a part of this disclosure.

Description

BRIEF DESCRIPTION OF SEVERAL VIEWS OF THE DRAWING(S)

- (1) The disclosure will be better understood and objects other than those set forth above will become apparent when consideration is given to the following detailed description thereof. Such description makes reference to the annexed drawings wherein:
- (2) FIG. 1 is a top perspective view of a towel warming assembly according to an embodiment of the disclosure.
- (3) FIG. 2 is a front view of an embodiment of the disclosure.
- (4) FIG. 3 is a left side view of an embodiment of the disclosure.
- (5) FIG. 4 is a back view of an embodiment of the disclosure.
- (6) FIG. 5 is a bottom view of an embodiment of the disclosure.
- (7) FIG. 6 is a cross sectional view taken along line 6-6 of FIG. 5 of an embodiment of the disclosure.

DETAILED DESCRIPTION OF THE INVENTION

- (8) With reference now to the drawings, and in particular to FIGS. 1 through 6 thereof, a new warming device embodying the principles and concepts of an embodiment of the disclosure and generally designated by the reference numeral 10 will be described.
- (9) As best illustrated in FIGS. 1 through 6, the towel warming assembly 10 generally comprises a housing 12 that has a plurality of vents 14 each extending into an interior of the housing 12 to pass air into the housing 12. The housing 12 has an entry 16 extending into an interior of the housing 12 to facilitate one or more towels 18 to be positioned within the housing 12. The towels 18 may be bathing towels or other types of towels that would commonly be employed for bathing or the like. The housing 12 has a bottom wall 20, a top wall 22 and an outer wall 24 extending between the top wall 22 and the bottom wall 20, and the outer wall 24 has a front side 26, a first lateral side 28, a second lateral side 30 and a back side 32. Each of the plurality of vents 14 extends through a respective one of the top wall 22, the first lateral side 28, the second lateral side 30 and the bottom wall 20, and the entry 16 extends through the front side 26. Additionally, the entry 16 extends through the front side 26 and the entry 16 is positioned closer to the top wall 22 than the bottom wall 20.
- (10) The housing 12 has a divider 34 that is positioned between the top wall 22 and the bottom wall 20 to define an electronics space 36 between the bottom wall 20 and the divider 34. The divider 34 is positioned closer to the bottom wall 20 than the top wall 22 and the divider 34 has an air opening 38 extending through the divider 34. The front side 26 has a fragrance opening 40 extending into the electronics space 36 and the fragrance opening 40 is positioned between the entry 16 and the bottom wall 20. The fragrance opening 40 is positioned adjacent to the second lateral side 30 of the outer wall 24.
- (11) The front side 26 has a depression 42 extending into the front side 26 and the depression 42 has a bounding surface 44. The bounding surface 44 is concavely arcuate with respect to the front side 26 and the depression 42 is positioned adjacent to the fragrance opening 40. The back side 32 has a first electronics opening 46 extending into the electronics space 36. Additionally, the bottom wall 20 has a second electronics opening 48 extending into the electronics space 36.
- (12) A plurality of hangers 50 is each positioned within the housing 12 and each of the hangers 50 can have a respective towel 18 hung from the hangers 50. Each of the hangers 50 is positioned on an inside surface 52 of the back side 32 of the outer wall 24 of the housing 12. Furthermore, each

of the hangers **50** is positioned adjacent to the top wall **22**. The hangers **50** are spaced apart from each other and are distributed between the first lateral side **28** and the second lateral side **30** of the outer wall **24** of the housing **12**.

(13) A door **54** is provided and the door **54** is slidably disposed in the entry **16**. The door **54** is positionable in a closed position having the door **54** closing the entry **16**. Conversely, the door **54** is positionable in an open position having the door **54** exposing the entry **16**. The door **54** has a top edge **56** and a bottom edge **58**, and the door **54** has a plurality of pleats **60** each extending between the top edge **56** and the bottom edge **58**. The door **54** is foldable along each of the pleats **60** thereby collapsing the door **54** into the closed position. Furthermore, the door **54** is un-foldable along each of the pleats **60** thereby expanding the door **54** into the open position. A grip **62** is disposed on a front surface **64** of the door **54** for gripping to urge the door **54** between the open position and the closed position.

(14) A plurality of mating units **66** is provided and each of the mating units **66** is coupled to the back side **32** of the outer wall **24** of the housing **12**. In this way each of the mating units **66** can engage a vertical support surface **68** for suspending the housing **12** on the vertical support surface **68**. The vertical support surface **68** may be a wall of a room or other similar vertical support surface **68**. Each of the mating units **66** is aligned with a respective one of four corners **70** of the back side **32**.

(15) A first panel **72** is removably attached to the back side **32** of the outer wall **24** and the first panel **72** covers the first electronics opening **46**. A second panel **74** is removably attached to the bottom wall **20** of the housing **12** and the second panel **74** covers the second electronics opening **48**. A fragrance door **76** is hingedly coupled to the front side **26** of the outer wall **24** of the housing **12** and the fragrance door **76** is aligned with the fragrance opening **40** in the front side **26** of the outer wall **24**. The fragrance door **76** has a perimeter edge **78** and the perimeter edge **78** is continuously arcuate such that the fragrance door **76** has a circular shape. The fragrance door **76** has a tab **80** extending away from the perimeter edge **78**, the tab **80** has a distal end **82** with respect to the perimeter edge **78** and the distal end **82** is hingedly coupled to the front side **26**.

(16) The fragrance door **76** covers the fragrance opening **40** when the fragrance door **76** is closed. Conversely, the fragrance door **76** exposes the fragrance opening **40** when the fragrance door **76** is closed. The perimeter edge **78** is aligned with the depression **42** in the front side **26** of the outer wall **24** of the housing **12**. In this way the depression **42** facilitates a user to grip **62** the perimeter edge **78** for opening the fragrance door **76**.

(17) A blower **84** is positioned in the housing **12** to blow air into the housing **12** such that the towels **18** are exposed to the air blown by the blower **84**. The blower **84** is positioned in the electronics space **36** and the blower **84** has a fragrance port **86** which is integrated into the blower **84**. The blower **84** has an intake **88** and an exhaust **90**, and the blower **84** urges air inwardly into the intake **88** and outwardly through the exhaust **90** when the blower **84** is turned on. The fragrance port **86** is in fluid communication with the intake **88** and the fragrance port **86** is aligned with the fragrance opening **40** in the front side **26** of the outer wall **24** of the housing **12**. In this way a fragrance pad **92** can be positioned on the fragrance port **86**. The fragrance pad **92** is infused with a chemical fragrance **94** to facilitate the chemical fragrance **94** to be released into the air blown by the blower **84**. In this way the chemical fragrance **94** can be distributed onto the towels **18** in the housing **12** thereby imparting a pleasing aroma into the towels **18**.

(18) A heating unit **96** is provided and the heating unit **96** is positioned in the housing **12**. The heating unit **96** is in fluid communication with the blower **84** such that the heating unit **96** heats air blown by the blower **84** thereby facilitating the towels **18** to be warmed. The heating unit **96** comprises a tube **98** that has a lower end **100**, an upper end **102** and an exterior wall **104** extending between the lower end **100** and the upper end **102**. The exterior wall **104** is fluidly coupled to the exhaust **90** of the blower **84** at a point that is located adjacent to the lower end **100**. In this way the tube **98** can receive the air blown by the blower **84**. The upper end **102** is coupled to the divider **34**

having the upper end **102** being aligned with the air opening **38** in the divider **34**. In this way the tube **98** can direct the air blown by the blower **84** through the air opening **38**.

(19) The heating unit **96** includes a heating element **106** that is disposed within the tube **98**. The heating element **106** generates heat when the heating element **106** is turned on. In this way the heating element **106** can heat the air is blown through the tube **98**. The heating element **106** may comprise an electric heating element or the like and the heating element **106** may have an operational temperature ranging between approximately 100.0 degrees Fahrenheit and 180.0 degrees Fahrenheit.

(20) A control unit **108** is positioned in the electronics space **36** in the housing **12** and the control unit **108** is in communication with the blower **84** and the heating unit **96**. The control unit **108** includes an electronic timer **110** and the electronic timer **110** is in communication with each of the blower **84** and the heating unit **96**. The electronic timer **110** counts down a pre-determined duration of time ranging between a minimum duration of time and a maximum duration of time. Furthermore, each of the blower **84** and the heating unit **96** is turned off when the electronic timer **110** counts down the pre-determined duration of time. The blower **84** is electrically coupled to the control unit **108**, the heating element **106** is electrically coupled to the control unit **108** and the control unit **108** is positioned within the electronics space **36** in the housing **12**.

(21) A power knob **112** is rotatably coupled to the housing **12** such that the power knob **112** can be manipulated by a user. The power knob **112** is positionable in an off position, a low position or a high position. Each of the blower **84** and the heating unit **96** is turned off when the power knob **112** is positioned in the off position. Each of the blower **84** and the heating unit **96** is actuated into a minimum intensity when the power knob **112** is positioned in the low position. Additionally, each of the blower **84** and the heating unit **96** is actuated into a maximum intensity when the power knob **112** is positioned in the high position. The power knob **112** is positioned on the front side **26** of the outer wall **24** of the housing **12** and the power knob **112** is positioned between the entry **16** and the bottom wall **20** of the housing **12**. Additionally, the power knob **112** is operationally coupled to the control unit **108**.

(22) A timer knob **114** is rotatably coupled to the housing **12** such that the timer knob **114** can be manipulated by a user. The timer knob **114** is positionable in a minimum position, a medial position or a maximum position. The electronic timer **110** counts down a minimum duration of time when the timer knob **114** is in the minimum position, which may be approximately five minutes. The electronic timer **110** counts down a medial duration of time when the timer knob **114** is in the medial position, which may be approximately ten minutes. Continuing, the electronic timer **110** counts down a maximum duration of time when the timer knob **114** is in the maximum position, which may be approximately fifteen minutes. The timer knob **114** is positioned on the front side **26** of the outer wall **24** of the housing **12**, and the timer knob **114** is positioned between the entry **16** and the bottom wall **20**. Additionally, the timer knob **114** is operationally coupled to the control unit **108**.

(23) A power cord **116** is coupled to and extends away from the back side **32** of the outer wall **24** of the housing **12** and the power cord **116** is electrically coupled to the control unit **108**. The power cord **116** has a distal end **118** with respect to the back side **32** and a male plug **120** is electrically coupled to the distal end **118**. The male plug **120** can be plugged into a power source **122** comprising a female electrical outlet.

(24) In use, the towels **18** are suspended on a respective hanger and the door **54** is positioned in the closed position. The power knob **112** is positioned in either the low position or the high position, depending on the user's preference, and the timer knob **114** is positioned in either the minimum position, the medial position or the maximum position, depending on the user's preference. In this way the blower **84** and the heating unit **96** are turned on to blow heated air into the housing **12** to warm the towels **18**. Additionally, the fragrance pad **92** imparts a pleasing aroma into the towels **18**. In this way the towels **18** are warmed and have a pleasing aroma when the towels **18** are employed

for drying off after bathing, for example. The fragrance pad **92** can be replaced when the chemical fragrance **94** in the fragrance pad **92** is depleted.

(25) With respect to the above description then, it is to be realized that the optimum dimensional relationships for the parts of an embodiment enabled by the disclosure, to include variations in size, materials, shape, form, function and manner of operation, assembly and use, are deemed readily apparent and obvious to one skilled in the art, and all equivalent relationships to those illustrated in the drawings and described in the specification are intended to be encompassed by an embodiment of the disclosure.

(26) Therefore, the foregoing is considered as illustrative only of the principles of the disclosure. Further, since numerous modifications and changes will readily occur to those skilled in the art, it is not desired to limit the disclosure to the exact construction and operation shown and described, and accordingly, all suitable modifications and equivalents may be resorted to, falling within the scope of the disclosure. In this patent document, the word “comprising” is used in its non-limiting sense to mean that items following the word are included, but items not specifically mentioned are not excluded. A reference to an element by the indefinite article “a” does not exclude the possibility that more than one of the element is present, unless the context clearly requires that there be only one of the elements.

Claims

1. A towel warming assembly comprising: a housing having a plurality of vents each extending into an interior of said housing wherein each of said vents is configured to pass air into said housing, said housing having an entry extending into said interior of said housing wherein said entry is configured to facilitate a plurality of towels to be positioned within said housing, said housing having a bottom wall, a top wall and an outer wall extending between said top wall and said bottom wall, said outer wall having a front side, a first lateral side, a second lateral side and a back side, said front side having a fragrance opening; a plurality of hangers, each of said hangers being positioned within said housing wherein each of said hangers is configured to have an associated towel of the plurality of towels to be hung from said hanger; a door being slidably disposed in said entry, said door being positionable in a closed position having said door closing said entry, said door being positionable in an open position having said door exposing said entry; a fragrance door being hingedly coupled to said front side of said outer wall of said housing, said fragrance door being aligned with said fragrance opening in said front side of said outer wall for opening and closing said fragrance opening; a blower being positioned in said housing wherein said blower is configured to blow air into said housing such that the plurality of towels is exposed to the air blown by said blower; a heating unit being positioned in said housing, said heating unit being in fluid communication with said blower wherein said heating unit is configured to heat air being blown by said blower thereby facilitating the plurality of towels to be warmed; and a control unit being positioned in said housing, said control unit being in communication with said blower and said heating unit, said control unit including an electronic timer, said electronic timer being in communication with each of said blower and said heating unit, said electronic timer counting down a pre-determined duration of time ranging between a minimum duration of time and a maximum duration of time, each of said blower and said heating unit being turned off when said electronic timer counts down said pre-determined duration of time.

2. The assembly according to claim 1, wherein: each of said plurality of vents extends through a respective one of said top wall, said first lateral side, said second lateral side and said bottom wall, said entry extending through said front side; said housing having a divider being positioned between said top wall and said bottom wall to define an electronics space between said bottom wall and said divider, said divider being positioned closer to said bottom wall than said top wall, said divider having an air opening extending through said divider; said entry extends through said front

side, said entry being positioned closer to said top wall than said bottom wall; said fragrance opening extending into said electronics space, said fragrance opening being positioned between said entry and said bottom wall, said fragrance opening being positioned adjacent to said second lateral side of said outer wall; said front side has a depression extending into said front side, said depression having a bounding surface, said bounding surface being concavely arcuate with respect to said front side, said depression being positioned adjacent to said fragrance opening; said back side has a first electronics opening extending into said electronics space; and said bottom wall has a second electronics opening extending into said electronics space.

3. The assembly according to claim 2, wherein each of said hangers is positioned on an inside surface of said back side of said outer wall of said housing, each of said hangers being positioned adjacent to said top wall, said hangers being spaced apart from each other and being distributed between said first lateral side and said second lateral side of said outer wall of said housing.

4. The assembly according to claim 2, further comprising a plurality of mating units, each of said mating units being coupled to said back side of said outer wall of said housing wherein each of said mating units is configured to engage a vertical support surface for suspending said housing on the vertical support surface, each of said mating units being aligned with a respective one of four corners of said back side.

5. The assembly according to claim 2, further comprising: a first panel being removably attached to said back side of said outer wall, said first panel covering said first electronics opening; and a second panel being removably attached to said bottom wall of said housing, said second panel covering said second electronics opening.

6. The assembly according to claim 2, wherein said fragrance door has a perimeter edge, said perimeter edge being continuously arcuate such that said fragrance door has a circular shape, said fragrance door having a tab extending away from said perimeter edge, said tab having a distal end with respect to said perimeter edge, said distal end being hingedly coupled to said front side, said fragrance door covering said fragrance opening when said fragrance door is closed, said fragrance door exposing said fragrance opening when said fragrance door is closed, said perimeter edge being aligned with said depression in said front side of said outer wall of said housing wherein said depression is configured to facilitate a user to grip said perimeter edge for opening said fragrance door.

7. The assembly according to claim 2, wherein: said blower is positioned in said electronics space, said blower having a fragrance port being integrated into said blower, said blower having an intake and an exhaust wherein said blower is configured to urge air inwardly into said intake and outwardly through said exhaust; and said fragrance port is in fluid communication with said intake, said fragrance port being aligned with said fragrance opening in said front side of said outer wall of said housing thereby facilitating a fragrance pad to be positioned on said fragrance port, said fragrance pad being infused with a chemical fragrance wherein said fragrance pad is configured to facilitate the chemical fragrance to be released into the air blown by said blower thereby facilitating the chemical fragrance to be distributed onto the plurality of towels in said housing thereby imparting a pleasing aroma into the plurality of towels.

8. The assembly according to claim 7, wherein said heating unit comprises: a tube having a lower end, an upper end and an exterior wall extending between said lower end and said upper end, said exterior wall being fluidly coupled to said exhaust of said blower at a point being located adjacent to said lower end wherein said tube is configured to receive the air blown by said blower, said upper end being coupled to said divider having said upper end being aligned with said air opening in said divider wherein said tube is configured to direct the air blown by said blower through said air opening; and a heating element being disposed within said tube, said heating element generating heat when said heating element is turned on wherein said heating element is configured to heat the air being blown through said tube.

9. The assembly according to claim 2, wherein: said assembly includes a power knob being

rotatably coupled to said housing wherein said power knob is configured to be manipulated by a user, said power knob being positionable in an off position, a low position or a high position, each of said blower and said heating unit being turned off when said power knob is positioned in said off position, each of said blower and said heating unit being actuated into a minimum intensity when said power knob is positioned in said low position, each of said blower and said heating unit being actuated into a maximum intensity when said power knob is positioned in said high position; and said power knob is positioned on said front side of said outer wall of said housing, said power knob being positioned between said entry and said bottom wall of said housing, said power knob being operationally coupled to said control unit.

10. The assembly according to claim 2, wherein: said assembly includes a timer knob being rotatably coupled to said housing wherein said timer knob is configured to be manipulated by a user, said timer knob being positionable in a minimum position, a medial position or a maximum position, said electronic timer counting down a minimum duration of time when said timer knob is in said minimum position, said electronic timer counting down a medial duration of time when said timer knob is in said medial position, said electronic timer counting down a maximum duration of time when said timer knob is in said maximum position; and said timer knob is positioned on said front side of said outer wall of said housing, said timer knob being positioned between said entry and said bottom wall, said timer knob being operationally coupled to said control unit.

11. The assembly according to claim 2, further comprising a power cord being coupled to and extending away from said back side of said outer wall of said housing, said power cord being electrically coupled to said control unit, said power cord having a distal end with respect to said back side, said distal end having a male plug being electrically coupled to said distal end wherein said male plug is configured to be plugged into a power source comprising a female electrical outlet.

12. The assembly according to claim 1, wherein; said door has a top edge and a bottom edge, said door having a plurality of pleats each extending between said top edge and said bottom edge, said door foldable along each of said pleats thereby collapsing said door into said closed position, said door being un-foldable along each of said pleats thereby expanding said door into said open position; and said assembly includes a grip being disposed on a front surface of said door wherein said grip is configured to be gripped for urging said door between said open position and said closed position.

13. A towel warming assembly comprising: a housing having a plurality of vents each extending into an interior of said housing wherein each of said vents is configured to pass air into said housing, said housing having an entry extending into an interior of said housing wherein said entry is configured to facilitate a plurality of towels to be positioned within said housing, said housing having a bottom wall, a top wall and an outer wall extending between said top wall and said bottom wall, said outer wall having a front side, a first lateral side, a second lateral side and a back side, each of said plurality of vents extending through a respective one of said top wall, said first lateral side, said second lateral side and said bottom wall, said entry extending through said front side, said housing having a divider being positioned between said top wall and said bottom wall to define an electronics space between said bottom wall and said divider, said divider being positioned closer to said bottom wall than said top wall, said divider having an air opening extending through said divider, said entry extending through said front side, said entry being positioned closer to said top wall than said bottom wall, said front side having a fragrance opening extending into said electronics space, said fragrance opening being positioned between said entry and said bottom wall, said fragrance opening being positioned adjacent to said second lateral side of said outer wall, said front side having a depression extending into said front side, said depression having a bounding surface, said bounding surface being concavely arcuate with respect to said front side, said depression being positioned adjacent to said fragrance opening, said back side having a first electronics opening extending into said electronics space, said bottom wall having a second

electronics opening extending into said electronics space; a plurality of hangers, each of said hangers being positioned within said housing wherein each of said hangers is configured to have an associated towel of said plurality of towels to be hung from said hanger, each of said hangers being positioned on an inside surface of said back side of said outer wall of said housing, each of said hangers being positioned adjacent to said top wall, said hangers being spaced apart from each other and being distributed between said first lateral side and said second lateral side of said outer wall of said housing; a door being slidably disposed in said entry, said door being positionable in a closed position having said door closing said entry, said door being positionable in an open position having said door exposing said entry, said door having a top edge and a bottom edge, said door having a plurality of pleats each extending between said top edge and said bottom edge, said door foldable along each of said pleats thereby collapsing said door into said closed position, said door being un-foldable along each of said pleats thereby expanding said door into said open position; a grip being disposed on a front surface of said door wherein said grip is configured to be gripped for urging said door between said open position and said closed position; a plurality of mating units, each of said mating units being coupled to said back side of said outer wall of said housing wherein each of said mating units is configured to engage a vertical support surface for suspending said housing on the vertical support surface, each of said mating units being aligned with a respective one of four corners of said back side; a first panel being removably attached to said back side of said outer wall, said first panel covering said first electronics opening; a second panel being removably attached to said bottom wall of said housing, said second panel covering said second electronics opening; a fragrance door being hingedly coupled to said front side of said outer wall of said housing, said fragrance door being aligned with said fragrance opening in said front side of said outer wall, said fragrance door having a perimeter edge, said perimeter edge being continuously arcuate such that said fragrance door has a circular shape, said fragrance door having a tab extending away from said perimeter edge, said tab having a distal end with respect to said perimeter edge, said distal end being hingedly coupled to said front side, said fragrance door covering said fragrance opening when said fragrance door is closed, said fragrance door exposing said fragrance opening when said fragrance door is closed, said perimeter edge being aligned with said depression in said front side of said outer wall of said housing wherein said depression is configured to facilitate a user to grip said perimeter edge for opening said fragrance door; a blower being positioned in said housing wherein said blower is configured to blow air into said housing such that the plurality of towels is exposed to the air blown by said blower, said blower being positioned in said electronics space, said blower having a fragrance port being integrated into said blower, said blower having an intake and an exhaust wherein said blower is configured to urge air inwardly into said intake and outwardly through said exhaust, said fragrance port being in fluid communication with said intake, said fragrance port being aligned with said fragrance opening in said front side of said outer wall of said housing thereby facilitating a fragrance pad to be positioned on said fragrance port, said fragrance pad being infused with a chemical fragrance wherein said fragrance pad is configured to facilitate the chemical fragrance to be released into the air blown by said blower thereby facilitating the chemical fragrance to be distributed onto the plurality of towels in said housing thereby imparting a pleasing aroma into the plurality of towels; a heating unit being positioned in said housing, said heating unit being in fluid communication with said blower wherein said heating unit is configured to heat air being blown by said blower thereby facilitating the plurality of towels to be warmed, said heating unit comprising: a tube having a lower end, an upper end and an exterior wall extending between said lower end and said upper end, said exterior wall being fluidly coupled to said exhaust of said blower at a point being located adjacent to said lower end wherein said tube is configured to receive the air blown by said blower, said upper end being coupled to said divider having said upper end being aligned with said air opening in said divider wherein said tube is configured to direct the air blown by said blower through said air opening; and a heating element being disposed within said tube, said heating

element generating heat when said heating element is turned on wherein said heating element is configured to heat the air being blown through said tube; a control unit being positioned in said electronics space in said housing, said control unit being in communication with said blower and said heating unit, said control unit including an electronic timer, said electronic timer being in communication with each of said blower and said heating unit, said electronic timer counting down a pre-determined duration of time ranging between a minimum duration of time and a maximum duration of time, each of said blower and said heating unit being turned off when said electronic timer counts down said pre-determined duration of time, said blower being electrically coupled to said control unit, said heating element being electrically coupled to said control unit, said control unit being positioned within said electronics space in said housing; a power knob being rotatably coupled to said housing wherein said power knob is configured to be manipulated by a user, said power knob being positionable in an off position, a low position or a high position, each of said blower and said heating unit being turned off when said power knob is positioned in said off position, each of said blower and said heating unit being actuated into a minimum intensity when said power knob is positioned in said low position, each of said blower and said heating unit being actuated into a maximum intensity when said power knob is positioned in said high position, said power knob being positioned on said front side of said outer wall of said housing, said power knob being positioned between said entry and said bottom wall of said housing, said power knob being operationally coupled to said control unit; a timer knob being rotatably coupled to said housing wherein said timer knob is configured to be manipulated by a user, said timer knob being positionable in a minimum position, a medial position or a maximum position, said electronic timer counting down a minimum duration of time when said timer knob is in said minimum position, said electronic timer counting down a medial duration of time when said timer knob is in said medial position, said electronic timer counting down a maximum duration of time when said timer knob is in said maximum position, said timer knob being positioned on said front side of said outer wall of said housing, said timer knob being positioned between said entry and said bottom wall, said timer knob being operationally coupled to said control unit; and a power cord being coupled to and extending away from said back side of said outer wall of said housing, said power cord being electrically coupled to said control unit, said power cord having a distal end with respect to said back side, said distal end having a male plug being electrically coupled to said distal end wherein said male plug is configured to be plugged into a power source comprising a female electrical outlet.
