

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403738
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Hasegawa; Kazuki

Fluid pressure shock absorber

Abstract

A fluid pressure shock absorber mounted on a vehicle includes: a cylinder tube; a rod inserted into the cylinder tube so as to be movable back and forth; a piston connected to the rod and dividing an interior of the cylinder tube into a bottom-side chamber and a rod-side chamber; a damping valve configured to impart resistance to a flow of working fluid between the bottom-side chamber and the rod-side chamber, the damping valve being capable of changing damping characteristic in response to a pilot pressure; and a solenoid valve configured to switch supply and shut off of a pilot pressure to the damping valve, wherein the working fluid in the bottom-side chamber or the rod-side chamber is used as the pilot pressure.

Inventors:	Hasegawa; Kazuki (Gifu, JP)
Applicant:	KYB Corporation (Tokyo, JP)
Family ID:	87935280
Assignee:	KYB CORPORATION (Tokyo, JP)
Appl. No.:	18/844356
Filed (or PCT Filed):	March 01, 2023
PCT No.:	PCT/JP2023/007659
PCT Pub. No.:	WO2023/171507
PCT Pub. Date:	September 14, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20250236148 A1	Jul. 24, 2025

Foreign Application Priority Data

JP2022-035293Mar. 08, 2022

Publication Classification

Int. Cl.: B60G13/08 (20060101); B60G17/015 (20060101)

U.S. Cl.:

CPC B60G17/0152 (20130101); B60G13/08 (20130101); B60G2202/24 (20130101); B60G2204/62 (20130101); B60G2206/41 (20130101); B60G2400/60 (20130101); B60G2500/104 (20130101); B60G2500/114 (20130101); B60G2800/162 (20130101); B60G2800/916 (20130101)

Field of Classification Search

CPC: B60G (17/0152); B60G (13/08); B60G (2202/24); B60G (2204/62); B60G (2206/41); B60G (2400/60); B60G (2500/104); B60G (2500/114); B60G (2800/162); B60G (2800/916)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
5311709	12/1993	Kobori et al.	N/A	N/A
6308973	12/2000	Griebel	280/124.159	B60G 17/0152
2006/0186728	12/2005	Mizuta	303/3	B60G 17/0152
2010/0044976	12/2009	Rades	280/5.507	B60G 21/106
2014/0084555	12/2013	Murakami	280/5.514	B62K 25/00
2016/0236533	12/2015	Inagaki	N/A	F16F 9/46
2017/0016505	12/2016	Funato	N/A	N/A
2017/0072762	12/2016	Kurita	N/A	F16F 9/46
2018/0015802	12/2017	Jeong	N/A	B60G 17/019
2018/0229574	12/2017	Okimura	N/A	B60G 15/14
2021/0310535	12/2020	Conti	N/A	F16F 9/185
2022/0136580	12/2021	Shimauchi	188/322.5	F16F 9/065
2022/0242186	12/2021	Tong	N/A	F16F 9/516
2024/0167532	12/2023	Hasegawa	N/A	F16F 9/19
2024/0227488	12/2023	Mochizuki	N/A	B60G 17/0565

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
H05-171836	12/1992	JP	N/A
2009-250396	12/2008	JP	N/A
2015-206374	12/2014	JP	N/A

Background/Summary

TECHNICAL FIELD

(1) The present invention relates to a fluid pressure shock absorber.

BACKGROUND ART

(2) With the fluid pressure shock absorber described in JP2015-206374A, a piston rod has a rod portion that extends outside a cylinder and a piston that is connected to an end portion of the rod portion and slidably moves within the cylinder to divide an interior of the cylinder into a bottom-side chamber and a rod-side chamber. The rod portion has: a rod inner space that is formed in the rod portion and communicates with the bottom-side chamber of the cylinder; a first communicating passage that connects the rod inner space and the rod-side chamber of the cylinder; and an orifice plug that is provided in the first communicating passage and generates a damping force.

SUMMARY OF INVENTION

(3) In the fluid pressure shock absorber described in JP2015-206374A, when a damping valve capable of changing damping characteristics is to be mounted, it may be conceivable to employ a solenoid valve as the damping valve. However, if the working fluid to be passed through the damping valve has a high pressure and a large flow rate, the size of the damping valve is increased, and a mountability of the damping valve is deteriorated.

(4) An object of the present invention is to improve a mountability of a damping valve that is capable of changing damping characteristics.

(5) According to one aspect of the present invention, a fluid pressure shock absorber mounted on a vehicle includes: a cylinder tube; a rod inserted into the cylinder tube so as to be movable back and forth; a piston connected to the rod and dividing an interior of the cylinder tube into a bottom-side chamber and a rod-side chamber; a damping valve configured to impart resistance to a flow of working fluid between the bottom-side chamber and the rod-side chamber, the damping valve being capable of changing damping characteristic in response to a pilot pressure; and a solenoid valve configured to switch supply and shut off of a pilot pressure to the damping valve, wherein the working fluid in the bottom-side chamber or the rod-side chamber is used as the pilot pressure.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a fluid pressure circuit diagram of a fluid pressure shock absorber according to an embodiment of the present invention.

(2) FIG. 2 is a sectional view of the fluid pressure shock absorber according to the embodiment of the present invention.

(3) FIG. 3 is a fluid pressure circuit diagram of the fluid pressure shock absorber according to a modification of the embodiment of the present invention.

(4) FIG. 4 is a fluid pressure circuit diagram of the fluid pressure shock absorber according to the modification of the embodiment of the present invention.

(5) FIG. 5 is a fluid pressure circuit diagram of the fluid pressure shock absorber according to the modification of the embodiment of the present invention.

DESCRIPTION OF EMBODIMENTS

(6) In the following, with reference to the drawings, a fluid pressure shock absorber according to an embodiment of the present invention will be described.

(7) In the following, a case in which the fluid pressure shock absorber is a hydraulic shock absorber **100** that is mounted on a vehicle. The hydraulic shock absorber **100** is a device that suppresses vibration of a vehicle body by, for example, being interposed between the vehicle body and an axle shaft of the vehicle and by generating a damping force.

(8) As shown in FIG. **1**, the hydraulic shock absorber **100** includes a tubular cylinder tube **10**, a rod **12** that is inserted into the cylinder tube **10** so as to be movable back and forth and that extends outside the cylinder tube **10**, and a piston **14** that is connected to a tip end of the rod **12** and that is slidably moved along an inner circumferential surface of the cylinder tube **10**. The hydraulic shock absorber **100** is installed on the vehicle in an orientation at which the cylinder tube **10** is positioned at the upper side and the rod **12** is positioned at the lower side.

(9) An interior of the cylinder tube **10** is divided by the piston **14** into a bottom-side chamber **1** and a rod-side chamber **2**. The bottom-side chamber **1** and the rod-side chamber **2** are respectively filled with working oil serving as working fluid. In the bottom-side chamber **1**, pressurized gas **G** for exhibiting a spring effect by compensating for a volume change in the cylinder tube **10** due to inward and outward movement of the rod **12** relative to the cylinder tube **10** is sealed together with the working oil. As described above, the hydraulic shock absorber **100** has a function of an air-suspension that is capable of supporting the vehicle body by the spring effect exerted by the gas **G**. In this case, even if a spring for supporting the vehicle body is not provided separately, it is possible to achieve generation of the damping force and support of the vehicle body by the hydraulic shock absorber **100**.

(10) Note that, the configuration is not limited to those described above, and the gas may not be sealed in the cylinder tube **10**. In addition, it may be possible to provide a free piston that is movably provided inside the bottom-side chamber **1** and that divides the bottom-side chamber **1** into a liquid chamber, into which the working oil is sealed, and a gas chamber, into which the gas **G** is sealed. In addition, an accumulator connected to the bottom-side chamber **1** may be provided outside the cylinder tube **10**, and the gas chamber may be provided in the accumulator.

(11) The bottom-side chamber **1** is connected to the rod-side chamber **2** through via a flow path **3**. The hydraulic shock absorber **100** includes a damping valve **20** that is provided in the flow path **3** and that generates the damping force by imparting resistance to a flow of the working oil between the rod-side chamber **2** and the bottom-side chamber **1**.

(12) The flow path **3** is formed by being branched at an intermediate position, and has a first flow path **21** and a second flow path **22** that are parallel with each other. The damping valve **20** has a first damping valve **20A** that is provided in the first flow path **21** and that imparts resistance to the flow of the working oil, and a second damping valve **20B** that is provided in the second flow path **22** and that imparts resistance to the flow of the working oil. The first damping valve **20A** and the second damping valve **20B** are provided in parallel with each other.

(13) The first flow path **21** includes a check valve **23** that only allows the flow of the working oil from the bottom-side chamber **1** to the rod-side chamber **2**. Therefore, the first damping valve **20A** imparts the resistance only to the flow of the working oil from the bottom-side chamber **1** towards the rod-side chamber **2**. In this embodiment, the first damping valve **20A** is, for example, a fixed orifice.

(14) The second damping valve **20B** imparts the resistance to the flow of the working oil between the bottom-side chamber **1** and the rod-side chamber **2** in both directions. The position of the second damping valve **20B** is switched in response to a pilot pressure, and the resistances imparted to the flows of the working oil passing through at respective positions are different. In other words, the damping characteristic of the second damping valve **20B** can be changed in response to the pilot pressure.

(15) In this embodiment, the second damping valve **20B** has two positions, i.e., a first restricting position **25A**, at which a predetermined resistance is imparted to the flow of the working oil passing therethrough, and a second restricting position **25B**, at which the resistance of a different

magnitude is imparted compared to the resistance imparted at the first restricting position **25A**. In other words, the first restricting position **25A** and the second restricting position **25B** have different pressure loss characteristics for the flow of the working oil passing therethrough.

(16) The second damping valve **20B** has a valve body (not shown) that switches the position, a spring **26** serving as a biasing member that biases the valve body, and a pilot chamber **27** to which the pilot pressure is supplied. In the second damping valve **20B**, the valve body is biased by the spring **26** so as to be positioned at the first restricting position **25A**. In the second damping valve **20B**, as the pilot pressure is guided to the pilot chamber **27**, the valve body is moved against the biasing force exerted by the spring **26**, and thereby, the second damping valve **20B** is switched to the second restricting position **25B**. When the supply of the pilot pressure is shut off, the second damping valve **20B** is switched to the first restricting position **25A** by the biasing force exerted by the spring **26**.

(17) When the hydraulic shock absorber **100** is contracted, the pressure in the bottom-side chamber **1** is increased, and a part of the working oil in the bottom-side chamber **1** opens the check valve **23**, passes through the first damping valve **20A** and is guided to the rod-side chamber **2**, while the rest of the working oil passes through the second damping valve **20B** and is guided to the rod-side chamber **2**. As described above, when the hydraulic shock absorber **100** is contracted, the working oil in the bottom-side chamber **1** is guided to the rod-side chamber **2** by passing through both of the first damping valve **20A** and the second damping valve **20B**. Therefore, when the hydraulic shock absorber **100** is contracted, the hydraulic shock absorber **100** generates the damping force corresponding to the overall flow path resistance exerted by the first damping valve **20A** and the second damping valve **20B**.

(18) When the hydraulic shock absorber **100** is extended, the pressure in the rod-side chamber **2** is increased, and the working oil in the rod-side chamber **2** passes through the second damping valve **20B** and is guided to the bottom-side chamber **1**. On the other hand, because the check valve **23** is closed by the increase in the pressure in the rod-side chamber **2**, the working oil in the rod-side chamber **2** is not guided to the bottom-side chamber **1** through the first damping valve **20A**. Thus, when the hydraulic shock absorber **100** is extended, the hydraulic shock absorber **100** generates the damping force corresponding to the flow path resistance exerted by the second damping valve **20B**. Therefore, when the hydraulic shock absorber **100** is contracted, because the flow of the working oil from the bottom-side chamber **1** to the rod-side chamber **2** through the first damping valve **20A** is allowed, the hydraulic shock absorber **100** generates a larger damping force during the extension than during the contraction correspondingly. As a result, in a case in which the vehicle drives over a bump on a road surface, the hydraulic shock absorber **100** is contracted in a relatively smoothly, and thereafter, the hydraulic shock absorber **100** generates the larger damping force during extension, thereby effectively damping the vibration exerted from the road surface to the vehicle body.

(19) Note that, the first flow path **21**, the first damping valve **20A**, and the check valve **23** are not essential configurations, and a configuration in which the damping force is generated only by the second damping valve **20B** may also be employed.

(20) The hydraulic shock absorber **100** includes a solenoid valve **30** that switches between the supply and shut off of the pilot pressure to the second damping valve **20B**. The solenoid valve **30** is provided in a pilot passage **33**. The pilot passage **33** is provided by being branched from the flow path **3** and connects the bottom-side chamber **1** and the pilot chamber **27** of the second damping valve **20B**. The pilot passage **33** need only be configured to guide the working oil in the bottom-side chamber **1** to the pilot chamber **27** of the second damping valve **20B** as the pilot pressure, and may, for example, be directly connected to the bottom-side chamber **1**.

(21) The solenoid valve **30** has two positions, i.e., a shut-off position **30A**, at which the supply of the pilot pressure is shut off, and a supply position **30B**, at which the pilot pressure is supplied.

(22) Operation of the solenoid valve **30** is controlled by an electric signal input from a controller

35. The solenoid valve **30** has the valve body (not shown) that switches the position, a spring **31** serving as a biasing member that biases the valve body, and a solenoid **32** that moves the valve body against the biasing force exerted by the spring **31** by being energized.

(23) In the solenoid valve **30**, the valve body is biased by the spring **31** such that the solenoid valve **30** is positioned at the shut-off position **30A**. When the solenoid **32** is excited by being energized, the valve body is moved against the biasing force exerted by the spring **31**, and the solenoid valve **30** is switched to the supply position **30B**. When the energization of the solenoid **32** is cutoff, the solenoid valve **30** is switched to the shut-off position **30A** by the biasing force exerted by the spring **31**.

(24) The vehicle includes a detector **34** that detects the weight of the load (a load weight) loaded on a loading platform, and a detection signal from the detector **34** is output to the controller **35**. When the load weight is less than a predetermined weight, the energization of the solenoid **32** of the solenoid valve **30** is cutoff by the controller **35** on the basis of the signal from the detector **34**. In addition, when the load weight is equal to or greater than a predetermined weight, the solenoid **32** of the solenoid valve **30** is energized by the controller **35** on the basis of the signal from the detector **34**. As described above, when the load weight of the vehicle is small, the solenoid valve **30** is positioned at the shut-off position **30A**, the supply of the pilot pressure to the second damping valve **20B** is shut off, and the second damping valve **20B** is positioned at the first restricting position **25A**. In addition, when the load weight of the vehicle is large, the solenoid valve **30** is positioned at the supply position **30B**, the pilot pressure is supplied to the second damping valve **20B**, and the second damping valve **20B** is positioned at the second restricting position **25B**.

(25) Here, with the vehicle such as the dump truck having a large maximum load capacity, because the overall weight of the vehicle, including the load, varies significantly between an empty state with no load and a state with the load, the energy to be damped by the hydraulic shock absorber **100** also varies significantly. However, in this embodiment, the damping characteristic of the second damping valve **20B** is changed by the solenoid valve **30** according to the load weight of the vehicle, and thus, the hydraulic shock absorber **100** can exhibit an optimal damping characteristic according to the load weight of the vehicle.

(26) In this embodiment, the working oil in the bottom-side chamber **1** is used as the pilot pressure for switching the position of the second damping valve **20B**. Instead, the working oil in the rod-side chamber **2** may also be used as the pilot pressure. However, while the vehicle is travelling, when the wheel lands on a bottom of a depression in the road surface or when the wheel rides over the bump on the road surface, the hydraulic shock absorber **100** is contracted suddenly and temporarily, and thus, the pressure in the rod-side chamber **2** may become negative pressure. In contrast, the bottom-side chamber **1** supports the weight of the vehicle body, and the pressurized gas **G** is sealed in the bottom-side chamber **1**, and thus, the pressure in the bottom-side chamber **1** does not become negative pressure during the operation of the hydraulic shock absorber **100**.

Therefore, it is preferable to use the working oil in the bottom-side chamber **1** as the pilot pressure.

(27) As described above, this embodiment employs a configuration in which the supply and shut off of the pilot pressure for the pilot-driven-type second damping valve **20B**, which is capable of changing the damping characteristic, is switched by the solenoid valve **30**. Here, in a large-sized vehicle such as a dump truck, because the hydraulic shock absorber **100** to be mounted has a large size, the flow rate of the working oil passing through the second damping valve **20B** is large. In addition, in the vehicle such as the dump truck having the large maximum load capacity, because the overall weight of the vehicle is large, the pressure of the working oil in the hydraulic shock absorber **100** supporting the weight thereof is high. Furthermore, in the hydraulic shock absorber **100**, because the gas **G** is sealed in the cylinder tube **10** and the hydraulic shock absorber **100** also has the function of the air-suspension, the pressure of the working oil in the cylinder tube **10** becomes high. As described above, in a case in which the hydraulic shock absorber **100** is mounted on the large-sized vehicle, such as the dump truck, the second damping valve **20B** needs to be a

valve capable of switching the flow of the working oil having a high pressure and a large flow rate. In a case in which a solenoid valve is employed as the second damping valve **20B** itself, a large solenoid thrust is required to switch the position of the second damping valve **20B**, and so, a size of a solenoid to be mounted on the second damping valve **20B** is increased. Therefore, a mountability of the second damping valve **20B** on the hydraulic shock absorber **100** is deteriorated.

(28) In contrast, in this embodiment, because the second damping valve **20B** is of a pilot-driven type, the size thereof is not increased. In addition, the supply and shut off of the pilot pressure to the second damping valve **20B** is switched by the solenoid valve **30**, the solenoid valve **30** is provided on the pilot passage **33**, and the flow rate of a pilot fluid flowing through the pilot passage **33** is small. In this way, it suffices that the solenoid valve **30** is a valve that is capable of switching the flow of the working oil having a high pressure and a small flow rate, and a large solenoid thrust is not required, and thus, the size of the solenoid valve **30** can be reduced. Therefore, the mountability of the second damping valve **20B** on the hydraulic shock absorber **100** is improved, and consequently, it is possible to make the hydraulic shock absorber **100** smaller.

(29) Next, with reference to FIG. 2, the structure of the hydraulic shock absorber **100**, and an example of mounting the damping valve **20** and the solenoid valve **30** on the hydraulic shock absorber **100** will be described. FIG. 2 is a sectional view of the hydraulic shock absorber **100**.

(30) The cylinder tube **10** has a bottomed cylindrical shape, and a cylinder head **11**, through which the rod **12** is slidably inserted, is provided on its opening end. An attachment portion **10a** for attaching the hydraulic shock absorber **100** to the vehicle is provided on a closing end of the cylinder tube **10** (the end portion on the opposite side from the cylinder head **11**).

(31) The rod **12** has a rod main body **51** that is connected to the piston **14** and that is slidably supported by the cylinder head **11** of the cylinder tube **10** and a head portion **52** that is exposed to the outside of the cylinder tube **10**.

(32) The rod main body **51** is formed with a rod inner space **40** that opens at an end surface on the piston **14** side. An end portion of the rod main body **51** is joined to the piston **14** by a bolt (not shown).

(33) The head portion **52** is formed to have a diameter larger than that of the rod main body **51**, and the head portion **52** is always exposed to the outside of the cylinder tube **10** regardless of the stroke position of the hydraulic shock absorber **100**. In other words, the head portion **52** is a portion of the rod **12** that does not slide with respect to the cylinder head **11**. The head portion **52** is, for example, formed separately from the rod main body **51**, and is connected to the end portion of the rod main body **51** by welding, etc. The rod main body **51** and the head portion **52** may be formed integrally.

(34) The head portion **52** includes a stopper portion **52a** that defines the stroke end when the hydraulic shock absorber **100** is contracted and an attachment portion **52b** for attaching the hydraulic shock absorber **100** to the vehicle. The stopper portion **52a** includes an annular cushion ring **53** that prevents collision between the cylinder head **11** and the rod **12** at the stroke end when the hydraulic shock absorber **100** is contracted.

(35) The rod inner space **40** includes a cylindrical pipe **43**. The one end of the pipe **43** is inserted into an insertion hole **52c** formed in the head portion **52** and the other end thereof is inserted into an insertion hole **14a** formed in the piston **14**. As described above, the pipe **43** is provided so as to be interposed between the head portion **52** and the piston **14**.

(36) By providing the pipe **43** in the rod inner space **40**, the rod inner space **40** is divided into a first space **41** that is a hollow portion in the pipe **43** and an annular second space **42** that is partitioned between an outer circumferential surface of the pipe **43** and an inner circumferential surface of the rod main body **51**. The first space **41** communicates with the bottom-side chamber **1** through a through hole **14b** that is formed in the piston **14**. The second space **42** communicates with the rod-side chamber **2** through a plurality of through holes **51a** that are formed in the rod main body **51** of the rod **12**. As described above, the rod inner space **40** has the first space **41** that communicates with the bottom-side chamber **1** and the second space **42** that communicates with the rod-side

chamber **2**. The first space **41** and the second space **42** each forms a part of the flow path **3** that connects the bottom-side chamber **1** with the rod-side chamber **2**.

(37) The flow path **3**, the first damping valve **20A**, the second damping valve **20B**, and the solenoid valve **30** are provided in the head portion **52** of the rod **12**. The pilot passage **33** that guides the pilot pressure for driving the second damping valve **20B** is also provided in the head portion **52**. The pilot pressure is guided from the bottom-side chamber **1** to the second damping valve **20B** through the first space **41** and the pilot passage **33**. As described above, in this configuration, the pilot pressure is guided through the first space **41** and the pilot passage **33** provided in the head portion **52**, and the pilot pressure is guided out from the vertically lower side with respect to the gas **G** that is stored on the vertically upper side of the hydraulic shock absorber **100**. Therefore, because the gas **G** is prevented from being mixed with the pilot fluid, the operation of the second damping valve **20B** is stabilized. As described above, even if the gas chamber, into which the gas **G** is to be sealed, is not divided by the free piston, it is possible to prevent the gas **G** from being mixed into the pilot fluid by guiding out the pilot pressure from the vertically lower side with respect to the gas **G**.

(38) When the working oil in the rod-side chamber **2** is to be used as the pilot pressure, the pilot pressure may be guided to the pilot chamber **27** of the second damping valve **20B** through the second space **42** and the pilot passages provided in the head portion **52**.

(39) According to the embodiment mentioned above, the advantages described below are afforded.

(40) The damping characteristic of the second damping valve **20B** can be changed by using the working oil in the bottom-side chamber **1** as the pilot pressure, and the supply and shut off of the pilot pressure can be switched by the solenoid valve **30**, and thus, the size of the second damping valve **20B** is not increased. Thus, it is possible to improve the mountability of the second damping valve **20B** that is capable of changing the damping force.

(41) In the following, modifications of the above-mentioned embodiment will be described. The modifications described below also fall within the scope of the present invention. It may also be possible to combine the following modifications with the configurations in the above-described embodiment, and it may also be possible to combine the following modifications with each other.

(42) (1) In a hydraulic shock absorber **101** shown in FIG. **3**, a plurality of second damping valves **20B** are provided in the second flow path **22** in series, and a plurality of solenoid valves **30** are provided in parallel, and the plurality of solenoid valves **30** respectively switch the supply and shut off of the pilot pressure to the plurality of second damping valves **20B**. The hydraulic shock absorber **100** according to the above-mentioned embodiment has two patterns of the damping characteristics. In contrast, the hydraulic shock absorber **101** according to this modification has four patterns of the damping characteristics. Therefore, it is possible to realize more optimal damping characteristic according to the load weight of the vehicle.

(43) (2) In a hydraulic shock absorber **102** shown in FIG. **4**, the damping characteristic can be changed in response to the pilot pressure also in the first damping valve **20A**. In other words, the first damping valve **20A** has the configuration that is the same as that of the second damping valve **20B** of the hydraulic shock absorber **100** according to the above-mentioned embodiment. In addition, two solenoid valves **30** are provided in parallel, and these two solenoid valves **30** respectively switch the supply and shut off of the pilot pressure to the first damping valve **20A** and the second damping valve **20B**. Also in this modification, it is possible to realize more optimal damping characteristic according to the load weight of the vehicle.

(44) In the hydraulic shock absorber **102**, only a single solenoid valve **30** may be provided, and the first damping valve **20A** and the second damping valve **20B** may be operated by the pilot pressure guided through this single solenoid valve **30**. In addition, the check valve **23** provided in the first flow path **21** may be provided in the reverse direction. In other words, the first damping valve **20A** may be configured such that the resistance is imparted only to the flow of the working oil directed from the one of the bottom-side chamber **1** and the rod-side chamber **2** towards the other.

Furthermore, the second flow path **22** in which the second damping valve **20B** is provided may be provided with a check valve that only allows the flow of the working oil from the rod-side chamber **2** to the bottom-side chamber **1**. In such a case, the second damping valve **20B** imparts the resistance only to the flow of the working oil directed from the rod-side chamber **2** towards the bottom-side chamber **1**.

(45) (3) A hydraulic shock absorber **103** shown in FIG. **5** includes a check valve **39** that only guides the pilot pressure from a downstream portion **33a** of the pilot passage **33** on the downstream side of the pilot valve **30** between the solenoid valve **30** and the second damping valve **20B** to the bottom-side chamber **1**. By providing the check valve **39**, when the solenoid valve **30** is switched from the supply position **30B** to the shut-off position **30A**, even if the pilot pressure remains in the downstream portion **33a** of the pilot passage **33** on the downstream side of the pilot valve **30**, the residual pressure is released to the bottom-side chamber **1** side through the check valve **39** when the hydraulic shock absorber **103** is extended, and so, the second damping valve **20B** is switched to the first restricting position **25A** smoothly. The check valve **39** may be provided so as to guide the pilot pressure only from the downstream portion **33a** of the pilot passage **33** on the downstream side of the pilot valve **30** to the rod-side chamber **2**. In this case, the residual pressure in the downstream portion **33a** is released to the rod-side chamber **2** side through the check valve **39** when the hydraulic shock absorber **103** is contracted.

(46) (4) In the above-mentioned embodiment, a description has been given of the configuration in which the hydraulic shock absorber **100** is mounted on the vehicle in the direction in which the cylinder tube **10** faces upward and the rod **12** faces downward. On the contrary, however, the hydraulic shock absorber **100** may be mounted on the vehicle in the direction in which the cylinder tube **10** faces downward and the rod **12** faces upward. In this case, in order to prevent upward movement of the gas **G** in the bottom-side chamber **1**, it is required to provide, in the bottom-side chamber **1**, a free piston that separates the liquid chamber in which the working oil is sealed and the gas chamber in which the gas is sealed. Alternatively, an accumulator connected to the bottom-side chamber **1** may be provided outside the cylinder tube **10**, and a gas chamber may be provided in the accumulator.

(47) (5) In the above-mentioned embodiment, although the hydraulic shock absorber **100** is of a single-rod type in which the tip end of the rod **12** projects out to the outside of the cylinder tube **10**, the hydraulic shock absorber **100** may also be of a double rod type in which both ends of the rod **12** project out to the outside of the cylinder tube **10**.

(48) In the following, the configurations, operations, and effects of the respective embodiments of the present invention will be collectively described.

(49) The hydraulic shock absorber **100**, **101**, **102**, **103** (the fluid pressure shock absorber) mounted on the vehicle includes: the cylinder tube **10**; the rod **12** inserted into the cylinder tube **10** so as to be movable back and forth; the piston **14** connected to the rod **12** and dividing the interior of the cylinder tube **10** into the bottom-side chamber **1** and the rod-side chamber **2**; the damping valve **20** configured to impart the resistance to the flow of the working oil (the working fluid) between the bottom-side chamber **1** and the rod-side chamber **2**, the damping valve **20** being capable of changing the damping characteristic in response to the pilot pressure; and the solenoid valve **30** configured to switch the supply and shut off of the pilot pressure to the damping valve **20**, wherein the working fluid in the bottom-side chamber **1** or the rod-side chamber **2** is used as the pilot pressure.

(50) With this configuration, the damping characteristic of the damping valve **20** can be changed by using the working oil in the bottom-side chamber **1** or the rod-side chamber **2** as the pilot pressure, and the supply and shut off of the pilot pressure can be switched by the solenoid valve **30**, and thus, the size of the damping valve **20** is not increased. Thus, it is possible to improve the mountability of the damping valve **20** that is capable of changing the damping force.

(51) In addition, the working oil in the bottom-side chamber **1** is used as the pilot pressure, and the

pressurized gas G is sealed in the bottom-side chamber 1.

(52) With this configuration, because the pressurized gas G is sealed in the bottom-side chamber 1, and the pressure in the bottom-side chamber 1 does not become negative pressure during the operation of the hydraulic shock absorber 100, it is possible to operate the damping valve 20 stably.

(53) In addition, the plurality of the damping valves 20 are provided in series, the plurality of the solenoid valves 30 are provided in parallel, and the plurality of solenoid valves 30 are configured to respectively switch the supply and shut off of the pilot pressure to the plurality of the damping valves 20.

(54) In addition, the hydraulic shock absorber 100 has, as the damping valve 20, the first damping valve 20A and the second damping valve 20B provided in parallel with each other, the first damping valve 20A and the second damping valve 20B being configured to impart the resistance to the flow of the working oil, and the first damping valve 20A imparts the resistance only to the flow of the working oil directed from the one of the bottom-side chamber 1 and the rod-side chamber 2 towards the other of the bottom-side chamber 1 and the rod-side chamber 2.

(55) With these configurations, it is possible to realize an optimal damping characteristic according to the state of the vehicle.

(56) In addition, the hydraulic shock absorber 100, 101, 102, 103 further includes: the pilot passage 33 provided with the solenoid valve 30, the pilot passage 33 being configuration to guide the working oil in the bottom-side chamber 1 or the rod-side chamber 2 to the damping valve 20 as the pilot pressure; and the check valve 39 configured to guide the pilot pressure from the downstream side of the solenoid valve 30 in the pilot passage 33 to the bottom-side chamber 1 or the rod-side chamber 2.

(57) With this configuration, because the residual pressure in the pilot passage 33 caused when the solenoid valve 30 shuts off the supply of the pilot pressure is released through the check valve 39, it is possible to switch the damping valve 20 smoothly.

(58) In addition, the rod 12 has: the rod main body 51 connected to the piston 14, the rod main body 51 being slidably supported by the cylinder tube 10; the head portion 52 exposed to the outside of the cylinder tube 10; and the rod inner space 40 formed inside the rod main body 51, the rod inner space 40 has: the first space 41 communicating with the bottom-side chamber 1; and the second space 42 communicating with the rod-side chamber 2, the damping valve 20 and the solenoid valve 30 are provided in the head portion 52, and the pilot pressure is guided through the first space 41 or the second space 42.

(59) With this configuration, it is possible to prevent the gas from being mixed with the pilot fluid.

(60) Embodiments of this invention were described above, but the above embodiments are merely examples of applications of this invention, and the technical scope of this invention is not limited to the specific constitutions of the above embodiments.

(61) This application claims priority based on Japanese Patent Application No. 2022-35293 filed with the Japan Patent Office on Mar. 8, 2022, the entire contents of which are incorporated into this specification.

Claims

1. A fluid pressure shock absorber mounted on a vehicle, comprising: a cylinder tube; a rod inserted into the cylinder tube so as to be movable back and forth; a piston connected to the rod and dividing an interior of the cylinder tube into a bottom-side chamber and a rod-side chamber; a damping valve configured to impart resistance to a flow of working fluid between the bottom-side chamber and the rod-side chamber, the damping valve being capable of changing damping characteristic in response to a pilot pressure; and a solenoid valve configured to switch supply and shut off of a pilot pressure to the damping valve, wherein the working fluid in the bottom-side chamber or the rod-side chamber is used as the pilot pressure.

2. The fluid pressure shock absorber according to claim 1, wherein the working fluid in the bottom-side chamber is used as the pilot pressure, and pressurized gas is sealed in the bottom-side chamber.
 3. The fluid pressure shock absorber according to claim 1, wherein a plurality of the damping valves are provided in series, a plurality of the solenoid valves are provided in parallel, and the plurality of the solenoid valves are configured to respectively switch the supply and shut off of the pilot pressure to the plurality of the damping valves.
 4. The fluid pressure shock absorber according to claim 1, wherein the damping valve has a first damping valve and a second damping valve provided in parallel with each other, the first damping valve and the second damping valve being configured to impart resistance to the flow of the working fluid, and the first damping valve imparts the resistance only to the flow of the working fluid directed from one of the bottom-side chamber and the rod-side chamber towards other of the bottom-side chamber and the rod-side chamber.
 5. The fluid pressure shock absorber according to claim 1, further comprising: a pilot passage provided with the solenoid valve, the pilot passage being configured to guide the working fluid in the bottom-side chamber or the rod-side chamber to the damping valve as the pilot pressure; and a check valve configured to guide the pilot pressure from a downstream side of the solenoid valve in the pilot passage to the bottom-side chamber or the rod-side chamber.
 6. The fluid pressure shock absorber according to claim 1, wherein the rod has: a rod main body connected to the piston, the rod main body being slidably supported by the cylinder tube; a head portion exposed to outside of the cylinder tube; and a rod inner space formed inside the rod main body, the rod inner space has a first space communicating with the bottom-side chamber and a second space communicating with the rod-side chamber, the damping valve and the solenoid valve are provided in the head portion, and the pilot pressure is supplied through the first space or the second space.
 7. The fluid pressure shock absorber according to claim 1, wherein the damping valve is configured to impart the resistance to the flow of the working fluid between the bottom-side chamber and the rod-side chamber in both directions.
 8. The fluid pressure shock absorber according to claim 1, wherein the damping valve is configured such that a position is switched in response to the pilot pressure, and the resistance imparted to the flow of the working fluid passing through the damping valve varies at each position.
-