

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12403904
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Yoshikawa; Fumiaki et al.

Control modification device for vehicle

Abstract

A control modification device for vehicle includes: an acceleration suppression control part against sudden accelerator step-down that is mounted in a subject vehicle and is configured to limit a speed of the vehicle when a speed of an accelerator pedal step-down exceeds a prescribed threshold; an ID key that stores therein setting information showing whether a function of the acceleration suppression control part against sudden accelerator step-down is made valid or invalid; a setting change part that is configured to recognize the setting information stored in the ID key and change a setting based on the recognized result; and a control switch part that is mounted on the vehicle and is configured to prompt a user of the vehicle to select and switch whether the function of the acceleration suppression control part against sudden accelerator step-down is made valid or invalid, independently from the result of the setting change.

Inventors: Yoshikawa; Fumiaki (Tokyo, JP), Yanagida; Hisanori (Tokyo, JP), Matsushita; Satoshi (Tokyo, JP), Watanabe; Takashi (Tokyo, JP)

Applicant: HONDA MOTOR CO., LTD. (Tokyo, JP)

Family ID: 88195453

Assignee: HONDA MOTOR CO., LTD. (Tokyo, JP)

Appl. No.: 18/189361

Filed: March 24, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230311872 A1	Oct. 05, 2023

Foreign Application Priority Data

JP	2022-057774	Mar. 31, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: **B60W30/14** (20060101); **B60W50/08** (20200101); **B60W50/10** (20120101);
B60W50/14 (20200101)

U.S. Cl.:

CPC **B60W30/146** (20130101); **B60W50/085** (20130101); **B60W50/10** (20130101);
B60W50/14 (20130101); B60W2050/146 (20130101); B60W2540/043 (20200201)

Field of Classification Search

CPC: B60W (30/146); B60W (50/085); B60W (50/10); B60W (50/14); B60W (2050/146);
B60W (2540/043); B60W (50/0098); B60W (2050/0063); B60W (2050/0064); B60W
(2540/106); B60W (2540/215); B60W (50/087); B60K (31/00); B60K (26/02); B60K
(2031/0091); B60R (25/04)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6868170	12/2004	Fuku	340/5.53	B60R 25/252
8751065	12/2013	Kato	340/426.2	B60R 16/037
9842448	12/2016	Lickfelt	N/A	G07C 9/00896
11945432	12/2023	Naka	N/A	B60W 30/09
2014/0087917	12/2013	Tanaka	477/3	B60W 10/06
2014/0188310	12/2013	Hatfield	701/2	B60R 16/0231
2015/0246676	12/2014	Keren	701/93	B60W 30/146
2018/0257655	12/2017	Westover	N/A	B60W 10/06
2020/0310406	12/2019	Lavoie	N/A	G05D 1/0016
2023/0245223	12/2022	Okai et al.	N/A	N/A
2023/0306092	12/2022	Yahata	N/A	B60R 25/24
2023/0366463	12/2022	Yudell	N/A	F16H 37/021

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2011-192031	12/2010	JP	N/A
2021-179664	12/2020	JP	N/A
20210057971	12/2020	KR	N/A

OTHER PUBLICATIONS

Toyota Motor Corporation released a new “Sudden accelerator acceleration suppression” system, [online], Jul. 1, 2020, [searched on Mar. 1, 2022], Internet, <URL:<https://global.toyota.jp/newsroom/corporate/33012004.html>>; English translation included, 8 pages. cited by applicant

Japanese Office Action received in corresponding Japanese application No. 2022-057774 dated Oct. 31, 2023 with English translation (13 pages). cited by applicant

Primary Examiner: Worden; Thomas E

Assistant Examiner: Emmett; Madison B

Attorney, Agent or Firm: Rankin, Hill & Clark LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS

(1) This application claims the benefit of Japanese Patent Application No. 2022-057774 filed on Mar. 31, 2022, the disclosure of which is incorporated herein by reference.

BACKGROUND OF THE INVENTION

1. Field of the Invention

(2) The present invention relates to a control modification device for vehicle.

2. Description of the Related Art

(3) Some vehicles are recently equipped with acceleration suppression function against sudden accelerator step-down, so as to limit a speed of the vehicle, when a speed at which an accelerator pedal is stepped down exceeds a prescribed threshold. For example, Non-Patent Document 1 discloses a system in which, when a door of a vehicle is unlocked with a dedicated key, the acceleration suppression function against sudden accelerator step-down starts up automatically.

[Non-Patent Document 1] “Toyota Motor Corporation released a new “Sudden accelerator acceleration suppression” system”, [online], Jul. 1, 2020, [searched on Mar. 1, 2022], Internet <URL: <https://global.toyota/jp/newsroom/corporate/33012004.html>>

SUMMARY OF THE INVENTION

(4) The technique of Non-Patent Document 1 realizes the acceleration suppression function against sudden accelerator step-down of a vehicle by using a dedicated key. In other words, if a driver of the vehicle carries not the dedicated key but a key with which the acceleration suppression function against sudden accelerator step-down is not valid, there is no way for the driver to make the acceleration suppression function against sudden accelerator step-down valid. For example, when an elderly person with an intention of using the acceleration suppression function against sudden accelerator step-down may mistakenly carry with him/her not a dedicated key but a standard key used by any other person in his/her family, the function will not be enabled. He/she carrying the standard key with him/her then needs to open and close a door of the vehicle again so as to turn back home to get the dedicated key, which reduces operability of the vehicle.

(5) In order to solve the problems as described above, the present invention has been made in an attempt to improve vehicle operability until when an acceleration suppression function against sudden accelerator step-down is realized. This also improve traffic safety and contributes to development of a sustainable transportation system. The present invention has been thus made in an attempt to provide a control modification device for vehicle that can set an acceleration suppression control against sudden accelerator step-down to valid or invalid in accordance with a driver of the vehicle.

(6) A first aspect of the present invention provides a control modification device for vehicle that includes: an acceleration suppression control part against sudden accelerator step-down that is mounted in a subject vehicle and is configured to limit a speed of the vehicle when a speed of an accelerator pedal step-down exceeds a prescribed threshold; an ID key that stores therein setting information showing whether a function of the acceleration suppression control part against sudden accelerator step-down is made valid or invalid; a setting change part that is configured to recognize the setting information stored in the ID key and change a setting based on the recognized result;

and a control switch part that is mounted on the vehicle and is configured to prompt a user of the vehicle to select and switch whether the function of the acceleration suppression control part against sudden accelerator step-down is made valid or invalid, independently from the result of the setting change.

(7) A second aspect of the present invention provides a control modification device for vehicle that includes: a wireless communication part that is configured to receive a key ID from an ID key of a subject vehicle and also receive setting information showing whether an acceleration suppression function against sudden accelerator step-down is made valid or invalid, the acceleration suppression function against sudden accelerator step-down being used for limiting a speed of the vehicle; a control switch part that is configured to prompt a user of the vehicle to select and switch whether the acceleration suppression function against sudden accelerator step-down is made valid or invalid, independently from the received setting information; and an acceleration suppression control part against sudden accelerator step-down that is configured to limit the speed of the vehicle, based on information prompted to be switched by the control switch part, when a speed of an accelerator pedal step-down exceeds a prescribed threshold.

(8) The present invention can improve operability of a vehicle until when an acceleration suppression function against sudden accelerator step-down is realized.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1A is a diagram for explaining functions of a control modification device for vehicle and a control modification system for vehicle according to an embodiment of the present invention.
- (2) FIG. 1B is another diagram for explaining the functions of the control modification device for vehicle and the control modification system for vehicle according to the embodiment.
- (3) FIG. 1C is a still another diagram for explaining the functions of the control modification device for vehicle and the control modification system for vehicle according to the embodiment.
- (4) FIG. 1D is a yet another diagram for explaining the functions of the control modification device for vehicle and the control modification system for vehicle according to the embodiment.
- (5) FIG. 1E is a further diagram for explaining the functions of the control modification device for vehicle and the control modification system for vehicle according to the embodiment.
- (6) FIG. 2 is a diagram illustrating a configuration of the control modification device for vehicle and the control modification system for vehicle according to the embodiment.
- (7) FIG. 3 is a diagram illustrating an example of data stored in a storage part of a vehicle according to the embodiment.
- (8) FIG. 4 is a flowchart for explaining operations when a key ID is received according to the embodiment.
- (9) FIG. 5A is a diagram illustrating an example of a user authentication screen according to the embodiment.
- (10) FIG. 5B is a diagram illustrating an example of an acceleration suppression function activation enable/disable screen according to the embodiment.
- (11) FIG. 5C is a diagram illustrating an example of a sudden accelerator step-down control activation screen according to the embodiment.

DETAILED DESCRIPTION OF THE EMBODIMENTS

(12) An embodiment of the present invention (which may be simply referred to as an “embodiment” hereinafter) is described in detail with reference to the related drawings. Note that each of the figures is schematically illustrated to such an extent that the embodiment can be well understood. In the figures, the same reference numerals are given to the same or similar components and description thereof is omitted herefrom.

(13) (Embodiment)

(14) FIG. 1A to FIG. 1E are each a diagram for explaining functions of a control modification system for vehicle as a control modification device for vehicle according to an embodiment of the present invention.

(15) In FIG. 1A to FIG. 1E, FOB (Frequency Operated Button) keys **200**, **201** are used for locking or unlocking a door of a vehicle **100**. A PC **250** is used when a dealer performs initial setting of the FOB keys **200**, **201**. The vehicle **100** has an acceleration suppression function against sudden accelerator step-down which limits a speed of the subject vehicle **100**, when a speed of an accelerator pedal step-down exceeds a prescribed threshold.

(16) FIG. 1A illustrates that a dealer performs an initial setting of the FOB key **200** or **201** using the PC **250**. Contents of the initial setting include: a key ID **71** (FIG. 2) which is used for locking or unlocking a door of the vehicle **100**; acceleration suppression control valid/invalid setting data **73** (FIG. 2) which is setting information showing that an acceleration suppression function against sudden accelerator step-down of vehicle **100** is made valid or invalid; and user information (for example, name information **72** (FIG. 2)) for identifying respective users of the FOB keys **200**, **201**. This makes it possible to set whether the acceleration suppression function against sudden accelerator step-down is made valid or invalid for each of the FOB keys **200**, **201**. For example, the PC **250** sets the FOB key **200** to “valid”; and, the FOB key **201**, “invalid”. In other words, the PC **250** serves as a setting change part that recognizes information on setting of the FOB keys **200**, **201** and change the setting to appropriate one, based on the recognized information.

(17) FIG. 1B illustrates that, when “Mr. A” who is an elderly person unlocks the door of the vehicle **100** using the FOB key **200** and gets into the vehicle **10**, then an acceleration suppression function against sudden accelerator step-down becomes “valid”. FIG. 1C illustrates that, when “Ms. B” who is a family member of Mr. A and is younger than Mr. A unlocks the door of the vehicle **100** using the FOB key **201** and gets into the vehicle **10**, then the acceleration suppression function against sudden accelerator step-down becomes “invalid”. FIG. 1D illustrates that, when Mr. A carries the FOB key **201** with him, unlocks the door of the vehicle **100** with the FOB key **201**, and gets into the vehicle, then the acceleration suppression function against sudden accelerator step-down becomes “invalid”, even though Mr. A as the elderly person wants to use the function.

(18) Therefore, in this embodiment, when Mr. A unlocks the door of the vehicle **100** with the FOB key **201** of which acceleration suppression function against sudden accelerator step-down is set to “invalid”, Mr. A can change the function as “valid” using a display operation part **2** illustrated in FIG. 1E. In other words, though a dealer of the vehicle **100** previously set the function to “invalid” using the PC **250**, Mr. A can change the setting of the function to “valid”.

(19) FIG. 2 is a diagram illustrating a configuration of the control modification system for vehicle as the control modification device for vehicle according to the embodiment of the present invention.

(20) A control modification system for vehicle **1000**: includes the vehicle **100** and the FOB key **200**; and serves as the control modification device for vehicle as a whole. Note that the system **1000** may include the FOB key **201**, . . . , instead of the FOB key **200**. The FOB key **200** includes a communication part **51**, a key control part **60**, and a storage part **70**. The storage part **70**: is a non-volatile storage part such as a FROM (Flash Read Only Memory); and stores therein a program and setting information of various types. The setting information includes the key ID **71**, the acceleration suppression control valid/invalid setting data **73**, and the name information **72**.

(21) The key ID **71** is an ID unique to the FOB key **200**. Note that the storage part **20** of the vehicle **100** also stores therein an ID same as the key ID **71**, as a key ID **21**. The name information **72**: is information on a name of an owner of the FOB key **200**; and is displayed in the display operation part **2** of the vehicle **100** where necessary. The acceleration suppression control valid/invalid setting data **73** is setting information on whether the acceleration suppression function against sudden accelerator step-down is previously set to “valid” or “invalid”. Based on the data **73**, whether the

acceleration suppression function against sudden accelerator step-down of the vehicle **100** is made valid or invalid is set for each of the FOB key **200** and the like.

(22) The communication part **51** performs a wireless near field communication with the communication part **1** or the PC **250** (FIG. **1A**) of the vehicle **100**. The key control part **60**: is a CPU (Central Processing Unit); and executes a program to thereby realize functions of the setting change part **61** and the communication control part **62**. The communication control part **62** is a function part for controlling the communication part **51**. The setting change part **61** is a function part for changing (updating) the setting information stored in the storage part **70** by performing a wireless near field communication with the PC **250** (FIG. **1A**). Note that the vehicle **100** may further include a setting change part **15** illustrated with a broken line, that performs functions otherwise performed by the PC **250** (functions of receiving the acceleration suppression control valid/invalid setting data **73** stored in the FOB key **200**, and changing the received acceleration suppression control valid/invalid setting data **73** stored in the FOB key **200** to an appropriate setting value).

(23) The vehicle **100** includes the communication part **1**, the display operation part **2**, an actuator **3**, an accelerator pedal sensor **4**, a vehicle control part **10**, and the storage part **20**. The communication part **1** performs a wireless near field communication with the communication part **51** of the FOB key **200**. The display operation part **2** is a touch panel disposed on a front part of a driver's seat (see FIG. **1E**). The actuator **3** drives an electric motor for driving a wheel or a fuel injection valve. The accelerator pedal sensor **4** detects an amount of depression of an accelerator pedal.

(24) The storage part **20**: is a non-volatile storage part such as a FROM; and includes respective storage areas of the key ID **21**, the name information **22**, the acceleration suppression control valid/invalid setting data **23**, and acceleration suppression control activation enable/disable data **24**. The key ID **21** is an ID same as the key ID **71** stored in each of a plurality of the FOB keys **200**, **201**, The name information **22** is information corresponding to the name information **72** stored in each of a plurality of the FOB keys **200**, **201**, . . . and received via the communication part **1**. The acceleration suppression control valid/invalid setting data **23** is data corresponding to the acceleration suppression control valid/invalid setting data **73** stored in each of a plurality of the FOB keys **200**, **201**, . . . and received via the communication part **1**. The acceleration suppression control activation enable/disable data **24** is data referenced when the vehicle control part **10** determines whether or not an acceleration suppression control is provided. The acceleration suppression control activation enable/disable data **24** is a copy of the acceleration suppression control valid/invalid setting data **23** or a data changed therefrom.

(25) FIG. **3** is a diagram illustrating an example of data stored in the storage part **20** of the vehicle **100**.

(26) Acceleration suppression valid/invalid data **300** contains a "Key ID" column **310**, a "Name Information" column **315**, a "Setting Data" column **320**, and an "Activation Enable/Disable Data" column **330**. The "Key ID" column **310** contains the key ID **21** (FIG. **2**) for each of the FOB keys **200**, **201**, The name information **72** is stored in the "Name Information" column **315**, when the name information **72** is received from any of the FOB keys **200**, **201**, For example, name information having a key ID "AA0001" corresponds to "Mr. A"; and, a key ID "AA0002", "Ms. B". The "Setting Data" column **320** contains therein the acceleration suppression control valid/invalid setting data **23** (FIG. **2**). The "Activation Enable/Disable Data" column **330** contains therein the acceleration suppression control activation enable/disable data **24** (FIG. **2**). Note that the "Setting Data" column **320** and the "Activation Enable/Disable Data" column **330** are collectively referred to as an "Acceleration Suppression Valid/Invalid Data" column **350**.

(27) Returning to explanation of FIG. **2**, the vehicle control part **10**: is a CPU; and executes a program to thereby realize respective functions of a communication control part **13**, a display control part **14**, an acceleration suppression control part against sudden accelerator step-down **11**, and a control switch part **12**. The communication control part **13** is a function part that controls the

communication part **1**. The display control part **14** is a function part that controls the display operation part **2**. The acceleration suppression control part against sudden accelerator step-down **11** is a function part that controls the actuator **3** such that, when a driver having the specific FOB key **200** drives the vehicle **100** and suddenly steps down the acceleration pedal with a speed of the step-down exceeding a prescribed threshold, a speed of the vehicle **100** is limited (a response suppression). More specifically, the acceleration suppression control part against sudden accelerator step-down **11** references the acceleration suppression control activation enable/disable data **24** (the “activation enable/disable data” column **330** (FIG. 3)), and if the data **24** is determined to be “enable”, the part **24** provides the acceleration suppression control against sudden accelerator step-down. If the data **24** is determined to be “disable”, the part **24** does not provide the acceleration suppression control against sudden accelerator step-down.

(28) The control switch **12** is a function part that switches the acceleration suppression control activation enable/disable data **24** from “disable” to “enable” in response to an operation of the display operation part **2** by the driver. The configuration makes it possible for the driver to switch the acceleration suppression control activation enable/disable data **24** to “valid” by operating the display operation part **2**, even when the driver carries the FOB key **200** with the acceleration suppression control valid/invalid setting data **73** having been set to “invalid” and the acceleration suppression control activation enable/disable data **24** is therefore set to “disable”. That is, even when the driver carries with him/her the FOB key **200** in which the acceleration suppression control valid/invalid setting data **73** has been set to “disable”, the acceleration suppression control against sudden accelerator step-down can be performed.

(29) FIG. 4 is a flowchart for explaining operations performed when a key ID is received.

(30) A flow of FIG. 4 starts when the key ID **71** same as the key ID **21** (FIG. 2) is received from the FOB key **200**. The acceleration suppression control part against sudden accelerator step-down **11** (FIG. 2) receives the acceleration suppression control valid/invalid setting data **73** and the name information **72** from the FOB key **200** (S1). After S1, the acceleration suppression control part against sudden accelerator step-down **11**: stores the received acceleration suppression control valid/invalid setting data **73** in the storage part **20** as the acceleration suppression control valid/invalid setting data **23**; and also stores the received name information **72** in the storage part **20** as the name information **22** (S2). After S2, the acceleration suppression control part against sudden accelerator step-down **11** determines whether the acceleration suppression control valid/invalid setting data **23** is “valid” or “invalid” (S3).

(31) If the acceleration suppression control valid/invalid setting data **23** is determined to have been set to “invalid” (“invalid” in S3), the acceleration suppression control part against sudden accelerator step-down **11** displays an authentication screen in the display operation part **2** (FIG. 2) (S5). FIG. 5A is a diagram illustrating an example of a user authentication screen. A user authentication screen **410** has a character string of “User Authentication”, a “Mr. A?” button **402**, and a “Ms. B?” button **403**. That is, the user authentication screen **410** displays the name information **22** corresponding to one or each of a plurality of the key IDs **21** stored in the storage part **20**. An operator (the driver) of the screen **410** selects either of the buttons **402**, **403**. The configuration makes it possible for the acceleration suppression control part against sudden accelerator step-down **11** to recognize who is the operator (driver) even when the operator carries any one of the FOB keys **200**, **201**,

(32) After S5, the acceleration suppression control part against sudden accelerator step-down **11** determines whether or not the operator (driver) is a person himself/herself (S6). More specifically, the acceleration suppression control part against sudden accelerator step-down **11**: determines that, when a name selected in the user authentication screen **410** matches the name information **22** corresponding to the FOB keys **200**, **201**, . . . , the operator (driver) is the “Person himself/herself”; and, when the name selected in the user authentication screen **410** does not match the name information **22** corresponding to the FOB keys **200**, **201**, . . . , the operator (driver) is “Not person

himself/herself". When the operator (driver) is determined to be "Not person himself/herself", ("Not person himself/herself" in S6), the acceleration suppression control part against sudden accelerator step-down **11** displays an acceleration suppression function activation enable/disable screen **420** (FIG. 5B) in the display operation part 2 (S7).

(33) FIG. 5B illustrates an example of the acceleration suppression function activation enable/disable screen **420**.

(34) The acceleration suppression function activation enable/disable screen **420** has a character string of "Sudden Accelerator Step-Down Control Function" **421**, a character string of "Do you want to activate acceleration suppression control, Mr. A?" **422**, a "YES" button **423**, and a "NO" button **424**.

(35) After the display of S7, the acceleration suppression control part against sudden accelerator step-down **11** determines whether or not the acceleration suppression control is enabled (S8). If the "YES" button **423** is pressed down ("YES" in S8), the acceleration suppression control part against sudden accelerator step-down **11** stores "enable" as activation enable data in the acceleration suppression control activation enable/disable data **24** (FIG. 2) (S10). After S10 is performed, the acceleration suppression control part against sudden accelerator step-down **11** displays a sudden accelerator step-down control activation screen in the display operation part 2 (S11), and the processing thus terminates.

(36) FIG. 5C illustrates an example of a sudden accelerator step-down control activation screen.

(37) The sudden accelerator step-down control activation screen **430** has a character string of "Sudden Accelerator Step-Down Control Function" **431** and a character string of "Acceleration suppression control is successfully activated, Mr. A." **433**. The configuration makes it possible for the operator (driver) to recognize that the acceleration suppression control against sudden accelerator step-down has started up.

(38) In the meanwhile, if the "NO" button **424** is pressed down ("NO" in S8) or the authentication is determined to be "Person himself/herself" ("Person himself/herself" in S6), the acceleration suppression control part against sudden accelerator step-down **11** stores "disable" as activation disable data in the acceleration suppression control activation enable/disable data **24** (S9), and the processing terminates.

(39) If the acceleration suppression control valid/invalid setting data **23** is determined to be "valid" ("valid" in S3), the acceleration suppression control part against sudden accelerator step-down **11**: stores the acceleration suppression control valid/invalid setting data **23** as the acceleration suppression control activation enable/disable data **24** (S4); and displays the sudden accelerator step-down control activation screen in the display operation part 2 (S11), which terminates the processing.

(40) As described above, the control modification system for vehicle **1000** (FIG. 2) according to the embodiment is configured such that a driver carries any one of a plurality of the FOB keys **200**, **201**, . . . , with which the driver locks or unlocks a door of the vehicle **100**. The FOB key **200** stores therein the key ID **71** and the acceleration suppression control valid/invalid setting data **73**. For example, the FOB key **200** stores therein "valid" as the acceleration suppression control valid/invalid setting data **73**; and the FOB key **201** "invalid".

(41) The vehicle **100** stores therein the key ID **21** for each of the FOB keys **200**, **201**; and also stores therein the acceleration suppression control activation enable/disable data **24**. When the received key ID **71** matches the key ID **21**, the vehicle **100**: receives the acceleration suppression control valid/invalid setting data **73** from the FOB keys **200**, **201**, . . . ; and stores a copy of the received acceleration suppression control valid/invalid setting data **73** as the acceleration suppression control activation enable/disable data **24**. The vehicle **100** performs an acceleration suppression control based on the acceleration suppression control activation enable/disable data **24** selected by the operator (driver) via the display operation part 2, independently from the received acceleration suppression control valid/invalid setting data **73**.

(42) The configuration described above makes it possible that, even when, for example, an elderly person mistakenly carries the FOB key **201** with the acceleration suppression control set to “invalid” therein, instead of the FOB key **200** with the acceleration suppression control set to “valid” therein, it is not necessary for the person to unlock and lock the door again and return home to take the FOB key **200** with him/her. In other words, operability until when the acceleration suppression function against sudden accelerator step-down is realized is improved. In another case in which a person is required to drive while on the go, the person as a driver (a user) can activate an acceleration suppression control by using an operation of the display operation part **2**. The user himself/herself can make the acceleration suppression control valid and can start up the acceleration suppression control even with an improper FOB key.

(43) In the embodiment, the display operation part **2** displays the acceleration suppression function activation enable/disable screen **420** (FIG. 5B) in which a driver can select whether an acceleration suppression control is made valid or invalid. This makes it possible for the driver to recognize that a current state of the control is valid or invalid, thus allowing safety to be increased.

(44) In the embodiment, when a driver carries the FOB key **201** with the acceleration suppression control set to “invalid” therein, the display operation part **2** displays the acceleration suppression function activation enable/disable screen **420** (FIG. 5B). When the driver carries the FOB key **200** with the acceleration suppression control set to “valid” therein, the display operation part **2** will not display the acceleration suppression function activation enable/disable screen **420** (FIG. 5B). The configuration makes it possible for the driver to, when the driver carries the FOB key **200** with the acceleration suppression control set to “valid” therein, eliminate a need for an input operation on the acceleration suppression function activation enable/disable screen, thus allowing a driver's operation to be reduced. Additionally, the driver can change a setting of the acceleration suppression control, only when he/she carries the FOB key **201** with the acceleration suppression control set to “invalid” therein.

(45) [Variation]

(46) The present invention is not limited to that explained in the above-described embodiment and can make various modifications as follows.

(47) (1) In the above-described embodiment, the acceleration suppression control valid/invalid setting data **73** is stored in the FOB key **200**; and the acceleration suppression control part against sudden accelerator step-down **11** (FIG. 2) of the vehicle **100** performs an acceleration suppression control, based on the stored acceleration suppression control valid/invalid setting data **73** (FIG. 2). The present invention is not, however, limited to the embodiment. The acceleration suppression control valid/invalid setting data **73** (the acceleration suppression control valid/invalid setting data **23**) corresponding to the key ID **71** may be stored in the vehicle **100**. When the vehicle **100** receives the key ID **21** from the FOB key **200**, the vehicle control part **10** may perform an acceleration suppression control, based on the acceleration suppression control valid/invalid setting data **23** corresponding to the key ID **21**. Note that the setting change part **15** (FIG. 2) updates the acceleration suppression control valid/invalid setting data **23**.

(48) (2) The vehicle **100** may receive the key ID **71** or any other appropriate data not from the FOB key **200** but from a smartphone or the like (a so-called digital key).

(49) (3) It is assumed in the above-described embodiment that a single unit of the FOB key **200** is carried into the vehicle **100**. Another case is assumed in which a plurality of the FOB keys **200**, **201**, . . . are carried into the vehicle **100** without any user's operation, and the vehicle control part **10** (FIG. 2) thus fails to determination whether the acceleration suppression function against sudden accelerator step-down is valid or invalid. In this case, if the acceleration suppression function against sudden accelerator step-down is set to valid in any of the FOB keys **200**, **201**, . . . carried into the vehicle **100**, the acceleration suppression function against sudden accelerator step-down of the vehicle may be valid. **1**, **51** communication part **2** display operation part (display part) **4** accelerator pedal sensor **10** vehicle control part **11** acceleration suppression control part against

sudden accelerator step-down (response suppression control part against sudden accelerator step-down) **12** control switch part **15**, **61** setting change part **21**, **71** key ID **23**, **73** acceleration suppression control valid/invalid setting data (setting information) **24** acceleration suppression control activation enable/disable data **60** key control part **100** vehicle (control modification device for vehicle) **200**, **201** FOB key (ID key) **250** PC (setting change part) **300** acceleration suppression valid/invalid data **400** acceleration suppression valid/invalid setting screen **410** user authentication screen **420** acceleration suppression function activation enable/disable screen (screen prompting for selection and switching) **430** sudden accelerator step-down control activation screen **1000** control modification system for vehicle (control modification device for vehicle)

Claims

1. A control modification device for a vehicle, comprising: an acceleration suppression control part against sudden accelerator step-down that is mounted in the vehicle and is configured to limit a speed of the vehicle when a speed of an accelerator pedal step-down exceeds a prescribed threshold; an identification (ID) key that stores therein setting information showing whether a function of the acceleration suppression control part against sudden accelerator step-down is made valid or invalid; a setting change part that is configured to recognize the setting information stored in the ID key and change a setting based on the recognized result; and a control switch part that is mounted on the vehicle and is configured to prompt a driver of the vehicle to select and switch whether the function of the acceleration suppression control part against sudden accelerator step-down is made valid or invalid, independently from the result of the setting change.
 2. The control modification device for the vehicle according to claim 1, further comprising a display part having a screen in which the driver of the vehicle is prompted to select and switch whether the function of the acceleration suppression control part against sudden accelerator step-down is made valid or invalid, independently from the result of the setting change.
 3. The control modification device for the vehicle according to claim 2, wherein, only when the setting information stored in the ID key is set to invalid, the screen in which the driver of the vehicle is prompted to select and switch the function appears in the display part.
 4. A control modification device for a vehicle, comprising: a wireless communication part that is configured to receive a key identification (ID) from an identification (ID) key of the vehicle and also receive setting information showing whether an acceleration suppression function against sudden accelerator step-down is made valid or invalid, the acceleration suppression function against sudden accelerator step-down being used for limiting a speed of the vehicle; a control switch part that is configured to prompt a driver of the vehicle to select and switch whether the acceleration suppression function against sudden accelerator step-down is made valid or invalid, independently from the received setting information; and an acceleration suppression control part against sudden accelerator step-down that is configured to limit the speed of the vehicle, based on information prompted to be switched by the control switch part, when a speed of an accelerator pedal step-down exceeds a prescribed threshold.
 5. The control modification device for the vehicle according to claim 4, further comprising a setting change part that is configured to change the received setting information and change the setting information stored in the ID key to a setting value corresponding to the received and changed setting information.
-