

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12404699
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Caines; Marcus A. et al.

Foot-operated systems and devices for handleless operation of a door

Abstract

Systems, devices, and methods are provided herein for the handleless operation of a door. Illustrative examples of a system disclosed herein include a user interaction assembly configured to be disposed at a bottom edge of the door, the user interaction assembly configured to generate a signal, a push-lock assembly configured to attach to a door handle external to a mounting rose of the door handle, and the push-lock assembly configured to receive the signal from the user interaction assembly and translate the signal into rotational movement configured to operate the door handle.

Inventors: Caines; Marcus A. (San Diego, CA), Tillinghast; Theodore (Vista, CA), Caines; Clarke A. (Carlsbad, CA)

Applicant: AZTECH INDUSTRIAL DEVICES LLC (Carlsbad, CA)

Family ID: 87851318

Assignee: AZTECH INDUSTRIAL DEVICES LLC (Carlsbad, CA)

Appl. No.: 18/316930

Filed: May 12, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230279698 A1	Sep. 07, 2023

Related U.S. Application Data

continuation-in-part parent-doc US 17522789 20211109 US 12024926 child-doc US 18316930
us-provisional-application US 63341569 20220513
us-provisional-application US 63113699 20201113

Publication Classification

Int. Cl.: E05B53/00 (20060101)

U.S. Cl.:

CPC E05B53/001 (20130101);

Field of Classification Search

CPC: E05B (53/001); E05F (13/02)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1583818	12/1925	White	N/A	N/A
1603722	12/1925	Stanley	N/A	N/A
2741504	12/1955	Dale	N/A	N/A
4569546	12/1985	Howard	N/A	N/A
4621848	12/1985	Pierce	292/336.3	E05B 53/001
5217265	12/1992	Lerner	N/A	N/A
5725263	12/1997	Rodriguez	292/342	E05C 17/48
6176042	12/2000	Rossman	N/A	N/A
6360488	12/2001	Darling	N/A	N/A
6967580	12/2004	Schulze	340/568.1	G08B 25/016
7270352	12/2006	Stuart	292/336.3	E05B 1/0053
7788954	12/2009	Schumm	N/A	N/A
8707622	12/2013	Neustel, Jr.	N/A	N/A
8745922	12/2013	Matsuda	N/A	N/A
8888149	12/2013	Lehr	292/201	E05B 53/001
9145713	12/2014	Norris	N/A	E05B 53/00
9347252	12/2015	Klein	N/A	N/A
11053718	12/2020	Finley	N/A	E05C 19/003
2007/0256362	12/2006	Hansen	N/A	N/A
2013/0118085	12/2012	Hedemark	49/504	F16H 21/44
2013/0318882	12/2012	Booker	N/A	N/A
2014/0353985	12/2013	Klein	N/A	N/A
2015/0020454	12/2014	Klein	49/267	E05F 11/54
2017/0218661	12/2016	Fraychineaud, Jr.	N/A	E05B 1/0053
2019/0128022	12/2018	Markway	N/A	N/A
2021/0310272	12/2020	Chu	N/A	E05B 53/001
2021/0332614	12/2020	Taylor	N/A	E05B 47/0001
2022/0154494	12/2021	Caines	N/A	E05F 13/02

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
211598112	12/2019	CN	N/A
202020101984	12/2019	DE	N/A

1048811	12/1999	EP	N/A
1889990	12/2007	EP	N/A
1889990	12/2007	EP	E05B 1/0053
2016037600	12/2015	WO	N/A

Primary Examiner: Williams; Mark A

Attorney, Agent or Firm: DICKINSON WRIGHT RLLP

Background/Summary

REFERENCE TO RELATED APPLICATION (1) The present application is a continuation-in-part of and claims priority to U.S. patent application Ser. No. 17/522,789, filed on Nov. 9, 2021 and titled “FOOT-OPERATED SYSTEMS AND DEVICES FOR HANDLESS OPERATION OF A DOOR,” now U.S. Pat. No. 12,024,926, which claims priority to U.S. Provisional Patent Application Ser. No. 63/113,699, filed on Nov. 13, 2020 and titled “Foot-Operated Systems and Devices for Handless Operation of a Door,” the disclosures of which are incorporated herein by reference in their entirety. (2) The present application also claims priority to U.S. Provisional Patent Application Ser. No. 63/341,569, filed on May 13, 2022 and titled “Foot-Operated Systems and Devices for Handless Operation of a Door,” which is incorporated herein by reference in its entirety.

BACKGROUND

Technical Field

(1) This disclosure relates to hands free operation of a door. More specifically, this disclosure relates to foot operated devices and systems that provide for operation of the door, without the need for a user to interact with a doorknob or handle.

Description of the Related Art

(2) In a world impacted by the spread of infectious disease, doorknobs and handles are among the dirtiest, most used surfaces within homes, restaurants, and bathrooms. Once the knob or handle is contaminated, each user thereafter opening or closing the door encounters the risk of being infected and contracting a cold, flu, coronavirus, or other disease. Contamination is best avoided by careful hand washing; however, many people using public facilities exhibit less than exemplary hygiene and either inadequately wash their hands or fail to wash them altogether. As a result, unsanitary and contaminated doorknobs and handles continue to be a health concern.

(3) The present disclosure is directed toward overcoming the problems identified above.

SUMMARY

(4) The present disclosure, in accordance with one or more various embodiments, is described in detail with reference to the following figures. The figures are provided for purposes of illustration only and merely depict typical or example embodiments.

(5) The disclosure describes a system comprising a door handle operating assembly and user interaction assembly designed for contactless usability when opening/closing your latched door. The design is simple to use and can help anyone get through any door with ease. The design makes it so opening a latched door can be done without using one's hands, thus mitigating risk of spreading bacteria. The ability to open latched doors this way will be most beneficial to hospitality and industrial businesses that require their employees/doctors to sterilize multiple times throughout the day.

(6) Other features and aspects of the disclosed technology will become apparent from the following detailed description, taken in conjunction with the accompanying drawings, which illustrate, by

way of example, the features in accordance with embodiments of the disclosed technology. The summary is not intended to limit the scope of any inventions described herein, which are defined solely by the claims attached hereto.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) The details of embodiments of the present disclosure, both as to their structure and operation, may be gleaned in part by study of the accompanying drawings, in which like reference numerals refer to like parts, and in which:
- (2) FIG. 1 is a schematic drawing of an embodiment of a system for handleless operation of a door in a first state, in accordance with embodiments disclosed herein.
- (3) FIG. 2 is a schematic drawing system for the handleless operation of FIG. 1 in a second state.
- (4) FIGS. 3A and 3B are schematic drawings of user interaction assembly, included as part of the system of FIG. 1.
- (5) FIGS. 4A and 4B are schematic drawings of the user interaction assembly of FIGS. 3A and 3B in the first and second states, respectively.
- (6) FIG. 5 is a schematic graphical representation of an example door handle operating assembly, included as part of the system of FIG. 1, coupled to a door handle assembly.
- (7) FIGS. 6-9 are schematic graphical representations of internal components of the example door handle operating assembly of FIG. 5, with a housing removed.
- (8) FIG. 10 is a schematic graphical representation of a back side view of the example door handle assembly of FIG. 5.
- (9) FIG. 11 is a schematic drawing of another embodiment of a system for handleless operation of a door in accordance with an embodiment disclosed herein.
- (10) FIGS. 12A and 12B are schematic drawings of an example user interaction assembly of the system of FIG. 11.
- (11) FIG. 13 is a cross-section of the user interaction assembly of FIG. 11 taken along the line A-A'.
- (12) FIG. 14 is a schematic drawing of an example L-shaped component of the user interaction assembly of the system of FIG. 11.
- (13) FIG. 15 is a graphical representation another example door handle operating assembly, with a housing removed, according to an embodiment of disclosed herein.
- (14) FIG. 16 is a graphical representation of a spindle interfacing component comprising a pinion according to an embodiment disclosed herein.
- (15) FIG. 17 is a cross section of the door handle operating assembly of FIG. 11 taken along the line B-B'.
- (16) FIG. 18 is a functional block diagram of a wireless computing system that can be implemented with embodiments of the systems disclosed herein.

DESCRIPTION

- (17) The detailed description set forth below, in connection with the accompanying drawings, is intended as a description of various embodiments and is not intended to represent the only embodiments in which the disclosure may be practiced. The detailed description includes specific details for the purpose of providing a thorough understanding of the embodiments. However, it will be apparent that those skilled in the art will be able to understand the disclosure without these specific details. In some instances, well-known structures and components are shown in simplified form for brevity of description. Some of the surfaces have been left out or exaggerated for clarity and ease of explanation.
- (18) References throughout this specification to one/an “implementation”, “one embodiment” or

“an embodiment” means that a particular feature, structure, or characteristic described in connection with the embodiment is included in at least one embodiment. Thus, appearances of the phrases “in one embodiment” or “in an embodiment” in various places throughout this specification are not necessarily all referring to the same embodiment. Furthermore, the particular features, structures, or characteristics may be combined in any suitable manner in one or more embodiments.

(19) The present disclosure is directed to the methods, apparatus, systems, and assemblies designed for contactless usability when opening/closing a latched door. Embodiments herein provide a system for the handleless operation of a door that is configured to attach to an existing door handle assembly and provide for user interaction at a location that is spaced apart from a door handle assembly. For example, a push-lock mechanism can be attached to a handle of a door handle assembly on the door, and configured to operate (e.g., turn) the handle in response to interaction with a user interaction assembly physically or wirelessly coupled to the push-lock mechanism, without the need of the user to grasp or otherwise turn the handle using their hand. The user interaction assembly can thus be positioned at any location separate from the door handle assembly. In an illustrative example, the user interaction assembly can be comprised of a foot pedal and the push-lock mechanism can be configured to operate (e.g., turn) the handle in response to operating the foot pedal. Upon operating the foot pedal, according to some embodiments, the push-lock mechanism may be employed to open an unlatched door, for example, by converting an upward translational force to a rotational force that rotates the door handle to unlatch and open the door. Alternatively, a pulling force may also be applied to the push-lock mechanism that may open the door. In yet another example, operating the foot pedal may generate a signal that can be used to trigger the push-lock mechanism to operate the door handle assembly.

(20) The design is simple to use and can help anyone get through any door with ease. The design makes it so that opening a latched door can be done without using one's hands, thus mitigating the risk of spreading bacteria. The ability to open latched doors this way will be most beneficial to hospitality and industrial businesses that require their employees/doctors to sterilize multiple times throughout the day.

(21) Another benefit of the embodiment disclosed herein is opening doors when one's hands are full. There's nothing worse than loading up your arms with groceries, laundry, or whatever it may be and realizing you've forgotten to open the door beforehand. Embodiments disclosed herein provide for operating a door without hands. Furthermore, embodiments herein also make it easier for children, or those who may not be able to reach a door handle, to open doors.

(22) Some embodiments herein comprise a knurled surface on a user interaction assembly that allows for optimal grip when opening/closing a latched door. Additionally, embodiments herein are easy to install on any doorway because the embodiments disclosed herein fit to any doorway seamlessly. To assemble, one may install the door handle as normal, attach the push-locking mechanism into the bottom of the door handle (e.g., external to the mounting rose along the spindle), do the same with the user interaction assembly, and finally attach the user interaction to the bottom of the door for stability. Once complete, the user interaction assembly will supply the capability that the door handle would, and may operate to lock the door handle.

(23) FIGS. 1 and 2 are schematic drawings of a system **100** for handleless operation of a door D in accordance with embodiments disclosed herein. System **100** comprises a user interaction assembly **110** and communication medium **120**. The communication medium **120** is coupled to the user interaction assembly **110** and a door handle operating assembly **130**, which comprises a push-lock mechanism. The system **100** can be used to operate a door handle assembly **140** to disengage a latch L from a strike plate S of a door frame (not shown) and allow a user to open the door through user interaction with the user interaction assembly **110**. In this way, the user need not grasp or otherwise make physical contact with the door handle **140**.

(24) In the embodiments disclosed herein, such as shown in FIG. 1, the door handle need not be

disassembled to install the push-lock mechanism. The communication medium **120** may be attached to a door handle via the door handle assembly **140**, in accordance with the embodiments disclosed herein. Thus, the system **100** may be connected to an existing door handle assembly **140**.

(25) As alluded to above, the system **100** may be connected to an existing door handle assembly **140**, without requiring access to internal mechanisms of the door handle. For example, a conventional door handle (such as a lever door handle assembly **140** shown in FIG. **1**) comprises two handles (such as knobs, levers, etc.)— one on each side of the door (one example door handle is shown in FIG. **1** as handle **142**). The handles are each connected to a mounting rose (or rosette), which is a plate that conceals and secures internal mechanisms of the door handle. The internal mechanisms of the door handle include a spindle, which is generally a square bar that connects both handles. The spindle passes through the mounting rose and is connected to the handle. The handle may include a housing or sleeve configured to receive a portion the spindle that extends externally to the door from the mounting rose to the handle. The housing or sleeve may include a handle extender in some implementations. A spindle interfacing component may be positioned within the sleeve such that the spindle interfacing component is stationary relative to the handle. The spindle interfacing component is configured to receive an end of the spindle extending from the mounting rose toward the handle and interlock the spindle with the handle, such that rotation of the handle is transferred to the spindle via the spindle interfacing component. The spindle interfacing component may generally comprise a square shaped hole extending along its length to receive the spindle for receive a square bar spindle. The internal mechanisms also include a latch assembly that is generally a spring-loaded bolt, which can be operated by rotating the spindle to engage or disengage a latch from a strike plate on a door frame. System **100** can be connected to the conventional door handle external to the mounting rose, such that a user need not access the internal mechanisms. In the example shown in FIG. **1**, door handle operating assembly **130** can be installed between the door handle **142** and a mounting rose. As will be described in greater detail below, the door handle operating assembly **130** can be coupled to a portion of the spindle that resides externally to the mounting rose and can be used to rotate the spindle so as to disengage or engage a latch from a strike plate.

(26) While the examples provided herein illustrate the door handle operating assembly **130** attached to a lever style door handle assembly **140**, the embodiments disclosed herein are not limited to lever style door handles. The embodiments disclosed herein may be applied to any style of door handle assembly, such as knob style door handles and any other mechanisms for operating a latch.

(27) In the illustrative example of FIG. **1**, the communication medium **120** is provided as an arm member **120**. The arm member **120** may include one or more plates of material, rods of material, wires, or any medium that physically couples to the user interaction assembly **110** to the door handle operating assembly **130**. Through physical coupling, operation of the user interaction assembly **110** can be transferred to door handle operating assembly **130**, which operates the door handle assembly **140** to unlatch the door (e.g., disengage the latch from the strike plate). The user may then move their foot using a pushing or pulling motion at the user interaction assembly **110** to open and/or close the door. In another example, the communication medium may be a wired or wireless communication medium that provides for exchange of electrical or wireless signals from the user interaction assembly **110** to the door handle operating assembly **130**. In this example, the arm member **120** may need not be included and instead system **100** uses a wired or wireless communication, such as antennas, transmitters, receivers, and the like, to communicate a signal to trigger operation of door handle operating assembly **130**.

(28) In operation, the user interaction assembly **110** may be configured for foot detection and/or actuation to generate a signal, which can be communicated to the door handle operating assembly **130** via the communication medium **120**. For example, user interaction assembly **110** may be referred to as a foot pedal assembly that a user can interact with using his/her foot. As another

example, user interaction assembly **110** may be sensors that can detect the presence of a foot. In either case, the door handle operating assembly **130** converts the signal to rotational movement that operates door handle assembly **140**. Thus, there is no need for a user to contact the door handle itself (e.g., by grasping the handle). In some examples, the generated signal is a translational force that is received at the door handle operating assembly **130** as a translational movement via the communication medium as an arm member **120**. The door handle operating assembly **130** then converts the translational movement to rotational movement. In another example, the signal may be communicated via a wired or wireless signal indicating that a foot has been detected, which is communicated via the communication medium (e.g., wired or wireless communication mediums) as electrical or wireless signals to the door handle operating assembly **130** (FIG. 5). The door handle operating assembly **130** may receive the signal, activate one or more actuators, and generate the rotational movement accordingly.

(29) In the illustrative example of FIG. 1, the communication medium is an arm member **120** that is physically coupled to the door handle operating assembly **130** at upper end and the user interaction assembly **110** at a lower end. The arm member **120** is configured to communicate a translational force from the user interaction assembly **110** into translational movement applied to the door handle operating assembly **130**. The user interaction assembly **110** may be configured to convert foot actuation into the translational force that is applied to the lower end of the arm member **120**. The arm member **120** then communicates the translational force to the door handle assembly as translational movement. The door handle operating assembly **130** converts the translation movement to rotational movement to operate door handle **142**. Thus, there is no need for a user to contact the door handle itself (e.g., by grasping the handle).

(30) FIG. 1 illustrates the system **100** in a first position or state, for example, in a latched state. The latched position may refer to a resting state, for example, when the door is not currently operated by a user and the latch of the door handle is engaged with the door. FIG. 2 illustrates the system **100** in a second position or state, for example, an unlatched state. The unlatched state may refer to a user engaged or user operating state and the system is engaged to open the door such that the latch is no longer engaged with the door. The unlatched state may be a result of user engagement or operation with the user interaction assembly **110** by a foot F of the user, as shown in FIG. 2.

(31) FIGS. 3A-3B and 4A-4B illustrate the user interaction assembly **110** according to an embodiment disclosed herein. FIGS. 3A and 3B are schematic drawings of the user interaction assembly **110** at different perspective views. FIGS. 4A and 4B provide schematic drawings of the user interaction assembly **110** in the unlatched state (user interaction assembly **110a**) and the unlatched state (user interaction assembly **110a**), respectively.

(32) The user interaction assembly **110** comprises an L-shaped component **114** (sometimes referred to as a kick-and-pull component, foot pedal, or a bracket), and an anchor component **112**. In the illustrative examples herein, the L-shaped component **114** comprises a knurled surface **104** on which the user's foot interacts. In another example, the L-shaped component **114** may have other textured surfaces on which the user's foot interacts. The texture or knurling of surface **104** may provide for increased gripping between a user's foot and the surface **104** by increasing friction therebetween. As another example, the L-shaped component **114** may comprise a padding covered by a fabric or leather material. Similarly, the padding or fabric may function to increase grip between the user's foot and the surface **104**, as well as providing for an aesthetic appearance. In yet another example, the L-shaped component **114** may have a flat surface without texture or fabric.

(33) The L-shaped component **114** may include a first (vertical) planar member **111** arranged to face the door and a second (horizontal) planar member **113** extending from a bottom end of the first planar member **111** outward from the door. The second planar member **113** may include a vertical protrusion **117** (also referred to as a lip structure) at an end opposite the first planar member **111** and configured to be engaged with by a user's foot to facilitate opening of the door through a pulling force applied, for example, by a toe and/or heel of the user's foot. A plurality of ribs **109**

may extend from the protrusion **117** to the first planar member **111** and the second planar member **113**. The plurality of ribs **109** may function to increase the structural rigidity of the L-shaped component **114** by increasing tensile strength at the intersection of second planar member **113** and first planar member **111**.

(34) The L-shaped component **114** also comprises opening **119** extending down a central portion of the L-shaped component **114**. The opening **119** has at least a first opening portion that extends from the upper end of the first planar member **111** toward the second planar member **113** and having a first width adapted to receive the arm member **120**. A lower end of arm member **120** can be inserted into the opening **119** and coupled to the first planar member **111** via fastener components **108a** and **108b**. As used herein, fastener components may refer to any component that is able to permanently or removably attach one structure to another, such as but not limited to, bolts (as shown in FIG. **10**), screws, nails, adhesive, suction cups, snaps, rivets, etc.

(35) The L-shaped component **114** is adapted to convert a force exerted by foot operation of the user interaction assembly **110** into a translational force that is applied to arm member **120**. For example, a translational force exerted parallel to the first planar member **111** exerts a similarly directed translational force on arm member **120** due to the coupling between the L-shaped component **114** and the arm member **120**. The force applied to the arm member **120** can be transferred to the door handle operating assembly **130** via arm member **120** to operate the door handle assembly **140**. For example, a user's foot may press downward on the L-shaped component **114** (e.g., pressing down on the second planar member **113** and/or protrusion **117**), which pulls down on the arm member **120**. This downward translational force is transferred to the door operating assembly **130** and causes the door handle operating assembly **130** to disengage the latch of the door handle assembly **140**. Once disengaged, the user's foot may interact with the protrusion **117** to open the door toward the user using a horizontal pulling motion of their foot to pull the door toward the user. Thus, the user need not use their hands to operate the door handle or physically open the door. As another example, after pressing L-shaped component **114** to disengage the latch, the user's foot may horizontally push on L-shaped component **114** and/or vertical protrusion **117** to open the door away from the user.

(36) In some embodiments, the vertical protrusion **117** may optionally comprise a toothed structure at an end of the protrusion **117** opposite the second planar member **113**. An example toothed structure is shown in U.S. patent application Ser. No. 17/522,789, the disclosure of which is incorporated herein by reference in its entirety. The tooth structure may be provided to increase the grip of the user's foot with the protrusion **117**. The increased grip ensures the user's foot is able to open the door without slipping off of the protrusion **117**, which would result in closing the door. Other textured surfaces may be used in place of the toothed structure, for example, a knurled surface, textured surface, textured fabric or material, or the like.

(37) Operation of the L-shaped component **114** by a downward force applied by the user is translated to a downward force applied to the arm member **120** via the physical coupling therebetween. The arm member **120** translates this force as a downward translational movement to the door handle operating assembly **130** which is converted to a rotational force to operate the door handle assembly **140**, as will be described in more detail below in connection with FIGS. **5-10**.

(38) The user interaction assembly **110** may be optionally coupled to the door via the anchor component **112**. The anchor component **112** may be physically coupled to the door by fastener components **107a** and **107b**. The anchor component **112** may include a step shaped profile when viewed from a horizontal direction parallel to the door (as shown in FIGS. **3A** and **3B**) having a main body component **116** and a cover or lip component **115** extending from the main body component **116** toward second planar member **113**. The main body component **116** may comprise a channel **106** extending therethrough that is adapted to slidably receive the arm member **120**. That is, for example, a portion of arm member **120** can be located within the channel **106** and held between the main body component **116** and the door. The cover component **115** may extend from

the main body component **116** toward the L-shaped component **114** and overlap with a portion of the first planar member **111** (e.g., the first planar member **111** is positioned between the door and the cover component **115** in a direction perpendicular to the first planar member **111**). A gap **118** may be formed between the main body component **116** and the upper end of the first planar member **111**, with the gap **118** covered by the cover component **115**. As shown in FIGS. **4A** and **4B**, the gap **118** is increased in distance between the upper end of the first planar member **111** and a lower end of the main body component **116** in the unlatched state (e.g., larger gap **118a**) and is decreased in the latched state (e.g., smaller gap **118b**).

(39) In some embodiments, the L-shaped component **114** and the arm member **120** may be free floating relative to the door. For example, the arm member **120** and L-shaped component **114** may not be physically coupled directly to the door, and only held in place relative to the door due to attachment of the door handle operating assembly **130** to the door handle assembly **140**.

Accordingly, anchor component **112** can be used to restrain the arm member **120** (and the coupled L-shaped component **114**) in lateral directions (e.g., horizontal directions) relative to the door, while permitting the arm member **120** (and coupled L-shaped component **114**) to move in the vertical direction (e.g., longitudinal direction) relative to the door. Accordingly, anchor component **112** may be stationary relative to the door, while L-shaped component **114** and arm member **120** are laterally stationary and longitudinally nonstationary relative to the door.

(40) FIGS. **5-10** are schematic graphical representations of the door handle operating assembly **130**. With reference to FIGS. **5-10**, the door handle assembly **140** includes a door handle **142** that interfaces with a housing (also referred to as a case or cover) **134** of the door handle operating assembly **130**. The door handle operating assembly **130** also includes a push-lock mechanism or assembly **135** (e.g., FIGS. **6-9**) physically coupled to the arm member **120** via fastener components. The push-lock assembly **135** is configured to rotate the door handle **142** to move the latch and disengage the latch from the strike plate of the door handle assembly **140**. For example, operation of the L-shaped component **114** causes a signal (e.g., a force in this example) to be translated along arm member **120** that is applied to the push-lock assembly **135**. The push-lock assembly **135** converts the translational force from arm member **120** to a rotational force that rotates the door handle **142**, thereby disengaging the latch of the door handle assembly **140** from a strike plate of a door frame (not shown).

(41) The door handle assembly **140** may include a lever door handle **142** for turning a spindle assembly **146**, housed in a sleeve **143**, configured to operate and disengage the latch (not shown) from a door frame (not shown). The spindle assembly **146** may comprise a spindle **146b** (as shown in FIG. **10**), a spindle interfacing component **146a**, or a combination thereof. Thus, reference to spindle assembly **146** may refer to the spindle itself, the spindle interfacing component, or both. The door handle **142** also includes a mounting rose **144** attached to the door via mounting holes **152** configured to receive fastener components (e.g., screws holes, nail, holes, etc.) that covers and houses the internal components of the door handle assembly **140**. Door handle **142** may be any type of doorknob, for example, a lever handle doorknob as shown in FIGS. **6-10**, a round or oval doorknob, etc. The illustrative examples herein are described in connection with a lever style doorknob, but the embodiments herein will be equally applicable to any type of doorknob known in the art.

(42) In the illustrative examples of FIGS. **5-10**, the housing **134** may be positioned to receive and house the mounting rose **144**. The housing **134** may comprise an opening **153** that slidably receives the arm member **120**. The housing **134** operates to protect the internal components of door handle operating assembly **130** from external interference, such as from a user. Similarly, a user is thus unable to interact with the internal components that may otherwise hurt the user.

(43) The push-lock assembly **135** may include a first component for receiving the signal from the arm member **120** and a second component interfaced with the first component and configured to convert the translational force from the arm member **120** to a rotational form applied to the door

handle **142** (e.g., a lever or knob) and/or spindle assembly **146**. For example, an end of the arm member **120** may be physically coupled to a plate **136** of the push-lock assembly **135**, the plate **136** may be an example of the first component. In the illustrative examples of FIGS. **6-8**, the plate **136** comprises at least an elongated member **137** extending vertically from a bottom portion of plate **136** adjacent to arm member **120** and defining an opening **133**. The plate **136** comprises at least one internal rack **132** along a vertical internal edge of elongated member **137** (as shown in FIGS. **6-8**). The internal rack **132** may also or alternatively be referred to as the first component of the push-lock assembly **135**. In some embodiments, the plate **136** may include internal pinions (instead of rack **132**) on one or more of the elongated members **137**. In another embodiment, the opening **133** may include an internal gear. The length of the rack **132** should be at least long enough to accommodate full travel of the door handle **142**.

(44) In some embodiments, the plate **136** may also comprise an optional elongated member **139** extending vertically from the arm member **120** on a side of the pinion **138** opposite the elongated member **137**. Elongated member **139** may act as a guide to keep the pinion **138** in contact with the rack **132**. In one example, elongated member **137** may be longer than the elongated member **139**. In another example, the member **137** and **139** may be the same length.

(45) In another example, the opening may be an oval or stadium shaped opening, for example, opening **233** of plate **236** of FIG. **9**. In this implementation, the opening comprises elongated members **239** and **237** (including rack **232**), which are similar to elongated members **139** and **137**, are connected as shown in FIG. **9**. Furthermore, the opening **233** need not be ovalar in shape, and may be circular, rectangular, rounded, etc.

(46) The push-lock assembly **135** may also include pinion **138** (or other type of gear) (e.g., the second component) that can interface or otherwise engage with the rack **132**. The pinion **138** may be physically coupled to and interlocked with the door handle assembly **140**. Thus, a translational force applied to the arm member **120** causes the plate **136** to move in a direction responsive to the applied force, which rotates the pinion **138** via the internal rack **132** and turns the door handle **142**.

(47) In some embodiments, the plate **136** may include a protrusion **122** that couples the plate **136** to the arm member **120** via fastener components, for example, as shown in FIGS. **6-8**. In another example, the arm member **120** may include a protrusion that couples to the plate **136** and the plate is substantially planar. Either protrusion may operate as to provide clearance for the plate **136** to be distances from the door so as to clear the mounting rose **144**. The protrusion may also operate as a stop for the vertical movement of the plate by butting up against the mounting rose **144**. In another example, protrusion **122** may extend from plate **136** and comprise an opening sized to receive arm member **120**. The arm member **120** can be inserted and attached to plate **136** within the opening, for example, via fasteners. In yet another embodiment, arm member **120** may be provided with a thickness such that the surface of the arm member **120** contacts the plate **136**, without protrusion **122**.

(48) In operation, when the user interaction assembly **110** is in the first state (e.g., as shown in FIG. **1** and FIG. **4B**), the pinion **138** can be positioned at a first (closed) position within the opening **133** (e.g., the pinion **138** is located at approximately the middle of the rack **132**) and the door handle assembly **140** is in a closed or latched position, as shown in FIG. **1**. Operation of the user interaction assembly **110** to the second state, for example, by a downward force exerted on user interaction assembly **110** as shown in FIG. **2**, causes the rack **132** to move in a vertical/downward direction (in the example shown in FIG. **6**) and the rack **132** turns the pinion **138**, which is translated to the handle **142** via interlocking of the pinion **138** with the spindle assembly **146** (e.g., spindle interfacing component **146a** as shown in FIGS. **8** and **9**). For example, pinion **138** may be affixed to a spindle interfacing component **146a** and/or a spindle **148a**. The pinion **138** may be removably affixed to the spindle assembly **146**, as described below in connection with FIGS. **8** and **9**, or integrally formed into the spindle assembly **146**, as described below in connection with FIGS. **15-17**. When the user interaction assembly **110** is in the second state (e.g., as shown in FIG. **2** and

FIG. 4B), the pinion **138** is positioned at a second position of the opening **133** (e.g., a lower portion of the opening **133**), as shown in FIGS. 7 and/or 8, and the door handle assembly **140** is in an open or unlatched position, as shown in FIG. 2. Releasing the user interaction assembly **110** releases the force applied to arm member **120** and plate **136** to move in a vertical/upward direction. The pinion **138** turns the rack **132** as the door handle **142** returns to the closed or latched position, which brings the user interaction assembly **110** into the first position. For example, a spring or other mechanism of the door handle assembly **140** causes door handle **142** to return to a closed position upon release of user interaction assembly **110**, which rotates the pinion **138** and causes the rack **132** to move. Movement of the rack **132** pulls plate **136** and arm member **120** in the vertical/upward direction and returns system **100** to the first state (e.g., latched or closed state).

(49) In some embodiments, a portion of the plate **136** may be exposed from the housing **134** via opening **155** (as shown in FIG. 10). For example, when the user interaction assembly **110** is in the second state, an upper portion of the plate **136** may be positioned above the mounting rose **144** (FIGS. 6 and 8) and/or above the housing **134**. In the first state, the plate **136** may be completely housed within the housing **134**. In some embodiments, the plate **136** need not be exposed and may be completely housed by the housing in both states, for example by constructing a housing **134** large enough to house all internal components in any state, for example, as shown in FIGS. 1 and 2.

(50) Openings **153** at the bottom side of the housing **134** (e.g., FIG. 5) and optional opening **155** (if present) form a guide or channel into which the arm member **120** may be received and guide the plate **136** up and down in the vertical direction while holding the plate **136** (and therefore the rack **132**) in place in the other non-vertical directions (e.g., horizontally stationary). For example, a channel extending from opening **153** may comprise side walls formed within the housing **134** that receive an upper end of arm member **120** and a plate **136**. During operation, the upper end of arm member **120** and plate **136** may be moved (e.g., sliding or other translational movement) in the vertical direction within the channel, while side walls of the channel restrain the arm member **120** and plate **136** from non-vertical translation movements.

(51) Embodiments herein may also permit normal operation of the door handle assembly **140** via a user operation of handle **142**. For example, a user may operate the door handle assembly **140** by applying a downward force on the handle **142**. The downward force rotates the spindle assembly **146** which is translated to pinion **138**. Rotation of pinion **138** causes vertical translational movement of the plate **136** via the rack **132**, which pulls on the arm member **120** and moves the user interaction assembly **110** into the second state. As another example, a user may apply an oppositely directed vertical force to the handle **142**, rotating the spindle assembly **146** which is translated to pinion **138**. Rotation of pinion **138** causes vertical translational movement of the plate **136** via the rack **132**, such that the pinion **138** is located at a third position of the opening **133** (e.g., at an upper portion of the opening as shown in FIG. 18). The translation movement of the plate **136** applies a translational force on the arm member **120**, which moves the user interaction assembly **110** into the third state in a direction opposite to the second state.

(52) Another example is where the rack **132** can be positioned on, for example, the elongated member **139** (e.g., the opposite side of opening **133** of elongated member **137**). In this configuration, directions of travel are reversed. For example, operation of the user interaction assembly **110** (e.g., pressing downward) results in upward movement of the plate **136**. Upward travel of plate **136** is translated by interaction between the rack **132** on elongated member **139** and pinion **138** to cause the door handle **142** to rotate in an upward direction.

(53) FIGS. 8 and 9 illustrate an example approach for interlocking the pinion **138** with the spindle assembly **146**. Particularly, FIGS. 8 and 9 illustrate pinion **138** interlocked with a spindle interfacing component **146a** and positioned between the mounting rose **144** and the handle **142**. In some embodiments, pinion **138** may be located between the mounting rose **144** and the sleeve **143**, while in other embodiments, pinion **138** may be housed within sleeve **143**. FIG. 8 illustrates the system for handleless operation of the door with the housing **134** removed and a cross sectional view

of the door handle **142** and sleeve **143**, so as to illustrate the interlocking of the pinion **138** to the spindle interfacing component **146a**. The door handle **142** may be coupled to the spindle interfacing component **146a** via an interfacing or locking member **151**. FIG. **9** illustrates the system with the housing **134** and the door handle **142** removed, and another example plate **236** having a stadium shape. The upper end of opening **233** may operate as a stop. For example, as the plate **236** is pulled downward responsive to a downward force on arm member **120**, the pinion **138** may move to the upper end of opening **233**. As a result, downward travel of plate **236** may be ceased, preventing further rotation of the handle along with a stop to exerting downward force on user interaction assembly **110** (e.g., stopping downward travel of L-shaped component **114**). Similarly, the lower end of opening **233** may operate as a stop for vertical travel of the plate **236**.

(54) In the illustrative example, the door handle **142** may comprise a collar that surrounds the spindle interfacing component **146a**. The collar can include one or more notches **150** (e.g., two notches **150a** and **150b** of FIG. **16**, collectively referred to as notches **150**). The pinion **138** (or other component configured to translate the translation force to a rotational force) may include one or more recesses **148** (e.g., two recess **148a** and **148b** of FIG. **16**, collectively referred to as recess **148**) shaped to receive the notches **150**, thereby physically coupling the pinion **138** to the spindle interfacing component **146a**. The collar with notches **150** may be included as a part of the door handle assembly **140** (e.g., part of spindle interfacing component **146a**) or may be an additional component that can be added to the door handle assembly **140**.

(55) In some implementations of door handle assembly **140**, the spindle interfacing component **146a** may be affixed to the collar and the notches may be configured to engage with the handle **142** via locking member **151**, such that a rotational force may applied to the spindle interfacing component **146a** via the notches **150** and operates the internal components to disengage the latch. Various embodiments of the door handle operating assembly **130** disclosed herein take advantage of the existing components of the door handle assembly **140** to operate the latch. For example, the pinion **138** is shaped, as described above, to engage with the existing notch **150** (e.g., as provided as an original, unaltered component of door handle assembly **140**). In some embodiments, this may be achieved by removing (e.g., grinding, cutting, etc.) at least a portion of the sleeve **143** that engages with the notches to provide space for the pinion **138**. In another example, the sleeve **143** need not be cut and may be pulled back from the notches **150** to permit the pinion **138** to be installed therein. In various embodiments, the recesses **148** may extend to less than the full extent of the notches, thereby leaving a portion of the notch to engage with the lever and permit use of the lever as well as the door handle operating assembly **130** as described herein. In another example, the pinion **138** may comprise additional notches (not shown) configured to engage with the sleeve **143** and operate in a manner substantively similar to notches **150**, that pinion **138** may include notches that are used in place of notches **150**. The notches on pinion **138** may be positioned over recess **148** such that the orientation of the lever is unchanged or may be positioned elsewhere about the spindle interfacing component **146a**.

(56) While notches and recesses are described herein for coupling the second component to the push-lock assembly **135** to the door handle assembly **140**, other methods may be equally applicable. For example, the second component may be affixed to the door handle assembly **140** by an adhesive, threaded assembly, screws, fasteners, etc. Furthermore, various components disclosed herein are described as coupled or physically coupled to each other. Physical coupling may be done using any means known in the art, for example, screws, nails, adhesive, rivets, dowels, etc. Slidable movement may be achieved, for example at the upper end of foot pedal assemble **110** by selecting materials to provide sliding interfaces, lubrication, spacing, etc.

(57) Further, while the notches **150** are describe as formed into the spindle interfacing component **146a**, embodiment disclosed here are not intended to be limited to such a configuration. For example, notches **150** may be formed into the spindle **146b** so to interlock the pinion **138** directly to the spindle **146b**. Other implementations are possible as long as the pinion **138** is physically

coupled to the spindle **146b**, either directly or indirectly, such that rotation of pinion **138** cause as corresponding rotation on the spindle **146a** in the same rotational direction.

(58) The components disclosed herein may be made of any material as desired by the particular application. For example, one or more of the parts may be made of metal (e.g., zinc, brass, steel, aluminum, etc.), plastic, carbon fiber, etc. Any material may be used to form the parts, such that operation of the user interaction assembly **110** is translated to the door handle assemble **140** so as to operate the latch. For example, the arm member **120**, L-Shaped component **114**, and/or anchor component **112** may be made of metal (e.g., brass, aluminum or the like) or plastic materials. In the case of metal, the arm member **120** may be powder coated to avoid damage to the door. According to various embodiments, the anchor component **112**, arm member **120**, and/or plate **136** may also be made from a lubricious plastic material, such as, but not limited to, acetal resins (e.g., Delrin® produced and sold by DuPont™). According to various embodiments, the housing **134** may also be made of metal, such as die cast zinc, similar to most door handle or doorknob parts.

(59) In some embodiments, the arm member **120**, L-shaped component **114**, anchor component **112**, and/or plate **136** may be a singular, integral body. That is, these components maybe fabricated as a single unit out of, for example, plastic, die casting, 3D printing or the like. Production as a single unit may reduce manufacturing costs.

(60) FIG. **11** is a schematic drawing of a system **300** for handleless operation of a door **D** in accordance with an embodiment disclosed herein. System **300** is similar to system **100**, except that system **300** comprises a user interaction assembly **310** that is coupled to communication medium **120** for communicating a signal to operating assembly **430** for operating the door handle assembly **140**. User interaction assembly **310** is another example of a user interaction assembly configured for foot actuation to generate a signal, which can be communicated to the door handle operating assembly **430** via the communication medium **120**, as described above. For example, a user may exert a downward translation force on L-shaped component **314** of the user interaction assembly **310**, which pulls down on the arm member **120** to operate operating assembly **430** as describe above. The user interaction assembly **310** may be optionally coupled to the door via anchor component **312**.

(61) FIGS. **12A-14** provide addition details of user interaction assembly **310** according to the example implementation of FIG. **11**. FIGS. **12A** and **12B** provide schematic drawings of the user interaction assembly **310** in the unlatched state and the unlatched state, respectively. FIG. **13** is a cross-section of the user interaction assembly **310** taken along the line A-A' shown in FIG. **12A**. FIG. **14** depicts the L-shaped component **314** with the arm member **120** and anchor component removed.

(62) The user interaction assembly **310** comprises L-shaped component **314** and anchor component **312**. The L-shaped component **314** may comprise a knurled surface or otherwise textured surface on which the user's foot interacts. As another example, the L-shaped component **314** may comprise a padding covered by a fabric or leather material. In yet another example, as shown in FIGS. **12A** and **12B**, the L-shaped component **114** may have a generally flat surface without texture or fabric.

(63) The L-shaped component **114** may include a first (vertical) planar member **311** arranged to face the door and a second (horizontal) planar member **313** extending from a bottom end of the first planar member **311** outward from the door. The second planar member **313** may include a vertical protrusion **317** (also referred to as a lip structure) at an end opposite the first planar member **311** and configured to be engaged with by a user's foot to facilitate opening of the door through a pulling force applied, for example, by a toe and/or heel of the user's foot.

(64) An upper end of the planar member **311** of the L-shaped component **314** can be affixed to a lower end of arm member **120**. For example, planar member **311** may comprise holes **324a** and **324b** (as shown in FIG. **14**) for receiving fastener components **322a** and **322b** that physically couple the upper end of planar member **311** to the lower end of arm member **120**. In another example, the upper end of planar member **311** may include an opening (e.g., similar to opening **119**

of FIGS. 3A and 3B) for receiving the lower end of arm member **120**.

(65) The L-shaped component **314** is adapted to convert a force exerted by foot operation of the user interaction assembly **310** into a translational force that is applied to arm member **120**. For example, a translational force exerted parallel to the first planar member **311** exerts a similarly directed translational force on arm member **120** due to the coupling between the L-shaped component **314** and the arm member **120**. The force applied to the arm member **120** can be transferred to the door handle operating assembly **430** via arm member **120** to operate the door handle assembly **140**, for example, as described above in connection with FIGS. 3A-10.

(66) In some embodiments, the vertical protrusion **317** may optionally comprise a toothed structure at an end of the protrusion **317** opposite the second planar member **313**. An example toothed structure is shown in U.S. patent application Ser. No. 17/522,789, the disclosure of which is incorporated herein by reference in its entirety. The tooth structure may be provided to increase grip of the user's foot with the protrusion **317**. The increased grip ensures the user's foot is able to open the door without slipping off of the protrusion **317**, which would result in closing the door. Other textured surfaces may be used in place of the toothed structure, for example, a knurled surface, textured surface, textured fabric or material, or the like.

(67) The user interaction assembly **310** may be optionally coupled to the door via the anchor component **312**. The anchor component **312** may be physically coupled to the door by fastener components **320a-320d**. In a case where fastener components **320a-320d** are provided as bolts or the like, fastener components **320a-320d** may be inserted into respective holes formed in anchor component **312**. In another embodiment, along or in combination with bolts or the like, fastener components **320a-320d** may include an adhesive placed on a rear surface of anchor component **312** interfacing with the surface of the door D so to affix the anchor component **312** to the door D. The use of adhesive may permit a removably attachment that does not necessitate forming holes into the door to receive bolts, screws, nails, or the like. The anchor component **312** may include a main body component **316** and an opening **315** formed in main body component **316**. The main body component **316** includes an upper portion positioned between the L-shaped component **314** and the door handle operating assembly **430**. In one example, the opening **315** may extend completely through main body component **316** forming a hole. In another example, opening **315** may extend partially through main body component **316** forming a planar member **321** on a side of L-shaped component **314** opposite cover component **319**. Planar member **321** extend from the lower end of opening **315** toward the upper end of opening **315**. Planar member **321** may be located between first planar member **311** and the door D so to space the arm member **120** away from the door D. In this way, the planar member **321** may operate to protect the door D from damage resulting from rubbing and/or friction between arm member **120** and the surface of the door D. The depth of opening **315** may be selected such that at least the entire depth of planar member **311** (e.g., thickness of **311** in a direction perpendicular to the door) is contained within opening **315**. That is, for example, opening **315** comprises sides that surround the L-shaped component **314** in a plane parallel to the arm member **120** (e.g. generally parallel to the door). By housing the planar member **311** within opening **315**, a likelihood of pinching or snagging a user's article or body part can be reduced.

(68) The main body component **316** may also comprise a channel **306** extending from an upper surface of main body component **316** to the opening **315**. More particularly, the channel **306** may extend through the upper portion of the main body component **316**. Channel **306** is adapted to slidably receive the arm member **120**. That is, for example, a portion of arm member **120** can be located within the channel **306** and held between the main body component **316** and the door.

(69) Similar to anchor component **112** of FIGS. 1-4, anchor component **312** may comprise a lip or cover component **319** as shown in FIG. 13. That is, for example, the anchor component **312** may include a step shaped cross-sectional profile having a main body component **316** and a cover component **319** extending from an upper portion of the main body component **316** toward second

planar member **313**. Similar to the cover component **115** described above in connection with FIGS. **2A-3B**, the cover component **319** of main body component **316** may extend from the upper portion of main body component **316** toward the L-shaped component **314** and overlap with a portion of the first planar member **311** (e.g., the first planar member **311** is positioned between the door and the cover component in a direction perpendicular to the first planar member **311**) in a direction perpendicular to the face of arm member **120** opposite the door. A gap may be formed between the upper portion of main body component **316** and the upper end of the first planar member **311**, with the gap covered by the cover component **319**. This gap can be increased in distance between the upper end of the first planar member **311** and the upper portion of the main body component **316** in the unlatched state (e.g., larger gap) and decreased in the latched state (e.g., smaller gap).

(70) The main body component **316** may also comprise knurling on a surface parallel to the door, as shown in FIGS. **12A-12B**. The knurled surface may provide for improved grip between a user's foot and the user interaction assembly **310** by increasing friction therebetween. In another example, the main body component **316** may have other textured surfaces in place of the knurled surface. As another example, main body component **316** may comprise a padding covered by a fabric or leather material. In yet another example, the main body component **316** may have a generally flat surface absent added texture or fabric.

(71) A gap **318** may be formed between the main body component **316** and the second planar member **313**. As shown in FIGS. **12A** and **12B**, the gap **318** is increased in distance between the second planar member **313** and a lower end of the opening **315** in the latched state (e.g., as shown as gap **318a** in FIG. **12A**) and is decreased in the unlatched state (e.g., as shown as gap **318b** in FIG. **12A**). In some implementations, the opening **315** may define the length of travel of the L-shaped component **314**, and thus the rotational travel provided by operating assembly **430**. For example, a lower end of opening **315** may provide a stop for downward movement of the L-shaped component **314** (e.g., stopping travel of the L-shaped component **314** in the downward direction), while the upper end of opening **315** may provide a stop of upward movement. As described above, in some embodiments, door handle operating assembly **430** may also comprise a stop functionality, for example, by implementing plate **236**. The stop functionality in the door handle operating assembly **430** may be used in place of or in combination with the stop functionality of the opening **315**.

(72) In some embodiments, the L-shaped component **314** and the arm member **120** may be free floating relative to the door. For example, the arm member **120** and L-shaped component **314** may not be physically coupled directly to the door, and only held in place relative to the door due to attachment of the door handle operating assembly **430** to the door handle assembly **140**. Accordingly, anchor component **312** can be affixed to the door, as described above, and used to restrain the arm member **120** (and the coupled L-shaped component **314**) in lateral directions (e.g., horizontal directions) relative to the door, while permitting the arm member **120** (and coupled L-shaped component **314**) to move in the vertical direction (e.g., longitudinal direction) relative to the door. Accordingly, anchor component **312** may be stationary relative to the door, while L-shaped component **314** and arm member **120** are laterally stationary and longitudinally nonstationary relative to the door.

(73) While main body component **316** is shown as a rectangular body with a rectangular opening, the present disclosure is not intended to be limited to only this implementation. Other shapes are possible. For example, main body component **316** may have a circular shape, ovular shape, stadium shape, or any desired shaped. Similarly, opening **315** may have any desired shape, which need not be the same as the shape of main body component **316**.

(74) System **100** and/or **300** may be implemented as a wireless system for operating a door handle according to some embodiments. In this case, an arm member may not be present and the communication medium may be a wireless communication interface. In this case, user interaction assembly **110** and/or **310** may function as a trigger and/or button that generates a signal

communicated to door handle operating assembly **430**. Door handle operating assembly **430** may comprise actuators (such as linear motors, hydraulic actuators, pneumatic actuators, electric actuators, and the like) coupled to plate **136** that are controlled responsive to receiving signal. The actuators may generate a translational force on plate **136** that operate the door handle assembly **140** as described above in connection with FIGS. **5-10**. In another example, the user interaction assembly may comprise one or more sensors, such as motion sensors, pressure sensors, photoelectric sensors, thermal sensors, radar technology, object recognition from imaging devices such as cameras, infrared detectors, acoustic sensors, vibration sensors, etc. Sensors may be configured to detect the presence of a user foot (or another body part) and generate a signal responsive to the detection, which can be used to trigger door handle operating assembly **430**.

(75) FIGS. **15-17** are schematic graphical representations of another example door handle operating assembly **430** according to an embodiment of disclosed herein. FIG. **15** is a schematic view of the internal components of door handle operating assembly **430** with the housing removed. In this example, door handle operating assembly **430** comprises a plate **436**, which may be substantially similar to plate **236**, except as provided herein. Additionally, door handle operating assembly **130** in this example comprises a pinion **538**, which is substantially similar to pinion **238**, except that pinion **538** is integrally formed as part of spindle interfacing component **500**.

(76) As described above, plate **436** is physically coupled to arm member **120** for receiving a signal (e.g., translational force in this example) from arm member **120** and transferring the signal to the pinion **538**. Plate **436** is physically coupled to arm member **120** via protrusion **422**, which may be substantially similar to protrusion **122** described above in connection with FIGS. **6-8**. Plate **436** also comprises an opening **433** that is similar to opening **233** described in connection with FIG. **9**. Plate **436** include elongated member **437** extending vertically from a bottom portion of plate **436** and elongated member **439** and defining opening **433**. An internal rack **432** is provided along a vertical internal edge of at least one of the elongated members, such as elongated member **437** as shown in FIG. **15**.

(77) In some embodiments, opening **433** may comprise a recess **431** provided at the lower end of the opening **433**. The recess **431** may be shaped to accommodate a lock assembly, such may include lock cylinder housing a mechanism to operate a door lock and/or user interface component **149** for operating the lock (e.g., a key hole or thumb turn mechanism). In FIG. **15** an end of a lock cylinder **147** is shown, where the user interface component is removed.

(78) FIG. **16** is a perspective view of an example spindle interfacing component **500** including pinion **538**. FIG. **17** is a cross section of the door handle operating assembly **430** taken along the line B-B' showing spindle interfacing component **500** interlocked with door handle **142**. FIG. **17** shows the door handle operating assembly **430** housed within housing **434**, which is substantially similar to housing **134** described above. While not shown in FIG. **17**, the spindle and additional components internal components housed by mounting rose **144** may be located within the hole H formed in the door to accommodate such components of the door handle assembly **140**.

(79) The spindle interfacing component **500** comprises a body **502** having a generally cylindrical shape. Spindle interfacing component **500** includes opening **504** at a proximal end **506** configured to receive a spindle (e.g., spindle **146b**). The opening **504** may be shaped so to interlock with the spindle, for example, by having a square shape to receive and interlock with a square bar spindle. At a distal end **508**, a plurality of ribs **510a** alternating with recessed surfaces **510b** form a handle interfacing structure **510** configured to interlock spindle interfacing component **500** with a corresponding structure provided in the handle. For example, sleeve **143** may house a interfacing structure configured to receive the handle interfacing structure **510** and physically couple the spindle interfacing component **500** to the handle. Thus, rotation applied to one of spindle interfacing component **500** and the handle is transferred to the other component. Additionally, a through hole **512** is provided to avoid a buildup of pressure when the spindle is inserted into opening **504** and dimples **514** are provided to receive fastener devices (e.g., set screws in one

example) to secure spindle interfacing component **500** to the door handle. Spindle interfacing component **500** also comprises groove **516** and groove **518** configured to receive spring clip, such as c-clips, e-clips or the like.

(80) As shown in FIG. **16**, spindle interfacing component **500** comprises pinion **538** located at between handle interfacing structure **510** and proximal end **506**. Pinion **538** may be formed to extend in a radial direction from a central longitudinal axis of spindle interfacing component **500**, for example, from an outer surface of body **502** away from the central longitudinal axis, as shown in FIG. **16**. In some embodiments, the pinion **538** may be provided at approximately the midpoint between distal end **508** and proximal end **506**. The length of spindle interfacing component **500** may be provide to ensure that handle interfacing structure **510** fully engages with the receiving structure within the handle, and such that pinion **538** is engaged with internal rack **432**.

(81) As shown in the example of FIG. **17**, the lock cylinder **147** may be received by user interface component **149**, which the user may interact with to operate lock cylinder **147**. In some embodiments, lock cylinder **147** may be offset in a vertical direction to accommodate the pinion **538**. While in some embodiments, the user interface component **149** is unmodified relative to the door handle assembly **140**. For example, a central axis of lock cylinder **147** may be aligned with a central axis of user interface component **149**. Whereas, in the offset example, the central axes may be parallel by spaced part in the vertical direction to provide clearance for pinion **538**.

(82) While FIGS. **11-14** are described with reference to user interaction assembly **310** operating on arm member **120** to communicate a signal to door handle operating assembly **430**, handle operating assembly **130** may be implemented with user interaction assembly **310**. That is, user interaction assembly **310** may be operated to apply a vertical movement that is transferred to handle operating assembly **130**, which operates the door handle assembly **140** as described above.

(83) FIG. **18** is a functional block diagram of a wireless computing system **600** (also referred to herein as a processing system) that can be implemented with the systems disclosed herein, for example, the wireless system described above. The computing system **600** may be included and/or communicably coupled to the user interaction assembly (and/or sensors) and/or the door handle assembly according to the embodiments disclosed herein. In some embodiments, both assemblies may be coupled to the same or a different computing system **600**.

(84) The system **600** can include one or more processor units (processor) **602**. The processor **602** can control operation of the system **600**. The processor **602** can also be referred to as a central processing unit (CPU). The processor **602** can include multiple processors or microprocessors as needed. Processor **602** can perform all the functions required to allow the systems to perform according to programmable instructions and user interaction, for example, automated operation of the door. The processor **602** can include or be a component of a processing system implemented with one or more processors **602**. The one or more processors can be implemented with any combination of general-purpose microprocessors, microcontrollers, digital signal processors (DSPs), field programmable gate array (FPGAs), programmable logic devices (PLDs), controllers, state machines, gated logic, discrete hardware components, dedicated hardware finite state machines, or any other suitable entities that can perform calculations or other manipulations of information.

(85) The system **600** can also have a memory **604** coupled to the processor **602**. The memory **604** can include both read-only memory (ROM) and random access memory (RAM). The memory **604** can provide instructions and data to the processor **602**. At least a portion of the memory **604** can also include non-volatile random access memory (NVRAM). The processor **602** can perform logical and arithmetic operations based on program instructions stored within the memory **604**. In some implementations, the memory **604** can store multiple programs, for example, operation of the door based on received signals.

(86) The processing system and the memory **604** can also include machine-readable media for storing software. Software shall be construed broadly to mean any type of instructions, whether

referred to as software, firmware, middleware, microcode, hardware description language, or otherwise. Instructions can include code (e.g., in source code format, binary code format, executable code format, or any other suitable format of code). The instructions, when executed by the one or more processors, cause the processing system to perform the various functions described herein.

(87) The system **600** can have a plurality of actuators **606** coupled to the system **600** that can control the door handle operating assembly **608**. The actuators **606** can be communicatively coupled to the processor **602**. The processor **602** can execute instructions contained in the memory **604** to command movement of one or more of the plurality of actuators **606** to operate the door. The actuators **606** can be mechanical, electrical, electro-mechanical, pneumatic, hydraulic, etc. to accomplish movement of the various assemblies.

(88) The system **600** can also include a transmitter **610** and/or a receiver **612** to allow transmission and reception of data between the components of system **600** (e.g., between the user interaction assembly and the handle assembly) and/or and a remote location. The transmitter **610** and the receiver **612** can be combined into a transceiver **610**. Transmitter **610** and/or receiver **612** may be included at the user interaction assembly and the door handle operating assembly. The system **600** can also include (not shown) multiple transmitters, multiple receivers, multiple transceivers, and/or multiple antennas as needed for various communication standards via wireless or wireline communications. The system **600** can further have a modem **616** coupled to the transmitter **610**, the receiver **612**, or the transceiver **614**. The modem **616** can perform modulation and demodulation tasks for communication with an external network, for example. In some implementations the processor **602** can communicate via the transmitter **610**, the receiver **612**, and/or the transceiver **614** via the Internet. In some embodiments, the transmitter **610** and the receiver **612** can be configured to transmit and receive information via other wired or wireline systems or means.

(89) The system **600** can have a user interface **622**. The user interface **622** can include one or more controls allowing user interaction by the user. For example, user interface **622** can include one or more of the foot pedal, door handle, input devices, speakers, and/or microphones to provide means for interaction with the system. A user can interact with the user interface **622** to operate the door.

(90) The system **600** can further include one or more sensors **624** for detecting the presence of a user. For example, the sensor **624** can include one or more of motion sensors, pressure sensors, photoelectric sensors, thermal sensors, radar technology, object recognition from imaging devices such as cameras, infrared detectors, acoustic sensors, vibration sensors, etc. Sensor(s) **624** may be configured to detect the presence of a foot within the proximity of the sensor(s) **624**.

(91) The system **600** can further have a power supply **620**. The power supply **620** can provide power to the system either via power backbone (e.g., AC power) or via battery.

(92) The various components of the system **600** can be coupled together by a bus system **626**. The bus system **626** can include a data bus, for example, as well as a power bus, a control signal bus, and a status signal bus in addition to the data bus. The components of the system **600** can be coupled together or accept or provide inputs to each other using some other mechanism. Bus system **626** may consist of multiple bus systems, for example, one for the user interaction assembly and one for the door handle operating assembly. In this case, for example, operating assembly **608** may include at least actuators **606**, receiver **612**, a first processor **602**, and a first memory **604** coupled together on a first bus system, and a user interaction assembly may include at least sensor(s) **624**, transmitter **610**, a second processor **602**, and a second memory **604** coupled together on a second bus system.

(93) The components of the system **600** can be enclosed by a housing **609**. The housing **609** can be the housing **134**, the mounting rose **144**, main body component **116**, and/or main body component **316**. For example, housing **609** may represent housing **134** in the case of a door handle operating assembly, which may house at least at least actuators **606**, receiver **612**, and the push-lock assembly **135**. Additionally, processor **602**, memory **604**, modem **616**, power supply **620**, user interface **622**,

and transmitter **610** may be housed in housing **609** implemented as housing **134**. In another example, housing **609** may represent main body component **116** and/or main body component **316**, in which case housing **609** may house at least transmitter **610** and at least one of sensor(s) **624** and an L-shaped component (e.g., L-shaped component **114** or L-shaped component **314**). Additionally, processor **602**, memory **604**, modem **616**, power supply **620**, user interface **622**, and receiver **612** may be housed in housing **609** implemented as main body component **116** and/or main body component **316**.

(94) Although a number of separate components are illustrated in FIG. **18**, one or more of the components can be combined or commonly implemented.

(95) The hardware used to implement the various illustrative logics, logical blocks, and modules described in connection with the various embodiments disclosed herein may be implemented or performed with a general purpose processor, a digital signal processor (DSP), an application specific integrated circuit (ASIC), a field programmable gate array (FPGA) or other programmable logic device, discrete gate or transistor logic, discrete hardware components, or any combination thereof designed to perform the functions described herein. A general-purpose processor may be a microprocessor, but, in the alternative, the processor may be any conventional processor, controller, microcontroller, or state machine. A processor may also be implemented as a combination of receiver devices, e.g., a combination of a DSP and a microprocessor, a plurality of microprocessors, one or more microprocessors in conjunction with a DSP core, or any other such configuration. Alternatively, some operations or methods may be performed by circuitry that is specific to a given function.

(96) In one or more exemplary embodiments, the functions described may be implemented in hardware, software, firmware, or any combination thereof. If implemented in software, the functions may be stored as one or more instructions or code on a non-transitory computer-readable storage medium or non-transitory processor-readable storage medium. The operations of a method or algorithm disclosed herein may be embodied in processor-executable instructions that may reside on a non-transitory computer-readable or processor-readable storage medium. Non-transitory computer-readable or processor-readable storage media may be any storage media that may be accessed by a computer or a processor. By way of example but not limitation, such non-transitory computer-readable or processor-readable storage media may include random access memory (RAM), read-only memory (ROM), electrically erasable programmable read-only memory (EEPROM), FLASH memory, CD-ROM or other optical disk storage, magnetic disk storage or other magnetic storage devices, or any other medium that may be used to store desired program codes in the form of instructions or data structures and that may be accessed by a computer. Disk and disc, as used herein, includes compact disc (CD), laser disc, optical disc, digital versatile disc (DVD), floppy disk, and Blu-ray disc where disks usually reproduce data magnetically, while discs reproduce data optically with lasers. Combinations of the above are also included within the scope of non-transitory computer-readable and processor-readable media. Additionally, the operations of a method or algorithm may reside as one or any combination or set of codes and/or instructions on a non-transitory processor-readable storage medium and/or computer-readable storage medium, which may be incorporated into a computer program product.

(97) Thus, the claims are not intended to be limited to the aspects shown herein, but are to be accorded the full scope consistent with the language claims, wherein reference to an element in the singular is not intended to mean “one and only one” unless specifically so stated, but rather “one or more.”

(98) The word “exemplary” is used herein to mean “serving as an example, instance, or illustration.” Any aspect described herein as “exemplary” is not necessarily to be construed as preferred or advantageous over other aspects. Unless specifically stated otherwise, the term “some” refers to one or more.

(99) All structural and functional equivalents to the elements of the various aspects described

throughout this disclosure that are known or later come to be known to those of ordinary skill in the art are expressly incorporated herein by reference and are intended to be encompassed by the claims. Moreover, nothing disclosed herein is intended to be dedicated to the public regardless of whether such disclosure is explicitly recited in the claims. The words “module,” “mechanism,” “element,” “device,” and the like may not be a substitute for the word “means.” As such, no claim element is to be construed as a means plus function unless the element is expressly recited using the phrase “means for.”

(100) It should be understood that the various features, aspects and functionality described in one or more of the individual embodiments are not limited in their applicability to the particular embodiment with which they are described. Instead, they can be applied, alone or in various combinations, to one or more other embodiments, whether or not such embodiments are described and whether or not such features are presented as being a part of a described embodiment. Thus, the breadth and scope of the present disclosure should not be limited by any of the above-described exemplary embodiments.

(101) Terms and phrases used in this document, and variations thereof, unless otherwise expressly stated, should be construed as open ended as opposed to limiting. As examples of the foregoing, the term “including” should be read as meaning “including, without limitation” or the like. The term “example” is used to provide exemplary instances of the item in discussion, not an exhaustive or limiting list thereof. The terms “a” or “an” should be read as meaning “at least one,” “one or more” or the like; and adjectives such as “conventional,” “traditional,” “normal,” “standard,” and “known,” and terms of similar meaning should not be construed as limiting the item described to a given time period or to an item available as of a given time, but instead should be read to encompass conventional, traditional, normal, or standard technologies that may be available or known now or at any time in the future. Terms of similar meaning should not be construed as limiting the item described to a given time period or to an item available as of a given time. Instead, they should be read to encompass conventional, traditional, normal, or standard technologies that may be available or known now or at any time in the future. Where this document refers to technologies that would be apparent or known to one of ordinary skill in the art, such technologies encompass those apparent or known to the skilled artisan now or at any time in the future.

(102) The presence of broadening words and phrases such as “one or more,” “at least,” “but not limited to” or other like phrases in some instances shall not be read to mean that the narrower case is intended or required in instances where such broadening phrases may be absent. The use of the term “component” does not imply that the aspects or functionality described or claimed as part of the component are all configured in a common package. Indeed, any or all of the various aspects of a component, whether control logic or other components, can be combined in a single package or separately maintained and can further be distributed in multiple groupings or packages or across multiple locations.

(103) Although the present disclosure provides certain example embodiments and applications, other embodiments that are apparent to those of ordinary skill in the art, including embodiments which do not provide all of the features and advantages set forth herein, are also within the scope of this disclosure. Accordingly, the scope of the present disclosure is intended to be defined only by reference to the appended claims.

Claims

1. A system for hands free operation of a door, the system comprising: a pinion configured to attach to a spindle of a door handle external to a mounting rose of the door handle; an arm member having an upper end and a lower end; a foot pedal connected to the lower end of the arm member; and a plate connected to the upper end of the arm member, the plate having: a first elongated member and

a second elongated member; an upper plate portion connected between the first and second elongated members, wherein the first and second elongated members extend in a direction from the upper end of the arm member to the upper plate portion; an opening formed by the first and second elongated members and the upper plate portion, the opening configured to receive the pinion, wherein the first and second elongated members provide first and second sides of the opening; and a rack formed on the first side of the opening of the plate and configured to engage with the pinion; and a stop on an upper end of the opening formed by the upper plate portion, wherein operation of the foot pedal in a downward direction away from the plate causes a downward translational movement of the plate toward the foot pedal via the arm member, and the rack and pinion translate the downward translational movement applied to the plate to a rotational movement that rotates the spindle and operates the door handle, and wherein the stop is configured to halt the downward translational movement applied to the plate when the pinion contacts the stop.

2. The system of claim 1, wherein the foot pedal comprises an L-shaped component, the L-shaped component comprising a first planar member, and a second planar member extending from a lower end of the first planar member approximately perpendicular to the first planar member.

3. The system of claim 2, wherein the foot pedal further comprises a protrusion extending from an end of the second planar member opposite the first planar member, wherein the protrusion is configured to engage with a foot of a user to facilitate applying a pulling or pushing force to the L-shaped component by a foot of a user.

4. The system of claim 3, wherein the protrusion comprises a toothed surface configured to provide grip between the protrusion and the foot of a user.

5. The system of claim 2, further comprising a communication medium, wherein the downward translational movement of the plate is communicated to the plate via the communication medium.

6. The system of claim 5, wherein the communication medium is an arm member having lower end coupled to the foot pedal and an upper end coupled to the plate.

7. The system of claim 6, wherein the foot pedal further comprises an anchor component configured to attach to a door, at least a portion of the anchor component is positioned between the L-shaped component and the plate, the at least a portion of the anchor component comprising a channel configured to slidably receive the arm member.

8. The system of claim 7, wherein the anchor component comprises a body configured to surround the L-shaped component on a plane parallel to the door, wherein the anchor component comprises an opening configured to house the L-shaped component.

9. The system of claim 7, wherein the anchor component comprises a cover member extending from the at least a portion of the anchor component toward the second planar member of the L-shaped component, wherein the cover member is configured to cover a gap between the at least a portion of the anchor component and the first planar member of the L-shaped component.

10. The system of claim 1, wherein the opening is one of a stadium opening, a circular opening, an ovular opening, and a rounded rectangular opening.

11. An apparatus for operating a door handle assembly for hands free operation of a door, the apparatus comprising: a bracket comprising: a first planar member, and a second planar member extending approximately perpendicular from the first planar member; an arm member extending from a first end connected to the first planar member to a second end in a first direction approximately parallel to the first planar member; and a push-lock mechanism at the second end of the arm member, the push-lock mechanism comprising: a pinion configured to attach to the door handle assembly at a position external to a mounting rose of the door handle assembly, and a plate coupled to the second end of the arm member, the plate having an ovular-shaped opening configured to receive the pinion, the ovular-shaped opening comprising an ovular cylinder surface that surrounds the pinion and a rack formed a first portion of the ovular cylinder surface extending in the first direction, and the rack is configured to engage with the pinion, wherein a force in the first direction away from the push-lock mechanism applied to the bracket exerts translational

movement to the plate via the arm member in the first direction towards the bracket, and the rack and pinion translate the translational movement on the plate to a rotational movement that rotates a handle of the door handle assembly and operates the door handle, and wherein the ovular-shaped opening comprises a stop at a second portion of the ovular cylinder surface extending in a second direction that is perpendicular to the first direction and parallel to the first planar member, the stop is configured to halt the translational movement of the plate when the pinion contacts the second portion of the ovular cylinder surface as a result of the translational movement on the plate in the first direction.

12. The apparatus of claim 11, wherein the bracket further comprises a protrusion extending from an end of the second planar member opposite the first planar member, wherein the protrusion is configured to engage with a foot of a user to facilitate applying a pulling or pushing force to the bracket by a foot of a user.

13. The apparatus of claim 12, wherein the protrusion comprises a toothed surface configured to provide grip between the protrusion and the foot of a user.

14. The apparatus of claim 11, further comprising an anchor component configured to attach to the door, at least a portion of the anchor component is positioned between the bracket and the push-lock mechanism, the at least a portion of the anchor component comprising a channel configured to slidably receive the arm member.

15. The apparatus of claim 14, wherein the anchor component comprises a body configured to surround the bracket on a plane parallel to the door, wherein the anchor component comprises an opening configured to house the bracket.

16. The apparatus of claim 15, wherein the anchor component comprises a cover member extending from the at least a portion of the anchor component toward the second planar member of the bracket, wherein the cover member is configured to cover a gap between the at least a portion of the anchor component and the first planar member of the bracket.

17. The apparatus of claim 11, wherein the ovular-shaped opening is a stadium-shaped opening.
