

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent

12407799

Kind Code

B2

Date of Patent

September 02, 2025

Inventor(s)

Wang; Yujie et al.

Projection apparatus

Abstract

A projection apparatus including: a light source component; a light polarization component for converting light from the light source component into first polarized light in a first polarization direction; a display panel on a side, away from the light source component, of the light polarization component for adjusting the polarization direction of the first polarized light to emit second polarized light in a polarization direction between the first polarization direction and a second polarization direction, the first polarization direction is perpendicular to the second polarization direction; a light reflective component on a side, away from the light polarization component, of the display panel for reflecting one of the polarized light in the first polarization direction and the polarized light in the second polarization direction; a projection lens, a light incident surface of which faces the light reflective component so as to receive light reflected by the light reflective component.

Inventors: Wang; Yujie (Beijing, CN), Cai; Site (Beijing, CN), Wang; Guangquan (Beijing, CN), Zhang; Wei (Beijing, CN), Li; Xi (Beijing, CN), Wang; Jingang (Beijing, CN), Liu; Xiaolong (Beijing, CN), Ji; Chengwei (Beijing, CN)

Applicant: Beijing BOE Display Technology Co., Ltd. (Beijing, CN); BOE TECHNOLOGY GROUP CO., LTD. (Beijing, CN)

Family ID: 87764354

Assignee: Beijing BOE Display Technology Co., Ltd. (Beijing, CN); BOE TECHNOLOGY GROUP CO., LTD. (Beijing, CN)

Appl. No.: 17/921392

Filed (or PCT Filed): February 28, 2022

PCT No.: PCT/CN2022/078195

PCT Pub. No.: WO2023/159545

Prior Publication Data

Document Identifier	Publication Date
US 20240388680 A1	Nov. 21, 2024

Publication Classification

Int. Cl.: H04N9/31 (20060101)

U.S. Cl.:

CPC H04N9/3167 (20130101); H04N9/317 (20130101);

Field of Classification Search

CPC: G03B (21/005); G03B (21/006); G03B (21/008); G03B (21/16); G03B (21/28); G03B (21/145); G03B (21/208); G03B (21/2033); G03B (21/2053); G03B (21/2073); H04N (9/315); H04N (9/317); H04N (9/3105); H04N (9/3108); H04N (9/3141); H04N (9/3144); H04N (9/3167)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6466375	12/2001	Kanaya	N/A	N/A
7237899	12/2006	Ma et al.	N/A	N/A
9122140	12/2014	Ouderkirk	N/A	N/A
9625801	12/2016	Baba	N/A	G03B 21/008
10809603	12/2019	Xu	N/A	N/A
10955666	12/2020	Ouderkirk et al.	N/A	N/A
10969672	12/2020	Maeda	N/A	H04N 9/3105
11493677	12/2021	Haag et al.	N/A	N/A
11561443	12/2022	Hu	N/A	N/A
2014/0160364	12/2013	Katou	349/5	G03B 21/2073
2018/0203338	12/2017	Kawamura et al.	N/A	N/A
2019/0049833	12/2018	Maeda	N/A	G03B 21/008
2019/0394429	12/2018	Tanaka	N/A	H04N 13/334

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
1274093	12/1999	CN	N/A
1792098	12/2005	CN	N/A
201285471	12/2008	CN	N/A
101846860	12/2009	CN	N/A
202281894	12/2011	CN	N/A
103460089	12/2012	CN	N/A
107709873	12/2017	CN	N/A

109164667	12/2018	CN	N/A
109407421	12/2018	CN	N/A
209356835	12/2018	CN	N/A
111650807	12/2019	CN	N/A
212540990	12/2020	CN	N/A
112782916	12/2020	CN	N/A
113009758	12/2020	CN	N/A
113419398	12/2020	CN	N/A
214228367	12/2020	CN	N/A
113608291	12/2020	CN	N/A
215117143	12/2020	CN	N/A
216670485	12/2021	CN	N/A
H 07319066	12/1994	JP	N/A

Primary Examiner: Chowdhury; Sultan

Attorney, Agent or Firm: HOUTTEMAN LAW LLC

Background/Summary

TECHNICAL FIELD

(1) The present disclosure relates to the field of display technology, and in particular to a projection apparatus.

BACKGROUND

(2) A projection apparatus is a display device which magnifies and images tiny image information on a screen through a lens, and is widely applied to daily life of people, such as teaching, business, media advertisement, home entertainment and the like.

SUMMARY

(3) The present disclosure provides a projection apparatus, including: a light source component; a light polarization component located on a light exiting side of the light source component and configured to convert light emitted from the light source component into first polarized light polarized in a first polarization direction; a display panel located on a side, away from the light source component, of the light polarization component and configured to adjust a polarization direction in which the first polarized light is polarized so as to emit second polarized light; a polarization direction in which the second polarized light is polarized is between the first polarization direction and a second polarization direction, and the first polarization direction is perpendicular to the second polarization direction; a light reflective component located on a side, away from the light polarization component, of the display panel and configured to reflect one of polarized light polarized in the first polarization direction and polarized light polarized in the second polarization direction; and a projection lens, a light incident surface of which faces the light reflective component so as to receive light reflected by the light reflective component.

(4) In some implementations, the light source component includes a light source, a second reflective layer, and a second lens; the second lens is arranged between the light source and the light polarization component and is configured to collimate light directly irradiated to the second lens by the light source, and the second lens includes a Fresnel lens; the second reflective layer is located between the light source and the second lens and is arranged surrounding an optical axis of the second lens to form a cylindrical structure having a first opening facing the light source and a second opening facing the second lens, and an area of the first opening is smaller than that of the

second opening; where, the light polarization component includes: a transreflective component configured to transmit the polarized light polarized in the first polarization direction and reflect at least a part of the polarized light polarized in the second polarization direction.

(5) In some implementations, the light source includes: a lamp panel; a light emitting device located on the lamp panel and located on a side, close to the display panel, of the lamp panel; and a light collector located between the light source and the second lens and configured to converge light emitted by the light emitting device.

(6) In some implementations, the light source further includes a first reflective layer located on the lamp panel, the light emitting device and the first reflective layer are located on a same side of lamp panel, and at least part of an orthographic projection of the first reflective layer on the lamp panel is not overlapped with an orthographic projection of the light emitting device on the lamp panel.

(7) In some implementations, the light collector includes a plano-convex lens, a flat surface of the plano-convex lens faces the light emitting device, and a ratio of a distance from the light emitting device to the plane of the plano-convex lens to a distance from the plane of the plano-convex lens to the second lens ranges from 1:30 to 1:50.

(8) In some implementations, a shape of a light exiting surface of the light emitting device is the same as a shape of a display surface of the display panel.

(9) In some implementations, the light exiting surface of the light emitting device and the display surface of the display panel are both rectangular, a direction in which a long side of the light exiting surface extends is the same as a direction in which a long side of the display surface extends, and a direction in which a short side of the light exiting surface extends is the same as a direction in which a short side of the display surface extends; a ratio of a length of the light exiting surface to a length of the display surface is 1:a, a ratio of a width of the light exiting surface to a width of the display surface is 1:b, a and b are both larger than 0, and a:b ranges from 0.8:1 to 1.2:1.

(10) In some implementations, a distance from the second lens to the light emitting device is a first distance, and a focal length of the second lens is equal to the first distance; or, the focal length of the second lens is xmm, and x is an integer closest to a value of the first distance and is divisible by 5.

(11) In some implementations, a divergence angle of light from the light source and a distance from the light source to the second lens satisfy: assuming that the light emitted from the light source is irradiated to a plane where the second lens is located without being obstructed, and a range where the light emitted from the light source is irradiated on the plane where the second lens is located completely covers the second lens.

(12) In some implementations, the divergence angle of light from the light source and the distance from the light source to the second lens satisfy: assuming that the light emitted from the light source is irradiated to the plane where the second lens is coated without being obstructed, a ratio of an area of the second lens to an area of a light spot formed on the plane where the second lens is located ranges from 0.65:1 to 0.75:1.

(13) In some implementations, the transreflective component includes an Advanced Polarizer Film (APF).

(14) In some implementations, the light polarization component further includes a transparent base, the transreflective component is located on a side of the transparent base away from the display panel, and a gap exists between the transparent base and the display panel.

(15) In some implementations, the light reflective component includes a polarizer and a reflective mirror, the polarizer is located between the display panel and the reflective mirror and is configured to transmit one of the polarized light polarized in the first polarization direction and the polarized light polarized in the second polarization direction.

(16) In some implementations, the light reflective component includes a plurality of optical film layers integrated together, refractive indexes of any two adjacent optical film layers are different so

as to form an optical interface therebetween, each optical interface corresponds to a wave band, and different optical interfaces correspond to different wave bands, each optical interface is configured to transmit the polarized light with a wavelength within a corresponding wave band and polarized in the first polarization direction, and reflect the polarized light with a wavelength within a corresponding wave band and polarized in the second polarization direction, or each optical interface is configured to transmit the polarized light with a wavelength within a corresponding wave band and polarized in the second polarization direction, and reflect the polarized light with a wavelength within a corresponding wave band and polarized in the first polarization direction.

(17) In some implementations, the light reflective component is configured to transmit the polarized light polarized in the first polarization direction and reflect the polarized light polarized in the second polarization direction.

(18) In some implementations, the light polarization component further includes a transparent base, the projection apparatus further includes: a first antireflective layer, where the transreflective component and the first antireflective layer are respectively arranged on two surfaces of the transparent base opposite to each other; and a second antireflective layer arranged on a surface of the display panel facing the light polarization component.

(19) In some implementations, the projection apparatus further includes a first lens; the light reflective component includes a polarizer and a reflective mirror, the polarizer is located between the display panel and the reflective mirror, the first lens is located between the polarizer and the reflective mirror and is configured to converge light exited from the polarizer and transmit the converged light to the reflective mirror; or, the light reflective component includes a plurality of optical film layers integrated together, the first lens is located between the display panel and the light reflective component, and is configured to converge light emitted from the display panel and transmit the converged light to the reflective mirror.

(20) In some implementations, the first lens is a Fresnel lens.

(21) In some implementations, a fourth antireflective layer is provided on a surface of the first lens facing the light reflective component.

(22) In some implementations, a third antireflective layer is provided on a surface of the second lens facing the light source.

(23) In some implementations, a focal length F of the projection lens, an image distance $l_{\text{sub.2'}}$ of the projection lens, and an optical path distance $l_{\text{sub.2}}$ from an intermediate plane to the projection lens satisfy the following formula (1):

(24) $\frac{1}{l_2} = \frac{1}{F} + \frac{1}{l_2}$ (1) a distance $l_{\text{sub.1}}$ from the first lens to the display panel, a distance from the intermediate surface M1 to the first lens, a focal length f of the first lens satisfy the following formula (2):

(25) $\frac{1}{l_1} = \frac{1}{f} + \frac{1}{l_1}$ (2) the distance $l_{\text{sub.1}}$ from the first lens to the display panel, the optical path distance $l_{\text{sub.2}}$ from the intermediate plane to the projection lens, and an optical path distance $f_{\text{sub.1'}}$ from the first lens to the projection lens satisfy the following formula (3):

(26) $l_1 = f_1' - \frac{1}{l_2}$.Math. $f_1'^2$ (3) where the intermediate plane is a virtual image surface formed by imaging the display panel by the first lens, and the intermediate plane and the display panel are located on a same side of the first lens.

(27) In some implementations, the display panel includes an array substrate, an opposite substrate and a liquid crystal layer located between the array substrate and the opposite substrate; the array substrate includes a first base substrate, a plurality of gate lines and a plurality of data lines which are arranged on the first base substrate, where the gate lines and the data lines are intersected with each other to define a plurality of pixel regions; the opposite substrate includes a second base substrate, and a color filter layer and a black matrix arranged on the second base substrate, the color filter layer includes a plurality of light-filtering portions in correspondence with the pixel

regions one to one, the black matrix includes a plurality of light blocking bars, orthographic projections of the light blocking bars on the first base substrate cover orthographic projections of the gate lines on the first base substrate, a gap exists between any two adjacent light blocking bars, and the gap exposes a part of each data line.

(28) In some implementations, the display panel includes a plurality of pixel units arranged in an array, each of the pixel units including a red pixel region, a green pixel region, and a blue pixel region, and the green pixel region has an area larger than each of areas of the red pixel region and the blue pixel region.

(29) In some implementations, the area of the green pixel region is 1.05 to 1.1 times the area of the blue pixel region, and the area of the red pixel region is 0.9 to 0.95 times the area of the blue pixel region.

(30) In some implementations, the display panel is in a shape of rectangle and has a first edge and a second edge adjacent to each other, and the first edge extends in a height direction of the projection apparatus; the light reflective component includes a light incident surface extending along the height direction of the projection apparatus, and the second edge is intersected with the light incident surface of the light reflective component.

(31) In some implementations, the height direction of the projection apparatus is perpendicular to a plane in which an optical axis of an optical system, constituted by the light source component, the light polarization component, the display panel, the light reflective component, and the projection lens, is located.

(32) In some implementations, the projection apparatus further includes a housing and a first fan, and the light polarization component, the display panel, the light reflective component, and at least a portion of the light source component are disposed within the housing; the projection apparatus further includes a heat dissipating portion which is configured to dissipate heat inside the housing, the first fan includes a first air outlet and a first air inlet, the first air outlet and the first air inlet are located outside the housing, and one of the first air outlet and the first air inlet is arranged facing the heat dissipating portion.

(33) In some implementations, the heat dissipating portion and the housing form a closed space.

(34) In some implementations, the projection apparatus further includes: a second fan including a second air outlet located in the housing, a heat dissipation air duct communicated with the second air outlet is formed in the housing, and the heat dissipation air duct is adjacent to the heat dissipating portion, so that heat in the housing passes by a surface of the heat dissipating portion facing interior of the housing, along with airflow blown out of the second air outlet, to be dissipated out of the housing; where the heat dissipation air duct includes a first channel, a first gap exists between the display panel and the light reflective component, the first gap is the first channel of the heat dissipation air duct, and/or, the heat dissipation air duct includes a second channel, a second gap exists between the display panel and the light source component, and the second gap is the second channel of the heat dissipation air duct.

(35) In some implementations, the projection apparatus includes a light polarization component and a first lens, there is a first gap between the first lens and the display panel, and there is a second gap between the display panel and the light polarization component.

(36) In some implementations, an area of a ventilation cross section of the first channel is 1 to 1.2 times an area of the second air outlet of the second fan; there is no gap between the second lens and the light polarization component, or a third gap exists between the second lens and the light polarization component, and a width of the third gap is smaller than that of the first gap.

(37) In some implementations, the heat dissipation air duct includes a first channel and a second channel; the heat dissipation air duct further includes a third channel connecting the first channel with the second channel.

(38) In some implementations, the housing further includes a curved portion corresponding to the third channel, an inner wall of the curved portion is a curved surface, and the curved surface is

protruded in a direction away from the first channel and the second channel, so that the airflow of the first channel enters the second channel along the curved surface.

(39) In some implementations, there are a fourth channel and a fifth channel within the housing, the fourth channel is configured to communicate the second air outlet with the first channel; the fifth channel is communicated with the second channel; and the fifth channel is arranged adjacent to the heat dissipating portion and is configured to cool the air in the fifth channel through the heat dissipation portion.

(40) In some implementations, the second fan further includes a second air inlet located in the housing, and the second air outlet, the fourth channel, the first channel, the third channel, the second channel, the fifth channel, and the second air inlet are sequentially connected to form a closed air loop.

(41) In some implementations, the second fan and the heat dissipating portion are both located on a side of at least a portion of the light reflective component away from the projection lens; one of side surfaces of the second fan is arranged in parallel with at least part of the light reflective component; the at least part of the light reflective component is a part or all of the light reflective component which reflect light into the projection lens; the fourth channel and the fifth channel share at least part of wall and are located on two sides of the at least part of wall.

(42) In some implementations, a material of the heat dissipating portion includes a metal.

(43) In some implementations, at least part of a surface of the heat dissipating portion facing the interior of the housing is a wall of the fifth channel.

(44) In some implementations, a contour of a portion of the heat dissipating portion adjacent to the fifth channel includes a curved surface; the heat dissipating portion further includes a plurality of first heat dissipation fins extending into the fifth channel, and a direction in which the first heat dissipation fin extending into the fifth channel extends is the same as a direction in which the fifth channel extends.

(45) In some implementations, the heat dissipating portion includes a plurality of second heat dissipation fins arranged in sequence between the first fan and the fifth channel; the first air outlet of the first fan is arranged facing the heat dissipating portion, an upwind surface is formed at a side, close to the first fan, of the second heat dissipation fins, and the upwind surface and an air outlet surface of the first fan have a same contour; or the first air inlet of the first fan is arranged facing the heat dissipating portion, a leeward surface is formed at a side, close to the first fan, of the second heat dissipation fins, and the leeward surface and an air inlet surface of the first fan have a same contour.

(46) In some implementations, the projection apparatus further includes: a light source heat dissipator connected with the light source component and configured to dissipate heat of the light source component; one of the first air inlet and the first air outlet of the first fan is arranged facing the heat dissipating portion, and the other one of the first air inlet and the first air outlet of the first fan is arranged facing the light source heat dissipator.

(47) In some implementations, the light source component includes a light source including a lamp panel and a light emitting element arranged on the lamp panel, the light source heat dissipator includes a heat sink component and a heat conduction connecting element, where the heat sink component is connected with the lamp panel through the heat conduction connecting element.

Description

DRAWINGS

(1) The drawings are intended to provide a further understanding of the present disclosure, constitute a part of the description, and are used to explain the present disclosure together with the following specific embodiments, but do not constitute a limitation of the present disclosure.

(2) FIG. 1 is a schematic diagram of a projection apparatus provided in some embodiments of the present disclosure.

(3) FIG. 2 is a schematic diagram of a film structure of a light reflective component provided in some embodiments of the present disclosure.

(4) FIG. 3 is a schematic diagram of a film structure of a light reflective component provided in some embodiments of the present disclosure.

(5) FIG. 4 is a schematic diagram of a projection apparatus provided in some embodiments of the present disclosure.

(6) FIG. 5 is an optical path diagram of an illumination module provided in some embodiments of the present disclosure.

(7) FIG. 6A is a schematic diagram illustrating antireflection of light by an antireflective layer.

(8) FIG. 6B is a waveform diagram of the reflected light in FIG. 6A.

(9) FIG. 7 is a schematic diagram illustrating a distribution of pixel regions of a display panel provided in some embodiments of the present disclosure.

(10) FIG. 8 is a plan view of a black matrix provided in some embodiments of the present disclosure.

(11) FIG. 9 is a schematic diagram illustrating a stack of some elements in a projection apparatus provided in some embodiments of the present disclosure.

(12) FIG. 10 is an overall structural top view of a projection apparatus provided in some embodiments of the present disclosure.

(13) FIG. 11 is an overall structural perspective view of a projection apparatus provided in some embodiments of the present disclosure.

(14) FIG. 12 is a schematic diagram illustrating a position relationship between a display panel and a light reflective component.

DETAILED DESCRIPTION

(15) The specific embodiments of the present disclosure will be described in detail below in combination with the accompanying drawings. It should be understood that the specific embodiments described herein are only for the purpose of explaining and interpreting the present disclosure and are not intended to limit the present disclosure.

(16) To make the objects, technical solutions and advantages of the embodiments of the present disclosure more apparent, the technical solutions of the embodiments of the present disclosure will be clearly and completely described below with reference to the drawings of the embodiments of the present disclosure. It is to be understood that the described embodiments are only a few embodiments of the present disclosure, and not all embodiments. All other embodiments, which can be derived by a person skilled in the art from the described embodiments of the present disclosure without creative effort, fall within the protection scope of the present disclosure.

(17) The terminology used herein to describe embodiments of the present disclosure is not intended to limit and/or define the scope of the present disclosure. For example, unless otherwise defined, technical or scientific terms used herein shall have the ordinary meaning as understood by one of ordinary skill in the art to which the present disclosure belongs. It should be understood that the terms “first,” “second,” and the like, as used in this disclosure, do not denote any order, quantity, or importance, but rather are used to distinguish one element from another. The singular forms “a,” “an,” or “the” and similar referents do not denote a limitation of quantity, but rather denote the presence of at least one, unless the context clearly dictates otherwise. The word

“comprise/comprising” or “include/including”, and the like, means that the element or item appearing in front of the word “comprising” or “comprises” includes the element or item listed after the word “comprise/comprising” or “include/including” and its equivalents, and does not exclude other elements or items. The terms “connected” or “coupled” and the like are not restricted to physical or mechanical connections, but may include electrical connections, whether direct or indirect. The words “upper/on”, “lower/under”, “left”, “right”, and the like are used merely to

indicate relative positional relationships, which may change accordingly when the absolute position of the object being described changes.

(18) FIG. 1 is a schematic diagram of a projection apparatus provided in some implementations of the present disclosure, as shown in FIG. 1, the projection apparatus includes a light source component 10, a light polarization component 20, a display panel 30, a light reflective component 40, and a projection lens 50.

(19) The light polarization component 20 is disposed at a light exiting side of the light source component 10, and is configured to convert light emitted by the light source component 10 into first polarized light polarized in a first polarization direction. The light emitted by the light source component 10 may be natural light.

(20) In the present disclosure, the natural light refers to light that does not exhibit any polarization characteristic. Specifically, the natural light emitted by the light source component 10 may be white light.

(21) The display panel 30 is disposed on a side of the light polarization component 20 away from the light source component 10, and is configured to adjust a polarization direction in which the first polarized light is polarized so as to emit a second polarized light. A polarization direction in which the second polarized light is polarized is between the first polarization direction and a second polarization direction, and the first polarization direction is perpendicular to the second polarization direction. It should be noted that the display panel 30 may include a plurality of pixel regions, and each pixel region may adjust the polarization direction in which the first polarized light is polarized, so as to obtain the second polarized light polarized in the polarization direction between the first polarization direction and the second polarization direction. It should be noted that “between the first polarization direction and the second polarization direction” includes two critical directions, i.e., the first polarization direction and the second polarization direction. That is, the polarization direction in which the second polarized light is polarized may be the first polarization direction, may be the second polarization direction, or may be a direction between the first polarization direction and the second polarization direction and intersecting both the first polarization direction and the second polarization direction.

(22) The display panel 30 may be a liquid crystal display panel, and specifically includes an array substrate and an opposite substrate which are oppositely arranged, and a liquid crystal layer located between the array substrate and the opposite substrate. In an example, the array substrate includes: a first base substrate, a plurality of gate lines and a plurality of data lines, where the gate lines and the data lines are arranged on the first base substrate, the gate lines are intersected with the data lines so as to define a plurality of pixel regions, and each pixel region is provided with a pixel electrode. The opposite substrate includes a second base substrate and a common electrode arranged on the second base substrate. A pixel voltage is applied to the pixel electrode and a common voltage is applied to the common electrode, so that an electric field is generated between the pixel electrode and the common electrode to drive liquid crystals in the pixel region to deflect, so as to adjust the polarization direction in which the first polarized light is polarized.

(23) Note that, the polarization direction, in which the second polarized light emitted from any pixel region is polarized, is not necessarily fixed, for example, when the projection apparatus projects different images, the second polarized light may have different polarization directions. It should be noted that, in the embodiments of the present disclosure, the liquid crystal display panel is not limited to a specific type, and for example, the liquid crystal display panel may be a Vertical Alignment (VA) type display panel or a Twisted Nematic (TN) type display panel, in such cases, the common electrode is disposed on the second base substrate. Certainly, the liquid crystal display panel may also be an In Plane Switching (IPS) display panel, a Fringe Field Switching (FFS) display panel, or an Advanced Super Dimension Switching (ADS) display panel, and in such cases, the common electrode is provided on the first base substrate, so long as the electric field is generated between the pixel electrode and the common electrode to drive the liquid crystals to

deflect.

(24) The light reflective component **40** is disposed on a side of the display panel **30** away from the light polarization component **20**, and is configured to reflect one of the polarized light polarized in the first polarization direction and the polarized light polarized in the second polarization direction.

(25) A light incident surface of the projection lens **50** faces the light reflective component **40** to receive the light reflected by the light reflective component **40** and transmit the received light to a surface of a target object (e.g., a projection screen) to implement projection display.

(26) The principle of projection display of the projection apparatus shown in FIG. **1** will be described below by taking an example in which the light reflective component **40** is configured to reflect the polarized light polarized in the second polarization direction.

(27) After passing through the light polarization component **20**, the light emitted by the light source component **10** becomes the first polarized light polarized in the first polarization direction, and the first polarized light irradiates to the display panel **30**. In a case where a white image is desired to be displayed, the voltage applied to each pixel region in the display panel **30** may be controlled, so that the liquid crystals in each pixel region adjust the polarization direction in which the first polarized light is polarized to generate the polarized light polarized in the second polarization direction, and the polarized light polarized in the second polarization direction is irradiated to the light reflective component **40** and reflected to the projection lens **50** by the light reflective component **40**, so as to display the white image. In a case where a black image is desired to be displayed, the voltage applied to each pixel region in the display panel **30** may be controlled, so that the liquid crystals in each pixel region still transmit the polarized light polarized in the first polarization direction without changing the polarization direction in which the first polarized light is polarized, and the polarized light polarized in the first polarization direction is transmitted through the light reflective component **40**, and in this case, no light is irradiated to the projection lens **50**, thereby displaying the black image. In a case where a gray-scale image (i.e., an image with a brightness lower than that of the white image and higher than that of the black image) is desired to be displayed, the voltage applied to each pixel region in the display panel **30** may be controlled, so that the liquid crystals in each pixel region adjust the polarization direction in which the first polarized light is polarized to generate polarized light polarized in a third polarization direction, and the polarized light polarized in the third polarization direction is irradiated to the light reflective component **40**. The third polarization direction intersects both the first polarization direction and the second polarization direction, and the polarized light polarized in the third polarization direction may be decomposed into a first component polarized in the first polarization direction and a second component polarized in the second polarization direction. The second component is reflected to the projection lens **50** by the light reflective component **40**, thereby displaying a gray-scale image.

(28) Similarly, when the light reflective component **40** is configured to reflect the polarized light polarized in the first polarization direction, in a case where a white image is desired to be displayed, the voltage applied to each pixel region in the display panel **30** is controlled, so that the liquid crystals in each pixel region do not change the polarization direction in which the first polarized light is polarized, and the polarized light polarized in the first polarization direction is still transmitted, and is irradiated to the light reflective component **40** and reflected to the projection lens **50** by the reflective component **40**, thereby displaying the white image. In a case where a black image is desired to be displayed, the voltage applied to each pixel region in the display panel **30** is controlled so that the liquid crystals in each pixel region adjust the polarization direction in which the first polarized light is polarized to generate polarized light polarized in the second polarization direction, and in this case, no light is irradiated to the projection lens **50**, thereby displaying the black image. In a case where a gray-scale image is desired to be displayed, the voltage applied to each pixel region in the display panel **30** is controlled, so that the liquid crystals in each pixel region adjust the polarization direction in which the first polarized light is

polarized to generate polarized light polarized in a third polarization direction, the polarized light polarized in the third polarization direction may be decomposed into a first component polarized in the first polarization direction and a second component polarized in the second polarization direction, and the first component is reflected to the projection lens 50 by the light reflective component 40, thereby displaying the gray-scale image.

(29) In the embodiments of the present disclosure, the light reflective component 40 may be designed to reflect the polarized light polarized in the second polarization direction in the light emitted from the display panel 30, or reflect the polarized light polarized in the first polarization direction in the light emitted from the display panel 30, so as to reflect the light with different brightnesses to the projection lens 50, thereby displaying images with different brightnesses. It will be appreciated that whether the light reflective component 40 is designed to reflect the polarized light polarized in the first polarization direction or the polarized light polarized in the second polarization direction depends on the particular type of the display panel. For example, when the display panel is of an ADS, IPS, VA, or TN (in normally white) type, the light reflective component may be designed to reflect the polarized light polarized in the second polarization direction; when the display panel is of a TN (in normally black) type, the light reflective component may be designed to reflect the first polarized light polarized in the first polarization direction.

(30) It will be appreciated that the light reflective component 40 is configured to change the direction in which the light propagates, which can advantageously reduce the volume of the projection apparatus.

(31) FIG. 2 is a schematic diagram of a film structure of a light reflective component provided in some embodiments of the present disclosure, and as shown in FIG. 2, in some implementations, the light reflective component 40 may include: a polarizer 43 and a reflective mirror 44, the polarizer 43 is located between the display panel 30 and the reflective mirror 44. The polarizer 43 is configured to transmit one of the polarized light polarized in the first polarization direction and the polarized light polarized in the second polarization direction, and may absorb the other of the polarized light polarized in the first polarization direction and the polarized light polarized in the second polarization direction. The polarizer 43 may be attached on a surface of the display panel 30.

(32) The projection apparatus may further include a housing, and the above-mentioned structures such as the light polarization component 20, the display panel 30, and the light reflective component 40 may be disposed in the housing, thus a compact structure is formed in the housing, which easily causes heat accumulation in the housing. Moreover, when the polarizer 43 is attached to the display panel 30, the polarizer 43 may absorb light to generate relatively high heat, which may cause adverse effects on the display panel 30, and therefore, in order to ensure normal operation of the display panel, a gap may be formed on at least one side of the display panel 30, so as to facilitate the heat dissipation of the display panel 30.

(33) In other embodiments, the light reflective component 40 may be configured to reflect one of the polarized light polarized in the first polarization direction and the polarized light polarized in the second polarization direction and transmit the other of the polarized light polarized in the first polarization direction and the polarized light polarized in the second polarization direction. Similarly, whether the light reflective component 40 is designed to reflect the polarized light polarized in the first polarization direction or the polarized light polarized in the second polarization direction depends on the specific type of display panel. FIG. 3 is a schematic diagram of a film structure of a light reflective component provided in other embodiments of the present disclosure, and as shown in FIG. 3, in other embodiments, the light reflective component 40 may include a plurality of optical film layers 42, which are integrated together, disposed on a side of a base substrate 41 (e.g., a glass substrate) facing the display panel 30 and inclined to the display panel 30. Refractive indexes of any two adjacent optical film layers 42 are different, so that an optical interface is formed therebetween. Each optical interface corresponds to one wave band,

different optical interfaces correspond to different wave bands, and each optical interface is configured to transmit the polarized light with a wavelength within a corresponding wave band and polarized in the first polarization direction, and to reflect the polarized light with a wavelength within a corresponding wave band and polarized in the second polarization direction. The number of the optical film layers **42** may be three, four, five, or more. For example, there are three optical interfaces between the plurality of optical film layers **42**, where a first optical interface is configured to transmit light in a red light band and polarized in the first polarization direction, and reflect light in the red light band and polarized in the second polarization direction; a second optical interface is configured to transmit light in a green light band and polarized in the first polarization direction and reflect light in the green light band and polarized in the second polarization direction; a third optical interface is configured to transmit light in a blue light band and polarized in the first polarization direction and reflect light in the blue light band and polarized in the second polarization direction.

(34) The interfaces between the plurality of optical film layers **42** allow the polarized light polarized in the first polarization direction in the natural light to pass therethrough and reflect the polarized light polarized in the second polarization direction in the natural light. Certainly, the refractive indexes of the optical film layers **42** may also be adjusted such that each optical interface in the light reflective component **40** can transmit the polarized light with a wavelength within a corresponding wave band and polarized in the second polarization direction, and reflect the polarized light with a wavelength within a corresponding wave band and polarized in the first polarization direction.

(35) The light reflective component **40** transmits the light that is not to be reflected to the projection lens **50**, which can reduce heat accumulation, thereby facilitating heat dissipation of the projection optical system and further facilitating improvement of display performance of the display panel **30**. Moreover, it can be seen from the above projection display principle that if the light reflective component **40** is configured to transmit the polarized light polarized in the second polarization direction and reflect the polarized light polarized in the first polarization direction, then when displaying a white image, the liquid crystal layer does not need to change the polarization direction in which the first polarized light is polarized; and when displaying a black image, the liquid crystals are to be turned over to make the polarization direction, in which the first polarized light is polarized, rotate by 90° , however, in actual driving process, a phenomenon where the liquid crystals cannot be sufficiently turned over easily occurs, thereby leading to light leak to a certain extent when displaying the black image, and then reducing the contrast. Thus, in an example of the present disclosure, the light reflective component **40** is configured to transmit the polarized light polarized in the first polarization direction and reflect the polarized light polarized in the second polarization direction. That is, each optical interface is configured to transmit the polarized light with a wavelength within the corresponding wave band and polarized in the first polarization direction and to reflect the polarized light with a wavelength within a corresponding wave band and polarized in the second polarization direction. In this case, the liquid crystals do not need to be turned over when displaying the black image, thereby avoiding the decrease in contrast as described above.

(36) FIG. **4** is a schematic diagram of a projection apparatus provided in other embodiments of the present disclosure, and as shown in FIG. **4**, the projection apparatus includes a light source component **10**, a polarization component **20**, a display panel **30**, a light reflective component **40**, and a projection lens **50**. In addition, the projection apparatus may further include a first lens **60**, where, when the light reflective component **40** includes a polarizer **43** and a reflective mirror **44**, the first lens **60** is disposed between the polarizer **43** and the reflective mirror **44**, and is configured to converge light exited from the polarizer **43** and irradiate the converged light to the reflective mirror **44**. When the light reflective component **40** includes a plurality of optical film layers **42** integrated together, the first lens **60** is disposed on a side of the display panel **30** away from the

light source component **10**, and is configured to converge the light exited from the display panel **30**, and the converged light is reflected into the projection lens **50** by the light reflective component **40** and then is irradiated and projected for imaging.

(37) In some implementations, the light source component **10** is a collimated light source component for emitting collimated light, such that the light source component **10** can irradiate more light to the light polarization component **20**, and thus the display panel **30** receives more polarized light polarized in the first polarization direction.

(38) It should be noted that “collimated light” in the embodiments of the present disclosure means that light having a divergence angle less than or equal to 20° . It should be noted that the divergence angle in the embodiments of the present disclosure is twice an included angle between a direction of the light, in the emitted light, farthest from a central axis of the emitted light and the central axis.

(39) In some implementations, the light source component **10** may include a light source **11** and a second lens **16**. In some implementations, the light source **11** may specifically include a lamp panel **11a**, a light emitting device **11b** and a light collector **12** arranged on the lamp panel **11a**, where the light emitting device **11b** is located on a side of the lamp panel **11a** close to the display panel **30**. The light emitting device **11b** may be an LED lamp.

(40) The light collector **12** is located on a light exiting side of the light emitting device **11b** and is configured to converge light emitted from the light emitting device **11b**, so as to reduce the divergence angle of the light. In addition, in a case where the light emitting device **11b** is an LED lamp, intensity of the light emitted from the light emitting device **11b** may be non-uniformly distributed, for example, the intensity of the light close to an axis of the light emitting device **11b** is relatively great, and the intensity of the light further away from the axis of the light emitting device **11b** is significantly reduced, but the intensity of the light emitted from the light source **11** may be more uniform in an overall by means of the light collector **12**. The light collector **12** may be a convex lens, and a surface of the convex lens facing the light source and a surface of the convex lens facing away from the light emitting device **11b** may both be convex surfaces, or the surface of the convex lens facing the light emitting device **11b** is a plane, and the surface of the convex lens facing away from the light emitting device **11b** is a convex surface. In particular, the light collector **12** may be a plano-convex lens.

(41) The second lens **16** is disposed between the light source **11** and the light polarization component **20**, and is configured to collimate the light directly irradiated to the second lens **16** from the light source **11**. Note that, the light directly irradiated to the second lens **16** from the light source **11** refer to the light emitted from the light source **11** and irradiated to the second lens **16** without being reflected by other elements. In a case where the light source **11** includes the light emitting device **11b** and the light collector **12**, the light directly irradiated to the second lens **16** from the light source **11** is the light directly irradiated to the second lens **16** from the light collector **12**.

(42) Both the first lens **60** and the second lens **16** may be Fresnel lenses. The Fresnel lens can prevent a relatively large spherical aberration and aberration from occurring at the edge of the lens, and the imaging quality is improved. Since the second lens **16** is configured to collimate the divergent light emitted from the light source, and the first lens **60** is configured to converge the light emitted from the display panel **30**, when both the first lens **60** and the second lens **16** may be the Fresnel lenses, sawtooth surfaces of the Fresnel lenses face the display panel **30**, so that a circular ring or a dark spot may appear on the displayed image.

(43) It is understood that the light collector **12** is configured to converge the light emitted from the light emitting device **11b**, but the light collector **12** may not be provided when the light emitting device **11b** emits the light with a desired exiting angle. That is, the light emitted from the light emitting device **11b** may be directly irradiated to the second lens **16**.

(44) In some implementations, the light collector **12** includes a plano-convex lens, a flat surface of the plano-convex lens faces the light emitting device **11b**, and a ratio of a distance from the light

emitting device **11b** to the plane of the plano-convex lens to a distance from the plane of the plano-convex lens to the second lens **16** ranges from 1:30 to 1:50, so that the light efficiency is improved. For example, the ratio of the distance from the light emitting device **11b** to the plane of the plano-convex lens to the distance from the plane of the plano-convex lens to the second lens **16** is 1:30, 1:35, 1:40, 1:45, or 1:50. In some implementations, the ratio of the distance from the light emitting device **11b** to the plane of the plano-convex lens to the distance from the plane of the plano-convex lens to the second lens **16** is 1:40. As can be seen from simulation tests, when the distance from the light emitting device **11b** to the plane of the plano-convex lens ranges from 2 mm to 3 mm and the distance from the plane of the plano-convex lens to the second lens **16** ranges from 80 mm to 120 mm, the light efficiency of the projection apparatus can be improved to the greatest extent. Also, the distance from the light emitting device **11b** to the plane of the plano-convex lens can prevent heat of the light emitting device **11b** from damaging the plano-convex lens.

(45) It should be noted that, the light exiting surface of the light emitting device **11b** is parallel to the plane of the plano-convex lens, and the distance from the light emitting device **11b** to the plane of the plano-convex lens is a distance from the light exiting surface of the light emitting device **11b** to the plane of the plano-convex lens. In a case where the second lens **16** is the Fresnel lens, the plane of the plano-convex lens is parallel to a plane where the second lens **16** is located, and the distance from the plane of the plano-convex lens to the second lens **16** is a distance from the plane of the plano-convex lens to the plane where the second lens **16** is located.

(46) In some implementations, the light exiting surface of the light emitting device **11b** has the same shape as that of a display surface of the display panel **30**, thereby improving light efficiency. The shape here refers to a type of shape, for example, the shape of the light exiting surface and the shape of the display surface of the display panel **30** are both rectangular; or both are elliptical; or both are circular; or both are hexagonal, etc.

(47) In some implementations, the light exiting surface of the light emitting device **11b** and the display surface of the display panel **30** are both rectangular, and a length direction of the light exiting surface is the same as a length direction of the display surface, and a width direction of the light exiting surface is the same as that of a width direction of the display surface, that is, a long side of the light exiting surface is parallel to a long side of the display surface, and a short side of the light exiting surface is parallel to a short side of the display surface. Certainly, the light exiting surface of the light emitting device **11b** and the display surface of the display panel **30** may be both square, and in this case, four sides of the light exiting surface are parallel to four sides of the display surface, respectively.

(48) A ratio of a length of the light exiting surface to a length of the display surface is 1:a, a ratio of a width of the light exiting surface to a width of the display surface is 1:b, a and b are both larger than 0, and a:b ranges from 0.8:1 to 1.2:1, so that occurrence of dark spots in the displayed image can be reduced or avoided. In some implementations, a is equal to b, thereby the occurrence of dark spots is reduced to the most extent and the display effect is improved. In an example, a dimension of the light exiting surface of the light source is equal to 10 mm×10 mm, or 16 mm×11 mm.

(49) In some implementations, the light source component **10** may further include a second reflective layer **15**, the second reflective layer **15** is located between the light collector **12** and the first lens **60**, and is disposed surrounding an optical axis of the second lens **16**, thereby forming a cylindrical structure having a first opening facing the light collector **12** and a second opening facing the second lens **16**, and the first opening has an area smaller than that of the second opening. By means of the second reflective layer **15**, at least a part of light irradiated to the second reflective layer **15** from the light source **11** can be reflected to the second lens **16**, so that the rate that the light is utilized is improved, and the brightness of the displayed image is improved.

(50) In some implementations, the divergence angle of the light source **11** and the distance from the light source **11** to the second lens **16** satisfy a first condition that: assuming that the light emitted from the light source **11** can be irradiated to a plane where the second lens **16** is located without

being obstructed, a region that the light emitted from the light source **11** irradiates on the plane where the second lens **16** is located completely covers the second lens **16**. Note that the phrase “the light emitted from the light source **11** being irradiated to the plane where the second lens **16** is located without being obstructed” means that the light emitted from the light source **11** is irradiated to the plane where the second lens **16** is located without being reflected by another element. Therefore, it can be ensured that any position of the second lens **16** can receive the light emitted from the light source **11**, and dark edge or dark corner can be prevented from occurring at the edge or corner of the projected image. In above implementations (i.e., in a case where the divergence angle of the light source **11** and the distance from the light source **11** to the second lens **16** satisfy the first condition), the specific structure of the light source **11** may include: the lamp panel **11a**, the light emitting device **11b** and the light collector **12**, and the lamp panel **11a** may be provided with a first reflective layer **14** thereon. The first reflective layer **14** and the light emitting device **11b** are located on a same side of the lamp panel **11a**, and at least a portion of the first reflective layer **14** is located outside an area where the light emitting device **11b** is located. The provision of the first reflective layer **14** is advantageous for improving the projection brightness, as will be explained in detail below.

(51) In some implementations, assuming that the light emitted from the light source **11** can be irradiated to the plane where the second lens **16** is located without being obstructed, a light spot is formed on the plane where the second lens **16** is located, and an area of the second lens **16** accounts for 60% to 80% of an area of the light spot. In particular, when too much light is directly irradiated on the second lens **16**, it may cause unevenness in brightness at a center and edges of the displayed image; when too little light is directly irradiated on the second lens **16**, since the second reflective layer **15** is provided, more light is reflected to the second lens **16** by the second reflective layer **15**, and a part of the light passing through the second lens **16** would not become collimated, so that in the case where too little light is directly irradiated on the second lens **16**, more non-collimated light is generated, thereby greatly affecting the display effect. In some implementations, when the light emitted from the light source **11** is irradiated to the plane where the second lens **16** is located without being obstructed, the light spot is formed on the plane where the second lens **16** is located, and the area of the second lens **16** accounts for 65% to 75% of the area of the light spot.

(52) It should be noted that, when the second lens **16** is the Fresnel lens, the area of the second lens **16** may be regarded as the area of the plane of the Fresnel lens.

(53) In an example, the distance from the second lens **16** to the light emitting device **11b** ranges from 70 mm to 80 mm, for example, may be 70 mm, 73 mm, 75 mm, 77 mm or 80 mm. The distance from the second lens **16** to the light emitting device **11b** refers to the distance from the light exiting surface of the light emitting device **11b** to the plane where the second lens **16** is located.

(54) In some implementations, the distance from the second lens **16** to the light emitting device **11b** is a first distance, and a focal length of the second lens **16** is equal to the first distance, so as to improve the collimation effect, and thus improve the light efficiency of the projection apparatus. In an example, the first distance and the focal length of the second lens **16** are both 73 mm.

(55) In some implementations, the focal length of the second lens **16** is xmm, and for cost reasons, x may be set to be equal to an integer nearest the first distance and divisible by 5.

(56) In some implementations, as shown in FIG. 4, the light polarization component **20** includes a transfective component **21**, the transfective component **21** is configured to transmit at least the polarized light polarized in the first polarization direction and to reflect at least a part of the polarized light polarized in other polarization directions. In an example of the present disclosure, the transfective component **21** may include an Advanced Polarizer Film (APF).

(57) In some implementations, the light polarization component **20** may further include a transparent base **22**, and there is a gap between the transparent base **22** and the display panel **30** for air to flow. The transfective component **21** is disposed on a side of the transparent base **22** away

from the display panel **30**, such that the light emitted from the light source **10** passes through the transfective component **21** firstly and then is irradiated to the light polarization component **20**, thereby improving the effect of the light polarization component **20** modulating the light. Specifically, the transfective component **21** may be secured to a surface of the transparent base **22** by means of an adhesive. The transparent base **22** may be a glass substrate.

(58) When the light emitted by light source component **10** passes through the light polarization component **20**, the light vibrating in the first polarization direction passes through the transfective component **21**, and at least part of the light vibrating in other directions is reflected by the transfective component **21**, thus the heat accumulation on the light polarization component **20** can be reduced to prevent the heat from causing influence on the display panel **30**.

(59) In addition, in the case where the projection apparatus includes the transfective component **21**, the second lens **16**, and the second reflective layer **15**, and the second lens **16** is the Fresnel lens, the light emitted from the light source component **10** passes through the second lens **16** to generate collimated light, and the collimated light is irradiated to the transfective component **21**. A part of the light irradiated to the transfective component **21** completely transmits through the transfective component **21**, another part of the light (including the light polarized in a polarization direction perpendicular to the polarization direction in which the part of the light transmitting through the transfective component **21** is polarized) is reflected by the transfective component **21** to the second lens **16**, and the second lens **16** has a depolarization effect on the light (the Fresnel lens has a depolarization effect on the light due to following reasons: the Fresnel lens is formed by pressure injection, and has non-uniform internal stress, which easily causes non-uniform refractive indexes inside the Fresnel lens, thereby causing multiple refractions of light inside the Fresnel lens, so that the polarized light polarized in a single polarization direction is converted into light polarized in respective polarization directions). A part of the light subjected to the depolarization is reflected by the second reflective layer **15** and then is emitted after being transmitted through the second lens **16**, which can improve the rate that the light is utilized and thus improve the projection brightness.

(60) In some implementations, as shown in FIG. 4, the lamp panel **11a** may be provided with a first reflective layer **14** thereon, the first reflective layer **14** and the light emitting device **11b** are located on a same side of the lamp panel **11a**, and at least a portion of the first reflective layer **14** is located outside the area where the light emitting device **11b** is located.

(61) In a case where the projection apparatus includes the transfective component **21**, the second lens **16** and the first reflective layer **14**, and the second lens **16** is the Fresnel lens, light emitted from the light source component **10** passes through the second lens **16** to generate collimated light, and the collimated light is irradiated to the transfective component **21**. A part of the light irradiated to the transfective component **21** is completely transmitted through the transfective component **21**, and another part of the light (including the light polarized in a polarization direction perpendicular to the polarization direction in which the part of the light transmitting through the transfective component **21** is polarized) is reflected by the transfective component **21** to the second lens **16**. The second lens **16** is to depolarize the light, so that the polarized light, polarized in a single polarization direction and reflected to the second lens **16**, becomes light having components polarized in respective polarization directions. A part of the light subjected to the depolarization is irradiated to the first reflective layer **14**, is reflected to the second lens **16** by the first reflective layer **14**, and is transmitted through the second lens **16** to be emitted, so that the rate that the light is utilized can be improved, and the projection brightness is further improved.

(62) FIG. 5 is an optical path diagram of an illumination module provided in some embodiments of the present disclosure, where the illumination module includes a light source component **10** and a light polarization component **20**. The light source component **10** includes a light source **11** and a second reflective layer **15**. The light source **11** includes a lamp panel **11a**, a light emitting device **11b** and a light collector **12**, and the lamp panel **11a** is provided with a first reflective layer **14**

thereon. The light polarization component **20** includes a transreflective component **21**. As shown in FIG. 5, the light emitted from the light emitting device **11b** is irradiated to the light collector **12**, the light collector **12** converges the light (for example, converges the light with a divergence angle of 160° into the light with a divergence angle of less than 60°), the converged light is irradiated to the second lens **16**, the second lens **16** collimates the light, and the collimated light is irradiated to the light polarization component **20**. A part of the light irradiated to the light polarization component **20** is completely transmitted through the polarizer component **20**, as shown by the solid arrows in FIG. 5; and another part of the light irradiated to the light polarization component **20** is reflected by the light polarization component **20** to the second lens **16**, as shown by the dotted arrows in FIG. 5. In a case where the second lens **16** is the Fresnel lens, it has a depolarization effect on light, so that the polarized light, which is polarized in a single polarization direction and is reflected to the second lens **16**, becomes light having components polarized in respective polarization directions. A first part of the light subjected to the depolarization is exited from the second lens **16** after being reflected multiply by the second reflective layer **15**; a second part of the light subjected to the depolarization is reflected to the second lens **16** by the first reflective layer **14**, and is exited from the second lens **16**. It can be seen that the provision of the first reflective layer **14** and the second reflective layer **15** can improve the light efficiency of the illumination module. It is verified that the projection brightness of the projection apparatus provided with the first reflective layer **14** and the second reflective layer **15** in FIG. 4 can be raised by 4.5%, compared with the projection apparatus not provided with first reflective layer **14** and the second reflective layer **15** (and other structures of the projection apparatus are the same as those in FIG. 4). Compared with the projection apparatus in which the first reflective layer **14** and the second reflective layer **15** are not provided and the light polarization component **20** has no reflection function (and other structures of the projection apparatus are the same as those in FIG. 4), the projection brightness of the projection apparatus provided with the first reflective layer **14**, the second reflective layer **15** and the transreflective component **21** in FIG. 4 can be raised by 21.36%.

(63) In addition, it is verified that the projection brightness of the projection apparatus provided with the light collector **12** shown in FIG. 4 can be raised by 30%, compared with the projection apparatus not provided with the light collector **12** (other structures of the projection apparatus are the same as those in FIG. 4). The reason is that: the light emitted from the light emitting device **11b** has a relatively large divergence angle, and in the case where the light collector **12** is not provided, most of the light is irradiated to the second reflective layer **15**, and a part of the light reflected by the second reflective layer **15** may not be collimated by the second lens **16**, resulting in low projection brightness. By providing the light collector **12**, by converging through the light collector **12**, little light emitted by the light source **11** is irradiated to the second reflective layer **15**, so that more collimated light is exited from the second lens **16**, thereby improving the projection brightness of the projection apparatus. It can be understood that the combination of the light emitting device **11b** and the light collector **12** may also be replaced by a light source with a relatively small divergence angle, for example, when the light emitted from the light source **11** is irradiated to a plane where the second lens **16** is located without being obstructed, the amount of light directly irradiated on the second lens **16** accounts for 60% to 80% of the total amount of light emitted from the light source **11**. In some implementations, when the light emitted from the light source **11** is irradiated to the plane where the second lens **16** is located without being obstructed, the amount of light directly irradiated on the second lens **16** accounts for 65% to 75% of the amount of light emitted from the light source **11**. In some implementations, the light emitting device **11b** emits light uniformly at different angles.

(64) In some implementations, as shown in FIG. 4, the transreflective component **21** is disposed on a surface of the transparent base **22**, and the transparent base **22** may serve as a support for the transreflective component **21**. The transparent base **22** may be a glass base. In view of the fact that the transparent base **22** has a certain reflection effect on light, especially when the transparent base

22 is the glass base, the reflection effect is more obvious than that of a base made of an organic material, and therefore, in the projection apparatus according to the embodiments of the present disclosure, a plurality of antireflective layers are provided, the antireflective layers include a first antireflective layer 71 disposed on a surface of the transparent base 22 away from the light polarization component 20, so that more light can be irradiated to the display panel 30, thereby improving the projection brightness of the projection apparatus. In addition, the antireflective layers may be formed by a coating method, and the transparent base 22 can prevent the high temperature during coating from damaging the film structure of the transmissive component 21.

(65) FIG. 6A is a schematic diagram illustrating antireflection of light by the antireflective layer, as shown in FIG. 6A, the antireflective layer includes a first sub-film layer 70a and a second sub-film layer 70b, when the light is irradiated to the antireflective layer, the light is refracted and reflected on a surface of the first sub-film layer 70a away from the second sub-film layer 70b, and the reflected light is denoted by R1 in FIG. 6A. The refracted light is reflected and refracted at an interface between the first sub-film layer 70a and the second sub-film layer 70b, and the reflected light is denoted by R2 in FIG. 6A. FIG. 6B is a waveform diagram of the reflected light in FIG. 6A, as shown in FIG. 6A and FIG. 6B, the antireflective layer is a film layer utilizing light's equal thickness interference principle, and a thickness of the first sub-film layer 70a is set such that destructive interference occurs between the reflected light R1 and R2, so as to reduce the overall light reflection capability of the antireflective layer and increase the light transmittance of the antireflective layer.

(66) In some implementations, the display panel 30 is a liquid crystal display panel, and a base substrate of the display panel 30 close to the light source component 10 may include a glass substrate to ensure structural stability of the display panel 30. In order to alleviate or prevent the light from being reflected on the surface of the display panel 30 facing the light source component 10, as shown in FIG. 4, the antireflective layers further include a second antireflective layer 72 disposed on a surface of the display panel 30 close to the light polarization component 20, and the second antireflective layer can alleviate the reflection of the light on the surface of the display panel 30, so that more light is incident into the display panel 30.

(67) In some implementations, as shown in FIG. 4, the antireflective layers further include a third antireflective layer 73 and a fourth antireflective layer 74, and the third antireflective layer 73 is disposed on a surface of the second lens 16 facing the light collector 12 to allow more light to transmit through the second lens 16 and irradiate to the light polarization component 20. The fourth antireflection coating 74 is disposed on a surface of the first lens 60 facing the light reflective component 40 to allow more light to transmit through the first lens 60 and irradiate to the reflector component 40.

(68) It should be noted that the projection apparatus may be provided with the first antireflective layer 71 to the fourth antireflective layer 74 simultaneously, or may be provided with part of the first antireflective layer 71 to the fourth antireflective layer 74, for example, only the first antireflective layer 71 and the second antireflective layer 72 may be provided. In some implementations, the first antireflective layer 71 to the fourth antireflective layer 74 are provided in the projection apparatus simultaneously, so that light is irradiated to the projection lens 50 as much as possible when a white image is displayed, thereby improving the light efficiency of the projection apparatus. Tests show that, the light efficiency of the projection apparatus, simultaneously provided with the first antireflective layer 71 to the fourth antireflective layer 74, is raised by 8.2%, compared with the light efficiency of the projection apparatus in which no antireflective layer is provided.

(69) In the embodiments of the present disclosure, as described above, the display panel 30 may be a liquid crystal display panel, and include the array substrate 31, the opposite substrate 32 and the liquid crystal layer between the array substrate 31 and the opposite substrate 32, as shown in FIG. 4, and the opposite substrate 32 may be located at a side of the array substrate 31 close to the light

source component **10**. The array substrate **31** includes a first base substrate, a plurality of gate lines and a plurality of data lines arranged on the first base substrate, and the plurality of gate lines intersect with the plurality of data lines to define a plurality of pixel regions. The opposite substrate **32** includes a color filter layer including a plurality of light-filtering portions, in addition to the second base substrate and the common electrode, and the light-filtering portions are disposed in correspondence with the pixel regions one to one. The plurality of pixel regions may include a plurality of red pixel regions, a plurality of green pixel regions, and a plurality of blue pixel regions, a color of the pixel region is the color of the light-filtering portion corresponding to the pixel region, for example, the color of the light-filtering portion corresponding to the red pixel region is red, the color of the light-filtering portion corresponding to the blue pixel region is blue, and the color of the light-filtering portion corresponding to the green pixel region is green.

(70) FIG. 7 is a schematic diagram illustrating a distribution of pixel regions of a display panel provided in some embodiments of the present disclosure, and as shown in FIG. 7, the pixel regions P of the display panel **30** may be arranged in a plurality of rows, each row includes a plurality of pixel regions P, each pixel region is substantially in a rectangular shape, and a length direction of each pixel region extends along a column direction. That is, every pixel region P has a first side and a second side opposite to each other, and the first side and the second side are arranged side by side in a row direction, the first side and the second side each extend in the column direction, in this way, an area of each pixel region P can be increased under a condition that an area of the display area is limited and the number of the pixel regions P is limited, therefore, the transmittance of the display panel **30** can be improved.

(71) In some implementations, the plurality of pixel regions P of the display panel **30** may constitute a plurality of pixel units arranged in an array, and each pixel unit may include a green pixel region Pg, a red pixel region Pr and a blue pixel region Pb, where an area of the green pixel region Pg is larger than an area of each of the red pixel region Pr and the blue pixel region Pb. Since the color of green is a main factor affecting the brightness of the pixel unit, compared with a case where areas of the pixel regions P of different colors are the same, increasing the area of the green pixel region Pg is beneficial to improving the brightness of the display panel **30**.

(72) It can be understood that, in a case where an area of the pixel unit is fixed, if the area of the green pixel region Pg is increased, a total area of the red pixel region Pr and the blue pixel region Pb is to be reduced, and since the color of blue has a relatively great influence on an overall color of the pixel unit, in some implementations, the total area of the red pixel region Pr and the blue pixel region Pb may be reduced by reducing the area of the red pixel region Pr, so as to improve the brightness of the pixel unit and reduce the influence on the color of the pixel unit. In this case, the area of the blue pixel region Pb is smaller than that of the green pixel region Pg and larger than that of the red pixel region Pr.

(73) In some implementations, a ratio of the area of the green pixel region Pg to the area of the blue pixel region Pb ranges from 1.05:1 to 1.1:1, and a ratio of the area of the red pixel region Pr to the area of the blue pixel region Pb ranges from 0.9:1 to 0.95:1. In some implementations, a ratio of the area of the red pixel region Pr to that of the green pixel region Pg and to that of the blue pixel region Pb is 0.93:1.07:1, so that the transmittance can be raised by 3.2% and the influence on the color temperature is relatively small (with such design, the color temperature is reduced by 400K).

(74) In some implementations, the opposite substrate **32** further includes a black matrix disposed on the second base substrate, FIG. 8 is a plan view of the black matrix provided in the embodiments of the present disclosure, as shown in FIG. 8, the black matrix BM includes a plurality of light-blocking bars BM1, and in some implementations, the light-blocking bars BM1 each may extend in the row direction. Orthographic projections of the light-blocking bars BM1 on the first base substrate cover orthographic projections of the gate lines on the first base substrate, and a space exists between any two adjacent light-blocking bars BM1, and the space exposes a part of each data line DL.

(75) In the projection apparatus, the light emitted from the display panel **30** passes through the light reflective component **40** and the projection lens **50**, and is then projected and imaged on the target object. That is, the light of each pixel region viewed by human eyes is nearly vertically emitted from the pixel region, and therefore, the crosstalk between the pixel units in the same row is less. Due to the arrangement of the light-blocking bars, the crosstalk may not occur between different pixel units in the same column, and therefore, the black matrix BM with the above mentioned structure in the embodiments of the disclosure can improve the transmittance of the display panel **30** while ensuring the display effect. It has been verified that the transmittance of the display panel **30** can be raised by 16.7% by using the black matrix BM having the above mentioned structure, compared with using a black matrix having a grid shape (i.e., the black matrix covers the gate lines and the data lines).

(76) FIG. **9** is a schematic diagram illustrating a stack of some elements in the projection apparatus provided in some implementations of the present disclosure, and as shown in FIG. **9**, the display panel **30** is located within a focal length of the first lens **60**, in such case, a virtual image formed by imaging the display panel **30** by the first lens **60** is located on an intermediate plane M1, the intermediate plane M1 and the display panel **30** are located on a same side of the first lens **60**, an optical path distance from the intermediate plane M1 to the projection lens **50** is l.sub.2, a projection distance of the projection lens **50** (i.e., an image distance of the projection lens **50**) is l.sub.2', a focal length of the projection lens **50** is F, a distance from the first lens **60** to the display panel **30** is l.sub.1, and a distance from the intermediate plane M1 to the first lens **60** is l.sub.1'. When designing an actual product of the projection apparatus, the focal length F of the projection lens may be determined according to a desired projection distance, a desired size of a projection image to be displayed, and a dimension of the display area of the display panel **30** to The focal length F is equal to

$$(77) \frac{\text{theprojectiondistance}l_2' * \text{thedimensionofthedisplayarea}}{\text{thedimensionoftheprojectionimage}}.$$

After the focal length

(78) F of the projection lens **50** is determined, an object distance of the projection lens **50** (i.e., the above l.sub.2) may be determined according to the lens maker's equation of the projection lens **50** (i.e., the following formula 1-1):

$$(79) \frac{1}{l_2} = \frac{1}{F} + \frac{1}{l_2'}, \quad \text{formula 1 - 1}$$

then, according to the focal length of the first lens **60** and an object-image relationship between the projection lens **50** and the first lens **60**, a formula 1-3 can be derived according to the above formula 1-1 and the following formula 1-2, where the formula 1-2 is the lens maker's equation of the first lens **60**, and f is the focal length of the first lens **60**, and f.sub.1' is an optical path distance from the first lens to the projection lens.

$$(80) \frac{1}{l_1} = \frac{1}{f} + \frac{1}{l_1'} \quad \text{formula 1 - 2} \quad l_1 = f_1' - \frac{1}{l_2'}. \text{Math. } f_1'^2 \quad \text{formula 1 - 3}$$

(81) The focal length of the first lens **60**, the optical path distance from the first lens **60** to the projection lens **50**, and the distance from the first lens **60** to the display panel **30** can be specified according to the above three formulas.

(82) It should be noted that, the optical path distance from an optical device to the projection lens **50** refers to a path length that the light emitted from a center of the optical device pass through when the light is reflected to a center of the projection lens **50** by the light reflective component. It should be further noted that, the first lens **60** is parallel to the display panel **30**, and the distance from the first lens **60** to the display panel **30** refers to a distance from a plane where the first lens **60** is located to the light exiting surface of the display panel **30**; the intermediate plane M1 is parallel to the first lens **60**, and the distance from the intermediate plane M1 to the first lens **60** refers to a distance from the intermediate plane M1 to the plane where the first lens **60** is located.

(83) FIG. **10** is an overall structural top view of a projection apparatus provided in some

embodiments of the present disclosure, and FIG. 11 is an overall structural perspective view of a projection apparatus provided in some embodiments of the present disclosure, and as shown in FIGS. 10 and 11, the projection apparatus further includes a housing 80, the light polarization component 20, the display panel 30, the light reflective component 40, and the first lens 60 are all disposed in the housing 80, at least a portion of the light source component 10 is disposed in the housing 80, and for example, the light emitting device 11b, the light collector 12, and the second lens 16 are disposed in the housing 80.

(84) The second lens 16, the light polarization component 20, the display panel 30, and the first lens 60 may be disposed on a support within the housing 80. For example, the second lens 16 and the light polarization component 20 may be disposed on a first support, and the display panel 30 and the first lens 60 may be disposed on a second support, both the first support and the second support are fixed on an inner surface of the housing 80.

(85) In some implementations, the projection apparatus adopts a horizontal structure, specifically, FIG. 12 is a schematic diagram illustrating a position relationship between the display panel and the light reflective component, as shown in FIG. 12, the display panel 30 is rectangular and has a first edge 301 and a second edge 302 adjacent to each other, the first edge 301 has a length smaller than that of the second edge 302, the horizontal structure means that the first edge 301 extends along a height direction of the projection apparatus (i.e., a z direction in FIGS. 11 and 12), the second edge 302 extends along a y direction in FIG. 12, and the light polarization component 20 and the display panel 30 are arranged along an x direction in FIG. 12; the first edge 301 of the display panel 30 is parallel to a plane where the light reflective component 40 is located, and the second edge 302 intersects the plane where the light reflective component 40 is located. Compared with a vertical structure, when the projection apparatus adopts the horizontal structure, the light path distance from the projection lens 50 to the display panel 30 is longer, which is beneficial to improving the luminous flux of the projection apparatus and improving the display effect.

(86) Moreover, the projection apparatus adopting the horizontal structure is beneficial to reducing an overall height of the projection apparatus. In some implementations, a height of the projection apparatus is less than or equal to 80 mm.

(87) It should be noted that, the first edge 301 being parallel to the plane where the light reflective component 40 is located means that an included angle between the first edge 301 and the plane where the light reflective component 40 is located is in a range of $[0, 10^\circ]$.

(88) It should be noted that, the horizontal structure is described above by taking the display panel 30 being rectangular as an example, in some implementations, the display panel 30 may also be non-rectangular, in such case, the horizontal structure is a structure satisfying that: the height direction of the projection apparatus is perpendicular to a plane where an optical axis of an optical system formed by the light source component 10, the light polarization component 20, the display panel 30, the light reflective component 40 and the projection lens 50 is located. It should be noted that, the plane where the optical axis of the optical system is located refers to a plane defined by optical axes of the light source component 10, the light polarization component 20, the display panel 30, the light reflective component 40, and the projection lens 50. For example, referring to FIG. 10, the optical axes of the light source component 10, the light polarization component 20, and the display panel 30 each extend along a third direction, and the optical axis of the projection lens 50 extends along a fourth direction, the plane where the optical axis of the optical system is located is parallel to the third direction and the fourth direction, and the height direction of the projection apparatus is a direction perpendicular to the paper as shown in FIG. 10.

(89) In some implementations, as shown in FIG. 10, the housing 80 may include a heat dissipating portion 80b for dissipating heat inside the housing 80. The heat dissipating portion 80b and the housing 80 may form an enclosed space, and specifically, the housing 80 may include a top wall, a bottom wall and a side wall connect between the top wall and the bottom wall, the side wall may have an opening therein, and the heat dissipating portion 80b covers the opening in the side wall to

form the enclosed space together with the side wall, the top wall and the bottom wall.

(90) The projection apparatus further includes a first fan **83** including a first air outlet and a first air inlet, the first air outlet and the first air inlet are located outside the housing **80**, and one of the first air outlet and the first air inlet is arranged facing the heat dissipating portion **80b**, so that facilitating heat dissipation by the heat dissipating portion **80b**. The first fan **83** may be an axial fan, which may have a rated power ranging from 1.5 W to 4 W, for example, may have a power of 2 W.

(91) As shown in FIG. **10**, the projection apparatus may further include a second fan **81** including a second air outlet and a second air inlet, and the second air outlet is located in the housing **80**. In some implementations, the second fan **81** may be a centrifugal fan, which may have a rated power ranging from 1.5 W to 4 W, for example, may have a power of 2 W.

(92) A heat dissipation air duct communicated with the second air outlet is further formed in the housing **80**, and the heat dissipation air duct is adjacent to the heat dissipating portion **80b**, so that when airflow is blown out from the second air outlet, the heat in the housing **80** can be diffused to the heat dissipating portion **80b** along with the airflow, and then is dissipated out of the housing **80**. The heat dissipation air duct includes a first channel **V1** and/or a second channel **V2**. A first gap exists between the display panel **30** and the light reflective component **40**, and the first gap is the first channel **V1** of the heat dissipation air duct, and a second gap exists between the display panel **30** and the light source component **10**, and the second gap is the second channel **V2** of the heat dissipation air duct.

(93) It should be noted that the first gap existing between the display panel **30** and the light reflective component **40** means that an air gap exists between the display panel **30** and a portion of the light reflective component **40** farthest away from the display panel **30**. In particular, when the light reflective component **40** includes the plurality of optical film layers **42** integrated together, the first gap may be at least a portion of the gap existing between the display panel **30** and the plurality of optical film layers **42**; when the light reflective component **40** includes the polarizer **43** and the reflective mirror **44**, the first gap may be at least a portion of a gap existing between the display panel **30** and the reflective mirror **44**.

(94) As described above, in some implementations, the projection apparatus may further include a light polarization component **20** and a first lens **60**, in such case, the first gap may be specifically located between the first lens **60** and the display panel **30**, and the second gap may be specifically located between the display panel **30** and the light polarization component **20**. In a case where the light polarization component **20** includes a transfective component **21** and a transparent base **22**, the second gap may be located between the display panel **30** and the transparent base **22**, and the transfective component **21** is not in contact with the second gap. It is understood that when the light emitted from the light source **11** is irradiated to the transfective component **21**, a portion of the light may be absorbed by the transfective component **21** to generate a certain amount of heat, and the transparent base **22** may transfer at least a portion of the heat from the transfective component **21** to the second channel **V2** for heat dissipation.

(95) With the first channel **V1** and the second channel **V2**, the heat of the display panel **30** can be dissipated from at least one side of the display panel **30**, and the heat can be prevented from concentrating on the display panel **30** to affect the performance of the display panel **30**.

(96) In some implementations, the heat dissipation air duct may include both the first channel **V1** and the second channel **V2**, so that heat of the display panel **30** may be dissipated from opposite sides of the display panel **30**. In addition, as shown in FIG. **10**, the heat dissipation air duct further includes a third channel **V3** connecting the first channel **V1** with the second channel **V2**. The side wall of the housing **80** further includes a curved portion **80a** corresponding to the third channel **V3**, an inner wall of the curved portion **80a** is an arc surface, and the arc surface protrudes in a direction away from the first channel **V1** and the second channel **V2**, so that the airflow in the first channel **V1** enters the second channel **V2** along the arc surface. It should be noted that, the curved portion **80a** “corresponding to” the third channel **V3** means that the curved portion **80a** is closely adjacent

to the third channel V3.

(97) As shown in FIG. 10, the housing 80 further includes a fourth channel V4 and a fifth channel V5, the fourth channel V4 communicates the second air outlet of the second fan 81 with the first channel V1, the fifth channel V5 is communicated with the second channel V2, and the fifth channel V5 is disposed adjacent to the heat dissipating portion 80b, so as to cool the gas in the fifth channel V5 through the heat dissipating portion 80b.

(98) In the present disclosure, the first channel V1, the second channel V2, the third channel V3, the fourth channel V4 and the fifth channel V5 form a continuous channel, and the continuous channel is communicated with the second air inlet and the second air outlet of the second fan 81, so that when the second fan 81 blows air out, an airflow is formed in the continuous channel, and the airflow passes by two sides of the display panel 30, so as to take away heat of the display panel 30, and when the heat passes by the heat dissipating portion 80b, the heat is dissipated to outside by the heat dissipating portion 80b.

(99) In some implementations, the second air inlet of the second fan 81 is located in the housing 80, and the second air outlet of the second fan 81, the fourth channel V4, the first channel V1, the third channel V3, the second channel V2, the fifth channel V5, and the second air inlet of the second fan 81 are connected in sequence to form a closed air loop. That is, the air blown out from the second air outlet of the second fan 81 firstly enters the fourth channel V4, then sequentially passes through the first channel V1, the third channel V3, the second channel V2 and the fifth channel V5, and finally enters the second air inlet of the second fan 81. The arrows in FIG. 10 indicate a direction of the airflow.

(100) In some implementations, an area of a ventilation cross section of the first channel V1 is 1 to 1.2 times of an area of the second air outlet of the second fan 81, so as to facilitate the air blown out from the second fan 81 to enter the first channel V1, and the heat dissipation efficiency is improved. Similarly, an area of the ventilation cross section of the second channel V2 is 1 to 1.2 times of the area of the second air outlet of the second fan 81. The ventilation cross section of the first channel V1 refers to a cross section of the first channel V1 taken along a direction perpendicular to a direction in which the air in the first channel is flowed. The ventilation cross section of the second channel V2 refers to a cross section of the second channel V2 taken along a direction perpendicular to a direction in which the air in the second channel is flowed. The first channel V1 and the second channel V2 both have a length, a width and a height, and the lengths of the first channel V1 and the second channel V2 are dimensions of the first channel V1 and the second channel V2 in a fourth direction in FIG. 10, respectively; the widths of the first channel V1 and the second channel V2 are dimensions of the first channel V1 and the second channel V2 in a third direction in FIG. 10, and the third direction is a thickness direction of the display panel 30; and the heights of the first channel V1 and the second channel V2 are dimensions of the first channel V1 and the second channel V2 in a direction perpendicular to the paper surface in FIG. 10, respectively.

(101) In some implementations, the widths of the first channel V1 and the second channel V2 each range from 6 mm to 10 mm, for example, each of the widths of the first channel V1 and the second channel V2 is 8 mm.

(102) In some implementations, there may be no gap between the second lens 16 and the light polarization component 20, thereby improving the compactness of the projection apparatus.

(103) In some implementations, a third gap V6 exists between the second lens 16 and the light polarization component 20, so as to provide some positioning structures on the housing for positioning the second lens 16 and/or the light polarization component 20.

(104) In a case where the third gap V6 exists between the second lens 16 and the light polarization component 20, in an example, the third gap V6 may not be in communication with the third channel V3. In this case, a width of the third gap V6 is as small as possible, for example, may be smaller than the width of the first gap, so as to improve the compactness of the projection

apparatus. For example, the width of the third gap V6 is less than 8 mm, for example, may be 2 mm. The width of the third gap V6 refers to a dimension of the third gap V6 in the thickness direction of the display panel 30. In another example, the third gap V6 may be in communication with the third channel V3 and the fifth channel V5, that is, a part of the airflow in the third channel V3 may enter the second channel V2, and another part of the airflow in the third channel V3 may enter the third gap V6, so that heat of the light polarization component 20 can be dissipated from two sides of the light polarization component 20 to improve the heat dissipation effect from inside of the projection apparatus. In this case, a sum of the areas of the ventilation cross sections of the third gap V6 and the second channel V2 may be the same as the area of the ventilation cross section of the first channel V1, thereby facilitating a smooth flow of the airflow inside the projection apparatus.

(105) Since the light source component 10 is a main heat generating source, and the light polarization component 20 is closer to the light source component 10, the heat in the first channel V1 is less than the heat in the second channel V2, and the first channel V1 being communicated with the first air outlet is equivalent to that the airflow firstly flows through a low-temperature area and then flows through a high-temperature area, so that the heat dissipation of the display panel 30 is more facilitated.

(106) As shown in FIG. 10, the fourth channel V4 and the fifth channel V5 share at least a portion of a channel wall 82 and are disposed on opposite sides of the at least the portion of the channel wall 82.

(107) As shown in FIG. 10, the second fan 81 and the heat dissipating portion 80b are located on a side of at least a portion of the light reflective component away from the projection lens 50, so as to prevent the second fan 81 and the heat dissipating portion 80b from affecting the optical path in the projection apparatus. The second fan 81 may include a plurality of side surfaces, one of which is disposed parallel to at least a portion of the light reflective component, so that the structure inside the housing 80 is more compact, thereby reducing an overall volume of the projection apparatus. For example, the second fan 81 has a cuboid structure, and one of side surfaces of the cuboid structure is disposed parallel to at least a portion of the light reflective component. It should be noted that the “at least a portion of the light reflective component” refers to a portion or an entire of the light reflective component 40 that reflect light into the projection lens 50, and specifically, in a case where the light reflective component 40 include the optical film layers 42 integrated together, the “at least a portion of the light reflective component” refers to the entire light reflective component 40; and in a case where the light reflective component 40 includes the polarizer 43 and the reflective mirror 44, the “at least a portion of the light reflective component” refers to the reflective mirror 44.

(108) As shown in FIG. 10, at least a part of a surface of the heat dissipating portion 80b facing the interior of the housing 80 is a wall of the fifth channel V5. For example, in a case where no other structural member is disposed on the surface of the heat dissipating portion 80b facing the interior of the housing 80, the entire surface of the heat dissipating portion 80b facing the interior of the housing 80 may serve as the wall of the fifth channel V5; in a case where there is any other structural member provided on the surface of the heat dissipating portion 80b facing the interior of the housing 80, a region of the surface of the heat dissipating portion 80b facing the interior of the housing 80 without any other structural member may serve as the wall of the fifth channel V5.

(109) In some implementations, a contour of a portion of the heat dissipating portion 80b adjacent to the fifth channel V5 includes an arc surface, the heat dissipating portion 80b further includes a plurality of first heat dissipating fins 91 extending into the fifth channel V5, and the plurality of first heat dissipating fins 91 may be arranged along the height direction of the housing 80. A direction in which the first heat dissipating fins 91 extending into the fifth channel V5 each extend is the same as a direction in which the fifth channel V5 extends. The direction in which the fifth channel V5 extends is the direction in which the air flows in the fifth channel V5. For example, the

direction in which the air flows in the fifth channel V5 is arc-shaped, and the heat dissipating portion **80** includes a curved heat dissipating wall **90** and the plurality of first heat dissipating fins **91** disposed on the heat dissipating wall **90**, and the heat dissipating wall **90**, together with the side wall, the top wall and the bottom wall of the housing, encloses a closed space, a surface of the heat dissipating wall **90** facing the interior of the housing **80** is an arc surface, the surface of the heat dissipating wall **90** facing the interior of the housing **80** is provided thereon with the plurality of first heat dissipating fins **91**, and an edge of each of the first heat dissipating fins **91** away from the heat dissipating wall **90** is arc-shaped.

(110) With the first heat dissipating fins **91**, the heat dissipating effect by the heat dissipating portion **80b** for the interior of the housing **80** can be improved.

(111) Further, as shown in FIG. **10**, the heat dissipating portion **80b** may further include a plurality of second heat dissipating fins **92** located between the first fan **83** and the fifth channel V5, the plurality of second heat dissipating fins **92** are sequentially arranged along the height direction of the housing **80**, and the second heat dissipating fins **92** may be disposed on the heat dissipating wall **90**.

(112) The first air outlet of the first fan **83** is disposed facing the heat dissipating portion **80b**, and an upwind surface is formed on a side of the second heat dissipating fins **92** close to the first fan **83**, and the upwind surface and an air outlet surface of the first fan **83** have a same contour; or, the first air inlet of the first fan **81** is disposed facing the heat dissipating portion **80b**, and a leeward surface is formed at a side of the second heat dissipating fins **92** close to the first fan **81**, and the leeward surface and an air inlet surface of the first fan **83** have a same contour. With such design, the airflow can sufficiently flow between the plurality of second dissipating fins **92** and the first fan **83**, thereby improving the heat dissipating effect of the second dissipating fins **92**.

(113) It should be noted that the air inlet surface of the first fan **83** refers to a surface where the first air inlet of the first fan **83** is located; the air outlet surface of the first fan **83** is a surface where the first air outlet of the first fan **83** is located.

(114) In the embodiments of the present disclosure, a material of the heat dissipating portion **80b** may include a metal material with better thermal conductivity, for example, may include aluminum, so as to improve the heat dissipating effect. Materials of the heat dissipating wall **90**, the first heat dissipating fins **91** and the first heat dissipating fins **92** may be the same.

(115) In some implementations, as shown in FIGS. **10** and **11**, the projection apparatus may further include a light source heat dissipator **84** for dissipating heat from the light source, and the light source heat dissipator **84** is connected to the light source component for dissipating heat of the light source component. Specifically, as shown in FIG. **11**, the light source heat dissipator **84** includes a heat sink component **841** and a heat conduction connecting element **842**, the heat sink component **841** is connected with lamp panel **11a** through the heat conduction connecting element **842**. The heat sink component **841** may include a plurality of heat sink fins, which may be made of a metal material having good thermal conductivity. The heat conduction connecting element **842** and the lamp panel **11a** may be formed into one piece.

(116) In a case where the projection apparatus includes the light source heat dissipator **84**, one of the first air inlet and the first air outlet of the first fan **83** is disposed facing the heat dissipating portion **80b**, and the other of the first air inlet and the first air outlet of the first fan **83** is disposed facing the light source heat dissipator **84**. In an implementation, the light source heat dissipator **84** generates more heat per unit time than the heat dissipating portion **80b**, and therefore, in some implementations, the first air inlet of the first fan **83** is disposed facing the heat dissipating portion **80b**, and the first air outlet of the first fan **83** is disposed facing the light source heat dissipator **84**, which is more favorable for heat dissipation of the whole projection apparatus.

(117) It should be noted that the expression related to the range, such as “from m1 to m2” appearing in the embodiments of the present disclosure, includes endpoint values m1 and m2.

(118) It will be understood that the above embodiments are merely exemplary embodiments

employed to illustrate the principles of the present disclosure, and the present disclosure is not limited thereto. It will be apparent to those skilled in the art that various changes and modifications may be made therein without departing from the spirit and scope of the present disclosure, and these changes and modifications are to be considered within the scope of the present disclosure.

Claims

1. A projection apparatus, comprising: a light source component; a light polarization component located on a light exiting side of the light source component and configured to convert light emitted from the light source component into first polarized light polarized in a first polarization direction; a display panel located on a side, away from the light source component, of the light polarization component and configured to adjust the polarization direction in which the first polarized light is polarized, so as to emit second polarized light; a polarization direction in which the second polarized light is polarized is between the first polarization direction and a second polarization direction, and the first polarization direction is perpendicular to the second polarization direction; a light reflective component located on a side, away from the light polarization component, of the display panel and configured to reflect one of the polarized light polarized in the first polarization direction and the polarized light polarized in the second polarization direction; and a projection lens, a light incident surface of which faces the light reflective component so as to receive the light reflected by the light reflective component, wherein the light source component comprises a light source, a second reflective layer, and a second lens; the second lens is arranged between the light source and the light polarization component and is configured to collimate light directly irradiated to the second lens by the light source, and the second lens comprises a Fresnel lens; the second reflective layer is located between the light source and the second lens and is arranged surrounding an optical axis of the second lens to form a cylindrical structure having a first opening facing the light source and a second opening facing the second lens, and an area of the first opening is smaller than that of the second opening; wherein, the light polarization component comprises: a transfective component configured to transmit the polarized light polarized in the first polarization direction and reflect at least a part of the polarized light polarized in the second polarization direction.
2. The projection apparatus of claim 1, wherein the light source comprises: a lamp panel; a light emitting device located on the lamp panel and located on a side, close to the display panel, of the lamp panel; and a light collector located between the light source and the second lens and configured to converge the light emitted by the light emitting device.
3. The projection apparatus of claim 2, wherein the light source further comprises: a first reflective layer located on the lamp panel, the light emitting device and the first reflective layer are located on a same side of lamp panel, and at least part of an orthographic projection of the first reflective layer on the lamp panel is not overlapped with an orthographic projection of the light emitting device on the lamp panel.
4. The projection apparatus of claim 2, wherein the light collector comprises a plano-convex lens, a flat surface of the plano-convex lens faces the light emitting device, and a ratio of a distance from the light emitting device to the plane of the plano-convex lens to a distance from the plane of the plano-convex lens to the second lens ranges from 1:30 to 1:50.
5. The projection apparatus of claim 2, wherein a shape of a light exiting surface of the light emitting device is the same as a shape of a display surface of the display panel.
6. The projection apparatus of claim 5, wherein the light exiting surface of the light emitting device and the display surface of the display panel are both rectangular, a direction in which a long side of the light exiting surface extends is the same as a direction in which a long side of the display surface extends, and a direction in which a short side of the light exiting surface extends is the same as a direction in which a short side of the display surface extends; a ratio of a length of the

light exiting surface to a length of the display surface is 1:a, a ratio of a width of the light exiting surface to a width of the display surface is 1:b, a and b are both larger than 0, and a:b ranges from 0.8:1 to 1.2:1.

7. The projection apparatus of claim 5, wherein a distance from the second lens to the light emitting device is a first distance, and a focal length of the second lens is equal to the first distance; or, the focal length of the second lens is xmm, and x is an integer closest to a value of the first distance and divisible by 5.

8. The projection apparatus of claim 1, wherein a divergence angle of light from the light source and a distance from the light source to the second lens satisfy that: assuming that the light emitted from the light source is irradiated to a plane where the second lens is located without being obstructed, a range where the light emitted from the light source is irradiated on the plane where the second lens is located completely covers the second lens.

9. The projection apparatus of claim 8, wherein the divergence angle of light from the light source and the distance from the light source to the second lens satisfy that: assuming that the light emitted from the light source is irradiated to the plane where the second lens is located without being obstructed, a ratio of an area of the second lens to an area of a light spot formed on the plane where the second lens is located ranges from 0.65:1 to 0.75:1.

10. The projection apparatus of claim 1, wherein the transfective component comprises an Advanced Polarizer Film (APF).

11. The projection apparatus of claim 1, wherein the light polarization component further comprises a transparent base, the transfective component is located on a side of the transparent base away from the display panel, and a gap exists between the transparent base and the display panel.

12. The projection apparatus of claim 1, further comprising a first lens; wherein the light reflective component comprises a polarizer and a reflective mirror, the polarizer is located between the display panel and the reflective mirror, the first lens is located between the polarizer and the reflective mirror and is configured to converge the light exited from the polarizer and transmit the converged light to the reflective mirror; or, the light reflective component comprises a plurality of optical film layers integrated together, the first lens is located between the display panel and the light reflective component, is configured to converge the light exited from the display panel and transmit the converged light to the reflective mirror.

13. The projection apparatus of claim 12, wherein the first lens is a Fresnel lens.

14. The projection apparatus of claim 12, wherein a focal length F of the projection lens, an image distance l.sub.2' of the projection lens, and an optical path distance l.sub.2 from an intermediate

plane to the projection lens satisfy the following formula (1): $\frac{1}{l_2'} = \frac{1}{F} + \frac{1}{l_2}$ (1) a distance l.sub.1 from the first lens to the display panel, a distance from the intermediate plane to the first lens, and a focal length f of the first lens satisfy the following formula (2): $\frac{1}{l_1} = \frac{1}{f} + \frac{1}{l_2}$ (2) the distance

l.sub.1 from the first lens to the display panel, the optical path distance l.sub.2 from the intermediate plane to the projection lens, and an optical path distance f.sub.1' from the first lens to the projection lens satisfy the following formula (3): $l_1 = f_1' - \frac{1}{l_2'}$.Math. $f_1'^2$ (3) wherein the intermediate plane is a virtual image surface formed by imaging the display panel by the first lens, and the intermediate plane and the display panel are located on a same side of the first lens.

15. The projection apparatus of claim 1, wherein the display panel comprises a plurality of pixel units arranged in an array, each of the pixel units comprises a red pixel region, a green pixel region, and a blue pixel region, the green pixel region has an area larger than each of areas of the red pixel region and the blue pixel region.

16. The projection apparatus of claim 15, wherein the area of the green pixel region is 1.05 to 1.1 times the area of the blue pixel region, and the area of the red pixel region is 0.9 to 0.95 times the

area of the blue pixel region.

17. A projection apparatus, comprising: a light source component; a light polarization component located on a light exiting side of the light source component and configured to convert light emitted from the light source component into first polarized light polarized in a first polarization direction; a display panel located on a side, away from the light source component, of the light polarization component and configured to adjust the polarization direction in which the first polarized light is polarized, so as to emit second polarized light; a polarization direction in which the second polarized light is polarized is between the first polarization direction and a second polarization direction, and the first polarization direction is perpendicular to the second polarization direction; a light reflective component located on a side, away from the light polarization component, of the display panel and configured to reflect one of the polarized light polarized in the first polarization direction and the polarized light polarized in the second polarization direction; and a projection lens, a light incident surface of which faces the light reflective component so as to receive the light reflected by the light reflective component, wherein the light reflective component comprises a polarizer and a reflective mirror, the polarizer is located between the display panel and the reflective mirror and is configured to transmit one of the polarized light polarized in the first polarization direction and the polarized light polarized in the second polarization direction.

18. A projection apparatus, comprising: a light source component; a light polarization component located on a light exiting side of the light source component and configured to convert light emitted from the light source component into first polarized light polarized in a first polarization direction; a display panel located on a side, away from the light source component, of the light polarization component and configured to adjust the polarization direction in which the first polarized light is polarized, so as to emit second polarized light; a polarization direction in which the second polarized light is polarized is between the first polarization direction and a second polarization direction, and the first polarization direction is perpendicular to the second polarization direction; a light reflective component located on a side, away from the light polarization component, of the display panel and configured to reflect one of the polarized light polarized in the first polarization direction and the polarized light polarized in the second polarization direction; and a projection lens, a light incident surface of which faces the light reflective component so as to receive the light reflected by the light reflective component, wherein the light reflective component comprises a plurality of optical film layers integrated together, refractive indexes of any two adjacent optical film layers are different so as to form an optical interface therebetween, and each optical interface corresponds to a wave band, different optical interfaces correspond to different wave bands, each optical interface is configured to transmit the polarized light with a wavelength within a corresponding wave band and polarized in the first polarization direction, and reflect the polarized light with a wavelength within a corresponding wave band and polarized in the second polarization direction, or each optical interface is configured to transmit the polarized light with a wavelength within a corresponding wave band and polarized in the second polarization direction, and reflect the polarized light with a wavelength within a corresponding wave band and polarized in the first polarization direction.

19. The projection apparatus of claim 18, wherein the light reflective component is configured to transmit the polarized light polarized in the first polarization direction and reflect the polarized light polarized in the second polarization direction.
