

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250275748

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

YOSHIDA; Satoshi

ULTRASOUND PROBE, ULTRASOUND TRANSDUCER UNIT, AND ULTRASOUND ENDOSCOPE

Abstract

An ultrasound probe includes: a transducer array in which a plurality of transducers configured to transmit and receive ultrasonic waves are arrayed with longitudinal directions of the transducers aligned; and a pair of housings each having a plate shape, the housings being configured to sandwich the transducers, the housings including a first conductive portion provided on a first face positioned on a side of each of the transducers, an insulating portion provided on an outer edge portion of a second face that is positioned on an opposite side of the first face, a second conductive portion provided on the second face, and a third conductive portion electrically connecting the first conductive portion and the second conductive portion.

Inventors: YOSHIDA; Satoshi (Kawagoe-shi, JP)

Applicant: OLYMPUS CORPORATION (Tokyo, JP)

Family ID: 83545253

Assignee: OLYMPUS CORPORATION (Tokyo, JP)

Appl. No.: 19/210678

Filed: May 16, 2025

Related U.S. Application Data

parent US continuation 18219797 20230710 parent-grant-document US 12324703 child US 19210678

parent WO continuation PCT/JP2021/014815 20210407 PENDING child US 18219797

Publication Classification

Int. Cl.: A61B8/12 (20060101); A61B8/00 (20060101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION [0001] This application is a continuation of U.S. patent application Ser. No. 18/219,797, filed on Jul. 10, 2023, which is a continuation of International Application No. PCT/JP2021/014815, filed on Apr. 7, 2021, the entire contents of each of which are incorporated herein by reference.

BACKGROUND

1. Technical Field

[0002] The present disclosure relates to an ultrasound probe, an ultrasound transducer unit, and an ultrasound endoscope.

2. Related Art

[0003] In the related art, an ultrasound probe including a transducer array in which a plurality of transducers for transmitting and receiving ultrasonic waves is arrayed with their longitudinal directions aligned and a housing for holding the transducer array is known (see, for example, Japanese Patent No. 5889121 A).

[0004] In an ultrasound probe, a structure is known in which a part of a housing has an electrical conductivity, and an outer periphery of the housing is covered with an insulating acoustic lens. According to this structure, since the part of the housing has an electrical conductivity, electromagnetic noise can be reduced. In addition, since the outer periphery of the housing is covered with the acoustic lens, a current applied to a transducer can be prevented from leaking to the outside via the housing.

SUMMARY

[0005] In some embodiments, an ultrasound probe includes: a transducer array in which a plurality of transducers configured to transmit and receive ultrasonic waves are arrayed with longitudinal directions of the transducers aligned; and a pair of housings each having a plate shape, the housings being configured to sandwich the transducers, the housings including a first conductive portion having an electrical conductivity, the first conductive portion being provided on a first face positioned on a side of each of the transducers, an insulating portion having an insulating property, the insulating portion being provided on an outer edge portion of a second face that is positioned on an opposite side of the first face, the edge portion including a region obtained by projecting each of the transducers on the second face in a longitudinal direction of each of the transducers, a second conductive portion having an electrical conductivity, the second conductive portion being provided on the second face, and a third conductive portion electrically connecting the first conductive portion and the second conductive portion.

[0006] In some embodiments, an ultrasound transducer unit includes: a transducer array in which a plurality of transducers configured to transmit and receive ultrasonic waves are arrayed with longitudinal directions of the transducers aligned; and a pair of housings each having a plate shape, the housings being configured to sandwich the transducers, the housings including a first conductive portion having an electrical conductivity, the first conductive portion being provided on a first face positioned on a side of each of the transducers, an insulating portion having an insulating property, the insulating portion being provided on an outer edge portion of a second face that is positioned on an opposite side of the first face, the edge portion including a region obtained by projecting each of the transducers on the second face in a longitudinal direction of each of the transducers, a second conductive portion having an electrical conductivity, the second conductive

portion being provided on the second face, and a third conductive portion electrically connecting the first conductive portion and the second conductive portion.

[0007] In some embodiments, an ultrasound endoscope includes: an ultrasound probe including a transducer array in which a plurality of transducers configured to transmit and receive ultrasonic waves are arrayed with longitudinal directions of the transducers aligned, and a pair of housings each having a plate shape, the housings being configured to sandwich the transducers, the housings including a first conductive portion having an electrical conductivity, the first conductive portion being provided on a first face positioned on a side of each of the transducers, an insulating portion having an insulating property, the insulating portion being provided on an outer edge portion of a second face that is positioned on an opposite side of the first face, the edge portion including a region obtained by projecting each of the transducers on the second face in a longitudinal direction of each of the transducers, a second conductive portion having an electrical conductivity, the second conductive portion being provided on the second face, and a third conductive portion electrically connecting the first conductive portion and the second conductive portion; and an insertion portion having a distal end provided with the ultrasound probe, the insertion portion being configured to be inserted into a subject.

[0008] The above and other features, advantages and technical and industrial significance of this disclosure will be better understood by reading the following detailed description of presently preferred embodiments of the disclosure, when considered in connection with the accompanying drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] FIG. 1 is a diagram illustrating an endoscope system including an ultrasound probe according to a first embodiment;

[0010] FIG. 2 is a perspective view illustrating a distal end of an insertion portion;

[0011] FIG. 3 is a schematic structure diagram of an ultrasound probe;

[0012] FIG. 4 is an exploded view of the ultrasound probe;

[0013] FIG. 5 is a cross-sectional view corresponding to line A-A in FIG. 2;

[0014] FIG. 6 is a diagram illustrating an inner face of a housing;

[0015] FIG. 7 is a diagram illustrating an outer face of the housing;

[0016] FIG. 8 is a diagram illustrating an inner face of a housing according to a first modification;

[0017] FIG. 9 is a diagram illustrating an inner face of a housing according to a second modification;

[0018] FIG. 10 is a diagram illustrating an outer face of the housing according to the second modification;

[0019] FIG. 11 is a diagram illustrating an outer face of a housing according to a third modification;

[0020] FIG. 12 is a schematic structure diagram of an ultrasound probe according to a second embodiment;

[0021] FIG. 13 is a diagram illustrating an inner face of a housing on a distal end side;

[0022] FIG. 14 is a diagram illustrating an outer face of the housing on the distal end side;

[0023] FIG. 15 is a diagram illustrating an inner face of the housing on a proximal end side;

[0024] FIG. 16 is a diagram illustrating an outer face of the housing on the proximal end side;

[0025] FIG. 17 is a schematic structure diagram of an ultrasound probe according to a third embodiment;

[0026] FIG. 18 is a diagram illustrating an inner face of a housing;

[0027] FIG. 19 is a diagram illustrating an outer face of the housing; and

[0028] FIG. 20 is a cross-sectional view of the ultrasound probe.

DETAILED DESCRIPTION

[0029] Hereinafter, embodiments of an ultrasound probe, an ultrasound transducer unit, and an ultrasound endoscope according to the disclosure will be described with reference to the drawings. Note that the disclosure is not limited by these embodiments. The disclosure is applicable to ultrasound probes, ultrasound transducer units, and ultrasound endoscopes in general.

[0030] Incidentally, in the description of the drawings, the same or corresponding elements are denoted by the same symbol as appropriate. In addition, it should be noted that the drawings are schematic and that a dimensional relationship of elements, a ratio of elements, and the like may be different from reality. Some parts may have a different dimensional relationship or different ratios between drawings.

First Embodiment

Schematic Configuration of Endoscope System

[0031] FIG. 1 is a diagram illustrating an endoscope system including an ultrasound probe according to a first embodiment. An endoscope system 1 performs ultrasound diagnosis and treatment on the inside of a subject such as a person by using an ultrasound endoscope. As illustrated in FIG. 1, the endoscope system 1 includes an ultrasound endoscope 2, an ultrasound imaging device 3, an endoscope imaging device 4, and a display device 5.

[0032] A part of the ultrasound endoscope 2 can be inserted into the subject and has a function of transmitting an ultrasound pulse (acoustic pulse) toward a body wall inside the subject and receiving an ultrasound echo reflected by the subject and a function of capturing an image of the inside of the subject and outputting an image signal. Note that a detailed structure of the ultrasound endoscope 2 will be described later.

[0033] The ultrasound imaging device 3 is electrically connected to the ultrasound endoscope 2 via an ultrasound cable 31 and outputs a pulse signal to the ultrasound endoscope 2 via the ultrasound cable 31 and receives an echo signal from the ultrasound endoscope 2. The ultrasound imaging device 3 further performs predetermined processing on the echo signal to generate an ultrasound image.

[0034] An endoscope connector 9 of the ultrasound endoscope 2 is detachably connected to the endoscope imaging device 4. As illustrated in FIG. 1, the endoscope imaging device 4 includes a video processor 41 and a light source device 42.

[0035] The video processor 41 receives an image signal from the ultrasound endoscope 2 via the endoscope connector 9. The video processor 41 further performs predetermined processing on the image signal to generate an endoscopic image.

[0036] The light source device 42 supplies illumination light for illuminating the inside of the subject to the ultrasound endoscope 2 via the endoscope connector 9.

[0037] The display device 5 includes liquid crystal, organic electro luminescence (EL), a cathode ray tube (CRT), or a projector and displays the ultrasound image generated by the ultrasound imaging device 3, the endoscopic image generated by the endoscope imaging device 4, or the like.

Structure of Ultrasound Endoscope

[0038] Next, the structure of the ultrasound endoscope 2 will be described. As illustrated in FIG. 1, the ultrasound endoscope 2 includes an insertion portion 6, an operating portion 7, a universal cord 8, and the endoscope connector 9.

[0039] FIG. 2 is a perspective view illustrating a distal end of the insertion portion. Note that, in the following description of the structure of the insertion portion 6, a distal end side of the insertion portion 6 (distal end side in an insertion direction into the subject) is simply referred to as “distal end side”, and a proximal end side of the insertion portion 6 (side away from a distal end of the insertion portion 6) is referred to as “proximal end side”.

[0040] The insertion portion 6 is a portion to be inserted inside the subject. As illustrated in FIG. 1 of FIG. 2, the insertion portion 6 includes an ultrasound probe 10 included on the distal end side, a

rigid portion **61** connected to the proximal end side of the ultrasound probe **10**, a bendable portion **62** which is bendable and is connected to the proximal end side of the rigid portion **61**, and a flexible tube **63** (FIG. 1) which is flexible and is connected to the proximal end side of the bendable portion **62**.

[0041] Note that, inside the insertion portion **6**, the operating portion **7**, the universal cord **8**, and the endoscope connector **9**, a light guide that transmits illumination light supplied from the light source device **42**, a transducer cable that transmits a pulse signal or an echo signal, and a signal cable that transmits an image signal are routed, and a pipeline for circulating a fluid is included.

[0042] The rigid portion **61** is a rigid member made of a resin material and others. As illustrated in FIG. 2, in the distal end of the rigid portion **61**, an illumination portion **611** that irradiates the inside of the subject with illumination light, an imaging portion **612** that captures an image of the inside of the subject, and a treatment instrument channel **613** that causes a treatment instrument to protrude from the distal end of the insertion portion **6** are arranged.

[0043] The illumination portion **611** includes a light guide that transmits the illumination light output from the light source device **42** to the distal end of the insertion portion **6** and an illumination lens that irradiates the inside of the subject with the illumination light emitted from an emission end of the light guide.

[0044] The imaging portion **612** includes an objective optical system that condenses light (subject image) emitted to the inside of the subject and reflected by the inside of the subject and an imaging element that captures a subject image obtained by condensing the light by the objective optical system. Then, an image signal captured by the imaging element is transmitted to the endoscope imaging device **4** (video processor **41**) via the signal cable.

[0045] The treatment instrument channel **613** is a passage through which a treatment instrument such as a puncture needle inserted inside the insertion portion **6** is caused to protrude to the outside.

[0046] The operating portion **7** is connected to the proximal end side of the insertion portion **6** and accepts various types of operation from a doctor or the like. As illustrated in FIG. 1, the operating portion **7** includes a bending knob **71** for bending operation of the bendable portion **62** and a plurality of operating members **72** for performing various types of operation.

[0047] In addition, the operating portion **7** includes a treatment instrument insertion port **73** (FIG. 1) which communicates with the treatment instrument channel **613** via a tube provided inside the bendable portion **62** and the flexible tube **63** and through which a treatment instrument is inserted.

[0048] The universal cord **8** extends from the operating portion **7** and in which a tube constituting parts of the light guide, the transducer cable, the signal cable, and the pipeline is disposed.

[0049] The endoscope connector **9** is provided at an end of the universal cord **8**. The endoscope connector **9** is further connected with the ultrasound cable **31** and is connected to the video processor **41** and the light source device **42** by being inserted into the endoscope imaging device **4**.

Structure of Ultrasound Transducer

[0050] Next, the structure of the ultrasound probe **10** will be described. FIG. 3 is a schematic structure diagram of the ultrasound probe. As illustrated in FIG. 3, the ultrasound probe **10** has a convex-type ultrasound transducer unit and includes a pair of housings **101**, a substrate **102** positioned between the housings **101**, and a transducer cable **103** connected to the substrate **102**.

[0051] FIG. 4 is an exploded view of the ultrasound probe. As illustrated in FIG. 4, the ultrasound probe **10** includes a transducer array **104** including a plurality of transducers **1041** that are arranged between the housings **101** and that are arrayed in an arc shape.

[0052] FIG. 5 is a cross-sectional view corresponding to line A-A in FIG. 2. As illustrated in FIG. 5, the ultrasound probe **10** includes an ultrasound transducer unit including the transducer array **104**, a first acoustic matching layer **105** and a second acoustic matching layer **106** provided facing (opposed to) the transducer array **104**, and the housings **101** holding the first acoustic matching layer **105** and the second acoustic matching layer **106**, the substrate **102** electrically connected to the transducer array **104**, the transducer cable **103** electrically connected to the substrate **102**, an

acoustic lens **107** covering an outer periphery of the ultrasound transducer unit, a backing material **108** filling the inside of the housings **101**, and wiring **109** and **110** electrically connected to the individual transducers **1041**, the ultrasound probe **10** accommodated in the rigid portion **61**. Note that to provide the first acoustic matching layer **105** and the second acoustic matching layer **106** facing (opposed to) the transducer array **104** includes, for example, a mode in which the first acoustic matching layer **105** and the second acoustic matching layer **106** hold the transducer array **104**. Also included are a mode in which the first acoustic matching layer **105** and the second acoustic matching layer **106** are placed in a state of being in contact with the transducer array **104** and a state in which the first acoustic matching layer **105** and the second acoustic matching layer **106** face the transducer array **104** via a liquid or gel, namely, states not limited to the state of being held.

[0053] The housings **101** hold both end sides in the longitudinal direction of the second acoustic matching layer **106** with the individual transducers **1041** interposed therebetween. The housings **101** is made of resin such as glass epoxy resin and has a pair of plate shapes. The housings **101** preferably holds both of the ends in the longitudinal direction of the second acoustic matching layer **106**. Furthermore, for example, the width of the second acoustic matching layer **106** may be set slightly larger than the interval between the housings **101**. In this case, the second acoustic matching layer **106** may be held by outer peripheries of the housings **101**. A detailed structure of the housings **101** will be described later. The substrate **102** is a flexible substrate and electrically connects the transducer cable **103** and each of the transducers **1041**.

[0054] The transducer cable **103** transmits the pulse signal output from the ultrasound imaging device **3** to each of the transducers **1041** and transmits an echo signal output from each of the transducers **1041** to the ultrasound imaging device **3**.

[0055] The transducer array **104** includes the plurality of transducers **1041** that transmits and receives ultrasonic waves. The transducers **1041** are arrayed along an arc with their longitudinal directions aligned.

[0056] Each of the transducers **1041** is formed of an elongated rectangular parallelepiped, and a pair of electrodes is formed on an outer face thereof. A transducer **1041** further converts a pulse signal input via the transducer cable **103** and a pair of electrodes into an ultrasound pulse and transmits the ultrasound pulse to the subject. The transducer **1041** also converts an ultrasound echo reflected by the subject into an electrical echo signal expressed by a voltage change and outputs the echo signal to the transducer cable **103** via the pair of electrodes. The transducers **1041** are formed using a PMN-PT single crystal, a PMN-PZT single crystal, a PZN-PT single crystal, a PIN-PZN-PT single crystal, or a relaxor-based material. Note that the PMN-PT single crystal is an abbreviation of a solid solution of lead-magnesium niobate and lead titanate. The PMN-PZT single crystal is an abbreviation of a solid solution of lead-magnesium niobate and lead zirconate titanate. The PZN-PT single crystal is an abbreviation of a solid solution of lead zinc-niobate and lead titanate. The PIN-PZN-PT single crystal is an abbreviation of a solid solution of lead indium niobate, lead zinc niobate, and lead titanate. The relaxor-based material is a generic term for three-component piezoelectric materials obtained by adding lead-based composite perovskite, which is a relaxor-based material, to lead zirconate titanate (PZT) for the purpose of increasing the piezoelectric constant and the dielectric constant. The lead-based composite perovskite is represented by $\text{Pb}(\text{B1}, \text{B2})\text{O}_{3}$, where **B1** is any one of magnesium, zinc, indium, or scandium, and **B2** is any one of niobium, tantalum, or tungsten. These materials have an excellent piezoelectric effect. Therefore, even if the size is reduced, the value of the electrical impedance can be reduced, which is preferable from the viewpoint of impedance matching between a pair of electrodes.

[0057] The first acoustic matching layer **105** and the second acoustic matching layer **106** are positioned, with respect to the transducer array **104**, in a direction in which each of the transducers **1041** transmits an ultrasonic wave. The second acoustic matching layer **106** forms a series along

the array direction of the plurality of transducers **1041** and holds the individual transducers **1041**. The first acoustic matching layer **105** and the second acoustic matching layer **106** match acoustic impedances between the transducer array **104** and an observation target in order to efficiently transmit sound (ultrasonic waves) between the transducer array **104** and the observation target. The first acoustic matching layer **105** and the second acoustic matching layer **106** are made of different materials. Note that, in the first embodiment, it is described on the premise that two acoustic matching layers (the first acoustic matching layer **105** and the second acoustic matching layer **106**) are included, however, it is optional whether to provide no acoustic matching layers, a single acoustic matching layer, or three or more acoustic matching layers depending on the characteristics of the transducer array **104** and an observation target.

[0058] The acoustic lens **107** is formed using silicone, polymethylpentene, epoxy resin, polyetherimide, or the like, has one face having a convex or concave shape, has a function of narrowing down ultrasonic waves, and emits ultrasonic waves having passed through the acoustic matching layers to the outside or captures an ultrasound echo from the outside. The acoustic lens **107** can also be provided as desired, and the acoustic lens **107** may not be included.

[0059] The backing material **108** attenuates unnecessary ultrasound vibration generated by the operation of the transducers **1041**. The backing material **108** is formed using a material having a high attenuation rate such as an epoxy resin in which a filler such as alumina or zirconia is dispersed or rubber in which the filler is dispersed. Note that the backing material **108** may not be provided depending on the characteristics of the transducer array **104** and the observation target.

[0060] The wiring **109** is electrically connected to a positive electrode of each of the transducers **1041**. The wiring **110** is electrically connected to a negative electrode of each of the transducers **1041**.

Structure of Housing

[0061] Next, the structure of the housing **101** will be described. In the following description, a first face of a housing **101** positioned on the individual transducers **1041** side is also referred to as an inner face, and a second face located on an opposite side of the first face is also referred to as an outer face.

[0062] FIG. **6** is a diagram illustrating the inner face of the housing. As illustrated in FIG. **6**, a housing **101** includes a conductive portion **1011** having an electrical conductivity, the conductive portion **1011** included over the entire inner face. The conductive portion **1011** may be provided by metal plating such as that of copper on the housing **101** made of an insulating member such as resin or may be provided by attaching a conductive sheet such as copper on the housing **101**. In addition, the conductive portion **1011** may be provided by activating a part of the insulating material. Alternatively, an insulating portion **1012** may be provided on the conductive portion **1011** by oxidizing a part of the conductive material. Note that being conductive means that the electrical conductivity is high enough to drive the transducers **1041**.

[0063] FIG. **7** is a diagram illustrating an outer face of a housing. As illustrated in FIG. **7**, a housing **101** includes an insulating portion **1012** that has an insulating property and that is provided on the outer face. The insulating portion **1012** is provided at an outer edge portion including a region where the individual transducers **1041** are projected in the longitudinal direction. The term “having an insulating property” means that the electrical conductivity is low enough to reduce the electromagnetic noise.

[0064] According to the first embodiment described above, since the conductive portion **1011** is provided on the inner face of the housing **101**, the electromagnetic noise can be reduced. Note that the electromagnetic noise is caused by electromagnetic waves generated by the ultrasound endoscope **2** such as the imaging portion **612**, electromagnetic waves generated by the ultrasound imaging device **3**, the endoscope imaging device **4**, and the display device **5**, and electromagnetic waves generated by various electric devices present around the endoscope system **1** such as other devices in the operating room, a fluorescent light, air conditioners, or others in the operating room.

[0065] Furthermore, since the insulating portion **1012** is provided on the outer edge portion of the outer face of the housing **101**, the conductive portion of the housing **101** is not included at a position close to the outside, and thus even in a case where a large current flows due to lightning or the like or in a case where the acoustic lens **107** is damaged, it is possible to prevent the current from flowing through the subject, and thus, there is high safety. Note that, since the ultrasound probe **10** is housed in the rigid portion **61** (see FIG. 7), a current is prevented from flowing to the subject from portions other than the insulating portion **1012**.

[0066] Incidentally, the conductive portion **1011** preferably includes a region where the individual transducers **1041** are projected in the longitudinal direction. With the conductive portion **1011** covers this region, the effect of reducing the electromagnetic noise can be enhanced.

[0067] In addition, the conductive portion **1011** is provided from the outer edge portion, including the region where the individual transducers **1041** are projected in the longitudinal direction, toward the center of the inner face and preferably has an area that is half or more of an area of the inner face. With the conductive portion **1011** having a sufficiently wide area, the effect of reducing the electromagnetic noise can be enhanced.

[0068] In addition, the housing **101** may include an insulating portion that has an insulating property and that is provided on the outer edge portion of the inner face. By making the outer edge portion of the inner face of the housing **101** insulating, the effect of preventing a current from flowing through the subject can be enhanced.

[0069] In addition, the housing **101** may include an insulating portion that has an insulating property and that is provided on a side face connecting the inner face and the outer face. By making the side face of the housing **101** insulating, the effect of preventing a current from flowing through the subject can be enhanced.

[0070] In addition, an insulating portion **1013** may be provided in a region inside the insulating portion **1012** on the outer face of the housing **101** to enhance the effect of preventing a current from flowing through the subject, or a conductive portion may be provided in this region to enhance the effect of reducing the electromagnetic noise. First Modification

[0071] FIG. 8 is a diagram illustrating an inner face of a housing according to a first modification. As illustrated in FIG. 8, a housing **101a** according to the first modification includes a conductive portion **1011a** provided on an inner face, and a grounding wire is electrically connected to the conductive portion **1011a**. Specifically, wiring **110** electrically connected to a negative electrode of each transducer **1041** is electrically connected to the conductive portion **1011a** by soldering or the like. As a result, the effect of reducing the electromagnetic noise can be enhanced.

Second Modification

[0072] FIG. 9 is a diagram illustrating an inner face of a housing according to a second modification. As illustrated in FIG. 9, a through hole **1014b** communicating from an inner face to an outer face is formed in a housing **101b** according to the second modification. The housing **101b** also includes a conductive portion that has an electrical conductivity and that is provided on the inner face of the through hole **1014b**.

[0073] FIG. 10 is a diagram illustrating the outer face of the housing according to the second modification. As illustrated in FIG. 10, the housing **101b** includes an elliptical conductive portion **1015b** having an electrical conductivity, the conductive portion **1015b** provided around the through hole **1014b** on the outer face. The conductive portion **1015b** on the outer face of the housing **101b** is electrically connected with a conductive portion **1011b** on the inner face via the conductive portion on the inner face of the through hole **1014b**.

[0074] Furthermore, a grounding wire connected to a transducer **1041** is electrically connected to the conductive portion **1015b**. As a result, the conductive portion **1011b** on the inner face is grounded via the conductive portion **1015b** and the conductive portion of the through hole **1014b**, and thus the effect of reducing the electromagnetic noise can be enhanced. In addition, since it is only required to solder the grounding wire (wiring **110**) to the conductive portion **1015b** on the

outer face, workability is better than a case where the grounding wire is soldered to the inner face. Furthermore, since the conductive portion **1015b** is provided on the outer face, whether or not the housing **101b** is grounded can be inspected from the outside of the housing **101b** by a tester or the like, and thus workability is good.

[0075] Note that the conductive portion **1015b** may have any shape as long as the grounding wire is easily soldered and may not be an ellipse.

Third Modification

[0076] FIG. **11** is a diagram illustrating an outer face of a housing according to a third modification. As illustrated in FIG. **11**, a housing **101c** according to a third modification includes a semicircular portion (insulating portion **1012c** and insulating portion **1013c**) having a semicircular shape and an extension portion **1016c** having a long side substantially coinciding with the diameter (long diameter) of the semicircular portion and extending to a side opposite to the arc of the semicircular portion. Note that the semicircular portion may have a shape obtained by cutting a part of an ellipse.

[0077] With the extension portion **1016c**, the housing **101c** and a transducer array **104** can be accurately aligned. Note that the extension portion **1016c** may be cut off after aligning the housing **101c** and the transducer array **104** and fixing the housing **101c** and the transducer array **104** with an adhesive agent or the like.

Second Embodiment

[0078] FIG. **12** is a schematic structure diagram of an ultrasound probe according to a second embodiment. FIG. **12** is a diagram in which a part of an ultrasound probe **10A**, which is a radial-type ultrasound transducer, is cut out. The ultrasound probe **10A** includes a pair of housings **101Aa** and **101Ab**, a transducer array **104A** in which a plurality of transducers that transmits and receives ultrasonic waves is arrayed with their longitudinal directions aligned, and a first acoustic matching layer **105A** and a second acoustic matching layer **106A** that are positioned in a direction in which the individual transducers transmit ultrasonic waves, the first acoustic matching layer **105A** and the second acoustic matching layer **106A** facing (opposed to) the individual transducers.

[0079] FIG. **13** is a diagram illustrating an inner face of a housing on the distal end side. As illustrated in FIG. **13**, the housing **101Aa** includes a conductive portion **1011Aa** that has an electrical conductivity and that is provided over the entire inner face.

[0080] A through hole **1014Aa** communicating from the inner face to the outer face is formed in the housing **101Aa**. In addition, the housing **101Aa** includes a conductive portion that has an electrical conductivity and that is provided on an inner face of the through hole **1014Aa**.

[0081] FIG. **14** is a diagram illustrating the outer face of the housing on the distal end side. As illustrated in FIG. **14**, the housing **101Aa** includes an insulating portion **1012Aa** that has an insulating property and that is provided on the outer face. The insulating portion **1012Aa** is provided at an outer edge portion including a region where the individual transducers are projected in the longitudinal direction. In addition, the housing **101Aa** includes an elliptical conductive portion **1015Aa** that has an electrical conductivity and that is provided around the through hole **1014Aa** on the outer face.

[0082] FIG. **15** is a diagram illustrating an inner face of the housing on the proximal end side. As illustrated in FIG. **15**, the housing **101Ab** includes a conductive portion **1011Ab** that has an electrical conductivity and that is provided over the entire inner face. A hole **1016Ab** through which a transducer cable is inserted is formed at the center of the housing **101Ab**.

[0083] In the housing **101Ab**, a through hole **1014Ab** communicating from the inner face to the outer face is formed. In addition, the housing **101Ab** includes a conductive portion that has an electrical conductivity and that is provided on an inner face of the through hole **1014Ab**.

[0084] FIG. **16** is a diagram illustrating the outer face of the housing on the proximal end side. As illustrated in FIG. **16**, the housing **101Ab** includes an insulating portion **1012Ab** that has an insulating property and that is provided on the outer face. The insulating portion **1012Ab** is

provided at an outer edge portion including a region where the individual transducers are projected in the longitudinal direction. In addition, the housing **101Ab** includes an elliptical conductive portion **1015Ab** that has an electrical conductivity and that is provided around the through hole **1014Ab** on the outer face.

[0085] According to the second embodiment described above, since the conductive portion **1011Aa** and the conductive portion **1011Ab** are provided on the inner faces of the housing **101Aa** and the housing **101Ab**, the electromagnetic noise can be reduced. Furthermore, since the insulating portion **1012Aa** and the insulating portion **1012Ab** are provided on the outer faces of the housing **101Aa** and the housing **101Ab**, even in a case where a large current flows due to lightning or the like, it is possible to prevent a current from flowing through a subject.

[0086] In addition, a grounding wire connected to the transducers is electrically connected to the conductive portion **1015Aa** and the conductive portion **1015Ab**. As a result, the conductive portion **1011Aa** and the conductive portion **1011Ab** on the inner face are grounded via the conductive portions of the through hole **1014Aa** and the through hole **1014Ab**, and thus the effect of reducing the electromagnetic noise can be enhanced. In addition, since it is only required to ground solder the grounding wire to the conductive portion **1015Aa** and the conductive portion **1015Ab** on the outer face, workability is better than in a case of soldering the grounding wire to the inner face. Furthermore, since the conductive portion **1015Aa** and the conductive portion **1015Ab** are provided on the outer face, it is possible to inspect whether the housing **101Aa** and the housing **101Ab** are grounded by a tester or the like from the outside of the housing **101Aa** and the housing **101Ab**, and thus workability is good.

[0087] Note that an insulating portion **1013Aa** and an insulating portion **1013Ab** may be provided in regions inside the insulating portion **1012Aa** and the insulating portion **1012Ab** on the outer faces of the housing **101Aa** and the housing **101Ab** to enhance the effect of preventing a current from flowing through a subject, or a conductive portion may be provided in these regions to enhance the effect of reducing the electromagnetic noise.

Third Embodiment

[0088] FIG. **17** is a schematic structure diagram of an ultrasound probe according to a third embodiment. FIG. **17** is an exploded perspective view of a part of an ultrasound probe **10B** which is a linear-type ultrasound transducer. The ultrasound probe **10B** includes a pair of housings **101B**, a transducer array **104B** in which a plurality of transducers that transmits and receives ultrasonic waves is arrayed with their longitudinal directions aligned, and an acoustic matching layer **105B** that is positioned in a direction in which the individual transducers transmit ultrasonic waves and holds the transducers.

[0089] FIG. **18** is a diagram illustrating an inner face of a housing. As illustrated in FIG. **18**, a housing **101B** includes a conductive portion **1011B** that has an electrical conductivity and that is provided over the entire inner face.

[0090] A through hole **1014B** communicating from the inner face to the outer face is formed in the housing **101B**. The housing **101B** also includes a conductive portion that has an electrical conductivity and that is provided on an inner face of the through hole **1014B**.

[0091] FIG. **19** is a diagram illustrating the outer face of the housing. As illustrated in FIG. **19**, the housing **101B** includes an insulating portion **1012B** that has an insulating property and that is provided on the outer face. The insulating portion **1012B** is provided at an outer edge portion including a region where the individual transducers are projected in the longitudinal direction. In addition, the housing **101B** includes an elliptical conductive portion **1015B** that has an electrical conductivity and that is provided around the through hole **1014B** on the outer face. According to the third embodiment described above, since the conductive portion **1011B** is provided on the inner face of the housing **101B**, the electromagnetic noise can be reduced. Furthermore, since the insulating portion **1012B** is provided on the outer face of the housing **101B**, even in a case where a large current flows due to lightning or the like, it is possible to prevent a current from flowing

through a subject.

[0092] Furthermore, a grounding wire connected to a transducer is electrically connected to the conductive portion **1015B**. As a result, the conductive portion **1011B** on the inner face is grounded via the conductive portion of the through hole **1014B**, and thus the effect of reducing the electromagnetic noise can be enhanced. In addition, since it is only required to solder the grounding wire to the conductive portion **1015B** on the outer face, workability is better than a case where the grounding wire is soldered to the inner face. Furthermore, since the conductive portion **1015B** is provided on the outer face, whether or not the housing **101B** is grounded can be inspected from the outside of the housing **101B** by a tester or the like, and thus workability is good.

[0093] Note that an insulating portion **1013B** may be provided in a region inside the insulating portion **1012B** on the outer face of the housing **101B** to enhance the effect of preventing a current from flowing through a subject, or a conductive portion may be provided in this region to enhance the effect of reducing the electromagnetic noise.

Other Modifications

[0094] FIG. **20** is a cross-sectional view of an ultrasound probe. FIG. **20** is a diagram illustrating the same cross section as that is FIG. **5**, however, transducer cables **103Ca** and **103Cb** not illustrated in FIG. **5** are illustrated. Each transducer **1041** and one of the transducer cables **103Ca** and **103Cb** need to be connected in association with numbers corresponding to each other in order to control which transducer **1041** is caused to transmit what ultrasound pulse. The transducer cable **103Ca** and the transducer cable **103Cb** have different colors in the appearance. Cables with odd numbers are classified to be included in the transducer cable **103Ca**, and the cables with even numbers are classified to be included in the transducer cable **103Cb**. As a result, when connecting the individual transducers **1041** and the respective cables of the transducer cables **103Ca** and **103Cb** in association with numbers corresponding to each other, it is possible to facilitate the work of searching for a corresponding cable.

[0095] According to the disclosure, it is possible to implement an ultrasound probe, an ultrasound transducer unit, and an ultrasound endoscope that reduce electromagnetic noise and have high safety.

[0096] Additional advantages and modifications will readily occur to those skilled in the art. Therefore, the disclosure in its broader aspects is not limited to the specific details and representative embodiments shown and described herein. Accordingly, various modifications may be made without departing from the spirit or scope of the general inventive concept as defined by the appended claims and their equivalents.

Claims

1. An ultrasound probe comprising: a plurality of transducers arrayed with a longitudinal direction, each of the plurality of transducers extending in a direction intersecting the longitudinal direction; a first plate including a through hole, the through hole penetrating the first plate in the direction; and a second plate facing the first plate, wherein the plurality of transducers are located between the first plate and the second plate to extend in the direction.
2. The ultrasound probe according to claim 1, wherein the first plate includes: a first inner surface; and a first material being electrically conductive, the first material located on the first inner surface.
3. The ultrasound probe according to claim 1, wherein the first plate includes: a first edge; and a first material being electrically insulative, the first material located on the first inner surface.
4. The ultrasound probe according to claim 1, wherein the through hole is defined by an inner surface, the first plate includes a first material being electrically conductive, the first material located on the inner surface.
5. The ultrasound probe according to claim 1, wherein the first plate includes: an outer surface; and a first material being electrically conductive, the first material located on the outer surface and

around an opening of the through hole.

6. The ultrasound probe according to claim 2, wherein the first plate includes: an outer surface; and a second material being electrically conductive, the second material located on the outer surface and around an opening of the through hole.

7. The ultrasound probe according to claim 6, wherein the through hole is defined by a second inner surface, the first plate includes a third material being electrically conductive, the third material located on the second inner surface, wherein the second material is electrically connected to the first material via the third material.

8. An endoscope comprising: the ultrasound probe according to claim 1; and an insertion portion having a distal end portion, wherein the ultrasound probe is located in the distal end portion.

9. An ultrasound probe comprising: a plurality of transducers arrayed with a longitudinal direction, each of the plurality of transducers extending in a direction intersecting the longitudinal direction; a first plate including: a first inner surface; a first material being electrically conductive, the first material located on the first inner surface; a first edge; and a second material being electrically insulative, the second material located on the first edge; a second plate including: a second inner surface facing the first inner surface; and a third material being electrically conductive, the third material located on the second inner surface, and wherein the plurality of transducers are located between the first inner surface and the second inner surface in the direction.

10. The ultrasound probe according to claim 9, wherein each of the plurality of transducers has a pair of terminal ends.

11. The ultrasound probe according to claim 10, wherein the first inner surface and the second inner surface are adjacent to the pair of terminal ends.

12. The ultrasound probe according to claim 9, wherein a fourth material electrically connects the first material and the third material.

13. An endoscope comprising: the ultrasound probe according to claim 9; and an insertion portion having a distal end portion, wherein the ultrasound probe is located in the distal end portion.

14. An ultrasound probe comprising: a plurality of transducers arrayed with a peripheral direction, each of the plurality of transducers extending in a longitudinal direction; a first plate including: a first inner surface; a first material being electrically conductive, the first material located on the first inner surface; and a second plate including: a second inner surface facing the first inner surface; and a second material being electrically conductive, the second material located on the second inner surface, and wherein the plurality of transducers are located between the first inner surface and the second inner surface to extend in the longitudinal direction.

15. The ultrasound probe according to claim 14, wherein the second plate includes a first through hole (**1014Ab**) and a second through hole (**1016Ab**), the first through hole and the second through hole penetrate the second plate.

16. The ultrasound probe according to claim 15, wherein the first through hole is defined by a third inner surface, the second plate includes a third material being electrically conductive and located on the third inner surface.

17. The ultrasound probe according to claim 15, wherein the first plate includes a third through hole penetrating the first plate.

18. The ultrasound probe according to claim 17, wherein the first through hole is defined by a third inner surface, the first plate includes a third material being electrically conductive and located on the third inner surface.

19. The ultrasound probe according to claim 14, wherein the first plate includes an outer surface and a third material being electrically insulative and located on the outer surface.

20. An endoscope comprising: the ultrasound probe according to claim 14; and an insertion portion having a distal end portion, wherein the ultrasound probe is located in the distal end portion.
