

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250276816

Kind Code

A1

Publication Date

September 04, 2025

Inventor(s)

Ishikawa; Mitsuru

FLYING APPARATUS AND METHOD FOR CONTROLLING THE SAME

Abstract

Provided is a flying apparatus and a method for controlling the same which are capable of precisely measuring a remaining charge of a battery with a simple configuration. A flying apparatus **10** comprises a rotor **11**, a motor **12**, a power converting unit **14**, a battery **21**, and a calculation control unit **15**. The rotor **11** rotates to generate thrust for causing an airframe base unit **16** to float, and the motor **12** is supplied with an electric power from the battery **21** to rotationally drive the rotor **11**. The calculation control unit **15** generates an instruction signal to bring the airframe base unit **16** into a certain positional posture. The power converting unit **14** adjusts an electric power to be supplied from the battery **21** to the motor **12** based on the instruction signal inputted. Further, the calculation control unit **15** estimates a remaining charge of the battery **21** based on the instruction signal.

Inventors: Ishikawa; Mitsuru (Ota-shi, Gunma, JP)

Applicant: ISHIKAWA ENERGY RESEARCH CO., LTD. (Ota-shi, Gunma, JP)

Family ID: 84027201

Assignee: ISHIKAWA ENERGY RESEARCH CO., LTD. (Ota-shi, Gunma, JP)

Appl. No.: 18/857754

Filed (or PCT Filed): August 21, 2023

PCT No.: PCT/JP2023/029976

Foreign Application Priority Data

JP 2022-143239

Sep. 08, 2022

Publication Classification

Int. Cl.: B64U10/14 (20230101); B64U30/295 (20230101); B64U50/30 (20230101); H02P29/40 (20160101)

U.S. Cl.:

CPC B64U10/14 (20230101); B64U30/295 (20230101); B64U50/30 (20230101); H02P29/40 (20160201);

Background/Summary

TECHNICAL FIELD

[0001] The present invention relates to a flying apparatus and a method for controlling the same.

BACKGROUND ART

[0002] A flying apparatus capable of flying in the air in an unmanned manner has been conventionally known. Such a flying apparatus is capable of flying in the air by using thrust of a rotor which is rotationally driven about a vertical axis.

[0003] As the fields to which flying apparatuses are applied, for example, a transportation field, a survey field, an imaging field, an agriculture field, and the like are considered. In the case where a flying apparatus is applied to such a field, the flying apparatus is equipped with various devices or drugs.

[0004] When considering flying a flying apparatus stably, it is necessary to measure a remaining charge of a battery included in the flying apparatus. Patent Literature 1 describes estimating a remaining charge of a battery during the flight of a flying apparatus.

[0005] Patent Literature 1 describes a matter of estimating the amount of charge of the battery based on one or a plurality of values among a battery voltage, a battery temperature, and a current. Further, Patent Literature 1 also describes calculating a calculated remaining charge value called SOC by measuring the battery voltage, the current, and the battery temperature, and estimating the amount of charge. Moreover, Patent Literature 1 also describes correcting the amount of charge of the battery estimated by the above-mentioned method, based on one or a plurality of values among an actual time of use, an ambient temperature, and the like of the battery.

CITATION LIST

Patent Literature

[0006] Patent Literature 1: International Publication No. WO2020/004366

SUMMARY OF INVENTION

Technical Problem

[0007] However, in the flying apparatus described in the above-described Patent Literature 1, there has been room for improvement from the viewpoint of measuring the remaining charge of the battery of the flying apparatus precisely at low cost.

[0008] Specifically, although it is possible to estimate the remaining charge of the battery based on the voltage of the electric power supplied from the battery, there has been a problem that the remaining charge cannot be precisely estimated by such a method.

[0009] This problem will be described with reference to FIG. 6. In FIG. 6, the horizontal axis indicates SOC, and the vertical axis indicates the voltage of the battery. Here, SOC is an abbreviation of State Of Charge, and is an index representing the charging rate or the charging state of the battery.

[0010] In general, SOC and battery voltage have a linear relation. That is, a large battery voltage indicates large SOC. In FIG. 6, the linear relation between SOC and battery voltage is indicated by a solid line. However, the linear relation varies depending on the state of the battery and the

external environment. For example, the linear relation varies depending on the degradation with time of the battery and the external temperature environment. In FIG. 6, a region in which the linear relation can vary is indicated by hatching. From this, it has not been easy to uniquely calculate SOC from a battery voltage value.

[0011] In addition, it is also possible to estimate the remaining charge of the battery based on a current value of an electric power supplied from the battery. However, since the estimation method based on a current value needs a sensor dedicated for measuring the current value, there has been a problem that such a measure brings about an increase in cost and an increase in weight.

[0012] The present invention has been made in view of the above-described circumstances, and an object thereof is to provide a flying apparatus and a method for controlling the same which are capable of precisely measuring a remaining charge of a battery with a simple configuration.

Solution to Problem

[0013] A flying apparatus of the present invention comprises: a rotor; a motor; a power converting unit; a battery; and a calculation control unit, wherein the rotor rotates to generate thrust for causing an airframe base unit to float, the motor is supplied with an electric power from the battery to rotationally drive the rotor, the calculation control unit generates an instruction signal to bring the airframe base unit into a certain positional posture, the power converting unit adjusts the electric power to be supplied from the battery to the motor based on the instruction signal inputted, and further the calculation control unit estimates a remaining charge of the battery based on the instruction signal.

[0014] The present invention is a method for controlling a flying apparatus including a rotor, a motor, a power converting unit, a battery, and a calculation control unit, the method comprising: rotating the rotor to generate thrust for causing an airframe base unit to float; supplying the motor with an electric power from the battery to rotationally drive the rotor; causing the calculation control unit to generate an instruction signal to bring the airframe base unit into a certain positional posture; causing the power converting unit to adjust the electric power to be supplied from the battery to the motor based on the instruction signal inputted; and further causing the calculation control unit to estimate a remaining charge of the battery based on the instruction signal.

Advantageous Effects of Invention

[0015] According to the flying apparatus of the present invention, the remaining charge of the battery can be precisely estimated without need of a sensor dedicated for measuring a current value or a voltage value of the battery, by estimating the remaining charge of the battery based on the instruction signal.

Description

BRIEF DESCRIPTION OF DRAWINGS

[0016] FIG. 1A is a top view showing a flying apparatus according to an embodiment of the present invention.

[0017] FIG. 1B is a front view showing the flying apparatus according to the embodiment of the present invention.

[0018] FIG. 2 is a block diagram showing a connection configuration of the flying apparatus according to the embodiment of the present invention.

[0019] FIG. 3 is a flowchart showing a method for calculating an estimated weight value of a transported object in the flying apparatus according to the embodiment of the present invention.

[0020] FIG. 4 is a graph showing changes with time of a DUTY value and a DUTY integrated value in the flying apparatus according to the embodiment of the present invention.

[0021] FIG. 5 is a graph showing a relation between the DUTY integrated value and SOC in the flying apparatus according to the embodiment of the present invention.

[0022] FIG. 6 is a graph showing a relation between a battery voltage and SOC in a flying apparatus according to a background art.

DESCRIPTION OF EMBODIMENTS

[0023] Hereinafter, a flying apparatus **10** according to the present embodiment will be described with reference to the drawings. In the following description, the same members are denoted by the same reference signs in principle, and repetitive description will be omitted. In addition, in the following description, upper, lower, front, rear, left, and right directions are used, where the left and right directions are left and right directions in the case where the flying apparatus **10** is viewed from the front side in FIG. 1A.

[0024] FIG. 1A is a top view showing the flying apparatus **10**, and FIG. 1B is a front view showing the flying apparatus **10**.

[0025] With reference to FIG. 1A, the flying apparatus **10** mainly includes an airframe base unit **16**, a power unit which is mounted on the airframe base unit **16** and is not shown here, arms **271** and the like which extend from peripheral portions of the airframe base unit **16** to a periphery, motors **121** and the like which are disposed on outer end portions of the arms **271** and the like, and rotors **111** and the like which are rotated by the motors **121** and the like. In the following description, the motors **121** and the like are collectively referred to as motors **12**, and the rotors **111** and the like are collectively referred to as rotors **11**.

[0026] The flying apparatus **10** is capable of floating and moving in the air by causing the motors **121** and the like to rotate the rotors **111** and the like at certain rotation speeds by using an electric power obtained from a battery **21** housed in the airframe base unit **16**.

[0027] The airframe base unit **16** is disposed at the center of the flying apparatus **10**, and various devices, which are not shown here, are housed in the airframe base unit **16**. The outer surface of the airframe base unit **16** is covered with a synthetic resin plate or a steel plate which is molded in a predetermined shape.

[0028] The arm **271**, the arm **272**, the arm **273**, and the arm **274** extend outward from a power converting unit **14**.

[0029] The motor **121** and the rotor **111** are disposed in an outer end portion of the arm **271**. The motor **122** and the rotor **112** are disposed in an outer end portion of the arm **272**. The motor **123** and the rotor **113** are disposed in an outer end portion of the arm **273**. The motor **124** and the rotor **114** are disposed in an outer end portion of the arm **274**. Here, the rotors **111** and the like rotate to generate thrust for causing the airframe base unit **16** to float. In addition, the motors **121** and the like rotationally drive the rotors **111** and the like.

[0030] With reference to FIG. 1B, the leg portion **32** and the leg portion **33**, which come into contact with the ground at the time of landing, are disposed on a lower portion of the airframe base unit **16**. The leg portion **32** and the leg portion **33** are members which are also referred to as skids. In the state where the flying apparatus **10** is landing, the lower ends of the leg portion **32** and the leg portion **33** come into contact with the ground.

[0031] FIG. 2 is a block diagram showing a connection configuration of the flying apparatus **10**.

[0032] The flying apparatus **10** mainly includes the motors **12** and the like, a flight sensor **13**, a power converting unit **14**, and a calculation control unit **15**. Moreover, the flying apparatus **10** includes a communication unit **25**, a battery **21**, and the power converting unit **14**. An operating device **28** is a device which the operator who operates the flying apparatus **10** manipulates on the ground. A communication unit **26**, a display device **22**, and a display unit **23** are set near the operator.

[0033] The flight sensor **13** measures physical amounts acting on the airframe base unit **16** and transmits signals indicating the magnitudes of the physical amounts to the calculation control unit **15**. Specifically, sensors included in the flight sensor **13** are, for example, an acceleration sensor, an angular rate sensor, a geomagnetic sensor, an atmospheric pressure sensor, and a GNSS antenna. The acceleration sensor detects changes in tilt and movement as physical amounts. The angular rate

sensor detects changes in tilt and direction as physical amounts. The geomagnetic sensor detects a direction as a physical amount by means of a magnetic force. The atmospheric pressure sensor detects the altitude as a physical amount. The GNSS antenna specifies the position.

[0034] The calculation control unit **15** includes a calculation device composed of a CPU (Central Processing Unit) and a storage device composed of a RAM (Random Access Memory) and a ROM (Read Only Memory), and controls the operation of the entire flying apparatus **10**. As described later, the calculation control unit **15** adjusts the amount of electric power to be supplied to the motors **121** and the like based on the signals inputted from the flight sensor **13**. Moreover, as described later, the calculation control unit **15** calculates SOC which corresponds to the remaining battery charge of the battery **21** based on the magnitude of an instruction signal.

[0035] The calculation control unit **15** includes a flight controller **17** and a companion controller **24**.

[0036] The flight controller **17** generates an instruction signal for obtaining a predetermined positional posture, moving speed, and the like of the flying apparatus **10** based on the signals inputted from the flight sensor **13**. As this instruction signal, a DUTY value in the PWM control can be employed, for example. Since the present embodiment includes the four motors **121**, **122**, **123**, and **124**, a DUTY value is calculated for each motor **121**. Here, as the instruction signal, an index other than a DUTY value in the PWM control can also be employed, and for example, an index in the PFM control, an index in the pulse height modulation method, or the like can be employed.

[0037] The companion controller **24** calculates the SOC of the battery **21** based on information inputted from the flight controller **17**, for example, information inputted from the flight sensor **13**, information indicating the voltage of the battery **21**, and the like.

[0038] The power converting unit **14** includes an ESC **141** to an ESC **144**. Here, ESC is abbreviation of Electric Speed Controller, and is an electronic device which controls the number of revolutions of the motor **12**. The power converting unit **14** receives an electric power supplied from the battery **21**, generates an alternating-current power having a predetermined frequency based on the DUTY value supplied from the calculation control unit **15**, and supplies the alternating-current power to each motor **12**.

[0039] The ESC **141** is disposed between the motor **121** and the calculation control unit **15** and the battery **21** and controls the number of revolutions of the motor **121**. The ESC **142** is disposed between the motor **122** and the calculation control unit **15** and the battery **21** and controls the number of revolutions of the motor **122**. The ESC **143** is disposed between the motor **123** and the calculation control unit **15** and the battery **21** and controls the number of revolutions of the motor **123**. The ESC **144** is disposed between the motor **124** and the calculation control unit **15** and the battery **21** and controls the number of revolutions of the motor **124**. When the DUTY values inputted from the flight controller **17** are large, the ESC **141** to the ESC **144** rotate the motor **121** to the motor **124** at a high speed.

[0040] Here, the basic flight operation of the flying apparatus **10** will be described. The flying apparatus **10** is capable of executing each operation of an ascending operation, a hovering operation, a moving operation, and a descending operation. The operation of the flying apparatus **10** is executed by the flight controller **17** based on a command transmitted from the operating device **28** based on the manipulation of the operator.

[0041] In each of the above-described operations, the flight controller **17** adjusts the rotation speeds of the motor **121** to the motor **124** to obtain a certain posture of the flying apparatus **10** based on information inputted from the acceleration sensor and the angular rate sensor included in the flight sensor **13**.

[0042] In the ascending operation, the flight controller **17** rotates the motors **12** at a relatively high speed such that the flying apparatus **10** ascends to a certain altitude. The flight controller **17** basically outputs substantially equal DUTY values to the ESC **141** to the ESC **144** to make the

rotation speeds of the motor **121** to the motor **124** substantially equal to one another. In addition, once the flying apparatus **10** is determined to have ascended to a certain altitude based on information inputted from the atmospheric pressure sensor included in the flight sensor **13**, the flight controller **17** executes the hovering operation of maintaining the altitude of the flying apparatus **10** at a substantially constant level.

[0043] In the hovering operation, the flight controller **17** adjusts the rotation speeds of the motor **121** to the motor **122** such that the altitude of the flying apparatus **10** becomes substantially constant based on information inputted from the atmospheric pressure sensor included in the flight sensor **13**. Here, basically, the flight controller **17** outputs substantially equal DUTY values to the ESC **141** to the ESC **144** to make the rotation speeds of the motor **121** to the motor **124** substantially equal to one another.

[0044] In the moving operation, the flight controller **17** adjusts the rotation speeds of the motor **121** to the motor **124** such that the flying apparatus **10** can move in each of the front, rear, left, and right directions at a certain speed. For example, the flight controller **17** makes the rotation speeds of the motor **121** and the motor **122** higher than the rotation speeds of the motor **123** and the motor **124**. That is, the flight controller **17** makes the DUTY values to be outputted to the ESC **141** and the ESC **142** larger than the DUTY values to be outputted to the ESC **143** and the ESC **144**. In this way, with reference to FIG. **1A**, the rotor **111** and the rotor **112** rotate at higher speeds than the rotor **113** and the rotor **114**, so that the airframe base unit **16** of the flying apparatus **10** is brought into a tilted posture and the flying apparatus **10** moves toward a certain direction.

[0045] Thereafter, once it is detected that the flying apparatus **10** has reached a certain position based on outputs of the GNSS antenna and the like included in the flight sensor **13**, the flight controller **17** execute a brake operation. For example, the flight controller **17** makes the rotation speeds of the motor **121** and the motor **122** lower than the rotation speeds of the motor **123** and the motor **124**. That is, the flight controller **17** makes the DUTY values to be outputted to the ESC **143** and the ESC **144** larger than the DUTY values to be outputted to the ESC **141** and the ESC **142**. In this way, with reference to FIG. **1A**, the rotor **111** and the rotor **112** rotate at lower speeds than the rotor **113** and the rotor **114**, so that the planar movement of the flying apparatus **10** can be stopped. Thereafter, the flight controller **17** executes the hovering operation.

[0046] In the descending operation, the flight controller **17** rotates the motors **12** at a relatively low speed such that the flying apparatus **10** descends to a certain altitude. The flight controller **17** basically outputs substantially equal DUTY values to the ESC **141** to the ESC **144** to make the rotation speeds of the motor **121** to the motor **124** substantially equal to one another. In addition, once the flying apparatus **10** is determined to have descended to a certain altitude based on information inputted from the atmospheric pressure sensor included in the flight sensor **13**, the flight controller **17** executes the hovering operation of maintaining the altitude of the flying apparatus **10** at a substantially constant level.

[0047] FIG. **3** is a flowchart showing a method for calculating the SOC of the battery **21** in the flying apparatus **10**.

[0048] In step **S10**, the flight sensor **13** measures physical amounts. Specifically, the acceleration sensor, the angular rate sensor, the geomagnetic sensor, the atmospheric pressure sensor, the GNSS antenna, and the like included in the flight sensor **13** measure the positional posture and the like of the flying apparatus **10**. The physical amounts measured by the flight sensor **13** are inputted into the flight controller **17**. In addition, the operation state during the flight of the flying apparatus **10** is also inputted into the flight controller **17**.

[0049] In step **S11**, the flight controller **17** calculates DUTY values as instruction signals based on the aforementioned physical amounts. The flight controller **17** outputs the DUTY values based on various kinds of information, the operation state, and the like inputted in step **S10**. The flight controller **17** calculates the DUTY value for each of the ESC **141** to the ESC **144** shown in FIG. **2**.

[0050] In step **S12**, the companion controller **24** calculates an estimated SOC of the battery **21**.

Specifically, the companion controller **24** sets in advance a conversion formula indicating a correlation between a DUTY integrated value, which is an integrated value of DUTY values, and SOC. Next, the companion controller **24** calculates a DUTY integrated value, which is an integrated value of DUTY values after the flight of the flying apparatus **10** is started, at a certain interval. Next, the companion controller **24** calculates the SOC of the battery **21** by using this conversion formula.

[0051] FIG. **4** is a graph showing changes with time of the DUTY value and the DUTY integrated value in the flying apparatus **10**. In this graph, the horizontal axis indicates elapsed time. The vertical axis on the left indicates the DUTY value. The vertical axis on the right indicates the DUTY integrated value.

[0052] Here, DUTY values outputted from the flight controller **17** respectively to the ESC **141** to the ESC **144** in order to rotate the four motors **121** to **124** included in the flying apparatus **10** are shown. The DUTY value outputted to the ESC **141** is indicated by a solid line, the DUTY value outputted to the ESC **142** is indicated by a dashed line, the DUTY value outputted to the ESC **143** is indicated by a dash-dot line, and the DUTY value outputted to the ESC **144** is indicated by a dash-dot-dot line. In addition, the DUTY integrated value is indicated by a thick solid line.

[0053] As is clear from the graph shown in FIG. **4**, there is a positive correlation between the continuous flight time of the flying apparatus **10** and the DUTY integrated value. That is, as the flight time increases, the DUTY integrated value increases. Here, with reference to FIG. **2**, the DUTY integrated value may be an integrated value of DUTY values supplied to one ESC **141**, or may be calculated from a plurality of DUTY values of the ESC **141** to the ESC **144**. In the case of calculating the DUTY integrated value from the ESC **141** to the ESC **144**, the DUTY integrated value may be calculated by individually integrating the DUTY values in each of the ESC **141** to the ESC **144**, and combining the DUTY values integrated individually.

[0054] Next, the companion controller **24** calculates the SOC from the DUTY integrated value. Specifically, the companion controller **24** creates a relational formula indicating a relation between the DUTY integrated value and the SOC by using a statistical method such as a least-squares method or the like. The companion controller **24** calculates the SOC from the DUTY integrated value by using this relational formula.

[0055] Here, in consideration of the fact that the longer the continuous flight time is, the smaller the SOC is, there is a negative correlation between the SOC and the DUTY integrated value. In addition, even with a similar flight time, the DUTY value to be supplied to the power converting unit **14** increases when the motor **12** is to be rotated at a high speed, and as a result, a consumed electric power increases, so that the SOC decreases. With this taken into account, in the present embodiment based on the DUTY integrated value, both of the flight time and the rotation can be considered, so that the SOC is precisely calculated.

[0056] In step **S13**, the companion controller **24** and the flight controller **17** transmit information indicating the SOC of the battery **21**. Specifically, the information indicating the SOC is transmitted from the flying apparatus **10** to the display device **22** through the communication unit **25** and the operating device **28** by means of wireless communication.

[0057] In step **S14**, the SOC of the battery **21** is displayed on the display unit **23** of the display device **22**. By visually checking the display unit **23**, the operator can know the SOC of the battery **21**. Therefore, if the SOC of the battery **21** becomes a certain level or lower, the operator can move the flying apparatus **10** to a certain position, and charge or replace the battery **21**. In this way, the fall of the flying apparatus **10** due to a reduced SOC of the battery **21** can be suppressed.

[0058] The aforementioned present embodiment makes it possible to achieve major advantageous effects as follows.

[0059] A flying apparatus of the present invention comprises: a rotor; a motor; a power converting unit; a battery; and a calculation control unit, wherein the rotor rotates to generate thrust for causing an airframe base unit to float, the motor is supplied with an electric power from the battery

to rotationally drive the rotor, the calculation control unit generates an instruction signal to bring the airframe base unit into a certain positional posture, the power converting unit adjusts the electric power to be supplied from the battery to the motor based on the instruction signal inputted, and further the calculation control unit estimates a remaining charge of the battery based on the instruction signal. According to the flying apparatus of the present invention, the remaining charge of the battery can be precisely estimated without need of a sensor dedicated for measuring a current value or a voltage value of the battery, by estimating the remaining charge of the battery based on the instruction signal.

[0060] In addition, in the flying apparatus of the present invention, the instruction signal is a DUTY value. According to the flying apparatus of the present invention, the remaining charge of the battery can be precisely estimated from the DUTY value.

[0061] In addition, in the flying apparatus of the present invention, the instruction signal is an integrated value of a DUTY value. According to the flying apparatus of the present invention, the remaining charge of the battery can be precisely estimated from the integrated value (DUTY integrated value) of the DUTY value.

[0062] In addition, in the flying apparatus of the present invention, the instruction signal is an integrated value of an average value of a DUTY value. According to the flying apparatus of the present invention, the remaining charge of the battery can be further precisely estimated from the integrated value of the average value of the DUTY value.

[0063] In addition, the flying apparatus of the present invention comprises: a plurality of the rotors; a plurality of the motors; and a plurality of the power converting units, wherein the calculation control unit estimates the remaining charge of the battery from an integrated value of DUTY values supplied respectively to the plurality of power converting units. According to the flying apparatus of the present invention, the SOC can be precisely calculated from the integrated value of the plurality of DUTY values.

[0064] In addition, in the flying apparatus of the present invention, the calculation control unit calculates an initial value or an intermediate value of the remaining charge from a current value or a voltage value of the battery, calculates a decrease value of the remaining charge from a DUTY integrated value based on a conversion formula set in advance, and calculates the remaining charge at the time by reducing the decrease value of the remaining charge from the initial value or the intermediate value of the remaining charge. According to the flying apparatus of the present invention, the remaining charge during the flight can be precisely calculated by calculating the initial value or the intermediate value of the remaining charge from the current value or the like, and calculating the remaining charge based on these values, for example, even when the remaining charge at the time of takeoff is about half of the battery capacity.

[0065] Although the embodiments of the present invention have been described above, the present invention is not limited to these, and modification is possible without departing from the gist of the present invention. In addition, the aforementioned embodiments can be combined with each other.

[0066] For example, with reference to FIG. 3, the flying apparatus **10** may be configured to return to a predetermined position when the remaining charge calculated in step S12 becomes a certain level or lower. This makes it possible to suppress the fall of the flying apparatus **10** due to shortage of the remaining charge.

[0067] Moreover, although in the aforementioned present embodiment, the calculation control unit **15** calculates the SOC from the DUTY integrated value, the SOC can also be calculated by combining the current value or the voltage value and the DUTY integrated value. For example, first, the calculation control unit **15** calculates an initial value or an intermediate value of the SOC from a current value or a voltage value of the battery. Here, the initial value of the SOC is SOC at the time when the flying apparatus **10** takes off. In addition, the intermediate value of the SOC is SOC during the flight of the flying apparatus **10**. The current value is a current value of a current supplied from the battery **21** to the power converting unit **14**. The voltage value is a voltage value

of the battery **21**.

[0068] Thereafter, the calculation control unit **15** calculates the decrease value of the SOC from the DUTY integrated value based on a conversion formula set in advance. Moreover, the calculation control unit **15** calculates the SOC at the time by reducing the decrease value of the SOC from the initial value or the intermediate value of the SOC.

REFERENCE SIGNS LIST

[0069] **10** flying apparatus [0070] **11** rotor [0071] **111** rotor [0072] **112** rotor [0073] **113** rotor [0074] **114** rotor [0075] **12** motor [0076] **121** motor [0077] **122** motor [0078] **123** motor [0079] **124** motor [0080] **13** flight sensor [0081] **14** power converting unit [0082] **141** ESC [0083] **142** ESC [0084] **143** ESC [0085] **144** ESC [0086] **15** calculation control unit [0087] **16** airframe base unit [0088] **17** flight controller [0089] **21** battery [0090] **22** display device [0091] **23** display unit [0092] **24** companion controller [0093] **25** communication unit [0094] **26** communication unit [0095] **271** arm [0096] **272** arm [0097] **273** arm [0098] **274** arm [0099] **28** operating device [0100] **32** leg portion [0101] **33** leg portion

Claims

1. A flying apparatus comprising: a rotor; a motor; a power converting unit; a battery; and a calculation control unit, wherein the rotor rotates to generate thrust for causing an airframe base unit to float, the motor is supplied with an electric power from the battery to rotationally drive the rotor, the calculation control unit generates an instruction signal to bring the airframe base unit into a certain positional posture, the power converting unit adjusts the electric power to be supplied from the battery to the motor based on the instruction signal inputted, and further the calculation control unit estimates a remaining charge of the battery based on the instruction signal.
2. The flying apparatus according to claim 1, wherein the instruction signal is an integrated value of a DUTY value.
3. The flying apparatus according to claim 1, comprising: a plurality of the rotors; a plurality of the motors; and a plurality of the power converting units, wherein the calculation control unit estimates the remaining charge of the battery from an integrated value of DUTY values supplied respectively to the plurality of power converting units.
4. The flying apparatus according to claim 1, wherein the calculation control unit calculates an initial value or an intermediate value of the remaining charge from a current value or a voltage value of the battery, calculates a decrease value of the remaining charge from a DUTY integrated value based on a conversion formula set in advance, and calculates the remaining charge at the time by reducing the decrease value of the remaining charge from the initial value or the intermediate value of the remaining charge.
5. A method for controlling a flying apparatus including a rotor, a motor, a power converting unit, a battery, and a calculation control unit, the method comprising: rotating the rotor to generate thrust for causing an airframe base unit to float; supplying the motor with an electric power from the battery to rotationally drive the rotor; causing the calculation control unit to generate an instruction signal to bring the airframe base unit into a certain positional posture; causing the power converting unit to adjust the electric power to be supplied from the battery to the motor based on the instruction signal inputted; and further causing the calculation control unit to estimate a remaining charge of the battery based on the instruction signal.
6. The method for controlling a flying apparatus according to claim 5, wherein an integrated value of a DUTY value is used as the instruction signal.
7. The method for controlling a flying apparatus according to claim 5, wherein the flying apparatus includes: a plurality of the rotors; a plurality of the motors; and a plurality of the power converting units, and the calculation control unit estimates the remaining charge of the battery from an integrated value of DUTY values supplied respectively to the plurality of power converting units.

8. The method for controlling a flying apparatus according to claim 5, wherein the calculation control unit calculates an initial value or an intermediate value of the remaining charge from a current value or a voltage value of the battery, calculates a decrease value of the remaining charge from the DUTY integrated value based on a conversion formula set in advance, and calculates the remaining charge at the time by reducing the decrease value of the remaining charge from the initial value or the intermediate value of the remaining charge.
