



US 20250280069A1

(19) **United States**

(12) **Patent Application Publication**
Willshire et al.

(10) **Pub. No.: US 2025/0280069 A1**

(43) **Pub. Date: Sep. 4, 2025**

(54) **MONITORING AND TESTING OF WEB
REAL-TIME COMMUNICATIONS (WEBRTC)
SESSIONS**

Publication Classification

(51) **Int. Cl.**
H04M 3/51 (2006.01)

(52) **U.S. Cl.**
CPC H04M 3/5175 (2013.01); H04M 3/5183 (2013.01)

(71) Applicant: **Cyara Solutions Pty Ltd**, Hawthorn (AU)

(72) Inventors: **Geoff Willshire**, Greenslopes (AU);
Tony Dux, Chermside (AU)

(73) Assignee: **Cyara Solutions Pty Ltd**, Hawthorn (AU)

(21) Appl. No.: **19/210,279**


(22) Filed: **May 16, 2025**

Related U.S. Application Data

(63) Continuation of application No. 18/677,504, filed on May 29, 2024, now Pat. No. 12,328,414, which is a continuation of application No. 18/322,588, filed on May 24, 2023, now Pat. No. 12,028,487, which is a continuation of application No. 17/695,732, filed on Mar. 15, 2022, now Pat. No. 11,743,383, which is a continuation of application No. 16/999,028, filed on Aug. 20, 2020, now Pat. No. 11,095,774.

(57) **ABSTRACT**

A system and method for monitoring, analyzing, and testing calls between computers of remotely working call center agents and callers in real-time. A real-time testing module implemented as a browser extension or a side-loaded application relays live call information and on-demand or periodic passive-test results to a test and dashboard server for analysis and triage. Additionally, the real-time testing module may actively test calling conditions between the agent's equipment and a distant caller by suspending the agents calls and tasks, intercepting and taking command of the agent's audio equipment, and placing a test call to a testing server. Thus, allowing actual data to be used in troubleshooting issues, rather than simulations or synthetic data. Dashboards with analytics and predictions are made available in both the browser application and an end point server for agents and operations/management personnel respectively.






Fig. 1 (PRIOR ART)




Fig. 2 (PRIOR ART)




Fig. 3 (PRIOR ART)




Fig. 4 (PRIOR ART)




Fig. 5




Fig. 6




Fig. 7




Fig. 8




Fig. 9




Fig. 10




Fig. 11




Fig. 12




Fig. 13




Fig. 14




Fig. 15




Fig. 16




Fig. 17




Fig. 18




Fig. 19




Fig. 20




Fig. 21




Fig. 22




Fig. 23




Fig. 24




Fig. 25




Fig. 26




Fig. 27




Fig. 28




Fig. 29




Fig. 30 (PRIOR ART)




Fig. 31




Fig. 32 (PRIOR ART)




Fig. 33




Fig. 34




Fig. 35




Fig. 36




Fig. 37




Fig. 38

MONITORING AND TESTING OF WEB REAL-TIME COMMUNICATIONS (WEBRTC) SESSIONS

CROSS-REFERENCE TO RELATED APPLICATIONS

[0001] Priority is claimed in the application data sheet to the following patents or patent applications, each of which is expressly incorporated herein by reference in its entirety:

[0002] Ser. No. 18/677,504

[0003] Ser. No. 18/322,588

[0004] Ser. No. 16/999,028

[0005] Ser. No. 17/965,732

BACKGROUND OF THE INVENTION

Field of the Art

[0006] The disclosure relates to the field of web technology, more specifically to the field of real-time communications between web browsers and testing thereof.

Discussion of the State of the Art

[0007] WebRTC (Web Real-Time Communication) is a free, open-source technology that provides web browsers and mobile applications with real-time communication (RTC) via simple application programming interfaces (APIs). It allows audio and video communication to work inside web pages by allowing direct peer-to-peer communication, eliminating the need to install plugins or download native apps. Supported by numerous corporations and software projects, WebRTC is being standardized through the World Wide Web Consortium (W3C) and the Internet Engineering Task Force (IETF).

[0008] WebRTC is largely responsible for the gradual replacement of older technologies that aimed at providing real time communications between browsers and either other browsers or servers, such as ActiveX, that provided the ability for browsers through extensions to handle real time communication, while using more traditional VOIP technologies such as Session Initiation Protocol ("SIP") for signaling and G.711 and G.729 for media encoding. WebRTC introduced completely different technologies and a different approach to solve a similar problem, but many of these technologies (ICE/STUN/TURN, WebRTC Native) are largely untested formally especially at large scale and can be problematic unless network configurations are carefully considered. Certain cloud contact center technologies such as those provided by AMAZON® have launched utilizing WebRTC clients as a part of their contact center's customer service infrastructure, but to date have had limited ability to be automatically tested. Typically, WebRTC testing solutions in the market today utilize technologies that require large amounts of computing resources to simulate even relatively small numbers of agents, and are limited to fully automated testing of audio quality in one direction only.

[0009] Moreover, with the proliferation of remote work due in large part to the pandemic created by the SARS-COV-2 virus, new technologies are needed to provide the same working parameters and conditions that were present pre-pandemic. Specifically, remote work now introduces a plethora of performance and security concerns because companies do not have full control over a remote worker's

home network or computer. Even if they did, IT staff who would typically resolve issues expeditiously on location are now not available except also over a remote connection. This is radically apparent for the call center industry where call center agents are using home networks and personal computer setups which are not under the same level of control, testing, and security as equipment in an office environment.

[0010] What is needed is a system and method for operating and testing real-time communications between call center agents and customers.

SUMMARY OF THE INVENTION

[0011] Accordingly, the inventor has conceived and reduced to practice, a system and method for monitoring, analyzing, and testing calls between remotely working call center agents and callers in real-time. A real-time testing module implemented as a browser extension or a side-loaded application relays ongoing call information and passive-test results to a test server for analysis and triage. Additionally, the real-time testing module may actively test calling conditions between the agent's equipment and a distant caller by suspending the agents calls and tasks, intercepting and taking command of the agent's audio equipment, and placing a test call to the test server. Thus, allowing actual data to be used in troubleshooting issues, rather than simulations or synthetic data. Dashboards with metrics and analytics are made available in both the browser application and test server.

BRIEF DESCRIPTION OF THE DRAWING FIGURES

[0012] The accompanying drawings illustrate several aspects and, together with the description, serve to explain the principles of the invention according to the aspects. It will be appreciated by one skilled in the art that the particular arrangements illustrated in the drawings are merely exemplary, and are not to be considered as limiting of the scope of the invention or the claims herein in any way.

[0013] FIG. 1 (PRIOR ART) is a system diagram illustrating the architecture of WebRTC technology.

[0014] FIG. 2 (PRIOR ART) is a system diagram illustrating the architecture of WebRTC NAT traversal technology.

[0015] FIG. 3 (PRIOR ART) is a message flow diagram illustrating the architecture of WebRTC interactive connectivity establishment technology.

[0016] FIG. 4 (PRIOR ART) is a system diagram illustrating the architecture of WebRTC signaling flow technology.

[0017] FIG. 5 is a system diagram illustrating components used in operating and testing real-time communications between web browsers with a dedicated desktop application, according to an embodiment.

[0018] FIG. 6 is a system diagram illustrating components used in operating and testing real-time communications between web browsers without a dedicated desktop application, according to an embodiment.

[0019] FIG. 7 is a system diagram illustrating components used in operating and testing real-time communications between web browsers using a cloud contact center such as AMAZONCONNECT™, according to an embodiment.

[0020] FIG. 8 is a system diagram illustrating components used in operating and testing real-time communications between web browsers using a media server as a proxy for a call engine, according to an embodiment.

[0021] FIG. 9 is a system diagram illustrating components used in operating and testing real-time communications between web browsers with all server-side functions integrated into a call engine, according to an embodiment.

[0022] FIG. 10 is a system diagram illustrating components used in operating and testing real-time communications between web browsers with a custom TURN (Traversal Using Relays around NAT) server as a man-in-the-middle, according to an embodiment.

[0023] FIG. 11 is a system diagram illustrating components used in operating and testing real-time communications between web browsers using a polyfill technique to implement WebRTC APIs with a custom implementation that bypass a browser's media and negotiates with an external media server, according to an embodiment.

[0024] FIG. 12 is a system diagram illustrating an API shim intercepting WebRTC API calls and enabling interactions between a cloud infrastructure or contact center, and an external media engine, with custom functionality in an agent browser, according to an embodiment.

[0025] FIG. 13 is a method diagram illustrating steps in operating and testing real-time communications between web browsers with a dedicated desktop application, according to an embodiment.

[0026] FIG. 14 is a method diagram illustrating steps in operating and testing real-time communications between web browsers without a dedicated desktop application, according to an embodiment.

[0027] FIG. 15 is a method diagram illustrating steps in operating and testing real-time communications between web browsers using a cloud contact center such as AMAZONCONNECT™, according to an embodiment.

[0028] FIG. 16 is a method diagram illustrating steps in operating and testing real-time communications between web browsers using a media server as a proxy for a call engine, according to an embodiment.

[0029] FIG. 17 is a method diagram illustrating steps in operating and testing real-time communications between web browsers with all server-side functions integrated into a call engine, according to an embodiment.

[0030] FIG. 18 is a method diagram illustrating steps in operating and testing real-time communications between web browsers with a custom TURN (Traversal Using Relays around NAT) server as a man-in-the-middle, according to an embodiment.

[0031] FIG. 19 is a method diagram illustrating steps in operating and testing real-time communications between web browsers using a polyfill technique to implement WebRTC APIs with a custom implementation that bypass a browser's media and negotiates with an external media server, according to an embodiment.

[0032] FIG. 20 is a method diagram illustrating steps in the operation of an API shim intercepting WebRTC API calls and enabling interactions between a cloud infrastructure or contact center, and an external media engine, with custom functionality in an agent browser, according to an embodiment.

[0033] FIG. 21 is a message flow diagram illustrating data exchange between components used in a process of operat-

ing and testing real-time communications between web browsers with a dedicated desktop application, according to an embodiment.

[0034] FIG. 22 is a message flow diagram illustrating data exchange between components used in a process of operating and testing real-time communications between web browsers without a dedicated desktop application, according to an embodiment.

[0035] FIG. 23 is a message flow diagram illustrating data exchange between components used in a process of operating and testing real-time communications between web browsers using a cloud contact center such as AMAZONCONNECT™, according to an embodiment.

[0036] FIG. 24 is a message flow diagram illustrating data exchange between components used in a process of operating and testing real-time communications between web browsers using a media server as a proxy for a call engine, according to an embodiment.

[0037] FIG. 25 is a message flow diagram illustrating data exchange between components used in a process of operating and testing real-time communications between web browsers with all server-side functions integrated into a call engine, according to an embodiment.

[0038] FIG. 26 is a block diagram illustrating an exemplary hardware architecture of a computing device.

[0039] FIG. 27 is a block diagram illustrating an exemplary logical architecture for a client device.

[0040] FIG. 28 is a block diagram showing an exemplary architectural arrangement of clients, servers, and external services.

[0041] FIG. 29 is another block diagram illustrating an exemplary hardware architecture of a computing device.

[0042] FIG. 30 (PRIOR ART) is a block diagram showing the typical mode of operation of existing WebRTC browser implementations in which WebRTC APIs use an internal media server for media processing.

[0043] FIG. 31 is a block diagram showing the use of a WebRTC "shim" to intercept WebRTC media for separate processing outside of the browser through polyfill of Javascript WebRTC APIs.

[0044] FIG. 32 (PRIOR ART) is a block diagram showing the typical mode of operation of existing WebRTC browser implementations from within a network external to a call center.

[0045] FIG. 33 is a block diagram showing a real-time testing module and a testing and dashboard server used to monitor and triage calls facilitated by a WebRTC-based cloud platform.

[0046] FIG. 34 is a block diagram illustrating the active-testing and audio interception aspect of a real-time testing module.

[0047] FIG. 35 is a block diagram illustrating an exemplary security configuration for a real-time testing module.

[0048] FIG. 36 is a block diagram illustrating an exemplary first stage for configuring a real-time testing module.

[0049] FIG. 37 is a block diagram illustrating an exemplary second stage for configuring a real-time testing module.

[0050] FIG. 38 is a flow diagram showing the method of operation of a real-time testing module and a testing and dashboard server.

DETAILED DESCRIPTION OF THE DRAWING
FIGURE

[0051] The inventor has conceived, and reduced to practice, a system and method for monitoring, analyzing, and testing calls between computers of remotely working call center agents and callers in real-time. A real-time testing module implemented as a browser extension or a side-loaded application relays live call information and on-demand or periodic passive-test results to a test and dashboard server for analysis and triage. Additionally, the real-time testing module may actively test calling conditions between the agent's equipment and a distant caller by suspending the agents calls and tasks, intercepting and taking command of the agent's audio equipment, and placing a test call to a testing server. Thus, allowing actual data to be used in troubleshooting issues, rather than simulations or synthetic data. Dashboards with analytics and predictions are made available in both the browser application and an end point server for agents and operations/management personnel respectively.

[0052] The claimed invention as described provides a real-time streaming and testing mechanism for use with live calls during the remote work performed by a call center agent. The streaming aspect is accomplished via injected code that hooks into a WebRTC platform from an agent's browser and streams information to a server for monitoring and triage. Additionally, active and passive testing may be performed to supplement monitoring and triage efforts. This is especially useful because agents typically may not be able to effectively describe the technical problems, he or she experience during one or more calls. While the claimed invention discloses both novel active and passive tests, a noted difference between the active test and passive test is that the passive testing submodule uses network statistics and a G.107 ITU standard to determine a MOS score (i.e., a quantitative voice quality score), whereas the active testing submodule analyses live audio call data to detect one or more issues.

[0053] The active testing submodule of the claimed invention uses APIs to inject code into the browser in order to rewire the audio from the test call. Whereas the previous embodiments utilizing media redirection, which are contained at least in FIG. 31, are directed to use shim that encapsulates a whole WebRTC subsystem within the browser and redirects the request to a server rather than to the browser. Whereas in the presently disclosed embodiments (at least FIGS. 33-34), the browser still handles the call, however the active testing submodule injected code captures the audio in an in-memory buffer and streams to a server for analysis.

[0054] One or more different aspects may be described in the present application. Further, for one or more of the aspects described herein, numerous alternative arrangements may be described; it should be appreciated that these are presented for illustrative purposes only and are not limiting of the aspects contained herein or the claims presented herein in any way. One or more of the arrangements may be widely applicable to numerous aspects, as may be readily apparent from the disclosure. In general, arrangements are described in sufficient detail to enable those skilled in the art to practice one or more of the aspects, and it should be appreciated that other arrangements may be utilized and that structural, logical, software, electrical and other changes may be made without departing from the

scope of the particular aspects. Particular features of one or more of the aspects described herein may be described with reference to one or more particular aspects or figures that form a part of the present disclosure, and in which are shown, by way of illustration, specific arrangements of one or more of the aspects. It should be appreciated, however, that such features are not limited to usage in the one or more particular aspects or figures with reference to which they are described. The present disclosure is neither a literal description of all arrangements of one or more of the aspects nor a listing of features of one or more of the aspects that must be present in all arrangements.

[0055] Headings of sections provided in this patent application and the title of this patent application are for convenience only, and are not to be taken as limiting the disclosure in any way.

[0056] Devices that are in communication with each other need not be in continuous communication with each other, unless expressly specified otherwise. In addition, devices that are in communication with each other may communicate directly or indirectly through one or more communication means or intermediaries, logical or physical.

[0057] A description of an aspect with several components in communication with each other does not imply that all such components are required. To the contrary, a variety of optional components may be described to illustrate a wide variety of possible aspects and in order to more fully illustrate one or more aspects. Similarly, although process steps, method steps, algorithms or the like may be described in a sequential order, such processes, methods and algorithms may generally be configured to work in alternate orders, unless specifically stated to the contrary. In other words, any sequence or order of steps that may be described in this patent application does not, in and of itself, indicate a requirement that the steps be performed in that order. The steps of described processes may be performed in any order practical. Further, some steps may be performed simultaneously despite being described or implied as occurring non-simultaneously (e.g., because one step is described after the other step). Moreover, the illustration of a process by its depiction in a drawing does not imply that the illustrated process is exclusive of other variations and modifications thereto, does not imply that the illustrated process or any of its steps are necessary to one or more of the aspects, and does not imply that the illustrated process is preferred. Also, steps are generally described once per aspect, but this does not mean they must occur once, or that they may only occur once each time a process, method, or algorithm is carried out or executed. Some steps may be omitted in some aspects or some occurrences, or some steps may be executed more than once in a given aspect or occurrence.

[0058] When a single device or article is described herein, it will be readily apparent that more than one device or article may be used in place of a single device or article. Similarly, where more than one device or article is described herein, it will be readily apparent that a single device or article may be used in place of the more than one device or article.

[0059] The functionality or the features of a device may be alternatively embodied by one or more other devices that are not explicitly described as having such functionality or features. Thus, other aspects need not include the device itself.

[0060] Techniques and mechanisms described or referenced herein will sometimes be described in singular form for clarity. However, it should be appreciated that particular aspects may include multiple iterations of a technique or multiple instantiations of a mechanism unless noted otherwise. Process descriptions or blocks in figures should be understood as representing modules, segments, or portions of code which include one or more executable instructions for implementing specific logical functions or steps in the process. Alternate implementations are included within the scope of various aspects in which, for example, functions may be executed out of order from that shown or discussed, including substantially concurrently or in reverse order, depending on the functionality involved, as would be understood by those having ordinary skill in the art.

Definitions

[0061] “MOS score” as used herein refers to a VOIP Quality Mean Opinion Score (MOS). The Mean Opinion Score (MOS) is a commonly used metric to measure the overall voice call quality. MOS score is a rating from 1 to 5 of the perceived quality of a voice call, 1 being the lowest score and 5 the highest for excellent quality.

[0062] “Shim” as used herein refers to a middleware library that intercepts API calls and changes arguments passed, handles the operation itself, or redirects the operation elsewhere, for the purposes of extended, replacing, or redirecting functionality on a local software execution that receives API requests from another piece of software. A shim may operate with, in, or as part of a web browser, or other application, and may achieve many different effects, and may be written in any computer programming language supported by the machine and operating system in use.

[0063] “Polyfill” as used herein refers to a code execution that implements a feature or features on web browsers that is not normally or natively supported on the web browser, or allows for the modification of an existing feature inside of the browser, and is often but not always written or implemented as a JavaScript library that implements an HTML5 web standard. A polyfill may be written in other languages and achieve other desired effects, but is at least, and always, middleware code that implements new features on a web browser that did not have the features before. It provides a means to override built in WebRTC APIs to allow for the interception of signaling information, to allow RTC media to be directed outside of the browser itself.

Conceptual Architecture

[0064] FIG. 1 (PRIOR ART) is a system diagram illustrating the architecture of WebRTC technology. A web browser **110** is operated on a computer, such as CHROME®, INTERNET EXPLORER® or EDGE®, OPERA®, or other web browsers, operates with WebRTC **111** installed. WebRTC **111** may comprise a number of different technologies and software, including JavaScript APIs as defined by the W3C, low level communication and media device control code (known as “WebRTC Native”), a variety of Network Address Translation (“NAT”) traversal technologies including or surpassing uPNP in capabilities, built-in security for incoming and outgoing media communications, and modern audio and video codecs. The WebRTC **111** software is accessible to exterior connections via a WebRTC API **112**, for the purpose of operating with peer-to-peer (p2p) audio or

video communications applications **113**. Such applications include, for example, video chat applications, VoIP (Voice over Internet Protocol) applications or tools, and the like. A WebRTC C++ API **114** exists which may be accessed by PeerConnection or RTCPeerConnection calls, and enables audio and video communications between connected peers, providing signal processing, codec handling, p2p communication, security, and bandwidth management. The API **114** may accept Session Description Protocol (“SDP”) information to identify the requirements for communications between the two peers, the SDP information possibly including at least information about the media types being used, the codecs allowed and used by the peers, and encryption parameters. The C++ API **114** may also handle Interactive Connectivity Establishment (“ICE”) negotiation, to attempt to find the clearest end-to-end path for media communications between peers, using NAT traversal techniques. Session management functionality may be accessed with a handle of Session **115** in software utilizing WebRTC, handling signaling data and session identification protocol (“SIP”) information. The software components that allow media capture and processing and signaling are a voice engine **120**, video engine **130**, and transport engine **140**, each with separate sub-components responsible for specific operation in the WebRTC software. An internet Speech Audio Codec (“iSAC”) and internet Low Bitrate Codec (“iLBC”) are both installed **121** as part of the voice engine **120**, for encoding and decoding of audio data according to either codec for p2p communications. A NetEQ component is installed **122** which is an applied software algorithm that reduces jitter and conceals errors in audio data to mitigate the effects of audio jitter and packet loss during communications, also designed to keep latency to a minimum. An echo canceler or noise reducer (or both) are installed **123** to reduce the effects of audio echo and background noise in outgoing audio data. A video engine has components installed or built into it including a VP8 codec **131**, an open source and commonly used video compression format; a video jitter buffer **132** similar in concept to the NetEQ **122**, meant to reduce the jitter and error prevalence in video media; and a set of image enhancement tools **133** for sharpening, brightening, or otherwise performing basic modifications to images for enhancement during communications, as needed. The transport engine **140** contains software for Secure Real-Time Transport Protocol (“SRTP”) **141**, signal multiplexing **142**, and p2p Session Traversal Utilities for NAT (“STUN”), Traversal Using Relays around NAT (“TURN”), and ICE software **143**, for communications with peers behind network address translators such as firewalls or local internet routers. The voice engine **120**, video engine **130**, and transport engine **140**, each provide a part of the functionality of WebRTC **111**, including an audio capture/render capability **120a**, video capture and rendering **130a**, and network input/output (“I/O”) capabilities **140a**.

[0065] FIG. 2 (PRIOR ART) is a system diagram illustrating the architecture of WebRTC NAT traversal technology. Two embodiments are shown, each utilizing a different network **210**, **220** architecture. In the first architecture, two peers **211**, **212** who wish to share media data are shown, and each is protected behind a NAT system **213**, **215**. This prevents them from easily or directly communicating with each other to share data over most protocols. A relay server **214** connects the two NAT **213**, **215** systems, known as a TURN server **214**. Further, two Session Traversal Utilities

for NAT (“STUN”) servers **216, 217** connect to the NATs. A STUN server provides a standardized set of methods, including a network protocol, for traversal of NAT gateways in applications of real-time voice, video, messaging, and other communications. A STUN server **216, 217** provides data to a requesting server or service that does not have access to the addresses behind a NAT **213, 215** such as the peers **211, 212**, such as a relay server, which may poll the relevant data from both STUNs **216, 217** to send data to the peers **211, 212** behind the NAT systems, allowing them to communicate with each other. A second implementation is shown, without any STUN servers, in which NAT systems **225, 224** communicate not just with their respective peers **222, 223** and a TURN server **221**, but also communicate with each other, in order to facilitate ICE frameworks in the peers’ WebRTC APIs to share their addresses directly without a STUN.

[0066] FIG. 3 (PRIOR ART) is a message flow diagram illustrating the architecture of WebRTC interactive connectivity establishment technology. Components or systems sharing data messages include a peer A **310**, STUN server **315**, TURN server **320**, signal channel **325**, and peer B **330**. First, a peer A sends a message to a connected STUN server **315**, asking for their own address and identifying information **335**, before getting a response back that defines the symmetric NAT to the peer A **340**. A symmetric NAT is a NAT in which requests sent from the same internal IP address and port to the same destination IP address, is mapped to a unique external source IP address and port, reachable from the STUN server. Peer A **310** then requests channel information from the TURN server **320, 345**, binding a channel to themselves for eventual connection to peer B **330**, before peer A is able to offer Session Description Protocol (“SDP”) information across the signal channel **350** to peer B **330, 355**. Peer B is able to respond to the SDP request to begin enabling media communications between the two peers **360, 365**, at which point peer A may send an ICE candidate through the signal channel **370** to peer B **375**. Interactive connectivity establishment (ICE) is a technique to find the most direct way for two networking peers to communicate through NAT systems. Peer B may then respond with its own ICE candidate **380, 385**, finally requesting symmetric NAT information from the STUN server **390** before the addresses to communicate with each other are set up and addresses are delivered to the peers through the signal channel **395**. In this way, through the use of a STUN server and TURN server, two peers behind NAT systems can establish media communications.

[0067] FIG. 4 (PRIOR ART) is a system diagram illustrating the architecture of WebRTC signaling flow technology. Two peers have web browsers open, labeled A **420** and B **430**, the web browsers from each not needing to be the same web browser, which could be any web browser such as SAFARI™, CHROME™, INTERNET EXPLORER™, OPERA™, and others. Each browser has several software components available to it for the purposes of using WebRTC communications, including a communication application **421, 431** which may be an application such as DISCORD™, GOOGLE CHAT™, SKYPE™, or others, a WebRTC JavaScript API **422, 432** which is a core feature of WebRTC, the WebRTC native code **423, 433** which is typically written in C++ and designed for a specific system rather than being a JavaScript API that may be implemented on a variety of system configurations, and a collection of

media devices **424, 434**, such as a webcam, microphone, or other media devices one might communicate over a network with. The JavaScript APIs **422, 432**, WebRTC native frameworks **423, 433**, and media devices **424, 434** may all communicate over the Internet **440**, while communication applications **421, 431** typically communicate not just over the Internet with each other but with an application server **410**. Such an application server may have the STUN and TURN functionality mentioned in other descriptions, and may provide the proper signal information for the applications to communicate, while the WebRTC code and APIs and media devices exchange media data with each other over the Internet.

[0068] FIG. 5 is a system diagram illustrating components used in operating and testing real-time communications between web browsers with a dedicated desktop application, according to an embodiment. A call and media testing operator network **510** connects over a network, or through direct connection, to a cloud contact center **520**, such as over a TCP/IP connection, a UDP connection, or some other protocol of connection between devices and services. An operator network communicates with a cloud contact center to send and receive data on making calls to a cloud contact center service user for the purpose of testing and receiving the results of the testing of the infrastructure used by agents connected through the contact cloud center, and to test client-agent exchanges. A web browser **530** such as OPERA™, SAFARI™, MICROSOFT EDGE™ or others, also connects to a cloud contact center **520**, through a network or through a direct connection, and may send and receive media data, with the use of a web-based contact center agent application **531**, a WebRTC native implementation **532**, and media server software **533**. Such software is capable of processing audio and video data, encoding and decoding it, providing basic encryption and decryption services for the media data, operating audio and video enhancement software or algorithms such as anti-jitter software, and more. An automated agent simulator or agent automation engine **540** provides automated responses to simulate an agent or client or generally a “peer” in a peer-to-peer communication session, providing either a pre-determined script of responses to another peer or by using a response tree, or through some other method such as with machine learning, to a web-based contact center agent application **531**. An agent automation engine **540** may be operated over a network on a separate computing device, or may be operated on the same computer as the browser **530** that operates the web-based contact center agent application **531** and WebRTC native implementation **532**. A software audio generation device (“AGD”) **550** communicates with a WebRTC native **532** and media server **533** software, to generate audio, listen for tones, and test the WebRTC connection and software via virtual audio devices to ensure that communication between a simulated agent **540** and a peer over a WebRTC software **532** is being properly handled.

[0069] FIG. 6 is a system diagram illustrating components used in operating and testing real-time communications between web browsers without a dedicated desktop application, according to an embodiment. A call and media testing operator network **610** connects over a network, or through direct connection, to a cloud contact center **620**, such as over a TCP/IP connection, a UDP connection, or some other protocol of connection between devices and

services. An operator network communicates with a cloud contact center to send and receive data on making calls to a cloud contact center service user for the purpose of testing and receiving the results of the testing of the infrastructure used by agents connected through the contact cloud center, and to test client-agent exchanges. A web browser **630** such as OPERA™, SAFARI™, MICROSOFT EDGE™, or others, also connects to a cloud contact center **620**, through a network or through a direct connection, and may send and receive media data, with the use of a cloud contact center web-based contact center agent application **631**, a WebRTC native implementation **632**, and media server software **633**. Such software is capable of processing audio and video data, encoding and decoding it, providing basic encryption and decryption services for the media data, operating audio and video enhancement software or algorithms such as anti-jitter software, and more. An automated agent simulator or agent automation engine **640** provides automated responses to simulate an agent or client or generally a “peer” in a peer-to-peer communication session, providing either a predetermined script of responses to another peer or by using a response tree, or through some other method such as with machine learning, to a web-based contact center agent application **631**. An agent automation engine **640** may be operated over a network on a separate computing device, or may be operated on the same computer as the browser **630** that operates the web-based contact center agent application **631** and WebRTC native implementation **632**. A simulated microphone and speaker **632a** communicate with a WebRTC native **632** and media server **633** software, to generate audio, listen for audio, and test the WebRTC connection and software to ensure that communication between a simulated agent **640** and a peer over a WebRTC software **632** is being properly handled. Audio output **650** may be discarded or saved as a file, while audio input **660** may be a set of audio data to simulate with a simulated microphone **632a**, or text descriptions of the things the system to simulate with a microphone emulator **632a**, or even an audio file that is interpreted through an emulated microphone.

[0070] FIG. 7 is a system diagram illustrating components used in operating and testing real-time communications between web browsers using a cloud contact center such as AMAZONCONNECT™, according to an embodiment. A call and media testing operator network **710** connects over a network, or through direct connection, to a cloud contact center **720**, such as over a TCP/IP connection, a UDP connection, a public switched telecommunication network (PSTN) or some other protocol of connection between devices and services. The operator network communicates with a cloud contact center to send and receive data on making calls to a cloud contact center service user for the purpose of testing and receiving the results of the testing of the infrastructure used by agents connected through the contact cloud center, and to test client-agent exchanges. A web browser **730** such as OPERA™, SAFARI™, MICROSOFT EDGE™, or others, also connects to a cloud contact center **720**, through a network or through a direct connection, and may send and receive media data, with the use of a web-based contact center agent application **732**, a WebRTC “shim” **731**, and media server software **760** connected through an agent signaling mediation server, which may operate using NODE.JS™ **750**. Such a NODE.JS™ intermediary may be operated on the same computer and facilitate communication between the two pieces of software

732, **760**, or may be operated on another computing device and connected to over a network or direct connection. Media server **760** software is capable of processing audio and video data, encoding and decoding it, providing basic encryption and decryption services for the media data, operating audio and video enhancement software or algorithms such as anti-jitter software, and more. A WebRTC “shim” is code injected by the agent automation **740** software in this embodiment, essentially acting as a separate piece of software that interacts with the web browser **730** to intercept signals coming from the cloud contact center **720** and provide custom or modular functionality, also taking the load off the browser, and instead putting it on the code operating outside the browser process, and the media server **760**, for processing media data separately from the browser itself. Browser media processing does not typically scale well for large numbers of calls, so offloading processing to an external media server may assist in increasing scalability of the testing application. An automated agent simulator or agent automation engine **740** also provides automated responses to simulate an agent or client or generally a “peer” in a peer-to-peer communication session, providing either a predetermined script of responses to another peer or by using a response tree, or through some other method such as with machine learning, to a web-based contact center agent application **731**. An agent automation engine **740** may be operated over a network on a separate computing device, or may be operated on the same computer as the browser **730** that operates the web-based contact center agent application **731** and WebRTC shim **731**. Audio output may be discarded or saved as a file **770**, while audio input **780** may be a set of audio data to simulate with a media server software package such as KURENTO™.

[0071] FIG. 8 is a system diagram illustrating components used in operating and testing real-time communications between web browsers using a media server as a proxy for a call engine, according to an embodiment. A call and media testing operator network **810** connects over a network, or through direct connection, to a cloud contact center **820**, such as over a TCP/IP connection, a UDP connection, or some other protocol of connection between devices and services. An operator network communicates with a cloud contact center to send and receive data on making calls to a cloud contact center service user for the purpose of testing and receiving the results of the testing of the infrastructure used by agents connected through the contact cloud center, and to test client-agent exchanges. A web browser **830** such as OPERA™, SAFARI™, MICROSOFT EDGE™, or others, also connects to a cloud contact center **820**, through a network or through a direct connection, and may send and receive media data, with the use of a web-based contact center agent application **831**, a WebRTC “shim” **832**, and media server software **850** connected to over a network or with a direct connection, or operating as separate software on the same computing device. Media server **850** software is capable of processing audio and video data, encoding and decoding it, providing basic encryption and decryption services for the media data, operating audio and video enhancement software or algorithms such as anti-jitter software, and more. A Session Initiation Protocol (“SIP”) proxy **860** is used to modularly handle the “handshake” and session initiation data such as what protocols, codecs, etc. are expected, communicating this with a call engine **870** which serves to simulate a peer connection across a network

hiding behind an SIP proxy, for testing the media communications between the simulated peer with an automated agent system **840** and the call engine **870**. A WebRTC “shim” is code injected by the agent automation **840** software in this embodiment, essentially acting as a separate piece of software that interacts with the web browser **830** to intercept signals coming from the cloud contact center **820** and provide custom or modular functionality, also taking the load off the browser, and instead putting it on the code operating outside the browser process, and the media server **850**, for processing media data separately from the browser itself. An automated agent simulator or agent automation engine **840** also provides automated responses to simulate an agent or client or generally a “peer” in a peer-to-peer communication session, providing either a predetermined script of responses to another peer or by using a response tree, or through some other method such as with machine learning, to a web-based contact center agent application **832**. An agent automation engine **840** may be operated over a network on a separate computing device, or may be operated on the same computer as the browser **830** that operates the web-based contact center agent application **831** and WebRTC shim **832**.

[0072] FIG. 9 is a system diagram illustrating components used in operating and testing real-time communications between web browsers with all server-side functions integrated into a call engine, according to an embodiment. A call and media testing operator network **910** connects over a network, or through direct connection, to a cloud contact center **920**, such as over a TCP/IP connection, a UDP connection, or some other protocol of connection between devices and services. An operator network communicates with a cloud contact center to send and receive data on making calls to a cloud contact center service user for the purpose of testing and receiving the results of the testing of the infrastructure used by agents connected through the contact cloud center, and to test client-agent exchanges. A web browser **930** such as OPERA™, SAFARI™, MICROSOFT EDGE™, or others, also connects to a cloud contact center **920**, through a network or through a direct connection, and may send and receive media data, with the use of a web-based contact center agent application **932**, a WebRTC “shim” **931**, and operator call engine **950** that may be used by an agent or synthetic agent, connected to over a network or with a direct connection, or operating as separate software on the same computing device. An operator call engine **950** that may be used by an agent or synthetic agent software may be responsible for receiving audio from an output source and taking it as input, for instance by simulating an audio output device like speakers or a headset, or by audio output device virtualization. A WebRTC “shim” is code injected by the agent automation **940** software in this embodiment, essentially acting as a separate piece of software that interacts with the web browser **930** to intercept signals coming from the cloud contact center **920** and provide custom or modular functionality, also taking the load off the browser, and instead putting it on the code operating outside the browser process, and the call engine **950**, for processing media and call data separately from the browser process itself. An automated agent simulator or agent automation engine **940** also provides automated responses to simulate an agent or client or generally a “peer” in a peer-to-peer communication session, providing either a predetermined script of responses to another peer or by

using a response tree, or through some other method such as with machine learning, to a web-based contact center agent application **932**. An agent automation engine **940** may be operated over a network on a separate computing device, or may be operated on the same computer as the browser **930** that operates the web-based contact center agent application **932** and WebRTC shim **931**.

[0073] FIG. 10 is a system diagram illustrating components used in operating and testing real-time communications between web browsers with a custom TURN (Traversal Using Relays around NAT) server as a man-in-the-middle, according to an embodiment. A call and media testing operator network **1010** connects over a network, or through direct connection, to a cloud contact center **1020**, such as over a TCP/IP connection, a UDP connection, or some other protocol of connection between devices and services. An operator network communicates with a cloud contact center to send and receive data on making calls to a cloud contact center service user for the purpose of testing and receiving the results of the testing of the infrastructure used by agents connected through the contact cloud center, and to test client-agent exchanges. A relay server **1020a**, such as a Traversal Using Relays around NAT (“TURN”) server, serves as a relay between the cloud contact center and a web browser **1030** such as OPERA™, SAFARI™, MICROSOFT EDGE™, or others, serving to aid in connecting a user behind a NAT to the cloud contact center **1020**, through a network or through a direct connection, and may send and receive media data, with the use of a web-based contact center agent application **1032**, a WebRTC “shim” **1031**, and call engine software **1050** connected to over a network or with a direct connection, or operating as separate software on the same computing device. A operator call engine **1050** that may be used by an agent or synthetic agent software, may be responsible for receiving audio from an output source and taking it as input, for instance by simulating an audio output device like speakers or a headset, or by audio output device virtualization. A WebRTC “shim” is code injected by the agent automation **1040** software in this embodiment, essentially acting as a separate piece of software that interacts with the web browser **1030** to intercept signals coming from the cloud contact center **1020** and provide custom or modular functionality, also taking the load off the browser, and instead putting it on the code operating outside the browser process, and the call engine **1050**, for processing media and call data separately from the browser process itself. An automated agent simulator or agent automation engine **1040** also provides automated responses to simulate an agent or client or generally a “peer” in a peer-to-peer communication session, providing either a predetermined script of responses to another peer or by using a response tree, or through some other method such as with machine learning, to a web-based contact center agent application **1032**. An agent automation engine **1040** may be operated over a network on a separate computing device, or may be operated on the same computer as the browser **1030** that operates the web-based contact center agent application **1032** and WebRTC shim **1031**.

[0074] FIG. 11 is a system diagram illustrating components used in operating and testing real-time communications between web browsers using a polyfill technique to implement WebRTC APIs with a custom implementation that bypasses a browser’s media and negotiates with an external media server, according to an embodiment. A call

and media testing operator network **1110** connects over a network, or through direct connection, to a cloud contact center **1120**, such as over a TCP/IP connection, a UDP connection, or some other protocol of connection between devices and services. The operator network **1110** communicates with a cloud contact center to send and receive data on making calls to a cloud contact center service user for the purpose of testing and receiving the results of the testing of the infrastructure used by agents connected through the contact cloud center, and to test client-agent exchanges. A web browser **1130** such as OPERA™, SAFARI™, MICROSOFT EDGE™, or others, also connects to a cloud contact center **1120**, through a network or through a direct connection, and may send and receive media data, with the use of a web-based contact center agent application **1132**, a polyfill of WebRTC APIs **1131**, and media server software **1140**. A polyfill of WebRTC APIs **1131** in this case provides a means to override built in WebRTC APIs to allow for the interception of signaling information to allow RTC media to be directed outside of the browser itself. Media server **1140** software is capable of processing audio and video data, encoding and decoding it, providing basic encryption and decryption services for the media data, operating audio and video enhancement software or algorithms such as anti-jitter software, and more. A polyfill of WebRTC APIs may act in some embodiments as a separate piece of software that interacts with the web browser **1130** to intercept signals coming from the cloud contact center **1120** and provide custom or modular functionality, also taking the load off the browser, and instead putting it on the code operating outside the browser process, and the media server **1140**, for processing media data separately from the browser itself. An automated agent simulator or agent automation engine **1170** also provides automated responses to simulate an agent or client or generally a “peer” in a peer-to-peer communication session, providing either a predetermined script of responses to another peer or by using a response tree, or through some other method such as with machine learning, to a web-based contact center agent application **1131**. An agent automation engine **1170** may be operated over a network on a separate computing device, or may be operated on the same computer as the browser **1130** that operates the web-based contact center agent application **1131** and WebRTC polyfill **1131**. Audio output may be discarded or saved as a file **1150**, while audio input **1160** may be a set of audio data to simulate with a media server software package such as KURENTO™.

[0075] FIG. 12 is a system diagram illustrating an API shim intercepting WebRTC API calls and enabling interactions between a cloud infrastructure or contact center, and an external media engine, with custom functionality in an agent browser, according to an embodiment. A cloud WebRTC infrastructure **1210** such as but not limited to AMAZON CONNECT™ may communicate and operate with an automated agent browser **1220**, such as but not limited to the AMAZON CONNECT™ contact control panel (CCP), which normally implements a WebRTC API **1223** and internal media server **1224** to handle media exchange between an agent and customer using the cloud infrastructure to interface between them. In this embodiment, the API **1223** and internal media server **1224** are bypassed due to a polyfill API shim **1222** which operates in the automated agent browser **1220**, and intercepts the API calls from the application **1221** itself and handle signaling between the agent browser **1220** and the cloud infrastructure **1210**. This

API shim **1222** then communicates the signaling data to an external media server **1250** which then uses the signaling information to communicate real time communications protocol (“RTP”) media with the cloud infrastructure, such as voice and video data, with a virtual agent or voice quality detection algorithm **1240** for automated testing and virtual agent operation through the use of an agent automation script **1230** to drive the client and make the API calls required to interact with a user on the other side of the cloud infrastructure.

[0076] FIG. 13 is a method diagram illustrating steps in operating and testing real-time communications between web browsers with a dedicated desktop application, according to an embodiment. A browser application is executed on a computing device, such as OPERA™ SAFARI™ CHROME™, or other browsers available, loading a media server wrapper and native WebRTC code **1210** into memory. A media server wrapper may also be called a media server plugin, or a separate piece of software that communicates with the web browser and WebRTC code. An operator network that initiates tests of peer-to-peer communications then may forward data through a cloud contact center such as AMAZON CONNECT™, to a browser operating a WebRTC framework and browser-side contact center web-based contact center agent application **1220** for cloud contact center integration. An agent automation engine may then operate as either a simple test of media communication connection, or as a complex test of other automated systems such as browser-based IVRs **1230**, while WebRTC native code may communicate with software audio generation devices, allowing automated testing of cloud contact center and WebRTC infrastructure/services **1240**. The automated agent or agents (depending on the implementation) may then communicate either directly, over a network, or with the web browser process on the same computing device, and with software audio generation device(s) to test responses, response times, reliability, and any other metrics or functionality desired to be tested by the operating network **1250**. The test results may then be forwarded to the operator services network by either controlling the call or calls directly through the cloud contact center, or by being sent the results of the tests over a network **1260**.

[0077] FIG. 14 is a method diagram illustrating steps in operating and testing real-time communications between web browsers without a dedicated desktop application, according to an embodiment. A browser application is executed on a computing device, such as OPERA™, SAFARI™ CHROME™, or other browsers available, loading a media server wrapper and native WebRTC code **1310** into memory. A media server wrapper may also be called a media server plugin, or a separate piece of software that communicates with the web browser and WebRTC code. An operator network that initiates tests of peer-to-peer communications then may forward data through a cloud contact center such as AMAZON CONNECT™, to a browser operating a WebRTC framework and browser-side contact center web-based contact center agent application **1320** for cloud contact center integration. An agent automation engine may then operate as either a simple test of media communication connection, or as a complex test of other automated systems such as browser-based IVRs **1330**, while WebRTC native code may communicate with a digital audio file or other audio stream, allowing automated testing of cloud contact center and WebRTC infrastructure/services

1340. Audio files may be prepared in advance or generated programmatically depending on the implementation of the WebRTC APIs. The automated agent or agents (depending on the implementation) may then communicate either directly, over a network, or with the web browser process on the same computing device, with audio files that mimic a software microphone or other audio stream to test responses, response times, reliability, and any other metrics or functionality desired to be tested by the operating network **1350**, the audio output being able to be captured and analyzed, discarded and deleted, or may be ignored and handled in some alternative manner, as desired depending on the programming. The test results may then be forwarded to the operator services network by either controlling the call or calls directly through the cloud contact center, or by being sent the results of the tests over a network **1360**.

[0078] FIG. **15** is a method diagram illustrating steps in operating and testing real-time communications between web browsers using a cloud contact center such as AMAZONCONNECT™, according to an embodiment. A browser application is executed on a computing device, such as OPERA™, SAFARI™ CHROME™, or other browsers available, loading a media server wrapper and a WebRTC “shim” **1410** into memory. A “shim” in computer programming refers to a library or set of functions or methods that intercept API calls to perform one or multiple of several possible actions on the API calls, including altering the arguments passed in the call, handling the operation itself rather than allowing the intended destination to, or redirecting it elsewhere. In this case, a WebRTC shim refers to an injected piece of code that acts similarly to WebRTC APIs in the browser but are not tied to the browser process and may behave differently and scale better than native WebRTC code running in a browser. A media server wrapper may also be called a media server plugin, or a separate piece of software that communicates with the web browser and WebRTC code. A WebRTC shim may intercept WebRTC API calls and other cloud contact center communications, as well as manage communications between the browser and a media server with a JavaScript handler such as one made with NODE.JS™ NODE.JS™ to separate the media server software rather than operating as part of the browser **1420**. The media server may be operated on a different computing device, or the same computing device, and may be connected to over a network. An operator network that initiates tests of peer-to-peer communications then may forward data through a cloud contact center such as AMAZON CONNECT™, to a browser operating a WebRTC shim and browser-side contact center web-based contact center agent application **1430** for cloud contact center integration. An agent automation engine may then operate as either a simple test of media communication connection, or as a complex test of other automated systems such as browser-based IVRs **1440**, while a WebRTC shim communicates with a media server through a javascript interface such as an interface coded in NODE.JS™ **1450**. The media server handles a connection between audio files that may be used for input and output of the test audio. Audio files may be prepared in advance or generated programmatically depending on the implementation of the shimmed APIs. The automated agent or agents (depending on the implementation) may then communicate either directly, over a network, or with the web browser process on the same computing device, with audio files that mimic a software microphone or other audio stream

to test responses, response times, reliability, and any other metrics or functionality desired to be tested by the operating network **1460**, the audio output being able to be captured or captured and analyzed, discarded and deleted, or may be ignored and handled in some alternative manner, as desired depending on the programming, by the media server. The test results may then be forwarded to the operator services network by either controlling the call or calls directly through the cloud contact center, or by being sent the results of the tests over a network **1470**.

[0079] FIG. **16** is a method diagram illustrating steps in operating and testing real-time communications between web browsers using a media server as a proxy for a call engine, according to an embodiment. A browser application is executed on a computing device, such as OPERA™, SAFARI™ CHROME™, or other browsers available, loading a media server wrapper and a WebRTC “shim” **1510** into memory. A “shim” in computer programming refers to a library or set of functions or methods that intercept API calls to perform one or multiple of several possible actions on the API calls, including altering the arguments passed in the call, handling the operation itself rather than allowing the intended destination to, or redirecting it elsewhere. In this case, a WebRTC shim refers to an injected piece of code that acts similarly to WebRTC APIs in the browser but are not tied to the browser process and may behave differently and scale better than native WebRTC code running in a browser. A media server wrapper may also be called a media server plugin, or a separate piece of software that communicates with the web browser and WebRTC code. A WebRTC shim may intercept WebRTC API calls and other cloud contact center communications, as well as manage communications between the browser and a media server to separate the media server software rather than operating as part of the browser **1520**. The media server may be operated on a different computing device, or the same computing device, and may be connected to over a network. An operator network that initiates tests of peer-to-peer communications then may forward data through a cloud contact center such as AMAZON CONNECT™, to a browser operating a WebRTC shim and browser-side contact center web-based contact center agent application **1530** for cloud contact center integration. An agent automation engine may then operate as either a simple test of media communication connection, or as a complex test of other automated systems such as browser-based IVRs **1540**, while a WebRTC shim communicates with the media server directly, the media server having session initiation protocol started with the SIP proxy, allowing unfiltered/unencrypted/unhindered video/audio data to be handed to an operator call engine while the proxy handles the session data with the media server **1550**. A call engine may process and generate unencrypted Real-Time Transport Protocol (“RTP”) media for the purpose of driving the actual generation of and processing of audio, and has access to the unencrypted RTP stream of media due to the use of an SIP proxy that handles the signaling data for the RTP transmission. The media server handles a connection between audio files that may be used for input and output of the test audio. Audio files may be prepared in advance or generated programmatically depending on the implementation of the shimmed APIs. The automated agent or agents (depending on the implementation) may then communicate either directly, over a network, or with the web browser process on the same computing device, with audio

files that mimic a software microphone or other audio stream to test responses, response times, reliability, and any other metrics or functionality desired to be tested by the operating network **1560**, the audio output being able to be captured or captured and analyzed, discarded and deleted, or may be ignored and handled in some alternative manner, as desired depending on the programming, by the media server. The test results may then be forwarded to the operator services network by either controlling the call or calls directly through the cloud contact center, or by being sent the results of the tests over a network **1570**.

[0080] FIG. **17** is a method diagram illustrating steps in operating and testing real-time communications between web browsers with all server-side functions integrated into a call engine, according to an embodiment. A browser application is executed on a computing device, such as OPERA™, SAFARI™ CHROME™, or other browsers available, loading a WebRTC “shim” **1610** into memory. A “shim” in computer programming refers to a library or set of functions or methods that intercept API calls to perform one or multiple of several possible actions on the API calls, including altering the arguments passed in the call, handling the operation itself rather than allowing the intended destination to, or redirecting it elsewhere. In this case, a WebRTC shim refers to an injected piece of code that acts similarly to WebRTC APIs in the browser but are not tied to the browser process and may behave differently and scale better than native WebRTC code running in a browser. A WebRTC shim may intercept WebRTC API calls and other cloud contact center communications, as well as manage communications between the browser and a call engine to separate the call engine software rather than operating as part of the browser **1620**. A call engine may process and generate unencrypted Real-Time Transport Protocol (“RTP”) media for the purpose of driving the actual generation of and processing of audio, and in this embodiment does not require an SIP proxy server but can operate with WebRTC signal data processing itself. An operator network that initiates tests of peer-to-peer communications then may forward data through a cloud contact center such as AMAZON CONNECT™, to a browser operating a WebRTC framework and browser-side contact center web-based contact center agent application **1630** for cloud contact center integration. An agent automation engine may then operate as either a simple test of media communication connection, or as a complex test of other automated systems such as browser-based IVRs **1640**, while WebRTC native code may communicate with a digital audio file or other audio stream, allowing automated testing of cloud contact center and WebRTC infrastructure/services **1650**. Audio files may be prepared in advance or generated programmatically depending on the implementation of the WebRTC APIs. The automated agent or agents (depending on the implementation) may then communicate either directly, over a network, or with the web browser process on the same computing device, with audio files that mimic a software microphone or other audio stream to test responses, response times, reliability, and any other metrics or functionality desired to be tested by the operating network **1660**, the audio output being able to be captured or captured and analyzed, discarded and deleted, or may be ignored and handled in some alternative manner, as desired depending on the programming. The test results may then be forwarded to the operator services network by either controlling the call

or calls directly through the cloud contact center, or by being sent the results of the tests over a network **1670**.

[0081] FIG. **18** is a method diagram illustrating steps in operating and testing real-time communications between web browsers with a custom TURN (Traversal Using Relays around NAT) server as a man-in-the-middle, according to an embodiment. A browser application is executed on a computing device, such as OPERA™, SAFARI™ CHROME™, or other browsers available, loading a WebRTC “shim” **1710** into memory. A “shim” in computer programming refers to a library or set of functions or methods that intercept API calls to perform one or multiple of several possible actions on the API calls, including altering the arguments passed in the call, handling the operation itself rather than allowing the intended destination to, or redirecting it elsewhere. In this case, a WebRTC shim refers to an injected piece of code that acts similarly to WebRTC APIs in the browser but are not tied to the browser process and may behave differently and scale better than native WebRTC code running in a browser. Cloud contact center communications with the browser are sent to a relay server such as a TURN server first, to bypass NAT such as those provided by firewalls or local routers, if possible **1720**. A WebRTC shim may intercept WebRTC API calls and other cloud contact center communications, as well as manage communications between the browser and a call engine to separate the call engine software rather than operating as part of the browser **1730**. A call engine may process and generate unencrypted Real-Time Transport Protocol (“RTP”) media for the purpose of driving the actual generation of and processing of audio, and in this embodiment does not require an SIP proxy server but can operate with WebRTC signal data processing itself. An operator network that initiates tests of peer-to-peer communications then may forward data through a cloud contact center such as AMAZON CONNECT™, to a browser operating a WebRTC shim and browser-side contact center web-based contact center agent application **1740** for cloud contact center integration. An agent automation engine may then operate as either a simple test of media communication connection, or as a complex test of other automated systems such as browser-based IVRs **1750**. Audio files may be prepared in advance or generated programmatically depending on the implementation of the shimmed APIs. The automated agent or agents (depending on the implementation) may then communicate either directly, over a network, or with the web browser process on the same computing device, with audio files that mimic a software microphone or other audio stream to test responses, response times, reliability, and any other metrics or functionality desired to be tested by the operating network **1760**, the audio output being able to be captured or captured and analyzed, discarded and deleted, or may be ignored and handled in some alternative manner, as desired depending on the programming of the call engine, if audio files are used. The test results may then be forwarded to the operator services network by either controlling the call or calls directly through the cloud contact center, or by being sent the results of the tests over a network **1770**.

[0082] FIG. **19** is a method diagram illustrating steps in operating and testing real-time communications between web browsers using a polyfill technique to implement WebRTC APIs with a custom implementation that bypass a browser’s media and negotiates with an external media server, according to an embodiment. A browser application

is executed on a computing device, such as OPERA™, SAFARI™ CHROME™, or other browsers available, loading a media server wrapper and a WebRTC polyfill **1810** into memory. A polyfill in computer programming refers to a library or set of functions or methods that intercept API calls to perform one or multiple of several possible actions on the API calls, including altering the arguments passed in the call, handling the operation itself rather than allowing the intended destination to, or redirecting it elsewhere. In this case, a WebRTC polyfill refers to an injected piece of code that acts similarly to WebRTC APIs in the browser but are not tied to the browser process and may behave differently and scale better than native WebRTC code running in a browser. A media server wrapper may also be called a media server plugin, or a separate piece of software that communicates with the web browser and WebRTC code. A WebRTC polyfill may intercept WebRTC API calls and other cloud contact center communications, as well as manage communications between the browser and a media server to separate the media server software rather than operating as part of the browser **1820**. The media server may be operated on a different computing device, or the same computing device, and may be connected to over a network. An operator network that initiates tests of peer-to-peer communications then may forward data through a cloud contact center such as AMAZON CONNECT™, to a browser operating a WebRTC polyfill and browser-side contact center web-based contact center agent application **1830** for cloud contact center integration. An agent automation engine may then operate as either a simple test of media communication connection, or as a complex test of other automated systems such as browser-based IVRs **1840**, while a WebRTC polyfill communicates with the media server directly **1850**. A call engine may process and generate unencrypted Real-Time Transport Protocol (“RTP”) media for the purpose of driving the actual generation of and processing of audio, signaling data for SIP being proxied through the polyfill. The media server handles a connection between audio files that may be used for input and output of the test audio. Audio files may be prepared in advance or generated programmatically depending on the implementation of the polyfill APIs. The automated agent or agents (depending on the implementation) may then communicate either directly, over a network, or with the web browser process on the same computing device, with audio files that mimic a software microphone or other audio stream to test responses, response times, reliability, and any other metrics or functionality desired to be tested by the operating network **1860**, the audio output being able to be captured or captured and analyzed, discarded and deleted, or may be ignored and handled in some alternative manner, as desired depending on the programming, by the media server. The test results may then be forwarded to the operator services network by either controlling the call or calls directly through the cloud contact center, or by being sent the results of the tests over a network **1870**.

[0083] Voice quality testing may be performed when audio captured at either end of a conversation can be compared with the initially transmitted audio. In order to perform this comparison, it is necessary to be able control audio that is input on each applicable end of the conversation. An existing call engine allows for input and capture of audio at the customer end of the conversation via legacy methods (including SIP, H.323, and PSTN). However, agent audio in WebRTC-based contact center solutions is delivered through

WebRTC technology to the agent web browser application running on their computer. In this case it is necessary to connect to these audio streams using different technologies.

[0084] FIG. **20** is a method diagram illustrating steps in the operation of an API shim intercepting WebRTC API calls and enabling interactions between a cloud infrastructure or contact center, and an external media engine, with custom functionality in an agent browser, according to an embodiment. A cloud infrastructure stack such as but not limited to AMAZON CONNECT™ makes an HTTP fetch request to client application **3110**, over a network such as the Internet, at which point the client application receives the request and an injected WebRTC API shim hijacks the connection to the normal WebRTC APIs and functionality, the shim instead handling API requests and signaling requests from cloud infrastructure and client application **3120**. Such a WebRTC API shim may take the form of a partial or complete polyfill of JAVASCRIPT™ tools and code, which prevents native WebRTC code from being executed, bypassing it entirely **3130**. The API shim then handles any cloud client application API calls with a connection to an external media server **3140**, as opposed to the internal media server normally used by WebRTC APIs, with an agent automation script communicating with and driving the cloud client app **3150**. The agent automation script in this embodiment drives the actual API calls and agent behavior and responses to user communications, while the shim and external media server handle communications between the virtual agent and API shim **3160** under the direction of the agent automation script. An external media server may communicate using the RTP protocol, to receive and send media with a cloud infrastructure and itself, the API shim giving signaling info to the media server so it may properly connect to and exchange data with the cloud infrastructure system **3170**. Using this method, a browser application may operate and communicate without alteration to a third party through a cloud contact center, and the audio and potentially video data may be redirected away from the browser itself towards an external media server to be handled in a different manner.

[0085] FIG. **21** is a message flow diagram illustrating data exchange between components used in a process of operating and testing real-time communications between web browsers with a dedicated desktop application, according to an embodiment. Components actively sending and receiving messages include an operator network **510**, a cloud contact center **520**, a contact center control panel framework **531**, a WebRTC native implementation **532**, a software Audio Generation Device (“AGD”) **550**, and an automated agent engine **540**. An operator network **510** sends a message to a cloud contact center **520** over a network such as the Internet, comprising a call on the contact center platform, and any relevant test parameters **1910** that might be transmissible to the contact center platform. In response to the call, the contact center sends connection data for the call to an agent to the control panel framework **1920** hosted by a web browser, and then forwards call data and test parameters (if any) **1930** to the web-based contact center agent application **531** and agent automation engine **540**. The agent automation engine sends back agent data including the browser status to simulate an agent (in this context the “agent” may also be a “client” as far as agent-client calls are concerned, and may be better understood as a peer in this context) **1940** to both the WebRTC native API **532** and the web-based contact center agent application **531**. The WebRTC native imple-

mentation 532 sends requests for audio to a software audio generation device 550, 1950, at which point the audio generation device sends the audio to either or both of the WebRTC implementation 532 and automated agent 540, 1960, to allow for end-to-end testing of the media connection between the simulated agent and the browser-native WebRTC client implementation. Results of the connection test and call data are sent back 1970 to the web-based contact center agent application 531 from the WebRTC APIs 532, and then sent back to the operator network 510 during or after the test and call completion, depending on the implementation of the cloud contact center's control panel framework.

[0086] FIG. 22 is a message flow diagram illustrating data exchange between components used in a process of operating and testing real-time communications between web browsers without a dedicated desktop application, according to an embodiment. Components actively sending and receiving messages include an operator network 610, a cloud contact center 620, a web-based contact center agent application 631, a WebRTC native implementation 632, a software microphone and possibly speaker 632a, an automated agent engine 640, and at least one but potentially a plurality of digital audio files 2005. An operator network 610 sends a message to a cloud contact center 620 over a network such as the Internet, comprising a call on the contact center platform, and any relevant test parameters 2010 that might be transmissible to the contact center platform. In response to the call, the contact center sends connection data for the call to an agent to the control panel framework 2020 hosted by a web browser, and then forwards call data and test parameters (if any) 2030 to the web-based contact center agent application and agent automation engine 640. The agent automation engine sends back agent data including the browser status to simulate an agent (in this context the "agent" may also be a "client" as far as agent-client calls are concerned, and may be better understood as a peer in this context) 2040 to both the WebRTC native API 632 and the web-based contact center agent application 631. The WebRTC native implementation 632 sends requests for audio to a software microphone 632a, 2050, the audio being provided by an audio file or files 2005, 2060, at which point the audio generation device sends the processed and generated audio to either or both of the WebRTC implementation 632 and automated agent 640, 2070, to allow for end-to-end testing of the media connection between the simulated agent and the browser-native WebRTC client implementation. Results of the connection test and call data are sent back 2080 to the web-based contact center agent application 631 from the WebRTC APIs 632, and then sent back to the operator network 610 during or after the test and call completion, depending on the implementation of the cloud contact center's control panel framework.

[0087] FIG. 23 is a message flow diagram illustrating data exchange between components used in a process of operating and testing real-time communications between web browsers using a cloud contact center such as AMAZONCONNECT™, according to an embodiment. Components actively sending and receiving messages include an operator network 710, a cloud contact center 720, a contact center control panel framework 732, a WebRTC shim 731, a media server 760, an automated agent engine 740, and at least one but potentially a plurality of digital audio files 2105. An operator network 710 sends a message to a cloud contact

center 720 over a network such as the Internet, comprising a call on the contact center platform, and any relevant test parameters 2110 that might be transmissible to the contact center platform. In response to the call, the contact center sends connection data for the call to an agent to the control panel framework 2120 hosted by a web browser, and then forwards call data and test parameters (if any) 2130 to the web-based contact center agent application 732 and agent automation engine 740. The agent automation engine sends back agent data including the browser status to simulate an agent (in this context the "agent" may also be a "client" as far as agent-client calls are concerned, and may be better understood as a peer in this context) 2140 to both the WebRTC shim APIs 731 and the web-based contact center agent application 732. The WebRTC shim 731 sends requests for audio to a media server 760, 2150, the audio being provided by an audio file or files 2105, 2160, at which point the audio generation device sends the processed and generated audio to either or both of the WebRTC implementation 731 and automated agent 740, 2170, to allow for end-to-end testing of the media connection between the simulated agent and the WebRTC shim implementation. Results of the connection test and call data are sent back 2180 to the web-based contact center agent application 732 from the WebRTC APIs 731, and then sent back to the operator network 710 during or after the test and call completion, depending on the implementation of the cloud contact center's control panel framework.

[0088] FIG. 24 is a message flow diagram illustrating data exchange between components used in a process of operating and testing real-time communications between web browsers using a media server as a proxy for a call engine, according to an embodiment. FIG. 23 is a message flow diagram illustrating data exchange between components used in a process of operating and testing real-time communications between web browsers using a cloud contact center such as AMAZONCONNECT™, according to an embodiment. Components actively sending and receiving messages include an operator network 810, a cloud contact center 820, a contact center control panel framework 831, a WebRTC shim 832, a media server 850, an automated agent engine 840, an SIP proxy 860, and a call engine 870. An operator network 810 sends a message to a cloud contact center 820 over a network such as the Internet, comprising a call on the contact center platform, and any relevant test parameters 2205 that might be transmissible to the contact center platform. In response to the call, the contact center sends connection data for the call to an agent to the control panel framework 2210 hosted by a web browser, and then forwards call data and test parameters (if any) 2215 to the web-based contact center agent application 831 and agent automation engine 840. The agent automation engine sends back agent data including the browser status to simulate an agent (in this context the "agent" may also be a "client" as far as agent-client calls are concerned, and may be better understood as a peer in this context) 2220 to both the WebRTC shim APIs 832 and the web-based contact center agent application 831. The WebRTC shim 832 sends requests for audio to a media server 850, 2225, which communicates to the SIP proxy service 860 to establish SIP (Session Initiation Protocol) data. The SIP signaling data is returned by the SIP proxy 2230, and sent to the call engine 2235 so that the call engine can use the session information to send client data including any initial audio prompts 2240

to the media server **850**, and receive unencrypted media in an RTP stream back **2245** from the media server, which also communicates this data to the WebRTC shim and therefore to the automated agent. Results of the connection test and call data are sent back **2250** to the web-based contact center agent application **831** from the WebRTC APIs **832**, and then sent back to the operator network **810** during or after the test and call completion, depending on the implementation of the cloud contact center's control panel framework.

[0089] FIG. **25** is a message flow diagram illustrating data exchange between components used in a process of operating and testing real-time communications between web browsers with all server-side functions integrated into a call engine, according to an embodiment. FIG. **23** is a message flow diagram illustrating data exchange between components used in a process of operating and testing real-time communications between web browsers using a cloud contact center such as AMAZONCONNECT™, according to an embodiment. Components actively sending and receiving messages include an operator network **910**, a cloud contact center **920**, a contact center control panel framework **932**, a WebRTC shim **931**, an automated agent engine **940**, and an operator call engine **950** that may be used by an agent, or used by a synthetic agent. An operator network **910** sends a message to a cloud contact center **920** over a network such as the Internet, comprising a call on the contact center platform, and any relevant test parameters **2305** that might be transmissible to the contact center platform. In response to the call, the contact center sends connection data for the call to an agent to the control panel framework **2310** hosted by a web browser, and then forwards call data and test parameters (if any) **2315** to the web-based contact center agent application **932** and agent automation engine **940**. The agent automation engine sends back agent data including the browser status to simulate an agent (in this context the "agent" may also be a "client" as far as agent-client calls are concerned, and may be better understood as a peer in this context) **2320** to both the WebRTC shim APIs **931** and the web-based contact center agent application **932**. The WebRTC shim **931** sends requests for audio to a call engine **950**, **2325**, at which point the call engine may send call media to the WebRTC shim, which then also sends the call media to the automated agent **2330**. Client data from the automated agent's responses are sent to the WebRTC shim **2335**, at the end of the exchanges of the media between these three components results of the connection test and call data are sent back **2340** to the web-based contact center agent application **932** from the WebRTC APIs **931**, and then sent back to the operator network **910** during or after the test and call completion, depending on the implementation of the cloud contact center's control panel framework.

[0090] FIG. **32** (PRIOR ART) is a block diagram showing the typical mode of operation of existing WebRTC browser implementations from within a network external to a call center. As with other figures of prior art previously presented, this figure illustrates the prior art of a WebRTC but comprising a remote working environment. According to one embodiment, a call center agent may use his or her own equipment, including but not limited to a computer **3200**, audio equipment **3204/3205** (e.g., a headset, speakers and a boom mic, etc.), and local networking devices **3220** (e.g., modem, router, etc.). While not shown, local networked devices such as tablets, smart TVs, and any other Internet-connected device that shares resources with the agent's

computer **3200** may be taken into account in the following embodiment, such as for performing a network speed test or network health test.

[0091] To perform call center work remotely, the agent may utilize a browser **3201** on his or her computer **3200** that initiates a WebRTC session **3202** to a WebRTC-based cloud platform **3210** which works in the same manner as previously described in other figures. Audio from calls is processed through the computer's **3200** sound card **3203**. Following FIG. **32** (PRIOR ART), FIG. **33** introduces a browser extension (or a sideloaded application) comprising a real-time testing module **3300** that communicates with a testing and dashboard server **3310**. Real-time testing module **3300** is similar in function to the embodiments presented in patent application Ser. No. 16/999,028 which is incorporated herein by reference. However, wherein the previous embodiments perform testing with synthetic agents and synthetic customers, this and following embodiments monitor live calls and may perform active testing. A real-time testing module **3300** may comprise a statistics relay service **3301** which periodically sends statistics and/or test data to an end point server (e.g., **3310**), a passive testing submodule **3302** which performs non-intrusive and non-interrupting testing of the call center agent's environment, and lastly an active testing submodule **3303** which performs the live call testing between an agent's computer **3200** and a server. Furthermore, this embodiment is tailored for, but not limited to cloud contact centers (e.g., AMAZON CONNECT, TWILIO, NICE, GENESYS CLOUD CX).

[0092] Real-time testing module **3300** injects or builds in code (i.e., via a statistics relay service **3301**) that hooks into a platform and WebRTC system within the agent's browser and streams information and statistics up to a back end server **3310** which may be hosted by AMAZON WEB SERVICES and provides a portal view of historical and real-time information about what is happening on the agent's desktop. The dashboard centers around network statistics but may also comprise other metrics related to calls. Network statistics (e.g., jitter, packet loss, bandwidth, etc.) are then combined together with the G.107 ITU (International Telecom Union) standard—which is a computational model for use in transmission planning—to produce a voice quality quantitative MOS score, which may be used to indicate low quality.

[0093] Real-time testing module **3300** employs browser APIs such as RTC API which may be an interface representing a WebRTC connection between the local computer and a remote peer. It may provide methods to connect to a remote peer, maintain and monitor the connection. A hardware API may be used which determines the number of logical processors available to run threads on the user's computer. Additionally, a device memory API may be used which measures the approximate amount of device memory in gigabytes and where the reported value is imprecise to curtail fingerprinting. It may be approximated by rounding down to the nearest power of 2, then dividing that number by 1024. It is then clamped within lower and upper bounds to protect the privacy of owners of very low- or high-memory devices. A last exemplary API may comprise a geolocation API which may be used to retrieve the user's location, so that it can, for example, be used to display their position using a further mapping API.

[0094] A non-exhaustive list of other API functions that may be utilized comprises a reverse Geocoding API that

converts coordinates to human-readable addresses and breaks down addresses into elements like street, city, state etc.; an API which is used to determine the Internet Service Provider, and autonomous system organization and number associated with an IP address and includes fallback geo data if no triangulation was possible via GPS or Wi-Fi signals; and time synchronization API which may be a configurable service that is used to determine the offset of the Agent's PC clock with a constant time.

[0095] A non-exhaustive list of libraries that may be utilized comprises libraires which comprise a large collection of open Internet performance data; a WebRTC adapter which is a shim to insulate apps from specification changes and prefix differences in WebRTC; Detect RTC which is a tiny JavaScript library that can be used to detect WebRTC features, e.g., system having speakers, microphone or webcam, screen capturing is supported, number of audio/video devices etc.; a library to generate RFC-compliant UUIDs in JavaScript; and various UI libraires to create the real-time testing module **3300** (i.e., extension or sideloaded app) interface.

[0096] The interface of a real-time testing module **3300** may comprise a window or other UI element that allows an agent to select a variety of options such as a health report, call statistics, options to vote on the quality of a call, and submit bug reports. A health report may be generated using a passive testing submodule **3302** that produces a general pass or fail rating for components such as the agent's browser (by detecting type, version, private browsing, etc.), connectivity and speed (by detecting latency minimum, maximum, and average values), firewalls (by detecting open ports and access to domains), microphones (by detecting device labels and status), speakers (by detecting device labels and status), and permissions (by detecting if various items are supported such as WebRTC, ORTC, screen capturing, web sockets, fetching of user media, audio context, creation of media streams, RTP data channels, set sink IDs, remote stream processing, multi-monitors, promises, and applied constraints and further by detecting various hardware such as microphones, speakers, webcams and lastly by detecting if the browser or website has permissions to access the hardware). A statistics screen may show an agent's and the caller's MOS score over time to give the agent an idea of the quality of the call. These reports and statistics may be communicated to a testing dashboard server **3310** where real-time metrics and historical data is displayed on a dashboard comprising visual elements such as pie charts, bar graphs, and other graphical elements that may be used to monitor the call center within a NOC **3321** (e.g., to identify failure patterns) or for management **3320** purposes.

[0097] Another component of a real-time testing module **3300** may be an active testing submodule **3303** (see FIG. **34**) which once started, either by an agent or remotely by a NOC **3321** agent, may put the call center agent in an unavailable state, i.e., the call center agent will not receive any new calls, and the active testing submodule **3303** may then dial out to a POP (point of presence), by creating a telephony connection, and intercept the audio of the active test call from within the browser **3401**. When the active testing submodule **3303** takes over the audio, it may do so by intercepting the data before the sound card **3203** such that the microphone **3205** is no longer the source of audio for the call and the output of the call is no longer the speakers **3204**. Capture audio is stored in an in-memory buffer then streamed to end

point server which at that point may be fed into a voice quality algorithm and may be analyzed using a referenced based metric to determine the source of one or more problems experienced by an agent. Additionally, network statistics may be captured during the active test call such that the active test call and statistics may be compared with what the passive test to determine if both tests report the same issues (e.g., robotic voice, dropout, etc.). Active tests may be configured to run any length of time. This is important because not all issues arise or are detectable within the initial time frame.

[0098] FIG. **35** is a block diagram illustrating an exemplary security configuration for a real-time testing module. An agent may be authorized access to the real-time testing service backend through the following process: the application access key and secret (provided by the hosting service) is base64 encoded and added to the Authorization header **3551** for the request **3550**, along with information about the agent **3551**. The backend **3500a-n** will validate the supplied information and return a short-lived JWT **3552**. This JWT may be added to the URL for the secure WebSocket to validate the socket connect **3553**.

[0099] The browser extension is configured in two stages, FIG. **36** and FIG. **37** respectively. The first stage is to generate a link between a portal **3601** and one or more webapps **3600a-n** containing the encrypted data for the request, wherein a JWT is created and embedded with the agent username and unique (one-time) request identifier **3650**. The expiry date is set on the token, which defaults to 24 hours. The token is encrypted using HMAC SHA-256 and is added to a URL. This URL is sent to the Agent to initiate the extension configuration process **3652**. The agent clicks on the provided link **3651** to initiate the configuration process for the real-time testing module browser extension **3300**. The page validates the extension has been installed and prompts to install the extension if it's missing **3750**. An agent clicks on the configure button or is set to automatically configure. The token is validated (for tampering and expiration), and the embedded request identifier is validated to ensure it's not been used before, and the embedded Agent username is validated **3751/3752/3753**. A unique access key and secret are generated and associated with the Agent. This together with other configuration data is returned to the Agent **3754**. The extension will intercept the response and store the configuration data in secure browser storage.

[0100] FIG. **38** is a flow diagram showing the method of operation of a real-time testing module and a testing and dashboard server. The following method may be implemented on a system for monitoring and testing real-time communications between web browsers and callers such as the various embodiments herein. In a first step **3801**, a code segment is injected into a call center agent's browser, wherein the browser is running a WebRTC session and the injected code acts upon that WebRTC session.

[0101] In a second step **3802**, use the injected code segment to collect information during a live call from within the WebRTC session. This information may be a recording of the call, metadata about the call, and other information known to those in the art.

[0102] In a third step **3803**, collect information related to the operating environment of the call center agent's computer. As described above, this may comprise information about an agent's browser, network connectivity and network speed, firewalls, hardware (e.g., microphones, speakers,

monitors, etc.), and permissions. The operating environment may also perform port scans, IP scans (to detect other devices on the agent's local network), and other scans to determine the security and resource load on the network and the agent's computer.

[0103] In a fourth step **3804**, stream the plurality of collected information to a testing and dashboard server. The server operating as both a collection and analysis point for network and call statistics as well as for active and passive diagnostic testing.

[0104] In a fifth step **3805**, receive a request to perform a diagnostic test. The diagnostic test may be a passive or active test as described herein. If the request is for an active test, the active test (via the real-time testing module) may be initiated remotely by NOC agents, management, or locally activated by the agent in some embodiments, and temporarily suspends the call center agent's incoming calls, effectively putting the agent on a work hold in order to perform the active test and where the agent is automatically placed back into a working status at the completion of the active test. At this point the real-time testing module creates a telephony connection with a point-of-presence server, conducts an automated live call with the server via the telephony connection, captures the incoming and outgoing audio in an in-memory buffer (rather than the audio being processed by the agent's computer's sound card), and streams the audio and live call metadata to the testing and dashboard server for analysis and triage if necessary.

[0105] In a sixth step **3806**, perform the requested diagnostics test and in a seventh step **3807** add the results of the diagnostics test to the stream of collected information.

[0106] In an eight **3808** and ninth **3809** step, display a plurality of infographics based on the collected information and compile diagnostics information based on a comparative analysis between at least one diagnostic test, the agent's reported operating environment, and live call data. The infographics may be hosted on a webserver, displayed locally, sent over a network, sent to a mobile application, displayed on a call agent's/NOC personnel's/manager's computer, or some combination thereof. The dashboard may display infographics such as a historical and real-time analysis of call statuses, a breakdown of MOS scores between all the calls, up- or down-time of an Internet Service Provider, a list of graphics of the geolocations of calls and agents, and how active specific call agents are. These metrics may be broken down into specific time frames and displayed as pie charts, bar graphs, lists, and other types of visual or text aids used in infographics. Furthermore, network statistics may be displayed as well such as jitter, packet loss, round-trip time, etc.

Hardware Architecture

[0107] Generally, the techniques disclosed herein may be implemented on hardware or a combination of software and hardware. For example, they may be implemented in an operating system kernel, in a separate user process, in a library package bound into network applications, on a specially constructed machine, on an application-specific integrated circuit ("ASIC"), or on a network interface card.

[0108] Software/hardware hybrid implementations of at least some of the aspects disclosed herein may be implemented on a programmable network-resident machine (which should be understood to include intermittently connected network-aware machines) selectively activated or

reconfigured by a computer program stored in memory. Such network devices may have multiple network interfaces that may be configured or designed to utilize different types of network communication protocols. A general architecture for some of these machines may be described herein in order to illustrate one or more exemplary means by which a given unit of functionality may be implemented. According to specific aspects, at least some of the features or functionalities of the various aspects disclosed herein may be implemented on one or more general-purpose computers associated with one or more networks, such as for example an end-user computer system, a client computer, a network server or other server system, a mobile computing device (e.g., tablet computing device, mobile phone, smartphone, laptop, or other appropriate computing device), a consumer electronic device, a music player, or any other suitable electronic device, router, switch, or other suitable device, or any combination thereof. In at least some aspects, at least some of the features or functionalities of the various aspects disclosed herein may be implemented in one or more virtualized computing environments (e.g., network computing clouds, virtual machines hosted on one or more physical computing machines, or other appropriate virtual environments).

[0109] Referring now to FIG. 26, there is shown a block diagram depicting an exemplary computing device **10** suitable for implementing at least a portion of the features or functionalities disclosed herein. Computing device **10** may be, for example, any one of the computing machines listed in the previous paragraph, or indeed any other electronic device capable of executing software- or hardware-based instructions according to one or more programs stored in memory. Computing device **10** may be configured to communicate with a plurality of other computing devices, such as clients or servers, over communications networks such as a wide area network a metropolitan area network, a local area network, a wireless network, the Internet, or any other network, using known protocols for such communication, whether wireless or wired.

[0110] In one embodiment, computing device **10** includes one or more central processing units (CPU) **12**, one or more interfaces **15**, and one or more busses **14** (such as a peripheral component interconnect (PCI) bus). When acting under the control of appropriate software or firmware, CPU **12** may be responsible for implementing specific functions associated with the functions of a specifically configured computing device or machine. For example, in at least one embodiment, a computing device **10** may be configured or designed to function as a server system utilizing CPU **12**, local memory **11** and/or remote memory **16**, and interface(s) **15**. In at least one embodiment, CPU **12** may be caused to perform one or more of the different types of functions and/or operations under the control of software modules or components, which for example, may include an operating system and any appropriate applications software, drivers, and the like.

[0111] CPU **12** may include one or more processors **13** such as, for example, a processor from one of the Intel, ARM, Qualcomm, and AMD families of microprocessors. In some embodiments, processors **13** may include specially designed hardware such as application-specific integrated circuits (ASICs), electrically erasable programmable read-only memories (EEPROMs), field-programmable gate arrays (FPGAs), and so forth, for controlling operations of

computing device **10**. In a specific embodiment, a local memory **11** (such as non-volatile random access memory (RAM) and/or read-only memory (ROM), including for example one or more levels of cached memory) may also form part of CPU **12**. However, there are many different ways in which memory may be coupled to system **10**. Memory **11** may be used for a variety of purposes such as, for example, caching and/or storing data, programming instructions, and the like. It should be further appreciated that CPU **12** may be one of a variety of system-on-a-chip (SOC) type hardware that may include additional hardware such as memory or graphics processing chips, such as a QUALCOMM SNAPDRAGON™ or SAMSUNG EXYNOS™ CPU as are becoming increasingly common in the art, such as for use in mobile devices or integrated devices.

[0112] As used herein, the term “processor” is not limited merely to those integrated circuits referred to in the art as a processor, a mobile processor, or a microprocessor, but broadly refers to a microcontroller, a microcomputer, a programmable logic controller, an application-specific integrated circuit, and any other programmable circuit.

[0113] In one embodiment, interfaces **15** are provided as network interface cards (NICs). Generally, NICs control the sending and receiving of data packets over a computer network; other types of interfaces **15** may for example support other peripherals used with computing device **10**. Among the interfaces that may be provided are Ethernet interfaces, frame relay interfaces, cable interfaces, DSL interfaces, token ring interfaces, graphics interfaces, and the like. In addition, various types of interfaces may be provided such as, for example, universal serial bus (USB), Serial, Ethernet, FIREWIRE™, THUNDERBOLT™, PCI, parallel, radio frequency (RF), BLUETOOTH™, near-field communications (e.g., using near-field magnetics), 802.11 (WiFi), frame relay, TCP/IP, ISDN, fast Ethernet interfaces, Gigabit Ethernet interfaces, Serial ATA (SATA) or external SATA (ESATA) interfaces, high-definition multimedia interface (HDMI), digital visual interface (DVI), analog or digital audio interfaces, asynchronous transfer mode (ATM) interfaces, high-speed serial interface (HSSI) interfaces, Point of Sale (POS) interfaces, fiber data distributed interfaces (FDDIs), and the like. Generally, such interfaces **15** may include physical ports appropriate for communication with appropriate media. In some cases, they may also include an independent processor (such as a dedicated audio or video processor, as is common in the art for high-fidelity A/V hardware interfaces) and, in some instances, volatile and/or non-volatile memory (e.g., RAM).

[0114] Although the system shown in FIG. **26** illustrates one specific architecture for a computing device **10** for implementing one or more of the inventions described herein, it is by no means the only device architecture on which at least a portion of the features and techniques described herein may be implemented. For example, architectures having one or any number of processors **13** may be used, and such processors **13** may be present in a single device or distributed among any number of devices. In one embodiment, a single processor **13** handles communications as well as routing computations, while in other embodiments a separate dedicated communications processor may be provided. In various embodiments, different types of features or functionalities may be implemented in a system according to the invention that includes a client device (such

as a tablet device or smartphone running client software) and server systems (such as a server system described in more detail below).

[0115] Regardless of network device configuration, the system of the present invention may employ one or more memories or memory modules (such as, for example, remote memory block **16** and local memory **11**) configured to store data, program instructions for the general-purpose network operations, or other information relating to the functionality of the embodiments described herein (or any combinations of the above). Program instructions may control execution of or comprise an operating system and/or one or more applications, for example. Memory **16** or memories **11**, **16** may also be configured to store data structures, configuration data, encryption data, historical system operations information, or any other specific or generic non-program information described herein.

[0116] Because such information and program instructions may be employed to implement one or more systems or methods described herein, at least some network device embodiments may include nontransitory machine-readable storage media, which, for example, may be configured or designed to store program instructions, state information, and the like for performing various operations described herein. Examples of such nontransitory machine-readable storage media include, but are not limited to, magnetic media such as hard disks, floppy disks, and magnetic tape; optical media such as CD-ROM disks; magneto-optical media such as optical disks, and hardware devices that are specially configured to store and perform program instructions, such as read-only memory devices (ROM), flash memory (as is common in mobile devices and integrated systems), solid state drives (SSD) and “hybrid SSD” storage drives that may combine physical components of solid state and hard disk drives in a single hardware device (as are becoming increasingly common in the art with regard to personal computers), memristor memory, random access memory (RAM), and the like. It should be appreciated that such storage means may be integral and non-removable (such as RAM hardware modules that may be soldered onto a motherboard or otherwise integrated into an electronic device), or they may be removable such as swappable flash memory modules (such as “thumb drives” or other removable media designed for rapidly exchanging physical storage devices), “hot-swappable” hard disk drives or solid state drives, removable optical storage discs, or other such removable media, and that such integral and removable storage media may be utilized interchangeably. Examples of program instructions include both object code, such as may be produced by a compiler, machine code, such as may be produced by an assembler or a linker, byte code, such as may be generated by for example a JAVA™ compiler and may be executed using a Java virtual machine or equivalent, or files containing higher level code that may be executed by the computer using an interpreter (for example, scripts written in Python, Perl, Ruby, Groovy, or any other scripting language).

[0117] In some embodiments, systems according to the present invention may be implemented on a standalone computing system. Referring now to FIG. **27**, there is shown a block diagram depicting a typical exemplary architecture of one or more embodiments or components thereof on a standalone computing system. Computing device **20** includes processors **21** that may run software that carry out

one or more functions or applications of embodiments of the invention, such as for example a client application 24. Processors 21 may carry out computing instructions under control of an operating system 22 such as, for example, a version of MICROSOFT WINDOWS™ operating system, APPLE OSX™ or iOS™ operating systems, some variety of the Linux operating system, ANDROID™ operating system, or the like. In many cases, one or more shared services 23 may be operable in system 20, and may be useful for providing common services to client applications 24. Services 23 may for example be WINDOWS™ services, user-space common services in a Linux environment, or any other type of common service architecture used with operating system 21. Input devices 28 may be of any type suitable for receiving user input, including for example a keyboard, touchscreen, microphone (for example, for voice input), mouse, touchpad, trackball, or any combination thereof. Output devices 27 may be of any type suitable for providing output to one or more users, whether remote or local to system 20, and may include for example one or more screens for visual output, speakers, printers, or any combination thereof. Memory 25 may be random-access memory having any structure and architecture known in the art, for use by processors 21, for example to run software. Storage devices 26 may be any magnetic, optical, mechanical, memristor, or electrical storage device for storage of data in digital form (such as those described above, referring to FIG. 26). Examples of storage devices 26 include flash memory, magnetic hard drive, CD-ROM, and/or the like.

[0118] In some embodiments, systems of the present invention may be implemented on a distributed computing network, such as one having any number of clients and/or servers. Referring now to FIG. 28, there is shown a block diagram depicting an exemplary architecture 30 for implementing at least a portion of a system according to an embodiment of the invention on a distributed computing network. According to the embodiment, any number of clients 33 may be provided. Each client 33 may run software for implementing client-side portions of the present invention; clients may comprise a system 20 such as that illustrated in FIG. 27. In addition, any number of servers 32 may be provided for handling requests received from one or more clients 33. Clients 33 and servers 32 may communicate with one another via one or more electronic networks 31, which may be in various embodiments any of the Internet, a wide area network, a mobile telephony network (such as CDMA or GSM cellular networks), a wireless network (such as WiFi, WiMAX, LTE, and so forth), or a local area network (or indeed any network topology known in the art; the invention does not prefer any one network topology over any other). Networks 31 may be implemented using any known network protocols, including for example wired and/or wireless protocols.

[0119] In addition, in some embodiments, servers 32 may call external services 37 when needed to obtain additional information, or to refer to additional data concerning a particular call. Communications with external services 37 may take place, for example, via one or more networks 31. In various embodiments, external services 37 may comprise web-enabled services or functionality related to or installed on the hardware device itself. For example, in an embodiment where client applications 24 are implemented on a smartphone or other electronic device, client applications 24 may obtain information stored in a server system 32 in the

cloud or on an external service 37 deployed on one or more of a particular enterprise's or user's premises.

[0120] In some embodiments of the invention, clients 33 or servers 32 (or both) may make use of one or more specialized services or appliances that may be deployed locally or remotely across one or more networks 31. For example, one or more databases 34 may be used or referred to by one or more embodiments of the invention. It should be understood by one having ordinary skill in the art that databases 34 may be arranged in a wide variety of architectures and using a wide variety of data access and manipulation means. For example, in various embodiments one or more databases 34 may comprise a relational database system using a structured query language (SQL), while others may comprise an alternative data storage technology such as those referred to in the art as “NoSQL” (for example, HADOOP CASSANDRA™, GOOGLE BIGTABLE™, and so forth). In some embodiments, variant database architectures such as column-oriented databases, in-memory databases, clustered databases, distributed databases, or even flat file data repositories may be used according to the invention. External remote storage 38 may be used in addition or in place of any local storage. It will be appreciated by one having ordinary skill in the art that any combination of known or future database technologies may be used as appropriate, unless a specific database technology or a specific arrangement of components is specified for a particular embodiment herein. Moreover, it should be appreciated that the term “database” as used herein may refer to a physical database machine, a cluster of machines acting as a single database system, or a logical database within an overall database management system. Unless a specific meaning is specified for a given use of the term “database”, it should be construed to mean any of these senses of the word, all of which are understood as a plain meaning of the term “database” by those having ordinary skill in the art.

[0121] Similarly, most embodiments of the invention may make use of one or more security systems 36 and configuration systems 35. Security and configuration management are common information technology (IT) and web functions, and some amount of each are generally associated with any IT or web systems. It should be understood by one having ordinary skill in the art that any configuration or security subsystems known in the art now or in the future may be used in conjunction with embodiments of the invention without limitation, unless a specific security 36 or configuration system 35 or approach is specifically required by the description of any specific embodiment.

[0122] FIG. 29 shows an exemplary overview of a computer system 40 as may be used in any of the various locations throughout the system. It is exemplary of any computer that may execute code to process data. Various modifications and changes may be made to computer system 40 without departing from the broader scope of the system and method disclosed herein. Central processor unit (CPU) 41 is connected to bus 42, to which bus is also connected memory 43, nonvolatile memory 44, display 47, input/output (I/O) unit 48, and network interface card (NIC) 53. I/O unit 48 may, typically, be connected to keyboard 49, pointing device 50, hard disk 52, real-time clock 51, and potentially also a camera 57. NIC 53 connects to network 54, which may be the Internet or a local network 56, which local network may or may not have connections to the Internet. Such a network may utilize a router 55 or wired or wireless

Local Area Network (LAN) **56**. Also shown as part of system **40** is power supply unit **45** connected, in this example, to a main alternating current (AC) supply **46**. Not shown are batteries that could be present, and many other devices and modifications that are well known but are not applicable to the specific novel functions of the current system and method disclosed herein. It should be appreciated that some or all components illustrated may be combined, such as in various integrated applications, for example Qualcomm or Samsung system-on-a-chip (SOC) devices, or whenever it may be appropriate to combine multiple capabilities or functions into a single hardware device (for instance, in mobile devices such as smartphones, video game consoles, in-vehicle computer systems such as navigation or multimedia systems in automobiles, or other integrated hardware devices).

[0123] FIG. 30 (PRIOR ART) is a block diagram showing the typical mode of operation of existing WebRTC browser implementations in which WebRTC APIs use an internal media server for media processing. WebRTC browser **3030** client applications **3031** (e.g., the Amazon Connect Contact Control Panel (CCP)) utilize a set of application programming interfaces **3032** (e.g., the WebRTC Native Code package) exposed by the web browser **3030** to allow for the environment setup, initiation, and control of media sessions between the client application **3031** and some other entity **3010**. In the case of contact center applications, for example, the web browser **3030** would be instantiated on a contact center agent computer **3020**, and the other entity **3010** would be a contact center framework such as Amazon Connect or Twilio Flex running on servers in the cloud. The APIs **3032** provide control of a black box communication system built into the browser, where the application does not need to concern itself with actual network communication, data decoding, or playback/recording devices. The APIs **3032** hide all these intricacies and utilize functionality in-built in the browser, such as a built-in media server **3033** to process the network packets, and send them to/from audio outputs **3021** (e.g., speakers) and audio inputs **3022** (e.g., microphones). However, this standard WebRTC implementation has drawbacks from the standpoint of media (audio/video) testing. First, the browser media server code is not optimized to run multiple sessions on a single server, so does not scale well and is difficult to use for load testing. Multiple sessions and/or connections is very CPU intensive and the internal media server is very CPU sensitive. At the slightest hint of CPU starvation, media quality drops dramatically, making media quality analysis of the connection impossible. Second, the standard WebRTC implementation sends the audio to the standard operating system (e.g., Windows) audio devices, which are not optimal for access and control for voice quality testing. Modifying the client application **3031** in many contexts is not feasible (e.g., in contact center applications where the contact center does not want to test a customized version of its application), so another method of routing media for separate processing outside of the browser is needed.

[0124] FIG. 31 is a block diagram showing the use of a WebRTC “shim” to intercept WebRTC media for separate processing outside of the browser through polyfill of JavaScript WebRTC APIs. In this embodiment, a server **3120** instantiates one or more browsers **3130a-n**, each running a client application **3131** (e.g., the Amazon Connect Contact Control Panel (CCP)). The browser(s) utilize a set

of WebRTC application programming interfaces **3032** (e.g., the WebRTC Native Code package) exposed by the web browsers **3130a-n** to allow for the environment setup, initiation, and control of media sessions between the client application **3131** and some other entity **3110**. In the case of contact center applications, for example, the web browsers **3130a-n** would be instantiated on a server acting as a virtual contact center **3120** or on a server at an actual contact center, and the other entity **3110** would be a contact center framework such as Amazon Connect or Twilio Flex running on servers in the cloud. In contrast to the standard WebRTC implementation, however, in this embodiment, a software “shim” is used to bypass the WebRTC internal media server **3123** and redirect the media to an external media server **3123** (in some cases called a call engine) for analysis by an audio/video quality analyzer **3122**.

[0125] The “shim” consists of changing the operating code of one or more of the WebRTC APIs through a process called “polyfilling.” Polyfilling is the use of JavaScript to insert code into the API which substitutes for the native code in the API and overrides any the operation of the API inside of the browser JavaScript engine. When the client application **3131** makes an API call for media handling, the polyfilled code intercepts the API call. Instead of resulting in negotiation of call media with the browser’s **3130a-n** internal media server **3133**, the API call results in negotiation of the media session with an external media server application **3123**, replicating all requisite the functionality of WebRTC’s `RTCPeerConnection` object with this external media server negotiation.

[0126] Once the external media server application has access to the media streams, the media streams can be tested for audio and/or video quality in both directions (i.e., from WebRTC-based cloud infrastructure **3110** to external media server **3123**, and vice-versa) using an audio/video quality analyzer **3122** separate from the standard operating system (e.g., Windows) audio devices. External media server application **3123** can be configured specifically to perform well when processing multiple media streams concurrently, allowing the operation of multiple concurrent testing agents at a much higher density (i.e., scalability). The testing agents may be automated through use of an agent automation script **3121**, allowing a high volume of automated testing.

[0127] In various embodiments, functionality for implementing systems or methods of the present invention may be distributed among any number of client and/or server components. For example, various software modules may be implemented for performing various functions in connection with the present invention, and such modules may be variously implemented to run on server and/or client components.

[0128] The skilled person will be aware of a range of possible modifications of the various embodiments described above. Accordingly, the present invention is defined by the claims and their equivalents.

What is claimed is:

1. A system for monitoring and testing of web real-time communications (WebRTC) sessions, comprising a computing device comprising a memory, a processor, and a plurality of programming instructions stored in the memory which, when operating on the processor, causes the computing device to:

- initiate a WebRTC session on a web browser operating on the computing device;

use an injected code segment within the web browser to collect live call data during a live call from within the WebRTC session;
collect information related to an operating environment of the computing device on which the web browser is operating;
perform a diagnostic test on the WebRTC session to obtain a diagnostic test result; and
produce a comparative analysis result based on a comparative analysis of the diagnostic test result, the operating environment, and the live call data.

2. The system of claim 1, wherein the diagnostic test is a passive test which provides a report on the health status of the computing device's operating environment.

3. The system of claim 1, wherein the diagnostic test is an active test that is initiated remotely from the computing device and comprises the following operations:

temporarily suspending the incoming WebRTC communications to the computing device;
creating a telephony connection between the computing device and a point-of-presence server;
conducting an automated live call between the computing device and the point-of-presence server via the telephony connection;
capturing incoming audio, outgoing audio, and live call metadata from the automated live call; and
streaming the captured audio and metadata to the real-time testing module for analysis.

4. The system of claim 1, wherein a portion of the plurality of programming instructions is implemented as a browser extension.

5. The system of claim 1, wherein a portion of the plurality of programming instructions is implemented as a sideloaded application.

6. A method for monitoring and testing of web real-time communications (WebRTC) sessions, comprising the steps of:

initiating a WebRTC session on a web browser operating on a computing device;
collecting live call data during a live call from within the WebRTC session using an injected code segment within the web browser;
collecting information related to an operating environment of the computing device on which the web browser is operating;
performing a diagnostic test on the WebRTC session to obtain a diagnostic test result; and
producing a comparative analysis result based on a comparative analysis of the diagnostic test result, the operating environment, and the live call data.

7. The method of claim 6, wherein the diagnostic test is a passive test which provides a report on the health status of the computing device's operating environment.

8. The method of claim 6, wherein:

the diagnostic test is an active test that is initiated remotely from the computing device and comprises the following operations:
temporarily suspending the incoming WebRTC communications to the computing device;
creating a telephony connection between the computing device and a point-of-presence server;
conducting an automated live call between the computing device and the point-of-presence server via the telephony connection;
capturing incoming audio, outgoing audio, and live call metadata from the automated live call; and
streaming the captured audio and metadata to the real-time testing module for analysis.

9. The method of claim 6, wherein a portion of the plurality of programming instructions is implemented as a browser extension.

10. The method of claim 6, wherein a portion of the plurality of programming instructions is implemented as a sideloaded application.

* * * * *