

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12398842
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Thomas; Mathew et al.

Bracket for mounting an electrical fixture housing

Abstract

A ceiling electrical box can include a housing and a bracket. The housing is defined by a rear wall at a first end, at least one sidewall, and an opening at a second end and includes a first emboss tab, a second emboss tab, a pair of screw holes, a pair of first bores, and a pair of second bores. The bracket includes a first portion, a second portion, a pair of first threaded apertures, and a pair of second threaded apertures. The bracket can include a third portion and a fourth portion extending on a first plane of the first portion. The ceiling electrical box can also include a pair of first fasteners to attach the housing to the bracket and a pair of second fasteners to engage the bracket through the housing, the second fasteners configured to receive a fixture plate for a ceiling fixture.

Inventors: Thomas; Mathew (Memphis, TN), Wolfe; James (Memphis, TN), O'Neil; Michael (Memphis, TN)

Applicant: ABB Schweiz AG (Baden, CH)

Family ID: 1000008777700

Assignee: ABB SCHWEIZ AG (Baden, CH)

Appl. No.: 18/476184

Filed: September 27, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240019080 A1	Jan. 18, 2024

Related U.S. Application Data

continuation parent-doc US 17807136 20220615 US 11802659 child-doc US 18476184

Publication Classification

Int. Cl.: H02G3/12 (20060101); F16M13/02 (20060101)

U.S. Cl.:

CPC F16M13/027 (20130101); H02G3/12 (20130101);

Field of Classification Search

CPC: F16M (13/027); H02G (3/12); H02G (3/125); H02G (3/126); H02G (3/121); H02G (3/123); H02G (3/128)

USPC: 248/27.1

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
1853203	12/1931	Cluny	220/3.9	H02G 3/125
D408906	12/1998	Toscano	D23/385	N/A
5954304	12/1998	Jorgensen	248/200.1	H02G 3/125
6734356	12/2003	Gretz	N/A	N/A
6979779	12/2004	Grady	N/A	N/A
7518059	12/2008	Herth	174/53	H02G 3/126
7595448	12/2008	Herth	174/53	H02G 3/20
8967575	12/2014	Gretz	N/A	N/A
9496698	12/2015	Korcz	N/A	H02G 3/10
9702533	12/2016	Harpenau	N/A	F21V 21/03
9735557	12/2016	Gretz	N/A	N/A
9887524	12/2017	Gretz	N/A	H02G 3/081
10103533	12/2017	Gretz	N/A	H02G 3/26
10907807	12/2020	Hsu	N/A	F21S 8/04
10965071	12/2020	Johnson	N/A	H02G 3/125
11050230	12/2020	Gretz	N/A	N/A
11581718	12/2022	Korcz	N/A	H02G 3/123
12166338	12/2023	Baldwin	N/A	E04B 9/006
2006/0016948	12/2005	Herth	248/318	H02G 3/20

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2839211	12/2020	CA	N/A

Primary Examiner: Smith; Nkeisha

Attorney, Agent or Firm: Greenberg Traurig, LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of U.S. patent application Ser. No. 17/807,136, filed on Jun. 15, 2022; which is herein incorporated by reference in its entirety.

FIELD

(1) The present disclosure relates to the field of electrical wiring, and more particularly to modular ceiling fixture electrical boxes for mounting ceiling fans, ceiling light fixtures, and other electrical devices.

BACKGROUND

(2) Ceiling boxes are used to mount ceiling fixtures including light fixtures, ceiling fans, or similar device onto structural members. In addition to providing an enclosure for electrical wiring, ceiling boxes provide mechanical support to the ceiling fixture. Typically, the electrical boxes are made of a plastic-like material. To attach the ceiling fixture to the structural member, the fixture plate of the ceiling fixture attaches to the electrical box by inserting a threaded fastener into threaded receptacles in the electrical box. However, the integrity of these ceiling boxes can weaken over time due to fatigue at the threaded receptacles, material degradation, and poor installation practices, thereby causing a safety hazard. Alternatively, high load rated ceiling boxes for ceiling fans mount the fixture plate directly onto the metallic bracket. However, high load rated ceiling boxes have higher costs compared to lower load rated ceiling boxes due to the increased costs associated with the heavier metallic brackets.

(3) Typically, ceiling boxes where the fixture plate mounts directly onto the electrical box is used due to their lower cost. Further, due to the increased cost, high load rated ceiling boxes are limited to locations where the installer knows a ceiling fan will be installed. Therefore, ceiling boxes with improved mounting for ceiling fixtures including low load rated ceiling fans is desired.

SUMMARY

(4) In some embodiments, an apparatus for mounting an electrical fixture to a structural member, the apparatus includes a housing having a rear wall at a first end, at least one sidewall extending from the first end to a second end and forming an opening at the second end, and wherein the housing includes: a first emboss tab at a first side of the at least one sidewall, a second emboss tab at a second side of the at least one sidewall, a pair of screw holes extending through the rear wall, a pair of first bores extending through the housing at the first emboss tab and the second emboss tab, and a pair of second bores extending through the housing at the first emboss tab and the second emboss tab; and a bracket, the bracket including: a first portion on a first plane, a second portion on a second plane, a pair of first threaded apertures extending through the first portion, a pair of second threaded apertures extending through the first portion, and a plurality of mounting holes extending through the second portion and configured to receive a plurality of fasteners to mount the bracket to the structural member; wherein the pair of first threaded apertures are configured to align with the pair of screw holes and the pair of second threaded apertures are configured to align with the pair of first bores.

(5) In some embodiments, the apparatus includes a pair of first fasteners at the pair of screw holes to attach the housing to the bracket; and a pair of second fasteners at the pair of first bores to engaging the bracket, wherein the pair of second fasteners are configured to engage a first fixture plate.

(6) In some embodiments, the pair of second bores is configured to engage a pair of third fasteners inserted into the pair of second bores; and wherein the pair of second bores mechanically deform in response to the third fasteners being threadingly inserted into the pair of second bores; wherein the pair of third fasteners are configured to engage a second fixture plate.

(7) In some embodiments, the first portion extends in a first direction on the first plane, and wherein the bracket further includes: a third portion extending in a second direction on the first plane; wherein an aperture of the pair of second threaded apertures is disposed on the third portion.

- (8) In some embodiments, the bracket further includes wherein the first portion and the second portion intersect to form approximately a 90° angle, and wherein the bracket further includes a gusset disposed at an intersection of the first portion and the second portion.
- (9) In some embodiments, the bracket further includes: a fourth portion extending in a third direction on the first plane, wherein the fourth portion is opposite from the third portion at the first portion; wherein the other aperture of the pair of second threaded apertures is disposed on the fourth portion.
- (10) In some embodiments, an axis of the second direction is at approximately a 45° angle from an axis of the first direction.
- (11) In some embodiments, the second portion is offset from the first portion to form a channel extending between a first segment and a second segment of the first portion, wherein the bracket is configured to receive a bar hanger between the bracket and the housing through the channel, and wherein the bar hanger is configured to mount the bracket to the structural member.
- (12) In some embodiments, the bar hanger includes an outer bar and an inner bar, the outer bar having a second channel along a lengthwise axis of the outer bar, wherein the inner bar fits inside the second channel to extend from the second channel to telescopically adjust a length of the bar hanger.
- (13) In some embodiments, the bracket further includes: a first flange disposed at an end of the third portion, and a second flange disposed at an end of the fourth portion, wherein the first flange and the second flange extend around the housing towards the second end.
- (14) In some embodiments, each of the first flange and the second flange further include at least one emboss portion at an intersection of the first flange or the second flange and the third portion and the fourth portion.
- (15) In some embodiments, the bracket further includes: a first emboss segment disposed on the first portion, a second emboss segment disposed on the third portion, and a third emboss segment disposed on the fourth portion, wherein the first emboss segment, the second emboss segment, and the third emboss segment provide support to a rigidity of the bracket.
- (16) In some embodiments, a system for mounting electrical fixtures to a structural member, the system includes a housing having a rear wall at a first end, at least one sidewall extending from the first end to a second end and forming an opening at the second end, the housing including: a first emboss tab at a first side of the at least one sidewall, a second emboss tab at a second side of the at least one sidewall, a pair of screw holes extending through the rear wall, a pair of first bores extending through the housing at the first emboss tab and the second emboss tab, and a pair of second bores extending through the housing at the first emboss tab and the second emboss tab; a bracket for mounting the housing to the structural member, the bracket including: a first portion on a first plane at the first end of the housing, a second portion on a second plane, a pair of first threaded apertures extending through the first portion and aligning with the pair of screw holes, a pair of second threaded apertures extending through the first portion and aligning with the pair of first bores, and a plurality of mounting holes extending through the second portion and configured to receive a plurality of fasteners; a pair of first fasteners to attach the housing to the bracket; a pair of second fasteners to threadingly engage the bracket, wherein the pair of second fasteners are configured to engage a first fixture plate; wherein the pair of first threaded apertures align with the pair of screw holes and the pair of second threaded apertures align with the pair of first bores; wherein the pair of second bores mechanically deform in response to a pair of third fasteners being threadedly inserted into the pair of second bores to mount a second fixture plate.
- (17) In some embodiments, the first portion extends in a first direction, and wherein the bracket further includes: a third portion extending in a second direction on the first plane, wherein an aperture of the pair of second threaded apertures is disposed on the third portion.
- (18) In some embodiments, the techniques described herein relate to a system, wherein the bracket further includes: a fourth portion extending in a third direction opposite the second direction on the

first plane, wherein the other aperture of the pair of second threaded apertures is disposed on the fourth portion.

(19) In some embodiments, the second direction is angularly offset from the first direction by a 45° angle.

(20) In some embodiments, the bracket further includes wherein the first portion and the second portion intersect to form approximately a 90° angle, and wherein the bracket further includes a gusset disposed at an intersection of the first portion and the second portion.

(21) In some embodiments, the bracket further includes wherein the second portion is offset from the first portion to form a channel extending between a first segment and a second segment of the first portion, wherein the bracket is configured to receive a bar hanger between the bracket and the housing through the channel, and wherein the bar hanger is configured to mount the bracket to the structural member.

(22) In some embodiments, the bracket further includes a first emboss segment disposed on the first portion, a second emboss segment disposed on the third portion, a third emboss segment disposed on the fourth portion, a first flange disposed at an end of the third portion, and a second flange disposed at an end of the fourth portion, wherein the first emboss segment, the second emboss segment, and the third emboss segment provide added support to a rigidity of the bracket, wherein the first flange and the second flange extend around a periphery of the housing towards the second end.

(23) In some embodiments, each of the first flange and the second flange further include at least one emboss portion at an intersection of the first flange and the second flange and a respective third portion and the fourth portion.

Description

DRAWINGS

(1) Some embodiments of the disclosure are herein described, by way of example only, with reference to the accompanying drawings. With specific reference now to the drawings in detail, it is stressed that the embodiments shown are by way of example and for purposes of illustrative discussion of embodiments of the disclosure. In this regard, the description taken with the drawings makes apparent to those skilled in the art how embodiments of the disclosure may be practiced.

(2) FIG. 1 shows a perspective view of a ceiling box including an electrical box and a bracket, according to some embodiments.

(3) FIG. 2 shows a top view of the electrical box, according to some embodiments.

(4) FIG. 3 shows a bottom view of the electrical box, according to some embodiments.

(5) FIG. 4 shows a side view of the ceiling box, according to some embodiments.

(6) FIG. 5 shows a perspective view of the bracket, according to some embodiments.

(7) FIG. 6 shows a top view of the bracket, according to some embodiments.

(8) FIG. 7 shows a perspective view of the bracket, according to some embodiments.

(9) FIG. 8 shows a perspective view of the bracket, according to some embodiments.

(10) FIG. 9 shows a perspective view of the ceiling box and a bar hanger, according to some embodiments.

DETAILED DESCRIPTION

(11) Ceiling boxes are used to mount lighting fixtures, including ceiling lights and/or ceiling fans, onto a structural member. For example, a ceiling box can include an electrical box and/or a bracket. The electrical box houses the electrical wiring and associated connectors of the lighting fixture and the wiring providing power to the lighting fixture. The electrical box can also connect to the fixture plate of the lighting fixture. The bracket can mount the electrical box and/or the lighting fixture to the structural member. Typically, low rated loads can be mounted to the electrical housing, whereas

high rated loads are generally mounted to the bracket for improved retention. Existing ceiling boxes are described in U.S. Pat. No. 7,518,059 of Herth and U.S. Pat. No. 6,734,356 of Gretz.

(12) Herth '059 describes an electrical box having an internal bracket and threaded receptacles for mounting a fixture plate of a ceiling fixture onto the electrical box. The metal bracket includes carriage bolts projecting outside the electrical box at the electrical box opening. The protruding bolts interferes with placement of the fixture plate for certain light fixtures and limits installation locations of the ceiling box. Further, the close position of the three mounting screws relative to each other reduce the effectiveness of mounting.

(13) Gretz '356 describes a ceiling box having a bracket to attach the electrical box to a structural surface. The metal bracket includes side walls extending along a side of the bracket and is mounted to the structural member by fasteners extending through the sidewall. However, the ceiling box is limited to high load rated ceiling fans and does not accommodate lighting fixtures of different sizes. Further, the electrical box includes fasteners for receiving a fixture plate that extend through an interior of the electrical box, thereby increasing a safety hazard from electrical components.

(14) FIG. 1 shows a perspective view of a ceiling box **100** including an electrical box **103** and a bracket **203**, according to some embodiments. The ceiling box **100** can include an electrical box **103** and a bracket **203**.

(15) The electrical box **103** can have a first end **109** and a second end **121** opposite the first end **109**. The electrical box **103** can include a rear wall **107** at the first end **109**, at least one sidewall **111**, and an opening **123** at the second end **121** that define a housing **105**. In some embodiments, the at least one sidewall **111** can include a emboss tab **113** (FIG. 2) at a first side **115** and a emboss tab **117** (FIG. 2) at a second side **119** of the at least one sidewall **111** opposite the first side **115**. Each of the emboss tab **113** and the emboss tab **117** inwardly extend from the at least one sidewall **111**. In the illustrated embodiment, the housing **105** is cylindrically shaped. It is to be appreciated that other geometries for the housing **105** are possible and that the shape is exemplary. Additional geometries are possible in accordance with the remaining disclosure.

(16) FIG. 2 shows a top view of the electrical box **103**, according to some embodiments. FIG. 3 shows a bottom view of the electrical box **103**, according to some embodiments. FIG. 4 shows a side view of the ceiling box **100**, according to some embodiments.

(17) The housing **105** can include a screw hole **125**. The screw hole **125** can extend through the rear wall **107** and form an aperture through the rear wall **107**. In some embodiments, the housing **105** can include a pair of screw hole **125**. In some embodiments, the housing **105** can include three screw holes **125**. In some embodiments, the housing **105** can include four or more screw holes **125**. In some embodiments, the housing **105** can include a plurality of screw hole **125**.

(18) The housing **105** can include a bore **127**. In some embodiments, the bore **127** extends through the housing **105**. In some embodiments, the bore **127** can be configured to receive a fastener that attaches to the bracket **203**. In some embodiments, the housing **105** can include a pair of bore **127**. In some embodiments, the pair of bore **127** can be configured to receive a pair of fastener **143** to couple a ceiling fan/light fixture plate to the ceiling box **100**. In some embodiments, each of the emboss tab **113** and the emboss tab **117** can include the bore **127** extending through the emboss tab **113** and the emboss tab **117** to form an aperture. The bore **127** on the emboss tab **113** and the bore **127** on the emboss tab **117** can be spaced a first distance apart. In some embodiments, the first distance can be 3.5" wide. In some embodiments, the first distance can be less than 3.5" wide. In some embodiments, the distance between the bore **127** on the emboss tab **113** and the bore **127** on the first side **115** can be based on the size of the fixture plate being mounted to the bracket **203**.

(19) In some embodiments, the housing **105** can include a bore **129**. In some embodiments, the bore **129** may be configured to receive a fastener to attach the fixture plate to the bracket **203**. In some embodiments, the bore **129** fully extends through the emboss tab **113** and the first side **115** to allow the fasteners to extend through the emboss tab **113** and the emboss tab **117** and to engage

each of the threaded apertures **249** on the bracket **203**. In some embodiments, the bore **129** partially extends through the emboss tab **113** and the emboss tab **117**. In some embodiments, the bore **129** can be configured to receive a fastener to attach a fixture plate to the housing **105**. In some embodiments, the bore **129** can be configured to mechanically deform in response to threadingly inserting a fastener into the bore **129**. The bore **129** on the emboss tab **113** and the bore **129** on the emboss tab **117** can be spaced a second distance apart. In some embodiments, the second distance can be 2.75" wide. In some embodiments, the second distance can be less than 2.75" wide. In some embodiments, the first distance can be greater than 2.75" wide. In some embodiments, the distance between the bore **129** on the emboss tab **113** and the bore **129** on the first side **115** can be based on the size of the fixture plate being mounted to the bracket **203**. In some embodiments, the second distance can be less than the first distance to accommodate a smaller fixture plate than the pair of bore **127**.

(20) In some embodiments, the bore **127** can include a first width diameter and can be configured to receive a fastener having a first size. In some embodiments, the bore **129** can include a second width diameter and can be configured to receive a fastener having a second size. In some embodiments, the first width diameter and the second width diameter can be substantially similar widths to receive fasteners of substantially similar size. In some embodiments, the first width diameter and the second width diameter can be the same widths. In some embodiments, the first width diameter can be wider than the second width diameter and the fastener having the first size can be larger than the fastener having the second size. In some embodiments, the first width diameter can be narrower than the second width diameter and the fastener having the first size can be a smaller size than the fastener having the second size. In some embodiments, the bore **127** can include a threaded inner surface. In some embodiments, the bore **129** can include a threaded inner surface. In some embodiments, the bore **127** and/or the bore **129** can include a threaded inner surface configured to receive a threaded fastener.

(21) In some embodiments, the housing **105** can include a tab **135** and a tab **137**. In some embodiments, the tab **135** and the tab **137** radially extend from an exterior surface of the at least one sidewall **111**. In some embodiments, the tab **135** and the tab **137** can include a bore **139** disposed at an outer end of the tab **135** and the tab **137**. The tab **137** can be configured to receive a fastener **145** to engage the structural member to mount the housing **105** to the structural member. Each bore of the pair of bore **139** can be angularly positioned through the bore **139** so the fastener **145** engages the structural surface at a predetermined angle. In some embodiments, the predetermined angle can be approximately 45°. In some embodiments, the predetermined angle can be 45°. In some embodiments, the predetermined angle can be less than 45°. In some embodiments, the predetermined angle can be more than 45°.

(22) In some embodiments, the at least one sidewall **111** of the housing **105** can include a flat planar segment **147** located between the tab **135** and the tab **137**. In some embodiments, the flat planar segment **147** can extend from the first end **109** and towards the second end **121** to form a step **149** so that the housing **105** at the first end **109** is arcuate and the housing **105** at the second end **121** is substantially circular. In some embodiments, the step **149** can be located at an end of the flat planar segment **147** proximate the second end **121** and protrudes from the flat planar segment **147** to form a ledge configured to abut an edge of the structural member when installing the ceiling box **100**. Further, in some embodiments, the step **149** may be configured to position the opening **123** of the housing **105** at the second end **121** a predetermined distance from the end of the structural member.

(23) The housing **105** can accommodate electrical conductors, electrical connectors, and similar components for mounting a ceiling fixture. In some embodiments, housing **105** can include a plurality of apertures and/or push-in covers for extending electrical conductors from an exterior of the housing **105** to an interior of housing **105** in the receptacle.

(24) FIG. 5 shows a perspective view of the bracket **203**, according to some embodiments. FIG. 6

shows a top view of the bracket **203**, according to some embodiments. FIG. 7 shows a perspective view of the bracket **203**, according to some embodiments. In the illustrated embodiment, the bracket **203** is L-shaped. It is to be appreciated that other geometries for the bracket **203** are possible and that the L-shape is exemplary. For example, the bracket **203** can be U-shaped. Additional geometries are possible in accordance with the remaining disclosure. The bracket **203** can include, at least, a first portion **209** and a second portion **211**. The first portion **209** can be on a first plane **213** and extend along a first direction. The first portion **209** fits at the first end **109** of housing **105** opposite the second end **121** of housing **105**. The second portion **211** can be contiguously connected to the first portion **209** and extend on a second plane **215**.

(25) In some embodiments, the first portion **209** and the second portion **211** can form an intersection **223** where a respective edge of the first portion **209** and the second portion **211** contiguously connect. In some embodiments, the angle of the intersection **223** of the first portion **209** and the second portion **211** can be substantially perpendicular. In some embodiments, the angle of intersection **223** between the first plane **213** and the second plane **215** can be approximately a 90° angle. In some embodiments, the angle of the intersection **223** between the first plane **213** and the second plane **215** can be less than 90°. In some embodiments, the angle of the intersection **223** between the first plane **213** and the second plane **215** can be greater than 90°. In some embodiments, the bracket **203** can be formed from a single piece. In some embodiments, the bracket **203** can include at least two pieces that can be joined together to form the bracket **203** by any of a plurality of methods including, but not limited to, pressing, stamping, cutting, welding, forging, filing, bending, other processes, and combinations thereof.

(26) In some embodiments, the bracket **203** can include a gusset **225** disposed at the intersection **223**. The gusset **225** provides support for the bracket **203** at the intersection **223** to prevent a mechanical deformation of the bracket **203** and the intersection **223** in response to a load being placed onto the bracket **203**. In some embodiments, the gusset **225** can extend along at least a portion of the intersection **223** and can further extend along a portion of each of the first portion **209** and the second portion **211**. The gusset **225** is raised from the surface of the bracket **203** in a direction opposite housing **105** when housing **105** is attached to the bracket **203**.

(27) In some embodiments, the bracket **203** can include a mounting hole **221**. The mounting hole **221** is configured to extend through the bracket **203** to form an aperture through the bracket **203**. The mounting holes **221** can receive a fastener to mount the bracket **203** to the structural member. In some embodiments, the housing **105** can be attached to the bracket **203** when mounting the bracket **203** to the structural member by inserting fasteners through the bracket **203**. In some embodiments, the mounting holes **221** can be disposed on the second portion **211**. In some embodiments, the second portion **211** can include a plurality of mounting holes **221**. In some embodiments, the plurality of mounting holes **221** can be spaced apart along a surface of the second portion **211** to improve the retaining strength of the bracket **203** to the structural member. In some embodiments, the second portion **211** can include two mounting holes **221**. In some embodiments, the second portion **211** can include three mounting holes **221**. In some embodiments, the second portion **211** can include four mounting holes **221**. In some embodiments, the second portion **211** can include five mounting holes **221**.

(28) In some embodiments, the second portion **211** can include more than five mounting holes **221**.

(29) In some embodiments, the bracket **203** can include a pointed ear **245** disposed at an end of the bracket **203**. In some embodiments, the pointed ears **245** can be disposed on the second portion **211** at the opposite end from the first portion **209**. In some embodiments, the pointed ears **245** can be configured to extend towards the structural member when the bracket **203** is mounted to the structural member. The pointed ear **245** can be configured to insert into the structural member after aligning the bracket **203** and prior to installing any fasteners through the bracket **203**. The pointed ears **245** can be inserted into the structural member prior to mounting the bracket **203** to retain a position of the bracket **203** onto the structural member during installation. In some embodiments,

the second portion **211** can include at least one pointed ear **245**. In some embodiments, the second portion **211** can include two pointed ears **245**. In some embodiments, the second portion **211** can include two or more pointed ears **245**.

(30) In some embodiments, the bracket **203** can include a third portion **229**. In some embodiments, the third portion **229** can extend on the first plane **213** in a second direction from the first portion **209**. In some embodiments, the second direction can be the same direction as the first direction. In some embodiments, an angle between an axis of the first direction and an axis of the second direction can be approximately 45° . In some embodiments, the angle between the first direction and the second direction can be 45° . In some embodiments, the third portion **229** can include the threaded aperture **219**, the threaded aperture **219** aligning with the bore **127** extending through the emboss tab **113**. In some embodiments, the fastener **141** can extend through the bore **127** and engage with the threaded aperture **219** on the third portion **229**. In some embodiments, the third portion **229** can include a threaded aperture **249**, the threaded aperture **249** aligning with the bore **129** extending through the emboss tab **113**. In some embodiments, the fastener **141** can extend through the bore **129** and engage with the threaded aperture **249** on the third portion **229**. In other embodiments, a fastener having a smaller diameter than fastener **141** can extend through the bore **129** and the threaded aperture **249** to engage the third portion **229**.

(31) In some embodiments, the bracket **203** can include a fourth portion **231**. In some embodiments, the fourth portion **231** can extend on the first plane **213** in a third direction from the first portion **209**. In some embodiments, the third portion **229** and the fourth portion **231** can be disposed at opposing ends of the first portion **209**. In some embodiments, the angle between the axis of the second direction and an axis of the third direction can be approximately 180° . In some embodiments, the angle between the second direction and the third direction can be 180° . Consequently, in some embodiments, the third direction can be an opposite direction from the second direction on the first plane **213**. In some embodiments, the fourth portion **231** can include the threaded aperture **219**, the threaded aperture **219** aligning with the bore **127** extending through the emboss tab **117**. In some embodiments, the fastener **141** can extend through the bore **127** and engage with the threaded aperture **219** on the fourth portion **231**. In some embodiments, the fourth portion **231** can include the threaded aperture **249**, the threaded aperture **249** aligning with the bore **129** extending through the emboss tab **117**. In some embodiments, the fastener **141** can extend through the bore **129** and engage with the threaded aperture **249** on the fourth portion **231**. In other embodiments, a fastener having a smaller diameter than fastener **141** can extend through the bore **129** and the threaded aperture **249** to engage the fourth portion **231**.

(32) In some embodiments, a width of the first portion **209** and the second portion **211** can be a first width. In some embodiments, a width of the third portion **229** and the fourth portion **231** can be a second width. In some embodiments, the second width can be narrower than the first width. In some embodiments, the second width can be approximately 0.50".

(33) The bracket **203** can include threaded aperture **217**. The threaded aperture **217** can be configured to receive a fastener **141**. In some embodiments, the threaded aperture **217** can be located on the first portion **209**. In some embodiments, the threaded aperture **217** can align with the screw hole **125** on the housing **105**. In some embodiments, the threaded aperture **217** can have a first diameter width. In some embodiments, the size, shape, diameter, thread size, and other factors for each of the threaded aperture **217** can be based on any of a plurality of factors including, but not limited to, the size of the fastener **141**, as will be further discussed below.

(34) The bracket **203** can include threaded aperture **219**. The threaded aperture **219** can be configured to receive a fastener **143**. In some embodiments, the threaded aperture **219** can be located on the first portion **209**. In some embodiments, the third portion **229** and the fourth portion **231** can include the threaded aperture **219**. In some embodiments, the threaded aperture **219** can align with the bore **127**. In some embodiments, the bracket **203** can include a pair of threaded apertures **219**, each threaded aperture **219** aligning with the pair of bore **127** of the housing **105**. In

some embodiments, the threaded aperture **219** can have a second diameter width. In some embodiments, the size, shape, diameter, thread size, and other factors for each of the threaded aperture **219** can be based on any of a plurality of factors including, but not limited to, the size of the fastener **141**, as will be further discussed below. In some embodiments, the first width and the second width can be substantially similar. In some embodiments, the first width can be narrower than the second width. For example, the threaded aperture **217** can be configured to receive a threaded fastener for mounting a lighting fixture plate and the threaded aperture **219** can be configured to receive a threaded fastener for mounting a ceiling fan fixture plate, the fasteners for the lighting fixture plate being a smaller sized fastener than the fasteners for the ceiling fan fixture plate. In some embodiments, the first width can be wider than the second width.

(35) In some embodiments, the threaded aperture **217** can include an extruded hole. In some embodiments, the threaded aperture **219** can include the extruded hole. In some embodiments, each of the plurality of threaded aperture **217** and the threaded aperture **219** on the bracket **203** can include extruded holes. The extruded holes can be configured to provide added retaining support for the fasteners to engage the bracket **203**. In some embodiments, the threaded aperture **217** and the threaded aperture **219** can include a threaded interior surface extending through the threaded aperture **217** and the threaded aperture **219** and along the inner surface of the extrusion to provide an increased surface area for each fastener to engage.

(36) In some embodiments, bracket **203** can include a flange **233**. In some embodiments, the flange **233** can be located at an end of the third portion **229**. In some embodiments, the bracket **203** can include a flange **235**. In some embodiments, the flange **235** can be disposed at an end of the fourth portion **231**. The flange **233** and the flange **235** can provide increased mechanical strength to the bracket **203** at the third portion **229** and the fourth portion **231**, respectively. In some embodiments, the flange **233** and the flange **235** can extend towards the second end **121** of the housing **105** at approximately a 90° angle.

(37) In some embodiments, the bracket **203** can include an emboss portion **237**. In some embodiments, the emboss portion **237** can be located at the intersection of the flange **233** and the third portion **229**. In some embodiments, the emboss portion **237** can be located at the intersection of the flange **235** and the fourth portion **231**. The emboss portion **237** extends towards the corner of the housing **105** formed by the rear wall **107** and the at least one sidewall **111** from the intersection of the third portion **229** or the fourth portion **231**. The emboss portion **237** retains the ends of the third portion **229** and the fourth portion **231** engaged with the corner of the housing **105** when the bracket **203** is coupled to the housing **105** and when the ceiling fan/light fixture is secured to the bracket **203**. In some embodiments, the bracket **203** can include a plurality of emboss portion **237**. In some embodiments, each of the third portion **229** and the fourth portion **231** can include a pair of emboss portion **237**.

(38) In some embodiments, the bracket **203** can include an emboss segment **239**. In some embodiment, the emboss segment **239** can be disposed on the first portion **209**. In some embodiments, the emboss segment **239** can be u-shaped. It is to be appreciated that other geometries for the emboss segment **239** are possible and that the u-shape is exemplary. Additional geometries are possible in accordance with the remaining disclosure. In some embodiments, the bracket **203** can include an emboss segment **241**. In some embodiments, the emboss segment **241** can be disposed on the third portion **229**. In some embodiments, the emboss segment **241** can be disposed on at least part of the third portion **229**. In some embodiments, the **241** can be disposed on the third portion **229** and the first portion **209**. In some embodiments, the emboss segment **241** can be y shaped. In some embodiments, the emboss segment **241** can include a columnal segment extending towards the first portion **209**. In some embodiments, the columnal segment of the emboss segment **241** can angularly extend around the threaded aperture **217** of the first portion **209**. It is to be appreciated that other geometries for the emboss segment **241** are possible and that the y shape is exemplary. Additional geometries are possible in accordance with the remaining

disclosure. In some embodiments, the bracket **203** can include an emboss segment **243**. In some embodiments, the emboss segment **243** can be disposed on the fourth portion **231**. In some embodiments, the emboss segment **243** can be disposed on at least part of the fourth portion **231**. In some embodiments, the emboss segment **243** can be y shaped. It is to be appreciated that other geometries for the emboss segment **243** are possible and that the y shape is exemplary. Additional geometries are possible in accordance with the remaining disclosure. The emboss segments provide added mechanical support to the bracket **203**. Further, the emboss segments provide added rigidity and added resistance against mechanical deformation when the electrical fixture is mounted to the bracket **203** and the structural member. In some embodiments, the emboss segment **239** can be a first emboss segment **239**. In some embodiments, the emboss segment **241** can be a second emboss segment **241**. In some embodiments, the emboss segment **243** can be a third emboss segment **243**.

(39) In some embodiments, the bracket **203** can have arcuate cutouts **247** disposed along a periphery of the bracket **203**. The arcuate cutouts **247** can reduce the overall amount of material that is required to form the bracket **203**, thereby reducing the cost of the bracket **203**. For example, in some embodiments, the first portion **209** of the bracket **203** can have an arcuate cutout **247** at a corner of the first portion **209** located between the third portion **229** and the fourth portion **231**.

(40) In some embodiments, the ceiling box **100** can include fastener **141**. In some embodiments, the ceiling box **100** can include a pair of fasteners **141**. The fastener **141** can couple the housing **105** to the bracket **203** at the pair of screw holes **125**. In some embodiments, the fastener **141** can include any of a plurality of fasteners including, but not limited to, screws, bolts, nuts, rivets, nails, lag bolts, anchor bolts, other fasteners, and combinations thereof. In some embodiments, the fastener **141** can be screws. In some embodiments, the fastener **141** can be bolts.

(41) In some embodiments, the ceiling box **100** can include fastener **143**. In some embodiments, the ceiling box **100** can include a pair of fasteners **143**. The fastener **143** are configured to extend through the housing **105** at the bore **127** and threadingly engage the bracket **203**. In some embodiments, the fastener **143** can threadingly engage the threaded aperture **219**. The fastener **143** can be located at the bore **127** and can be configured to receive the first fixture plate having the first size. For example, in some embodiments, each fastener of the pair of fasteners **143** can include a pan head to be inserted into apertures on the first fixture plate, the apertures being sized to receive the pan head at one end and retain the pan head at the other end. In some embodiments, the fastener **143** can include any of a plurality of fasteners including, but not limited to, screws, bolts, nuts, rivets, nails, lag bolts, anchor bolts, other fasteners, and combinations thereof. In some embodiments, the fastener **143** can be screws. In some embodiments, the fastener **143** can be bolts.

(42) In some embodiments, the ceiling box **100** can include fastener **151**. In some embodiments, the ceiling box **100** can include a pair of fasteners **151**. The fastener **151** can couple the housing **105** to the structural member. The fastener **151** can be located at the pair of bore **139** and configured to engage the structural member to mount the housing **105**. In some embodiments, the fastener **151** can include any of a plurality of fasteners including, but not limited to, screws, nuts, bolts, nails, lag bolts, anchor bolts, other fasteners, and combinations thereof. In some embodiments, the fastener **151** can be a nail.

(43) In some embodiments, the bracket **203** can be positioned onto the first end **109** of the housing **105**, the pair of screw holes **125** aligning with the pair of threaded apertures **217** and the pair of bore **127** aligning with the pair of threaded apertures **219**. In some embodiments, the housing **105** can be attached to the bracket **203** by inserting a pair of fasteners **141** through the pair of screw holes **125** to engage the bracket **203** at the pair of threaded apertures **217**. Further, in some embodiments, the pair of bore **127** can receive the pair of fasteners **143** to engage the bracket **203** at the pair of threaded apertures **219** to receive the first fixture plate.

(44) Referring to FIG. 7, in some embodiments, the bracket **203** can include threaded aperture **249**. In some embodiments, the bracket **203** can include a pair of threaded apertures **249**. In some embodiments, the bracket **203** can include a plurality of threaded apertures **249**. The threaded

aperture **249** can be located on the first portion **209**. In some embodiments, the threaded aperture **249** can be located on the first portion **209**, the third portion **229**, the fourth portion **231**, and combinations thereof. For example, in one embodiment, the bracket **203** can include a threaded aperture **249** disposed on the third portion **229** and another threaded aperture **249** disposed on the fourth portion **231**. In another embodiment, the bracket **203** can include a threaded aperture **249** disposed on the first portion **209** and another threaded aperture disposed on the third portion **229**. In some embodiments, the threaded aperture **249** can be configured to receive a fastener to mount an electrical fixture plate to the bracket **203**. In some embodiments, the threaded aperture **249** can receive the fastener **143** located in the bore **129** and engaging the threaded aperture **249**. For example, in some embodiments, the fasteners **143** can be relocated from the bore **127** and the threaded aperture **219** and into the bore **129** and the threaded aperture **249** to accommodate a smaller diameter electrical fixture plate. In some embodiments, the bore **129** and the threaded aperture **249** can be configured to receive a fastener (not pictured) having a smaller diameter width than the fastener **143**, the fastener extending through the bore **129** on the emboss tab **113** and the emboss tab **117** and threadingly engaging the pair of threaded apertures **249** on the bracket **203** to mount the smaller diameter electrical fixture plate to the fasteners.

(45) FIG. **8** shows a perspective view of the bracket **203**, according to some embodiments. FIG. **9** shows a perspective view of the ceiling box **100** and a bar hanger **303**, according to some embodiments.

(46) In some embodiments, the bracket **203** can include a channel **227** formed by the second portion **211** offset from the first portion **209** and extending parallel to the first portion **209**, the channel **227** defining a space between the bracket **203** and housing **105** to receive a bar hanger **303**. In some embodiments, the second portion **211** can be contiguously connected to the first portion **209** along two sides of the second portion **211**, the first portion **209** forming a first segment and a second segment and extending along opposing sides of the second portion **211**. In some embodiments, the housing **105** can be configured to receive the bar hanger **303** between the bracket **203** and the housing **105** through a length of the channel **227**.

(47) In some embodiments, the ceiling box **100** can include a bar hanger **303**. The bar hanger can extend between two structural members to mount the ceiling box **100** to the structural members. The bar hanger **303** can be disposed between the housing **105** and the bracket **203** at the channel **227** and extend away from the ceiling box **100** towards the two structural members. Each end of the bar hanger **303** can include a mounting plate **305** to attach the bar hanger **303** to each respective structural member. Further, in some embodiments, each mounting plate **305** can include a plurality of mounting holes **221** to attach the bar hanger **303** to the structural members. In some embodiments, the bar hanger **303** can be a fixed length bar member.

(48) In some embodiments, the bar hanger **303** can include an inner bar **307** having a first dimension and an outer bar **309** having a second dimension, the outer bar **309** including a second channel extending through the outer bar **309** along a lengthwise axis, the inner bar **307** fitting inside the second channel of the outer bar **309** to extend from the second channel to telescopically adjust a length of the bar hanger **303** to engage two structural members of varying distances to install the ceiling box **100** to the structural members. In some embodiments, the outer bar **309** of the bar hanger **303** can be disposed between the housing **105** and the bracket **203**. Further, in some embodiments, the outer bar **309** can include a tab to prevent the bracket **203** from sliding off the outer bar **309** and onto the inner bar **307**. In some embodiments, the outer bar **309** can include a retaining tab to retain the inner bar **307** in the second channel of the outer bar **309**, the inner bar **307** further including an aperture on a corresponding surface of the inner bar **307** to engage the retaining tab when the inner bar **307** is extended from the outer bar **309** a fixed distance.

(49) Among those benefits and improvements that have been disclosed, other objects and advantages of this disclosure will become apparent from the following description taken in conjunction with the accompanying figures. Detailed embodiments of the present disclosure are

disclosed herein; however, it is to be understood that the disclosed embodiments are merely illustrative of the disclosure that may be embodied in various forms. In addition, each of the examples given regarding the various embodiments of the disclosure which are intended to be illustrative, and not restrictive.

(50) All prior patents and publications referenced herein are incorporated by reference in their entireties.

(51) Throughout the specification and claims, the following terms take the meanings explicitly associated herein, unless the context clearly dictates otherwise. The phrases “in one embodiment,” “in an embodiment,” and “in some embodiments” as used herein do not necessarily refer to the same embodiment(s), though it may. Furthermore, the phrases “in another embodiment” and “in some other embodiments” as used herein do not necessarily refer to a different embodiment, although it may. All embodiments of the disclosure are intended to be combinable without departing from the scope or spirit of the disclosure.

(52) As used herein, the term “based on” is not exclusive and allows for being based on additional factors not described, unless the context clearly dictates otherwise. In addition, throughout the specification, the meaning of “a,” “an,” and “the” include plural references. The meaning of “in” includes “in” and “on.”

(53) As used herein, the term “between” does not necessarily require being disposed directly next to other elements. Generally, this term means a configuration where something is sandwiched by two or more other things. At the same time, the term “between” can describe something that is directly next to two opposing things. Accordingly, in any one or more of the embodiments disclosed herein, a particular structural component being disposed between two other structural elements can be: disposed directly between both of the two other structural elements such that the particular structural component is in direct contact with both of the two other structural elements; disposed directly next to only one of the two other structural elements such that the particular structural component is in direct contact with only one of the two other structural elements; disposed indirectly next to only one of the two other structural elements such that the particular structural component is not in direct contact with only one of the two other structural elements, and there is another element which juxtaposes the particular structural component and the one of the two other structural elements; disposed indirectly between both of the two other structural elements such that the particular structural component is not in direct contact with both of the two other structural elements, and other features can be disposed therebetween; or any combination(s) thereof.

(54) As used herein “embedded” means that a first material is distributed throughout a second material.

Claims

1. A bracket device for mounting an electrical fixture housing to a structural member, the bracket device comprising: a first portion extending on a first plane in a first direction, the first portion defining a first pair of apertures configured to receive a first pair of fasteners to attach the electrical fixture housing to the bracket device; a second portion extending on a second plane in a second direction, the second portion defining at least one mounting hole configured to receive at least one fastener to attach the bracket device to the structural member; a third portion extending from the first portion on the first plane in a third direction; and a fourth portion extending from the first portion on the first plane in a fourth direction; wherein the fourth direction is opposite from the third direction; wherein the third portion and the fourth portion each define an aperture of a second pair of apertures configured to receive a second pair of fasteners to attach the electrical fixture housing to the bracket device.

2. The bracket device according to claim 1, wherein the first pair of apertures of the first portion are

configured to engage the first pair of fasteners to attach a first fixture plate for mounting a first electrical fixture to the electrical fixture housing and the bracket device.

3. The bracket device according to claim 1, wherein the the first portion is substantially perpendicular relative to the second portion.

4. The bracket device according to claim 1, wherein the third direction is approximately a 45° angle from the first direction.

5. The bracket device according to claim 1, wherein each of the first pair of apertures is configured to receive a corresponding one of the first pair of fasteners having a first length to attach a first fixture plate for mounting a first type of electrical fixture to the electrical fixture housing and the bracket device; wherein the each of the second pair of apertures defined by the third portion and the fourth portion is configured to receive a corresponding one of the second pair of fasteners having a second length to engage a second fixture plate for mounting a second type of electrical fixture to the electrical fixture housing and to attach the electrical fixture housing to the bracket device.

6. The bracket device according to claim 1, further comprising: a plurality of emboss segments, wherein the plurality of emboss segments is configured to provide rigidity to the bracket device to resist mechanical deformation.

7. The bracket device according to claim 6, wherein the plurality of emboss segments comprises: a first emboss segment arranged on the first portion, a second emboss segment at least partially arranged on the third portion, and a third emboss segment at least partially arranged on the fourth portion.

8. The bracket device according to claim 1, wherein the third portion further comprises: a first flange, and at least one first emboss portion located at an intersection of the third portion and the first flange; and wherein the fourth portion further comprises: a second flange, and at least one second emboss portion located at an intersection of the third portion and the second flange; wherein the at least one first emboss portion and the at least one second emboss portion are configured to provide rigidity to the bracket device to resist mechanical deformation.

9. The bracket device according to claim 1, further comprising: a gusset, wherein the gusset is disposed at an intersection of the first portion and the second portion.

10. A bracket comprising: a first portion extending on a first plane in a first direction; a first pair of apertures extending through the first portion to receive corresponding first pair of fasteners to attach the bracket to an electrical fixture housing; a second portion extending on a second plane, the second portion defining a channel to receive a bar hanger at the channel for mounting the electrical fixture housing and the bracket to one or more structural members using one or more fasteners; a third portion extending from the first portion on the first plane; a fourth portion extending from the first portion on the first plane; wherein the third portion and the fourth portion extend from the first portion in opposite directions relative each other; wherein the third portion and the fourth portion each define an aperture of a second pair of apertures configured to receive a second pair of fasteners to attach the electrical fixture housing to the bracket.

11. The bracket according to claim 10, wherein the first pair of apertures of the first portion are configured to engage the first pair of fasteners to attach a first fixture plate for mounting a first type of electrical fixture to the electrical fixture housing and the bracket.

12. The bracket according to claim 10, wherein each of the first pair of apertures is configured to receive one of the first pair of fasteners to attach a first fixture plate to mount a first type of electrical fixture to the electrical fixture housing and the bracket; wherein each of the second pair of apertures is configured to receive one of the second pair of fasteners to engage a second fixture plate for mounting a second type of electrical fixture to the electrical fixture housing and to the bracket.

13. The bracket according to claim 10, further comprising: a first emboss segment arranged on the third portion; and a second emboss segment arranged on the fourth portion; wherein the first emboss segment and the second emboss segment are configured to provide rigidity to the bracket to

resist mechanical deformation.

14. The bracket according to claim 10, wherein the third portion further comprises: a first flange, and at least one first emboss portion located at an intersection of the third portion and the first flange; and wherein the fourth portion further comprises: a second flange, and at least one second emboss portion located at an intersection of the third portion and the second flange; wherein the at least one first emboss portion and the at least one second emboss portion are configured to provide rigidity to the bracket to resist mechanical deformation.

15. A system comprising: an electrical fixture housing; a bracket comprising: a first portion extending on a first plane, the first portion comprising: a pair of first apertures, wherein the pair of first apertures extends through the first portion, wherein the pair of first apertures receives a first fastener to attach the electrical fixture housing to the bracket; a second portion extending on a second plane, the second portion comprising: a channel; a third portion; and a fourth portion; wherein the third portion and the fourth portion extend from the first portion in opposite directions relative each other, and wherein the third portion and the fourth portion each define an aperture of a pair of second apertures configured to receive a pair of second fasteners to attach the electrical fixture housing to the bracket; and a bar hanger, wherein the bar hanger is configured to extend between one or more structural members and receive one or more third fasteners for mounting the bar hanger to one or more structural members; wherein the bracket is configured to receive the bar hanger at the channel such that the bracket and the electrical fixture housing also mount to the one or more structural members when the one or more third fasteners attach the bar hanger to the one or more structural members.

16. The system according to claim 15, further comprising: a first emboss segment arranged on the third portion, and a second emboss segment arranged on the fourth portion, wherein the first emboss segment and the second emboss segment are configured to provide rigidity to the bracket to resist mechanical deformation.

17. The system according to claim 16, wherein the third portion further comprises: a first flange, and at least one first emboss portion located at an intersection of the third portion and the first flange; and wherein the fourth portion further comprises: a second flange, and at least one second emboss portion located at an intersection of the third portion and the second flange; wherein the at least one first emboss portion and the at least one second emboss portion are configured to provide rigidity to the bracket to resist mechanical deformation.
