



US012399324B2

(12) **United States Patent**
Watté et al.

(10) **Patent No.:** **US 12,399,324 B2**

(45) **Date of Patent:** **Aug. 26, 2025**

(54) **MULTIPLE FIBER CONNECTIVITY BASED ON 2-PHOTON, 3D PRINTED, TAPERED FIBER TIPS**

(71) Applicant: **COMMSCOPE TECHNOLOGIES LLC**, Hickory, NC (US)

(72) Inventors: **Jan Watté**, Grimbergen (BE); **Vivek Panapakkam Venkatesan**, Leuven (BE); **Saurav Kumar**, Ghent (BE); **Koen Vanmol**, Vilvoorde (BE); **Jürgen Albert Jan Van Erps**, Tervuren (BE); **Hugo Thienpont**, Gooik (BE)

(73) Assignee: **COMMSCOPE TECHNOLOGIES LLC**, Hickory, NC (US)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 92 days.

(21) Appl. No.: **17/913,754**

(22) PCT Filed: **Mar. 23, 2021**

(86) PCT No.: **PCT/US2021/023744**

§ 371 (c)(1),

(2) Date: **Sep. 22, 2022**

(87) PCT Pub. No.: **WO2021/195121**

PCT Pub. Date: **Sep. 30, 2021**

(65) **Prior Publication Data**

US 2023/0098658 A1 Mar. 30, 2023

Related U.S. Application Data

(60) Provisional application No. 62/993,449, filed on Mar. 23, 2020, provisional application No. 63/046,479, filed on Jun. 30, 2020.

(51) **Int. Cl.**

G02B 6/26 (2006.01)

G02B 6/30 (2006.01)

(52) **U.S. Cl.**

CPC **G02B 6/262** (2013.01); **G02B 6/305** (2013.01)

(58) **Field of Classification Search**

CPC **G02B 6/262**; **G02B 6/305**

See application file for complete search history.

(56)

References Cited

U.S. PATENT DOCUMENTS

9,302,430 B2 4/2016 Thiel et al.
10,288,810 B2 * 5/2019 Lu **G02B 6/4225**
(Continued)

FOREIGN PATENT DOCUMENTS

EP 0 989 422 B1 12/2010
EP 2 795 382 B1 2/2019
(Continued)

OTHER PUBLICATIONS

International Search Report and Written Opinion of the International Searching Authority for International Patent Application No. PCT/US2021/023744 mailed Jul. 13, 2021, 10 pages.

(Continued)

Primary Examiner — Michael P Mooney


(74) *Attorney, Agent, or Firm* — Merchant & Gould P.C.

(57)

ABSTRACT

Optical guiding elements are 3D printed on the ends of optical fibers. A multifiber connector includes fibers having 3D printed elements that are flush with the end face of the connector. The printed 3D element may be down-tapered for coupling between a single mode optical fiber and an optical chip waveguide. The cross-sectional shape of the 3D printed optical element may change along its length so as to more closely match to the mode field of a non-circular waveguide on the optical chip. The optical element may be printed with a gradient index. The optical element may be provided with

(Continued)



an output face distal from the optical fiber that is not flat and which changes the divergence of the light passing there-through.

20 Claims, 21 Drawing Sheets

(56)

References Cited

U.S. PATENT DOCUMENTS

2008/0197285	A1 *	8/2008	Frey	G01J 1/02
				250/336.2
2018/0281324	A1	10/2018	Gießen et al.	
2018/0372960	A1	12/2018	Wohlfeil	
2019/0331868	A1	10/2019	Watte et al.	

FOREIGN PATENT DOCUMENTS

JP	2004-530927	A	10/2004
WO	2019/165205	A1	8/2019

OTHER PUBLICATIONS

Augustin, L. et al., "Standardized Process Could Revolutionize Photonic Integration", *Euro Photonics*, 18: 30-34 (2013).

Billah, M.R. et al., "Hybrid integration of silicon photonics circuits and InP lasers by photonic wire bonding", *Optica*, 5(7): 876-883 (Jul. 2018).

Bowers, J.E. et al., "Recent Advances in Silicon Photonic Integrated Circuits", *Proc. of SPIE*, 9774: 1-18 (2016).

Dietrich, P.I. et al., "In situ 3D nanoprinting of free-form coupling elements for hybrid photonic integration", *Nature Photonics*, 12:241-247 (Apr. 2018).

Dong, P. et al., "Silicon photonic devices and integrated circuits", *Nanophotonics*, 3(4-5): 215-228 (2014).

Farsari, M. et al., "Two-photon fabrication", *Nature Photonics*, 3: 450-452 (Aug. 2009).

Gissibl, T. et al., "Spatial beam intensity shaping using phase masks on single-mode optical fibers fabricated by femtosecond direct laser writing", *Optica*, 3(4): 448-451 (Apr. 2016).

Gissibl, T. et al., "Sub-micrometre accurate free-form optics by three-dimensional printing on single-mode fibres", *Nature Communications*, (Jun. 1-9, 2016).

Gissibl, T. et al., "Two-photon direct laser writing of ultracompact multi-lens objectives", *Nature Photonics*, 1-7 (2016).

Kowalczyk, M. et al., "Microstructured gradient-index antireflective coating fabricated on a fiber tip with direct laser writing", *Optics Express*, 22(10): (May 1-6, 2014).

Lindenmann, N. et al., "Connecting Silicon Photonic Circuits to Multi-Core Fibers by Photonic Wire Bonding", *Journal of Lightwave Technology*, 33(4): 1-7 (2015).

Marchetti, R. et al., "Coupling strategies for silicon photonics integrated chips [Invited]", *Photonics Research*, 7(2):201-239 (Feb. 2019).

Milton, A.F. et al., "Mode Coupling in Optical Waveguide Horns", *IEEE Journal of Quantum Electronics*, QE-13(10):828-835 (Oct. 1977).

Mitomi, O. et al., "Design of a Single-Mode Tapered Waveguide for Low-Loss Chip-to-Fiber Coupling", *IEEE Journal of Quantum Electronics*, 30(8): 1787-1793 (Aug. 1994).

Mu, X. et al., "Edge Couplers in Silicon Photonic Integrated Circuits: A Review", *Appl. Sci*, 10: 2-29 (2020).

Munoz, P. et al., "Silicon Nitride Photonic Integration Platforms for Visible, Near-Infrared and Mid-Infrared Applications", *Sensors*, 17: 1-25 (2017).

Presby, H., "Near 100% Efficient Fiber Microlenses", *OSA/OFC*, 404-407 (1992).

Rahim, A. et al., "Expanding the Silicon Photonics Portfolio With Silicon Nitride Photonic Integrated Circuits", *Journal of Lightwave Technology*, 35(4): 639-649 (Feb. 2017).

Smit, M. et al., "An Introduction to InP-based generic integration technology", *Semiconductor Science and Technology*, 29: 1-41 (2014).

Smit, M. et al., "Past, present, and future of InP-based photonic integration", *APL Photon*, 4: 050901-1-050901-10 (2019).

Son, G. et al., "High-efficiency broadband light coupling between optical fibers and photonic integrated circuits", *Nanophotonics*, 7(12): 1845-1864 (2018).

Vanmol, K. et al., "Two-photon direct laser writing of beam expansion tapers on single-mode optical fibers", *Optics and Laser Technology*, 112: 292-298 (2019).

Yin, P. et al., "Low connector-to-connector loss through silicon photonic chips using ultra-low loss splicing of SMF-28 to high numerical aperture fibers", *Optics Express*, 27(17): (Aug. 1-6, 2019).

Zukauskas, A. et al., "Tuning the refractive index in 3D direct laser writing lithography: towards GRIN microoptics", *Laser Photonics Rev*, 9(6): 706-712 (2015).

Series G: Transmission Systems and Media, Digital Systems and Networks, Transmission media and optical systems characteristics—Optical fibre cables, Characteristics of a single-mode optical fibre and cable, ITU-Telecommunication Standardization Sector of ITU, G.652, (Nov. 1-28, 2016).

Vanmol Koen et al.: "3D direct laser writing of microstructured optical fiber tapers on single-mode fibers for mode-field conversion", *Optics Express*, vol. 28, No. 24, Nov. 13, 2020 (Nov. 13, 2020), p. 36147, XP093009677, DOI: 10.1364/OE.409148 Retrieved from the Internet: URL: https://opg.optica.org/DirectPDFAccess/AD4E4350-B874-4788-81CC3430F57A85D4_442637/OE-28-24-36147.pdf?da=1&id=442637&seq=0&mobile=no.

Liu Ying et al.: "Three-dimensional printing and deformation behavior of low-density target structures by two-photon polymerization", *Proceedings of SPIE*; [Proceedings of SPIE ISSN 0277-786X vol. 10524], SPIE, US, vol. 10354, Aug. 31, 2017 (Aug. 31, 2017), pp. 103541U-103541U, XP060092911, DOI: 10.1117/12.2274193 ISBN: 978-1-5106-1533-5.

European Search Report for Application No. 21774893.8 mailed Mar. 22, 2024, 8pgs.

* cited by examiner




FIG. 1

Normalized Electric Field Intensity




FIG. 2A




FIG. 2B




FIG. 2C




FIG. 2D




FIG. 2E




FIG. 2F




FIG. 3A




FIG. 3B




FIG. 3C




FIG. 3D




FIG. 4A




FIG. 4B




FIG. 4C




FIG. 4D




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 9




FIG. 10A




FIG. 10B




FIG. 10C




FIG. 10D




FIG. 11A






FIG. 11B






FIG. 13




FIG. 14




FIG. 15A




FIG. 15B




FIG. 15C




FIG. 15D

FIG. 15E

FIG. 15F

FIG. 15G





FIG. 16A







FIG. 16B






FIG. 17E




FIG. 17D




FIG. 17F




FIG. 18D




FIG. 18B




FIG. 18A




FIG. 18C




FIG. 19A




FIG. 19B




FIG. 19C




FIG. 20A




FIG. 20B




FIG. 20C

1

MULTIPLE FIBER CONNECTIVITY BASED ON 2-PHOTON, 3D PRINTED, TAPERED FIBER TIPS

CROSS-REFERENCE TO RELATED APPLICATIONS

This application is a National Stage Application of PCT/US2021/023744, filed on Mar. 23, 2021, which claims the benefit of U.S. Patent Application Ser. No. 62/993,449, filed on Mar. 23, 2020, and claims the benefit of U.S. Patent Application Ser. No. 63/046,479, filed on Jun. 30, 2020, the disclosures of which are incorporated herein by reference in their entireties. To the extent appropriate, a claim of priority is made to each of the above disclosed applications.

FIELD OF THE INVENTION

The invention relates to fiber optical communications, and more particularly to tips that are 3D printed onto the end of a fiber to enhance the coupling of light into and out of the fiber.

BACKGROUND

Connections between standard single-mode fibers and photonic integrated circuits tend to have relatively high coupling losses due to a difference in mode size and profile between both waveguides. Edge coupling strategies involving specialty fibers are frequently used to obtain the best performance in terms of coupling efficiency, bandwidth and polarization independence.

The integration of many different optical components and functionalities into a compact device or chip has been actively investigated for many years. Research into these so-called Photonic Integrated Circuits (PIC) has led to three main material platforms, namely silicon (Si), silicon nitride (SiN) and indium phosphide (InP). All of these platforms have their intrinsic merits and challenges, and are found to be particularly useful for specific components and applications. The Si-platform can make use of high-yield optimized processing techniques compatible with the complementary metal-oxide-semiconductor (CMOS) manufacturing industry for the fabrication of high-volume and small-footprint chips, whereas SiN is showing better performance for passive components in terms of propagation loss and transparency at visible wavelengths, at the expense of a larger footprint. Finally, the InP-platform allows monolithic integration of active components and hence is the platform-of-choice for optical amplifiers and lasers.

While the many developments in chip-level components bring various fascinating opportunities and applications, one of the limiting factors in the widespread adoption of PICs is their packaging, and in particular their connection to the outside world. As the optical modes in integrated waveguides tend to be significantly smaller than those in standard single-mode fibers, creating a highly efficient, robust and alignment-tolerant fiber-to-chip interface remains a challenge.

The two main coupling strategies that have been conventionally investigated are grating couplers and edge couplers. Grating couplers are not as efficient as edge couplers, and their efficiency is dependent on the wavelength and polarization of the light, which can be restrictive when the PIC is intended to operate over a range of wavelengths and/or polarization is not controlled. The edge-coupling approach, also referred to as "in-plane coupling," generally offers the

2

best optical performance in terms of coupling efficiency, spectral transmission bandwidth and polarization independence. This approach often relies on an intermediate coupling scheme that transforms and matches the modal field of the chip waveguide to that of the single mode fiber. Various approaches to achieving this in the past include the implementation of on-chip taper features, specialty fibers, or a combination of both.

The most frequently used types of specialty fibers for fiber-to-chip coupling are lensed fibers. These end-shaped fibertips (usually conical) can be micro-polished or laser-ablated out of standard optical fibers to produce a focal spot down to about $>1\ \mu\text{m}$ (full width at half maximum). This free-space approach of coupling is subject to Fresnel reflections at the optical interfaces of the glass fiber and the semiconductor chip. Anti-reflection coatings can improve the coupling efficiency, but they also introduce a wavelength dependence, negatively affecting one of the important advantages that the edge coupling approach has over grating coupling. Secondly, the lensed approach is limited in its design freedom on the shape and size of the focused spot, making it hard to exactly match to the chip's modal fields. Third, the additional step of providing the antireflection coating increases the cost of the PIC product.

As an alternative, research has been done on the use of ultra-high numerical aperture (UHNA) fibers to create a true butt-coupled (physical contact) fiber-to-chip connection. This technique permits the use of an index-matching medium to minimize reflections and is more suitable for mutual alignment of an array of fibers in multifiber edge-coupling structures. On the other hand, these UHNA fibers do not come in a large variety, have little freedom in the desired mode-field diameter (MFD), which is usually between 3 and $5\ \mu\text{m}$, and require thermal core expansion to achieve efficient coupling to standard single mode fibers. The latter process is cumbersome and its repeatability could still greatly be improved.

There remains a need, therefore, to find improved approaches for coupling between optical fibers, particularly single mode optical fibers, and PICs.

SUMMARY OF THE INVENTION

One embodiment of the invention is directed to a multi-fiber optical device that has a multi-fiber aligning element, a first optical fiber terminating at a first fiber end at the multi-fiber aligning element and at least a second optical fiber terminating at a second fiber end at the multi-fiber aligning element. A first tapered optical element is 3D printed on the first fiber end; and a second tapered optical element is 3D printed on the second fiber end. The first tapered optical element and the second tapered optical element have respective coupling ends flush with an end face of the multi-fiber aligning element.

Another embodiment of the invention is directed to a fiber-coupled optical chip device, that includes a first optical fiber having a first end. A first down-tapered optical element is 3D printed on the first end of the first optical fiber. The first down-tapered optical element has a fiber end proximate the first end of the first optical fiber and a coupling end distal from the fiber end. An optical chip has a first waveguide configured for edge coupling. The coupling end of the first down-tapered optical element is aligned with the first waveguide of the optical chip.

Another embodiment of the invention is directed to a fiber optic device that includes an optical fiber having a first end face and a core. A tapered optical element is 3D printed on

the first end face of the optical fiber. The tapered optical element has a fiber end and a coupling end, the fiber end of the tapered optical element being aligned with the core of the optical fiber. The fiber end of the tapered optical element has a first cross-sectional shape and the coupling end of the tapered optical element has a second cross-sectional shape different from the first cross-sectional shape.

Another embodiment of the invention is directed to an optical device that includes an optical fiber having an end face. A tapered optical element is 3D printed on the end face of the optical fiber. The tapered optical element has a fiber end proximate the optical fiber and a coupling end distal to the optical fiber. The tapered optical element has an output face at the coupling end, where the output face is configured to alter divergence of light passing through the output face.

Another embodiment of the invention is directed to an optical device that includes an optical fiber having an end face. An optical element is 3D printed on the end face of the optical fiber, the optical element having a fiber end proximate the optical fiber and a coupling end distal to the optical fiber. An optical axis of the optical fiber passes through the optical element. The optical element has a refractive index gradient in a direction perpendicular to the optical axis.

The above summary of the present invention is not intended to describe each illustrated embodiment or every implementation of the present invention. The figures and the detailed description which follow more particularly exemplify these embodiments.

BRIEF SUMMARY OF THE FIGURES

The invention may be more completely understood in consideration of the following detailed description of various embodiments of the invention in connection with the accompanying drawings, in which:

FIG. 1 schematically illustrates a plan view of an optical fiber that is edge-coupled to a photonic integrated circuit (PIC) via an attached down-tapered optical element, according to an embodiment of the invention;

FIGS. 2A-2F present simulated TE modal field intensities of the estimated input/output waveguides of the different material platforms: (A) SiON SSC; (B) inverted Si-taper; (C) inverted SiN-taper; (D) SiN symmetric double-strip; (E) InP waveguide; and (F) G652 standard single mode fiber;

FIGS. 3A-3D schematically illustrate a tapered optical element having a coupling end that has a different cross-sectional shape, in particular an elliptical shape, from the cross-sectional shape of its fiber end, which has a circular shape, according to an embodiment of the invention;

FIGS. 4A-4D schematically illustrate relative cross-sectional shapes of fiber ends and coupling ends of tapered optical elements, according to embodiments of the invention;

FIG. 5 schematically illustrates an embodiment of a down-tapered optical element showing definitions used in modeling confined optical propagation along tapered optical elements, according to embodiments of the invention;

FIG. 6 graphically presents three different taper profiles employed in the modeling of confined optical propagation along tapered optical elements according to embodiments of the invention;

FIG. 7 presents a graph of results of modeling confined optical propagation along tapered optical elements having different taper profiles according to embodiments of the invention, as a function of taper length: curve 700 is for a linear taper, curve 702 is for a thick nonlinear taper and curve 704 is for a thin nonlinear taper;

FIG. 8 presents a graph showing minimal mode-field diameter (MFD) as a function of refractive index difference between a tapered optical element and a cladding, according to embodiments of the invention;

FIG. 9 schematically illustrates an embodiment of an approach to manufacturing tapered optical elements using 2-photon polymerization, 3D printing, and dip-in laser lithography, according to embodiments of the invention;

FIGS. 10A-10D present scanning electron microscope (SEM) images of various embodiments of tapered optical elements according to the present invention;

FIGS. 11A and 11B present results of MFD measurements on tapered optical elements according to the invention: (A) presents near field measurements made at the output of a tapered optical element and (B) presents a graph showing measured MFD as a function of coupling tip diameter for a linear tapered optical element and a single MFD measurement for a nonlinearly tapered optical element;

FIG. 12A schematically illustrates an experimental set-up used for measuring coupling losses between a tapered optical element according to the invention and an optical chip;

FIG. 12B schematically illustrates an experimental set-up used for calibrating the set-up illustrated in FIG. 12A;

FIG. 13 presents a graph of experimentally obtained values of coupling loss per facet for a linear tapered optical element according to the invention, as a function of coupling tip diameter, for five different semiconductor photonic integrated chip platforms;

FIG. 14 presents a graph of experimentally obtained values of coupling loss per facet, as a function of wavelength, for coupling via a tapered optical element according to the invention and via a lensed fiber;

FIGS. 15A-15F schematically illustrate various steps in manufacturing a multi-fiber holder for fibers terminated using tapered optical elements, using a multi-fiber ferrule according to an embodiment of the invention;

FIG. 15G schematically illustrates the multi-fiber holder for fibers of FIG. 15F attached to an optical chip, according to an embodiment of the invention;

FIGS. 16A and 16B schematically illustrate tapered optical elements, formed with an excess length that may be removed during manufacture of a multi-fiber holder for fibers terminated using tapered optical elements, according to an embodiment of the invention;

FIGS. 17A-17E schematically illustrate various steps in manufacturing a multi-fiber holder for fibers terminated using tapered optical elements, using a multi-fiber alignment block according to an embodiment of the invention;

FIG. 17F schematically illustrates the multi-fiber holder of FIG. 17E coupling fibers to an optical chip, according to an embodiment of the invention;

FIGS. 18A-18B schematically illustrate various steps in manufacturing a multi-fiber holder for fibers terminated using tapered optical elements, using a multi-fiber alignment block, according to another embodiment of the invention;

FIGS. 18C and 18D schematically illustrate the multi-fiber holder of FIG. 18B coupling fibers to an optical chip, according to another embodiment of the invention;

FIGS. 19A-19C schematically illustrate embodiments of optical element having a curved output face, according to the present invention; and

FIGS. 20A-20C schematically illustrate embodiments of optical element having a graded index, according to the present invention.

While the invention is amenable to various modifications and alternative forms, specifics thereof have been shown by way of example in the drawings and will be described in

detail. It should be understood, however, that the intention is not to limit the invention to the particular embodiments described. On the contrary, the intention is to cover all modifications, equivalents, and alternatives falling within the spirit and scope of the invention as defined by the appended claims.

DETAILED DESCRIPTION OF THE INVENTION

The approach described herein may be useful for optimizing the fiber side of the fiber-to-chip connection and tailoring the design of the fiber taper to the on-chip waveguide schemes employed in photonic integrated circuit (PIC) devices. The fabrication of free-standing down-taper structures, using two-photon direct laser printing, directly on top of cleaved fiber facets is described. These tapers can find utility for coupling between a fiber and silicon, silicon nitride and indium phosphide PIC chip platforms. The tapered structures may be tailored to provide flexibility in the output modal fields and coupling efficiencies.

An exemplary coupling arrangement **100** is schematically illustrated in FIG. 1, showing a tapered optical element **102** attached to a fiber **104** that has a core **106**. The tapered optical element **102** may include a pedestal base **108** that provides a larger surface area for attaching the tapered optical element **102** to the end facet **110** of the fiber **104**. The tapered optical element **102** includes a tapered section **112** that aligned to the fiber core **106** and has a first cross-sectional area at the fiber end **113** and a second cross-sectional area at the coupling end **114**, which may also be referred to as a coupling tip. The coupling end **114** is aligned to a waveguide **116** of optical chip **118**. The second cross-sectional area is typically smaller than the first cross-sectional area when coupling between a single mode fiber and a semiconductor PIC, due to the tighter confinement of the light in the waveguide **116** compared to the fiber core **106**. Such a tapered optical element **102** may be referred to as a “down-taper” because the first cross-sectional area at the fiber end **113** is greater than the second cross-sectional area at the coupling end **114**. The tapered optical element **102** confines the light passing therethrough and operates as a tapered waveguide that is attached to the end of the fiber core **106**.

The tapered optical element **102** may be printed on the end facet **110** of the optical fiber **104** using two-photon polymerization (2PP)-based direct laser writing using a dip-in geometry. This fabrication technology allows the creation of 3D structures with design freedom and submicrometer resolution. A taper structure with excellent modal match in terms of shape and size may be fabricated directly on the end face of the optical fiber such that it can be butt-coupled with the photonic chip to minimize reflections. Furthermore, the design flexibility associated with the 2PP, 3D printed, tapered optical element **102** does not put extra constraints on any on-chip coupling structures. The chip **118** may be coupled to other optical fibers using similar tapered optical elements, for example with the fiber **104** providing an input to the chip **118** and the other fiber or fibers being used for an output or outputs from the chip **118** at a different edge of the chip **118**. In other embodiments, for example as discussed below, the fiber **104** may be one of a number of optical fibers aligned to the chip **118** in a multi-fiber alignment device.

The 2PP 3D printing technique has been used in the development of a microstructured antireflective coating, phase masks, lenses, and mode-field expansion up-taper

structures on optical fiber tips. In the latter, the fabrication method was demonstrated for use in alignment tolerant physical contact expanded beam fiber-to-fiber connections, as described in K. Vanmol et al., “Two-photo direct laser writing of beam expansion tapers on single-mode optical fibers,” *Optics and Laser Technology* (2019), vo. **112**, pp. 292-298, incorporated herein by reference. The 2PP, 3D printing of tapered optical elements on fibers has also been described in International Publication No. WO2019/165205, also incorporated herein by reference.

The present approach may advantageously reduce reflection losses for light passing between the fiber **104** and the chip **118** by, for example, allowing the fiber coupling end **114** to physically contact the edge of the chip **118** at the waveguide **116**, or to optically couple to the waveguide **116** via a short path of index matching material. This approach provides a coupling solution for optical chips that does not require re-engineering of the optical chips. Furthermore, connections formed using the tapered optical element can be designed with complete 3D freedom to provide a high degree of matching between the mode-field of the chip **118** and that of the optical fiber **104**.

Mode Field Matching

The embodiment of a down-tapered optical element schematically illustrated in FIG. 1, i.e., a tapered element **102** whose cross-sectional area is less at its coupling end than at the base attached to the optical fiber, fabricated on a single mode fiber, includes a 3D printed polymer tapered section **112** that is a core with an air cladding. In such an embodiment, the tapered optical element **102** itself has a large refractive index difference between its core and the air cladding, in which case multiple optical modes may be supported. However, excitation and mode coupling to these higher order modes and radiative modes may be avoided by careful design of the taper structure and proper placement on the fiber facet, such that maximal transmission is obtained in the fundamental mode of the tapered optical element **102**. In order to transmit light efficiently between the optical fiber core **106** and the chip waveguide **116**, the tapered optical element **102** advantageously has a good overlap between its modal fields and the modal fields of the tapered optical element and chip waveguide.

An eigenmode solver in the MODE simulator of the Lumerical Device Multiphysics Simulation Suite, available from Lumerical Inc., Vancouver, Canada, was used to model the modes of the fiber and the waveguides in various chip platforms. All simulations were performed at a wavelength of 1550 nm, which is one of the main wavelengths used in single mode fiber and PIC technology, due to low material absorption in that spectral range and the many telecom-related applications that come with it.

At the coupling end of the down-taper optical element, the polymer core is advantageously mode-matched to the PIC waveguide mode profile. The modal fields of five different types of PICs, across three different material platforms, were modeled. FIG. 2 gives an overview of the estimated waveguide layouts and their simulated mode profiles.

Two different chips with different input/output waveguide strategies were examined for the silicon platform. The first, shown in FIG. 2A, assumes a silicon oxynitride (SiON) spot-size converter (SSC). The second, shown in FIG. 2B, assumes the use of an inverted Si-taper. Two different chips with different input/output waveguide strategies were examined for the SiN platform. The first, shown in FIG. 2C has a single buried tapered waveguide. The second, shown in

FIG. 2D, has a symmetric double-strip geometry. A single chip based on an InP platform is shown in FIG. 2E, having an InGaAsP rib-waveguide. The output mode from a G.652 standard telecom fiber, used as the input in simulations of the down-tapered optical element, is shown in FIG. 2F.

The design was based on the Transverse Electric (TE) polarization state. An analogous methodology may be used to find optimal coupling design for the Transverse Magnetic (TM) polarization states.

An eigenmode analysis and optimization makes it possible to find the optimal taper input and output dimensions for maximal mode overlap with the optical fiber and the optical chips, respectively. The optimal input polymer waveguide diameter at the fiber side is found to be about 15.1 μm , to mode match with the G.652 single mode fiber. At the output side of the tapered optical element, the optimal coupling dimensions depend on the exact PIC waveguide scheme. Such information is often maintained confidential by the manufacturer of the chip.

Many waveguide geometries have strong elliptical mode profiles, such as the profiles for the SION SSC shown in FIG. 2A and the InGaAsP rib waveguide shown in FIG. 2E. A tapered optical element having a coupling end shaped for a mode that closely matches the mode of the chip waveguide increases coupling efficiency between the fiber and the chip waveguide. For example, in the case of a chip waveguide having an elliptical mode, an elliptical or oblong shaped coupling end on the tapered optical element may increase coupling efficiency relative to a circular coupling end. One embodiment of tapered optical element 300, schematically illustrated in FIG. 3A, has a coupling end 302 that has an elliptical shape. The tapered optical element 300 is shown without a pedestal base. In the illustrated embodiment, the fiber end 304 of the tapered optical element 300, opposite the coupling end 302, is that part of the tapered optical element whose optical mode is matched to the optical mode of the fiber to which the tapered optical element is attached. FIG. 3B schematically illustrates an end-on view of the tapered optical element 300 (looking in the $-z$ direction), while FIG. 3C schematically illustrates a side view of the tapered optical element 300 looking along the direction along the major axis of the elliptical coupling end 302 (the x -direction) and FIG. 3D schematically illustrates a side view of the tapered optical element 300 looking along the direction of the minor axis of the elliptical coupling end 302 (the y -direction).

The 2PP 3D laser printing process used to manufacture the tapered optical element conveniently allows a wide variety of shapes to be used at the coupling end of the tapered optical element, some of which are schematically illustrated in FIGS. 4A-4D, which show end-on views of the tapered optical element. In FIG. 4A, the tapered optical element 400 has a circular coupling end 402 and a circular fiber end 404. In the embodiment schematically illustrated in FIG. 4B, the tapered optical element 410 has a square coupling end 412 and a circular fiber end 414. In the embodiment schematically illustrated in FIG. 4C, the tapered optical element 420 has a rectangular coupling end 422 and circular fiber end 424. In the examples shown in FIGS. 3B, 4A, 4B and 4C, the coupling end of the tapered optical element has a shape that has two orthogonal axes of mirror symmetry. This need not be the case, and a shape with different symmetry, or no symmetry, may be used at the coupling end. An embodiment of such an approach is schematically illustrated in FIG. 4D, where the tapered optical element 430 has a triangular coupling end 432 and a circular fiber end 434. Other shapes of coupling end may be

used in order to efficiently match the optical mode of the coupling end of the tapered optical element to the mode of the chip waveguide including, but not limited to, other triangles, regular and irregular quadrilateral shapes, including trapezoids, and shapes with more than four sides.

In the embodiments discussed with reference to FIGS. 3 and 4, the fiber ends of the tapered optical elements were all circular. This is not a necessary condition but, where the fiber has a circular core and, therefore, a concomitant circular optical mode, coupling to the tapered optical element from the fiber is efficient when the mode of the fiber end is also circular. The fiber end of the tapered optical element may also have a cross-sectional shape that is not circular.

Taper Profile

The Lumerical Mode Solutions software, referenced above, was used to model propagation of light from the fiber through the tapered optical element. A schematic of the model used for these calculations is provided in FIG. 5, which shows a fiber 500 having a core 502 and an output face 504. The tapered optical element 506 is assumed to be circularly symmetrical and has a diameter, D_1 , at its fiber end 508 of 15.1 μm . The length of the tapered optical element is L and the diameter of the coupling end 510 is D_2 . The values of D_2 ranged from 1 μm to 7 μm in 1 μm increments.

A sweep of the taper length permits a (local) maximum in transmission for the fundamental mode to be found. In general, a larger taper length, which corresponds to a more gradual change in cross section, provides better transmission of the fundamental mode, although this is not always the case. It was found that a taper length of 250 μm is quite adiabatic, giving more than 90% fundamental mode transmission for all output diameters. This taper length limit was chosen to prevent the need for stitching of writing fields in the fabrication process.

While linear tapers provide adiabatic operation, it was found that shorter taper lengths could be achieved using nonlinear tapers. The use of a shorter tapered element reduces the chance that it suffers from mechanical damage, which increases propagation loss. Such nonlinear-shaped tapered optical elements can decrease the total taper length, while keeping the radiation loss from mode-field conversion low. To investigate the usefulness of a nonlinear taper in a tapered optical element, the simulations included a nonlinear function for the diameter of the tapered optical element as a function of distance along the elements, $D(z)$, as follows:

$$D(z)=D_2+(D_1-D_2)\cdot(1-z/L)^m \quad (1)$$

where L is the length of the taper, m is the nonlinear exponent, and D_1 and D_2 are the taper's input and output diameters respectively.

The profile of different tapers is shown in FIG. 6, which shows the taper radius ($=D(z)/2$) as a function of position along the tapered optical element. The input radius at position zero mode-matched with a single mode fiber (diameter 15.1 μm , radius 7.505 μm) and an output diameter of 2 μm (radius 1 μm). Curve 600 corresponds to a linear taper profile, with the nonlinear exponent, $m=1$. Curve 602 corresponds to a nonlinear taper profile, with $m=1/2$. This type of nonlinear taper profile 602, where the radius is greater than the corresponding linear taper profile 600 (with both tapers starting at $L=0$ and terminating at $L=L$), is referred to herein as a thick nonlinear taper. Curve 604 corresponds to a nonlinear taper profile, with $m=2$. This type of nonlinear

taper profile **604**, where the radius is less than the corresponding linear taper profile **600**, is referred to herein as a thin nonlinear taper.

The calculation of the evolution of the fundamental mode's transmission as a function of taper length for each of these three taper profiles is illustrated in FIG. 7. Curve **700** corresponds to the taper profile having a value of $m=1$ (linear). Curve **702** corresponds to the taper profile having a value of $m=1/2$ (thick nonlinear). Curve **704** corresponds to the taper profile having a value of $m=2$ (thin nonlinear). The profile corresponding to an exponent of $m=2$ gives less efficient transmission than the other profiles. On the other hand, the thin nonlinear profile, having $m=1/2$, reaches a point of 89% transmission at a length of 62.7 μm , whereas the linear profile only reaches such a high transmission for lengths larger than 127 μm . Therefore, a nonlinear taper profile structure may allow the use of shorter taper lengths, with a resultant reduction in exposure to damage, with only a small decrease in efficiency compared to longer taper lengths.

Material absorption was not taken into account in the transmission simulations. Cured IP-DIP polymer has an absorption loss of less than 1 dB/cm at 1550 nm. As the length of the tapered optical elements is typically less than one half of one millimeter, material absorption may be sufficiently small as to be neglected.

Reflective Losses

Reflection of the incoming light at an interface of different refractive index media can impair the coupling efficiency. Even when two waveguides are perfectly butt-coupled, without having any air-gap between them, a mismatch between the effective indices of both waveguides may generate back-reflections. The reflectance, R , for a normally incident light beam passing an interface from medium 1 to medium 2 is given by:

$$R = (n_2 - n_1)^2 / (n_2 + n_1)^2 \quad (2)$$

where n_1 and n_2 respectively represent the refractive or effective indices of the two media or waveguides.

An optimal mode overlap is targeted for every chip platform, and the difference in effective indices between the tapered fiber and the chip is relatively small, leading to an estimated reflectance of <3% per facet in the Si- and SiN-based platforms. In the InP platform, however, which has a relatively high refractive index, the Fresnel reflection is about 15% per facet.

Misalignment Tolerances

In the investigation of coupling between (sub)micrometer-scale structures, a misalignment tolerance analysis gives many insights into the realistically achievable efficiency of the designed structure in practice. A good understanding of alignment tolerances aids in making decisions in the design phase, in analyzing experimental results, and in defining packaging strategies.

In a butt-coupled (physical contact) connection, lateral misalignments have a higher impact on loss than axial and angular misalignments. The consequences from misalignments are found to be larger with decreasing mode-field diameters. Simulations show that a submicrometer accurate alignment is needed for all chip platforms (Si, SiN and InP) in order to achieve <1 dB misalignment losses. In general,

a larger misalignment tolerance may be achieved by making use of wider taper tips, but this may result in lower coupling efficiency.

It may be possible to introduce a small misalignment between the tapered optical element and the fiber core during the taper fabrication process. Nevertheless, the use of high-magnification real-time imaging of the fiber end-facet during the printing process can result in the achievement of submicrometer positioning control.

Impact of Adding Cladding Material

This disclosure has, so far, only considered an air-clad tapered optical element. However, index matching materials play an important role in photonic chip packaging. Such materials usually come in the form of gels or UV-curable epoxies and may be used to fill the air-gap between the chip and the tapered optical element. Judicious selection of the material may result in reducing unwanted reflections at the optical interfaces, thus reducing transmission losses.

The index matching material may, at the same time as providing index matching, be used as an effective cladding for the down-tapered waveguide, and provide mechanical support to the tapered optical element. The cladding may also prevent contamination of the taper interface that could lead to undesired radiation losses and may possibly also decrease possible scattering due to roughness at the taper's side wall.

A decrease in refractive index difference between the tapered optical element, which is its own waveguide, and the cladding (Δn) reduces the degree of light confinement in the tapered optical element, therefore increasing the size of its mode-field. As such, the minimal mode-field diameter that is possible to obtain increases with decreasing index contrast, as can be seen in FIG. 8. As a result, the choice of cladding material (which determines the index contrast) may include a compromise between fiber-to-taper and taper-to-chip coupling efficiency, and Fresnel reflections.

Methods of Fabrication

A Photonic Professional GT+ system from Nanoscribe GmbH, Eggenstein-Leopoldshafen, Germany, was used in the dip-in configuration to fabricate various tapered optical elements directly on the end-facet of cleaved G.652 single mode fibers.

The fiber core position is identified by sending red laser light through the fiber and then aligned with the printer axes. The full tapered optical element may be printed in a matter of minutes using the built-in galvo scanner. The processing steps may be carried out without any specific environmental restrictions, e.g. temperature or humidity control, other than processing the undeveloped material in a room with UV-filtered lighting conditions to prevent undesired single-photon polymerization of the resist.

A typical set up **900** for dip-in laser lithography (DiLL), two photon polymerization, 3D printing process is schematically illustrated in FIG. 9, in which a polished end facet **902** of a fiber **904** is immersed in a photosensitive liquid resist **906**. Light **908** from a pulsed laser, such as a femtosecond erbium-doped fiber laser, operating at around 1550 nm, or a modelocked Ti:Al₂O₃ laser operating around 800 nm, is focused by a focusing unit **910**, through the liquid resist **906** to a focal point **912**. The focusing unit **910** may include one or focusing elements such as lenses or mirrors. In most cases, the volume between the focusing unit **910** and the fiber end facet **902** is filled with the liquid resist **906**. In the

illustrated embodiment, the focal point **912** is at the intersection of the lens axis **914** and the focal plane **916**.

The liquid resist **906** undergoes a multi-photon polymerization reaction at the focal point **912**, in most cases a 2-photon reaction, and solidifies. The correct selection of the optical power of the light **908** and the focusing properties of the focusing unit **910** can, therefore, result in the volume element (voxel) where the liquid resist **906** reacts with the light **908** being extremely small, and may be submicron in size. The tapered optical elements discussed below were fabricated using a voxel of around 150 nm×150 nm×500 nm, obtained using a 63×objective with a numerical aperture (NA) of 1.4. The fiber end facet **902** and/or the focal point **912**, can be moved in the x-y plane (the y-direction lies out of the plane of the figure) which, together with selective switching of the light **908**, results in writing a layer of solidified resist having a desired 2D pattern. The end facet **902** can then be moved in the z-direction by an amount equal to about that of the thickness of the 2D pattern just printed, and another 2D layer can then be printed on top of the previous layer. In this manner, a 3D object can be formed by sequentially printing a number of 2D layers. An advantage of DiLL, in which the liquid resist **906** is polymerized at a point between the fiber **904** and the focusing unit **910** is that the height (z-direction) of the resulting 3D structure is not limited by the focal length of the focusing unit **910**.

A system suitable for use in DiLL is the Photonic Professional GT 3D laser lithography system available from Nanoscribe GmbH, Eggenstein-Leopoldshafen, Germany. DiLL is further described in U.S. Pat. No. 9,302,430, incorporated herein by reference. The resist used to fabricate the tapered optical elements is IP-DIP, obtainable from Nanoscribe GmbH. The writing speed and power were according to the manufacturer's specifications.

Good adhesion of the polymer tapered optical element to the fused silica (SiO₂) end-facet **902** is an important consideration. For this reason, in some embodiments, a pedestal base layer is first formed on the end facet **902** prior to forming the tapered body, where the base plate has a larger area in contact with the end facet **902** than would the fiber end of the tapered body alone. The base plate layer may be any suitable thickness. In some embodiments, a base plate layer having a thickness of about 6 μm is employed. Simulations show that such a thin base layer has negligible impact on the light transmission.

Additionally, an adhesion promotor may be used to enhance the adhesion of the polymerized material to the surface of the fiber's end facet **902**. In some embodiments, the adhesion promotor is a silane, for example, 3-(methacryloyloxy)propyltrimethoxysilane ethanol solution (2%, v/v), which may be applied by dipping the fiber end into the silane solution. This chemical surface treatment may enhance the formation of covalent bonds between the organic polymer and the inorganic fiber silica glass upon laser exposure, effectively connecting both materials. In an experiment to test the ability of the silane to promote adhesion to glass, when an increasing shear force was applied to a tapered optical element that was written without a silane-pretreatment on the glass surface, the tapered optical element broke free of the glass at an applied force of 0.015 N. In contrast, when the experiment was performed on a similar tapered optical element that was written on the glass after a silane-pretreatment, the tapered optical element resiliently withstood an applied shear force of 0.15 N.

Submicrometer fabrication tolerances are obtained with the 2PP direct laser writing system, which is quantitatively verified using an SNE-4500M scanning electron microscope

(SEM) (Hirox Europe, Limonest, France), a Contour GT-I white-light interferometer (Bruker Corp, Billerica, MA, USA), and a VideoCheck UA400 coordinate measurement machine (Werth Messtechnik GmbH, Giessen, Germany). SEM images of the linear and nonlinear down-taper models are shown in FIG. **10**. FIG. **10A** shows a scanning electron microscope (SEM) image of a linear tapered optical element that is approximately 250 μm long, fabricated on the end of a single mode fiber. The element has a pedestal base that is approximately 6 μm thick, and has a diameter of 100 μm. The diameter of the tapered optical element at its coupling end is 3 μm. FIG. **10B** shows an SEM image of a thick nonlinear tapered element that is approximately 63 μm long, fabricated on the end of a single mode fiber. The element has a pedestal base that is approximately 6 μm thick, and has a diameter of 100 μm. The diameter of the thick nonlinearly tapered optical element at its coupling end is 2 μm. FIG. **10C** shows an SEM image of a linear tapered optical element fabricated on a glass block. FIG. **10D** shows a magnified image of the element of FIG. **10C**. The element has a pedestal base that is approximately 6 μm thick, and has a diameter of 100 μm. The diameter of the tapered optical element at its coupling end is 3 μm.

The output modal fields of the tapered optical elements were characterized using a Bobcat SWIR camera from Xenics nv (Leuven, Belgium), accompanied by a Zeiss 100×NA0.9 microscope objective (Carl Zeiss Microscopy GmbH, Jena, Germany) allowing high-magnification and high-resolution images of the modes at telecom wavelengths. An experimentally obtained mode-field image from the end-facet of a linear tapered optical element having a tip diameter of 3 μm is shown in FIG. **11A**. The inset shows the image obtained by the camera. The curve **1102** shows intensity as a function of radial position. The dot-dashed line **1104** is the 1/e² intensity contour, from which it can be seen that the 3 μm coupling tip diameter produces an MFD of just over 2 μm. FIG. **11B** shows the measured mode field diameters (MFDs) for different taper designs. The dots show the measured MFDs for linear tapers having output diameters of 1 μm to 7 μm. This near-field measurement technique allows imaging MFDs down to about 1.8 μm, determined by the microscope's resolving power. Thus, the measurement of the MFD of the linear taper having a 1 μm output diameter was resolution limited at 1.8 μm. The sloped line **1106** shows the calculated MFD as a function of output diameter. For all but the smallest tip diameters, the measured MFD was less than the calculated MFD.

The point **1108** shows the measured MFD for the thick nonlinear taper having an output diameter of 2 μm. The MFD of the thick nonlinear taper is only slightly larger than that of its linear counterpart, which may be caused by the change in nonlinear taper diameter being more abrupt close to the coupling end of the element, making it more sensitive to the layered fabrication approach inherent to the 3D printing process.

Coupling Experiments

Coupling experiments were carried out using fibers terminated with a tapered optical element having a linear profile, fibers terminated with a tapered optical element having a nonlinear profile and, for comparison with conventional approaches, commercially obtained lensed fibers. The results reported below for the linearly tapered optical element were obtained using an element of around 250 μm long and coupling tip diameters ranging from 1 μm to 7 μm. The linearly tapered optical element had a base like that

13

shown in FIG. 10A. The commercially obtained lensed fibers were measured to have an MFD of about 2.7 μm . Some experiments were also carried out using a thick nonlinearly coupled element ($m=1/2$) having a length of around 63 μm , and coupling tip diameter of 2 μm . The nonlinearly tapered optical element had a base like that shown in FIG. 10B.

The experimental set-up **1200** used in the coupling experiments is schematically illustrated in FIG. 12A. A light source **1202** is used to generate light, in this case at around 1550 nm. The light source **1202** included a fiber-coupled tunable WDM8-C-27A-20-NM laser source operating at 1549.36 nm combined with a Pro **8000** controller (both available from Thorlabs, Newton NJ, USA). Light from the light source **1202** propagated along a first fiber **1204** via a first fiber coupler **1206** to a fiber-coupled polarization controller **1208**, which was used to align the polarization of the fiber mode to the desired mode of the PIC waveguide under test. The fiber-coupled polarization controller **1208** was coupled, via a second fiber coupler **1210** to a first test fiber **1212**, which was terminated using a tapered optical element or a lens. The output end of the fiber **1212** was mounted to a translation stage **1214**, for example a piezo translation stage, so that its position could be adjusted relative to the PIC **1216**. The translation stage was operated via a translation controller **1218**. The translation controller **1218** was used to move the translation stage **1214** so as to align the fiber termination to the waveguide of the PIC **1216**. A second test fiber **1220**, terminated with a tapered optical element or lens, and mounted on a second translation stage **1222** which was also operated via the translation controller **1218**, was aligned with an output waveguide of the PIC **1216**. The second fiber **1220** was coupled via a third fiber coupler **1224** and fiber **1226** to a fiber-coupled power meter **1228**.

A reference measurement, where the chip and functionalized fibers are removed, was made using the experimental set-up **1250**, schematically illustrated in FIG. 12B. The reference measurement produced a baseline power level which was subtracted from the power level obtained using the set-up **1200** in FIG. 12A, together with the known waveguide loss in the PIC **1216** to obtain a value for the coupling loss per chip/fiber interface. A reference measurement taken by the set-up **1250** shown in FIG. 12B takes into account one less fiber connector than the measurement made in FIG. 12A, and will, therefore tend to overestimate the coupling loss. This way, the obtained coupling loss includes Fresnel reflections and the loss due to absorption, mode conversion and mode mismatch from both the on-chip coupling structures and the fiber taper terminations. A comparison with commercial lensed fibers is then easily done by measuring the losses in the same way.

FIG. 13 presents the experimentally obtained coupling losses/facet for all five different chip platforms as a function of coupling tip diameter using linear tapered optical elements. Curve **1302** (circles) represents the results obtained for the SiON platform, whose mode calculation is presented in FIG. 2A. Curve **1304** (diamonds) represents the results for the Si platform, whose mode calculation is presented in FIG. 2B. Curve **1306** (squares) represents the results for the SiN platform, whose mode calculation is presented in FIG. 2C. Curve **1308** (6-pointed star) represents the results for the SiN 2-strip chip, whose mode calculation is presented in FIG. 2D. Curve **1310** represents the results for the InP platform, whose mode calculation is presented in FIG. 2E. A minimum coupling loss was found as a function of taper tip diameter for every PIC platform. This illustrates an

14

advantage of this flexible design and fabrication strategy, which permits an optimization for coupling efficiency for any given on-chip structure.

A summary of the minimum coupling losses for each of the PIC platforms is given in Table I below, for the linear tapered optical element and the lensed fiber. For four out of the five PIC platforms the tapered optical element was found to incur lower losses than the lensed fiber, with an improvement in coupling efficiency of respectively 0.97 dB, 0.44 dB, 0.03 dB and 1.43 dB for the SiON, SiN, double-strip SiN, and InP platforms. For the Si-platform, it was found that the linear tapered optical element achieved a slightly lower coupling efficiency (0.59 dB) than for the lensed fiber. It is believed this was due to a small mismatch in mode profile, which is expected to be improved with further development. These observations show that it is beneficial to use an optimized mode-matching design so as to reduce the overall coupling losses in fiber-to-chip connections. An additional advantage of using a tapered optical element over lensed fibers is that a physical contact through butt-coupling can be used, which facilitates a more robust packaging of the PIC. Such approaches are described in more detail below.

TABLE I

Summary of the experimental results for chip coupling loss per facet for lensed fibers, and fibers terminated by a tapered optical element, both linear and nonlinear			
PIC Platform	Lensed (dB)	Linear taper (dB)	Nonlinear taper (dB)
(1) SiON	-2.31	-1.34	n/a
(2) Si	-2.10	-2.69	-2.78
(3) SiN	-2.09	-1.65	n/a
(4) SiN	-2.58	-2.55	n/a
(5) InP	-5.61	-4.18	-4.27

In addition, a thick nonlinear tapered optical element ($m=1/2$) was fabricated on single mode fibers and the per facet coupling loss determined. As discussed above, the nonlinear taper is advantageous in that it may be shorter than its linear equivalent while still transmitting a similar fraction of the optical signal. The nonlinear tapered optical elements were formed with a coupling tip diameter of about 2 μm and a length of about 63 μm . They were tested with the Si and InP platforms, which had been shown to have a minimum coupling loss for a linear tapered optical element having a coupling tip diameter of around 2 μm . The coupling between the Si-chip and the nonlinear tapered optical element was found to produce a per facet coupling loss of -2.78 dB, and -4.27 dB for the InP chip. These results show that the use of a nonlinear taper profile may allow the length of the tapered optical element to be significantly decreased, with only a small penalty, around 0.1 dB, in terms of coupling efficiency.

A coupling comparison was made over a wide range of wavelengths between fibers using a linear tapered optical element and lensed fibers, around 1525 nm-1630 nm, which encompasses the C and L telecommunication bands. For this experiment, the light source **1202** was a Tunicas T100S-HP tunable laser obtained from EXFO Inc., Quebec City, Canada. Facet coupling losses were obtained using the SiON platform. The linear tapered optical element had a coupling tip diameter of 6 μm , which was found to be the optimal size for the SiON platform. The results of the comparison are shown in FIG. 14. Curve **1402** shows the facet coupling loss as a function of wavelength using the tapered optical element, while curve **1404** shows the same thing but for the lensed fibers. The losses incurred using the tapered optical element were uniformly less than those incurred using the

15

lensed fibers over the entire wavelength range. Furthermore, the range in coupling efficiency obtained using the tapered coupling element was about 0.44 dB, compared to 0.46 dB obtained using the lensed fibers. This shows that a coupling scheme based on the use of a tapered optical element may be relatively independent of wavelength over the C and L bands.

As the tapered optical element coupling scheme makes use of a true butt-coupled approach, it is advantageous that no damage occurs to either the chip of the tapered optical elements upon physical contact. It has been found that the polymer tapered optical elements are sufficiently bendable, such that the element would bend upon physical contact with the chip without causing any damage (when using translation stages, under practical and realistic circumstances). Unless excessive force is applied, the taper returns to its original straight shape when it is withdrawn from the chip facet, and no degradation in coupling loss is observed.

Multiple Fiber Connectivity

Tapered optical elements may be used for single fiber connections, for example to a PIC or to another fiber. In fiber-fiber coupling, the tapered optical element may be referred to as an "up-taper" where the cross-sectional area of the element becomes larger for distances further from the base.

There is an increasing need to provide multiple fiber connections in a single device. For example, MPO connectors have become widely used in fiber-to-fiber connections, and remains a need to provide multiple fiber connections to an optical chip. These connections need to be efficient, i.e. introduce low loss, and be mechanically sturdy to withstand the rigors of deployment in different environments.

Some embodiments of the invention are directed to providing multi-fiber connectivity between a fiber ribbon and another plurality of waveguides by terminating the fibers of the fiber ribbon with tapered optical elements, and housing the fibers in a multi-fiber aligning element. The other plurality of waveguides may comprise, for example, cores of fibers of another ribbon cable, or waveguides in an optical chip. A multi-fiber aligning element is an element that holds multiple optical fibers in a defined, spatial relation. In some embodiments the multi-fiber aligning element may be the ferrule of a multi-fiber coupler, such as an MPO coupler. In other embodiments the multifiber aligning element may be an alignment block provided with alignment grooves. Different embodiments of the invention that provide multi-fiber connectivity are now discussed.

One approach to providing multiple fiber connectivity using fibers mounted in a ferrule, such as an MPO ferrule, and terminated with tapered optical elements is now discussed with reference to FIGS. 15A-15D. FIG. 15A schematically illustrates a fiber cable ribbon 1502. In the illustrated embodiment, the ribbon cable 1502 contains five optical fibers 1504, but the ribbon cable 1502 may contain any number of fibers. The end of the ribbon cable 1502 has been stripped to expose the individual fibers 1504, and the fibers 1504 are cleaved to be the same length, i.e. so that their ends lie in the same plane, indicated by dotted line 1506. In some embodiments, the fibers 1504 may be polished in order to increase the coplanarity of the fiber ends.

The ribbon cable 1502 is then inserted into a ferrule 1508, for example an MPO ferrule, that is adapted to receive multiple fibers, as is schematically illustrated in FIG. 15B. The ribbon cable 1502 is inserted to a point such that the

16

ends 1510 of the fibers 1504 are slightly protruding from the end surface 1512 of the ferrule 1508, for example by 1 mm or less. A small amount of temporary adhesive, such as an epoxy, may be used to temporarily maintain the position of the ribbon cable 1502 within the ferrule 1508 through the next steps. In some embodiments the temporary adhesive may be injected in the ferrule 1508 through the window 1518 using a micropipette. In another embodiment, the ribbon cable 1502 may be clamped to the ferrule 1508, so that both cannot move relative to each other.

Tapered optical elements 1514 are then fabricated on the ends 1510 of the fibers 1504, for example in a manner as described above, as schematically illustrated in FIG. 15C. The tapered optical elements may include a down-taper profile, for example if the finished article is going to be used to couple the fiber ribbon cable 1502 to a PIC having waveguides smaller in dimension than the cores of the fibers 1504, or may have an up-taper profile, for example for coupling from one fiber ribbon to another.

Next, as is schematically illustrated in FIG. 15D, after releasing any temporary adhesive or clamp, the ribbon cable 1502 is withdrawn from the ferrule 1508 in the direction shown by the arrow so that the end tips of the tapered optical elements 1514 are protruding from the ferrule 1508. The fibers 1504 may then be glued in place within the ferrule 1508, for example using an adhesive 1516, as schematically illustrated in FIG. 15E. The adhesive 1516 may be, for example, a uv cured epoxy or other suitable adhesive material, such as uv curable ORMOCOMP, available from micro resist technology GmbH, Berlin, Germany. The adhesive 1516 may spread into the volume between the fibers 1504 and between the tapered optical elements 1514, in which case the adhesive 1516 may operate as a cladding for the tapered optical elements 1514.

The end surface 1512 of the ferrule 1508 may then be polished, removing any portion of the tapered optical elements 1514 extending beyond the end surface 1512 of the ferrule 1508, along with any excess adhesive 1516 that extends beyond the end surface 1512. The resulting multi-fiber coupling device 1519, as schematically illustrated in FIG. 15F, comprises a multi-fiber ferrule whose guided outputs have a different MFD from the core of the fibers 1504 that enter the ferrule 1508. The multi-fiber coupling device 1519 may include a fiber clamp 1520 along with the ferrule 1508.

In some embodiments, the tapered optical elements 1514 within the ferrule 1508 have the same coupling tip dimensions. In other embodiments, one or more of the tapered optical elements 1514 may be larger or smaller than others within the same ferrule 1508.

If the multi-fiber coupling device 1519 is to be used for coupling to an optical chip 1530, as schematically illustrated in FIG. 15G, the optical chip substrate and the device 1519 may be provided with alignment elements to ensure the correct alignment of the tapered optical elements 1514 with the waveguides in the PIC. For example, in some embodiments, the device 1519 may include an MPO ferrule 1508, which is provided with guide pins 1532. In such a case, the optical chip 1530 to which it is to be mated may be provided with acceptance holes suitable positioned for correct alignment with the waveguides of the chip 1530. The multi-fiber coupling device 1519 may be attached to the chip using an adhesive, such as a uv cured adhesive.

The step of polishing the ends of the tapered optical elements 1514 may remove some material from the tapered optical elements 1514. In some embodiments, the tapered optical elements may be printed with an excess of material

at the coupling tip that is provided for polishing off so that, once the polishing process has completed, the tapered optical elements **1514** have the desired length. FIG. **16A** schematically illustrates an embodiment of a tapered optical element **1514**, having an up-tapered profile, on the end of a fiber **1504**. In the illustrated embodiment, the tapered optical element **1514** has a pedestal base **1540** printed on the end of the fiber **1504**. The desired length of the tapered optical element is shown as L , whereas the tapered optical element **1514** is fabricated with a length of L' , where $\Delta L = L' - L$ is the excess material **1522** provided for removal during polishing. An embodiment of a tapered optical element **1514** having a down-tapered profile is shown in FIG. **16B**. In some embodiments, when the fibers are drawn inside the ferrule **1508**, for example as illustrated in FIG. **15E**, only the excess material **1522** protrudes beyond the end surface **1512** of the ferrule **1508**, and is available for polishing.

Another embodiment of multi-fiber coupling that implements the use of tapered optical elements on the end of single mode fibers is now described with reference to FIGS. **17A-17E**. This embodiment uses an alignment block **1702**, an embodiment of which is schematically illustrated in plan view in FIG. **17A** and side view in FIG. **17B**. In some embodiments, the alignment block may be formed of a glass, but may also be formed of other materials, such as ceramic or crystalline materials, including crystalline semiconductor materials such as silicon. The alignment block **1702** is provided with alignment grooves **1704** that receive optical fibers. In some embodiments, the alignment grooves **1704** may have a V-shaped profile, although other profile shapes may also be used.

Fibers **1706** are placed in the alignment grooves **1704**, as schematically illustrated in FIG. **17C**. In some embodiments, the fibers **1706** have had their covering **1710** removed to expose the cladding **1712** at their ends, and the cladding **1712** sits in the alignment grooves **1704**. The fibers **1706** are provided with tapered optical elements **1708** at their ends, preferably prior to being installed in the alignment grooves **1704**. In some embodiments the fibers **1706** may be positioned within the alignment grooves **1704** so that the tapered optical elements **1708** slightly overhang the end face **1714** of the alignment block **1702**, as shown in FIG. **17C**, preferably by an amount equal to the length of excess material added at the ends of the tapered optical elements **1708**. In other embodiments, the fibers **1706** may be positioned within the alignment grooves **1704** so that the coupling ends of the tapered optical elements **1708** are flush with the end face **1714** of the alignment block.

A cover **1716** may be placed over the exposed claddings **1712** of the fibers **1706**, as is schematically illustrated in FIG. **17D**. In some embodiments, the cover **1716** is placed over the exposed claddings **1712** after an adhesive has been placed over the claddings and the area of the alignment block **1702**. In other embodiments, the cover **1716** may be placed over the claddings **1712** and then an adhesive is allowed to wick into the alignment grooves **1704**. The adhesive may be any suitable adhesive, such as a low viscous, UV curable adhesive, for example OPTOCAST™ 3553-LV-UTF-HW uv-curable epoxy, available from Electronic Materials Inc., Breckenridge, Colorado, GA700H, available from NTT-Advanced Technology Corp., East Palo Alto, California or NOA 60 available from Norland, Cranbury, New Jersey. The cover **1716** may be formed of any suitable materials, including a glass, ceramic or crystalline material such as a semiconductor crystalline material. In some embodiments, the cover **1716** may be formed of the same material as the alignment block **1702**. The adhesive

may wick into the spaces between the fiber and the alignment block **1702** and the cover **1716**, and thus become a cladding for the tapered optical elements **1708**.

The end face **1714** of the alignment block **1702** may then be polished to ensure that it is flat and to remove any portions of the tapered optical elements **1708** that overhang the end face **1714** of the alignment block **1702**, as is schematically illustrated in FIG. **17E**. Note that a portion of the cover **1716** has been omitted in this figure to show that the coupling tips of the tapered optical elements **1708** are flush with the end face **1714** of the alignment block. In those embodiments where the polishing step removes material from the tapered optical elements **1708**, the tapered optical elements **1708** may have originally been printed with some excess material at their coupling ends, as was discussed above with reference to FIGS. **16A** and **16B**.

In some embodiments, the alignment block **1702** may be positioned adjacent the optical chip **1720** so that the tapered optical element **1708** butt-couple to the waveguides **1722** of the optical chip **1720**. An exemplary embodiment of such a configuration is schematically illustrated in FIG. **17F**, which shows a side view of the alignment block **1702** and optical chip **1720** mounted to a base **1724**. The alignment block **1702** and the optical chip **1720** may be attached to the base **1724** using any suitable method, including adhesive, such as a UV curable adhesive. In some embodiments, the adhesive **1726** may be applied in such a thickness as to achieve vertical alignment of the tapered optical elements **1708** and the chip waveguides **1722** relative to the base **1724**.

Another approach to coupling multiple fibers to an optical chip using tapered optical elements is described with reference to FIGS. **18A-18D**. In this embodiment, fibers **1706** are placed in alignment grooves of the alignment block **1702** and secured in place, for example using an adhesive and/or using a cover **1716**, as is schematically illustrated in FIG. **18A**. The end face **1714** of the alignment block **1702** may then be polished to ensure that the ends of the fibers **1706** are flush with the end **1714**.

Tapered optical elements **1708** may then be printed onto the ends of the fibers **1706**, in a manner like that discussed hereinabove, as is schematically illustrated in FIG. **18B**, so that the tapered optical elements **1708** are overhanging the end face **1714** of the alignment block.

The alignment block **1702** and the optical chip **1720** may then be brought close together, so that the tapered optical elements **1708** align, and are in contact, with the waveguides **1722** of the optical chip **1720**. The gap **1728** between the alignment block **1702** and the chip **1720** may then be filled with an adhesive **1726** and cured so that the alignment block **1702** chip **1720** remain in the same relative position, as shown in FIG. **18C**. An embodiment of a cured device, comprising an alignment block **1702** and optical chip **1720** adhered together on a base **1724**, where the tapered optical elements **1708** overhang the end face **1714** of the alignment block, is schematically illustrated in FIG. **18D**.

Other embodiments of optical elements may be employed in addition to those discussed above. For example, a tapered optical element may be provided with a curved output surface instead of a flat output surface, so that divergence of the light exiting or entering the element is changed. An embodiment of a tapered optical element **1902** having a curved output surface **1904** is schematically illustrated in FIG. **19A**. The tapered optical element **1902** is printed on the end face **1906** of a fiber **1908** that has a core **1910**. The core **1910** and the tapered optical element **1902** may be centered on an axis **1912** of the fiber **1908**. In the illustrated embodiment, the tapered optical element **1902** is up-tapered. The

19

curved output surface **1904** has a center of curvature to the left of the surface **1904**, i.e., has a positive optical power, so that light propagating to the right, out of the tapered optical element **1902**, is converged towards the axis **1912**. The optical power of the curved output surface **1904** may be selected for a particular application. In some embodiments, the curved output surface **1904** may have a negative power. While the illustrated embodiment of tapered optical element **1902** is not shown to include a pedestal base, a pedestal base may be present in some embodiments.

Another embodiment of tapered optical element **1922** having a curved output surface **1924** is schematically illustrated in FIG. **19B**. The tapered optical element **1922** is printed on the end **1926** of a fiber **1928** that has a core **1930**. The core **1930** and the tapered optical element **1922** may be centered on an axis **1932** of the fiber **1928**. In the illustrated embodiment, tapered optical element **1922** is down-tapered. In other embodiments, the optical element **1902** may have sidewalls parallel to the optical axis **1932**.

Another embodiment of tapered optical element **1942** having a curved output surface **1944** is schematically illustrated in FIG. **19C**. In the illustrated embodiment, the tapered optical element **1942** has a thick nonlinear taper. The tapered optical element **1942** is printed on the end **1946** of a fiber **1948** that has a core **1950**. The core **1950** and the tapered optical element **1942** may be centered on an axis **1952** of the fiber **1948**. In the illustrated embodiment, tapered optical element **1942** is up-tapered. In other embodiments, the non-linearly tapered optical element **1942** may be down-tapered.

Some embodiments of printed optical element may include spatial variations in the refractive index. For example, where the printed optical element has a refractive index profile that has a higher refractive index on-axis than off-axis, in other words it has a refractive index gradient in a direction that is perpendicular to its axis, then the printed element may operate as a gradient-index (GRIN) element. One embodiment of a GRIN printed tapered optical element **2002** is schematically illustrated in FIG. **20A**. The tapered optical element **2002**, having tapered sidewalls **2003**, is printed on the end **2006** of a fiber **2008** that has a core **2010**. The core **2010** and the tapered optical element **2002** are centered on an axis **2012** of the fiber **2008**. The tapered optical element **2002** has an output face **2004**, which may be flat, as illustrated, or curved to provide optical power to the light exiting the tapered optical element **2002**. In some embodiments, the tapered optical element **2002** may be provided with a cladding **2014**. In the illustrated embodiment, the tapered optical element **2002** has a linear up-taper. In other embodiments, the tapered element may have a down-taper and the taper may be nonlinear. While the material of the tapered optical element **2002** contains a graded index, the tapered optical element **2002** may operate as a waveguide between its fiber end and the output face **2004**, for light propagating therethrough.

The refractive index of the printed material may be varied by altering the writing speed and/or the writing power. This is described, for example, in Zukauskas A. et al., "Tuning the refractive index in 3D direct laser writing lithography: towards GRIN microoptics," *Laser Photonics Rev.* (2015) **9** 706-712, DOI 10.1002/lpor.201500170, incorporated herein by reference. A greater refractive index is obtained when the degree of conversion (DC, the percentage of carbon double bonds that are consumed during the polymerization process) is higher, which is obtained by exposing the material to more light. Thus, by increasing the DC in those volume elements (voxels) of the tapered optical element **2002** where it is

20

intended that the refractive index be increased, a desired 3D refractive index profile may be obtained in the tapered optical element **2002**.

Another embodiment of a GRIN printed tapered optical element **2022** is schematically illustrated in FIG. **20B**. The tapered optical element **2022**, having tapered sidewalls **2023**, is printed on the end **2026** of a fiber **2028** that has a core **2030**. The core **2030** and the tapered optical element **2022** are centered on an axis **2032** of the fiber **2028**. The tapered optical element **2022** has an output face **2024**, which may be flat, as illustrated, or curved to provide optical power to the light exiting the element **2022**. In some embodiments, the tapered optical element **2022** may be provided with a cladding **2034**. In the illustrated embodiment, the tapered optical element **2022** has a thick nonlinear up-taper. Other embodiments may include a thin nonlinear up-taper, or may include a nonlinear down-taper.

Another embodiment of a GRIN printed tapered optical element **2042** is schematically illustrated in FIG. **20C**. The tapered optical element **2042** is printed on the end **2046** of a fiber **2048** that has a core **2050**. The core **2050** and the printed optical element **2042** are centered on an axis **2052** of the fiber **2048**. The tapered optical element **2042** has an output face **2044**, which may be flat, as illustrated, or curved to provide optical power to the light exiting the element **2042**. In the illustrated embodiment, the divergence of the light exiting the fiber **2048** is controlled by the GRIN properties of the tapered optical element **2042**, rather than being confined by the sidewalls **2054** of the element **2042**. The sidewalls **2054** of the element **2042** may be substantially parallel to the axis **2052**.

The graded index profile may be present throughout the entirety of the tapered optical element **2042** or, as in the illustrated embodiment, the graded index profile may be restricted to that portion of the tapered optical element **2042** which light from the fiber **2048** will pass through. The dashed lines **2056** indicate the expected divergence of the light from the fiber **2048**, and the GRIN material is found between the dashed lines **2056**. Since the slower writing speed associated with voxels of relatively high refractive index increases the length of time required to manufacture the tapered optical element **2042**, this approach reduces the costs of making the element **2042**, as it avoids writing GRIN voxels where the light from the fiber **2048** does not pass through.

The description of the coupling devices is primarily described in terms of optical signals propagating from the fiber to the optical chip. It should be understood that the embodiments of the invention described herein operate for light propagating both from the fiber to the chip and from the chip to the fiber, and there is no intention in the present description to limit the direction in which optical signals propagate through the claimed optical devices, unless otherwise stated.

As noted above, the present invention is applicable to fiber optical communication and data transmission systems. Accordingly, the present invention should not be considered limited to the particular examples described above, but rather should be understood to cover all aspects of the invention as fairly set out in the attached claims.

LIST OF NUMBERED ELEMENTS

- 100** Coupling arrangement
- 102** Tapered optical element
- 104** Fiber
- 106** Fiber core

108 Pedestal base
 110 End facet
 112 Tapered section
 113 Fiber end
 114 Coupling end
 116 Waveguide
 118 Optical chip
 300 Tapered optical element
 302 Coupling end
 304 Fiber end
 400 Tapered optical element
 402 Circular coupling end
 404 Circular fiber end
 410 Tapered optical element
 412 Square coupling end
 414 Circular fiber end
 420 Tapered optical element
 422 Rectangular coupling end
 424 Circular fiber end
 430 Tapered optical element
 432 Coupling end
 434 Circular fiber end
 500 Fiber
 502 Core
 504 Output face
 506 Tapered optical element
 508 Fiber end
 510 Coupling end
 600 Linear taper profile
 602 Nonlinear taper profile
 604 Nonlinear taper profile
 700 Linear taper
 702 Thick nonlinear taper
 704 Thin nonlinear taper
 900 Set up for dip-in laser lithography
 902 Polished end facet
 904 Fiber
 906 Liquid resist
 908 Light
 910 Focusing unit
 912 Focal point
 914 Lens axis
 916 Focal plane
 1102 Curve
 1104 Dot-dashed line
 1106 Sloped line
 1108 Point showing measured MFD
 1200 Set-up
 1202 Light source
 1204 First fiber
 1206 First fiber coupler
 1208 Fiber-coupled polarization controller
 1210 Second fiber coupler
 1212 Fiber
 1214 Translation stage
 1216 PIC
 1218 Translation controller
 1220 Second fiber
 1222 Second translation stage
 1224 Third fiber coupler
 1226 Fiber
 1228 Fiber-coupled power meter
 1250 Set-up
 1302 Curve (circles)
 1304 Curve (diamonds)
 1306 Curve (squares)
 1308 Curve (6-pointed star)

1310 Curve
 1402 Curve
 1404 Curve
 1502 Fiber ribbon cable
 5 1504 Fibers
 1506 Dotted line
 1508 Ferrule
 1510 Ends
 1512 End surface
 10 1514 Tapered optical elements
 1516 Adhesive
 1518 Window
 1519 Multi-fiber coupling device
 1520 Fiber clamp
 15 1522 Excess material
 1530 Chip
 1532 Guide pins
 1540 Pedestal base
 1702 Alignment block
 20 1704 Alignment grooves
 1706 Fibers
 1708 Tapered optical elements
 1710 Covering
 1712 Cladding
 25 1714 End face
 1716 Cover
 1720 Chip
 1722 Waveguides
 1724 Base
 30 1726 Adhesive
 1902 Optical element
 1904 Curved output surface
 1906 End face
 1908 Fiber
 35 1910 Core
 1912 Axis
 1922 Tapered optical element
 1924 Curved output surface
 1926 End
 40 1928 Fiber
 1930 Core
 1932 Axis
 1942 Tapered optical element
 1944 Curved output surface
 45 1946 End
 1948 Fiber
 1950 Core
 1952 Axis
 50 2002 Tapered optical element
 2004 Output face
 2006 End
 2008 Fiber
 2010 Core
 2012 Axis
 55 2014 Cladding
 2022 Tapered optical element
 2024 Output face
 2026 End
 2028 Fiber
 60 2030 Core
 2032 Axis
 2034 Cladding
 2042 Tapered optical element
 2044 Output face
 65 2046 End
 2048 Fiber
 2050 Core

23

2052 Axis
2054 Sidewalls
2056 Dashed lines

What is claimed is:

1. A fiber-coupled optical chip device, comprising
a first optical fiber, the first optical fiber having a first end;
a first down-tapered optical element 3D printed on the
first end of the first optical fiber, the first down-tapered
optical element having a fiber end proximate the first
end of the first optical fiber and a coupling end distal
from the fiber end;
an optical chip having a first waveguide configured for
edge coupling;
wherein the coupling end of the first down-tapered optical
element is aligned with the first waveguide of the
optical chip; and
wherein the fiber end of the first down-tapered optical
element comprises a first cross-sectional shape and the
coupling end of the first down-tapered optical element
comprises a second cross-sectional shape different
from the first cross-sectional shape.
2. The device as recited in claim 1, wherein the first
down-tapered optical element comprises a linear taper pro-
file.
3. The device as recited in claim 1, wherein the first
down-tapered optical element comprises a nonlinear taper
profile.
4. The device as recited in claim 3, wherein the nonlinear
taper profile is a thick nonlinear taper profile.
5. The device as recited in claim 1, wherein the first
cross-sectional shape is circular.
6. The device as recited in claim 5, wherein the second
cross-sectional shape is elliptical.
7. The device as recited in claim 1, wherein the first
down-tapered optical element comprises a base pedestal 3D
printed on the first end of the first optical fiber.
8. The device as recited in claim 1, further comprising a
second optical fiber having a second fiber end, a second
down-tapered optical element 3D printed on the second end
of the second optical fiber, the second down-tapered optical
element having a fiber end proximate the second end of the
second optical fiber and a coupling end distal from the fiber
end;
wherein the optical chip has a second waveguide config-
ured for edge coupling;
wherein the coupling end of the second down-tapered
optical element is aligned with the second waveguide.
9. The device as recited in claim 8, wherein the first end
of the first optical fiber and the second end of the second
optical fiber are aligned with the chip by a multi-fiber
alignment element.

24

10. A fiber optic device, comprising:
an optical fiber having a first end face and a core; and
a tapered optical element 3D printed on the first end face
of the optical fiber, the tapered optical element having
a fiber end and a coupling end, the fiber end of the
tapered optical element being aligned with the core of
the optical fiber;
the fiber end of the tapered optical element having a first
cross-sectional shape and the coupling end of the
tapered optical element having a second cross-sectional
shape different from the first cross-sectional shape.
11. The device as recited in claim 10, wherein the tapered
optical element is a down-tapered optical element.
12. The device as recited in claim 10, wherein the first
cross-sectional shape is circular.
13. The device as recited in claim 10, wherein the second
cross-sectional shape is one of elliptical, rectangular, square
and triangular.
14. The device as recited in claim 10, further comprising
a photonic integrated circuit (PIC) having a first waveguide
terminating proximate an edge of the PIC, the coupling end
of the tapered optical element being aligned with the first
waveguide thereby permitting light to couple between the
first waveguide and the optical fiber.
15. An optical device for coupling an optical signal,
comprising:
an optical fiber having a fiber core and an end face; and
a tapered optical element 3D printed on the end face of the
optical fiber, the tapered optical element having a fiber
end aligned with the fiber core proximate the optical
fiber and a coupling end distal to the optical fiber;
wherein the tapered optical element has an output face at
the coupling end, the output face is curved to alter
divergence of light passing through the output face; and
wherein the tapered optical element acts as a wave-
guide for the optical signal after the optical signal has
propagated into the tapered optical element from the
fiber core.
16. The optical device as recited in claim 15, wherein the
output face is characterized by a positive optical power for
light passing through the output face.
17. The optical device as recited in claim 15, wherein the
waveguiding tapered optical element has a linear taper.
18. The optical device as recited in claim 15, wherein the
waveguiding tapered optical element has a nonlinear taper.
19. The optical device as recited in claim 15, wherein the
waveguiding tapered optical element has a down-taper pro-
file.
20. The optical device as recited in claim 15, further
comprising a waveguide disposed to receive the optical
signal from the tapered optical element.

* * * * *