

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent
Kind Code
Date of Patent
Inventor(s)

12399902
B2
August 26, 2025
Takahashi; Jun et al.

Information display apparatus, information display method, and computer-readable recording medium storing information display program

Abstract

An information display apparatus including: a memory; and a processor coupled to the memory, the processor being configured to perform processing including: analyzing transmission information to extract first analysis information with respect to the transmission information; acquiring, from among a plurality of pieces of second analysis information, second analysis information similar to the first analysis information, the plurality of pieces of second analysis information being obtained by analyzing a plurality of pieces of reliable information; comparing the first analysis information with the acquired second analysis information similar to the first analysis information; and displaying a result of the comparison and the transmission information.

Inventors: Takahashi; Jun (Kawasaki, JP), Zheng; Mingxie (Kawasaki, JP), Yoshitake; Toshiyuki (Kawasaki, JP), Nimura; Kazuaki (Kawasaki, JP)

Applicant: Fujitsu Limited (Kawasaki, JP)

Family ID: 1000008777653

Assignee: Fujitsu Limited (Kawasaki, JP)

Appl. No.: 18/334796

Filed: June 14, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20240104109 A1	Mar. 28, 2024

Foreign Application Priority Data

JP	2022-153332	Sep. 27, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: G06F16/00 (20190101); G06F16/248 (20190101); G06F16/951 (20190101)

U.S. Cl.:

CPC G06F16/248 (20190101); G06F16/951 (20190101);

Field of Classification Search

CPC: G06F (16/248); G06F (21/64)

USPC: 707/600-899

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9582763	12/2016	Myslinski	N/A	N/A
10872100	12/2019	Shefferman et al.	N/A	N/A
11734262	12/2022	Lintilhac	707/703	G06F 16/2379
2002/0198866	12/2001	Kraft et al.	N/A	N/A
2015/0208245	12/2014	Robinton	455/411	H04L 9/3247
2017/0199936	12/2016	Steelberg	N/A	G06F 16/9535
2017/0242865	12/2016	Maita	N/A	G06F 16/951
2017/0262754	12/2016	Mizuno et al.	N/A	N/A
2018/0210821	12/2017	Raghavan	N/A	G06F 11/3684
2019/0349204	12/2018	Enke	N/A	H04L 9/3247

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2017-162050	12/2016	JP	N/A
2020-508518	12/2019	JP	N/A
2012/008503	12/2011	WO	N/A
2018/156641	12/2017	WO	N/A

OTHER PUBLICATIONS

Miriam J. Metzger et al., “Making Sense of Credibility on the Web: Models for Evaluating Online Information and Recommendations for Future Research”, Journal of the American Society for Information Science and Technology., vol. 58, No. 13, Sep. 21, 2007, pp. 2078-2091, XP093129531. cited by applicant

Matthias Quasthoff et al., “Who Reads and Writes the Social Web? A Security Architecture for Web 2.0 Applications”, Internet and Web Applications and Services, 2008. ICIW '08. Third International Conference on, IEEE, Piscataway, NY, USA, Jun. 8, 2009, pp. 576-582, XP031274360. cited by applicant

EESR—Extended European Search Report dated Feb. 28, 2024 for corresponding European Patent Application No. 23179212.8. cited by applicant

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application is based upon and claims the benefit of priority of the prior Japanese Patent Application No. 2022-153332, filed on Sep. 27, 2022, the entire contents of which are incorporated herein by reference.

FIELD

(2) The embodiments discussed herein are related to an information display apparatus and the like.

BACKGROUND

(3) With spread of smartphones and social networking services (SNSs), individuals, organizations, and the like may transmit information to the world anytime and anywhere via the Internet.

(4) On the other hand, many pieces of information that may be acquired via the Internet may not be easily confirmed by a viewer as to whether content of the acquired information is true or false, and erroneous information may be spread. Furthermore, when a plurality of viewers misunderstands the content of the information, social or economic confusion may be induced.

(5) Thus, there is a demand for a mechanism capable of presenting information with which a viewer may confirm reliability of information with respect to the information acquired via the Internet.

(6) For example, there is the following existing technology as a technology for evaluating reliability of information. In the existing technology, reliability of news content is calculated by using current scores set for associated media outlets, associated journalists, and associated predetermined topics for the news content.

(7) Japanese Laid-open Patent Publication No. 2017-162050 and Japanese National Publication of International Patent Application No. 2020-508518 are disclosed as related art.

SUMMARY

(8) According to an aspect of the embodiments, there is provided an information display apparatus including: a memory; and a processor coupled to the memory, the processor being configured to perform processing including: analyzing transmission information to extract first analysis information with respect to the transmission information; acquiring, from among a plurality of pieces of second analysis information, second analysis information similar to the first analysis information, the plurality of pieces of second analysis information being obtained by analyzing a plurality of pieces of reliable information; comparing the first analysis information with the acquired second analysis information similar to the first analysis information; and displaying a result of the comparison and the transmission information.

(9) The object and advantages of the invention will be realized and attained by means of the elements and combinations particularly pointed out in the claims.

(10) It is to be understood that both the foregoing general description and the following detailed description are exemplary and explanatory and are not restrictive of the invention.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a diagram illustrating a configuration example of an information display apparatus according to the present embodiment;

(2) FIG. 2 is a diagram illustrating an example of a data structure of a white list table;

- (3) FIG. 3 is a diagram illustrating an example of a data structure of a public key table;
- (4) FIG. 4 is a diagram illustrating an example of a data structure of a reliable information database (DB);
- (5) FIG. 5 is a diagram illustrating an example of a data structure of a domain table;
- (6) FIG. 6 is a diagram illustrating an example of a data structure of a search condition table;
- (7) FIG. 7 is a diagram for describing processing of a display control unit;
- (8) FIG. 8 is a flowchart (1) illustrating a processing procedure of the information display apparatus according to the present embodiment;
- (9) FIG. 9 is a flowchart illustrating a processing procedure of reliability confirmation processing;
- (10) FIG. 10 is a flowchart (2) illustrating a processing procedure of the information display apparatus according to the present embodiment;
- (11) FIG. 11 is a flowchart illustrating a processing procedure of display processing;
- (12) FIG. 12 is a diagram for describing another embodiment; and
- (13) FIG. 13 is a diagram illustrating an example of a hardware configuration of a computer that implements functions similar to those of the information display apparatus of the embodiment.

DESCRIPTION OF EMBODIMENTS

- (14) However, in the existing technology described above, there is a problem that information for determining reliability of transmitted information may not be presented.
- (15) For example, in the existing technology described above, it is possible to calculate a reliability score for information transmitted from a person, an organization, or the like whose identity is known to some extent, such as a media publishing station, but it is difficult to apply the reliability score to information transmitted from an ordinary individual or anonymously through an SNS.
- (16) In one aspect, an object of an embodiment is to provide an information display apparatus, an information display method, and an information display program capable of presenting information for determining reliability of transmitted information.
- (17) Hereinafter, embodiments of an information display apparatus, an information display method, and an information display program disclosed in the present application will be described in detail with reference to the drawings. Note that the present disclosure is not limited by the embodiments.

EMBODIMENTS

- (18) An information display apparatus according to the present embodiment will be described. The information display apparatus acquires reliable information and analyzes the reliable information in advance. When transmission information transmitted by an anonymous user is acquired, the information display apparatus analyzes the transmission information. The information display apparatus acquires reliable information corresponding to an analysis result similar to an analysis result of the transmission information, and displays a difference portion between the acquired reliable information and the transmission information together with the transmission information. With this configuration, it is possible to present information for determining reliability of transmitted information.
- (19) Subsequently, the information display apparatus according to the present embodiment will be specifically described. FIG. 1 is a diagram illustrating a configuration example of the information display apparatus according to the present embodiment. As illustrated in FIG. 1, the information display apparatus **100** includes a communication unit **110**, an input unit **120**, a display unit **130**, a storage unit **140**, and a control unit **150**.
- (20) The communication unit **110** executes data communication with a server in a network, another external device, or the like. The control unit **150** to be described later exchanges data with the server or the another external device via the communication unit **110**.
- (21) The input unit **120** is an input device that inputs various types of information to the control unit **150** of the information display apparatus **100**. The input unit **120** is a keyboard, a mouse, a touch panel, or the like.
- (22) The display unit **130** is a display device that displays information output from the control unit

- (23) The storage unit **140** includes a white list table **141**, a public key table **142**, a reliable information database (DB) **143**, a domain table **144**, and a search condition table **145**. The storage unit **140** corresponds to a semiconductor memory element such as a random access memory (RAM) or a flash memory, or a storage device such as a hard disk drive (HDD).
- (24) The white list table **141** is a table in which a location of reliable information is registered in advance. FIG. 2 is a diagram illustrating an example of a data structure of the white list table. As illustrated in FIG. 2, the white list table **141** associates a uniform resource locator (URL) with a domain.
- (25) The URL of the white list table **141** indicates a location of reliable information. The domain indicates a domain (genre) of information existing in the URL. For example, FIG. 2 indicates that a domain of information (reliable information) of a URL “https://www.river.zzzz.go.jp/” is “weather information”.
- (26) The public key table **142** is a table indicating availability of a public key for each piece of information with a digital signature. FIG. 3 is a diagram illustrating an example of a data structure of the public key table. As illustrated in FIG. 3, the public key table **142** associates a URL, availability of a public key, and a domain.
- (27) The URL of the public key table **142** indicates a location of information with a digital signature. The availability of a public key indicates whether or not a public key of the corresponding information with a digital signature is in a situation where it may be acquired. In a case where the availability of a public key is “available”, the public key is in a situation where it may be acquired. In a case where the availability of a public key is “unavailable”, the public key is not in a situation where it may be acquired. The domain indicates a domain (genre) of information existing in the URL.
- (28) For example, FIG. 3 indicates that availability of a public key of information of a URL “https://www.data1.com” (information with a digital signature) is “available” and a domain is “weather information”.
- (29) The reliable information DB **143** holds an analysis result of reliable information. FIG. 4 is a diagram illustrating an example of a data structure of the reliable information DB. As illustrated in FIG. 4, the reliable information DB **143** associates an item number with an analysis result. For example, one analysis result is registered for one piece of reliable information. A Key and a Value are set in each analysis result.
- (30) As an example, a data structure of an analysis result (1) is indicated. In the Key, an identifier (ID), an information acquisition time, an information update time, a location, a domain, an event, and a vector are set. In the Value for the Key “ID”, a URL of information to be analyzed (reliable information) is set. In the Value for the Key “information acquisition time”, a time when the information to be analyzed is acquired is set. In the Value for the Key “information update time”, an update time of the information to be analyzed is set.
- (31) In the Value for the Key “location”, a keyword related to a location extracted from a text included in the information to be analyzed (reliable information) is set. In the Value for the Key “event”, a keyword related to an event extracted from a text included in the information to be analyzed (reliable information) is set. In the Value for the Key “vector”, an average value of vectors of the respective words included in a text included in the information to be analyzed (reliable information) is set. The vectors of the respective words are calculated by using a deep learning model or the like subjected to training using an appearance frequency, order, similarity, and the like of the respective words.
- (32) The domain table **144** is used in a case where a domain to which information belongs is determined. FIG. 5 is a diagram illustrating an example of a data structure of the domain table. As illustrated in FIG. 5, the domain table **144** associates a domain with associated keywords. In a case where any of the associated keywords is included in a text of certain information, a domain

corresponding to the associated keyword is allocated. For example, in a case where a text of certain information includes “river”, a domain of such information is “weather information”.

(33) The search condition table **145** is a table in which a search condition in a case where reliable information similar to an analysis result of transmission information is searched for is set. FIG. **6** is a diagram illustrating an example of a data structure of the search condition table. As illustrated in FIG. **6**, the search condition table **145** associates a domain with a search condition. The search condition includes a time search condition, a location search condition, and another search condition. The domain indicates a domain of information to be searched for.

(34) The time search condition is a search condition related to a time. For example, in a case where the time search condition is “error of one day”, it is indicated that a plurality of pieces of reliable information is searched for reliable information in which an error between an information acquisition time of transmission information and an information acquisition time of the reliable information is within one day.

(35) The location search condition is a search condition related to a location. For example, in a case where the location search condition is “same municipality”, it is indicated that a plurality of pieces of reliable information is searched for reliable information in which a location of transmission information and a location of the reliable information are the same municipality.

(36) The another search condition is an another search condition. For example, in a case where the another search condition is “texts are similar”, it is indicated that a plurality of pieces of reliable information is searched for reliable information in which a text of transmission information and a text of the reliable information are similar. For example, it is assumed that, in a case where cosine similarity between a vector of transmission information and a vector of reliable information is equal to or greater than a threshold, a text of the transmission information and a text of the reliable information are similar.

(37) For example, in a case where a domain of transmission information is “weather information” and reliable information similar to such transmission information is searched for, a domain of the reliable information to be searched for is limited to “weather information”. Furthermore, determination as to whether or not there is similarity to the transmission information with the domain “weather information” is executed based on the time search condition “error of one day”, the location search condition “same municipality”, and the another search condition “texts are similar”.

(38) The description returns to FIG. **1**. The control unit **150** includes an acquisition unit **151**, a reliability confirmation unit **152**, a first analysis unit **153**, and a reliable information storage unit **154**. The control unit **150** includes a second analysis unit **155**, a reliable information acquisition unit **156**, a comparison unit **157**, and a display control unit **158**. The control unit **150** is implemented by a central processing unit (CPU), a graphics processing unit (GPU), a hard-wired logic such as an application specific integrated circuit (ASIC) or a field programmable gate array (FPGA), or the like.

(39) The acquisition unit **151** acquires information from the Internet by crawling or the like. In the following description, the information acquired by the acquisition unit **151** is referred to as “acquisition information”. The acquisition unit **151** sets, in the acquisition information, a URL as an acquisition source of the acquisition information, and outputs the acquisition information to the reliability confirmation unit **152**.

(40) The reliability confirmation unit **152** determines whether or not acquisition information is reliable information. For example, in a case where a URL set in the acquisition information matches a URL in the white list table **141**, the reliability confirmation unit **152** determines that the acquisition information is the reliable information. Furthermore, the reliability confirmation unit **152** specifies a domain corresponding to the URL based on the white list table **141**, and associates the specified domain with the reliable information.

(41) In a case where the URL set in the acquisition information does not match the URL in the

white list table **141**, the reliability confirmation unit **152** determines whether or not a digital signature is added to the acquisition information. When the digital signature is added to the acquisition information, the reliability confirmation unit **152** refers to the public key table **142**, and determines that the acquisition information is the reliable information in a case where availability of a public key corresponding to the URL of the acquisition information is “available”. Furthermore, the reliability confirmation unit **152** specifies a domain corresponding to the URL based on the public key table **142**, and associates the specified domain with the reliable information.

(42) The reliability confirmation unit **152** outputs the reliable information to the first analysis unit **153**. In the following description, the reliable information in the acquisition information is simply referred to as “reliable information”.

(43) The first analysis unit **153** generates an analysis result by analyzing reliable information. The analysis result includes the Value for each Key described with reference to FIG. **4**. The first analysis unit **153** outputs the analysis result of the reliable information to the reliable information storage unit **154**.

(44) For example, the first analysis unit **153** executes parsing on the reliable information, and acquires an element corresponding to “Key, Value” among the respective elements of the reliable information (HyperText Markup Language (HTML)/Extensible Markup Language (XML)/JavaScript Object Notation (JSON)). The first analysis unit **153** executes syntax analysis for a text of the element that is “Key, Value”, extracts an information acquisition time, an information update time, a location, a domain, and an event, and sets them in the analysis result. Note that the first analysis unit **153** may use a domain associated with the reliable information (domain set in the reliability confirmation unit **152**) as the Value corresponding to the Key “domain”.

(45) The first analysis unit **153** specifies vectors of a plurality of words included in the text of the element that is “Key, Value”, and calculates an average value of the vectors of the respective words. For example, the first analysis unit **153** may specify the vectors of the respective words included in the text based on dictionary information in which words and vectors of the words are associated. Furthermore, the first analysis unit **153** sets a URL set in the reliable information to the Value corresponding to the Key “ID” of the analysis result.

(46) The first analysis unit **153** repeatedly executes the processing described above for each piece of the reliable information acquired from the reliability confirmation unit **152**, generates each analysis result, and outputs the analysis result to the reliable information storage unit **154**.

(47) The reliable information storage unit **154** stores each analysis result acquired from the first analysis unit **153** in the reliable information DB **143**.

(48) The second analysis unit **155** acquires transmission information transmitted through a social networking service (SNS) or the like, which is transmission information for determining reliability. A user may operate the input unit **120** to specify the transmission information to be acquired. The first analysis unit **153** generates an analysis result by analyzing the transmission information. The analysis result includes the Value for each Key described with reference to FIG. **4**. The second analysis unit **155** outputs the analysis result of the transmission information to the reliable information acquisition unit **156**.

(49) For example, the second analysis unit **155** executes parsing on the transmission information, and acquires an element corresponding to “Key, Value” among the respective elements of the transmission information (HTML/XML/JSON). In a case where the transmission information includes an image, the second analysis unit **155** may perform person detection based on the image.

(50) The second analysis unit **155** executes syntax analysis for a text of the element that is “Key, Value”, extracts an information acquisition time, an information update time, a location, and an event, and sets them in the analysis result.

(51) The second analysis unit **155** specifies vectors of a plurality of words included in the text of

the element that is “Key, Value”, and calculates an average value of the vectors of the respective words. For example, the second analysis unit **155** may specify the vectors of the respective words included in the text based on the dictionary information in which words and vectors of the words are associated. Furthermore, the second analysis unit **155** sets a URL as an acquisition source of the transmission information to the Value corresponding to the Key “ID” of the analysis result.

(52) The second analysis unit **155** compares the words of the text of the element that is “Key, Value” of the transmission information with the associated keywords of the domain table **144**, specifies a domain of the transmission information, and sets the domain in the analysis result.

(53) The reliable information acquisition unit **156** searches the reliable information DB **143** for an analysis result (analysis result of reliable information) similar to an analysis result of transmission information, and outputs the analysis result of the transmission information and the analysis result searched for to the comparison unit **157**. Hereinafter, processing of the reliable information acquisition unit **156** will be specifically described. Hereinafter, for convenience of description, an analysis result of transmission information is referred to as a “first analysis result”, and an analysis result of reliable information is referred to as a “second analysis result”.

(54) The reliable information acquisition unit **156** specifies a search condition corresponding to the domain based on the domain set in the first analysis result and the search condition table **145**. For example, when it is assumed that the domain of the first analysis result is “weather information”, the time search condition is “error of one day”, the location search condition is “same municipality”, and the another search condition is “texts are similar”.

(55) The reliable information acquisition unit **156** searches for a second analysis result whose domain is the same as the domain of the first analysis result and that satisfies all of the time search condition, the location search condition, and the another search condition as a second analysis result similar to the first analysis result. Note that setting may be performed on the reliable information acquisition unit **156** so that it is determined that the second analysis result is similar to the first analysis result when a part of the search conditions is satisfied.

(56) Processing of determining whether or not the “time search condition” is satisfied by the reliable information acquisition unit **156** will be described. Here, description will be made assuming that the time search condition is “error of one day”. In a case where a difference between the Value of the Key “information update time” of the first analysis result and the Value of the Key “information update time” of the second analysis result is less than one day (24 hours), the reliable information acquisition unit **156** determines that the second analysis result satisfies the time search condition.

(57) Processing of determining whether or not the “location search condition” is satisfied by the reliable information acquisition unit **156** will be described. Here, description will be made assuming that the location search condition is “same municipality”. In a case where the Value of the Key “location” of the first analysis result and the Value of the Key “location” of the second analysis result are included in the same municipality, the reliable information acquisition unit **156** determines that the second analysis result satisfies the location search condition. The reliable information acquisition unit **156** may determine whether or not the Value of the Key “location” of the first analysis result and the Value of the Key “location” of the second analysis result are included in the same municipality by using map information or the like in which regions of municipalities and names of locations are set.

(58) Processing of determining whether or not the “another search condition” is satisfied by the reliable information acquisition unit **156** will be described. Here, description will be made assuming that the another search condition is “texts are similar”. In a case where cosine similarity between the Value of the Key “vector” of the first analysis result and the Value of the Key “vector” of the second analysis result is calculated and the cosine similarity is equal to or greater than a threshold, the reliable information acquisition unit **156** determines that the second analysis result satisfies the another search condition.

(59) The reliable information acquisition unit **156** outputs the transmission information, the first analysis result, and a search result to the comparison unit **157**. The search result includes the second analysis result determined to be similar to the first analysis result.

(60) On the other hand, in a case where there is no second analysis result similar to the first analysis result, the reliable information acquisition unit **156** outputs the fact that there is no second analysis result similar to the first analysis result and the transmission information to the display control unit **158**.

(61) The comparison unit **157** compares a first analysis result with a second analysis result included in a search result, and determines whether or not there is a difference portion between the first analysis result and the second analysis result. For example, the comparison unit **157** compares the Values of the Key (for example, event) other than the Key used in a case where the reliable information acquisition unit **156** described above determines whether or not the “time search condition”, the “location search condition”, and the “another search condition” are satisfied.

(62) The comparison unit will be described assuming that the Value of the Key “event” of the first analysis result is “likely to overflow” and the Value of the Key “event” of the second analysis result included in the search result is “water level 1.5 m, no evacuation information”. For example, the Value “likely to overflow” of the Key “event” of the first analysis result is referred to as a first event text, and the Value “water level 1.5 m, no evacuation information” of the Key “event” of the second analysis result included in the search result is referred to as a second event text.

(63) The comparison unit **157** executes morphological analysis on the first event text and the second event text, and divides the first event text and the second event text into morphemes. The comparison unit **157** compares each morpheme of the first event text with each morpheme of the second event text. The comparison unit **157** specifies, as a difference portion, each morpheme that does not match each morpheme of the second event text among the respective morphemes of the first event text. For example, a difference portion based on a comparison result between the Value “likely to overflow” of the Key “event” of the first analysis result and the Value “water level 1.5 m, no evacuation information” of the Key “event” of the second analysis result included in the search result is “likely to overflow”.

(64) The comparison unit **157** executes the processing described above, and in a case where there is no difference portion, outputs the transmission information and first comparison result information to the display control unit **158**. For example, a URL of the second analysis result is set in the first comparison result information.

(65) On the other hand, in a case where there is a difference portion, the comparison unit **157** outputs the transmission information and second comparison result information to the display control unit **158**. For example, the difference portion and the URL of the second analysis result are set in the second comparison result information.

(66) The display control unit **158** causes the display unit **130** to display transmission information and a difference portion in association with each other. FIG. 7 is a diagram for describing processing of the display control unit. In FIG. 7, original transmission information (text of the transmission information) is set as display information **50**.

(67) When acquiring first comparison result information from the comparison unit **157**, the display control unit **158** causes the display unit **130** to display display information **51**. In the display information **51**, an icon **51a** of “associated information exists” is displayed together with a location of transmission information and a text of an event. When the icon **51a** is selected, the display control unit **158** causes a URL of a second analysis result set in the first comparison result information and a text of the second analysis result to be displayed.

(68) When second comparison result information is acquired from the comparison unit **157**, the display control unit **158** causes the display unit **130** to display display information **52**. In the display information **52**, a difference portion between the location of the transmission information and the text of the event is highlighted. In a case where the highlighted difference portion is

selected by a user, the display control unit **158** may cause the URL of the second analysis result and the text of the second analysis result to be displayed together.

(69) When the fact that there is no second analysis result similar to the first analysis result and the transmission information are acquired from the reliable information acquisition unit **156**, the display control unit **158** causes the display unit **130** to display display information **53**. The display control unit **158** may cause the fact that there is no associated information to be displayed together with the display information **53**.

(70) Next, an example of a processing procedure of the information display apparatus **100** according to the present embodiment will be described. FIG. **8** is a flowchart (1) illustrating the processing procedure of the information display apparatus according to the present embodiment. As illustrated in FIG. **8**, the acquisition unit **151** of the information display apparatus **100** executes crawling to acquire information (Step **S101**). The reliability confirmation unit **152** of the information display apparatus **100** executes reliability confirmation processing (Step **S102**).

(71) The first analysis unit **153** of the information display apparatus **100** executes parsing for reliable information (Step **S103**). The first analysis unit **153** executes syntax analysis for a text (Step **S104**). The first analysis unit **153** calculates an average value of vectors of the respective words included in the text (Step **S105**).

(72) The reliable information storage unit **154** of the information display apparatus **100** stores an analysis result of the reliable information in the reliable information DB **143** (Step **S106**).

(73) Here, an example of a processing procedure of the reliability confirmation processing described in Step **S102** in FIG. **8** will be described. FIG. **9** is a flowchart illustrating the processing procedure of the reliability confirmation processing. As illustrated in FIG. **9**, the reliability confirmation unit **152** of the information display apparatus **100** determines whether or not a URL of the acquisition information matches a URL of the white list table **141** (Step **S201**).

(74) In a case where the URL of the acquisition information matches the URL of the white list table **141** (Step **S202**, Yes), the reliability confirmation unit **152** determines that the acquisition information is reliable information (Step **S203**).

(75) On the other hand, in a case where the URL of the acquisition information does not match the URL of the white list table **141** (Step **S202**, No), the reliability confirmation unit **152** determines whether or not a digital signature is added to the acquisition information (Step **S204**).

(76) In a case where the digital signature is not added (Step **S205**, No), the reliability confirmation unit **152** determines that the acquisition information is not reliable information (Step **S206**).

(77) On the other hand, in a case where the digital signature is added (Step **S205**, Yes), the reliability confirmation unit **152** determines whether or not availability of a public key corresponding to the URL of the acquisition information is “available” based on the public key table **142** (Step **S207**).

(78) In a case where the availability is not “available” (Step **S208**, No), the reliability confirmation unit **152** proceeds to Step **S206**. On the other hand, in a case where the availability is “available” (Step **S208**, Yes), the reliability confirmation unit **152** proceeds to Step **S203**.

(79) FIG. **10** is a flowchart (2) illustrating the processing procedure of the information display apparatus according to the present embodiment. The second analysis unit **155** of the information display apparatus **100** acquires transmission information (Step **S301**). The second analysis unit **155** executes parsing for the transmission information (Step **S302**).

(80) The second analysis unit **155** executes person detection in a case where the transmission information includes an image (Step **S303**). The second analysis unit **155** executes syntax analysis for a text (Step **S304**). The second analysis unit **155** calculates an average value of vectors of the respective words included in the text (Step **S305**). The second analysis unit **155** estimates a domain of the transmission information based on the domain table **144** (Step **S306**).

(81) The reliable information acquisition unit **156** specifies a search condition corresponding to the domain of the transmission information based on the search condition table **145** (Step **S307**). The

reliable information acquisition unit **156** searches the reliable information DB **143** for an analysis result similar to an analysis result of the transmission information based on the search condition (Step **S308**).

(82) The comparison unit **157** of the information display apparatus **100** compares the analysis result of the transmission information with the analysis result searched for from the reliable information DB **143** (Step **S309**). The display control unit **158** of the information display apparatus **100** executes display processing (Step **S310**).

(83) Here, an example of a processing procedure of the display processing described in Step **S310** in FIG. **10** will be described (Step **S310**). FIG. **11** is a flowchart illustrating the processing procedure of the display processing. As illustrated in FIG. **11**, the display control unit **158** of the information display apparatus **100** determines whether or not the analysis result similar to the analysis result of the transmission information has been searched for (Step **S401**).

(84) In a case where the similar analysis result has not been searched for (Step **S402**, No), the display control unit **158** causes the display unit **130** to display information indicating that there is no reliable information (Step **S403**). For example, in Step **S403**, the display control unit **158** causes the display unit **130** to display the display information **53** in FIG. **7**.

(85) On the other hand, in a case where the similar analysis result has been searched for (Step **S402**, Yes), the display control unit **158** determines whether or not there is a difference portion between the analysis result of the transmission information and the analysis result searched for (Step **S404**).

(86) In a case where there is the difference portion between the analysis result of the transmission information and the analysis result searched for (Step **S405**, Yes), the display control unit **158** causes the display unit **130** to display the transmission information and the difference portion (Step **S406**). For example, in Step **S406**, the display control unit **158** causes the display unit **130** to display the display information **52** in FIG. **7**.

(87) In a case where there is no difference portion between the analysis result of the transmission information and the retrieved analysis result (Step **S405**, No), the display control unit **158** causes the display unit **130** to display the transmission information and reliable information (Step **S407**). For example, in Step **S407**, the display control unit **158** causes the display unit **130** to display the display information **51** in FIG. **7**.

(88) Next, effects of the information display apparatus **100** according to the present embodiment will be described. The information display apparatus **100** acquires reliable information and analyzes the reliable information in advance. When transmission information transmitted by an anonymous user is acquired, the information display apparatus **100** analyzes the transmission information. The information display apparatus **100** acquires reliable information corresponding to an analysis result similar to an analysis result of the transmission information, and displays a difference portion between the acquired reliable information and the transmission information together with the transmission information. With this configuration, it is possible to present information for determining reliability of the transmission information.

(89) In a case where a URL of acquisition information is set in the white list table **141**, the information display apparatus **100** determines that the acquisition information is the reliable information. Furthermore, in a case where a digital signature is added to acquisition information and a public key may be acquired, the information display apparatus **100** determines that the acquisition information is the reliable information. With this configuration, the reliable information may be appropriately acquired.

(90) The information display apparatus **100** displays transmission information and a text of an analysis result of reliable information similar to an analysis result of the transmission information. With this configuration, it is possible to confirm a basis that the transmission information is reliable information.

(91) The information display apparatus **100** analyzes reliable information, and extracts an

information acquisition time, an information update time, a location, a domain, and an event as an analysis result. The information display apparatus **100** analyzes transmission information, and extracts an information acquisition time, an information update time, a location, a domain, and an event as an analysis result. With this configuration, it is possible to determine whether or not the analysis result of the transmission information is similar to the analysis result of the reliable information.

(92) Incidentally, the embodiment of the information display apparatus **100** described above is an example. For example, the information display apparatus **100** may communicate with a client and receive transmission information from the client. When the transmission information is received from the client, the information display apparatus **100** analyzes the transmission information. The information display apparatus **100** acquires reliable information corresponding to an analysis result similar to an analysis result of the transmission information, and causes the client to display a difference portion between the acquired reliable information and the transmission information together with the transmission information. With this configuration, it is possible to present information for determining reliability of the transmitted information with minimum functions of the client.

(93) FIG. **12** is a diagram for describing another embodiment. As illustrated in FIG. **12**, an information display apparatus **100** is coupled to a client **60**. The client **60** includes a reception unit **61**, a request transmission unit **62**, a comparison result reception unit **63**, and a display control unit **64**.

(94) The reception unit **61** receives transmission information transmitted through an SNS or the like, which is transmission information for determining reliability. The reception unit **61** outputs the transmission information to the request transmission unit **62**.

(95) The request transmission unit **62** transmits a request for transmission information to the information display apparatus **100**.

(96) The information display apparatus **100** executes transmission and reception of data to and from the client **60** via a communication unit **110**. In the information display apparatus **100**, when a request for transmission information is received from the client **60**, a second analysis unit **155**, a reliable information acquisition unit **156**, and a comparison unit **157** execute the processing described above, and transmit a comparison result to the client **60**.

(97) The comparison result reception unit **63** outputs, when a comparison result is received from the information display apparatus **100**, the comparison result to the display control unit **64**.

(98) The display control unit **64** executes processing corresponding to the display control unit **158** of the information display apparatus **100**. For example, the display control unit **64** causes a display unit of the client to display transmission information and a difference portion in association with each other.

(99) Next, an example of a hardware configuration of a computer that implements functions similar to those of the information display apparatus **100** described above will be described. FIG. **13** is a diagram illustrating an example of the hardware configuration of the computer that implements the functions similar to those of the information display apparatus of the embodiment.

(100) As illustrated in FIG. **13**, a computer **200** includes a CPU **201** that executes various types of arithmetic processing, an input device **202** that receives data input from a user, and a display **203**. Furthermore, the computer **200** includes a communication device **204** that exchanges data with an external device or the like via a wired or wireless network, and an interface device **205**.

Furthermore, the computer **200** includes a RAM **206** that temporarily stores various types of information, and a hard disk device **207**. Additionally, each of the devices **201** to **207** is coupled to a bus **208**.

(101) The hard disk device **207** includes an acquisition program **207a**, a reliability confirmation program **207b**, a first analysis program **207c**, and a reliable information storage program **207d**. The hard disk device **207** includes a second analysis program **207e**, a reliable information acquisition

program **207f**, a comparison program **207g**, and a display control program **207h**. Furthermore, the CPU **201** reads each of the programs **207a** to **207h** and develops the programs to the RAM **206**. (102) The acquisition program **207a** functions as an acquisition process **206a**. The reliability confirmation program **207b** functions as a reliability confirmation process **206b**. The first analysis program **207c** functions as a first analysis process **206c**. The reliable information storage program **207d** functions as a reliable information storage process **206d**. The second analysis program **207e** functions as a second analysis process **206e**. The reliable information acquisition program **207f** functions as a reliable information acquisition process **206f**. The comparison program **207g** functions as a comparison process **206g**. The display control program **207h** functions as a display control process **206h**.

(103) Processing of the acquisition process **206a** corresponds to the processing of the acquisition unit **151**. Processing of the reliability confirmation process **206b** corresponds to the processing of the reliability confirmation unit **152**. Processing of the first analysis process **206c** corresponds to the processing of the first analysis unit **153**. Processing of the reliable information storage process **206d** corresponds to the processing of the reliable information storage unit **154**. Processing of the second analysis process **206e** corresponds to the processing of the second analysis unit **155**. Processing of the reliable information acquisition process **206f** corresponds to the processing of the reliable information acquisition unit **156**. Processing of the comparison process **206g** corresponds to the processing of the comparison unit **157**. Processing of the display control process **206h** corresponds to the processing of the display control unit **158**.

(104) Note that each of the programs **207a** to **207h** does not necessarily have to be stored in the hard disk device **207** from the beginning. For example, each of the programs is stored in a “portable physical medium” to be inserted into the computer **200**, such as a flexible disk (FD), a compact disc read only memory (CD-ROM), a digital versatile disc (DVD), a magneto-optical disk, or an integrated circuit (IC) card. Then, the computer **200** may read and execute each of the programs **207a** to **207h**.

(105) All examples and conditional language provided herein are intended for the pedagogical purposes of aiding the reader in understanding the invention and the concepts contributed by the inventor to further the art, and are not to be construed as limitations to such specifically recited examples and conditions, nor does the organization of such examples in the specification relate to a showing of the superiority and inferiority of the invention. Although one or more embodiments of the present invention have been described in detail, it should be understood that the various changes, substitutions, and alterations could be made hereto without departing from the spirit and scope of the invention.

Claims

1. An information display apparatus comprising: a memory; and a processor coupled to the memory, the processor being configured to perform processing including: analyzing transmission information to extract first analysis information with respect to the transmission information, the first analysis information including a domain of the transmission information determined by comparing keywords extracted from the transmission information with a plurality of predefined associated keywords stored in a domain table, each set of associated keywords being associated with a respective domain; acquiring, from among a plurality of pieces of second analysis information, second analysis information similar to the first analysis information, the plurality of pieces of second analysis information being obtained by analyzing a plurality of pieces of reliable information, each of the plurality of pieces of reliable information being information that has been confirmed in advance to have a content considered to be reliable; comparing the first analysis information with the acquired second analysis information similar to the first analysis information; and displaying a result of the comparison and the transmission information, wherein the acquiring

of the second analysis information includes specifying, from among a plurality of search conditions stored in a search condition table, a search condition corresponding to the domain included in the first analysis information, the search condition table being a table configured to store, for each domain of a plurality of domain, at least one or more search conditions among the plurality of search conditions in association with the each domain, the plurality of search conditions including at least a time search condition and a location search condition, each of the plurality of search conditions being a respective condition to be compared to each of the plurality of pieces of second analysis information in determining whether the each of the plurality of pieces of second analysis information is satisfied with the respective condition, and searching for, using the specified search condition, from among the plurality of pieces of second analysis information, at least one piece of second analysis information that is associated with the domain included in the first analysis information and that satisfies the specified search condition.

2. The information display apparatus according to claim 1, the processing further comprising: acquiring, as the reliable information, information acquired from a location registered in advance and information to which a digital signature is added.

3. The information display apparatus according to claim 2, wherein the displaying includes displaying a difference portion between the first analysis information and the second analysis information similar to the first analysis information, and the transmission information.

4. The information display apparatus according to claim 1, wherein the analyzing of the transmission information includes analyzing the transmission information to extract, as the first analysis information, a time when the transmission information is transmitted, a location included in a text of the transmission information, or an event included in the text included in the transmission information, or any combination of the time, the location, or the event, and the acquiring includes extracting, as the second analysis information, a time when the reliable information is transmitted, a location included in a text of the reliable information, or an event included in the text, or any combination of the time, the location, or the event by analyzing the reliable information.

5. The information display apparatus according to claim 3, wherein each second analysis information of the plurality of pieces of second analysis information includes at least a location and an event, both of the location and the event being extracted from at least any one of the plurality of pieces of reliable information, and the displaying includes displaying: the transmission information; and the location and the event included in the acquired second analysis information.

6. The information display apparatus according to claim 1, wherein the analyzing of the transmission information includes extracting first analysis information of transmission information by analyzing the transmission information received from a client, and transmitting, to the client, a comparison result between the first analysis information and second analysis information similar to the first analysis information.

7. An information display method implemented by a computer, the information display method comprising: analyzing transmission information to extract first analysis information with respect to the transmission information, the first analysis information including a domain of the transmission information determined by comparing keywords extracted from the transmission information with a plurality of predefined associated keywords stored in a domain table, each set of associated keywords being associated with a respective domain; acquiring, from among a plurality of pieces of second analysis information, second analysis information similar to the first analysis information, the plurality of pieces of second analysis information being obtained by analyzing a plurality of pieces of reliable information, each of the plurality of pieces of reliable information being information that has been confirmed in advance to have a content considered to be reliable; comparing the first analysis information with the acquired second analysis information similar to the first analysis information; and displaying a result of the comparison and the transmission information, wherein the acquiring of the second analysis information includes specifying, from

among a plurality of search conditions stored in a search condition table, a search condition corresponding to the domain included in the first analysis information, the search condition table being a table configured to store, for each domain of a plurality of domain, at least one or more search conditions among the plurality of search conditions in association with the each domain, the plurality of search conditions including at least a time search condition and a location search condition, and another search condition, each of the plurality of search conditions being a respective condition to be compared to each of the plurality of pieces of second analysis information in determining whether the each of the plurality of pieces of second analysis information is satisfied with the respective condition, and searching for, using the specified search condition, from among the plurality of pieces of second analysis information, at least one piece of second analysis information that is associated with the domain included in the first analysis information and that satisfies the specified search condition.

8. A non-transitory computer-readable recording medium storing an information display program for causing a computer to perform processing including: analyzing transmission information to extract first analysis information with respect to the transmission information, the first analysis information including a domain of the transmission information determined by comparing keywords extracted from the transmission information with a plurality of predefined associated keywords stored in a domain table, each set of associated keywords being associated with a respective domain; acquiring, from among a plurality of pieces of second analysis information, second analysis information similar to the first analysis information, the plurality of pieces of second analysis information being obtained by analyzing a plurality of pieces of reliable information, each of the plurality of pieces of reliable information being information that has been confirmed in advance to have a content considered to be reliable; comparing the first analysis information with the acquired second analysis information similar to the first analysis information; and displaying a result of the comparison and the transmission information, wherein the acquiring of the second analysis information includes specifying, from among a plurality of search conditions stored in a search condition table, a search condition corresponding to the domain included in the first analysis information, the search condition table being a table configured to store, for each domain of a plurality of domain, at least one or more search conditions among the plurality of search conditions in association with the each domain, the plurality of search conditions including a time search condition, a location search condition, and another search condition, each of the plurality of search conditions being a respective condition to be compared to each of the plurality of pieces of second analysis information in determining whether the each of the plurality of pieces of second analysis information is satisfied with the respective condition, and searching for, using the specified search condition, from among the plurality of pieces of second analysis information, at least one piece of second analysis information that is associated with the domain included in the first analysis information and that satisfies the specified search condition.
