

(12) **United States Patent**
Thanickel

(10) **Patent No.:** **US 12,401,525 B2**
(45) **Date of Patent:** **Aug. 26, 2025**

(54) **VEHICLE TEMPORARY CERTIFICATE AUTHENTICATION**
(71) Applicant: **TOYOTA MOTOR NORTH AMERICA, INC.**, Plano, TX (US)
(72) Inventor: **Ismail Thanickel**, Frisco, TX (US)
(73) Assignees: **TOYOTA MOTOR NORTH AMERICA, INC.**, Plano, TX (US); **TOYOTA JIDOSHA KABUSHIKI KAISHA**, Aichi (JP)

(*) Notice: Subject to any disclaimer, the term of this patent is extended or adjusted under 35 U.S.C. 154(b) by 287 days.

(21) Appl. No.: **17/952,195**

(22) Filed: **Sep. 23, 2022**

(65) **Prior Publication Data**
US 2024/0106663 A1 Mar. 28, 2024

(51) **Int. Cl.**
H04L 9/32 (2006.01)
H04L 12/40 (2006.01)
(52) **U.S. Cl.**
CPC **H04L 9/3268** (2013.01); **H04L 12/40006** (2013.01); **H04L 2012/40273** (2013.01)
(58) **Field of Classification Search**
CPC H04L 9/3268; H04L 12/40006; H04L 2012/40273
See application file for complete search history.

(56) **References Cited**
U.S. PATENT DOCUMENTS

6,233,341 B1 * 5/2001 Riggins H04L 63/0823 713/175
7,868,736 B2 1/2011 Fukushima et al.

9,361,452 B2 6/2016 Saint
9,678,896 B2 6/2017 O'Loughlin et al.
9,953,167 B2 4/2018 Wooten et al.
10,021,100 B2 7/2018 Ellingson et al.
10,333,720 B2 6/2019 Kravitz et al.
10,530,586 B2 * 1/2020 Meriac H04W 12/0431
10,911,245 B2 2/2021 Pottier et al.
10,943,005 B2 3/2021 Chen
2008/0022104 A1 * 1/2008 Deishi H04L 63/0823 713/171
2008/0232595 A1 * 9/2008 Pietrowicz H04L 9/3297 380/277
2009/0254750 A1 * 10/2009 Bono H04L 63/065 380/282
2010/0315197 A1 * 12/2010 Solomon G06F 21/31 340/5.2
2011/0202760 A1 * 8/2011 Hahn H04W 12/062 713/162
2012/0049785 A1 * 3/2012 Tanaka B60L 53/305 320/106
2012/0183266 A1 * 7/2012 Wiley G02B 6/2551 385/96

(Continued)

FOREIGN PATENT DOCUMENTS


CN 108833445 B 4/2021
KR 102390745 B1 4/2022

Primary Examiner — Shewaye Gelagay
Assistant Examiner — Thomas A Carnes

(57) **ABSTRACT**

An example operation includes one or more of obtaining, by a server, a certificate from an IoT device associated with a vehicle, determining, by the server, the certificate is not a revoked certificate, assigning, by the server, a temporary certificate to the IoT device, and validating, by the server, the temporary certificate.

15 Claims, 27 Drawing Sheets



(56)

References Cited

U.S. PATENT DOCUMENTS

2015/0256534	A1 *	9/2015	Goudy	H04W 12/033 713/156
2017/0063842	A1 *	3/2017	Ahn	H04L 63/123
2017/0118025	A1	4/2017	Shastri et al.	
2018/0012433	A1	1/2018	Ricci	
2018/0241739	A1 *	8/2018	Takazoe	G06F 21/44
2019/0245703	A1 *	8/2019	Simplicio Junior, Jr.	H04L 9/3268
2019/0289012	A1	9/2019	Kandel et al.	
2019/0386986	A1	12/2019	O'Brien et al.	
2020/0101367	A1	4/2020	Tran et al.	
2020/0280842	A1	9/2020	Liu et al.	
2022/0167166	A1 *	5/2022	Je	H04L 63/0823
2022/0406109	A1 *	12/2022	Hsu	G01S 13/825
2023/0188361	A1 *	6/2023	Misuraca	H04L 63/0428 713/158

* cited by examiner


100

FIG. 1A




FIG. 1B


200

FIG. 2A

210




FIG. 2B

240




FIG. 2C


250

FIG. 2D




FIG. 2E


265

FIG. 2F




FIG. 2G

290




FIG. 2H

290A




FIG. 2I


290B

FIG. 2J

290C




FIG. 2K


290D

FIG. 2L

290E




FIG. 2M

290E




FIG. 2N


300

FIG. 3A


320

FIG. 3B


340

FIG. 3C




FIG. 4

500




FIG. 5A

550




FIG. 5B


600

FIG. 6A


640

FIG. 6B



660

FIG. 6C




700

FIG. 7

1

VEHICLE TEMPORARY CERTIFICATE AUTHENTICATION

BACKGROUND

Vehicles or transports, such as cars, motorcycles, trucks, planes, trains, etc., generally provide transportation needs to occupants and/or goods in a variety of ways. Functions related to transports may be identified and utilized by various computing devices, such as a smartphone or a computer located on and/or off the transport.

SUMMARY

One example embodiment provides a method that includes one or more of obtaining, by a server, a certificate from an IoT device associated with a vehicle, determining, by the server, the certificate is not a revoked certificate, assigning, by the server, a temporary certificate to the IoT device, and validating, by the server, the temporary certificate.

Another example embodiment provides a system that includes a memory communicably coupled to a processor, wherein the processor performs one or more of obtain, by a server, a certificate from an IoT device associated with a vehicle, determine, by the server, the certificate is not a revoked certificate, assign, by the server, a temporary certificate to the IoT device, and validate, by the server, the temporary certificate.

A further example embodiment provides a computer readable storage medium comprising instructions, that when read by a processor, cause the processor to perform one or more of obtaining, by a server, a certificate from an IoT device associated with a vehicle, determining, by the server, the certificate is not a revoked certificate, assigning, by the server, a temporary certificate to the IoT device, and validating, by the server, the temporary certificate.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1A illustrates a network diagram of a vehicle temporary certificate authentication system, according to example embodiments.

FIG. 1B illustrates an example diagram of a vehicle temporary certificate authentication system, according to example embodiments.

FIG. 2A illustrates a transport network diagram, according to example embodiments.

FIG. 2B illustrates another transport network diagram, according to example embodiments.

FIG. 2C illustrates yet another transport network diagram, according to example embodiments.

FIG. 2D illustrates a further transport network diagram, according to example embodiments.

FIG. 2E illustrates yet a further transport network diagram, according to example embodiments.

FIG. 2F illustrates a diagram depicting electrification of one or more elements, according to example embodiments.

FIG. 2G illustrates a diagram depicting interconnections between different elements, according to example embodiments.

FIG. 2H illustrates a further diagram depicting interconnections between different elements, according to example embodiments.

FIG. 2I illustrates yet a further diagram depicting interconnections between elements, according to example embodiments.

2

FIG. 2J illustrates yet a further diagram depicting a keyless entry system, according to example embodiments.

FIG. 2K illustrates yet a further diagram depicting a CAN within a transport, according to example embodiments.

FIG. 2L illustrates yet a further diagram depicting an end-to-end communication channel, according to example embodiments.

FIG. 2M illustrates yet a further diagram depicting an example of transports performing secured V2V communications using security certificates, according to example embodiments.

FIG. 2N illustrates yet a further diagram depicting an example of a transport interacting with a security processor and a wireless device, according to example embodiments.

FIG. 3A illustrates a flow diagram, according to example embodiments.

FIG. 3B illustrates another flow diagram, according to example embodiments.

FIG. 3C illustrates yet another flow diagram, according to example embodiments.

FIG. 4 illustrates a machine learning transport network diagram, according to example embodiments.

FIG. 5A illustrates an example vehicle configuration for managing database transactions associated with a vehicle, according to example embodiments.

FIG. 5B illustrates another example vehicle configuration for managing database transactions conducted among various vehicles, according to example embodiments.

FIG. 6A illustrates a blockchain architecture configuration, according to example embodiments.

FIG. 6B illustrates another blockchain configuration, according to example embodiments.

FIG. 6C illustrates a blockchain configuration for storing blockchain transaction data, according to example embodiments.

FIG. 6D illustrates example data blocks, according to example embodiments.

FIG. 7 illustrates an example system that supports one or more of the example embodiments.

DETAILED DESCRIPTION

It will be readily understood that the instant components, as generally described and illustrated in the figures herein, may be arranged and designed in a wide variety of different configurations. Thus, the following detailed description of the embodiments of at least one of a method, apparatus, computer readable storage medium and system, as represented in the attached figures, is not intended to limit the scope of the application as claimed but is merely representative of selected embodiments. Multiple embodiments depicted herein are not intended to limit the scope of the solution. The computer-readable storage medium may be a non-transitory computer readable medium or a non-transitory computer readable storage medium.

Communications between the transport(s) and certain entities, such as remote servers, other transports and local computing devices (e.g., smartphones, personal computers, transport-embedded computers, etc.) may be sent and/or received and processed by one or more 'components' which may be hardware, firmware, software or a combination thereof. The components may be part of any of these entities or computing devices or certain other computing devices. In one example, consensus decisions related to blockchain transactions may be performed by one or more computing devices or components (which may be any element described and/or depicted herein) associated with the trans-

port(s) and one or more of the components outside or at a remote location from the transport(s).

The instant features, structures, or characteristics described in this specification may be combined in any suitable manner in one or more embodiments. For example, the usage of the phrases “example embodiments,” “some embodiments,” or other similar language, throughout this specification refers to the fact that a particular feature, structure, or characteristic described in connection with the embodiment may be included in at least one example. Thus, appearances of the phrases “example embodiments,” “in some embodiments,” “in other embodiments,” or other similar language, throughout this specification do not necessarily all refer to the same group of embodiments, and the described features, structures, or characteristics may be combined in any suitable manner in one or more embodiments. In the diagrams, any connection between elements can permit one-way and/or two-way communication, even if the depicted connection is a one-way or two-way arrow. In the current solution, a vehicle or transport may include one or more of cars, trucks, walking area battery electric vehicle (BEV), e-Palette, fuel cell bus, motorcycles, scooters, bicycles, boats, recreational vehicles, planes, and any object that may be used to transport people and/or goods from one location to another.

In addition, while the term “message” may have been used in the description of embodiments, other types of network data, such as, a packet, frame, datagram, etc. may also be used. Furthermore, while certain types of messages and signaling may be depicted in exemplary embodiments they are not limited to a certain type of message and signaling.

Example embodiments provide methods, systems, components, non-transitory computer readable medium, devices, and/or networks, which provide at least one of a transport (also referred to as a vehicle or car herein), a data collection system, a data monitoring system, a verification system, an authorization system, and a vehicle data distribution system. The vehicle status condition data received in the form of communication messages, such as wireless data network communications and/or wired communication messages, may be processed to identify vehicle/transport status conditions and provide feedback on the condition and/or changes of a transport. In one example, a user profile may be applied to a particular transport/vehicle to authorize a current vehicle event, service stops at service stations, to authorize subsequent vehicle rental services, and enable vehicle-to-vehicle communications.

Within the communication infrastructure, a decentralized database is a distributed storage system which includes multiple nodes that communicate with each other. A blockchain is an example of a decentralized database, which includes an append-only immutable data structure (i.e., a distributed ledger) capable of maintaining records between untrusted parties. The untrusted parties are referred to herein as peers, nodes, or peer nodes. Each peer maintains a copy of the database records, and no single peer can modify the database records without a consensus being reached among the distributed peers. For example, the peers may execute a consensus protocol to validate blockchain storage entries, group the storage entries into blocks, and build a hash chain via the blocks. This process forms the ledger by ordering the storage entries, as is necessary, for consistency. In public or permissionless blockchains, anyone can participate without a specific identity. Public blockchains can involve cryptocurrencies and use consensus-based on various protocols such as proof of work (PoW). Conversely, a permissioned

blockchain database can secure interactions among a group of entities, which share a common goal, but which do not or cannot fully trust one another, such as businesses that exchange funds, goods, information, and the like. The instant solution can function in a permissioned and/or a permissionless blockchain setting.

Smart contracts are trusted distributed applications which leverage tamper-proof properties of the shared or distributed ledger (which may be in the form of a blockchain) and an underlying agreement between member nodes, which is referred to as an endorsement or endorsement policy. In general, blockchain entries are “endorsed” before being committed to the blockchain while entries, which are not endorsed are disregarded. A typical endorsement policy allows smart contract executable code to specify endorser for an entry in the form of a set of peer nodes that are necessary for endorsement. When a client sends the entry to the peers specified in the endorsement policy, the entry is executed to validate the entry. After validation, the entries enter an ordering phase in which a consensus protocol produces an ordered sequence of endorsed entries grouped into blocks.

Nodes are the communication entities of the blockchain system. A “node” may perform a logical function in the sense that multiple nodes of different types can run on the same physical server. Nodes are grouped in trust domains and are associated with logical entities that control them in various ways. Nodes may include different types, such as a client or submitting-client node, which submits an entry-invocation to an endorser (e.g., peer), and broadcasts entry proposals to an ordering service (e.g., ordering node). Another type of node is a peer node, which can receive client submitted entries, commit the entries and maintain a state and a copy of the ledger of blockchain entries. Peers can also have the role of an endorser. An ordering-service-node or orderer is a node running the communication service for all nodes and which implements a delivery guarantee, such as a broadcast to each of the peer nodes in the system when committing entries and modifying a world state of the blockchain. The world state can constitute the initial blockchain entry, which normally includes control and setup information.

A ledger is a sequenced, tamper-resistant record of all state transitions of a blockchain. State transitions may result from smart contract executable code invocations (i.e., entries) submitted by participating parties (e.g., client nodes, ordering nodes, endorser nodes, peer nodes, etc.). An entry may result in a set of asset key-value pairs being committed to the ledger as one or more operands, such as creates, updates, deletes, and the like. The ledger includes a blockchain (also referred to as a chain), which stores an immutable, sequenced record in blocks. The ledger also includes a state database, which maintains a current state of the blockchain. There is typically one ledger per channel. Each peer node maintains a copy of the ledger for each channel of which they are a member.

A chain is an entry log structured as hash-linked blocks, and each block contains a sequence of N entries where N is equal to or greater than one. The block header includes a hash of the blocks’ entries, as well as a hash of the prior block’s header. In this way, all entries on the ledger may be sequenced and cryptographically linked together. Accordingly, it is not possible to tamper with the ledger data without breaking the hash links. A hash of a most recently added blockchain block represents every entry on the chain that has come before it, making it possible to ensure that all peer nodes are in a consistent and trusted state. The chain may be

stored on a peer node file system (i.e., local, attached storage, cloud, etc.), efficiently supporting the append-only nature of the blockchain workload.

The current state of the immutable ledger represents the latest values for all keys that are included in the chain entry log. Since the current state represents the latest key values known to a channel, it is sometimes referred to as a world state. Smart contract executable code invocations execute entries against the current state data of the ledger. To make these smart contract executable code interactions efficient, the latest values of the keys may be stored in a state database. The state database may be simply an indexed view into the chain's entry log and can therefore be regenerated from the chain at any time. The state database may automatically be recovered (or generated if needed) upon peer node startup and before entries are accepted.

A blockchain is different from a traditional database in that the blockchain is not a central storage but rather a decentralized, immutable, and secure storage, where nodes must share in changes to records in the storage. Some properties that are inherent in blockchain and which help implement the blockchain include, but are not limited to, an immutable ledger, smart contracts, security, privacy, decentralization, consensus, endorsement, accessibility, and the like.

Example embodiments provide a service to a particular vehicle and/or a user profile that is applied to the vehicle. For example, a user may be the owner of a vehicle or the operator of a vehicle owned by another party. The vehicle may require service at certain intervals, and the service needs may require authorization before permitting the services to be received. Also, service centers may offer services to vehicles in a nearby area based on the vehicle's current route plan and a relative level of service requirements (e.g., immediate, severe, intermediate, minor, etc.). The vehicle needs may be monitored via one or more vehicle and/or road sensors or cameras, which report sensed data to a central controller computer device in and/or apart from the vehicle. This data is forwarded to a management server for review and action. A sensor may be located on one or more of the interior of the transport, the exterior of the transport, on a fixed object apart from the transport, and on another transport proximate the transport. The sensor may also be associated with the transport's speed, the transport's braking, the transport's acceleration, fuel levels, service needs, the gear-shifting of the transport, the transport's steering, and the like. A sensor, as described herein, may also be a device, such as a wireless device in and/or proximate to the transport. Also, sensor information may be used to identify whether the vehicle is operating safely and whether an occupant has engaged in any unexpected vehicle conditions, such as during a vehicle access and/or utilization period. Vehicle information collected before, during and/or after a vehicle's operation may be identified and stored in a transaction on a shared/distributed ledger, which may be generated and committed to the immutable ledger as determined by a permission granting consortium, and thus in a "decentralized" manner, such as via a blockchain membership group.

Each interested party (i.e., owner, user, company, agency, etc.) may want to limit the exposure of private information, and therefore the blockchain and its immutability can be used to manage permissions for each particular user vehicle profile. A smart contract may be used to provide compensation, quantify a user profile score/rating/review, apply vehicle event permissions, determine when service is needed, identify a collision and/or degradation event, iden-

tify a safety concern event, identify parties to the event and provide distribution to registered entities seeking access to such vehicle event data. Also, the results may be identified, and the necessary information can be shared among the registered companies and/or individuals based on a consensus approach associated with the blockchain. Such an approach could not be implemented on a traditional centralized database.

Various driving systems of the instant solution can utilize software, an array of sensors as well as machine learning functionality, light detection and ranging (Lidar) projectors, radar, ultrasonic sensors, etc. to create a map of terrain and road that a transport can use for navigation and other purposes. In some embodiments, GPS, maps, cameras, sensors and the like can also be used in autonomous vehicles in place of Lidar.

The instant solution includes, in certain embodiments, authorizing a vehicle for service via an automated and quick authentication scheme. For example, driving up to a charging station or fuel pump may be performed by a vehicle operator or an autonomous transport and the authorization to receive charge or fuel may be performed without any delays provided the authorization is received by the service and/or charging station. A vehicle may provide a communication signal that provides an identification of a vehicle that has a currently active profile linked to an account that is authorized to accept a service, which can be later rectified by compensation. Additional measures may be used to provide further authentication, such as another identifier may be sent from the user's device wirelessly to the service center to replace or supplement the first authorization effort between the transport and the service center with an additional authorization effort.

Data shared and received may be stored in a database, which maintains data in one single database (e.g., database server) and generally at one particular location. This location is often a central computer, for example, a desktop central processing unit (CPU), a server CPU, or a mainframe computer. Information stored on a centralized database is typically accessible from multiple different points. A centralized database is easy to manage, maintain, and control, especially for purposes of security because of its single location. Within a centralized database, data redundancy is minimized as a single storing place of all data also implies that a given set of data only has one primary record. A blockchain may be used for storing transport-related data and transactions.

Any of the actions described herein may be performed by one or more processors (such as a microprocessor, a sensor, an Electronic Control Unit (ECU), a head unit, and the like), with or without memory, which may be located on-board the transport and/or off-board the transport (such as a server, computer, mobile/wireless device, etc.). The one or more processors may communicate with other memory and/or other processors on-board or off-board other transports to utilize data being sent by and/or to the transport. The one or more processors and the other processors can send data, receive data, and utilize this data to perform one or more of the actions described or depicted herein.

FIG. 1A illustrates a network diagram of a vehicle temporary certificate authentication system 100, according to example embodiments. A system 100 may include one or more vehicles 104, a key management server (KMS) 120, and an external entity 130. Vehicles 104 may include cars, trucks, recreational vehicles, construction vehicles, motorcycles, mopeds, powered bicycles, trains, aircraft, and the like. In one embodiment, the vehicle 104 may be at least

partially powered by electric energy (i.e., electric vehicles or EVs). Vehicles **104** may include one or more Internet-of-Things (IoT) devices **110**. IoT devices **110** may include modules included as part of the vehicle **104**, including but not limited to an ECU, a head unit, or various processors associated with vehicle **104** functions.

Authentication is an effective means to ensure the security of communication within vehicular networks. In the process of communication, a vehicle **104** proves its legality by providing a valid certificate, which is issued by a certificate authority, such as a Key Management Server (KMS **120**). There may be a case in which the vehicle **104** has obtained a valid certificate from the certificate authority but becomes compromised before the certificate expiration date. In this case, the compromised vehicle **104** can communicate with other entities normally and may be able to potentially broadcast false messages. To prevent the compromised vehicle **104** jeopardizing the network **100**, the issued certificate to the vehicle **104** should be made invalid. The process of making invalid an issued certificate of a compromised vehicle **104** is called revocation. The process of certificate revocation is the inverse of the process of certificate issuance.

The IoT device **110**, the KMS **120**, and external entity **130** may include computing devices used for communicating with other users/entities and other computers. IoT devices **110** may include various embedded processors of the vehicle **104**, and may include one or more IoT device processors **160** and associated memory devices. The KMS **120** may include one or more processors and associated memory devices. External entity **130** may include smartphones, tablets, laptop computers, desktop computers, servers, wearable computers, vehicle processors of other vehicles, and the like. The external entity **130** may include one or more external entity processors **170** and associated memory devices, and may be associated with a manufacturer of the vehicle **104**, a service facility for the vehicle **104**, a charging station, and the like. The IoT device processor **160** may communicate with the KMS **120** and/or external entity processor **170** over wired interfaces or wireless interfaces such as WI-FI or BLUETOOTH.

In one embodiment, the external entity **130** may require a trusted identity for other computing devices that request communication with the external entity **130**. The trusted identity may be provided in the form of a validated certificate. For example, when the vehicle **104** connects to an external entity **130** that requires a trusted identity of the vehicle **104**, the vehicle **104** (or more specifically, an IoT device **110**) must authenticate with the KMS server **120**. This is necessary for transaction layer security (TLS) transactions/connections, which secure higher bandwidth technologies in vehicles **104**. The TLS protocol is designed to prevent data from being eavesdropped on or tampered with. It protects the integrity of private communications and sensitive information, which may include browsing habits, personal correspondence, conference calls, passwords, account numbers, financial data, and the like. A protocol, such as the TLS protocol secures the transmission and delivery of data. It does not encrypt the data but is a security protocol for HTTPS connections.

In one embodiment, the IoT device **110** may provide an existing certificate **112** to the KMS **120**. The KMS **120** may determine the certificate **112** has not been revoked and may assign a temporary certificate to the IoT device **110** for a period of time. The period of time is a fixed time period that may be related to a purpose of the temporary certificate, and may be beneficial due to reduced security exposure. For

example, a copied or hacked temporary certificate may not be valid after the time period and the copied or hacked temporary certificate may not be usable. The temporary certificate may be validated by the KMS **120** and provided to the vehicle **104** as a validated temporary certificate **114**. An IoT device processor of the IoT device **110** may store the validated temporary certificate **114** in an accessible memory device.

In one embodiment, the IoT device **110** may need to communicate with an external entity **130**. For example, the IoT device **110** may need to schedule a service appointment with a service facility to have the IoT device **110** serviced. The IoT device **110** may transmit a service request to the external entity **130**, where the service request may include the temporary certificate **116**. The external entity **130** may approve the temporary certificate **116** and schedule a service appointment. The external entity **130**, requiring TLS transactions, may require the certificate or a temporary certificate in order to schedule the appointment.

FIG. **1B** illustrates an example diagram of a vehicle temporary certificate authentication system **150**, according to example embodiments. A system **150** may include one or more IoT device processors **160**, which may be associated with IoT devices **110** of vehicles **104**. IoT processor **160** may include a vehicle processor, other vehicle processors, a navigation processor, a communication processor, a head unit processor, an ECU processor, a sensor processor, and the like.

The system **150** may include a key management server (KMS) **120**, which may include one or more processors and memory devices for storing applications and data. In one embodiment, the KMS **120** may be associated with a manufacturer of the vehicle **104**, a vehicle **104** repair facility, an organization, or a business/organization associated with the vehicle **104**. In one embodiment, the KMS **120** may be located in a network or cloud, may be part of the vehicle **104**, and/or in or connected to one or more vehicle charging stations. In one embodiment, the KMS **120** may include one or more software applications associated with a manufacturer of the vehicle **104**. The KMS **120** may create/assign new certificates and temporary certificates with vehicles **104** and/or IoT devices **110**, check certificates, revoke certificates, and/or replace certificates.

In one embodiment, the system may also include one or more external entities **130**, which include external entity processor(s) **170**. External entities **130** may include computing devices that are intended recipients for messages from vehicles **104**. For example, external entities **130** may be associated with retail or wholesale businesses, government entities, an individual, a vehicle **104** occupant, or any other entity that may receive messages, process transaction requests, and/or respond to received messages.

In one embodiment, the KMS **120** may request a certificate **152** from an IoT device processor **160**. For example, the KMS **120** may initially receive a notification from the IoT device processor **160** to request a temporary certificate. In one embodiment, the IoT device processor **160** may have one or more certificates, or no certificates. In response, the KMS **120** may request an existing certificate **152** from the IoT device processor **160**. In another embodiment, the KMS **120** may initially receive the certificate and a time period **156** as part of a request to issue the temporary certificate, prior to step **152**.

In one embodiment, the IoT device processor **160** may determine a temporary certificate time period **154**. The temporary certificate time period **154** may be based on an expected time to complete a request with an external entity

130 or a group of external entities 130. In one embodiment, the time period may be less than a time period associated with the original certificate. For the previous example of scheduling a maintenance operation for the IoT device 110, the period of time may be two or three weeks, for example. This may allow for sufficient time to schedule an upcoming vehicle maintenance visit and have the maintenance operation performed. In one embodiment, a maximum duration for the period of time may be stored in a memory device coupled to the IoT device processor 160 and/or the KMS 120. In another embodiment, the KMS 120 may determine the temporary certificate time period 154. For example, an accessible memory device of the KMS 120 may store time periods for previous temporary certificate requests similar to the current temporary certificate request. The KMS 120 may identify a similar temporary certificate request and apply the time period for the similar request to the current temporary certificate request.

In one embodiment, the IoT device processor 160 may transmit a notification 156 to the KMS 120 that includes the requested certificate and a requested time period. In one embodiment, the notification 156 may also include a reason for the request. For example, the reason may be to request a service appointment at a facility or to register a new IoT device 110 with the vehicle 104 manufacturer. In one embodiment, the KMS 120 may modify the received time period from the IoT device processor 160. For example, the KMS 120 may have durations for similar temporary certificate requests (i.e., based on a received reason for the request) stored in an accessible memory device and may modify the received time period based on the stored previous results for a similar reason.

In one embodiment, the KMS 120 may determine the certificate from the IoT device 110 is not revoked 158. For the example, the KMS 120 may store a list of revoked certificates in an accessible memory device. Revoked certificates may include previous certificates that have expired or the requester (e.g., IoT device 110 or vehicle 104) is now out of service. If the certificate for the IoT device 110 is in the revoked certificate list, the KMS 120 may notify the IoT device processor 160 that a temporary certificate may not be issued. If the certificate for the IoT device 110 is not on the revoked certificate list, the KMS 120 may proceed with issuing a temporary certificate as described herein.

In one embodiment, after the KMS 120 determines the certificate is not revoked 158, the KMS 120 may assign a temporary certificate to the IoT device 162. A temporary certificate is a certificate that is only active for a time period, and expires at the conclusion of the time period. In one embodiment, the time period may have one or more of a minimum value and/or a maximum value. In another embodiment, the time period may have a duration after a first use of the temporary certificate. In one embodiment, the KMS 120 may assign the temporary certificate to the IoT device 162 by creating a new temporary certificate, storing an identification of the temporary certificate in an accessible memory device along with an association to the IoT device 110. The association may include one or more of a date created, an expiration date, the time period, a reason for requesting the temporary certificate, an identifier associated with the IoT device 110 and the vehicle 104, and a reference to other certificates and/or temporary certificates for the IoT device 110 (including revoked certificates). In one embodiment, expired temporary certificates may not be stored in the revoked certificates list.

In one embodiment, the KMS 120 may validate the assigned temporary certificate 164. In one embodiment, the

KMS 120 may execute steps 158, 162, and 164 to validate a temporary certificate. Once the temporary certificate has been validated, it is ready for use during the time period. The KMS 120 may transfer the validated temporary certificate 166 to the IoT device processor 160, and the IoT device processor 160 may store the validated temporary certificate 166 in an accessible memory device. At this point, the IoT device processor 160 is ready to use the validated temporary certificate 166.

In one embodiment, the IoT device 110 may have a need to contact an external entity 130 and request a form of service. The IoT device processor 160 may prepare a request 168 for the service and transmit a notification 172 to an external entity processor 170 that corresponds to the requested external entity 130. In one embodiment, the notification 172 may include the request, the validated temporary certificate 166, and the time period. The external entity processor 170 may receive the notification 172 and process the request 174. In one embodiment, processing the request 174 may include performing or completing the request within the requested time period.

In one embodiment, obtaining the certificate from the IoT device 110 associated with the vehicle 104 may include the KMS server 120 receives a request from the IoT device 110 to access the KMS 120, where the request may include a time period to access the KMS 120, request the certificate from the IoT device 110, and provide, by the IoT device 110, the certificate to the KMS 120. In one embodiment, the IoT device 110 may request access to the KMS 120 for a limited period of time, which may indicate a request for a temporary certificate. The KMS 120 may respond by requesting an existing certificate from the IoT device 110. The IoT device processor 160 may be required to provide an existing certificate that has not expired and is still in-force. In one embodiment, if the IoT device processor 160 responds by providing an expired certificate, the KMS 120 may not issue a temporary certificate to the IoT device 110.

In one embodiment, determining the certificate is not a revoked certificate may include the KMS 120 determining the certificate is not included within a revoked certificate list and one or more of the certificate is being used within a predetermined time period, and the certificate is being used in an approved application on the IoT device 110. The KMS 120 may access a revoked certificate list stored in an accessible memory device, another server, or in the cloud. The revoked certificate list may include all known certificates that have been previously revoked. In one embodiment, the revoked certificate list may not include expired temporary certificates in order to limit the size and search time of the revoked certificate list. If the KMS 120 identifies the certificate in the list, the certificate may be a revoked certificate. If the KMS 120 does not identify the certificate in the list, the KMS 120 may check whether the certificate is being used within a predetermined time period and/or the certificate is being used in an approved application on the IoT device 110. The predetermined time period may be specified in a data structure of an accessible memory device along with identification of the certificate the predetermined time period applies to. For example, the certificate may apply to a warranty for the vehicle 104, and the warranty period may be one year from a specified warranty date. If the certificate is being used within the predetermined time period (i.e., warranty time period), the KMS 120 may determine the certificate is not being used outside the predetermined time period.

In one embodiment, the IoT device 110 may have an application installed on the IoT device 110. The KMS 120

11

may transmit a notification to the IoT device processor **160** that inquires if the IoT device **110** has an approved application installed to an accessible memory device. The IoT device processor **160** may determine if the certificate is being used in an approved application on the IoT device **110**, and may transmit a notification to the KMS **120** of the result of the determination. If the result indicates the certificate is being used in an approved application on the IoT device **110**, the KMS **120** may determine the certificate is not a revoked certificate. If the result indicates the certificate is not being used in an approved application on the IoT device **110**, the KMS **120** may determine the certificate is a revoked certificate.

In another embodiment, determining the certificate is not the revoked certificate may include the KMS **120** comparing the certificate to a list of revoked certificates. In response to the certificate not being in the list of revoked certificates, the KMS **120** may identify the certificate as an unrevoked certificate. In response to the certificate being in the list of revoked certificates, the KMS **120** may identify the certificate as a revoked certificate.

In one embodiment, assigning the temporary certificate to the IoT device **110** may include the KMS **120** associating the IoT device **110** with a running vehicle **104**, creating a temporary certificate corresponding to the IoT device **110**, and adding the temporary certificate to a temporary certificate revocation list.

In one embodiment, the IoT device processor **160** may include an identification of the vehicle **104** associated with the IoT device **110** in the notification **156** that includes the certificate and time period, or another notification. The KMS **120** may create a new entry in an accessible memory device that associates the temporary certificate with an identifier for the IoT device **110** and the vehicle **104**. For example, the temporary certificate may have one or more of an associated certificate number, a time period for the temporary certificate, and a description of what the temporary certificate applies to. The IoT device **110** may have associated data that may include one or more of a device identifier, a serial number, a description, or any other forms of identification. The vehicle **104** may have associated data that may include one or more of a license plate number, a VIN number, a manufacturer, a model, a model year, or a physical description.

In one embodiment, the KMS **120** creates the temporary certificate may include the KMS **120** notifies the IoT device processor **160** of the identifiers for the temporary certificate and the IoT device processor **160** stores the temporary certificate identifiers in an accessible memory device. In one embodiment, the KMS **120** may add the temporary certificate to a temporary certificate revocation list stored in an accessible memory device. The temporary certificate may be removed from the temporary certificate revocation list when the temporary certificate expires.

In one embodiment, validating the temporary certificate may include the KMS **120** determines the temporary certificate has not been used, determines the temporary certificate is not in a revocation list, and authorizes use of the temporary certificate for a time period. In one embodiment, the KMS **120** may perform a one-time check prior to initial use of the temporary certificate. For example, after a temporary certificate has been created, the IoT device processor **160** may attempt to use the temporary certificate for a product or service.

In one embodiment, the KMS **120** may determine the temporary certificate has not been used by querying an accessible memory device for evidence us temporary cer-

12

tificate usage. When the IoT device **110** initially receives the temporary certificate, the IoT device processor **160** may store the temporary certificate to an accessible memory device. The first time the temporary certificate is used for a product or service, the IoT device processor **160** may transfer a request to an external entity processor **170** associated with the product or service that may include a transaction and the temporary certificate. The external entity processor **170** may transfer a request to the KMS **120** requesting validation of the temporary certificate. The KMS **120** may query the accessible memory device and determine if this is the first time the temporary certificate has attempted to be used. The memory device may include one or more identifiers of the temporary certificate along with an indicator of previous use of the temporary certificate.

In one embodiment, the indicator may indicate no previous use of the temporary certificate, the KMS **120** may check a revocation list in an accessible memory device to see if the temporary certificate is valid (i.e. the temporary certificate is not in the revocation list), authorize use of the temporary certificate for a time period associated with the temporary certificate, change the indicator to reflect previous use of the temporary certificate, and transfer a notification to the external entity processor **170** that indicates authorization to process the requested product or service transaction.

In another embodiment, the indicator may indicate a previous use of the temporary certificate, which may remove the need for the KMS **120** to check the revocation list. The KMS **120** may authorize use of the temporary certificate for the time period associated with the temporary certificate and transfer a notification to the external entity processor **170** that indicates authorization to process the requested product or service transaction.

In one embodiment, the KMS **120** may provide the validated temporary certificate in place of an original certificate for a time period, based on an amount of time to validate the original certificate each time a connection to an entity is required. The original certificate must be validated each time it is used by checking a large and growing list of revoked certificates. Because this can potentially take much time, the temporary certificate may be validated against the list of revoked certificates only the first time it is used. The temporary certificate is only valid for a defined period of time.

For example, a transaction may have a time component that may only be effective for a transaction time period, or the transaction may be related to a product or service with limited availability (e.g., movie or event tickets). Either condition may make the temporary certificate (that has already been validated for an initial use) more useful than the original certificate for use during the temporary certificate time period because the revocation list does not need to be searched. This may make transactions using the temporary certificate complete faster than transactions using the original certificate.

In one embodiment, the KMS **120** may determine a time period associated with the temporary certificate has expired, notify the IoT device **110** the temporary certificate has expired, determine the certificate is not a revoked certificate, assign a single-use temporary certificate to the IoT device **110**, and validate the single-use temporary certificate. The temporary certificate is only valid for a time period. When it expires, the KMS **120** may notify the IoT device **110** and may assign a new single-use temporary certificate to give the IoT device **110** time to apply for a new temporary certificate.

13

In one embodiment, the KMS 120 may determine the time period associated with the temporary certificate has expired. The KMS 120 may receive a transaction request with the temporary certificate from an external entity processor 170. The KMS 120 may check an accessible memory device to see if the temporary certificate is still valid. If the current time is within the time period assigned to the temporary certificate, the time period has not expired. If the current time is after the time period assigned to the temporary certificate, the time period has expired.

In one embodiment, the KMS 120 may check an accessible memory device in order to determine if the certificate has been revoked, or not. The accessible memory device may include a revocation list that includes identifiers for all revoked certificates, including expired certificates. If the certificate is not in the revocation list, the KMS 120 may assign a single-use temporary certificate to the IoT device 110 in order to allow a current transaction to complete while giving the IoT device 110 more time to apply for a new temporary certificate. The KMS 120 may provide the single-use temporary certificate to the external entity processor 170 and/or the IoT device processor 160, along with an indication that the temporary certificate is only valid for one use.

In one embodiment, the temporary certificate may be stored on an external entity 130, such as a mobile device. The mobile device may be required to be within the vehicle 104 when the temporary certificate is used. Therefore, an IoT device processor 160 may detect if the mobile device is within the vehicle 104 before allowing use of the temporary certificate.

In one embodiment, a vehicle processor, including the IoT device processor 160, may determine an external entity 130 is within the vehicle 104. For example, a wireless connection, such as a BLUETOOTH connection may be enabled in the vehicle 104 and the external entity 130. The vehicle processor may detect a new BLUETOOTH device and request pairing with the device. A user associated with the vehicle 104 and/or the external entity 130 may approve the pairing request, and the vehicle 104 pairs with the external entity 130. An application executed by a vehicle processor may request GPS coordinates from the external entity 130 and may determine the external entity 130 GPS coordinates match the GPS coordinates of the vehicle 104. This may indicate the external entity 130 is within the vehicle 104. The vehicle processor may transmit a notification to the external entity 130 and KMS 120 indicating that transactions using the temporary certificate are now approved. The external entity 130 may conduct various transactions while the transactions are approved.

In one embodiment, the external entity 130 may continue to periodically send GPS coordinates to the vehicle processor. Each time the vehicle processor receives the GPS coordinates, it continues to compare the GPS coordinates to the vehicle's current GPS coordinates. As long as they continue to match, the external entity 130 is approved to conduct transactions. However, once they do not match, the vehicle processor may transmit a notification to the external entity 130 and KMS 120 indicating that transactions using the temporary certificate are no longer approved.

Flow diagrams depicted herein, such as FIG. 1A, FIG. 1B, FIG. 2C, FIG. 2D, FIG. 2E, FIG. 3A, FIG. 3B and FIG. 3C are separate examples but may be the same or different embodiments. Any of the operations in one flow diagram could be adopted and shared with another flow diagram. No example operation is intended to limit the subject matter of any embodiment or corresponding claim.

14

It is important to note that all the flow diagrams and corresponding processes derived from FIG. 1A, FIG. 1B, FIG. 2C, FIG. 2D, FIG. 2E, FIG. 3A, FIG. 3B, and FIG. 3C may be part of a same process or may share sub-processes with one another thus making the diagrams combinable into a single preferred embodiment that does not require any one specific operation but which performs certain operations from one example process and from one or more additional processes. All the example processes are related to the same physical system and can be used separately or interchangeably.

FIG. 2A illustrates a transport network diagram 200, according to example embodiments. The network comprises elements including a transport 202 including a processor 204, as well as a transport 202' including a processor 204'. The transports 202, 202' communicate with one another via the processors 204, 204', as well as other elements (not shown) including transceivers, transmitters, receivers, storage, sensors, and other elements capable of providing communication. The communication between the transports 202, and 202' can occur directly, via a private and/or a public network (not shown), or via other transports and elements comprising one or more of a processor, memory, and software. Although depicted as single transports and processors, a plurality of transports and processors may be present. One or more of the applications, features, steps, solutions, etc., described and/or depicted herein may be utilized and/or provided by the instant elements.

FIG. 2B illustrates another transport network diagram 210, according to example embodiments. The network comprises elements including a transport 202 including a processor 204, as well as a transport 202' including a processor 204'. The transports 202, 202' communicate with one another via the processors 204, 204', as well as other elements (not shown), including transceivers, transmitters, receivers, storage, sensors, and other elements capable of providing communication. The communication between the transports 202, and 202' can occur directly, via a private and/or a public network (not shown), or via other transports and elements comprising one or more of a processor, memory, and software. The processors 204, 204' can further communicate with one or more elements 230 including sensor 212, wired device 214, wireless device 216, database 218, mobile phone 220, transport 222, computer 224, I/O device 226, and voice application 228. The processors 204, 204' can further communicate with elements comprising one or more of a processor, memory, and software.

Although depicted as single transports, processors and elements, a plurality of transports, processors and elements may be present. Information or communication can occur to and/or from any of the processors 204, 204' and elements 230. For example, the mobile phone 220 may provide information to the processor 204, which may initiate the transport 202 to take an action, may further provide the information or additional information to the processor 204', which may initiate the transport 202' to take an action, may further provide the information or additional information to the mobile phone 220, the transport 222, and/or the computer 224. One or more of the applications, features, steps, solutions, etc., described and/or depicted herein may be utilized and/or provided by the instant elements.

FIG. 2C illustrates yet another transport network diagram 240, according to example embodiments. The network comprises elements including a transport 202, a processor 204, and a non-transitory computer readable medium 242C. The processor 204 is communicably coupled to the computer readable medium 242C and elements 230 (which were

depicted in FIG. 2B). The transport **202** could be a transport, server, or any device with a processor and memory.

The processor **204** performs one or more of obtaining, by a server, a certificate from an IoT device associated with a vehicle **244C**, determining, by the server, the certificate is not a revoked certificate **246C**, assigning, by the server, a temporary certificate to the IoT device **248C**, and validating, by the server, the temporary certificate **250C**.

FIG. 2D illustrates a further transport network diagram **250**, according to example embodiments. The network comprises elements including a transport **202**, a processor **204**, and a non-transitory computer readable medium **242D**. The processor **204** is communicably coupled to the computer readable medium **242D** and elements **230** (which were depicted in FIG. 2B). The transport **202** could be a transport, server or any device with a processor and memory.

The processor **204** performs one or more of receiving a request, from the IoT device, to access the server, where the request includes a time period to access the server, requesting the certificate from the IoT device, and validating the temporary certificate **244D**, determining the certificate is not included within a revoked certificate list and one or more of the certificate is being used within a predetermined time period, and the certificate is being used in an approved application on the IoT device **245D**, associating the IoT device with a running vehicle, creating a temporary certificate corresponding to the IoT device, and adding the temporary certificate to a temporary certificate revocation list **246D**, determining the temporary certificate has not been used, determining the temporary certificate is not in a revocation list, and authorizing use of the temporary certificate for a time period **247D**, providing the validated temporary certificate in place of an original certificate for a time period, based on an amount of time to validate the original certificate each time a connection to an entity is required **248D**, and determining a time period associated with the temporary certificate has expired, notifying the IoT device the temporary certificate has expired, determining the certificate is not a revoked certificate, assigning a single-use temporary certificate to the IoT device, and validating the single-use temporary certificate **249D**.

FIG. 2E illustrates yet a further transport network diagram **260**, according to example embodiments. Referring to FIG. 2E, the network diagram **260** includes a transport **202** connected to other transports **202'** and to an update server node **203** over a blockchain network **206**. The transports **202** and **202'** may represent transports/vehicles. The blockchain network **206** may have a ledger **208** for storing software update validation data and a source **207** of the validation for future use (e.g., for an audit).

While this example describes in detail only one transport **202**, multiple such nodes may be connected to the blockchain **206**. It should be understood that the transport **202** may include additional components and that some of the components described herein may be removed and/or modified without departing from a scope of the instant application. The transport **202** may have a computing device or a server computer, or the like, and may include a processor **204**, which may be a semiconductor-based microprocessor, a central processing unit (CPU), an application-specific integrated circuit (ASIC), a field-programmable gate array (FPGA), and/or another hardware device. Although a single processor **204** is depicted, it should be understood that the transport **202** may include multiple processors, multiple cores, or the like without departing from the scope of the instant application. The transport **202** could be a transport, server or any device with a processor and memory.

The processor **204** performs one or more of receiving a confirmation of an event from one or more elements described or depicted herein, wherein the confirmation comprises a blockchain consensus between peers represented by any of the elements **244E** and executing a smart contract to record the confirmation on a blockchain-based on the blockchain consensus **246E**. Consensus is formed between one or more of any element **230** and/or any element described or depicted herein, including a transport, a server, a wireless device, etc. In another example, the transport **202** can be one or more of any element **230** and/or any element described or depicted herein, including a server, a wireless device, etc.

The processors and/or computer readable medium **242E** may fully or partially reside in the interior or exterior of the transports. The steps or features stored in the computer readable medium **242E** may be fully or partially performed by any of the processors and/or elements in any order. Additionally, one or more steps or features may be added, omitted, combined, performed at a later time, etc.

FIG. 2F illustrates a diagram **265** depicting the electrification of one or more elements. In one example, a transport **266** may provide power stored in its batteries to one or more elements, including other transport(s) **268**, charging station(s) **270**, and electric grid(s) **272**. The electric grid(s) **272** is/are coupled to one or more of the charging stations **270**, which may be coupled to one or more of the transports **268**. This configuration allows the distribution of electricity/power received from the transport **266**. The transport **266** may also interact with the other transport(s) **268**, such as via Vehicle to Vehicle (V2V) technology, communication over cellular, Wi-Fi, and the like. The transport **266** may also interact wirelessly and/or wired with other transports **268**, the charging station(s) **270** and/or with the electric grid(s) **272**. In one example, the transport **266** is routed (or routes itself) in a safe and efficient manner to the electric grid(s) **272**, the charging station(s) **270**, or the other transport(s) **268**. Using one or more embodiments of the instant solution, the transport **266** can provide energy to one or more of the elements depicted herein in various advantageous ways as described and/or depicted herein. Further, the safety and efficiency of the transport may be increased, and the environment may be positively affected as described and/or depicted herein.

The term 'energy' may be used to denote any form of energy received, stored, used, shared, and/or lost by the transport(s). The energy may be referred to in conjunction with a voltage source and/or a current supply of charge provided from an entity to the transport(s) during a charge/use operation. Energy may also be in the form of fossil fuels (for example, for use with a hybrid transport) or via alternative power sources, including but not limited to lithium-based, nickel-based, hydrogen fuel cells, atomic/nuclear energy, fusion-based energy sources, and energy generated on-the-fly during an energy sharing and/or usage operation for increasing or decreasing one or more transports energy levels at a given time.

In one example, the charging station **270** manages the amount of energy transferred from the transport **266** such that there is sufficient charge remaining in the transport **266** to arrive at a destination. In one example, a wireless connection is used to wirelessly direct an amount of energy transfer between transports **268**, wherein the transports may both be in motion. In one embodiment, wireless charging may occur via a fixed charger and batteries of the transport in alignment with one another (such as a charging mat in a garage or parking space). In one example, an idle vehicle, such as a vehicle **266** (which may be autonomous) is

17

directed to provide an amount of energy to a charging station 270 and return to the original location (for example, its original location or a different destination). In one example, a mobile energy storage unit (not shown) is used to collect surplus energy from at least one other transport 268 and transfer the stored surplus energy at a charging station 270. In one example, factors determine an amount of energy to transfer to a charging station 270, such as distance, time, as well as traffic conditions, road conditions, environmental/weather conditions, the vehicle's condition (weight, etc.), an occupant(s) schedule while utilizing the vehicle, a prospective occupant(s) schedule waiting for the vehicle, etc. In one example, the transport(s) 268, the charging station(s) 270 and/or the electric grid(s) 272 can provide energy to the transport 266.

In one embodiment, a location such as a building, a residence, or the like (not depicted), communicably coupled to one or more of the electric grid 272, the transport 266, and/or the charging station(s) 270. The rate of electric flow one or more of the location, the transport 266, the other transport(s) 268 is modified, depending on external conditions, such as weather. For example, when the external temperature is extremely hot or extremely cold, raising the chance for an outage of electricity, the flow of electricity to a connected vehicle 266/268 is slowed to help minimize the chance for an outage.

In one example, the solutions described and depicted herein can be utilized to determine load effects on the transport and/or the system, to provide energy to the transport and/or the system based on future needs and/or priorities, and provide intelligence between an apparatus containing a module and a vehicle allowing the processor of the apparatus to wirelessly communicate with a vehicle regarding an amount of energy store in a battery on the vehicle. In one example, the solutions can also be utilized to provide charge to a location from a transport based on factors such as the temperature at the location, the cost of the energy, and the power level at the location. In one example, the solutions can also be utilized to manage an amount of energy remaining in a transport after a portion of the charge has been transferred to a charging station. In one example, the solutions can also be utilized to notify a vehicle to provide an amount of energy from batteries on the transport, wherein the amount of energy to transfer is based on the distance of the transport to a module to receive the energy.

In one example, the solutions can also be utilized to use a mobile energy storage unit that uses a determined path to travel to transports with excess energy and deposit the stored energy into the electric grid. In one example, the solutions can also be utilized to determine a priority of the transport's determination of the need to provide energy to grid and the priority of a current need of the transport, such as the priority of a passenger or upcoming passenger, or current cargo, or upcoming cargo. In one example, the solutions can also be utilized to determine that when a vehicle is idle, the vehicle decides to maneuver to a location to discharge excess energy to the energy grid, then return to the previous location. In one example, the solutions can also be utilized to determine an amount of energy needed by a transport to provide another transport with needed energy via transport to transport energy transfer based on one or more conditions such as weather, traffic, road conditions, car conditions, and occupants and/or goods to another transport, and instruct the transport to route to another transport and provide the energy. In one example, the solutions can also be utilized to transfer energy from one vehicle in motion to another vehicle in motion. In one example, the solutions can also be

18

utilized to retrieve energy by a transport based on an expended energy by the transport to reach a meeting location with another transport, provide a service, and an estimated expended energy to return to an original location. In one example, the solutions can also be utilized to provide a remaining distance needed to a charging station and the charging station to determine an amount of energy to be retrieved from the transport wherein the amount of charge remaining is based on the remaining distance. In one example, the solutions can also be utilized to manage a transport that is concurrently charged by more than one point simultaneously, such as both a charging station via a wired connection and another transport via a wireless connection. In one example, the solutions can also be utilized to apply a priority to the dispensing of energy to transports wherein a priority is given to those transports that will provide a portion of their stored charge to another entity such as an electric grid, a residence, and the like.

In one embodiment, transports 266 and 268 may be utilized as bidirectional transports. Bidirectional transports are those that may serve as mobile microgrids that can assist in the supplying of electrical power to the grid 272 and/or reduce the power consumption when the grid is stressed. Bidirectional transports incorporate bidirectional charging, which in addition to receiving a charge to the transport, the transport can take energy from the transport and "push" the energy back into the grid 272, otherwise referred to as "V2G". In bidirectional charging, the electricity flows both ways; to the transport and from the transport. When a transport is charged, alternating current (AC) electricity from the grid 272 is converted to direct current (DC). This may be performed by one or more of the transport's own converter or a converter on the charger 270. The energy stored in the transport's batteries may be sent in an opposite direction back to the grid. The energy is converted from DC to AC through a converter usually located in the charger 270, otherwise referred to as a bidirectional charger. Further, the instant solution as described and depicted with respect to FIG. 2F can be utilized in this and other networks and/or systems.

FIG. 2G is a diagram showing interconnections between different elements 275. The instant solution may be stored and/or executed entirely or partially on and/or by one or more computing devices 278', 279', 281', 282', 283', 284', 276', 285', 287' and 277' associated with various entities, all communicably coupled and in communication with a network 286. A database 287 is communicably coupled to the network and allows for the storage and retrieval of data. In one example, the database is an immutable ledger. One or more of the various entities may be a transport 276, one or more service provider 279, one or more public buildings 281, one or more traffic infrastructure 282, one or more residential dwellings 283, an electric grid/charging station 284, a microphone 285, and/or another transport 277. Other entities and/or devices, such as one or more private users using a smartphone 278, a laptop 280, an augmented reality (AR) device, a virtual reality (VR) device, and/or any wearable device may also interwork with the instant solution. The smartphone 278, laptop 280, the microphone 285, and other devices may be connected to one or more of the connected computing devices 278', 279', 281', 282', 283', 284', 276', 285', 287', and 277'. The one or more public buildings 281 may include various agencies. The one or more public buildings 281 may utilize a computing device 281'. The one or more service provider 279 may include a dealership, a tow truck service, a collision center or other repair shop. The one or more service provider 279 may

utilize a computing apparatus 279'. These various computer devices may be directly and/or communicably coupled to one another, such as via wired networks, wireless networks, blockchain networks, and the like. The microphone 285 may be utilized as a virtual assistant, in one example. In one example, the one or more traffic infrastructure 282 may include one or more traffic signals, one or more sensors including one or more cameras, vehicle speed sensors or traffic sensors, and/or other traffic infrastructure. The one or more traffic infrastructure 282 may utilize a computing device 282'.

In one example, a transport 277/276 can transport a person, an object, a permanently or temporarily affixed apparatus, and the like. In one example, the transport 277 may communicate with transport 276 via V2V communication through the computers associated with each transport 276' and 277' and may be referred to as a transport, car, vehicle, automobile, and the like. The transport 276/277 may be a self-propelled wheeled conveyance, such as a car, a sports utility vehicle, a truck, a bus, a van, or other motor or battery-driven or fuel cell-driven transport. For example, transport 276/277 may be an electric vehicle, a hybrid vehicle, a hydrogen fuel cell vehicle, a plug-in hybrid vehicle, or any other type of vehicle with a fuel cell stack, a motor, and/or a generator. Other examples of vehicles include bicycles, scooters, trains, planes, boats, and any other form of conveyance that is capable of transportation. The transport 276/277 may be semi-autonomous or autonomous. For example, transport 276/277 may be self-maneuvering and navigate without human input. An autonomous vehicle may have and use one or more sensors and/or a navigation unit to drive autonomously.

In one example, the solutions described and depicted herein can be utilized to determine an access to a transport via consensus of blockchain. In one example, the solutions can also be utilized to perform profile validation before allowing an occupant to use a transport. In one example, the solutions can also be utilized to have the transport indicate (visually, but also verbally in another example, etc.) on or from the transport for an action the user needs to perform (that could be pre-recorded) and verify that it is the correct action. In one example, the solutions can also be utilized to provide an ability to for a transport to determine, based on the risk level associated with data and driving environment, how to bifurcate the data and distribute a portion of the bifurcated data with a lower risk level during a safe driving environment, to the occupant, and later distributing a remaining portion of the bifurcated data, with a higher risk level, to the occupant after the occupant has departed the transport. In one example, the solutions can also be utilized to handle the transfer of a vehicle across boundaries (such as a country/state/etc.) through the use of blockchain and/or smart contracts and apply the rules of the new area to the vehicle.

In one example, the solutions can also be utilized to allow a transport to continue to operate outside a boundary when a consensus is reached by the transport based on the operation of the transport and characteristics of an occupant of the transport. In one example, the solutions can also be utilized to analyze the available data upload/download speed of a transport, size of the file, and speed/direction the transport is traveling to determine the distance needed to complete a data upload/download and assign a secure area boundary for the data upload/download to be executed. In one example, the solutions can also be utilized to perform a normally dangerous maneuver in a safe manner, such as when the system determines that an exit is upcoming and when the

transport is seemingly not prepared to exit (e.g., in the incorrect lane or traveling at a speed that is not conducive to making the upcoming exit) and instruct the subject transport as well as other proximate transports to allow the subject transport to exit in a safe manner. In one example, the solutions can also be utilized to use one or more vehicles to validate diagnostics of another transport while both the one or more vehicles and the other transport are in motion.

In one example, the solutions can also be utilized to detect lane usage at a location and time of day to either inform an occupant of a transport or direct the transport to recommend or not recommend a lane change. In one example, the solutions can also be utilized to eliminate the need to send information through the mail and the need for a driver/occupant to respond by making a payment through the mail or in person. In one example, the solutions can also be utilized to provide a service to an occupant of a transport, wherein the service provided is based on a subscription and wherein the permission is acquired from other transports connected to the profile of the occupant. In one example, the solutions can also be utilized to record changes in the condition of a rented object. In one example, the solutions can also be utilized to seek a blockchain consensus from other transports that are in proximity to a damaged transport. In one example, the solutions can also be utilized to receive media, from a server such as an insurance entity server, from the transport computer, which may be related to an accident. The server accesses one or more media files to access the damage to the transport and stores the damage assessment onto a blockchain. In one example, the solutions can also be utilized to obtain a consensus to determine the severity of an event from several devices over various times before the event related to a transport.

In one example, the solutions can also be utilized to solve a problem without video evidence for transport-related accidents. The current solution details the querying of media, by the transport involved in the accident, related to the accident from other transports that may have been proximate to the accident. In one example, the solutions can also be utilized to utilize transports and other devices (for example, a pedestrian's cell phone, a streetlight camera, etc.) to record specific portions of a damaged transport.

In one example, the solutions can also be utilized to warn an occupant when a transport is navigating toward a dangerous area and/or event, allowing for a transport to notify occupants or a central controller of a potentially dangerous area on or near the current transport route. In one example, the solutions can also be utilized to detect when a transport traveling at a high rate of speed, at least one other transport is used to assist in slowing down the transport in a manner that minimally affects traffic. In one example, the solutions can also be utilized to identify a dangerous driving situation where media is captured by the vehicle involved in the dangerous driving situation. A geofence is established based on the distance of the dangerous driving situation, and additional media is captured by at least one other vehicle within the established geofence. In one example, the solutions can also be utilized to send a notification to one or more occupants of a transport that that transport is approaching a traffic control marking on a road, then if a transport crosses a marking, receiving indications of poor driving from other, nearby transports. In one example, the solutions can also be utilized to make a transport partially inoperable by (in certain embodiments), limiting speed, limiting the ability to be near another vehicle, limiting speed to a maximum, and allowing only a given number of miles allowed per time period.

In one example, the solutions can also be utilized to overcome a need for reliance on software updates to correct issues with a transport when the transport is not being operated correctly. Through observing other transports on a route, a server will receive data from potentially multiple other transports observing an unsafe or incorrect operation of a transport. Through analysis, these observations may result in a notification to the transport when the data suggest an unsafe or incorrect operation. In one example, the solutions can also be utilized to notify between a transport and a potentially dangerous situation involving a person external to the transport. In one example, the solutions can also be utilized to send data to a server by devices either associated with an accident with a transport, or devices proximate to the accident. Based on the severity of the accident or near accident, the server notifies the senders of the data. In one example, the solutions can also be utilized to provide recommendations for operating a transport to either a driver or occupant of a transport based on the data analysis. In one example, the solutions can also be utilized to establish a geofence associated with a physical structure and determine payment responsibility to the transport. In one example, the solutions can also be utilized to coordinate the ability to drop off a vehicle at a location using both the current state at the location and a proposed future state using navigation destinations of other vehicles. In one example, the solutions can also be utilized to coordinate the ability to automatically arrange for the drop off of a vehicle at a location such as a transport rental entity.

In one example, the solutions can also be utilized to move transport to another location based on a user's event. More particularly, the system tracks a user's device and modifies the transport to be moved proximate to the user upon the conclusion of the original event or a modified event. In one example, the solutions can also be utilized to allow for the validation of available locations within an area through the existing transports within the area. The approximate time when a location may be vacated is also determined based on verifications from the existing transports. In one example, the solutions can also be utilized to move a transport to closer parking spaces as one becomes available and the elapsed time since initially parking is less than the average event time. Furthermore, moving the transport to a final parking space when the event is completed or according to a location of a device associated with at least one occupant of the transport. In one example, the solutions can also be utilized to plan for the parking before the upcoming crowd. The system interacts with the transport to offer some services at a less than full price and/or guide the transport to alternative parking locations based on a priority of the transport, increasing optimization of the parking situation before arriving.

In one example, the solutions can also be utilized to sell fractional ownership in transports or determine pricing and availability in ride-sharing applications. In one example, the solutions can also be utilized to provide accurate and timely reports of dealership sales activities well beyond what is currently available. In one example, the solutions can also be utilized to allow a dealership to request an asset over the blockchain. By using the blockchain, a consensus is obtained before any asset is moved. Additionally, the process is automated, and payment may be initiated over the blockchain. In one example, the solutions can also be utilized to arrange agreements that are made with multiple entities (such as service centers) wherein a consensus is acquired and an action performed (such as diagnostics). In one example, the solutions can also be utilized to associate

digital keys with multiple users. A first user may be the transport operator, and a second user is a responsible party for the transport. These keys are authorized by a server where the proximity of the keys is validated against the location of a service provider. In one example, the solutions can also be utilized to determine a needed service on a transport destination. One or more service locations are located that can provide the needed service that is both within an area on route to the destination and has availability to perform the service. The navigation of the transport is updated with the determined service location. A smart contract is identified that contains a compensation value for the service, and a blockchain transaction is stored in a distributed ledger for the transaction.

In one example, the solutions can also be utilized to interfacing a service provider transport with a profile of an occupant of a transport to determine services and goods which may be of interest to occupants in a transport. These services and goods are determined by an occupant's history and/or preferences. The transport then receives offers from the service provider transport and, in another example, meets the transport to provide the service/good. In one example, the solutions can also be utilized to detect a transport within a range and send a service offer to the transport (such as a maintenance offer, a product offer, or the like). An agreement is made between the system and the transport, and a service provider is selected by the system to provide the agreement. In one example, the solutions can also be utilized to assign one or more transports as a roadway manager, where the roadway manager assists in controlling traffic. The roadway manager may generate a roadway indicator (such as lights, displays, and sounds) to assist in the flow of traffic. In one example, the solutions can also be utilized to alert a driver of a transport by a device, wherein the device may be the traffic light or near an intersection. The alert is sent upon an event, such as when a light turns green, and the transport in the front of a list of transports does not move.

FIG. 2H is another block diagram showing interconnections between different elements in one example **290**. A transport **276** is presented and includes ECUs **295**, **296**, and a Head Unit (otherwise known as an Infotainment System) **297**. An Electrical Control Unit (ECU) is an embedded system in automotive electronics controlling one or more of the electrical systems or subsystems in a transport. ECUs may include but are not limited to the management of a transport's engine, brake system, gearbox system, door locks, dashboard, airbag system, infotainment system, electronic differential, and active suspension. ECUs are connected to the transport's CAN bus **294**. The ECUs may also communicate with a transport computer **298** via the CAN bus **294**. The transport's processors/sensors (such as the transport computer) **298** can communicate with external elements, such as a server **293** via a network **292** (such as the Internet). Each ECU **295**, **296**, and Head Unit **297** may contain its own security policy. The security policy defines permissible processes that can be executed in the proper context. In one example, the security policy may be partially or entirely provided in the transport computer **298**.

ECUs **295**, **296**, and Head Unit **297** may each include a custom security functionality element **299** defining authorized processes and contexts within which those processes are permitted to run. Context-based authorization to determine validity if a process can be executed allows ECUs to maintain secure operation and prevent unauthorized access from elements such as the transport's Controller Area Network (CAN Bus). When an ECU encounters a process that

is unauthorized, that ECU can block the process from operating. Automotive ECUs can use different contexts to determine whether a process is operating within its permitted bounds, such as proximity contexts such as nearby objects, distance to approaching objects, speed, and trajectory relative to other moving objects, and operational contexts such as an indication of whether the transport is moving or parked, the transport's current speed, the transmission state, user-related contexts such as devices connected to the transport via wireless protocols, use of the infotainment, cruise control, parking assist, driving assist, location-based contexts, and/or other contexts.

In one example, the solutions described and depicted herein can be utilized to make a transport partially inoperable by (in certain embodiments), limiting speed, limiting the ability to be near another vehicle, limiting speed to a maximum, and allowing only a given number of miles allowed per time period. In one example, the solutions can also be utilized to use a blockchain to facilitate the exchange of vehicle possession wherein data is sent to a server by devices either associated with an accident with a transport, or devices proximate to the accident. Based on the severity of the accident or near accident, the server notifies the senders of the data. In one example, the solutions can also be utilized to help the transport to avoid accidents, such as when the transport is involved in an accident by a server that queries other transports that are proximate to the accident. The server seeks to obtain data from the other transports, allowing the server to understand the nature of the accident from multiple vantage points. In one example, the solutions can also be utilized to determine that sounds from a transport are atypical and transmit data related to the sounds and a possible source location to a server wherein the server can determine possible causes and avoid a potentially dangerous situation. In one example, the solutions can also be utilized to establish a location boundary via the system when a transport is involved in an accident. This boundary is based on decibels associated with the accident. Multimedia content for a device within the boundary is obtained to assist in further understanding the scenario of the accident. In one example, the solutions can also be utilized to associate a vehicle with an accident, then capture media obtained by devices proximate to the location of the accident. The captured media is saved as a media segment. The media segment is sent to another computing device which builds a sound profile of the accident. This sound profile will assist in understanding more details surrounding the accident.

In one example, the solutions can also be utilized to utilize sensors to record audio, video, motion, etc. to record an area where a potential event has occurred, such as if a transport comes in contact or may come in contact with another transport (while moving or parked), the system captures data from the sensors which may reside on one or more of the transports and/or on fixed or mobile objects. In one example, the solutions can also be utilized to determine that a transport has been damaged by using sensor data to identify a new condition of the transport during a transport event and comparing the condition to a transport condition profile, making it possible to safely and securely capture critical data from a transport that is about to be engaged in a detrimental event.

In one example, the solutions can also be utilized to warn occupants of a transport when the transport, via one or more sensors, has determined that it is approaching or going down a one-way road the incorrect way. The transport has sensors/cameras/maps interacting with the system of the current solution. The system knows the geographic location of

one-way streets. The system may audibly inform the occupants, "Approaching a one-way street," for example. In one example, the solutions can also be utilized to allow the transport to get paid, allowing autonomous vehicle owners to monetize the data their vehicle sensors collect and store, creating an incentive for vehicle owners to share their data and provide entities with additional data through which to improve the performance of future vehicles, provide services to the vehicle owners, etc.

In one example, the solutions can also be utilized to either increase or decrease a vehicle's features according to the action of the vehicle over a period of time. In one example, the solutions can also be utilized to assign a fractional ownership to a transport. Sensor data related to one or more transports and a device proximate to the transport are used to determine a condition of the transport. The fractional ownership of the transport is determined based on the condition, and a new transport responsibility is provided. In one example, the solutions can also be utilized to provide data to a replacement/upfitting component, wherein the data attempts to subvert an authorized functionality of the replacement/upfitting component, and responsive to a non-subversion of the authorized functionality, permitting, by the component, use of the authorized functionality of the replacement/upfitting component.

In one example, the solutions can also be utilized to provide individuals the ability to ensure that an occupant should be in a transport and for that occupant to reach a particular destination. Further, the system ensures a driver (if a non-autonomous transport) and/or other occupants are authorized to interact with the occupant. Also, pickups, drop-offs and location are noted. All of the above are stored in an immutable fashion on a blockchain. In one example, the solutions can also be utilized to determine the characteristics of a driver via an analysis of driving style and other elements to take action if the driver is not driving in a normal manner, such as a manner in which the driver has previously driven in a particular condition, for example during the day, at night, in the rain, in the snow, etc. Further, the attributes of the transport are also taken into account. Attributes include weather, whether the headlights are on, whether navigation is being used, a HUD is being used, the volume of media being played, etc. In one example, the solutions can also be utilized to notify occupants in a transport of a dangerous situation when items inside the transport signify that the occupants may not be aware of the dangerous situation.

In one example, the solutions can also be utilized to mount calibration devices on a rig that is fixed to a vehicle, wherein the various sensors on the transport can automatically self-adjust based on what should be detected by the calibration devices as compared to what is actually detected. In one example, the solutions can also be utilized to use a blockchain to require consensus from a plurality of service centers when a transport needing service sends malfunction information allowing remote diagnostic functionality wherein a consensus is required from other service centers on what a severity threshold is for the data. Once the consensus is received, the service center may send the malfunction security level to the blockchain to be stored. In one example, the solutions can also be utilized to determine a difference in sensor data external to the transport and the transport's own sensor data. The transport requests, from a server, a software to rectify the issue. In one example, the solutions can also be utilized to allow for the messaging of transports that are either nearby or in the area when an event occurs (e.g., a collision).

25

Referring to FIG. 2I, an operating environment **290A** for a connected transport, is illustrated according to some embodiments. As depicted, the transport **276** includes a CAN bus **291A** connecting elements **292A-299A** of the transport. Other elements may be connected to the CAN bus and are not depicted herein. The depicted elements connected to the CAN bus include a sensor set **292A**, Electronic Control Units **293A**, autonomous features or Advanced Driver Assistance Systems (ADAS) **294A**, and the navigation system **295A**. In some embodiments, the transport **276** includes a processor **296A**, a memory **297A**, a communication unit **298A**, and an electronic display **299A**.

The processor **296A** includes an arithmetic logic unit, a microprocessor, a general-purpose controller, and/or a similar processor array to perform computations and provide electronic display signals to a display unit **299A**. The processor **296A** processes data signals and may include various computing architectures, including a complex instruction set computer (CISC) architecture, a reduced instruction set computer (RISC) architecture, or an architecture implementing a combination of instruction sets. The transport **276** may include one or more processors **296A**. Other processors, operating systems, sensors, displays, and physical configurations that are communicably coupled to one another (not depicted) may be used with the instant solution.

Memory **297A** is a non-transitory memory storing instructions or data that may be accessed and executed by the processor **296A**. The instructions and/or data may include code to perform the techniques described herein. The memory **297A** may be a dynamic random-access memory (DRAM) device, a static random-access memory (SRAM) device, flash memory, or another memory device. In some embodiments, the memory **297A** also may include non-volatile memory or a similar permanent storage device and media, which may include a hard disk drive, a floppy disk drive, a CD-ROM device, a DVD-ROM device, a DVD-RAM device, a DVD-RW device, a flash memory device, or some other mass storage device for storing information on a permanent basis. A portion of the memory **297A** may be reserved for use as a buffer or virtual random-access memory (virtual RAM). The transport **276** may include one or more memories **297A** without deviating from the current solution.

The memory **297A** of the transport **276** may store one or more of the following types of data: navigation route data **295A**, and autonomous features data **294A**. In some embodiments, the memory **297A** stores data that may be necessary for the navigation application **295A** to provide the functions.

The navigation system **295A** may describe at least one navigation route including a start point and an endpoint. In some embodiments, the navigation system **295A** of the transport **276** receives a request from a user for navigation routes wherein the request includes a starting point and an ending point. The navigation system **295A** may query a real-time data server **293** (via a network **292**), such as a server that provides driving directions, for navigation route data corresponding to navigation routes, including the start point and the endpoint. The real-time data server **293** transmits the navigation route data to the transport **276** via a wireless network **292**, and the communication system **298A** stores the navigation data **295A** in the memory **297A** of the transport **276**.

The ECU **293A** controls the operation of many of the systems of the transport **276**, including the ADAS systems **294A**. The ECU **293A** may, responsive to instructions received from the navigation system **295A**, deactivate any

26

unsafe and/or unselected autonomous features for the duration of a journey controlled by the ADAS systems **294A**. In this way, the navigation system **295A** may control whether ADAS systems **294A** are activated or enabled so that they may be activated for a given navigation route.

The sensor set **292A** may include any sensors in the transport **276** generating sensor data. For example, the sensor set **292A** may include short-range sensors and long-range sensors. In some embodiments, the sensor set **292A** of the transport **276** may include one or more of the following vehicle sensors: a camera, a Lidar sensor, an ultrasonic sensor, an automobile engine sensor, a radar sensor, a laser altimeter, a manifold absolute pressure sensor, an infrared detector, a motion detector, a thermostat, a sound detector, a carbon monoxide sensor, a carbon dioxide sensor, an oxygen sensor, a mass airflow sensor, an engine coolant temperature sensor, a throttle position sensor, a crankshaft position sensor, a valve timer, an air-fuel ratio meter, a blind spot meter, a curb feeler, a defect detector, a Hall effect sensor, a parking sensor, a radar gun, a speedometer, a speed sensor, a tire-pressure monitoring sensor, a torque sensor, a transmission fluid temperature sensor, a turbine speed sensor (TSS), a variable reluctance sensor, a vehicle speed sensor (VSS), a water sensor, a wheel speed sensor, a GPS sensor, a mapping functionality, and any other type of automotive sensor. The navigation system **295A** may store the sensor data in the memory **297A**.

The communication unit **298A** transmits and receives data to and from the network **292** or to another communication channel. In some embodiments, the communication unit **298A** may include a DSRC transceiver, a DSRC receiver, and other hardware or software necessary to make the transport **276** a DSRC-equipped device.

The transport **276** may interact with other transports **277** via V2V technology. V2V communication includes sensing radar information corresponding to relative distances to external objects, receiving GPS information of the transports, setting areas as areas where the other transports **277** are located based on the sensed radar information, calculating probabilities that the GPS information of the object vehicles will be located at the set areas, and identifying transports and/or objects corresponding to the radar information and the GPS information of the object vehicles based on the calculated probabilities, in one example.

In one example, the solutions described and depicted herein can be utilized to manage emergency scenarios and transport features when a transport is determined to be entering an area without network access. In one example, the solutions can also be utilized to manage and provide features in a transport (such as audio, video, navigation, etc.) without network connection. In one example, the solutions can also be utilized to determine when a profile of a person in proximity to the transport matches profile attributes of a profile of at least one occupant in the transport. A notification is sent from the transport to establish communication.

In one example, the solutions can also be utilized to analyze the availability of occupants in respective transports that are available for a voice communication based on an amount of time remaining in the transport and context of the communication to be performed. In one example, the solutions can also be utilized to determine two levels of threat of roadway obstruction and receiving a gesture that may indicate that the obstruction is not rising to an alert above a threshold, and proceeding, by the transport along the roadway. In one example, the solutions can also be utilized to delete sensitive data from a transport when the transport has had damage such that it is rendered unable to be used.

In one example, the solutions can also be utilized to verify that the customer data to be removed has truly been removed from all of the required locations within the enterprise, demonstrating GDPR compliance. In one example, the solutions can also be utilized to provide consideration from one transport to another transport in exchange for data related to safety, important notifications, etc. to enhance the autonomous capabilities of the lower-level autonomous vehicle. In one example, the solutions can also be utilized to provide an ability for a transport to receive data based on a first biometric associated with an occupant. Then the transport unencrypts the encrypted data based on a verification of a second biometric, wherein the second biometric is a continuum of the first biometric. The transport provides the unencrypted data to the occupant when only the occupant can receive the unencrypted data and deletes a sensitive portion of the unencrypted data as the sensitive portion is being provided and a non-sensitive portion after a period of time associated with the biometric elapses. In one example, the solutions can also be utilized to provide an ability for a transport to validate an individual based on a weight and grip pressure applied to the steering wheel of the transport. In one example, the solutions can also be utilized to provide a feature to a car that exists but is not currently enabled, presenting features to an occupant of the automobile that reflects the occupant's characteristics.

In one example, the solutions can also be utilized to allow for the modification of a transport, particularly the interior of the transport and the exterior of the transport to reflect and assist at least one occupant, in one example. In another example, recreating an occupant's work and/or home environment is disclosed. The system may attempt to "recreate" the user's work/home environment while the user is in the transport if it determines that the user is in "work mode" or "home mode". All data relating to the interior and exterior of the transport as well as the various occupants utilizing the transport are stored on a blockchain and executed via smart contracts. In one example, the solutions can also be utilized to detect occupant gestures to assist in communicating with nearby transports wherein the transport may maneuver accordingly. In one example, the solutions can also be utilized to provide the ability for a transport to detect intended gestures using a gesture definition datastore. In one example, the solutions can also be utilized to provide an ability for a transport to take various actions based on a gait and a user's gesture. In one example, the solutions can also be utilized to ensure that a driver of a transport that is currently engaged in various operations (for example, driving while talking with navigation on, etc.) does not exceed an unsafe number of operations before being permitted to gesture.

In one example, the solutions can also be utilized to assign a status to each occupant in a transport and validating a gesture from an occupant based on the occupant's status. In one example, the solutions can also be utilized to collect details of sound related to a collision (in what location, in what direction, rising or falling, from what device, data associated with the device such as type, manufacturer, owner, as well as the number of contemporaneous sounds, and the times the sounds were emanated, etc.) and provide to the system where analysis of the data assists in determining details regarding the collision. In one example, the solutions can also be utilized to determine whether a transport is unsafe to operate. The transport includes multiple components that interoperate to control the transport, and each component is associated with a separate component key. A cryptographic key is sent to the transport to decrease

transport functionality. In response to receiving the cryptographic key, the transport disables one or more of the component keys. Disabling the one or more component keys results in one or more of limiting the transport to not move greater than a given speed, limiting the transport to not come closer than a distance to another transport, and limiting the transport to not travel greater than a threshold distance.

In one example, the solutions can also be utilized to provide an indication from one specific transport (that is about to vacate a location) to another specific transport (that is seeking to occupy a location), a blockchain is used to perform authentication and coordination. In one example, the solutions can also be utilized to determine a fractional responsibility for a transport. Such as the case where multiple people own a single transport, and the use of the transport, which may change over a period of time, is used by the system to update the fractional ownership. Other embodiments will be included in the application, including a minimal ownership of a transport based on not the use of the transport but the availability of the transport, and the determination of the driver of the transport as well as others.

In one example, the solutions can also be utilized to permit in a transport a user to his/her subscriptions with a closed group of people such as family members or friends. For example, a user might want to share a membership, and if so, associated transactions are stored in a blockchain or traditional database. When the subscribed materials are requested by a user, who is not a primary subscriber, a blockchain node (i.e., a transport) can verify that a person requesting a service is an authorized person with whom the subscriber has shared the profile. In one example, the solutions can also be utilized to allow a person to utilize supplemental transport(s) to arrive at an intended destination. A functional relationship value (e.g., value that indicates the various parameters and their importance in determining what type of alternate transport to utilize) is used in determining the supplemental transport. In one example, the solutions can also be utilized to allow the occupants in an accident to access other transports to continue to their initial destination.

In one example, the solutions can also be utilized to propagate a software/firmware upload to a first subset of transports. This first set of transports tests the update, and when the test is successful, the update is propagated to a further set of transports. In one example, the solutions can also be utilized to propagate software/firmware updates to vehicles from a master transport where the update is propagated through the network of vehicles from a first subset, then a larger subset, etc. A portion of the update may be first sent, then the remaining portion sent from the same or another vehicle. In one example, the solutions can also be utilized to provide an update for a transport's computer to the transport and a transport operator's/occupant's device. The update is maybe authorized by all drivers and/or all occupants. The software update is provided to the vehicle and the device(s). The user does not have to do anything but go proximate to the vehicle and the functionality automatically occurs. A notification is sent to the device(s) indicating that the software update is completed. In one example, the solutions can also be utilized to validate that an OTA software update is performed by a qualified technician and generation, by the one or more transport components, of a status related to an originator of the validation code, a procedure for wirelessly receiving the software update, information contained in the software update, and results of the validation.

In one example, the solutions can also be utilized to provide the ability to parse a software update located in a first component by a second component. Then verifying the first portion of critical updates and a second portion of non-critical updates, assigning the verified first portion to one process in the transport, running the verified first portion with the one process for a period of time, and responsive to positive results based on the period of time, running the verified first portion with other processes after the period of time. In one example, the solutions can also be utilized to provide a selection of services to an occupant where the services are based on a profile of an occupant of the transport, and a shared profile that is shared with the profile of the occupant. In one example, the solutions can also be utilized to store user profile data in a blockchain and intelligently present offers and recommendations to a user based on the user's automatically gathered history of purchases and preferences acquired from the user profile on the blockchain.

For a transport to be adequately secured, the transport must be protected from unauthorized physical access as well as unauthorized remote access (e.g., cyber-threats). To prevent unauthorized physical access, a transport is equipped with a secure access system such as a keyless entry in one example. Meanwhile, security protocols are added to a transport's computers and computer networks to facilitate secure remote communications to and from the transport in one example.

Electronic Control Units (ECUs) are nodes within a transport that control tasks such as activating the windshield wipers to tasks such as an anti-lock brake system. ECUs are often connected to one another through the transport's central network, which may be referred to as a CAN bus. State-of-the-art features such as autonomous driving are strongly reliant on implementing new, complex ECUs such as advanced driver-assistance systems (ADAS), sensors, and the like. While these new technologies have helped improve the safety and driving experience of a transport, they have also increased the number of externally-communicating units inside of the transport, making them more vulnerable to attack. Below are some examples of protecting the transport from physical intrusion and remote intrusion.

FIG. 2J illustrates a keyless entry system **290B** to prevent unauthorized physical access to a transport **291B**, according to example embodiments. Referring to FIG. 2J, a key fob **292B** transmits commands to a transport **291B** using radio frequency signals in one example. In this example, the key fob **292B** includes a transmitter **2921B** with an antenna that is capable of sending short-range wireless radio signals. The transport **291B** includes a receiver **2911B** with an antenna that is capable of receiving the short-range wireless signal transmitted from the transmitter **2921B**. The key fob **292B** and the transport **291B** also include CPUs **2922B** and **2913B**, respectively, which control the respective devices. Here, a memory of the CPUs **2922B** and **2913B** (or accessible to the CPUs). Each of the key fob **292B** and the transport **291B** includes power supplies **2924B** and **2915B** for powering the respective devices in one example.

When the user presses a button **293B** (or otherwise actuates the fob, etc.) on the key fob **292B**, the CPU **2922B** wakes up inside the key fob **292B** and sends a data stream to the transmitter **2921B**, which is output via the antenna. In other embodiments, the user's intent is acknowledged on the key fob **292B** via other means, such as via a microphone that accepts audio, a camera that captures images and/or video, or other sensors that are commonly utilized in the art to detect intent from a user including receiving gestures,

motion, eye movements, and the like. The data stream may be a 64-bit to 128-bit long signal, which includes one or more of a preamble, a command code, and a rolling code. The signal may be sent at a rate between 2 KHz and 20 KHz, but embodiments are not limited thereto. In response, the receiver **2911B** of the transport **291B** captures the signal from the transmitter **2921B**, demodulates the signal, and sends the data stream to the CPU **2913B**, which decodes the signal and sends commands (e.g., lock the door, unlock the door, etc.) to a command module **2912B**.

If the key fob **292B** and the transport **291B** use a fixed code between them, replay attacks can be performed. In this case, if the attacker can capture/sniff the fixed code during the short-range communication, the attacker could replay this code to gain entry into the transport **291B**. To improve security, the key fob and the transport **291B** may use a rolling code that changes after each use. Here, the key fob **292B** and the transport **291B** are synchronized with an initial seed **2923B** (e.g., a random number, pseudo-random number, etc.) This is referred to as pairing. The key fob **292B** and the transport **291B** also include a shared algorithm for modifying the initial seed **2914B** each time the button **293B** is pressed. The following keypress will take the result of the previous keypress as an input and transform it into the next number in the sequence. In some cases, the transport **291B** may store multiple next codes (e.g., **255** next codes) in case the keypress on the key fob **292B** is not detected by the transport **291B**. Thus, a number of keypress on the key fob **292B** that are unheard by the transport **291B** do not prevent the transport from becoming out of sync.

In addition to rolling codes, the key fob **292B** and the transport **291B** may employ other methods to make attacks even more difficult. For example, different frequencies may be used for transmitting the rolling codes. As another example, two-way communication between the transmitter **2921B** and the receiver **2911B** may be used to establish a secure session. As another example, codes may have limited expirations or timeouts. Further, the instant solution as described and depicted with respect to FIG. 2J can be utilized in this and other networks and/or systems, including those that are described and depicted herein.

FIG. 2K illustrates a CAN bus **290C** within a transport, according to example embodiments. Referring to FIG. 2K, the CAN **290C** includes a CAN bus **297C** with a high and low terminal and a plurality of electronic control units (ECUs) **291C**, **292C**, **293C**, etc. which are connected to the CAN bus **297C** via wired connections. The CAN bus **297C** is designed to allow microcontrollers and devices to communicate with each other in an application without a host computer. The CAN bus **297C** implements a message-based protocol (i.e., ISO 11898 standards) that allows ECUs **291C-293C** to send commands to one another at a root level. Meanwhile, the ECUs **291C-293C** represent controllers for controlling electrical systems or subsystems within the transport. Examples of the electrical systems include power steering, anti-lock brakes, air-conditioning, tire pressure monitoring, cruise control, and many other features.

In this example, the ECU **291C** includes a transceiver **2911C** and a microcontroller **2912C**. The transceiver may be used to transmit and receive messages to and from the CAN bus **297C**. For example, the transceiver **2911C** may convert the data from the microcontroller **2912C** into a format of the CAN bus **297C** and also convert data from the CAN bus **297C** into a format for the microcontroller **2912C**. Meanwhile, the microcontroller **2912C** interprets the messages and also decide what messages to send using ECU software installed therein in one example.

31

To protect the CAN 290C from cyber threats, various security protocols may be implemented. For example, sub-networks (e.g., sub-networks A and B, etc.) may be used to divide the CAN 290C into smaller sub-CANs and limit an attacker's capabilities to access the transport remotely. In the example of FIG. 2K, ECUs 291C and 292C may be part of a same sub-network, while ECU 293C is part of an independent sub-network. Furthermore, a firewall 294C (or gateway, etc.) may be added to block messages from crossing the CAN bus 297C across sub-networks. If an attacker gains access to one sub-network, the attacker will not have access to the entire network. To make sub-networks even more secure, the most critical ECUs are not placed on the same sub-network, in one example.

Although not shown in FIG. 2K, other examples of security controls within a CAN include an intrusion detection system (IDS) which can be added to each sub-network and read all data passing to detect malicious messages. If a malicious message is detected, the IDS can notify the automobile user. Other possible security protocols include encryption/security keys that can be used to obscure messages. As another example, authentication protocols are implemented that enables a message to authenticate itself, in one example.

In addition to protecting a transport's internal network, transports may also be protected when communicating with external networks such as the Internet. One of the benefits of having a transport connection to a data source such as the Internet is that information from the transport can be sent through a network to remote locations for analysis. Examples of transport information include GPS, onboard diagnostics, tire pressure, and the like. These communication systems are often referred to as telematics because they involve the combination of telecommunications and informatics. Further, the instant solution as described and depicted with respect to FIG. 2K can be utilized in this and other networks and/or systems, including those that are described and depicted herein.

FIG. 2L illustrates a secure end-to-end transport communication channel according to example embodiments. Referring to FIG. 2L, a telematics network 290D includes a transport 291D and a host server 295D that is disposed at a remote location (e.g., a web server, a cloud platform, a database, etc.) and connected to the transport 291D via a network such as the Internet. In this example, a device 296D associated with the host server 295D may be installed within the network inside the transport 291D. Furthermore, although not shown, the device 296D may connect to other elements of the transport 291D, such as the CAN bus, an onboard diagnostics (OBDII) port, a GPS system, a SIM card, a modem, and the like. The device 296D may collect data from any of these systems and transfer the data to the server 295D via the network.

Secure management of data begins with the transport 291D. In some embodiments, the device 296D may collect information before, during, and after a trip. The data may include GPS data, travel data, passenger information, diagnostic data, fuel data, speed data, and the like. However, the device 296D may only communicate the collected information back to the host server 295D in response to transport ignition and trip completion. Furthermore, communication may only be initiated by the device 296D and not by the host server 295D. As such, the device 296D will not accept communications initiated by outside sources in one example.

To perform the communication, the device 296D may establish a secured private network between the device

32

296D and the host server 295D. Here, the device 296D may include a tamper-proof SIM card that provides secure access to a carrier network 294D via a radio tower 292D. When preparing to transmit data to the host server 295D, the device 296D may establish a one-way secure connection with the host server 295D. The carrier network 294D may communicate with the host server 295D using one or more security protocols. As a non-limiting example, the carrier network 294D may communicate with the host server 295D via a VPN tunnel which allows access through a firewall 293D of the host server 295D. As another example, the carrier network 294D may use data encryption (e.g., AES encryption, etc.) when transmitting data to the host server 295D. In some cases, the system may use multiple security measures such as both a VPN and encryption to further secure the data.

In addition to communicating with external servers, transports may also communicate with each other. In particular, transport-to-transport (V2V) communication systems enable transports to communicate with each other, roadside infrastructures (e.g., traffic lights, signs, cameras, parking meters, etc.), and the like, over a wireless network. The wireless network may include one or more of Wi-Fi networks, cellular networks, dedicated short-range communication (DSRC) networks, and the like. Transports may use V2V communication to provide other transports with information about a transport's speed, acceleration, braking, and direction, to name a few. Accordingly, transports can receive insight into the conditions ahead before such conditions become visible, thus greatly reducing collisions. Further, the instant solution as described and depicted with respect to FIG. 2L can be utilized in this and other networks and/or systems, including those that are described and depicted herein.

FIG. 2M illustrates an example 290E of transports 293E and 292E performing secured V2V communications using security certificates, according to example embodiments. Referring to FIG. 2M, the transports 293E and 292E may communicate via V2V communications over a short-range network, a cellular network, or the like. Before sending messages, the transports 293E and 292E may sign the messages using a respective public key certificate. For example, the transport 293E may sign a V2V message using a public key certificate 294E. Likewise, the transport 292E may sign a V2V message using a public key certificate 295E. The public key certificates 294E and 295E are associated with the transports 293E and 292E, respectively, in one example.

Upon receiving the communications from each other, the transports may verify the signatures with a certificate authority 291E or the like. For example, the transport 292E may verify with the certificate authority 291E that the public key certificate 294E used by transport 293E to sign a V2V communication is authentic. If the transport 292E successfully verifies the public key certificate 294E, the transport knows that the data is from a legitimate source. Likewise, the transport 293E may verify with the certificate authority 291E that the public key certificate 295E used by the transport 292E to sign a V2V communication is authentic. Further, the instant solution as described and depicted with respect to FIG. 2M can be utilized in this and other networks and/or systems including those that are described and depicted herein.

FIG. 2N illustrates yet a further diagram 290F depicting an example of a transport interacting with a security processor and a wireless device, according to example embodiments. In some embodiments, the computer 224 shown in FIG. 2B may include security processor 292F as shown in

33

the process 290F of the example of FIG. 2N. In particular, the security processor 292F may perform authorization, authentication, cryptography (e.g., encryption), and the like, for data transmissions that are sent between ECUs and other devices on a CAN bus of a vehicle, and also data messages that are transmitted between different vehicles.

In the example of FIG. 2N, the security processor 292F may include an authorization module 293F, an authentication module 294F, and a cryptography module 295F. The security processor 292F may be implemented within the transport's computer and may communicate with other transport elements, for example, the ECUs/CAN network 296F, wired and wireless devices 298F such as wireless network interfaces, input ports, and the like. The security processor 292F may ensure that data frames (e.g., CAN frames, etc.) that are transmitted internally within a transport (e.g., via the ECUs/CAN network 296F) are secure. Likewise, the security processor 292F can ensure that messages transmitted between different transports and devices attached or connected via a wire to the transport's computer are also secured.

For example, the authorization module 293F may store passwords, usernames, PIN codes, biometric scans, and the like for different transport users. The authorization module 293F may determine whether a user (or technician) has permission to access certain settings such as a transport's computer. In some embodiments, the authorization module may communicate with a network interface to download any necessary authorization information from an external server. When a user desires to make changes to the transport settings or modify technical details of the transport via a console or GUI within the transport or via an attached/connected device, the authorization module 293F may require the user to verify themselves in some way before such settings are changed. For example, the authorization module 293F may require a username, a password, a PIN code, a biometric scan, a predefined line drawing or gesture, and the like. In response, the authorization module 293F may determine whether the user has the necessary permissions (access, etc.) being requested.

The authentication module 294F may be used to authenticate internal communications between ECUs on the CAN network of the vehicle. As an example, the authentication module 294F may provide information for authenticating communications between the ECUS. As an example, the authentication module 294F may transmit a bit signature algorithm to the ECUs of the CAN network. The ECUs may use the bit signature algorithm to insert authentication bits into the CAN fields of the CAN frame. All ECUs on the CAN network typically receive each CAN frame. The bit signature algorithm may dynamically change the position, amount, etc., of authentication bits each time a new CAN frame is generated by one of the ECUs. The authentication module 294F may also provide a list of ECUs that are exempt (safe list) and that do not need to use the authentication bits. The authentication module 294F may communicate with a remote server to retrieve updates to the bit signature algorithm and the like.

The encryption module 295F may store asymmetric key pairs to be used by the transport to communicate with other external user devices and transports. For example, the encryption module 295F may provide a private key to be used by the transport to encrypt/decrypt communications, while the corresponding public key may be provided to other user devices and transports to enable the other devices to decrypt/encrypt the communications. The encryption module 295F may communicate with a remote server to receive

34

new keys, updates to keys, keys of new transports, users, etc., and the like. The encryption module 295F may also transmit any updates to a local private/public key pair to the remote server.

FIG. 3A illustrates a flow diagram 300, according to example embodiments. Referring to FIG. 3A, the flow diagram includes one or more of obtaining, by a server, a certificate from an IoT device associated with a vehicle 302, determining, by the server, the certificate is not a revoked certificate 304, assigning, by the server, a temporary certificate to the IoT device 306, and validating, by the server, the temporary certificate 308.

FIG. 3B illustrates another flow diagram 320, according to example embodiments. Referring to FIG. 3B, the flow diagram includes one or more of receiving a request, from the IoT device, to access the server, where the request includes a time period to access the server, requesting the certificate from the IoT device, and validating the temporary certificate 322, determining the certificate is not included within a revoked certificate list and one or more of the certificate is being used within a predetermined time period, and the certificate is being used in an approved application on the IoT device 323, associating the IoT device with a running vehicle, creating a temporary certificate corresponding to the IoT device, and adding the temporary certificate to a temporary certificate revocation list 324, determining the temporary certificate has not been used, determining the temporary certificate is not in a revocation list, and authorizing use of the temporary certificate for a time period 325, providing the validated temporary certificate in place of an original certificate for a time period, based on an amount of time to validate the original certificate each time a connection to an entity is required 326, and determining a time period associated with the temporary certificate has expired, notifying the IoT device the temporary certificate has expired, determining the certificate is not a revoked certificate, assigning a single-use temporary certificate to the IoT device, and validating the single-use temporary certificate 327.

FIG. 3C illustrates yet another flow diagram 340, according to example embodiments. Referring to FIG. 3C, the flow diagram includes one or more of receiving a confirmation of an event from one or more elements described or depicted herein, wherein the confirmation comprises a blockchain consensus between peers represented by any of the elements 342 and executing a smart contract to record the confirmation on a blockchain-based on the blockchain consensus 344.

FIG. 4 illustrates a machine learning transport network diagram 400, according to example embodiments. The network 400 includes a transport 402 that interfaces with a machine learning subsystem 406. The transport includes one or more sensors 404.

The machine learning subsystem 406 contains a learning model 408, which is a mathematical artifact created by a machine learning training system 410 that generates predictions by finding patterns in one or more training data sets. In some embodiments, the machine learning subsystem 406 resides in the transport 402. In other embodiments, the machine learning subsystem 406 resides outside of the transport 402.

The transport 402 sends data from the one or more sensors 404 to the machine learning subsystem 406. The machine learning subsystem 406 provides the one or more sensor 404 data to the learning model 408, which returns one or more predictions. The machine learning subsystem 406 sends one

35

or more instructions to the transport **402** based on the predictions from the learning model **408**.

In a further embodiment, the transport **402** may send the one or more sensor **404** data to the machine learning training system **410**. In yet another example, the machine learning subsystem **406** may send the sensor **404** data to the machine learning subsystem **410**. One or more of the applications, features, steps, solutions, etc., described and/or depicted herein may utilize the machine learning network **400** as described herein.

FIG. 5A illustrates an example vehicle configuration **500** for managing database transactions associated with a vehicle, according to example embodiments. Referring to FIG. 5A, as a particular transport/vehicle **525** is engaged in transactions (e.g., vehicle service, dealer transactions, delivery/pickup, transportation services, etc.), the vehicle may receive assets **510** and/or expel/transfer assets **512** according to a transaction(s). A transport processor **526** resides in the vehicle **525** and communication exists between the transport processor **526**, a database **530**, a transport processor **526** and the transaction module **520**. The transaction module **520** may record information, such as assets, parties, credits, service descriptions, date, time, location, results, notifications, unexpected events, etc. Those transactions in the transaction module **520** may be replicated into a database **530**. The database **530** can be one of a SQL database, an RDBMS, a relational database, a non-relational database, a blockchain, a distributed ledger, and may be on board the transport, may be off-board the transport, may be accessed directly and/or through a network, or be accessible to the transport.

FIG. 5B illustrates an example vehicle configuration **550** for managing database transactions conducted among various vehicles, according to example embodiments. The vehicle **525** may engage with another vehicle **508** to perform various actions such as to share, transfer, acquire service calls, etc. when the vehicle has reached a status where the services need to be shared with another vehicle. For example, the vehicle **508** may be due for a battery charge and/or may have an issue with a tire and may be in route to pick up a package for delivery. A transport processor **528** resides in the vehicle **508** and communication exists between the transport processor **528**, a database **554**, and the transaction module **552**. The vehicle **508** may notify another vehicle **525**, which is in its network and which operates on its blockchain member service. A transport processor **526** resides in the vehicle **525** and communication exists between the transport processor **526**, a database **530**, the transport processor **526** and a transaction module **520**. The vehicle **525** may then receive the information via a wireless communication request to perform the package pickup from the vehicle **508** and/or from a server (not shown). The transactions are logged in the transaction modules **552** and **520** of both vehicles. The credits are transferred from vehicle **508** to vehicle **525** and the record of the transferred service is logged in the database **530/554** assuming that the blockchains are different from one another, or are logged in the same blockchain used by all members. The database **554** can be one of a SQL database, an RDBMS, a relational database, a non-relational database, a blockchain, a distributed ledger, and may be on board the transport, may be off-board the transport, may be accessible directly and/or through a network.

FIG. 6A illustrates a blockchain architecture configuration **600**, according to example embodiments. Referring to FIG. 6A, the blockchain architecture **600** may include certain blockchain elements, for example, a group of blockchain

36

member nodes **602-606** as part of a blockchain group **610**. In one example embodiment, a permissioned blockchain is not accessible to all parties but only to those members with permissioned access to the blockchain data. The blockchain nodes participate in a number of activities, such as blockchain entry addition and validation process (consensus). One or more of the blockchain nodes may endorse entries based on an endorsement policy and may provide an ordering service for all blockchain nodes. A blockchain node may initiate a blockchain action (such as an authentication) and seek to write to a blockchain immutable ledger stored in the blockchain, a copy of which may also be stored on the underpinning physical infrastructure.

The blockchain transactions **620** are stored in memory of computers as the transactions are received and approved by the consensus model dictated by the members' nodes. Approved transactions **626** are stored in current blocks of the blockchain and committed to the blockchain via a committal procedure, which includes performing a hash of the data contents of the transactions in a current block and referencing a previous hash of a previous block. Within the blockchain, one or more smart contracts **630** may exist that define the terms of transaction agreements and actions included in smart contract executable application code **632**, such as registered recipients, vehicle features, requirements, permissions, sensor thresholds, etc. The code may be configured to identify whether requesting entities are registered to receive vehicle services, what service features they are entitled/required to receive given their profile statuses and whether to monitor their actions in subsequent events. For example, when a service event occurs and a user is riding in the vehicle, the sensor data monitoring may be triggered, and a certain parameter, such as a vehicle charge level, may be identified as being above/below a particular threshold for a particular period of time, then the result may be a change to a current status, which requires an alert to be sent to the managing party (i.e., vehicle owner, vehicle operator, server, etc.) so the service can be identified and stored for reference. The vehicle sensor data collected may be based on types of sensor data used to collect information about vehicle's status. The sensor data may also be the basis for the vehicle event data **634**, such as a location(s) to be traveled, an average speed, a top speed, acceleration rates, whether there were any collisions, was the expected route taken, what is the next destination, whether safety measures are in place, whether the vehicle has enough charge/fuel, etc. All such information may be the basis of smart contract terms **630**, which are then stored in a blockchain. For example, sensor thresholds stored in the smart contract can be used as the basis for whether a detected service is necessary and when and where the service should be performed.

FIG. 6B illustrates a shared ledger configuration, according to example embodiments. Referring to FIG. 6B, the blockchain logic example **640** includes a blockchain application interface **642** as an API or plug-in application that links to the computing device and execution platform for a particular transaction. The blockchain configuration **640** may include one or more applications, which are linked to application programming interfaces (APIs) to access and execute stored program/application code (e.g., smart contract executable code, smart contracts, etc.), which can be created according to a customized configuration sought by participants and can maintain their own state, control their own assets, and receive external information. This can be deployed as an entry and installed, via appending to the distributed ledger, on all blockchain nodes.

The smart contract application code **644** provides a basis for the blockchain transactions by establishing application code, which when executed causes the transaction terms and conditions to become active. The smart contract **630**, when executed, causes certain approved transactions **626** to be generated, which are then forwarded to the blockchain platform **652**. The platform includes a security/authorization **658**, computing devices, which execute the transaction management **656** and a storage portion **654** as a memory that stores transactions and smart contracts in the blockchain.

The blockchain platform may include various layers of blockchain data, services (e.g., cryptographic trust services, virtual execution environment, etc.), and underpinning physical computer infrastructure that may be used to receive and store new entries and provide access to auditors, which are seeking to access data entries. The blockchain may expose an interface that provides access to the virtual execution environment necessary to process the program code and engage the physical infrastructure. Cryptographic trust services may be used to verify entries such as asset exchange entries and keep information private.

The blockchain architecture configuration of FIGS. **6A** and **6B** may process and execute program/application code via one or more interfaces exposed, and services provided, by the blockchain platform. As a non-limiting example, smart contracts may be created to execute reminders, updates, and/or other notifications subject to the changes, updates, etc. The smart contracts can themselves be used to identify rules associated with authorization and access requirements and usage of the ledger. For example, the information may include a new entry, which may be processed by one or more processing entities (e.g., processors, virtual machines, etc.) included in the blockchain layer. The result may include a decision to reject or approve the new entry based on the criteria defined in the smart contract and/or a consensus of the peers. The physical infrastructure may be utilized to retrieve any of the data or information described herein.

Within smart contract executable code, a smart contract may be created via a high-level application and programming language, and then written to a block in the blockchain. The smart contract may include executable code that is registered, stored, and/or replicated with a blockchain (e.g., distributed network of blockchain peers). An entry is an execution of the smart contract code, which can be performed in response to conditions associated with the smart contract being satisfied. The executing of the smart contract may trigger a trusted modification(s) to a state of a digital blockchain ledger. The modification(s) to the blockchain ledger caused by the smart contract execution may be automatically replicated throughout the distributed network of blockchain peers through one or more consensus protocols.

The smart contract may write data to the blockchain in the format of key-value pairs. Furthermore, the smart contract code can read the values stored in a blockchain and use them in application operations. The smart contract code can write the output of various logic operations into the blockchain. The code may be used to create a temporary data structure in a virtual machine or other computing platform. Data written to the blockchain can be public and/or can be encrypted and maintained as private. The temporary data that is used/generated by the smart contract is held in memory by the supplied execution environment, then deleted once the data needed for the blockchain is identified.

A smart contract executable code may include the code interpretation of a smart contract, with additional features.

As described herein, the smart contract executable code may be program code deployed on a computing network, where it is executed and validated by chain validators together during a consensus process. The smart contract executable code receives a hash and retrieves from the blockchain a hash associated with the data template created by use of a previously stored feature extractor. If the hashes of the hash identifier and the hash created from the stored identifier template data match, then the smart contract executable code sends an authorization key to the requested service. The smart contract executable code may write to the blockchain data associated with the cryptographic details.

FIG. **6C** illustrates a blockchain configuration for storing blockchain transaction data, according to example embodiments. Referring to FIG. **6C**, the example configuration **660** provides for the vehicle **662**, the user device **664** and a server **666** sharing information with a distributed ledger (i.e., blockchain) **668**. The server may represent a service provider entity inquiring with a vehicle service provider to share user profile rating information in the event that a known and established user profile is attempting to rent a vehicle with an established rated profile. The server **666** may be receiving and processing data related to a vehicle's service requirements. As the service events occur, such as the vehicle sensor data indicates a need for fuel/charge, a maintenance service, etc., a smart contract may be used to invoke rules, thresholds, sensor information gathering, etc., which may be used to invoke the vehicle service event. The blockchain transaction data **670** is saved for each transaction, such as the access event, the subsequent updates to a vehicle's service status, event updates, etc. The transactions may include the parties, the requirements (e.g., 18 years of age, service eligible candidate, valid driver's license, etc.), compensation levels, the distance traveled during the event, the registered recipients permitted to access the event and host a vehicle service, rights/permissions, sensor data retrieved during the vehicle event operation to log details of the next service event and identify a vehicle's condition status, and thresholds used to make determinations about whether the service event was completed and whether the vehicle's condition status has changed.

FIG. **6D** illustrates blockchain blocks **680** that can be added to a distributed ledger, according to example embodiments, and contents of block structures **682A** to **682N**. Referring to FIG. **6D**, clients (not shown) may submit entries to blockchain nodes to enact activity on the blockchain. As an example, clients may be applications that act on behalf of a requester, such as a device, person or entity to propose entries for the blockchain. The plurality of blockchain peers (e.g., blockchain nodes) may maintain a state of the blockchain network and a copy of the distributed ledger. Different types of blockchain nodes/peers may be present in the blockchain network including endorsing peers, which simulate and endorse entries proposed by clients and committing peers which verify endorsements, validate entries, and commit entries to the distributed ledger. In this example, the blockchain nodes may perform the role of endorser node, committer node, or both.

The instant system includes a blockchain that stores immutable, sequenced records in blocks, and a state database (current world state) maintaining a current state of the blockchain. One distributed ledger may exist per channel and each peer maintains its own copy of the distributed ledger for each channel of which they are a member. The instant blockchain is an entry log, structured as hash-linked blocks where each block contains a sequence of N entries. Blocks may include various components such as those

shown in FIG. 6D. The linking of the blocks may be generated by adding a hash of a prior block's header within a block header of a current block. In this way, all entries on the blockchain are sequenced and cryptographically linked together preventing tampering with blockchain data without breaking the hash links. Furthermore, because of the links, the latest block in the blockchain represents every entry that has come before it. The instant blockchain may be stored on a peer file system (local or attached storage), which supports an append-only blockchain workload.

The current state of the blockchain and the distributed ledger may be stored in the state database. Here, the current state data represents the latest values for all keys ever included in the chain entry log of the blockchain. Smart contract executable code invocations execute entries against the current state in the state database. To make these smart contract executable code interactions extremely efficient, the latest values of all keys are stored in the state database. The state database may include an indexed view into the entry log of the blockchain, it can therefore be regenerated from the chain at any time. The state database may automatically get recovered (or generated if needed) upon peer startup, before entries are accepted.

Endorsing nodes receive entries from clients and endorse the entry based on simulated results. Endorsing nodes hold smart contracts, which simulate the entry proposals. When an endorsing node endorses an entry, the endorsing nodes creates an entry endorsement, which is a signed response from the endorsing node to the client application indicating the endorsement of the simulated entry. The method of endorsing an entry depends on an endorsement policy that may be specified within smart contract executable code. An example of an endorsement policy is "the majority of endorsing peers must endorse the entry." Different channels may have different endorsement policies. Endorsed entries are forward by the client application to an ordering service.

The ordering service accepts endorsed entries, orders them into a block, and delivers the blocks to the committing peers. For example, the ordering service may initiate a new block when a threshold of entries has been reached, a timer times out, or another condition. In this example, blockchain node is a committing peer that has received a data block **682A** for storage on the blockchain. The ordering service may be made up of a cluster of orderers. The ordering service does not process entries, smart contracts, or maintain the shared ledger. Rather, the ordering service may accept the endorsed entries and specifies the order in which those entries are committed to the distributed ledger. The architecture of the blockchain network may be designed such that the specific implementation of 'ordering' (e.g., Solo, Kafka, BFT, etc.) becomes a pluggable component.

Entries are written to the distributed ledger in a consistent order. The order of entries is established to ensure that the updates to the state database are valid when they are committed to the network. Unlike a cryptocurrency blockchain system (e.g., Bitcoin, etc.) where ordering occurs through the solving of a cryptographic puzzle, or mining, in this example the parties of the distributed ledger may choose the ordering mechanism that best suits that network.

Referring to FIG. 6D, a block **682A** (also referred to as a data block) that is stored on the blockchain and/or the distributed ledger may include multiple data segments such as a block header **684A** to **684n**, transaction-specific data **686A** to **686n**, and block metadata **688A** to **688n**. It should be appreciated that the various depicted blocks and their contents, such as block **682A** and its contents are merely for purposes of an example and are not meant to limit the scope

of the example embodiments. In some cases, both the block header **684A** and the block metadata **688A** may be smaller than the transaction-specific data **686A**, which stores entry data; however, this is not a requirement. The block **682A** may store transactional information of *N* entries (e.g., **100**, **500**, **1000**, **2000**, **3000**, etc.) within the block data **690A** to **690n**. The block **682A** may also include a link to a previous block (e.g., on the blockchain) within the block header **684A**. In particular, the block header **684A** may include a hash of a previous block's header. The block header **684A** may also include a unique block number, a hash of the block data **690A** of the current block **682A**, and the like. The block number of the block **682A** may be unique and assigned in an incremental/sequential order starting from zero. The first block in the blockchain may be referred to as a genesis block, which includes information about the blockchain, its members, the data stored therein, etc.

The block data **690A** may store entry information of each entry that is recorded within the block. For example, the entry data may include one or more of a type of the entry, a version, a timestamp, a channel ID of the distributed ledger, an entry ID, an epoch, a payload visibility, a smart contract executable code path (deploy tx), a smart contract executable code name, a smart contract executable code version, input (smart contract executable code and functions), a client (creator) identify such as a public key and certificate, a signature of the client, identities of endorsers, endorser signatures, a proposal hash, smart contract executable code events, response status, namespace, a read set (list of key and version read by the entry, etc.), a write set (list of key and value, etc.), a start key, an end key, a list of keys, a Merkel tree query summary, and the like. The entry data may be stored for each of the *N* entries.

In some embodiments, the block data **690A** may also store transaction-specific data **686A**, which adds additional information to the hash-linked chain of blocks in the blockchain. Accordingly, the data **686A** can be stored in an immutable log of blocks on the distributed ledger. Some of the benefits of storing such data **686A** are reflected in the various embodiments disclosed and depicted herein. The block metadata **688A** may store multiple fields of metadata (e.g., as a byte array, etc.). Metadata fields may include signature on block creation, a reference to a last configuration block, an entry filter identifying valid and invalid entries within the block, last offset persisted of an ordering service that ordered the block, and the like. The signature, the last configuration block, and the orderer metadata may be added by the ordering service. Meanwhile, a committer of the block (such as a blockchain node) may add validity/invalidity information based on an endorsement policy, verification of read/write sets, and the like. The entry filter may include a byte array of a size equal to the number of entries in the block data **610A** and a validation code identifying whether an entry was valid/invalid.

The other blocks **682B** to **682n** in the blockchain also have headers, files, and values. However, unlike the first block **682A**, each of the headers **684A** to **684n** in the other blocks includes the hash value of an immediately preceding block. The hash value of the immediately preceding block may be just the hash of the header of the previous block or may be the hash value of the entire previous block. By including the hash value of a preceding block in each of the remaining blocks, a trace can be performed from the *N*th block back to the genesis block (and the associated original file) on a block-by-block basis, as indicated by arrows **692**, to establish an auditable and immutable chain-of-custody.

The above embodiments may be implemented in hardware, in a computer program executed by a processor, in firmware, or in a combination of the above. A computer program may be embodied on a computer readable medium, such as a storage medium. For example, a computer program may reside in random access memory ("RAM"), flash memory, read-only memory ("ROM"), erasable programmable read-only memory ("EPROM"), electrically erasable programmable read-only memory ("EEPROM"), registers, hard disk, a removable disk, a compact disk read-only memory ("CD-ROM"), or any other form of storage medium known in the art.

An exemplary storage medium may be coupled to the processor such that the processor may read information from, and write information to, the storage medium. In the alternative, the storage medium may be integral to the processor. The processor and the storage medium may reside in an application-specific integrated circuit ("ASIC"). In the alternative, the processor and the storage medium may reside as discrete components. For example, FIG. 7 illustrates an example computer system architecture 700, which may represent or be integrated in any of the above-described components, etc.

FIG. 7 is not intended to suggest any limitation as to the scope of use or functionality of embodiments of the application described herein. Regardless, the computing node 700 is capable of being implemented and/or performing any of the functionality set forth hereinabove.

In computing node 700 there is a computer system/server 702, which is operational with numerous other general purpose or special purpose computing system environments or configurations. Examples of well-known computing systems, environments, and/or configurations that may be suitable for use with computer system/server 702 include, but are not limited to, personal computer systems, server computer systems, thin clients, thick clients, hand-held or laptop devices, multiprocessor systems, microprocessor-based systems, set-top boxes, programmable consumer electronics, network PCs, minicomputer systems, mainframe computer systems, and distributed cloud computing environments that include any of the above systems or devices, and the like.

Computer system/server 702 may be described in the general context of computer system-executable instructions, such as program modules, being executed by a computer system. Generally, program modules may include routines, programs, objects, components, logic, data structures, and so on that perform particular tasks or implement particular abstract data types. Computer system/server 702 may be practiced in distributed cloud computing environments where tasks are performed by remote processing devices that are linked through a communications network. In a distributed cloud computing environment, program modules may be located in both local and remote computer system storage media including memory storage devices.

As shown in FIG. 7, computer system/server 702 in cloud computing node 700 is shown in the form of a general-purpose computing device. The components of computer system/server 702 may include, but are not limited to, one or more processors or processing units 704, a system memory 706, and a bus that couples various system components including system memory 706 to processor 704.

The bus represents one or more of any of several types of bus structures, including a memory bus or memory controller, a peripheral bus, an accelerated graphics port, and a processor or local bus using any of a variety of bus architectures. By way of example, and not limitation, such architectures include Industry Standard Architecture (ISA)

bus, Micro Channel Architecture (MCA) bus, Enhanced ISA (EISA) bus, Video Electronics Standards Association (VESA) local bus, and Peripheral Component Interconnects (PCI) bus.

Computer system/server 702 typically includes a variety of computer system readable media. Such media may be any available media that is accessible by computer system/server 702, and it includes both volatile and non-volatile media, removable and non-removable media. System memory 706, in one example, implements the flow diagrams of the other figures. The system memory 706 can include computer system readable media in the form of volatile memory, such as random-access memory (RAM) 708 and/or cache memory 710. Computer system/server 702 may further include other removable/non-removable, volatile/non-volatile computer system storage media. By way of example only, memory 706 can be provided for reading from and writing to a non-removable, non-volatile magnetic media (not shown and typically called a "hard drive"). Although not shown, a magnetic disk drive for reading from and writing to a removable, non-volatile magnetic disk (e.g., a "floppy disk"), and an optical disk drive for reading from or writing to a removable, non-volatile optical disk such as a CD-ROM, DVD-ROM or other optical media can be provided. In such instances, each can be connected to the bus by one or more data media interfaces. As will be further depicted and described below, memory 706 may include at least one program product having a set (e.g., at least one) of program modules that are configured to carry out the functions of various embodiments of the application.

Program/utility, having a set (at least one) of program modules, may be stored in memory 706 by way of example, and not limitation, as well as an operating system, one or more application programs, other program modules, and program data. Each of the operating system, one or more application programs, other program modules, and program data or some combination thereof, may include an implementation of a networking environment. Program modules generally carry out the functions and/or methodologies of various embodiments of the application as described herein.

As will be appreciated by one skilled in the art, aspects of the present application may be embodied as a system, method, or computer program product. Accordingly, aspects of the present application may take the form of an entirely hardware embodiment, an entirely software embodiment (including firmware, resident software, micro-code, etc.) or an embodiment combining software and hardware aspects that may all generally be referred to herein as a "circuit," "module" or "system." Furthermore, aspects of the present application may take the form of a computer program product embodied in one or more computer readable medium(s) having computer readable program code embodied thereon.

Computer system/server 702 may also communicate with one or more external devices via an I/O device 712 (such as an I/O adapter), which may include a keyboard, a pointing device, a display, a voice recognition module, etc., one or more devices that enable a user to interact with computer system/server 702, and/or any devices (e.g., network card, modem, etc.) that enable computer system/server 702 to communicate with one or more other computing devices. Such communication can occur via I/O interfaces of the device 712. Still yet, computer system/server 702 can communicate with one or more networks such as a local area network (LAN), a general wide area network (WAN), and/or a public network (e.g., the Internet) via a network adapter. As depicted, device 712 communicates with the other com-

ponents of computer system/server 702 via a bus. It should be understood that although not shown, other hardware and/or software components could be used in conjunction with computer system/server 702. Examples, include, but are not limited to: microcode, device drivers, redundant processing units, external disk drive arrays, RAID systems, tape drives, and data archival storage systems, etc.

Although an exemplary embodiment of at least one of a system, method, and non-transitory computer readable medium has been illustrated in the accompanied drawings and described in the foregoing detailed description, it will be understood that the application is not limited to the embodiments disclosed, but is capable of numerous rearrangements, modifications, and substitutions as set forth and defined by the following claims. For example, the capabilities of the system of the various figures can be performed by one or more of the modules or components described herein or in a distributed architecture and may include a transmitter, receiver or pair of both. For example, all or part of the functionality performed by the individual modules, may be performed by one or more of these modules. Further, the functionality described herein may be performed at various times and in relation to various events, internal or external to the modules or components. Also, the information sent between various modules can be sent between the modules via at least one of: a data network, the Internet, a voice network, an Internet Protocol network, a wireless device, a wired device and/or via plurality of protocols. Also, the messages sent or received by any of the modules may be sent or received directly and/or via one or more of the other modules.

One skilled in the art will appreciate that a “system” could be embodied as a personal computer, a server, a console, a personal digital assistant (PDA), a cell phone, a tablet computing device, a smartphone or any other suitable computing device, or combination of devices. Presenting the above-described functions as being performed by a “system” is not intended to limit the scope of the present application in any way but is intended to provide one example of many embodiments. Indeed, methods, systems and apparatuses disclosed herein may be implemented in localized and distributed forms consistent with computing technology.

It should be noted that some of the system features described in this specification have been presented as modules to more particularly emphasize their implementation independence. For example, a module may be implemented as a hardware circuit comprising custom very-large-scale integration (VLSI) circuits or gate arrays, off-the-shelf semiconductors such as logic chips, transistors, or other discrete components. A module may also be implemented in programmable hardware devices such as field-programmable gate arrays, programmable array logic, programmable logic devices, graphics processing units, or the like.

A module may also be at least partially implemented in software for execution by various types of processors. An identified unit of executable code may, for instance, comprise one or more physical or logical blocks of computer instructions that may, for instance, be organized as an object, procedure, or function. Nevertheless, the executables of an identified module need not be physically located together but may comprise disparate instructions stored in different locations that, when joined logically together, comprise the module and achieve the stated purpose for the module. Further, modules may be stored on a computer-readable medium, which may be, for instance, a hard disk drive, flash device, random access memory (RAM), tape, or any other such medium used to store data.

Indeed, a module of executable code could be a single instruction, or many instructions, and may even be distributed over several different code segments, among different programs, and across several memory devices. Similarly, operational data may be identified and illustrated herein within modules and may be embodied in any suitable form and organized within any suitable type of data structure. The operational data may be collected as a single data set or may be distributed over different locations, including over different storage devices, and may exist, at least partially, merely as electronic signals on a system or network.

It will be readily understood that the components of the application, as generally described and illustrated in the figures herein, may be arranged and designed in a wide variety of different configurations. Thus, the detailed description of the embodiments is not intended to limit the scope of the application as claimed but is merely representative of selected embodiments of the application.

One having ordinary skill in the art will readily understand that the above may be practiced with steps in a different order and/or with hardware elements in configurations that are different from those which are disclosed. Therefore, although the application has been described based upon these preferred embodiments, it would be apparent to those of skill in the art that certain modifications, variations, and alternative constructions would be apparent.

While preferred embodiments of the present application have been described, it is to be understood that the embodiments described are illustrative only and the scope of the application is to be defined solely by the appended claims when considered with a full range of equivalents and modifications (e.g., protocols, hardware devices, software platforms etc.) thereto.

What is claimed is:

1. A method, comprising:

obtaining, by a server, a request from an IoT device associated with a running vehicle;

assigning, by the server, a temporary certificate to the IoT device based on the request and storing the temporary certificate within a list in a memory device of the server along with an indicator which indicates the temporary certificate has not been used, wherein the IoT device and the temporary certificate are associated with the running vehicle;

determining a temporary period of time for which the temporary certificate is valid based on a purpose included in the request;

validating, by the server, that the temporary certificate is not on a list of revoked certificates stored within the memory device;

in response to successful validation, modifying the indicator of the temporary certificate within the list in the memory device to indicate that the temporary certificate has been used;

receiving an additional request from the IoT device, where the additional request includes the validated temporary certificate;

validating, by the server, that the validated temporary certificate is being received within the temporary period of time; and

in response to successful validation of the validated temporary certificate, processing the additional request from the IoT device by the server.

2. The method of claim 1, wherein the assigning comprises determining that the certificate is not a revoked certificate based on the list of revoked certificates.

45

3. The method of claim 1, wherein the validating the temporary certificate comprises:

determining the temporary certificate is not in a revocation list; and

authorizing use of the temporary certificate for the temporary period of time.

4. The method of claim 1, comprising:
providing the validated temporary certificate in place of an original certificate for a time period.

5. The method of claim 1, comprising:
determining the temporary period of time has expired;
notifying the IoT device the temporary certificate has expired;

assigning a single-use temporary certificate to the IoT device; and

validating the single-use temporary certificate.

6. A system, comprising:

a processor; and

a memory, coupled to the processor, comprising instructions that when executed by the processor are configured to:

obtain, by a server, a request from an IoT device associated with a running vehicle;

assign, by the server, a temporary certificate to the IoT device based on the request and store the temporary certificate within a list in a memory device of the server along with an indicator which indicates the temporary certificate has not been used, wherein the IoT device and the temporary certificate are associated with the running vehicle;

determine a temporary period of time for which the temporary certificate is valid based on a purpose included in the request;

validate, by the server, that the temporary certificate is not on a list of revoked certificates stored within the memory device;

in response to successful validation, modify the indicator of the temporary certificate within the list in the memory device to indicate that the temporary certificate has been used;

receive an additional request from the IoT device, where the additional request includes the validated temporary certificate;

validate, by the server, that the validated temporary certificate is being received within the temporary period of time; and

in response to successful validation of the validated temporary certificate, process the additional request from the IoT device by the server.

7. The method of claim 1, comprising:

receiving an additional request to validate the temporary certificate; and

authorizing the additional request without checking the list of revoked certificates stored within the memory device of the server based on the indicator indicating the temporary certificate has been used.

8. The system of claim 6, wherein the processor is configured to determine the certificate is not revoked based on the list of revoked certificates.

9. The system of claim 6, wherein the processor is configured to:

determine the temporary certificate is not in a revocation list; and

46

authorize use of the temporary certificate for the temporary period of time.

10. The system of claim 6, wherein the instructions are configured to:

provide the validated temporary certificate in place of an original certificate for a time period.

11. The system of claim 6, wherein the instructions are configured to:

determine the temporary period of time has expired;

notify the IoT device the temporary certificate has expired;

assign a single-use temporary certificate to the IoT device; and

validate the single-use temporary certificate.

12. A non-transitory computer readable storage medium comprising instructions, that when read by a processor, cause the processor to perform:

obtaining, by a server, a request from an IoT device associated with a running vehicle;

assigning, by the server, a temporary certificate to the IoT device based on the request and storing the temporary certificate within a list in a memory device of the server along with an indicator which indicates the temporary certificate has not been used, wherein the IoT device and the temporary certificate are associated with the running vehicle;

determining a temporary period of time for which the temporary certificate is valid based on a purpose included in the request;

validating, by the server, that the temporary certificate is not on a list of revoked certificates stored within the memory device;

in response to successful validation, modifying the indicator of the temporary certificate within the list in the memory device to indicate that the temporary certificate has been used;

receiving an additional request from the IoT device, where the additional request includes the validated temporary certificate;

validating, by the server, that the validated temporary certificate is being received within the temporary period of time; and

in response to successful validation of the validated temporary certificate, processing the additional request from the IoT device by the server.

13. The non-transitory computer readable storage medium of claim 12, wherein the assigning comprises determining the certificate is not revoked based on the list of revoked certificates.

14. The non-transitory computer readable storage medium of claim 12, wherein the validating the temporary certificate comprises:

determining the temporary certificate has not been used;

determining the temporary certificate is not in the list of revoked certificates; and

authorizing use of the temporary certificate for a time period.

15. The non-transitory computer readable storage medium of claim 12, wherein the instructions cause the processor to perform:

providing the validated temporary certificate in place of an original certificate for a time period.

* * * * *