

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12401886
Kind Code	B2
Date of Patent	August 26, 2025
Inventor(s)	Uekusa; Tomotaka

Electronic device, control method, and non-transitory computer readable medium

Abstract

An electronic device includes a processor, and a memory storing a program which, when executed by the processor, causes the electronic device to detect an eyepoint of a user in an image which is captured by an imaging unit and is displayed in a display unit, track a plurality of subjects in the image, determine an attention degree of the user of each of the plurality of subjects based on the eyepoint of the user, and select any of the plurality of subjects as a main subject based on the attention degree of each of the plurality of subjects.

Inventors:	Uekusa; Tomotaka (Kanagawa, JP)
Applicant:	CANON KABUSHIKI KAISHA (Tokyo, JP)
Family ID:	1000008777635
Assignee:	CANON KABUSHIKI KAISHA (Tokyo, JP)
Appl. No.:	18/297665
Filed:	April 10, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230336862 A1	Oct. 19, 2023

Foreign Application Priority Data

JP	2022-066950	Apr. 14, 2022
----	-------------	---------------

Publication Classification

Int. Cl.: H04N23/62 (20230101); G06F3/01 (20060101); G06T7/50 (20170101); G06T7/70 (20170101); G06V40/18 (20220101); H04N23/61 (20230101); H04N23/63 (20230101)

U.S. Cl.:

CPC H04N23/62 (20230101); G06F3/013 (20130101); G06T7/50 (20170101); G06T7/70 (20170101); G06V40/18 (20220101); H04N23/61 (20230101); H04N23/633 (20230101); G06T2200/24 (20130101); G06T2207/10024 (20130101); G06T2207/30196 (20130101)

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9894339	12/2017	Uekusa et al.	N/A	N/A
10015431	12/2017	Uekusa et al.	N/A	N/A
2020/0358984	12/2019	Wang	N/A	H04N 7/181

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2021-67853	12/2020	JP	N/A
2021-108447	12/2020	JP	N/A

Primary Examiner: Braniff; Christopher

Attorney, Agent or Firm: Carter, DeLuca & Farrell LLP

Background/Summary

BACKGROUND OF THE INVENTION

Field of the Invention

(1) The technique of the present disclosure relates to an electronic device, a control method, and a non-transitory computer readable medium, and particularly relates to switching control of a subject in an electronic device.

Description of the Related Art

(2) The number of mirrorless cameras is increasing in recent years, and there is used a technique which detects an eyepoint of a user who looks into a finder, displays an eyepoint pointer based on position information, and allows the user to designate any position even without operating an arrow key or a multi-controller manually.

(3) Japanese Patent Application Publication No. 2021-67853 discloses a technique related to selection and switching of a main subject serving as a target on which autofocus (AF) control is performed by using position designation by a line of sight of a photographer who is a user.

(4) In addition, Japanese Patent Application Publication No. 2021-108447 discloses a technique in which, in order to cope with a characteristic of an eyeball of a human which is referred to as

involuntary eye movement during fixation in which an eyeball makes small movements even when a human gazes at a given point, an eyepoint pointer is displayed with a position which is averaged with time to alleviate an influence of the characteristic.

SUMMARY OF THE INVENTION

(5) An object of the technique of the present disclosure is to provide an electronic device which allows an improvement in the responsiveness of a selection-switching operation of a main subject which uses detection of an eyepoint of a user.

(6) According to an aspect of the present disclosure, it is provided an electronic device including a processor, and a memory storing a program which, when executed by the processor, causes the electronic device to detect an eyepoint of a user in an image which is captured by an imaging unit and is displayed in a display unit, track a plurality of subjects in the image, determine an attention degree of the user of each of the plurality of subjects based on the eyepoint of the user, and select any of the plurality of subjects as a main subject based on the attention degree of each of the plurality of subjects. In addition, according to an aspect of the present disclosure, it is provided an electronic device including a processor, and a memory storing a program which, when executed by the processor, causes the electronic device to display a plurality of subjects in an image which is captured by an imaging unit and is displayed in a display unit such that the plurality of subjects can be selected, and select any of the plurality of subjects displayed such that the plurality of subjects can be selected, wherein a subject at which a user has looked for a second time period which is longer than a first time period is more likely to be selected from among the plurality of subjects than a subject at which the user has looked for the first time period. In addition, according to an aspect of the present disclosure, it is provided an electronic device including a processor, and a memory storing a program which, when executed by the processor, causes the electronic device to display an image captured by an imaging unit in a display unit, detect an eyepoint of a user in the image displayed in the display unit, select any of a plurality of subjects as a main subject, and receive an operation by the user, wherein switching of the main subject selected by the received operation is allowed, and the program when executed by the processor causes the electronic device to display, among the plurality of subjects, instead of a first subject, a second subject at which a user has looked for a time period which is longer than a time period for which the user has looked at the first subject as a switching candidate for the main subject such that the second subject is distinguishable. In addition, according to an aspect of the present disclosure, it is provided an electronic device including a processor, and a memory storing a program which, when executed by the processor, causes the electronic device to detect an eyepoint of a user in an image displayed in a display unit, determine an attention degree of the user for each of a plurality of objects in the image based on the eyepoint of the user, and select the object based on the attention degree of each of the plurality of objects.

(7) According to an aspect of the present disclosure, it is provided a control method of an electronic device, the method including a detection step of detecting an eyepoint of a user in an image which is captured by an imaging unit and is displayed in a display unit, a tracking step of tracking a plurality of subjects in the image, a determination step of determining an attention degree of the user of each of the plurality of subjects based on the eyepoint of the user, and a selection step of selecting any of the plurality of subjects as a main subject, wherein the main subject is selected based on the attention degree of each of the plurality of subjects in the selection step.

(8) Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIGS. **1A** and **1B** are external views of a digital camera according to an embodiment;
- (2) FIG. **2** is a block diagram showing a configuration of the digital camera according to the embodiment;
- (3) FIG. **3** is a cross-sectional view of a casing of the digital camera according to the embodiment;
- (4) FIG. **4** is a diagrammatic illustration for explaining principles of a line-of-sight detection method;
- (5) FIG. **5** includes a schematic view of an eyeball image projected onto an imaging element and a view of output intensity in the imaging element;
- (6) FIG. **6** is a flowchart showing line-of-sight detection processing in the embodiment;
- (7) FIG. **7** is a flowchart showing switching control processing of a main subject of a first embodiment;
- (8) FIGS. **8A** to **8C** are schematic views showing the switching control processing of the main subject of the first embodiment;
- (9) FIGS. **9A** to **9C** are schematic views showing display examples of an attention degree in the embodiment;
- (10) FIG. **10** is a flowchart showing the switching control processing of the main subject of a second embodiment;
- (11) FIGS. **11A** to **11C** are schematic views showing the switching control processing of the main subject of the second embodiment;
- (12) FIG. **12** is a flowchart showing the switching control processing of the main subject of a third embodiment;
- (13) FIGS. **13A** to **13C** are schematic views showing the switching control processing of the main subject of the third embodiment;
- (14) FIG. **14** is a flowchart showing the switching control processing of the main subject of a fourth embodiment; and
- (15) FIGS. **15A** to **15D** are schematic views showing the switching control processing of the main subject of the fourth embodiment.

DESCRIPTION OF THE EMBODIMENTS

(16) Hereinbelow, embodiments of the present disclosure will be described by using the drawings. Note that the present disclosure is not limited to the following embodiments, and can be changed appropriately without departing from the gist thereof. In addition, in the drawings described below, components having the same function are designated by the same reference numerals and the description thereof will be omitted or simplified in some cases.

(17) In the conventional art disclosed in Japanese Patent Application Publication No. 2021-67853 or Japanese Patent Application Publication No. 2021-108447, the position of the eyepoint pointer is averaged with time and the eyepoint pointer is displayed for alleviating the influence of the involuntary eye movement during fixation, and hence there is a possibility that responsiveness of position designation by the eyepoint may be spoiled.

(18) As a result, in a selection-switching operation of a main subject which is a target on which autofocus (hereinafter referred to as AF) control which uses the position designation by the eyepoint is performed, there is a possibility that photographing opportunity may be lost due to delay of timing.

First Embodiment

(19) FIGS. **1A** and **1B** show an outer appearance of a digital camera **100** which is an electronic device according to a first embodiment. The digital camera **100** is an example of an imaging apparatus which images a subject. FIG. **1A** is a front perspective view, and FIG. **1B** is a rear perspective view. As shown in FIG. **1A**, the camera **100** has a photographing lens **100A** and a casing **100B**. In the casing **100B**, a release button **5** which is an operation member for receiving an

imaging operation from a user (photographer) is disposed. As shown in FIG. 1B, on a back surface of the camera casing **100B**, an eyepiece window frame **6** and an eyepiece **203** (eyepiece optical system) for the user to look into a display unit **113** included in the camera casing **100B** are disposed. The eyepiece window frame **6** surrounds the eyepiece **203**, and protrudes to the outside (back surface side) of the camera casing **100B** with respect to the eyepiece **203**. Note that the eyepiece optical system may include a plurality of lenses. On the back surface of the camera casing **100B**, an operation unit **115** constituted by operation members **115a**, **115b**, and **115c** which receive various operations from the user is also disposed. For example, the operation member **115a** is a touch panel which receives a touch operation, the operation member **115b** is an operation lever which can be tilted in each direction, and the operation member **115c** is a four-direction key which can be pushed in in each of four directions. The operation member **115a** (touch panel) includes a display panel such as a liquid crystal panel, and has the function of displaying an image with the display panel.

(20) FIG. 2 is a block diagram of the digital camera **100** which is an electronic device according to the first embodiment of the present invention. In FIG. 2, an image-forming optical unit **101** includes a plurality of lens groups including a focus lens and a vibration isolation lens, and a diaphragm. When photographing is performed, the image-forming optical unit **101** performs focus adjustment with a focus control unit **118**, and exposure adjustment and camera shake correction with a diaphragm control unit **119**, and forms an optical image on an imaging element **102**. The imaging element **102** has a photoelectric conversion function of converting the optical image to an electric signal (analog image signal). The imaging element **102** is constituted by, e.g., a CCD (Charged Coupled Device) or a CMOS (Complementary Metal-Oxide Semiconductor) sensor. In addition, the imaging element **102** includes dedicated pixels and a plurality of independent photodiodes in each pixel for imaging surface phase difference AF. An A/D conversion unit **103** converts the analog image signal from the imaging element **102** to a digital image signal. Image data after the conversion is input to an image processing unit **104** in the subsequent stage.

(21) A bus **116** is a system bus for transmitting a control signal of each block mainly from a CPU **114** or the like, and a bus **117** is a data bus for transferring mainly image data. The CPU **114** is constituted by a microcomputer or the like which is in charge of control of the entire digital camera **100**, and issues an operation instruction to each functional block and executes various control processing steps. In addition, the CPU **114** performs arithmetic calculation required when the various control processing steps are performed. The CPU **114** controls the image processing unit **104**, a data transfer unit **105**, a memory control unit **106**, a non-volatile memory control unit **108**, a recording medium control unit **110**, a display control unit **112**, an operation unit **115**, and the imaging element **102** via the system bus **116**. The CPU **114** executes a program recorded in a ROM **109**, and thereby implements each processing of a control method of the digital camera described below. Further, the CPU **114** performs information acquisition of the lens of the image-forming optical unit **101**, diaphragm control, and a focal length.

(22) The data transfer unit **105** is constituted by a plurality of DMACs (Direct Memory Access Controller) which perform data transfer. A DRAM (memory) **107** is a memory which stores data, and has storage capacity which is sufficient to store data such as a predetermined number of still images, a movie of predetermined time, and sound, constants for the operation of the CPU **114**, and a program. The memory control unit **106** performs data write and data read in and from the DRAM **107** in response to an instruction from the CPU **114** or the data transfer unit **105**.

(23) The non-volatile memory control unit **108** performs data write and data read in and from a ROM (non-volatile memory) **109** in response to an instruction from the CPU **114**. The ROM **109** is an electrically erasable-recordable memory, and an EEPROM or the like is used. In the ROM **109**, constants for the operation of the CPU **114** and a program are stored.

(24) The image processing unit **104** is constituted by various image processing units and a buffer memory, and performs processing such as magnification chromatic aberration correction,

development processing, noise reduction processing, geometric deformation, and resizing such as enlargement and reduction. In addition, the image processing unit **104** includes an imaging correction unit or the like which performs processing of detecting, recognizing, and tracking a subject from a developed or processed image, and properly performs pixel correction, black level correction, shading correction, and flaw correction on image data which is converted by the A/D conversion unit **103**.

(25) A recording medium **111** is a recording medium such as an SD card, and is controlled by the recording medium control unit **110** and performs recording of image data and read of recorded data.

(26) The display unit **113** is constituted by a liquid crystal display and an electronic viewfinder, and is controlled by the display control unit **112** and displays various pieces of image data transferred from the image processing unit **104** and a menu screen. In addition, the display unit **113** processes image data input from the A/D conversion unit **103** in real time and displays the image data before photographing of a still image and at the time of movie shooting.

(27) The operation unit **115** serving as an operation unit includes a switch, a button, and a touch panel operated by a user, and is used in operations such as ON/OFF of a power supply and ON/OFF of a shutter. An eyeball imaging element **121** forms an optical image of an eyeball of the user who looks into a viewfinder, and outputs image data to a line-of-sight detection unit **120**. The line-of-sight detection unit **120** detects a line-of-sight direction of the user based on an image input from the eyeball imaging element **121**. The detail of a line-of-sight detection operation will be described later.

(28) An illumination light source **123** and an illumination light source drive unit **124** are an infrared light source for line-of-sight detection and a drive unit which controls the infrared light source. Infrared light is emitted toward the eyeball of the user, and its reflection image is formed on the eyeball imaging element **120**.

(29) An attention degree detection unit **125** calculates an interest degree of the user of each subject based on line-of-sight data of the user detected by the line-of-sight detection unit **120** and subject area information recognized by the image processing unit **104**, and outputs the interest degree as an attention degree.

(30) An automatic focus detection unit **122** calculates a lens drive amount to a focused area which is output by the line-of-sight detection unit **120** or the image processing unit **104**, and instructs the focus control unit **118** to perform drive control of the focus lens. The calculation of the lens drive amount is performed by, e.g., an imaging surface phase difference method or the like based on an image for focus detection acquired by the imaging element **102**.

(31) FIG. 3 is a cross-sectional view of a casing of the digital camera **100** according to the first embodiment, and is an explanatory view schematically showing its configuration. In FIGS. 1 and 2, corresponding portions are designated by the same numbers.

(32) In FIG. 3, the photographing lens **100A** is a lens for an interchangeable-lens camera. In the present embodiment, for the sake of convenience, the inside of the photographing lens **100A** is constituted by two lenses **205** and **206**, but the inside thereof may also be constituted by a larger number of lenses actually. The casing **100B** is a camera main body, and the imaging element **102** is disposed on a planned image forming plane of the photographing lens **100A** of the digital camera **100**. The eyepiece **203** is a lens for observing a subject image displayed in the display unit **113**.

(33) In the casing **100B**, light sources **123a** and **123b** constituted by infrared light-emitting diodes for irradiating an eyeball **204** of the user for detecting the line-of-sight direction from a relationship between reflection images by corneal reflection of the light sources and a pupil are disposed around the eyepiece **203**. An image of an irradiated eyeball and images formed by corneal reflection of the light sources **123a** and **123b** pass through the eyepiece **203**, are reflected by an optical divider **202**, and are formed on the eyeball imaging element **121** in which rows of photo-electric elements such as CCDs are two-dimensionally arranged by a light receiving lens **201**. The light receiving lens **201** is disposed such that the pupil of the eyeball **204** of the user and the eyeball imaging element **121**

have a conjugate image forming relationship. The line-of-sight direction is detected by a predetermined algorithm described later from a positional relationship between the eyeball of which the image is formed on the eyeball imaging element **121** and the images by the corneal reflection of the light sources **123a** and **123b**.

(34) In the photographing lens **100A**, a diaphragm **207**, a diaphragm control unit **119**, a lens drive member **210** constituted by a drive gear and the like, and a lens drive motor **211** are provided. In addition, in the photographing lens **100A**, a photocoupler **209** which detects rotation of a pulse plate **208** which moves in synchronization with the lens drive member **210** and notifies the focus control unit **118** of the rotation thereof is provided. The focus control unit **118** drives the lens drive motor **211** by a predetermined amount based on information from the photocoupler **209** and information on the lens drive amount from a camera side, and moves the focus lens **205** to a focal point position. In addition, the photographing lens **100A** has mount contacts **212** serving as interfaces between the camera and the lens.

(35) FIG. **4** is an explanatory view showing principles of the line-of-sight detection method, and is a diagrammatic illustration of an optical system for performing line-of-sight detection. In FIG. **3**, the light sources **123a** and **123b** are light-emitting diodes or the like which emit infrared light to which the user is insensitive, and the light sources **123a** and **123b** are disposed so as to be substantially symmetrical with respect to the optical axis of the light receiving lens **201** and irradiate the eyeball **204** of an observer. Part of illumination light reflected by the eyeball **204** is condensed on the eyeball imaging element **121** by the light receiving lens **201**.

(36) FIG. **5** shows a schematic view of an eyeball image projected onto the eyeball imaging element **121** and a view of output intensity of a CCD in the eyeball imaging element **121**. In the drawing, an upper view is the schematic view of the eyeball image, and a lower view is the view of output intensity of the CCD. FIG. **6** shows a flowchart of line-of-sight detection processing executed by the CPU **114** of the digital camera **100** in the present embodiment. Hereinbelow, by using FIGS. **4** to **6**, the line-of-sight detection processing in the present embodiment will be described.

(37) (Explanation of Line-of-sight Detection Operation) When a line-of-sight detection routine is started, in Step **S601**, the CPU **114** emits infrared light toward the eyeball **204** of the user with the light sources **123a** and **123b**. The eyeball image of the user irradiated by the infrared light is formed on the eyeball imaging element **121** through the light receiving lens **201** and is subjected to photoelectric conversion by the eyeball imaging element **121**, and it becomes possible to process the eyeball image as an electric signal.

(38) In Step **S602**, the CPU **114** sends an eyeball image signal obtained from the eyeball imaging element **121** to the line-of-sight detection unit **120**.

(39) In Step **S603**, the CPU **114** determines coordinates of points corresponding to corneal reflection images P_d and P_e of the light sources **123a** and **123b** shown in FIG. **4** and a pupil center c from information on the eyeball image signal obtained in Step **S602**. A cornea **301** of the eyeball **204** of the user is irradiated with the infrared light emitted from the light sources **123a** and **123b**. At this point, the corneal reflection images P_d and P_e formed by part of the infrared light reflected on the surface of the cornea **301** are condensed by the light receiving lens **201**, and are formed on the eyeball imaging element **121** (points P_d' and P_e' in the drawing). Similarly, images of light fluxes from ends a and b of a pupil **302** are also formed on the eyeball imaging element **121**.

(40) FIG. **5** shows an image example (an upper view in the drawing) of reflection images obtained from the eyeball imaging element **121** and an example (a lower view in the drawing) of brightness information obtained from the eyeball imaging element **121** in an area a in the image example. As shown in the drawing, it is assumed that a horizontal direction corresponds to an X-axis, and a vertical direction corresponds to a Y-axis. It is assumed that, at this point, coordinates in an X-axis direction (horizontal direction) of the images P_d' and P_e' obtained by formation of the corneal reflection images of the light sources **123a** and **123b** are X_d and X_e . In addition, it is assumed that

coordinates in the X-axis direction of images a' and b' obtained by image formation of the light fluxes from the ends a and b of the pupil **302** are Xa and Xb. In the example of the brightness information in FIG. 5, at each of positions Xd and Xe corresponding to the images Pd' and Pe' obtained by the formation of the corneal reflection images of the light sources **123a** and **123b**, brightness of an extremely high level is obtained. In an area from the coordinate Xa to the coordinate Xb which corresponds to an area of the pupil **302**, brightness of an extremely low level is obtained except the positions Xd and Xe described above. In contrast to this, in an area having a value of the X coordinate lower than Xa and an area having a value of the X coordinate higher than Xb which correspond to an area of an iris **401** outside the pupil **302**, a value of a brightness level between the two types of the brightness levels described above is obtained. Subsequently, it is possible to obtain the X coordinates Xd and Xe of the images Pd' and Pe' obtained by the formation of the corneal reflection images of the light sources **123a** and **123b**, and the X coordinates Xa and Xb of the images a' and b' of pupil ends from fluctuation information of the brightness level of the above X coordinate positions. In addition, in the case where a rotation angle θ_x of the optical axis of the eyeball **204** with respect to the optical axis of the light receiving lens **201** is small, a coordinate Xc of a location (indicated by c') corresponding to the pupil center c which is formed into an image on the eyeball imaging element **121** can be expressed as $Xc \approx (Xa + Xb)/2$. From the foregoing, it is possible to estimate the X coordinate of c' corresponding to the pupil center which is formed into the image on the eyeball imaging element **121** and the coordinates of the corneal reflection images Pd' and Pe' of the light sources **123a** and **123b**.

(41) Next, in Step **S604**, the CPU **114** calculates an image forming magnification β of the eyeball image. The image forming magnification β is a magnification determined according to the position of the eyeball **204** with respect to the light receiving lens **201** and, actually, the image forming magnification β can be determined as a function of an interval (Xd-Xe) between the corneal reflection images Pd' and Pe'.

(42) In addition, in Step **S605**, the X coordinate of the middle point between the corneal reflection images Pd and Pe substantially matches the X coordinate of the center of curvature O of the cornea **301**. Accordingly, when it is assumed that a standard distance between the center of curvature O of the cornea **301** and the center c of the pupil **302** is Oc, the rotation angle θ_x of the optical axis of the eyeball **204** in a Z-X plane can be determined by the following formula (1).

$$\beta \times Oc \times \sin \theta_x \approx \{(Xd + Xe)/2\} - Xc \quad (1)$$

(43) In addition, each of FIGS. 4 and 5 shows an example in which the rotation angle θ_x in the case where the eyeball of the user rotates in a plane perpendicular to the Y-axis is calculated, and a calculation method of a rotation angle θ_y in the case where the eyeball of the user rotates in a plane perpendicular to the X-axis is similar to the above calculation method.

(44) When the rotation angles θ_x and θ_y of the optical axis of the eyeball **204** of the user are calculated, in Step **S506**, the CPU **114** determines the position of the line of sight of the user (the position of a point at which the user gazes. Hereinafter referred to as a gaze point) on the display unit **113** by using θ_x and θ_y . The gaze point position can be determined as coordinates (Hx, Hy) corresponding to the center c of the pupil **302** on the display unit **113** by the following formulas (2) and (3).

$$Hx = m \times (Ax \times \theta_x + Bx) \quad (2)$$

$$Hy = m \times (Ay \times \theta_y + By) \quad (3)$$

(45) Herein, a coefficient m is a constant determined by the configuration of a finder optical system of a camera and is a conversion coefficient for converting the rotation angles θ_x and θ_y to position coordinates corresponding to the center c of the pupil **302** on the display unit **113**, and is determined in advance and is stored in the memory **107**. In addition, Ax, Bx, Ay, and By are line-of-sight correction coefficients for correcting an individual difference of the line of sight of the user, are acquired by performing calibration work, and are stored in the memory **107** before the line-of-sight detection routine in FIG. 6 is started.

(46) As described above, after the coordinates (Hx, Hy) of the center c of the pupil **302** on the display unit **113** are calculated, the CPU **114** applies a time-series filter which averages a predetermined time period to the calculated coordinates in order to alleviate an influence of coordinate fluctuation by involuntary eye movement during fixation in Step **S607**. Subsequently, in Step **S608**, the CPU **114** stores the above coordinates in the memory **107**, and ends the line-of-sight detection routine. In addition, the CPU **114** measures a time period in which the position of the line of sight stays in a given area, and stores a staying time period of the position of the line of sight in each area in the memory **107** as a gaze time period.

(47) Note that, while the above-described processing is an example of a method of acquiring gaze point coordinates on a display element which uses the corneal reflection images of the light sources **123a** and **123b**, any method can be applied to the present embodiment as long as the eyeball rotation angle can be acquired from the captured eyeball image.

(48) FIG. 7 shows a flowchart of selection-switching control processing of a main subject executed by the digital camera **100** according to the present embodiment, and FIGS. **8A** to **8C** are views schematically explaining the selection-switching control processing of the main subject of the present embodiment. In addition, FIGS. **9A** to **9C** are views showing display examples of the attention degree of the user. Hereinafter, processing executed in FIG. 7 will be described with reference to FIG. 7, FIGS. **8A** to **8C**, and FIGS. **9A** to **9C**.

(49) When photographing by the user is started, the CPU **114** starts the selection-switching control processing of the main subject, and two processing steps in Step **S701** and Step **S704** are executed in parallel with each other.

(50) In Step **S701**, the imaging element **102** acquires an image of a photographing area including the main subject, and outputs the acquired image to the image processing unit **104** via the A/D conversion unit **103**. When the acquisition and the output of the image of the photographing area are completed in Step **S701**, the processing proceeds to Step **S702**.

(51) In Step **S702**, the image processing unit **104** performs recognition of a subject in a live-view image generated to be displayed in the display unit **113** in a finder. Subject recognition processing is processing in which a specific subject area is estimated by using, e.g., deep learning, i.e., a multi-layer neural network including a learned convolution layer. In addition, the subject recognition processing may also be processing in which a conspicuous area in an image is calculated from a texture, a color, and a histogram without using the deep learning, and the calculated area is estimated as the subject area. In the case where a plurality of subjects are present in the image, a plurality of estimation results of the subject area are output. In the estimation result of the subject area, results corresponding to all subjects in an initial frame and, in a subsequent frame, a result corresponding to a subject which is not a tracking target and has newly appeared in the frame by frame-in are output. For example, as shown in FIG. **8A**, in the case where subjects **801**, **803**, and **805** are present in a live-view image, their subject areas **802**, **804**, and **806** are output as estimation results. When the subject area is estimated by the subject recognition processing in Step **S702**, the processing proceeds to Step **S703**.

(52) In Step **S703**, the image processing unit **104** functions as a tracking unit, performs tracking of a plurality of subjects output in Step **S702**, and outputs a subject tracking result to the CPU **114**. In subject tracking processing, an area in a current frame which corresponds to the subject area of the tracking target in a previous frame is estimated by using, e.g., deep learning. More specifically, the subject tracking processing has the function of extracting feature points of the subject area and feature amounts included in the feature points, and the function of associating the extracted feature points with frames. That is, from the feature point in the current frame which is associated with the feature point of the subject area of the tracking target in the previous frame, the position and the size of the subject area of the tracking target in the current frame are estimated. In addition, the subject tracking processing may also be processing in which the subject area in the current frame corresponding to the subject area of the tracking target in the previous frame is estimated from a

texture, a color, and a histogram without using deep learning. The subject tracking result results in a loss determination in the case where the subject area of the tracking target in the previous frame is not found in the current frame due to frame-out of the subject or the like. In addition, with regard to a subject which is newly recognized in the current frame in Step S702, the estimation result of the subject recognition processing is output as the subject tracking result without altering the estimation result.

(53) For example, as shown in FIG. 8A, in the case where the subjects **801**, **803**, and **805** are present in the live-view image, the corresponding subject areas **802**, **804**, and **806** in the immediately preceding frame are estimated, and it becomes possible to continuously recognize the subjects as the same subjects in a plurality of frames. When the individual subject areas in the current frame are estimated by the subject tracking processing in Step S703, its result is output also to the attention degree calculation unit **125**, and the processing performs completion of Step S705 and queuing and proceeds to Step S706.

(54) On the other hand, in Step S704, the eyeball imaging element **121** acquires the image of the eyeball of the user irradiated by the illumination light source **123**, and outputs image data to the line-of-sight detection unit **120**. When the eyeball image of the user is acquired in Step S704, the processing proceeds to Step S705.

(55) In Step S705, the line-of-sight detection unit **120** functions as a detection unit, and detects the line of sight of the user with the above-described line-of-sight detection routine. Subsequently, the line-of-sight detection unit **120** calculates an eyepoint coordinate in the live-view image displayed in the display unit **113** in the finder, and displays an eyepoint pointer (e.g., **808** in FIG. 8A). In addition, the line-of-sight detection unit **120** outputs the eyepoint coordinate to the CPU **114** and the attention degree calculation unit **125**. When the eyepoint coordinate of the user is calculated in Step S705, the processing performs completion of Step S703 and queuing, and proceeds to Step S706.

(56) In Step S706, the attention degree calculation unit **125** functions as a determination unit, and determines the attention degree of the user for each of a plurality of subjects based on the eyepoint of the user. Specifically, the attention degree calculation unit **125** calculates the attention degree of the user of each subject from individual subject area information in the current frame output by the image processing unit **104** in Step S703, and the eyepoint coordinate output by the line-of-sight detection unit **120** in Step S705. The attention degree of each subject is a degree of inclusion of the detected eyepoint of the user in the area of a tracked subject. An example of the degree of inclusion of the eyepoint of the user includes a period in which the eyepoint coordinate stays in the subject area (for example, the number of times of sampling of the eyepoint coordinate calculation, the number of corresponding display frames, a count value of the number of times of staying for a predetermined time period, or a ratio to a total value of all subjects). With regard to the subject which has been determined to be lost in Step S703, the attention degree thereof is cancelled. The calculated attention degree of each subject is output to the CPU **114**. In addition, attention degree information is displayed so as to be superimposed on the live-view image (e.g., **809** in FIG. 8A) displayed in the display unit **113** in the finder according to setting.

(57) With regard to the display of the attention degree information, the attention degree information may be divided into several levels (e.g., five levels) with preset thresholds and is displayed as numerical values as shown in FIG. 9A, the attention degree information may also be displayed as numerical values without altering the attention degree information as shown in FIG. 9B, and level values may be displayed with a meter as shown in FIG. 9C. In addition, the attention degree information may also be displayed such that level values are expressed by using a color, a thickness, or a multiple line of frame display indicative of the subject area. Thus, in the display unit **113**, it is possible to display the determined attention degrees of a plurality of subjects by using at least one of a numerical value, a diagram, and a color. When the attention degree of each subject is calculated in Step S706, the processing proceeds to Step S707.

(58) In Step **S707**, the CPU **114** determines whether or not a switching determination operation of the main subject serving as an AF control target has been performed by operating the operation unit **115** serving as an operation unit by the user. Herein, an example of the switching determination operation of the main subject includes an operation in which the main subject after switching is determined by using at least one of the touch panel **115a**, the operation lever **115b**, and the four-direction key **115c**. In the case where the switching determination operation of the main subject has been performed (**S707**: YES), the processing proceeds to Step **S708** and, in the case where the switching determination operation of the main subject is not performed (**S707**: NO), the processing proceeds to Step **S709**.

(59) In Step **S709**, the CPU **114** determines whether or not a distance between the eyepoint coordinate and the coordinate of the subject (e.g., a center coordinate of the subject area) is not more than a specific threshold distance. As shown in FIG. **8A**, when the eyepoint pointer indicative of the eyepoint of the user moves from the position of **807** to the position of **808**, the eyepoint coordinate is included in an area **810** indicating that the area **810** is within the specific threshold distance from the subject **803** in FIG. **8B**. With this, it is determined that the distance between the eyepoint coordinate and the subject coordinate is not more than the specific threshold distance. The size of the area **810** indicating that the area **810** is within the specific threshold distance from the subject **803** is calculated so as to be equal to the size of the subject area **804** when the attention degree of the subject **803** is, e.g., zero and is calculated so as to be larger as the attention degree is higher. In addition, for the convenience of description, the area **810** is shown in the drawing so as to be displayed in the display unit **113**, but it is assumed that the area **810** is not displayed in the display unit **113** in the finder, and information related to the area **810** is internally held by the digital camera **100**.

(60) In addition, basically, in switching of the main subject, switching from the main subject to a subject other than the main subject is assumed to be performed, and hence, in Step **S709**, it is assumed that the attention degree of the main subject **801** is handled as zero. When it is determined that the distance between the eyepoint coordinate and the subject coordinate is not more than the specific distance in Step **S709** (**S709**: YES), the processing proceeds to Step **S710**. When it is determined that the distance between the eyepoint coordinate and the subject coordinate is more than the specific distance (**S709**: NO), the processing proceeds to Step **S711**.

(61) In Step **S710**, the CPU **114** functions as a selection unit, and brings a subject having the distance to the eyepoint coordinate which is not more than the specific distance into an enabled state (a selection state which allows the subject to be determined as the main subject) as a switching target of the main subject. Subsequently, the CPU **114** outputs a command to perform display for notifying the user of the state to the display control unit **112**. The display control unit **112** functions as a display control unit according to the command from the CPU **114**, and displays a plurality of subjects in the image such that the plurality of subjects can be selected. Specifically, an example of the display includes display of a double frame **811** which surrounds the subject as shown in FIG. **8B**, and the display is different from a thick-line frame **802** of the main subject **801** serving as the current AF control target and a broken-line frame **806** indicative of the subject area of the subject other than the main subject. When display of enabling of the subject as the switching target of the main subject is performed in Step **S710**, the processing proceeds to Step **S711**.

(62) On the other hand, in Step **S708**, the CPU **114** sets the subject selected when the switching determination operation of the main subject is performed by the user as the main subject, and resets the attention degrees of all subjects to initial values. In addition, the display of the attention degree information is reset to zero which is the initial value. When switching processing of the main subject is performed in Step **S708**, the processing proceeds to Step **S711**.

(63) In Step **S711**, the CPU **114** instructs the automatic focus detection unit **122** to perform focus control on a main subject area (**802** or **812**), and the automatic focus detection unit **122** calculates a lens drive amount and instructs the focus control unit **118** to perform drive control of a focus lens.

When the focus control of the main subject area is completed by the drive control of the focus lens of the focus control unit **118**, the processing proceeds to Step **S712**.

(64) In examples in FIGS. **8A** to **8C**, when the eyepoint pointer **808** indicative of the eyepoint position of the user moves into the area **810** in a state in which the subject **801** is set as the main subject, a notification that the subject **803** can be determined as the main subject (display of the frame **811**) is provided. AF control is performed on the subject **801** until the user performs the determination operation for switching the main subject to the subject **803**. Subsequently, when the user performs the determination operation for switching the main subject to the subject **803**, as shown in FIG. **8C**, the main subject is switched from the subject **801** to the subject **803**, and the AF control is performed on the subject **803**. In addition, with regard to the frame of the subject area, a broken-line frame **813** indicative of a subject other than the main subject and a thick-line frame **812** indicative of the main subject are displayed in the display unit **113**.

(65) Subsequently, in Step **S712**, the CPU **114** determines whether or not photographing by the user is ended. In the case where the power supply of the digital camera **100** is tuned OFF by the user or an AF operation is released (**S712**: YES), the CPU **114** ends the selection-switching control processing of the main subject. In addition, in the case where the photographing is continued (**S712**: NO), the CPU **114** returns the processing to Steps **S701** and **S704** and repeats the processing in Steps **S701** to **S712** described above.

(66) As described thus far, a range in which the subject is selected as the subject candidate for the main subject based on the attention degree of each subject is enlarged. Subsequently, among a plurality of subjects, on a subject in the image which has the higher attention degree, i.e., a subject having attracted more eyepoints of the user, display having a priority higher than those of the other subjects is performed. Among a plurality of subjects, the display control unit **120** displays, instead of a first subject, a second subject at which the user has looked for a time period which is longer than a time period for which the user has looked at the first subject as the switching candidate for the main subject such that the second subject is distinguishable. Accordingly, among a plurality of the subjects, the subject at which the user has looked for a second time period which is longer than a first time period becomes more likely to be selected than the subject at which the user has looked for the first time period. In addition, even in a state in which the eyepoint pointer is not completely on the subject area, it becomes possible to select the subject as the switching target of the main subject. With this, in the case where the switching operation of the main subject is performed by position designation by the line of sight of the user and the determination operation by a button operation, it becomes possible to improve responsiveness of the selection-switching operation of the main subject and achieve a reduction in the loss of photographing opportunity.

Second Embodiment

(67) Next, a description will be given of a digital camera which is an electronic device according to a second embodiment with reference to FIG. **10** and FIGS. **11A** to **11C**. In the second embodiment, instead of enabling the subject having the distance to the eyepoint coordinate which is not more than the specific distance as the switching target of the main subject, the position of the eyepoint pointer is moved. With this, even in the state in which the eyepoint pointer is not completely on the subject area, it becomes possible to select the subject as the switching target.

(68) The configuration of the digital camera according to the present embodiment is the same as that of the first embodiment, and part of the selection-switching control processing of the main subject is the same as that of the first embodiment. In the following description, portions different from the first embodiment will be mainly described, and the same components and the same processing steps are designed by the same reference numerals and the detailed description thereof will be omitted.

(69) FIG. **10** is a view showing a flowchart of the selection-switching control processing of the main subject of the digital camera **100** according to the present embodiment, and FIGS. **11A** to **11C** are views schematically explaining the selection-switching control processing of the main subject

of the present embodiment. Hereinafter, processing executed in FIG. 10 will be described with reference to FIG. 10 and FIGS. 11A to 11C.

(70) When photographing by the user is started, the CPU 114 starts the selection-switching control processing of the main subject, and two processing steps in Step S701 and Step S704 are executed in parallel with each other. Note that Steps S701 to S709 are the same processing steps as those of the first embodiment.

(71) Next, in Step S1001, the CPU 114 moves the eyepoint pointer to the coordinate which is on the subject having the distance to the eyepoint coordinate which is not more than the specific distance. Subsequently, the CPU 114 establishes a state in which the subject on the eyepoint pointer can be determined as the switching target of the main subject, and outputs a command to perform display for notifying the user of the state to the display control unit 112. Herein, the display of the notification to the user is, e.g., display in which the position of the eyepoint pointer 808 is changed to a position on a subject 1101 as shown in FIG. 11B. Note that, as a display form of the movement of the eyepoint pointer 808 from the position of the eyepoint pointer 808 in FIG. 11A to the position of the eyepoint pointer 808 in FIG. 11B, any display form can be adopted. For example, the eyepoint pointer 808 in FIG. 11A may be switched to the display in FIG. 11B instantly, and movement display in which the eyepoint pointer 808 in FIG. 11A is attracted to the position of the eyepoint pointer 808 in FIG. 11B may also be adopted. When the eyepoint coordinate and the display position of the eyepoint pointer are changed in Step S1001, the processing proceeds to Step S711. The processing in Steps S711 and S712 is the same as that of the first embodiment.

(72) As described thus far, by application of the movement range of the eyepoint coordinate determined based on the attention degree of each subject, the eyepoint pointer is moved even in a state in which the eyepoint pointer is not on the subject, and it becomes possible to select the subject as the switching target of the main subject. With this, in the case where the switching operation of the main subject is performed by the position designation by the line of sight of the user and the determination operation by the button operation, it becomes possible to improve the responsiveness of the selection-switching operation of the main subject, and achieve a reduction in the loss of photographing opportunity.

Third Embodiment

(73) Next, a description will be given of a digital camera according to a third embodiment with reference to FIG. 12 and FIGS. 13A to 13C. In the third embodiment, a description will be given of an example of the selection-switching processing of the main subject in the case where the determination when the subject is selected is performed not by the button operation but by a gaze determination.

(74) The configuration of the digital camera according to the present embodiment is the same as that of the first embodiment, and part of the selection-switching control processing of the main subject is the same as that of the first embodiment. In the following description, portions different from the first embodiment will be mainly described, and the same components and the same processing steps are designated by the same reference numerals and the detailed description thereof will be omitted.

(75) FIG. 12 is a view showing a flowchart of the selection-switching control processing of the main subject of the digital camera 100 according to the present embodiment, and FIGS. 13A to 13C are views schematically explaining the selection-switching control processing of the main subject of the present embodiment. Hereinafter, processing executed in FIG. 12 will be described with reference to FIG. 12 and FIGS. 13A to 13C.

(76) When photographing by the user is started, the CPU 114 starts the selection-switching control processing of the main subject, and two processing steps in Step S701 and Step S704 are executed in parallel with each other. Steps S701 to S706 are the same processing steps as those of the first embodiment.

(77) Next, in Step S1201, the CPU 114 determines whether or not the eyepoint coordinate is

present in the subject area of the subject other than the main subject. As a specific example, as shown in FIG. 13A, the position of the eyepoint pointer indicative of the eyepoint of the user is moved to the position of an eyepoint pointer **1301** in the subject area **804** from the position of the eyepoint pointer **807**. At this point, the CPU **114** determines that the eyepoint coordinate of the user is present in the subject area **804** of the subject **803**. In the case where it is determined that the eyepoint coordinate is present in the subject area of the subject other than the main subject (S1201: YES), the processing proceeds to Step S1202. On the other hand, in the case where it is determined that the eyepoint coordinate is not present in the subject area of the subject other than the main subject (S1201: NO), the processing proceeds to Step S711.

(78) In Step S1202, the CPU **114** reads a gaze time period of the user stored in the memory **107** in Step S705, and determines whether or not the gaze time period is not less than a specific time period. For example, as shown in FIG. 13B, after the eyepoint pointer **1301** moves into the subject area **804**, the eyepoint pointer **1301** continuously stays in the subject area **804** of the subject **803** for the specific time period or longer. At this point, the CPU **114** determines that the gaze time period is not less than the specific time period, and determines that the determination operation for switching the main subject has been performed. Herein, the specific time period serving as a threshold for performing the gaze determination is, e.g., a threshold time period which is preset, e.g., when the attention degree of the subject **803** is zero. This time period is set to be shorter as the attention degree is higher, and the subject having the higher attention degree has a shorter required time period of the gaze determination. In the case where it is determined that the gaze time period is not less than the specific time period (S1202: YES), the processing proceeds to Step S708. On the other hand, in the case where it is determined that the gaze time period is less than the specific time period (S1202: NO), the processing proceeds to Step S711. The processing in Step S708 and Steps S711 and S712 is the same processing as that of the first embodiment.

(79) As described thus far, the threshold time period of the gaze determination is set based on the attention degree of each subject, whereby the subject having the higher attention degree has the shorter time period required until the subject having the higher attention degree is determined as the switching target of the main subject. With this, in the case where the switching operation of the main subject is performed by the position designation by the line of sight of the user and the determination operation by the gaze determination, it becomes possible to improve the responsiveness of the selection-switching operation of the main subject, and achieve a reduction in the loss of photographing opportunity.

Fourth Embodiment

(80) Next, a description will be given of a digital camera according to a fourth embodiment with reference to FIG. 14 and FIGS. 15A to 15D. In the fourth embodiment, a description will be given of an example of the selection-switching processing of the main subject in the case where the determination when the subject is selected is not performed based on the processing which uses the eyepoint position of the user but is performed by the button operation.

(81) The configuration of the digital camera according to the present embodiment is the same as that of the first embodiment, and part of the selection-switching control processing of the main subject is the same as that of the first embodiment. In the following description, portions different from the first embodiment will be mainly described, and the same components and the same processing steps are designated by the same reference numerals and the detailed description thereof will be omitted.

(82) FIG. 14 is a view showing a flowchart of the selection-switching control processing of the main subject of the digital camera **100** according to the present embodiment, and FIGS. 15A to 15D are views schematically explaining the selection-switching control processing of the main subject of the present embodiment. Hereinafter, processing executed in FIG. 14 will be described with reference to FIG. 14 and FIGS. 15A to 15D.

(83) When photographing by the user is started, the CPU **114** starts the selection-switching control

processing of the main subject, and two processing steps in Step S701 and Step S704 are executed in parallel with each other. Steps S701 to S708 are the same processing steps as those of the first embodiment.

(84) Next, in Step S1401, the CPU 114 determines whether or not the user has performed the operation of selecting the subject for switching of the main subject serving as the AF control target with a specific operation of an arrow key of the operation unit 115. Herein, the selection operation of the subject is an operation of switching selection of the subject serving as the subject candidate for the main subject displayed in the display unit 113. In the present step, a determination of whether or not the operation of determining the selected subject as the main subject is not performed, and this determination is performed in Step S707. In the case where it is determined that the selection operation of the subject has been performed by the user (S1401: YES), the processing proceeds to Step S1402. On the other hand, in the case where it is determined that the selection operation of the subject is not performed by the user (S1401: NO), the processing proceeds to Step S711.

(85) In Step S1402, the CPU 114 sequentially selects subjects in descending order of the attention degree as the subject candidate for the switching target of the main subject in response to the selection operation by the user, and output a command to perform display for notifying the user of a selection state of the subject to the display control unit 112. The display of the notification to the user is, e.g., display with a double frame 1501 in FIG. 15B, and is different from the thick-line frame 802 indicative of the main subject 801 serving as the AF control target or the broken-line frame 806 indicative of the subject area of the subject other than the main subject. In addition, FIG. 15B shows a display state of the display unit 113 when the subject selection operation is performed once by the user, and shows that the subject 803 having the highest attention degree other than that of the main subject 801 is selected as the switching target of the main subject. After the selection state of the subject serving as the subject candidate for the main subject is displayed in Step S1402, the processing proceeds to Step S711. Steps S711 and S712 are the same processing steps as those of the first embodiment.

(86) FIG. 15D shows a state in which the selection operation of the subject is performed one more time by the user in the state of FIG. 15B. More specifically, after the processing in Step S1402 is executed and the display state of the display unit 113 becomes the state shown in FIG. 15B, the processing proceeds to Step S711, and the AF control is executed on the main subject 801. Subsequently, after the processing returns to Steps S701 and S704 from Step S712, the processing in Steps S701 to S706 is executed and the processing proceeds to Step S1401 from Step S707. Subsequently, the selection operation of the subject is performed one more time by the user, whereby the processing proceeds to Step S1402 from Step S1401. In Step S1402, as shown in FIG. 15D, the display state of the display unit 113 becomes a state in which the subject 805 having the second highest attention degree after the attention degree of the subject 803 other than the attention degree of the main subject 801 is selected as the switching target of the main subject. Note that, in the case where the subject having the second highest attention degree after that of the currently selected and displayed subject other than that of the main subject is not present, display control may be performed such that a state in which, among subjects other than the main subject, a subject having the highest attention degree is selected again is established. In examples in FIGS. 15A to 15D, when the user performs the selection operation of the subject one more time in the state in which the subject 805 is selected as the switching target of the main subject as shown in FIG. 15D, the display state of the display unit 113 returns to the state shown in FIG. 15B.

(87) As described thus far, the subject serving as the subject candidate for the switching target of the main subject is selected and displayed in display order based on the attention degree of each subject, whereby the subject having the higher attention degree is selected as the switching target of the main subject more preferentially. That is, the display control unit 120 displays, among a plurality of subjects, the subject candidate for the switching target such that the attention degree of

each subject candidate is distinguishable. With this, in the case where the switching operation of the main subject is performed by the subject selection and the determination operation by the button operation of the user, it becomes possible to improve the responsiveness of the selection-switching operation of the main subject and achieve a reduction in the loss of photographing opportunity.

(88) While the present invention has been described in detail based on its preferred embodiments thus far, the present invention is not limited to these specific embodiments, and various forms without departing from the gist of the invention are also included in the present invention. Parts of the above-described embodiments may be combined appropriately.

(89) While the example in which the present invention is applied to the digital camera has been described in each of the above-described embodiments, the electronic device to which the present invention can be applied is not limited to the digital camera. For example, the present invention can also be applied to a personal computer, a smartphone, a tablet, a head-mounted display, and smart glasses. In addition, an image to be displayed is not limited to an image captured by the imaging apparatus. For example, the present invention can also be applied to, e.g., the case where an item is selected from a screen (an image, e.g., a menu screen or a desktop screen) including a plurality of items (objects).

(90) In addition, for example, while the example of the detection method which is based on the assumption that the user looks into the finder has been described as the line-of-sight detection method in the first embodiment, the detection method may detect the line of sight in the case where the user looks at display on a back panel. In addition, while the form in which the subject other than the main subject is assumed to be used as the switching target of the main subject, and the attention degree of the main subject is handled as zero has been described, the present invention is not limited thereto. The main subject may also be handled similarly to the subject other than the main subject.

(91) In addition, while the example in which the target of the selection-switching operation of the main subject is the subject other than the main subject has been described in the third embodiment, the processing may be executed such that the main subject is re-selected by using the main subject as the processing target similarly to the other subjects. With this, it becomes possible to perform what is called re-catching control of the subject.

(92) Note that each functional unit of each embodiment (each modification) described above may or may not be individual hardware. Functions of two or more functional units may be implemented by common hardware. Each of a plurality of functions of one functional unit may be implemented by individual hardware. Two or more functions of one functional unit may be implemented by common hardware. In addition, each functional unit may or may not be implemented by hardware such as ASIC, FPGA, or DSP. For example, an apparatus may have a processor and a memory (storage medium) which stores a control program. Further, functions of at least part of functional units of the apparatus may be implemented by the processor which reads the control program from the memory and executes the control program.

Other Embodiments

(93) Embodiment(s) of the present invention can also be realized by a computer of a system or apparatus that reads out and executes computer executable instructions (e.g., one or more programs) recorded on a storage medium (which may also be referred to more fully as a 'non-transitory computer-readable storage medium') to perform the functions of one or more of the above-described embodiment(s) and/or that includes one or more circuits (e.g., application specific integrated circuit (ASIC)) for performing the functions of one or more of the above-described embodiment(s), and by a method performed by the computer of the system or apparatus by, for example, reading out and executing the computer executable instructions from the storage medium to perform the functions of one or more of the above-described embodiment(s) and/or controlling the one or more circuits to perform the functions of one or more of the above-described

embodiment(s). The computer may comprise one or more processors (e.g., central processing unit (CPU), micro processing unit (MPU)) and may include a network of separate computers or separate processors to read out and execute the computer executable instructions. The computer executable instructions may be provided to the computer, for example, from a network or the storage medium. The storage medium may include, for example, one or more of a hard disk, a random-access memory (RAM), a read only memory (ROM), a storage of distributed computing systems, an optical disk (such as a compact disc (CD), digital versatile disc (DVD), or Blu-ray Disc (BD)TM), a flash memory device, a memory card, and the like.

(94) According to the present disclosure, it is possible to improve the responsiveness by controlling the selection-switching operation of the main subject on which the AF control is performed based on the attention degree of each subject calculated from the area of the subject which is recognized by the eyepoint of the user and the image processing. In addition, according to the present disclosure, it is possible to reduce the loss of photographing opportunity.

(95) While the present invention has been described with reference to exemplary embodiments, it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

(96) This application claims the benefit of Japanese Patent Application No. 2022-066950, filed on Apr. 14, 2022, which is hereby incorporated by reference herein in its entirety.

Claims

1. An electronic device comprising: a processor; and a memory storing a program which, when executed by the processor, causes the electronic device to: detect an eyepoint of a user in an image which is captured by an imaging unit and is displayed in a display unit; track a plurality of subjects in the image; determine an attention degree of the user of each of the plurality of subjects based on the eyepoint of the user; and receive an operation by the user; display, among the plurality of subjects, a subject candidate serving as a switching target such that the subject candidate is distinguishable; and display the subject candidate serving as the switching target such that the attention degree of each subject candidate is distinguishable in a case where switching of a main subject is performed by the received operation.
2. The electronic device according to claim 1, wherein the program when executed by the processor causes the electronic device to determine a degree of inclusion of the eyepoint of the user detected in an area of the tracked subject as the attention degree.
3. The electronic device according to claim 2, wherein the degree of inclusion of the eyepoint of the user is the number of times of sampling or the number of display frames of an image in which the detected eyepoint of the user is present in the area of the subject, or the number of times of staying of the detected eyepoint of the user for a predetermined time period in the area of the subject.
4. The electronic device according to claim 1, wherein the program when executed by the processor causes the electronic device to select any of the plurality of subjects as the main subject based on the attention degree of each of the plurality of subjects and select, from among the plurality of subjects, a subject having a higher attention degree preferentially as the main subject.
5. The electronic device according to claim 1, wherein the program when executed by the processor causes the electronic device to select, from among the plurality of subjects, the main subject based on the attention degree of each subject other than a subject selected as the main subject.
6. The electronic device according to claim 1, wherein the program when executed by the processor causes the electronic device to set the attention degree of the tracked subject back to an initial value in a case where the tracked subject ceases to be present in the image.
7. The electronic device according to claim 1, wherein the program when executed by the processor

causes the electronic device to display the determined attention degrees of the plurality of subjects in the display unit by using at least one of a numerical value, a diagram, and a color.

8. The electronic device according to claim 1, wherein the program when executed by the processor causes the electronic device to determine a gaze time period used in a gaze determination based on the attention degree of the subject in a case where switching of the main subject is performed by position designation by the eyepoint of the user and the gaze determination of the eyepoint of the user.

9. An electronic device comprising: a processor; and a memory storing a program which, when executed by the processor, causes the electronic device to: detect an eyepoint of a user in an image which is captured by an imaging unit and is displayed in a display unit; track a plurality of subjects in the image; determine an attention degree of the user of each of the plurality of subjects based on the eyepoint of the user; receive an operation by the user; and determine a subject candidate serving as the main subject based on a distance between the subject and the eyepoint of the user and the attention degree in a case where switching of the main subject is performed by position designation by the eyepoint of the user in the image and the received operation.

10. The electronic device according to claim 9, wherein the program when executed by the processor causes the electronic device to determine a subject having the distance between the subject and the eyepoint of the user which is not more than a threshold distance determined according to the attention degree as the subject candidate.

11. The electronic device according to claim 9, wherein the program when executed by the processor causes the electronic device to notify the user that it is possible to switch the main subject.

12. An electronic device comprising: a processor; and a memory storing a program which, when executed by the processor, causes the electronic device to: detect an eyepoint of a user in an image which is captured by an imaging unit and is displayed in a display unit; track a plurality of subjects in the image; determine an attention degree of the user of each of the plurality of subjects based on the eyepoint of the user; receive an operation by the user; and determine a display position of the eyepoint of the user in the image based on a distance between the subject and the eyepoint of the user and the attention degree in a case where switching of the main subject is performed by position designation by the eyepoint of the user in the image and the received operation.

13. The electronic device according to claim 12, wherein the program when executed by the processor causes the electronic device to determine a position on a subject having the distance between the subject and the eyepoint of the user which is not more than a threshold distance determined according to the attention degree as the display position of the eyepoint of the user.

14. An electronic device comprising: a processor; and a memory storing a program which, when executed by the processor, causes the electronic device to: display a plurality of subjects in an image which is captured by an imaging unit and is displayed in a display unit such that the plurality of subjects can be selected; determine an attention degree of a user of each of the plurality of subjects, wherein the attention degree of the user of each of the plurality of subjects is based at least in part on a time period for which the user has looked at each of the plurality of subjects; receive an operation by the user; display, among the plurality of subjects, a subject candidate serving as a switching target such that the subject candidate is distinguishable; and display the subject candidate serving as the switching target such that the attention degree of each subject candidate is distinguishable in a case where switching of a main subject is performed by the received operation.

15. An electronic device comprising: a processor; and a memory storing a program which, when executed by the processor, causes the electronic device to: display an image captured by an imaging unit in a display unit; detect an eyepoint of a user in the image displayed in the display unit; select any of a plurality of subjects as a main subject; determine an attention degree of the user of each of the plurality of subjects based on the eyepoint of the user; receive an operation by

the user, wherein switching of the main subject selected by the received operation is allowed; display, among the plurality of subjects, a subject candidate serving as a switching target such that the subject candidate is distinguishable; and display the subject candidate serving as the switching target such that the attention degree of each subject candidate is distinguishable in a case where switching of the main subject is performed by the received operation.

16. An electronic device comprising: a processor; and a memory storing a program which, when executed by the processor, causes the electronic device to: detect an eyepoint of a user in an image displayed in a display unit; determine an attention degree of the user for each of a plurality of objects in the image based on the eyepoint of the user; receive an operation by the user; display, among the plurality of objects, an object candidate serving as a switching target such that the object candidate is distinguishable; and display the object candidate serving as the switching target such that the attention degree of each object candidate is distinguishable in a case where switching of a main object is performed by the received operation.

17. A control method of an electronic device, the method comprising: detecting an eyepoint of a user in an image which is captured by an imaging unit and is displayed in a display unit; tracking a plurality of subjects in the image; determining an attention degree of the user of each of the plurality of subjects based on the eyepoint of the user; receiving an operation by the user; displaying, among the plurality of subjects, a subject candidate serving as a switching target such that the subject candidate is distinguishable; and displaying the subject candidate serving as the switching target such that the attention degree of each subject candidate is distinguishable in a case where switching of a main subject is performed by the received operation.

18. A non-transitory computer readable medium in which a program for causing a computer to execute the control method of claim 17 is stored.
