

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12402655
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Okada; Mitsuru et al.

Cartridge and manufacturing method of cartridge

Abstract

A leftover material is prevented from being generated from a part, of a cartridge that forms a vapor product, where positioning is performed. There is provided a cartridge that is assembled in a part of a vapor product that includes a heating element for heating an aerosol source. The cartridge includes a first component and a second component, at least one of which being formed of resin, a connection section that extends between the first component and the second component, with one end connected to the first component and another end connected to the second component, and a guide section that extends from the first component, and that is not joined or welded to the second component. The second component includes a receiving section where the guide section fits.

Inventors: Okada; Mitsuru (Tokyo, JP), Kimura; Masayuki (Tokyo, JP), Serizawa; Yuya (Tokyo, JP)

Applicant: Japan Tobacco Inc. (Tokyo, JP)

Family ID: 81602157

Assignee: JAPAN TOBACCO INC. (Tokyo, JP)

Appl. No.: 17/720675

Filed: April 14, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20220240578 A1	Aug. 04, 2022

Related U.S. Application Data

continuation parent-doc WO PCT/JP2020/042580 20201116 PENDING child-doc US 17720675

Publication Classification

Int. Cl.: A24F40/70 (20200101); A24F40/42 (20200101)

U.S. Cl.:

CPC A24F40/42 (20200101); A24F40/70 (20200101);

Field of Classification Search

CPC: A24F (40/10); A24F (40/40); A24F (40/42); A24F (42/60); A24F (7/00); A24F (15/015); A24F (15/01); A24F (5/10); A24F (1/14); A24D (1/20); A24D (1/02); A24D (1/042); A24D (1/04)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
9986768	12/2017	Force	N/A	N/A
2013/0213419	12/2012	Tucker et al.	N/A	N/A
2014/0109921	12/2013	Chen	N/A	N/A
2014/0209106	12/2013	Liu	131/329	A24F 40/40
2016/0324215	12/2015	Mironov	N/A	A61M 15/0011
2017/0341308	12/2016	Lemay et al.	N/A	N/A
2018/0184710	12/2017	Tucker et al.	N/A	N/A
2020/0214343	12/2019	Fursa	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
3 085 802	12/2018	CA	N/A
103416853	12/2012	CN	N/A
103416853	12/2015	CN	N/A
110274372	12/2018	CN	N/A
2 711 534	12/2017	EP	N/A
62-221526	12/1986	JP	N/A
2002-18960	12/2001	JP	N/A
2012-2342	12/2011	JP	N/A
2012-241561	12/2011	JP	N/A
2018-19681	12/2017	JP	N/A
2020-503866	12/2019	JP	N/A
10-2016-0016348	12/2015	KR	N/A
531750	12/1975	SU	N/A
WO 2012/173322	12/2011	WO	N/A
WO 2017/048782	12/2016	WO	N/A
WO 2018/211390	12/2017	WO	N/A
WO 2019/048841	12/2018	WO	N/A
WO 2020/002924	12/2019	WO	N/A

WO 2020/023540	12/2019	WO	N/A
WO 2020/081849	12/2019	WO	N/A

OTHER PUBLICATIONS

Russian Office Action and Search Report for Russian Application No. 2022113062, dated Dec. 28, 2022, with an English translation. cited by applicant

Russian Office Action and Search Report for Russian Application No. 2022113066, dated Dec. 29, 2022, with an English translation. cited by applicant

Russian Office Action and Search Report for Russian Application No. 2022112944, dated Nov. 9, 2022, with an English translation. cited by applicant

International Search Report for International Application No. PCT/JP2020/042573, dated Dec. 22, 2020. cited by applicant

International Search Report for International Application No. PCT/JP2020/042576, dated Dec. 22, 2020. cited by applicant

International Search Report for International Application No. PCT/JP2020/042577, dated Dec. 22, 2020. cited by applicant

Extended European Search Report for European Application No. 20954320.6, dated Jul. 3, 2023. cited by applicant

Extended European Search Report for European Application No. 20954319.8, dated May 19, 2023. cited by applicant

International Search Report (in Japanese), issued in PCT/JP2020/042580, dated Dec. 22, 2020. cited by applicant

Chinese Office Action and Search Report for Chinese Application No. 202080042063.7, dated Jan. 25, 2025, with English translation. cited by applicant

English translation of the International Search Report for International Application No. PCT/JP2020/042573, dated Dec. 22, 2020. cited by applicant

English translation of the International Search Report for International Application No. PCT/JP2020/042576, dated Dec. 22, 2020. cited by applicant

English translation of the International Search Report for International Application No. PCT/JP2020/042577, dated Dec. 22, 2020. cited by applicant

English translation of the International Search Report for International Application No. PCT/JP2020/042580, dated Dec. 22, 2020. cited by applicant

Russian Office Action and Search Report for Russian Application No. 2022112958, dated Dec. 9, 2022, with English Translation. cited by applicant

Chinese Office Action for Chinese Application No. 202080042063.7, dated Jun. 28, 2025, with English translation. cited by applicant

Primary Examiner: Wilson; Michael H.

Assistant Examiner: Moore; Stephanie Lynn

Attorney, Agent or Firm: Birch, Stewart, Kolasch & Birch, LLP

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) The present application is a continuation application of International Application No. PCT/JP2020/042580, filed on Nov. 16, 2020, which is hereby expressly incorporated by reference into the present application.

TECHNICAL FIELD

(1) The present invention relates to a cartridge, and a manufacturing method of the cartridge.

BACKGROUND ART

(2) Conventionally, heated tobacco products are known that are used to inhale an atmosphere containing aerosol, the aerosol being obtained by causing a dried leaf tobacco coming from plants in the genus *Nicotiana tobacum*, a reconstituted tobacco containing plants in the same genus, strips and granules of the reconstituted tobacco, and/or a mixture thereof to pass through vapor of alcohol, without burning the same, and by causing ingredients derived from a leaf tobacco and the like to transfer to a gas phase. Furthermore, there are known electronic tobacco products that are used to inhale an atmosphere in which vapor and outside air are mixed, the vapor being generated by atomizing or vaporizing aromatic alcoholic or aqueous solutions by an appropriate electric component (hereinafter, in the present specification, such heated tobacco products and electronic tobacco products will be collectively referred to as “vapor product(s)”). Such a vapor product includes a component for containing an aerosol source, a component for generating aerosol, a component forming a channel for aerosol, or the like. As such a component, a component made of resin is generally used from the standpoints of ease in processing, weight and the like.

(3) In the process of manufacturing the vapor product, a resin component is sometimes joined or welded with another component. As methods of joining resin components or a resin component and a metal component that form the vapor product, there are known a laser welding method and an ultrasonic welding method (see PTLs 1 to 4).

CITATION LIST

Patent Literature

(4) PTL 1: International Publication No. WO 2020/081849 PTL 2: International Publication No. WO 2020/023540 PTL 3: U.S. Patent Application No. 2020/0214343 PTL 4: Japanese Patent Laid-Open No. 2018-019681

SUMMARY OF INVENTION

Technical Problem

(5) When welding two components as mentioned above, the components have to be positioned relative to each other. To perform positioning of two components, it is conceivable to provide one component with a step section and the other component with a protruding section that fits the step section. However, when the protruding section and the step section are joined, melted resin is pushed out from a joined part and solidified resin (a leftover material) remains around the joined part. In the case where such a leftover material is present in an aerosol channel of a vapor product, aerosol passing through the aerosol channel may condense on the leftover material and liquid droplets may possibly be collected. As a result, the collected liquid droplets may flow into the mouth of a user, or performance of the vapor product may deviate from design due to a cross-sectional area of the aerosol channel being narrowed.

(6) Furthermore, such a leftover material may fall off at a later stage in the manufacturing of the vapor product to be accumulated on a transfer route or to get mixed in the product. Even when the leftover material does not fall off, appearance of the vapor product is impaired. Particularly, in the case where the leftover material is formed on a tank (a cartridge) that forms the vapor product and that is mainly for containing an aerosol source, the leftover material that is exposed is possibly erroneously recognized as a foreign substance in the aerosol source. Furthermore, a semi-finished product on which the leftover material is generated deviates from design dimensions, and may easily fall down at a later stage and block the transfer route.

(7) An object of the present invention is to prevent generation of a leftover material from a part, of a cartridge that forms a vapor product, for performing positioning.

Solution to Problem

(8) According to a first mode, there is provided a cartridge that is assembled in a part of a vapor

product that includes a heating element for heating an aerosol source. The cartridge includes a first component and a second component, at least one of which being formed of resin, a connection section that extends between the first component and the second component, with one end connected to the first component and another end connected to the second component, and a guide section that extends from the first component, and that is not joined or welded to the second component. The second component includes a receiving section where the guide section fits.

(9) According to the first mode, the first component includes the guide section, and the second component includes the receiving section, and thus, when connecting the first component and the second component by the connection section, the first component may be positioned relative to the second component by fitting the guide section in the receiving section. Furthermore, because the guide section is not joined or welded to the second component, generation of a leftover material from the guide section may be prevented. Additionally, to “fit” in the present specification refers not only to a case where the guide section and the receiving section are fitted together without a gap, but also to a case where the guide section is fitted in the receiving section with a gap provided between the guide section and the receiving section, the gap being such that the position of the connection section relative to the second component may be guided to an allowable range. That is, to “fit” in the present specification may also mean to “loosely fit”.

(10) A second mode is summarized as the cartridge according to the first mode, the cartridge including an aerosol channel where aerosol that is generated by evaporation of the aerosol source passes through, where at least a part of the aerosol channel is demarcated by at least one of the first component and the second component.

(11) According to the second mode, at least one of the first component and the second component demarcates the aerosol channel, and thus, at a time of connecting the first component and the second component by the connection section, positioning of the connection section and the first component relative to the second component may be performed at the component that demarcates such an aerosol channel, by fitting the guide section in the receiving section. Furthermore, a leftover material may be prevented from being generated from the guide section at the component that demarcates the aerosol channel. Furthermore, as described above, the cartridge according to the second mode is formed of resin. Demarcation as described above of the aerosol channel by at least a part of the first component and the second component may be achieved by integrally die-molding each of the components in such a way that there is included a portion at which at least a part of the component forms the aerosol channel. This enables an assembly step or a bonding step necessary in the case of molding separate bodies to be omitted, and because there are no fitting sections or bonded parts, the component can be easily handled and is not easily broken when a consumer holds it in his/her hand at the time of use in spite of being a small resin component. However, the design is restricted with respect to shape of the aerosol channel in such a way that the two components may each be allowed to be integrally die-molded.

(12) A third mode is summarized as the cartridge according to the first or second mode, the cartridge including a space capable of containing the aerosol source, where at least a part of the space is demarcated by at least one of the first component and the second component.

(13) According to the third mode, at least one of the first component and the second component demarcates the space capable of containing the aerosol source, and thus, at a time of connecting the first component and the second component by the connection section, positioning of the connection section and the first component relative to the second component may be performed at the component that demarcates such a space, by fitting the guide section in the receiving section. Furthermore, a leftover material may be prevented from being generated from the guide section at the component that demarcates the space. Furthermore, as described above, the cartridge according to the third mode citing the first and second modes is formed of resin. Provision of the space that is capable of containing the aerosol source and demarcation of at least a part of the space by at least one of the first component and the second component described above may be achieved by

integrally die-molding each of the components in such a way that there is included a portion at which at least a part of the component forms the aerosol channel and there is included a portion that forms the space that is capable of containing the aerosol source. The effects described in the second mode may thus also be obtained.

(14) A fourth mode is summarized as the cartridge according to any one of the first to third modes, where at least a part of the heating element is housed in at least one of the first component and the second component.

(15) According to the fourth mode, at least one of the first component and the second component houses at least a part of the heating element, and thus, at a time of connecting the first component and the second component by the connection section, positioning of the connection section and the first component relative to the second component may be performed at the component that houses such a heating element, by fitting the guide section in the receiving section. Furthermore, a leftover material may be prevented from being generated from the guide section at the component that houses the heating element. Furthermore, the cartridge according to the fourth mode may be easily used at the time of use by a consumer because assembly with the heating element is not required.

(16) A fifth mode is summarized as the cartridge according to any one of the first to fourth modes, where the guide section is disposed to overlap the other end of the connection section when seen along a direction perpendicular to a direction in which the connection section extends between the first component and the second component.

(17) According to the fifth mode, because the guide section is disposed to cover the other end of the connection section from a side, a leftover material that is generated when the connection section is joined or welded to the second component is covered by the guide section and is prevented from being exposed.

(18) A sixth mode is summarized as the cartridge according to any one of the first to fifth modes, where the second component includes a facing surface that faces the first component, a first opening formed in the facing surface, and a first opening edge that demarcates at least a part of the first opening, and the receiving section is the first opening.

(19) According to the sixth mode, the connection section and the first component may be positioned relative to the second component by fitting the guide section in the first opening. At this time, because the guide section is fitted in the first opening, a leftover material that is generated from the connection section is prevented by the guide section from being exposed to the first opening. In other words, the guide section may prevent the leftover material from entering the first opening. Additionally, in the present specification, the “facing surfaces” of the first component and the second component refer to surfaces that directly face each other in the direction in which the connection section extends between the first component and the second component. Members other than the connection section are not present between the facing surface of the first component and the facing surface of the second component. The “facing surfaces” of the first component and the second component may also be said to be surfaces that are at an angle relative to the direction in which the connection section extends between the first component and the second component.

(20) A seventh mode is summarized as the cartridge according to the sixth mode, where the first opening has an annular shape when seen along a direction in which the connection section extends between the first component and the second component, the first opening edge includes an opening outer edge and an opening inner edge that demarcate the first opening, and the guide section fits with the opening outer edge or the opening inner edge, the guide section having an annular shape when seen along the direction in which the connection section extends between the first component and the second component.

(21) According to the seventh mode, the guide section having an annular shape is fitted with the opening outer edge or the opening inner edge of the first opening, and the connection section and the first component may thus be positioned relative to the second component. At this time, because the guide section is fitted with the opening outer edge or the opening inner edge, a leftover material

that is generated from the connection section may be prevented by the guide section from being exposed to the first opening. In other words, the guide section may prevent the leftover material from entering the first opening.

(22) According to an eighth mode, there is provided a manufacturing method of the cartridge according to any one of the first to seventh modes. In the manufacturing method of the cartridge, the first component is a lid member, and the second component is a cylindrical member. The manufacturing method of the cartridge includes connecting a heating assembly including the heating element to one end of the cylindrical member and closing an opening on the one end of the cylindrical member, filling an inside of the cylindrical member, to which the heating assembly is connected, with the aerosol source, and joining or welding the connection section to another end of the cylindrical member filled with the aerosol source.

(23) When the aerosol source is put in a cylindrical member with a bottom to which the heating assembly is not assembled, up to assembly of the heating assembly has to be completed to prevent leakage of the aerosol source from the cylindrical member. By contrast, according to the eighth mode, the heating assembly can be assembled with the cylindrical member before filling with the aerosol source is performed, and thus, for example, the cylindrical member to which the heating assembly is connected may be manufactured in advance as one unit and then be transported, and filling with the aerosol source and joining or welding of the lid member may be performed at another place.

(24) A ninth mode is summarized as the manufacturing method of the cartridge according to the eighth mode, the manufacturing method including ultrasonically welding the connection section of the lid member to the other end of the cylindrical member.

(25) According to a tenth mode, there is provided a manufacturing method of the cartridge according to any one of the first to seventh modes. The manufacturing method of the cartridge includes fitting the guide section in the receiving section and positioning the first component and the second component relative to each other, and joining or welding the other end of the connection section to the second component.

(26) According to the tenth mode, at the time of joining or welding, to the second component, the connection section that is connected to the first component, the connection section and the first component may be positioned relative to the second component by fitting the guide section in the receiving section.

(27) An eleventh mode is summarized as the manufacturing method of the cartridge according to the tenth mode, where the guide section extends in parallel to the connection section, and is, in a direction in which the connection section extends, longer than the connection section before the connection section is joined or welded to the second component, and the manufacturing method includes fitting the guide section in the receiving section and positioning the first component and the second component relative to each other before the other end of the connection section is joined or welded to the second component.

(28) According to the eleventh mode, because the guide section is longer than the connection section that is not yet joined or welded to the second component, the first component and the second component may be positioned relative to each other before the connection section that is connected to the first component is joined or welded to the second component.

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) FIG. 1 is an exploded perspective view of a vapor product according to a present embodiment.
- (2) FIG. 2 is an exploded perspective view of a cartridge.
- (3) FIG. 3A is a perspective view of a tank main body.

(4) FIG. 3B is a cross-sectional view of the tank main body seen along arrows 3B-3B shown in FIG. 3A.

(5) FIG. 4A is a perspective view of a lid.

(6) FIG. 4B is a cross-sectional view including a center of the lid.

(7) FIG. 5A is a cross-sectional view cutting a tank along a longitudinal direction.

(8) FIG. 5B is an enlarged view of a connection section between the lid and the tank main body shown in FIG. 5A.

(9) FIG. 6A is a schematic view showing a manufacturing process of the cartridge.

(10) FIG. 6B is a schematic view showing the manufacturing process of the cartridge.

(11) FIG. 6C is a schematic view showing the manufacturing process of the cartridge.

(12) FIG. 6D is a schematic view showing the manufacturing process of the cartridge.

(13) FIG. 6E is a schematic view showing the manufacturing process of the cartridge.

(14) FIG. 6F is a schematic view showing the manufacturing process of the cartridge.

DESCRIPTION OF EMBODIMENTS

(15) Hereinafter, an embodiment of the present invention will be described with reference to the drawings. In the drawings described below, same or corresponding structural elements are denoted by a same reference sign, and redundant description is omitted.

(16) FIG. 1 is an exploded perspective view of a vapor product according to the present embodiment. A vapor product **100** is a device used to inhale an atmosphere containing aerosol, the aerosol being obtained by a method, among a plurality of methods for generating aerosol, of causing aerosol generated by heating an aerosol source extending outside from a container section of a cartridge by an electric heater or by atomizing the aerosol source by application of ultrasonic waves to pass through strips/granules of a reconstituted tobacco, and thereby causing ingredients derived from a leaf tobacco and the like to transfer to a gas phase. Additionally, the above example is not restrictive, and the vapor product **100** may be a device that is used to inhale aerosol containing aromatic components, with which an aerosol source mixing components such as nicotine/menthol, flavors and alcohol is heated or atomized.

(17) As shown in FIG. 1, the vapor product **100** includes a main body unit **10**, and a cartridge **30** and a tobacco capsule **12** that are detachably attached to the main body unit **10**. The main body unit **10** includes a power supply unit **14**, a holding unit **16**, and a mouthpiece **18**. The power supply unit **14**, the holding unit **16**, and the mouthpiece **18** are each formed into a cylindrical shape. The mouthpiece **18** may be screwed to one end of the holding unit **16**, and the power supply unit **14** may be connected to the other end of the holding unit **16**, for example. In the present specification, a direction along which the mouthpiece **18**, the holding unit **16**, and the power supply unit **14** are coupled will be referred to as a longitudinal direction.

(18) The power supply unit **14** includes a battery **14a**, a switch **14b**, pin electrodes **14c**, and an engaging section **14d**. The battery **14a** is housed inside the power supply unit **14**. The switch **14b** is capable of switching on or off the power of the vapor product **100** by being held down in a state where the vapor product **100** is assembled, for example. The pin electrodes **14c** contact electrodes, described later, of the cartridge **30** and may electrically connect the battery **14a** and the electrodes, when the vapor product **100** is assembled in a state where the cartridge **30** is housed inside the holding unit **16**. The engaging section **14d** may cause the holding unit **16** and the power supply unit **14** to be engaged with each other, by engaging with an engagement receiving section, not shown, inside the holding unit **16**. The power supply unit **14** includes a controller **14e** for controlling power to be supplied by the battery **14a** to the electrodes of the cartridge **30**. Furthermore, the power supply unit **14** may include a puff sensor, not shown. In this case, the controller **14e** may control the battery **14a** such that power is supplied by the battery **14a** to the cartridge **30** when a puff is detected.

(19) The holding unit **16** includes a cylindrical body **16a**, and houses the cartridge **30** inside the cylindrical body **16a**, with the electrodes, described later, of the cartridge **30** facing the power

supply unit **14**. By attaching the mouthpiece **18** to the holding unit **16** in a state where the cartridge **30** is housed in the holding unit **16**, the cartridge **30** may be fixed inside the holding unit **16**. The holding unit **16** includes, at the cylindrical body **16a**, a window **16c** for visually checking the aerosol source contained in the cartridge **30**, and an air hole **16b** for supplying air to the cartridge **30**.

(20) The mouthpiece **18** includes a screw section **18a** to be screwed with the holding unit **16**, and a cylindrical section **18b** that extends in the longitudinal direction from the screw section **18a**. A user may inhale aerosol generated by the vapor product **100** by holding the cylindrical section **18b** in his/her mouth.

(21) The tobacco capsule **12** includes a capsule section **12a** for containing strips/granules of a reconstituted tobacco inside, and a filter section **12b**. The capsule section **12a** has a cylindrical shape, and a mesh is formed on an end surface on one side, for example, and an opening is formed in an end surface on the other side. The size of the mesh that is formed on the end surface on one side of the capsule section **12a** may be designed in such a way that strips/granules of the reconstituted tobacco contained in the capsule section **12a** do not escape from the capsule section **12a**. The filter section **12b** is fitted with the opening of the capsule section **12a** to close the opening. The tobacco capsule **12** may be detachably attached into the cylindrical section **18b** of the mouthpiece **18** in the longitudinal direction, from an opposite side from the holding unit **16**.

(22) The cartridge **30** stores a liquid aerosol source, and generates aerosol by atomizing the aerosol source when power is supplied from the power supply unit **14**. The aerosol source may include at least one of water, propylene glycol, and glycerin, for example. A specific structure of the cartridge **30** will be described later. The cartridge **30** that includes an atomization function of atomizing the aerosol source in the manner described above is sometimes referred to as a cartomizer.

(23) A method of using the vapor product **100** will be described. First, the switch **14b** is pressed in a state where the vapor product **100** is assembled, and the power is switched on. Next, a user holds the cylindrical section **18b** in his/her mouth and inhales. At this time, when inhalation by the user is detected by the puff sensor, not shown, of the power supply unit **14**, power is supplied from the battery **14a** of the power supply unit **14** to the electrodes of the cartridge **30**, and aerosol is generated at the cartridge **30**. The aerosol generated at the cartridge **30** passes through the strips/granules of the reconstituted tobacco inside the tobacco capsule **12** due to inhalation by the user, and is supplied into the mouth of the user together with ingredients derived from a leaf tobacco and the like.

(24) Next, a detailed description will be given of the cartridge **30** shown in FIG. 1. FIG. 2 is an exploded perspective view of the cartridge **30**. As shown in FIG. 2, the cartridge **30** includes a tank **50** that has a bottomed cylindrical shape, a gasket **31** that is substantially disc-shaped and that is to be housed inside the tank **50**, a mesh body **32** that is substantially disc-shaped, a heating section **33**, an atomization container **34**, and a heater holder **35**.

(25) The tank **50** includes an opening **51** through which the gasket **31**, the mesh body **32**, the heating section **33**, the atomization container **34**, and the heater holder **35** are to be inserted inside, a circumferential wall **52** that demarcates the opening **51**, and a pair of engaging holes **53** formed in the circumferential wall **52**. The engaging holes **53** are for fixing the heater holder **35** to the tank **50**.

(26) The gasket **31** is formed such that an outer diameter is substantially the same as an inner diameter of the tank **50**. The gasket **31** performs positioning of the mesh body **32**, and also, maintains the shape of the mesh body **32**. The gasket **31** includes, at a center in a radial direction, an insertion hole **31a** through which a channel tube **61** (see FIGS. 3A and 3B), described later, of the tank **50** can be inserted, and includes, around the insertion hole **31a**, openings **31b** (four in the drawing) that allow the aerosol source in the tank **50** to pass through. The gasket **31** is housed inside the tank **50** in such a way that the channel tube **61**, described later, is inserted through the insertion hole **31a**.

(27) The mesh body **32** is disposed in contact with the gasket **31** in a manner covering the openings **31b** of the gasket **31**. The mesh body **32** is a porous medium made of fiber such as cotton, for example, and holds the aerosol source that passed through the openings **31b** of the gasket **31**. An insertion hole **32a** that allows insertion of the channel tube **61**, described later, is formed at a center of the mesh body **32** in the radial direction. The mesh body **32** is positioned when the channel tube **61**, described later, is inserted through the insertion hole **32a** and the mesh body **32** contacts the gasket **31**.

(28) The heating section **33** atomizes a liquid aerosol source. The heating section **33** includes a wick **33a** that is substantially U-shaped, and a heating wire **33b** (corresponding to an example of a heating element) wound around the wick **33a**. The wick **33a** is made of glass fiber or the like, and absorbs and holds the aerosol source held at the mesh body **32**. Aerosol is generated when the aerosol source that is held at the wick **33a** is heated and atomized by the heating wire **33b**. In FIG. 2, the mesh body **32** and the heating section **33** are shown as one body, but the heating section **33** is housed inside the atomization container **34** and is connected to the heater holder **35**, and forms a heating assembly **38** together with the atomization container **34** and the heater holder **35**.

(29) The atomization container **34** includes a container section **34a** for housing the heating section **33**, and a fitting section **34b** to be fitted with the heater holder **35**. The atomization container **34** is formed by an elastic member, such as a resin material such as silicone resin, for example. As illustrated, the fitting section **34b** includes a groove section **34c** that is cross-shaped, and projecting sections **34d** formed by the groove section **34c**. End portions of the heating wire **33b** of the heating section **33** housed in the container section **34a** enter the groove section **34c** from holes, not shown, and are wound around the projecting sections **34d**.

(30) The heater holder **35** is formed into a substantially cup shape as a whole, and includes a side wall section **35a**, a bottom wall section **35b**, and a pair of electrodes **35c**. The pair of electrodes **35c** is exposed from a bottom surface of the bottom wall section **35b**, as illustrated, and is also exposed on an inside of the side wall section **35a**. The fitting section **34b** of the atomization container **34** is fitted with the side wall section **35a**. At this time, each of the end portions of the heating wire **33b** wound around the projecting sections **34d** of the fitting section **34b** come into contact with one of the pair of electrodes **35c**. The side wall section **35a** includes a claw **35d** that is to be engaged with the engaging hole **53** of the tank **50**.

(31) The heating assembly **38** is assembled by fitting the fitting section **34b** of the atomization container **34** with the heater holder **35** and by housing the heating section **33** in the container section **34a** of the atomization container **34**. The heating assembly **38** is fixed to the tank **50**, with the wick **33a** of the heating section **33** in contact with the mesh body **32**, by fitting the heating assembly **38** with the tank **50** and causing the claw **35d** to be engaged with the engaging hole **53** of the tank **50**. The opening **51** of the tank **50** is thereby closed by the heating assembly **38**.

(32) Next, the structure of the tank **50** shown in FIG. 2 will be described in detail. In the present embodiment, the tank **50** is formed from at least two components, and a connection section for connecting the two components to each other. Specifically, the tank **50** according to the present embodiment includes a tank main body **60** (corresponding to an example of a cylindrical member), and a lid **80** (corresponding to an example of a lid member), and the tank **50** is formed by connecting the tank main body **60** and the lid **80** to each other by the connection section (the tank main body **60** and the lid **80** each correspond to an example of a first component or a second component). In the present embodiment, the tank main body **60** and the lid **80** are both formed of resin, but this is not restrictive, and one of the tank main body **60** and the lid **80** may be formed of resin and the other one may be formed of a different material such as metal.

(33) FIG. 3A is a perspective view of the tank main body **60**. FIG. 3B is a cross-sectional view of the tank main body **60** seen along arrows **3B-3B** shown in FIG. 3A. As shown in FIG. 3A, in the present specification, an end portion of the tank main body **60** on the mouthpiece **18** side will be referred to as a first end portion **60a**, and an end portion on an opposite side will be referred to as a

second end portion **60b**. As shown in FIGS. 3A and 3B, the tank main body **60** includes the circumferential wall **52** and the channel tube **61**. The circumferential wall **52** demarcates a part of a space **52a** where the aerosol source can be contained. The channel tube **61** demarcates a part of an aerosol channel **61a** where aerosol that is generated by evaporation of the aerosol source passes through. In the present specification, a direction in which the channel tube **61** and the circumferential wall **52** extend is referred to as a longitudinal direction. The channel tube **61** is disposed within the circumferential wall **52**, and demarcates a part of the space **52a** together with the circumferential wall **52**. In other words, the space **52a** is formed between an inner surface of the circumferential wall **52** and an outer surface of the channel tube **61**. As shown in FIG. 3B, the channel tube **61** extends to the first end portion **60a** of the tank main body **60**, and forms a part of an end surface of the first end portion **60a**. In the illustrated example, the tank main body **60** is formed into a cylindrical or columnar shape as a whole, but may be formed into any shape such as a square cylindrical shape without being limited to the examples mentioned above.

(34) A plurality of ribs **62** (in the illustrated example, three) are provided between the inner surface of the circumferential wall **52** and the outer surface of the channel tube **61**, in a manner extending between the circumferential wall **52** and the channel tube. That is, the ribs **62** support the channel tube **61**. In the illustrated example, the ribs **62** are provided on the first end portion **60a** side of the tank main body **60**, and are disposed at equal intervals in a circumferential direction while being disposed radially when seen along the longitudinal direction.

(35) On the inner surface of the circumferential wall **52**, protruding sections **63** are integrally formed with the ribs **62**. The protruding section **63** extends in the longitudinal direction, from the rib **62** toward the second end portion **60b**. The protruding section **63** extends from an end portion, of the rib **62**, on the second end portion **60b** side to before a tip end, of the channel tube **61**, on the second end portion **60b** side. The protruding sections **63** increase mechanical strength of the tank main body **60**, and also perform positioning of the gasket **31**.

(36) The tank main body **60** includes the opening **51** for inserting the gasket **31**, the mesh body **32** and the heating assembly **38** shown in FIG. 2. At least a part of the heating assembly **38** including the heating wire **33b** is housed in a space **64** in the tank main body **60**, on a side more to the second end portion **60b** than the channel tube **61**. A part of the heating assembly **38** may protrude outside the tank main body **60** without being housed in the space **64**.

(37) The tank main body **60** includes, on the first end portion **60a**, a facing surface **65** (corresponding to an example of a second facing surface) that faces the lid **80** described later. The facing surface **65** of the tank main body **60** here refers to a surface that directly faces the lid **80** in a direction along which a first connection section **90** and a second connection section **92**, described later, extend (the longitudinal direction). In the following, the direction along which the first connection section **90** and the second connection section **92** extend will sometimes be referred to as the longitudinal direction. The facing surface **65** can also be said to be a surface that directly faces the lid **80** and that is at an angle relative to the longitudinal direction. Accordingly, an outer surface of the circumferential wall **52** of the tank main body **60** extends substantially in parallel to the longitudinal direction and is thus not a facing surface with respect to the lid **80**, and an end surface of the second end portion **60b** of the tank main body **60** does not directly face the lid **80** and is thus not a facing surface. As shown in FIG. 3B, the facing surface **65** includes an outermost edge **65a** (corresponding to an example of a second outermost edge). In the illustrated example, the outermost edge **65a** has a circular shape when seen along the longitudinal direction, but the outermost edge **65a** may be formed into any shape without being limited thereto.

(38) As shown in FIGS. 3A and 3B, a first opening **66** may be formed in the facing surface **65**. In the illustrated example, the first opening **66** is formed into an annular shape when seen along the longitudinal direction, and is demarcated by an opening inner edge **66a** (corresponding to an example of a first opening edge) and an opening outer edge **66b** (corresponding to an example of the first opening edge) formed on the facing surface **65**. Accordingly, the opening inner edge **66a**

and the opening outer edge **66b** each have a circular shape when seen along the longitudinal direction. In this case, the opening inner edge **66a** and the opening outer edge **66b** are desirably positioned concentrically. In the present embodiment, the first opening **66** communicates with the space **52a** where the aerosol source can be contained.

(39) Furthermore, a second opening **67** may be further formed in the facing surface **65**. In the illustrated example, the second opening **67** is formed into a circular shape when seen along the longitudinal direction, and is demarcated by a second opening edge **67a** formed on the facing surface **65**. Accordingly, the second opening edge **67a** has a circular shape when seen along the longitudinal direction. In the present embodiment, the second opening **67** communicates with the aerosol channel **61a**. Additionally, in the present embodiment, the shape of the second opening **67** is circular, but this is not restrictive, and the shape may be an annular shape like that of the first opening **66**, and in this case, the second opening edge **67a** demarcates a part of the second opening **67** as an opening edge on an outer side.

(40) As shown in FIGS. **3A** and **3B**, the facing surface **65** may include a first recessed section **68** (corresponding to an example of a recessed section) provided between the outermost edge **65a** and the opening outer edge **66b**, and a second recessed section **69** (corresponding to an example of the recessed section) provided between the opening inner edge **66a** and the second opening edge **67a**. At least one of the first recessed section **68** and the second recessed section **69** may be provided on the facing surface **65**. Alternatively, it is also possible to omit the first recessed section **68** and the second recessed section **69**.

(41) As shown in FIG. **3A**, in the present embodiment, the first recessed section **68** and the second recessed section **69** are annular grooves that extend along the circumferential direction of the tank main body **60**. However, such a case is not restrictive, and planar shapes of the first recessed section **68** and the second recessed section **69** may take any shape. As shown in FIG. **3B**, the first recessed section **68** includes a bottom section **68a** and a side wall section **68b**. In the illustrated example, the side wall section **68b** has a tapered surface **68b** that causes the width of the first recessed section **68** to be reduced toward the bottom section **68a**. Furthermore, the second recessed section **69** includes a bottom section **69a** and a side wall section **69b**. In the illustrated example, the side wall section **69b** includes a tapered surface **69b** that causes the width of the second recessed section **69** to be reduced toward the bottom section **69a**.

(42) FIG. **4A** is a perspective view of the lid **80**. FIG. **4B** is a cross-sectional view including a center of the lid **80**. As shown in FIGS. **4A** and **4B**, the lid **80** includes a flat plate section **80a** that is substantially disc-shaped. An opening **80b** that communicates with the second opening **67** of the tank main body **60** may be provided at substantially center of the flat plate section **80a**. The lid **80** is provided with a first connection section **90** (corresponding to an example of a connection section) and a second connection section **92** (corresponding to an example of the connection section), the first connection section **90** and the second connection section **92** each having one end thereof connected to one surface of the flat plate section **80a**. The first connection section **90** or the second connection section **92** may be integrally formed with the lid **80** or may be connected to the lid **80** by being joined or welded. Furthermore, it is also possible to provide the lid **80** with only one of the first connection section **90** and the second connection section **92**. Other ends of the first connection section **90** and the second connection section **92** are joined or welded to the tank main body **60**. When seen along a direction in which the second connection section **92** extends between the lid **80** and the tank main body **60**, the second connection section **92** is positioned more inward from the first connection section **90**. Furthermore, as shown in FIG. **4A**, the first connection section **90** and the second connection section **92** may be ridge sections having an annular shape when seen along the direction in which the first connection section **90** and the second connection section **92** extend between the lid **80** and the tank main body **60** (the longitudinal direction). In FIG. **4B**, a cross-sectional shape of each of the ridge sections is rectangular, but the shape is not limited thereto and may be polygonal, such as triangular, or may be circular with the ridge section having a round

tip end. Furthermore, the cross-sectional shape of the ridge section and a cross-sectional shape of the first recessed section **68** or the second recessed section **69** are desirably not similar to each other. Furthermore, the first connection section **90** and the second connection section **92** are desirably disposed substantially concentrically on a cross-section perpendicular to the longitudinal direction. The aerosol channel **61a** that can be housed at a center of the tank **50** and that is separate from the space **52a** may thus be formed.

(43) The other end of the first connection section **90** is joined or welded to the first recessed section **68** of the tank main body **60**. A melted material (a leftover material) that is generated when the first connection section **90** is joined or welded may thus be accumulated in the first recessed section **68**. Accordingly, the leftover material from the first connection section **90** may be prevented from being exposed between the lid **80** and the tank main body **60**. Furthermore, the other end of the first connection section **90** may be joined or welded to the facing surface **65** of the tank main body **60**, at a position away from the outermost edge **65a** of the facing surface **65**. This may prevent the leftover material from the first connection section **90** from being exposed from the outermost edge **65a** of the facing surface **65** of the tank main body **60**. Moreover, the other end of the first connection section **90** may be joined or welded to the facing surface **65** of the tank main body **60**, at a position away from the opening outer edge **66b**. This may prevent the leftover material from the first connection section **90** from being exposed in the first opening **66**. The other end of the first connection section **90** is desirably joined or welded to the bottom section **68a** of the first recessed section **68**. This allows the leftover material from the first connection section **90** to be accumulated in the bottom section **68a**, and the leftover material may be efficiently contained in the first recessed section **68**.

(44) The other end of the second connection section **92** is joined or welded to the second recessed section **69** of the tank main body **60**. A melted material (a leftover material) that is generated when the second connection section **92** is joined or welded may thus be accumulated in the second recessed section **69**. Accordingly, the leftover material from the second connection section **92** may be prevented from being exposed between the lid **80** and the tank main body **60**. The other end of the second connection section **92** may be joined or welded to the facing surface **65** of the tank main body **60**, at a position away from the opening inner edge **66a**. This may prevent the leftover material from the second connection section **92** from being exposed in the first opening **66**. Furthermore, the other end of the second connection section **92** may be joined or welded to the facing surface **65**, at a position away from the second opening edge **67a**. This may prevent the leftover material from the second connection section **92** from being exposed in the second opening **67**. The other end of the second connection section **92** is desirably joined or welded to the bottom section **69a** of the second recessed section **69**. This allows the leftover material from the second connection section **92** to be accumulated in the bottom section **69a**, and the leftover material may be efficiently contained in the second recessed section **69**. The first connection section **90** and the second connection section **92** are desirably capable of being welded to the tank main body **60** by ultrasonic welding.

(45) The lid **80** includes a facing surface **80d** (corresponding to an example of a first facing surface) that faces the tank main body **60**. The facing surface **80d** of the lid **80** here refers to a surface that directly faces the tank main body **60** in the longitudinal direction. The facing surface **80d** can also be said to be a surface that directly faces the tank main body **60** and that is at an angle relative to the longitudinal direction. As shown in FIG. **4B**, the facing surface **80d** includes an outermost edge **80c** (corresponding to an example of a first outermost edge). In the illustrated example, the outermost edge **80c** has a circular shape when seen along the longitudinal direction, but the outermost edge **80c** may be formed into any shape without being limited thereto. Furthermore, the facing surface **80d** includes an opening edge **80e** that demarcates the opening **80b**. The opening edge **80e** can also be said to be an innermost edge of the lid **80**.

(46) The lid **80** is connected to the tank main body **60** by the first connection section **90** and the

second connection section **92**, and the first opening **66** of the tank main body **60** is thereby closed. At this time, the lid **80** demarcates a part of the aerosol channel **61a**, and the opening **80b** of the lid **80** forms a part of the aerosol channel **61a**. Furthermore, the lid **80** demarcates a part of the space **52a** where the aerosol source can be contained, by the first opening **66** of the tank main body **60** being closed by the lid **80**.

(47) The lid **80** is further provided with a guide section **95** that extends from the facing surface **80d** of the lid **80**. As shown in FIG. 4A, the guide section **95** may be formed into an annular shape when seen along the longitudinal direction. The guide section **95** may have any shape, and a plurality of pin-shaped guide sections **95** may be provided, for example. In the present embodiment, the guide section **95** is to fit into the first opening **66** of the tank main body **60**. More specifically, the guide section **95** is to fit with the opening outer edge **66b** that demarcates the first opening **66**. The lid **80** may thus be positioned relative to the tank main body **60** at the time of joining or welding the first connection section **90** and the second connection section **92** to the tank main body **60**. At this time, because the guide section **95** is fitted with the opening outer edge **66b** of the first opening **66**, exposure of the leftover material generated from the first connection section **90** toward the first opening **66** may be prevented by the guide section **95**. In other words, the guide section **95** may prevent the leftover material from the first connection section **90** from entering the first opening **66**.

(48) The guide section **95** may be provided on the lid **80** in such a way as to be fitted with the opening inner edge **66a** that demarcates the first opening **66**. Furthermore, two guide sections **95** may be provided on the lid **80** to be fitted with both the opening inner edge **66a** and the opening outer edge **66b**. As shown in FIG. 4B, the guide section **95** is desirably longer than the first connection section **90** or the second connection section **92** in the longitudinal direction.

(49) FIG. 5A is a cross-sectional view cutting the tank **50** along the longitudinal direction. FIG. 5B is an enlarged view of the connection section between the lid **80** and the tank main body **60** shown in FIG. 5A. As shown in FIGS. 5A and 5B, the lid **80** includes an extending section **82** that extends, in a direction perpendicular to the longitudinal direction, from a connection part between the first connection section **90** and the lid **80** toward the outermost edge **65a** of the tank main body. The leftover material from the first connection section **90** may thus be prevented from being exposed to outside from a gap between the lid **80** and the tank main body **60**.

(50) As shown in FIGS. 5A and 5B, the guide section **95** is not joined or welded to the tank main body **60**. Accordingly, generation, from the guide section **95**, of a leftover material that is generated by melting of the guide section **95** may be prevented. Furthermore, as illustrated, when seen along the direction perpendicular to the direction (the longitudinal direction) of extension of the first connection section **90** and the second connection section **92** between the lid **80** and the tank main body **60**, the guide section **95** is disposed to overlap a connection portion between the first connection section **90** and the first recessed section **68**. Accordingly, a leftover material that is generated when the first connection section **90** is joined or welded to the tank main body **60** (the first recessed section **68**) is covered by the guide section **95**, and may be prevented from being exposed in the first opening **66**.

(51) Furthermore, in the present embodiment, in a state where the lid **80** is joined to the tank main body **60**, a gap is present between the outermost edge **80c** of the lid **80** and the tank main body **60**, and these are not joined or welded. Furthermore, a gap is also present between the outermost edge **65a** of the facing surface **65** of the tank main body **60** and the lid **80**, and these are not joined or welded. When the outermost edge **80c** of the lid **80** or the outermost edge **65a** of the tank main body **60** is joined or welded to a component, a material (a leftover material) generated by melting of such a part is possibly exposed to outside the tank **50**. By contrast, according to the present embodiment, the outermost edge **80c** of the lid **80** or the outermost edge **65a** of the tank main body **60** is not joined or welded to any part, and thus, the outermost edge **80c** and the outermost edge **65a** are not melted, and exposure of leftover materials therefrom to outside the tank **50** may be prevented. More specifically, in the present embodiment, the outermost edge **80c** of the lid **80** and

the outermost edge **65a** of the tank main body **60** are desirably not joined or welded to each other. When the outermost edge **80c** of the lid **80** and the outermost edge **65a** of the tank main body **60** are joined or welded to each other, a leftover material is possibly exposed from the outermost edge **80c** and the outermost edge **65a**. By contrast, in the case where the outermost edge **80c** of the lid **80** and the outermost edge **65a** of the tank main body **60** are not joined or welded to each other, exposure of a leftover material from the outermost edge **80c** and the outermost edge **65a** may be prevented.

(52) As shown in FIGS. 5A and 5B, the tank **50** may include a gap between the outermost edge **80c** of the lid **80** and the outermost edge **65a** of the tank main body **60**. This allows a leftover material generated between the lid **80** and the tank main body **60** to be accumulated in the gap, and thus, leftover materials generated from the first connection section **90** and the second connection section **92** may be accumulated in the gap, and exposure of the leftover materials to outside the tank **50** may be better prevented.

(53) As shown in FIGS. 5A and 5B, with the tank **50**, the opening inner edge **66a** or the opening outer edge **66b** of the first opening **66** is desirably not joined or welded to the lid **80**. Generation of a leftover material from the opening inner edge **66a** or the opening outer edge **66b** is thereby prevented, and exposure of a leftover material in the first opening **66** (the space **52a**) may be prevented, and erroneous recognition of mixing of a foreign substance in the aerosol source may be prevented.

(54) As shown in FIGS. 5A and 5B, with the tank **50**, the second opening edge **67a** of the second opening **67** is desirably not joined or welded to the lid **80**. Generation of a leftover material from the second opening edge **67a** is thereby prevented, and exposure of a leftover material in the second opening **67** (the aerosol channel **61a**) may be prevented, and aerosol may be prevented from condensing on the leftover material. Furthermore, with the tank **50**, the opening edge **80e** that demarcates the opening **80b** of the lid **80** is desirably not joined or welded to the tank main body **60**. Generation of a leftover material from the opening edge **80e** is thereby prevented, and exposure of a leftover material in the opening **80b** may be prevented.

(55) As shown in FIGS. 5A and 5B, the facing surface **80d** of the lid **80** and the facing surface **65** of the tank main body **60** are desirably not joined or welded to each other. In other words, the lid **80** and the tank main body **60** are desirably fixed to each other only by the first connection section **90** and the second connection section **92**. Generation of a leftover material from the facing surface **80d** and the facing surface **65** is thereby prevented, and as a result, exposure of a leftover material to outside may be prevented.

(56) As shown in FIGS. 5A and 5B, a part of the first recessed section **68** of the tank main body **60** is desirably filled by a part of the first connection section **90** of the lid **80** (including a leftover material). In other words, the first recessed section **68** is desirably not completely filled by the first connection section **90**. The first recessed section **68** is thereby able to contain all the leftover material that is generated by melting of the first connection section **90**, and the leftover material may be prevented from sticking out from the first recessed section **68**. Furthermore, a part of the second recessed section **69** of the tank main body **60** is desirably filled by a part of the second connection section **92** of the lid **80** (including a leftover material). In other words, the second recessed section **69** is desirably not completely filled by the second connection section **92**. The second recessed section **69** is thereby able to contain all the leftover material that is generated by melting of the second connection section **92**, and the leftover material may be prevented from sticking out from the second recessed section **69**.

(57) Next, a manufacturing method of the cartridge **30** of the vapor product **100** will be described. FIGS. 6A to 6F are schematic views showing a manufacturing process of the cartridge **30**. As shown in FIG. 6A, first, the tank main body **60** for forming the cartridge **30** is prepared. At this time, the tank main body **60** may be installed with the second end portion **60b** positioned at the top. Additionally, in FIG. 6A, only the circumferential wall **52** of the tank main body **60** is shown, and

illustration of other structural elements is omitted.

(58) As shown in FIG. 6B, the gasket **31** is disposed inside the tank main body **60** from the opening **51** of the tank main body **60**. At this time, the channel tube **61** of the tank main body **60** is inserted through the insertion hole **31a** (see FIG. 2) of the gasket **31**, and positioning of the gasket **31** is performed by the protruding sections **63** (see FIG. 3B) of the tank main body **60**. Furthermore, as shown in FIG. 6C, the mesh body **32** is disposed inside the tank main body **60** from the opening **51** of the tank main body **60** to overlap the gasket **31**. At this time, the channel tube **61** of the tank main body **60** is inserted through the insertion hole **32a** (see FIG. 2) of the mesh body **32**. Then, as shown in FIG. 6D, the heating assembly **38** is connected to the second end portion **60b** of the tank main body **60**, and the opening **51** is closed. A part of the heating assembly **38** may be inserted into the tank main body **60** through the opening **51**.

(59) Subsequently, as shown in FIG. 6E, the space **52a** of the tank main body **60** to which the heating assembly **38** is connected is filled with aerosol source **L1**. At this time, the tank main body **60** may be installed with the first end portion **60a** positioned at the top. Lastly, as shown in FIG. 6F, the lid **80** is joined or welded to the first end portion **60a** of the tank main body **60** by ultrasonic welding, for example, and the cartridge **30** is thus manufactured. When the aerosol source **L1** is put in the bottomed tank main body **60** to which the heating assembly **38** is not assembled, up to assembly of the heating assembly **38** has to be completed to prevent leakage of the aerosol source **L1** from the tank main body **60**. By contrast, according to the processes shown in FIGS. 6A to 6E, the heating assembly **38** can be assembled with the tank main body **60** before filling with the aerosol source **L1** is performed, and thus, for example, the tank main body **60** to which the heating assembly **38** is connected as shown in FIG. 6D may be manufactured as one unit and then be transported, and filling with the aerosol source and joining or welding of the lid **80** may be performed as shown in FIGS. 6E and 6F at another place.

(60) In the process shown in FIG. 6F, a part of the first recessed section **68** of the tank main body **60** is desirably filled by a part of the first connection section **90** of the lid **80** (including a leftover material). In other words, the first recessed section **68** is desirably not completely filled by the first connection section **90**. The first recessed section **68** is thereby able to contain all the leftover material that is generated by melting of the first connection section **90**, and the leftover material may be prevented from sticking out from the first recessed section **68**. Furthermore, a part of the second recessed section **69** of the tank main body **60** is desirably filled by a part of the second connection section **92** of the lid **80** (including a leftover material). In other words, the second recessed section **69** is desirably not completely filled by the second connection section **92**. The second recessed section **69** is thereby able to contain all the leftover material that is generated by melting of the second connection section **92**, and the leftover material may be prevented from sticking out from the second recessed section **69**.

(61) In the process shown in FIG. 6F, the first connection section **90** and the second connection section **92** are desirably joined or welded to the tank main body **60** in such a way that the facing surface **80d** of the lid **80** and the facing surface **65** of the tank main body **60** are not joined or welded to each other. This prevents generation of a leftover material from the facing surface **80d** and the facing surface **65**, and as a result, exposure of a leftover material to outside may be prevented.

(62) In the process shown in FIG. 6F, the first connection section **90** and the second connection section **92** are desirably joined or welded to the tank main body **60** in a state where the lid **80** and the tank main body **60** are positioned relative to each other by fitting the guide section **95** with the first opening **66** (the opening outer edge **66b**). Furthermore, as shown in FIG. 4B, the guide section **95** extends in parallel to the first connection section **90** and the second connection section **92**, and is, in the direction in which the first connection section **90** and the second connection section **92** extend (the longitudinal direction), longer than the first connection section **90** and the second connection **92** before the two are joined or welded to the tank main body **60**. Accordingly, the guide

section **95** may be fitted in the first opening **66** and the lid **80** and the tank main body **60** may be positioned relative to each other before the first connection section **90** and the second connection section **92** are joined or welded to the tank main body **60**.

(63) Heretofore, an embodiment of the present invention has been described, but the present invention is not limited to the embodiment described above, and various modifications may be made within the scope of the claims and within the technical ideas described in the specification and the drawings. Additionally, any shape and material not described explicitly in the specification and the drawings are included in the scope of the technical ideas of the present invention as long as they exhibit the same functions and effects as those of the present invention.

(64) In the following, some of modes disclosed by the present specification will be described.

(65) According to a first mode, there is provided a cartridge that is assembled in a part of a vapor product that includes a heating element for heating an aerosol source. The cartridge includes a first component and a second component, at least one of which being formed of resin, and a connection section whose one end is connected to the first component and whose another end is joined or welded to the second component. The second component includes a recessed section. The other end of the connection section is joined or welded to the recessed section.

(66) According to the first mode, because the second component includes the recessed section to which the other end of the connection section is joined or welded, a melted material from the connection section may be accumulated in the recessed section. Accordingly, the melted material (a leftover material) from the connection section may be prevented from being exposed between the first component and the second component.

(67) A second mode is summarized as the cartridge according to the first mode, the cartridge including an aerosol channel where aerosol that is generated by evaporation of the aerosol source passes through, where at least a part of the aerosol channel is demarcated by at least one of the first component and the second component.

(68) According to the second mode, because the aerosol channel is demarcated by at least one of the first component and the second component, a leftover material may be prevented from being exposed in such an aerosol channel, and condensation of aerosol on a leftover material may be prevented. Furthermore, as described above, the cartridge according to the second mode is formed of resin. Demarcation as described above of the aerosol channel by at least a part of the first component and the second component may be achieved by integrally die-molding each of the components in such a way that there is included a portion that forms a part of the recessed section mentioned above and there is included a portion at which at least a part of the component forms the aerosol channel. This enables an assembly step or a bonding step necessary in the case of molding separate bodies to be omitted, and because there are no fitting sections or bonded parts, the component can be easily handled and is not easily broken when a consumer holds it in his/her hand at the time of use in spite of being a small resin component. However, designs are restricted with respect to shapes of the recessed section and the aerosol channel in such a way that the two components may each be allowed to be integrally die-molded.

(69) A third mode is summarized as the cartridge according to the first mode or the second mode, the cartridge including a space capable of containing the aerosol source, where at least a part of the space is demarcated by at least one of the first component and the second component.

(70) According to the third mode, because at least one of the first component and the second component demarcates a space that is capable of containing the aerosol source, exposure of a leftover material in such a space may be prevented, and erroneous recognition of mixing of a foreign substance in the aerosol source may be prevented. Furthermore, as described above, the cartridge according to the third mode citing the first mode and the second mode is formed of resin. Provision of the space that is capable of containing the aerosol source and demarcation of at least a part of the space by at least one of the first component and the second component described above may be achieved by integrally die-molding each of the components in such a way that there is

included a portion that forms a part of the recessed section mentioned above or there is included a portion at which at least a part of the component forms the aerosol channel, and in such a way that there is included a portion that forms the space that is capable of containing the aerosol source. The effects described in the second mode may thus also be obtained.

(71) A fourth mode is summarized as the cartridge according to any one of the first to third modes, where at least a part of the heating element is housed in at least one of the first component and the second component.

(72) According to the fourth mode, because at least one of the first component and the second component houses at least a part of the heating element, exposure of a leftover material to such a heating element may be prevented. Furthermore, the cartridge according to the fourth mode may be easily used at the time of use by a consumer because assembly with the heating element is not required.

(73) A fifth mode is summarized as the cartridge according to any one of the first to fourth modes, where the first component includes a flat plate section, the connection section is a ridge section that has an annular shape and that is provided on a flat surface of the flat plate section, and the recessed section is a groove extending along the ridge section.

(74) According to the fifth mode, the annular ridge section is joined or welded to the annular groove. Accordingly, exposure of a leftover material at an annular joined or welded part may be prevented. Furthermore, when the annular ridge section is joined or welded to the annular groove, a closed space may be formed by the first component, the second component, and the connection section, and such a space may be made a space for containing the aerosol source, for example.

(75) A sixth mode is summarized as the cartridge according to any one of the first to fifth modes, where the first component includes a facing surface that faces the second component, the connection section includes a first connection section and a second connection section, each of the first connection section and the second connection section has one end connected to the first component and another end joined or welded to the second component, and has an annular shape when seen along a direction in which the first connection section and the second connection section extend between the first component and the second component, the second connection section is positioned more inward from the first connection section when seen along the direction in which the second connection section extends between the first component and the second component, and the recessed section includes a first recessed section to which the other end of the first connection section is joined or welded, and a second recessed section to which the other end of the second connection section is joined or welded.

(76) According to the sixth mode, the annular first connection section and the annular second connection section are joined or welded to the first recessed section and the second recessed section, respectively. Accordingly, exposure of a leftover material at an annular joined or welded part may be prevented. Furthermore, when the annular first connection section and the annular second connection section are joined or welded to the first recessed section and the second recessed section, an annular closed space and a separate space inside such a space may be formed by the first component, the second component, the first connection section, and the second connection section. Accordingly, the closed space may be made a space for containing the aerosol source, for example, and the separate space may be made the aerosol channel. Additionally, in the present specification, the “facing surfaces” of the first component and the second component refer to surfaces that directly face each other in a direction in which the connection section extends between the first component and the second component, and members other than the connection section are not present between the facing surface of the first component and the facing surface of the second component. The “facing surfaces” of the first component and the second component may also be said to be surfaces that are at an angle relative to the direction in which the connection section extends between the first component and the second component.

(77) A seventh mode is summarized as the cartridge according to the sixth mode, where the first

connection section and the second connection section are disposed substantially concentrically on a cross-section perpendicular to the first direction.

(78) According to the seventh mode, a separate space may be formed at a center of the annular closed space in the first component and the second component. Accordingly, the space at the center may be made the aerosol channel.

(79) An eighth mode is summarized as the cartridge according to any one of the first to seventh modes, where the recessed section includes a bottom section, and the other end of the connection section is joined or welded to the bottom section of the recessed section.

(80) According to the eighth mode, because the other end of the connection section is joined or welded to the bottom section of the recessed section, a melted material (a leftover material) from the connection section may be accumulated in the bottom section, and the leftover material may be efficiently contained in the recessed section.

(81) A ninth mode is summarized as the cartridge according to the eighth mode, where the recessed section includes a side wall section, and the side wall section includes a tapered surface that causes a width of the recessed section to be reduced toward the bottom section.

(82) According to the ninth mode, the other end of the joining section is guided along the tapered surface at a time of joining or welding of the other end of the connection section to the recessed section, and thus, the other end of the connection section may be easily joined or welded to the bottom section of the recessed section.

(83) A tenth mode is summarized as the cartridge according to any one of the first to ninth modes, where a part of the recessed section of the second component is filled by a part of the connection section.

(84) According to the tenth mode, a part of the recessed section is filled by the connection section, or in other words, the recessed section is not completely filled by the connection section, and thus, the recessed section may contain all the melted material (a leftover material) from the connection section, and the leftover material may be prevented from sticking out from the recessed section.

(85) According to an eleventh mode, there is provided a manufacturing method of the cartridge according to any one of the first to tenth modes. In the manufacturing method of the cartridge, the first component is a lid member, and the second component is a cylindrical member. The manufacturing method of the cartridge includes connecting a heating assembly including the heating element to one end of the cylindrical member and closing an opening on the one end of the cylindrical member, filling an inside of the cylindrical member, to which the heating assembly is connected, with the aerosol source, and joining or welding the connection section to another end of the cylindrical member filled with the aerosol source.

(86) When the aerosol source is put in a cylindrical member with a bottom to which the heating assembly is not assembled, up to assembly of the heating assembly has to be completed to prevent leakage of the aerosol source from the cylindrical member. By contrast, according to the eleventh mode, the heating assembly can be assembled with the cylindrical member before filling with the aerosol source is performed, and thus, for example, the cylindrical member to which the heating assembly is connected may be manufactured in advance as one unit and then be transported, and filling with the aerosol source and joining or welding of the lid member may be performed at another place.

(87) A twelfth mode is summarized as the cartridge according to the eleventh mode, the cartridge including ultrasonically welding the connection section of the lid member to the other end of the cylindrical member.

(88) According to a thirteenth mode, there is provided a manufacturing method of the cartridge according to any one of the first to tenth modes. The manufacturing method of the cartridge includes joining or welding the connection section of the first component to the second component, and filling a part of the recessed section of the second component by a part of the connection section.

- (89) According to the thirteenth mode, a part of the recessed section is filled by the connection section, or in other words, the recessed section is not completely filled by the connection section, and thus, the recessed section may contain all the melted material (a leftover material) from the connection section, and the leftover material may be prevented from sticking out from the recessed section.
- (90) According to a fourteenth mode, there is provided a cartridge including a heating element for heating an aerosol source. The cartridge includes a first component and a second component, at least one of which being formed of resin, and a connection section whose one end is connected to the first component and whose another end is joined or welded to the second component. The second component includes a facing surface that faces the first component, and an outermost edge of the facing surface. The other end of the connection section is joined or welded to the facing surface of the second component, at a position away from the outermost edge.
- (91) According to the fourteenth mode, because the connection section is at a position away from the outermost edge of the facing surface of the second component, a melted material (a leftover material) from the connection section may be prevented from being exposed from the outermost edge of the facing surface of the second component. Additionally, in the present specification, the “facing surfaces” of the first component and the second component refer to surfaces that directly face each other in the direction in which the connection section extends between the first component and the second component, and members other than the connection section are not present between the facing surface of the first component and the facing surface of the second component. The “facing surfaces” of the first component and the second component may also be said to be surfaces that are at an angle relative to the direction in which the connection section extends between the first component and the second component.
- (92) A fifteenth mode is summarized as the cartridge according to the fourteenth mode, the cartridge including an aerosol channel where aerosol that is generated by evaporation of the aerosol source passes through, where at least a part of the aerosol channel is demarcated by at least one of the first component and the second component.
- (93) According to the fifteenth mode, because the aerosol channel is demarcated by at least one of the first component and the second component, a leftover material may be prevented from being exposed in such an aerosol channel, and condensation of aerosol on a leftover material may be prevented. Furthermore, as described above, the cartridge according to the fifteenth mode is formed of resin. Demarcation as described above of the aerosol channel by at least a part of the first component and the second component may be achieved by integrally die-molding each of the components in such a way that there is included a portion that forms a part of the recessed section mentioned above and there is included a portion at which at least a part of the component forms the aerosol channel. This enables an assembly step or a bonding step necessary in the case of molding separate bodies to be omitted, and because there are no fitting sections or bonded parts, the component can be easily handled and is not easily broken when a consumer holds it in his/her hand at the time of use in spite of being a small resin component. However, designs are restricted with respect to shapes of the recessed section and the aerosol channel in such a way that the two components may each be allowed to be integrally die-molded.
- (94) A sixteenth mode is summarized as the cartridge according to the fourteenth or fifteenth mode, the cartridge including a space capable of containing the aerosol source, where at least a part of the space is demarcated by at least one of the first component and the second component.
- (95) According to the sixteenth mode, because at least one of the first component and the second component demarcates a space that is capable of containing the aerosol source, exposure of a leftover material in such a space may be prevented, and erroneous recognition of mixing of a foreign substance in the aerosol source may be prevented. Furthermore, as described above, the cartridge according to the sixteenth mode citing the fourteenth mode and the fifteenth mode is formed of resin. Provision of the space that is capable of containing the aerosol source and

demarcation of at least a part of the space by at least one of the first component and the second component described above may be achieved by integrally die-molding each of the components in such a way that there is included a portion that forms a part of the recessed section mentioned above or there is included a portion at which at least a part of the component forms the aerosol channel, and in such a way that there is included a portion that forms the space that is capable of containing the aerosol source. The effects described in the fifteenth mode may thus also be obtained.

(96) A seventeenth mode is summarized as the cartridge according to any one of the fourteenth to sixteenth modes, where at least a part of the heating element is housed in at least one of the first component and the second component.

(97) According to the seventeenth mode, because at least one of the first component and the second component houses at least a part of the heating element, exposure of a leftover material to such a heating element may be prevented. Furthermore, the cartridge according to the seventeenth mode may be easily used at the time of use by a consumer because assembly with the heating element is not required.

(98) An eighteenth mode is summarized as the cartridge according to any one of the fourteenth to seventeenth modes, where the second component includes a first opening formed in the facing surface, and a first opening edge that demarcates at least a part of the first opening, and the other end of the connection section is joined or welded to the end surface of the second component, at a position away from the first opening edge.

(99) According to the eighteenth mode, exposure of a leftover material in the first opening may be prevented.

(100) A nineteenth mode is summarized as the cartridge according to the eighteenth mode, where the first opening has an annular shape when seen along a direction in which the connection section extends between the first component and the second component, the first opening edge includes an opening outer edge and an opening inner edge that demarcate the first opening, the connection section includes a first connection section and a second connection section, each of the first connection section and the second connection section has one end connected to the first component and another end joined or welded to the second component, and has an annular shape when seen along a direction in which the first connection section and the second connection section extend between the first component and the second component, the second connection section is positioned more inward from the first connection section when seen along the direction in which the second connection section extends between the first component and the second component, the other end of the first connection section is joined or welded to the second component, at a position away from the opening outer edge, and the other end of the second connection section is joined or welded to the second component, at a position away from the opening inner edge.

(101) According to the nineteenth mode, melted materials (leftover materials) from the first connection section and the second connection section may be prevented from being exposed in the first opening.

(102) A twentieth mode is summarized as the cartridge according to the nineteenth mode, where the second component includes a second opening that is positioned more inward from the first opening when seen along the direction in which the second connection section extends between the first component and the second component, and a second opening edge that demarcates at least a part of the second opening, and the other end of the second connection section is joined or welded to the second component, at a position away from the second opening edge.

(103) According to the twentieth mode, a melted material (a leftover material) from the second connection section may be prevented from being exposed in the second opening.

(104) A twenty-first mode is summarized as the cartridge according to any one of the fourteenth to twentieth modes, where the first component includes an extending section that extends, in a direction perpendicular to a direction of extension of the connection section, from the one end of

the connection section toward the outermost edge of the second component.

(105) According to the twenty-first mode, because the first component includes the extending section, a leftover material may be prevented from being exposed to outside from a gap between the first component and the second component.

(106) According to a twenty-second mode, there is provided a manufacturing method of the cartridge according to any one of the fourteenth to twenty-first mode. In the manufacturing method of the cartridge, the first component is a lid member, and the second component is a cylindrical member. The manufacturing method of the cartridge includes connecting a heating assembly including the heating element to one end of the cylindrical member and closing an opening on the one end of the cylindrical member, filling an inside of the cylindrical member, to which the heating assembly is connected, with the aerosol source, and joining or welding the connection section to another end of the cylindrical member filled with the aerosol source.

(107) When the aerosol source is put in a cylindrical member with a bottom to which the heating assembly is not assembled, up to assembly of the heating assembly has to be completed to prevent leakage of the aerosol source from the cylindrical member. By contrast, according to the twenty-second mode, the heating assembly can be assembled with the cylindrical member before filling with the aerosol source is performed, and thus, for example, the cylindrical member to which the heating assembly is connected may be manufactured in advance as one unit and then be transported, and filling with the aerosol source and joining or welding of the lid member may be performed at another place.

(108) A twenty-third mode is summarized as the manufacturing method of the cartridge according to the twenty-second mode, the manufacturing method including ultrasonically welding the connection section of the lid member to the other end of the cylindrical member.

(109) According to a twenty-fourth mode, there is provided a cartridge that is assembled in a part of a vapor product that includes a heating element for heating an aerosol source. The cartridge includes a first component and a second component, at least one of which being formed of resin, and a connection section whose one end is connected to the first component and whose another end is joined or welded to the second component. The first component includes a first facing surface that faces the second component, and a first outermost edge of the first facing surface. The second component includes a second facing surface that faces the first component, and a second outermost edge of the second facing surface. The first outermost edge and the second component are not joined or welded to each other, and the second outermost edge and the first component are not joined or welded to each other.

(110) When the first outermost edge or the second outermost edge is joined or welded to a component, a melted material (a leftover material) from these parts is exposed to outside the components. According to the twenty-fourth mode, the first outermost edge of the first component and the second outermost edge of the second component are not joined or welded to any part, and thus, the first outermost edge and the second outermost edge are not melted, and exposure of leftover materials therefrom to outside the components may be prevented. Additionally, in the present specification, the “first facing surface” of the first component and the “second facing surface” of the second component are surfaces of the first component and the second component that directly face each other in the direction in which the connection section extends between the first component and the second component. Members other than the connection section are not present between the facing surface of the first component and the facing surface of the second component. The “facing surfaces” of the first component and the second component may also be said to be surfaces that are at an angle relative to the direction in which the connection section extends between the first component and the second component.

(111) A twenty-fifth mode is summarized as the cartridge according to the twenty-fourth mode, the cartridge including an aerosol channel where aerosol that is generated by evaporation of the aerosol source passes through, where at least a part of the aerosol channel is demarcated by at least one of

the first component and the second component.

(112) According to the twenty-fifth mode, because the aerosol channel is demarcated by at least one of the first component and the second component, a leftover material may be prevented from being exposed in such an aerosol channel, and condensation of aerosol on a leftover material may be prevented. Furthermore, as described above, the cartridge according to the twenty-fifth mode is formed of resin. Demarcation as described above of the aerosol channel by at least a part of the first component and the second component may be achieved by integrally die-molding each of the components in such a way that there is included a portion that forms a part of the recessed section mentioned above and there is included a portion at which at least a part of the component forms the aerosol channel. This enables an assembly step or a bonding step necessary in the case of molding separate bodies to be omitted, and because there are no fitting sections or bonded parts, the component can be easily handled and is not easily broken when a consumer holds it in his/her hand at the time of use in spite of being a small resin component. However, designs are restricted with respect to shapes of the recessed section and the aerosol channel in such a way that the two components may each be allowed to be integrally die-molded.

(113) A twenty-sixth mode is summarized as the cartridge according to the twenty-fourth or twenty-fifth mode, the cartridge including a space capable of containing the aerosol source, where at least a part of the space is demarcated by at least one of the first component and the second component.

(114) According to the twenty-sixth mode, because at least one of the first component and the second component demarcates a space that is capable of containing the aerosol source, exposure of a leftover material in such a space may be prevented, and erroneous recognition of mixing of a foreign substance in the aerosol source may be prevented. Furthermore, as described above, the cartridge according to the twenty-sixth mode citing the twenty-fourth mode and the twenty-fifth mode is formed of resin. Provision of the space that is capable of containing the aerosol source and demarcation of at least a part of the space by at least one of the first component and the second component described above may be achieved by integrally die-molding each of the components in such a way that there is included a portion that forms a part of the recessed section mentioned above or there is included a portion at which at least a part of the component forms the aerosol channel, and in such a way that there is included a portion that forms the space that is capable of containing the aerosol source. The effects described in the twenty-fifth mode may thus also be obtained.

(115) A twenty-seventh mode is summarized as the cartridge according to any one of the twenty-fourth to twenty-sixth modes, where at least a part of the heating element is housed in at least one of the first component and the second component.

(116) According to the twenty-seventh mode, because at least one of the first component and the second component houses at least a part of the heating element, exposure of a leftover material to such a heating element may be prevented. Furthermore, the cartridge according to the twenty-seventh mode may be easily used at the time of use by a consumer because assembly with the heating element is not required.

(117) A twenty-eighth mode is summarized as the cartridge according to any one of the twenty-fourth to twenty-seventh modes, where the first outermost edge and the second outermost edge are not joined or welded to each other.

(118) When the first outermost edge of the first component and the second outermost edge of the second component are joined or welded to each other, a leftover material is exposed from the first outermost edge and the second outermost edge. By contrast, according to the twenty-eighth mode, because the first outermost edge and the second outermost edge are not joined or welded to each other, exposure of a leftover material from the first outermost edge and the second outermost edge may be prevented.

(119) A twenty-ninth mode is summarized as the cartridge according to the twenty-eighth mode, the

cartridge including a gap between the first outermost edge and the second outermost edge.

(120) According to the twenty-ninth mode, because there is a gap where a leftover material generated between the first component and the second component may be retained, exposure, to outside, of the leftover material generated from the connection section that is joined or welded to the second component may be better prevented.

(121) A thirtieth mode is summarized as the cartridge according to any one of the twenty-fourth to twenty-ninth modes, where the second component includes a first opening formed in the second facing surface, and a first opening edge that demarcates at least a part of the first opening, and the first opening edge is not joined or welded to the first component.

(122) According to the thirtieth mode, because the first opening edge is not joined or welded to the first component, a leftover material is not generated from the first opening edge, and exposure of a leftover material in the first opening may be prevented.

(123) A thirty-first mode is summarized as the cartridge according to the thirtieth mode, where the first opening has an annular shape when seen along a direction in which the connection section extends between the first component and the second component, the first opening edge includes an opening outer edge and an opening inner edge that demarcate the first opening, and the opening outer edge and the opening inner edge are not joined or welded to the first component.

(124) According to the thirty-first mode, because the opening outer edge and the opening inner edge are not joined or welded to the first component, exposure of a leftover material from the opening outer edge and the opening inner edge in the first opening may be prevented.

(125) A thirty-second mode is summarized as the cartridge according to the thirty-first mode, where the second component includes a second opening that is formed in the second facing surface and that is positioned more inward from the first opening when seen along the direction in which the connection section extends between the first component and the second component, and a second opening edge that demarcates at least a part of the second opening, and the second opening edge is not joined or welded to the first component.

(126) According to the thirty-second mode, because the second opening edge is not joined or welded to the first component, a leftover material is not generated from the second opening edge, and exposure of a leftover material in the second opening may be prevented.

(127) A thirty-third mode is summarized as the cartridge according to any one of the twenty-fourth to thirty-second modes, where the first facing surface of the first component and the second facing surface of the second component are not joined or welded to each other.

(128) According to the thirty-third mode, because the first facing surface of the first component and the second facing surface of the second component are not joined or welded to each other, a leftover material may be prevented from being generated from the first facing surface and the second facing surface, and as a result, exposure of a leftover material to outside may be prevented.

(129) According to a thirty-fourth mode, there is provided a manufacturing method of the cartridge according to any one of the twenty-fourth to thirty-third modes. In the manufacturing method of the cartridge, the first component is a lid member, and the second component is a cylindrical member. The manufacturing method of the cartridge includes connecting a heating assembly including the heating element to one end of the cylindrical member and closing an opening on the one end of the cylindrical member, filling an inside of the cylindrical member, to which the heating assembly is connected, with the aerosol source, and joining or welding the connection section to another end of the cylindrical member filled with the aerosol source.

(130) When the aerosol source is put in a cylindrical member with a bottom to which the heating assembly is not assembled, up to assembly of the heating assembly has to be completed to prevent leakage of the aerosol source from the cylindrical member. By contrast, according to the thirty-fourth mode, the heating assembly can be assembled with the cylindrical member before filling with the aerosol source is performed, and thus, for example, the cylindrical member to which the heating assembly is connected may be manufactured in advance as one unit and then be

transported, and filling with the aerosol source and joining or welding of the lid member may be performed at another place.

(131) A thirty-fifth mode is summarized as the manufacturing method of the cartridge according to the thirty-third mode, the manufacturing method including ultrasonically welding the connection section of the lid member to the other end of the cylindrical member.

(132) According to a thirty-sixth mode, there is provided the manufacturing method of the cartridge according to any one of the twenty-fourth to thirty-third modes. The manufacturing method of the cartridge includes joining or welding the other end of the connection section to the second component in such a way that the first facing surface of the first component and the second facing surface of the second component are not joined or welded to each other.

(133) According to the thirty-sixth mode, because the first facing surface of the first component and the second facing surface of the second component are not joined or welded to each other, a leftover material may be prevented from being generated from the first facing surface and the second facing surface, and as a result, exposure of a leftover material to outside may be prevented.

(134) According to a thirty-seventh mode, there is provided a cartridge that is assembled in a part of a vapor product that includes a heating element for heating an aerosol source. The cartridge includes a first component and a second component, at least one of which being formed of resin, a connection section that extends between the first component and the second component, with one end connected to the first component and another end connected to the second component, and a guide section that extends from the first component, and that is not joined or welded to the second component. The second component includes a receiving section where the guide section fits.

(135) According to the thirty-seventh mode, the first component includes the guide section, and the second component includes the receiving section, and thus, when connecting the first component and the second component by the connection section, the first component may be positioned relative to the second component by fitting the guide section in the receiving section. Furthermore, because the guide section is not joined or welded to the second component, generation of a leftover material from the guide section may be prevented. Additionally, to “fit” in the present specification refers not only to a case where the guide section and the receiving section are fitted together without a gap, but also to a case where the guide section is fitted in the receiving section with a gap provided between the guide section and the receiving section, the gap being such that the position of the connection section relative to the second component may be guided to an allowable range. That is, to “fit” in the present specification may also mean to “loosely fit”.

(136) A thirty-eighth mode is summarized as the cartridge according to the thirty-seventh mode, the cartridge including an aerosol channel where aerosol that is generated by evaporation of the aerosol source passes through, where at least a part of the aerosol channel is demarcated by at least one of the first component and the second component.

(137) According to the thirty-eighth mode, at least one of the first component and the second component demarcates the aerosol channel, and thus, at a time of connecting the first component and the second component by the connection section, positioning of the connection section and the first component relative to the second component may be performed at the component that demarcates such an aerosol channel, by fitting the guide section in the receiving section. Furthermore, a leftover material may be prevented from being generated from the guide section at the component that demarcates the aerosol channel. Furthermore, as described above, the cartridge according to the thirty-eighth mode is formed of resin. Demarcation as described above of the aerosol channel by at least a part of the first component and the second component may be achieved by integrally die-molding each of the components in such a way that there is included a portion at which at least a part of the component forms the aerosol channel. This enables an assembly step or a bonding step necessary in the case of molding separate bodies to be omitted, and because there are no fitting sections or bonded parts, the component can be easily handled and is not easily broken when a consumer holds it in his/her hand at the time of use in spite of being a

small resin component. However, the design is restricted with respect to shape of the aerosol channel in such a way that the two components may each be allowed to be integrally die-molded. (138) A thirty-ninth mode is summarized as the cartridge according to the thirty-seventh or thirty-eighth mode, the cartridge including a space capable of containing the aerosol source, where at least a part of the space is demarcated by at least one of the first component and the second component.

(139) According to the thirty-ninth mode, at least one of the first component and the second component demarcates the space capable of containing the aerosol source, and thus, at a time of connecting the first component and the second component by the connection section, positioning of the connection section and the first component relative to the second component may be performed at the component that demarcates such a space, by fitting the guide section in the receiving section. Furthermore, a leftover material may be prevented from being generated from the guide section at the component that demarcates the space. Furthermore, as described above, the cartridge according to the thirty-ninth mode citing the thirty-seventh and thirty-eighth modes is formed of resin. Provision of the space that is capable of containing the aerosol source and demarcation of at least a part of the space by at least one of the first component and the second component described above may be achieved by integrally die-molding each of the components in such a way that there is included a portion at which at least a part of the component forms the aerosol channel and there is included a portion that forms the space that is capable of containing the aerosol source. The effects described in the thirty-eighth mode may thus also be obtained.

(140) A fortieth mode is summarized as the cartridge according to any one of the thirty-seventh to thirty-ninth modes, where at least a part of the heating element is housed in at least one of the first component and the second component.

(141) According to the fortieth mode, at least one of the first component and the second component houses at least a part of the heating element, and thus, at a time of connecting the first component and the second component by the connection section, positioning of the connection section and the first component relative to the second component may be performed at the component that houses such a heating element, by fitting the guide section in the receiving section. Furthermore, a leftover material may be prevented from being generated from the guide section at the component that houses the heating element. Furthermore, the cartridge according to the fortieth mode may be easily used at the time of use by a consumer because assembly with the heating element is not required.

(142) A forty-first mode is summarized as the cartridge according to any one of the thirty-seventh to fortieth modes, where the guide section is disposed to overlap the other end of the connection section when seen along a direction perpendicular to a direction in which the connection section extends between the first component and the second component.

(143) According to the forty-first mode, because the guide section is disposed to cover the other end of the connection section from a side, a leftover material that is generated when the connection section is joined or welded to the second component is covered by the guide section and is prevented from being exposed.

(144) A forty-second mode is summarized as the cartridge according to any one of the thirty-seventh to forty-first modes, where the second component includes a facing surface that faces the first component, a first opening formed in the facing surface, and a first opening edge that demarcates at least a part of the first opening, and the receiving section is the first opening.

(145) According to the forty-second mode, the connection section and the first component may be positioned relative to the second component by fitting the guide section in the first opening. At this time, because the guide section is fitted in the first opening, a leftover material that is generated from the connection section is prevented by the guide section from being exposed to the first opening. In other words, the guide section may prevent the leftover material from entering the first opening. Additionally, in the present specification, the “facing surfaces” of the first component and the second component refer to surfaces that directly face each other in the direction in which the

connection section extends between the first component and the second component. Members other than the connection section are not present between the facing surface of the first component and the facing surface of the second component. The “facing surfaces” of the first component and the second component may also be said to be surfaces that are at an angle relative to the direction in which the connection section extends between the first component and the second component.

(146) A forty-third mode is summarized as the cartridge according to the forty-second mode, where the first opening has an annular shape when seen along a direction in which the connection section extends between the first component and the second component, the first opening edge includes an opening outer edge and an opening inner edge that demarcate the first opening, and the guide section fits with the opening outer edge or the opening inner edge, the guide section having an annular shape when seen along the direction in which the connection section extends between the first component and the second component.

(147) According to the forty-third mode, the guide section having an annular shape is fitted with the opening outer edge or the opening inner edge of the first opening, and the connection section and the first component may thus be positioned relative to the second component. At this time, because the guide section is fitted with the opening outer edge or the opening inner edge, a leftover material that is generated from the connection section may be prevented by the guide section from being exposed to the first opening. In other words, the guide section may prevent the leftover material from entering the first opening.

(148) According to a forty-fourth mode, there is provided a manufacturing method of the cartridge according to any one of the thirty-seventh to forty-third modes. In the manufacturing method of the cartridge, the first component is a lid member, and the second component is a cylindrical member. The manufacturing method of the cartridge includes connecting a heating assembly including the heating element to one end of the cylindrical member and closing an opening on the one end of the cylindrical member, filling an inside of the cylindrical member, to which the heating assembly is connected, with the aerosol source, and joining or welding the connection section to another end of the cylindrical member filled with the aerosol source.

(149) When the aerosol source is put in a cylindrical member with a bottom to which the heating assembly is not assembled, up to assembly of the heating assembly has to be completed to prevent leakage of the aerosol source from the cylindrical member. By contrast, according to the forty-fourth mode, the heating assembly can be assembled with the cylindrical member before filling with the aerosol source is performed, and thus, for example, the cylindrical member to which the heating assembly is connected may be manufactured in advance as one unit and then be transported, and filling with the aerosol source and joining or welding of the lid member may be performed at another place.

(150) A forty-fifth mode is summarized as the manufacturing method of the cartridge according to the forty-fourth mode, the manufacturing method including ultrasonically welding the connection section of the lid member to the other end of the cylindrical member.

(151) According to a forty-sixth mode, there is provided a manufacturing method of the cartridge according to any one of the thirty-seventh to forty-third modes. The manufacturing method of the cartridge includes fitting the guide section in the receiving section and positioning the first component and the second component relative to each other, and joining or welding the other end of the connection section to the second component.

(152) According to the forty-sixth mode, at the time of joining or welding, to the second component, the connection section that is connected to the first component, the connection section and the first component may be positioned relative to the second component by fitting the guide section in the receiving section.

(153) A forty-seventh mode is summarized as the manufacturing method of the cartridge according to the forty-sixth mode, where the guide section extends in parallel to the connection section, and is, in a direction in which the connection section extends, longer than the connection section before

the connection section is joined or welded to the second component, and the manufacturing method includes fitting the guide section in the receiving section and positioning the first component and the second component relative to each other before the other end of the connection section is joined or welded to the second component.

(154) According to the forty-seventh mode, because the guide section is longer than the connection section that is not yet joined or welded to the second component, the first component and the second component may be positioned relative to each other before the connection section that is connected to the first component is joined or welded to the second component.

(155) According to a forty-eighth mode, there is provided a vapor product including the cartridge according to any one of the first to forty-seventh modes.

REFERENCE SIGNS LIST

(156) **30**: cartridge **33b**: heating wire **38**: heating assembly **50**: tank **51**: opening **52**: circumferential wall **52a**: space **60**: tank main body **60a**: first end portion **60b**: second end portion **61a**: aerosol channel **65**: facing surface **65a**: outermost edge **66**: first opening **66a**: opening inner edge **66b**: opening outer edge **67**: second opening **67a**: second opening edge **68**: first recessed section **68a**: bottom section **68b**: tapered surface **69**: second recessed section **69a**: bottom section **69b**: tapered surface **80**: lid **80a**: flat plate section **80b**: opening **80c**: outermost edge **80d**: facing surface **80e**: opening edge **82**: extending section **90**: first connection section **92**: second connection section **95**: guide section **100**: vapor product **L1**: aerosol source

Claims

1. A cartridge that is assembled in a part of a vapor product that includes a heating element for heating an aerosol source, the cartridge comprising: a first component and a second component, at least one of which being formed of resin; a connection section that extends in a longitudinal direction between the first component and the second component; and a guide section that extends from the first component in the longitudinal direction, and that is not joined or welded to the second component, wherein the guide section has an annular shape when seen along the longitudinal direction, wherein the second component includes a receiving section where the guide section fits, the receiving section is a first opening in which the guide section is inserted in the longitudinal direction, and which has an annular shape when seen along the longitudinal direction, and wherein the connection section has a first end in the longitudinal direction connected to the first component and not the guide section, and a second end welded to the second component opposite to the first end in the longitudinal direction.
2. The cartridge according to claim 1, further comprising an aerosol channel where aerosol that is generated by evaporation of the aerosol source passes through, wherein at least a part of the aerosol channel is demarcated by at least one of the first component and the second component.
3. The cartridge according to claim 1, further comprising a space capable of containing the aerosol source, wherein at least a part of the space is demarcated by at least one of the first component and the second component.
4. The cartridge according to claim 1, wherein at least a part of the heating element is housed in at least one of the first component and the second component.
5. The cartridge according to claim 1, wherein the guide section is disposed to overlap the second end of the connection section when seen along a direction perpendicular to a direction in which the connection section extends between the first component and the second component.
6. The cartridge according to claim 1, wherein the second component includes a facing surface that faces the first component, the first opening formed in the facing surface, and a first opening edge that demarcates at least a part of the first opening.
7. The cartridge according to claim 6, wherein the first opening edge includes an opening outer edge and an opening inner edge that demarcate the first opening, and wherein the guide section fits

with the opening outer edge or the opening inner edge.

8. A manufacturing method of the cartridge according to claim 1, wherein the first component is a lid member, and the second component is a cylindrical member, and the manufacturing method comprises: connecting a heating assembly including the heating element to a first end of the cylindrical member and closing an opening on the first end of the cylindrical member; filling an inside of the cylindrical member, to which the heating assembly is connected, with the aerosol source; and welding the connection section to a second end of the cylindrical member filled with the aerosol source.

9. The manufacturing method of the cartridge according to claim 8, comprising ultrasonically welding the connection section to the second end of the cylindrical member.

10. A manufacturing method of the cartridge according to claim 1, the manufacturing method comprising: fitting the guide section in the receiving section and positioning the first component and the second component relative to each other; and welding the second end of the connection section to the second component.

11. The manufacturing method of the cartridge according to claim 10, wherein the guide section extends in parallel to the connection section, and is, in a direction in which the connection section extends, longer than the connection section before the connection section is joined or welded to the second component, and the manufacturing method comprises fitting the guide section in the receiving section and positioning the first component and the second component relative to each other before the second end of the connection section is welded to the second component.
