

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405308
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Jang; Yong Seok et al.

Control program, container and semiconductor device manufacturing system for charging of wafer type sensor and auto teaching

Abstract

The present disclosure provides a control device for charging and auto teaching of a wafer type sensor, a control program executed by the control device, a wafer type sensor storage device, a wafer type sensor charging device, and a semiconductor device manufacturing facility. The control program is a program executed by a control device equipped with a processor, and monitors a semiconductor device manufacturing facility and its part using a wafer type sensor, and monitors the remaining battery level of the wafer type sensor.

Inventors: Jang; Yong Seok (Chungcheongnam-do, KR), Park; In Kyu (Gyeonggi-do, KR)

Applicant: SEMES Co., Ltd. (Chungcheongnam-do, KR)

Family ID: 81848890

Assignee: SEMES CO., LTD. (Chungcheongnam-do, KR)

Appl. No.: 17/543884

Filed: December 07, 2021

Prior Publication Data

Document Identifier	Publication Date
US 20220179000 A1	Jun. 09, 2022

Foreign Application Priority Data

KR	10-2020-0171125	Dec. 09, 2020
KR	10-2021-0037356	Mar. 23, 2021

Publication Classification

Int. Cl.: H02J7/00 (20060101); **G01R31/36** (20200101); **H01J37/32** (20060101); **H01L21/67** (20060101); **H01L21/68** (20060101)

U.S. Cl.:

CPC **G01R31/36** (20130101); **H01J37/32715** (20130101); **H01J37/32899** (20130101); **H01J37/32926** (20130101); **H01L21/67201** (20130101); **H01L21/67259** (20130101); **H01L21/68** (20130101); **H02J7/0048** (20200101);

Field of Classification Search

CPC: H01L (21/67259); H01L (21/68); H01J (37/32715); H02J (50/90)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6558962	12/2002	Nishiki	N/A	N/A
7135852	12/2005	Renken et al.	N/A	N/A
7855549	12/2009	Renken et al.	N/A	N/A
10014198	12/2017	Richardson	N/A	N/A
10541168	12/2019	Tan et al.	N/A	N/A
10665490	12/2019	Lee et al.	N/A	N/A
11569138	12/2022	Azarya et al.	N/A	N/A
2007/0142962	12/2006	Takizawa	414/744.5	H01L 21/67781
2008/0087116	12/2007	Rate	73/865.9	H01L 21/67259
2012/0247954	12/2011	Yamawaku et al.	N/A	N/A
2013/0080099	12/2012	Akada	307/104	H02J 50/12
2014/0122654	12/2013	Jensen	709/219	G05B 19/41865
2014/0346467	12/2013	Yun et al.	N/A	N/A
2017/0053819	12/2016	Richardson	N/A	N/A
2018/0025928	12/2017	Chito	N/A	N/A
2018/0301322	12/2017	Sugita et al.	N/A	N/A
2019/0033103	12/2018	Sugita et al.	N/A	N/A
2020/0194295	12/2019	Sugita et al.	N/A	N/A
2023/0119169	12/2022	Azarya et al.	N/A	N/A

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
102737940	12/2011	CN	N/A
102934213	12/2012	CN	N/A
104183529	12/2013	CN	N/A
104823273	12/2014	CN	N/A
107644830	12/2017	CN	N/A
107690604	12/2017	CN	N/A
108091589	12/2017	CN	N/A

2007-536726	12/2006	JP	N/A
2011091071	12/2010	JP	N/A
2011238823	12/2010	JP	N/A
2018526814	12/2017	JP	N/A
6598745	12/2018	JP	N/A
2020-096122	12/2019	JP	N/A
1020020066201	12/2001	KR	N/A
1020060135926	12/2005	KR	N/A
20070009600	12/2006	KR	N/A
1020170022907	12/2016	KR	N/A
1020190011617	12/2018	KR	N/A
1020190072669	12/2018	KR	N/A
20200004684	12/2019	KR	N/A
201842301	12/2017	TW	N/A
2005088683	12/2004	WO	N/A
2021180607	12/2019	WO	N/A

OTHER PUBLICATIONS

Japanese Notice of Reasons for Refusal for Japanese Application No. 2021-198285, dated Jan. 31, 2023 with translation, 14 pages. cited by applicant

Korean Request for the Submission of an Opinion for Korean Application No. 10-2021-0037356, dated Oct. 24, 2022 with translation, 20 pages. cited by applicant

Office Action (The First Office Action) issued Mar. 26, 2025, by the State Intellectual Property Office of People's Republic of China in corresponding Chinese Patent Application No.

202111515895.9 and an English translation of the Office Action. (23 pages). cited by applicant

Primary Examiner: Miller, Jr.; Joseph A

Attorney, Agent or Firm: Buchanan Ingersoll & Rooney PC

Background/Summary

CROSS REFERENCE TO RELATED APPLICATION

(1) This application claims the benefit of Korean Patent Application No. 10-2020-0171125, filed on Dec. 9, 2020, and 10-2021-0037356, filed on Mar. 23, 2021, in the Korean Intellectual Property Office, the disclosure of which is incorporated herein by reference in its entirety.

FIELD OF THE INVENTION

(2) The present invention relates to a wafer type sensor control device, a control program executed by the control device, a wafer type sensor storage device (container), a wafer type sensor charging device (load port module), and a semiconductor device manufacturing facility including the wafer type sensor charging device. More particularly, it relates to a control device, a control program, a container, a load port module, and a semiconductor device manufacturing facility for charging and auto teaching of a wafer type sensor.

BACKGROUND OF THE INVENTION

(3) The semiconductor device manufacturing process may be continuously performed in a semiconductor device manufacturing facility, and may be divided into a pre-process and a post-process. The semiconductor manufacturing facility may be installed in a space defined as a FAB to manufacture semiconductor devices.

(4) The pre-process refers to a process of forming a circuit pattern on a substrate (e.g., a wafer) to complete a chip. These pre-processes may comprise a deposition process for forming a thin film on a substrate, a photo lithography process for transferring a photo resist onto a thin film using a photo mask, an etching process for selectively removing unnecessary parts using a chemical material or reactive gas in order to form a desired circuit pattern on a substrate, an ashing process for removing the photoresist remaining after etching, an ion implantation process for implanting ions into the portion connected to a circuit pattern to have characteristics of an electronic device, a cleaning process for removing contamination sources from the substrate, and the like.

(5) The post-process refers to the process of evaluating the performance of the product finished through the pre-process. The post-processes may comprise a board inspection process for determining good products or defective products by inspecting the operation of each chip on the board, a package process for cutting and separating each chip through dicing, die bonding, wire bonding, molding, marking, etc. to have the shape of the product, a final inspection process for finally inspecting product characteristics and reliability through electrical characteristic inspection and burn-in inspection, and the like.

SUMMARY OF THE INVENTION

(6) In a semiconductor device manufacturing process, an etching chamber may be used to form a desired circuit pattern on a substrate. Such an etching facility may etch the substrate using plasma.

(7) When the etching facility uses plasma, an electrostatic chuck (ESC) may be installed as a substrate support unit to be used as a lower electrode. In this case, a ring assembly may be formed around the electrostatic chuck in order to prevent the side surface of the electrostatic chuck from being damaged by the plasma and to increase the efficiency of substrate etching.

(8) However, since the ring assembly is a consumable part that is gradually etched over time, it may adversely affect the substrate processing process if it is not periodically corrected in the position or replaced.

(9) An aspect of the present disclosure is an auto teaching system for monitoring a semiconductor device manufacturing facility and its part using a wafer type sensor, a control device included therein, and a control program executed by the control device.

(10) In addition, an aspect of the present disclosure is an auto teaching system that automatically charges the wafer type sensor for smooth use in case of emergency, and a wafer type sensor storage device (container) included therein, and a wafer type sensor charging device (load port module), and semiconductor device manufacturing facility.

(11) Aspects of the present disclosure are not limited to the aspects mentioned above, and other aspects not mentioned will be clearly understood by those skilled in the art from the following description.

(12) One aspect of the control program of the present disclosure for achieving the above object is a control program executed by a control device equipped with a processor, and comprises an instruction for monitoring a semiconductor device manufacturing facility and its part by using a wafer type sensor, and an instruction for monitoring a remaining battery level of the wafer type sensor.

(13) The control program may further comprise an instruction for monitoring whether a consumable part is centered in a substrate processing apparatus.

(14) The control program may further comprise an instruction for monitoring whether the consumable part is centered in response to the consumable part being replaced.

(15) Wherein the wafer type sensor may measure a gap between the consumable part and a chuck.

(16) The control program may further comprise an instruction for correcting a position of the consumable part by using a transfer robot based on correction information related to centering, in response to the consumable part being not centered.

(17) The control program may further comprise an instruction for charging the wafer type sensor using a battery charging device installed in a load port module (LPM) based on a remaining battery

level of the wafer type sensor being less than a reference value.

(18) The control program may further comprise an instruction for mounting the wafer type sensor in a container for charging the wafer type sensor.

(19) The control program may further comprise an instruction for seating the container, in which the wafer type sensor is mounted, on the load port module for charging the wafer type sensor.

(20) The control program may further comprise an instruction for monitoring a semiconductor device manufacturing facility and its parts after charging the wafer type sensor based on a remaining battery level of the wafer type sensor being less than a reference value.

(21) One aspect of the wafer type sensor storage device (container) of the present disclosure for achieving the above object includes a wafer type sensor, and charges the wafer type sensor using a load port module having a battery charging device.

(22) Wherein the container may charge the wafer type sensor in response to the wafer type sensor being mounted.

(23) Wherein the wafer type sensor may be mounted in the container for charging the wafer type sensor.

(24) The container may comprise a plurality of slots installed in a vertical direction inside the container.

(25) The container may comprise a first slot installed inside the container; and a second slot installed under the first slot, wherein different objects may be mounted in the first slot and the second slot.

(26) Wherein the wafer type sensor may be mounted in the first slot.

(27) Wherein the container may charge the wafer type sensor based on a monitoring result of a remaining battery level of the wafer type sensor.

(28) Wherein the container may be a FOUP.

(29) Wherein the container may charge the wafer type sensor using at least one of a magnetic resonance method and an electromagnetic induction method.

(30) One aspect of the wafer type sensor charging device (load port module) of the present disclosure for achieving the above object comprises a battery charging device, wherein a wafer type sensor mounted in a container is charged using the battery charging device.

(31) Wherein the battery charging device may comprise a power supply module for supplying first power; a power conversion module installed inside the load port module and for converting the first power into second power; and a power output terminal installed above the load port module and connected to a connector of the container.

(32) Wherein the battery charging device may charge the wafer type sensor in response to the container being seated on the load port module.

(33) One aspect of the semiconductor device manufacturing facility of the present disclosure for achieving the above object comprise a load port module installed as a front end module (FEM); an index module installed adjacent to the load port module and including a first transfer robot for transferring a substrate mounted in a container on the load port module; a plurality of process chambers for processing the substrate; and a transfer chamber installed adjacent to the process chamber and having a second transfer robot for carrying in an unprocessed substrate transferred by the first transfer robot into the process chamber, or carrying out a pre-processed substrate from the process chamber, wherein the load port module includes a battery charging device, wherein a wafer type sensor mounted in the container is charged using the battery charging device.

(34) Wherein the load port module may be plural.

(35) Wherein each container seated on each load port module may mount different objects.

(36) Wherein, among each of the containers, one container may mount the wafer type sensor, and the other container may mount the substrate.

(37) Wherein a plurality of process chambers may be disposed according to any one structure of a

cluster platform, a quad platform, and an inline platform.

(38) The details of other embodiments are included in the detailed description and drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) These and/or other aspects will become apparent and more readily appreciated from the following description of the embodiments, taken in conjunction with the accompanying drawings in which:
- (2) FIG. 1 is a diagram schematically illustrating an internal configuration of an auto teaching system according to an embodiment of the present disclosure;
- (3) FIG. 2 is a diagram schematically illustrating an internal structure of a substrate processing apparatus constituting an auto teaching system according to an embodiment of the present disclosure;
- (4) FIG. 3 is a diagram schematically illustrating an internal configuration of a wafer type sensor constituting an auto teaching system according to an embodiment of the present disclosure;
- (5) FIG. 4 is a first exemplary view for describing the role of the wafer type sensor constituting the auto teaching system according to an embodiment of the present disclosure;
- (6) FIG. 5 is a second exemplary view for describing the role of the wafer type sensor constituting the auto teaching system according to an embodiment of the present disclosure;
- (7) FIG. 6 is a first flowchart for illustratively describing a method of operating a control device constituting an auto teaching system according to an embodiment of the present disclosure;
- (8) FIG. 7 is a second flowchart for illustratively describing a method of operating a control device constituting an auto teaching system according to an embodiment of the present disclosure;
- (9) FIG. 8 is a third flowchart for illustratively describing a method of operating a control device constituting an auto teaching system according to an embodiment of the present disclosure;
- (10) FIG. 9 is a first exemplary diagram schematically illustrating an internal structure of a storage device constituting an auto teaching system according to an embodiment of the present disclosure;
- (11) FIG. 10 is a second exemplary diagram schematically illustrating an internal structure of a storage device constituting an auto teaching system according to an embodiment of the present disclosure;
- (12) FIG. 11 is a third exemplary diagram schematically illustrating an internal structure of a storage device constituting an auto teaching system according to an embodiment of the present disclosure;
- (13) FIG. 12 is a diagram schematically illustrating an internal structure of a load port module constituting an auto teaching system according to an embodiment of the present disclosure;
- (14) FIG. 13 is an exemplary diagram schematically illustrating a structure of a power output terminal constituting the load port module of FIG. 12;
- (15) FIG. 14 is an exemplary view for describing a storage method when not in use of a storage device constituting an auto teaching system according to an embodiment of the present disclosure;
- (16) FIG. 15 is an exemplary view of a semiconductor device manufacturing facility including a load port module according to the first embodiment;
- (17) FIG. 16 is an exemplary view of a semiconductor device manufacturing facility including a load port module according to a second embodiment; and
- (18) FIG. 17 is an exemplary view of a semiconductor device manufacturing facility including a load port module according to a third embodiment.

DETAILED DESCRIPTION OF THE INVENTION

- (19) Hereinafter, preferred embodiments of the present invention will be described in detail with reference to the accompanying drawings. Advantages and features of the present invention and

methods of achieving them will become apparent with reference to the embodiments described below in detail in conjunction with the accompanying drawings. However, the present invention is not limited to the embodiments described below, but may be implemented in various different forms, and these embodiments are provided only for making the description of the present invention complete and fully informing those skilled in the art to which the present invention pertains on the scope of the invention, and the present invention is only defined by the scope of the claims. Like reference numerals refer to like elements throughout.

(20) When an element or layer is referred as being located “on” another element or layer, it includes not only being located directly on the other element or layer, but also with intervening other layers or elements. On the other hand, when an element is referred as being “directly on” or “immediately on,” it indicates that no intervening element or layer is interposed.

(21) Spatially relative terms “below,” “beneath,” “lower,” “above,” and “upper” can be used to easily describe a correlation between an element or components and other elements or components. The spatially relative terms should be understood as terms including different orientations of the device during use or operation in addition to the orientation shown in the drawings. For example, when an element shown in the figures is turned over, an element described as “below” or “beneath” another element may be placed “above” the other element. Accordingly, the exemplary term “below” may include both directions below and above. The device may also be oriented in other orientations, and thus spatially relative terms may be interpreted according to orientation.

(22) Although first, second, etc. are used to describe various elements, components, and/or sections, it should be understood that these elements, components, and/or sections are not limited by these terms. These terms are only used to distinguish one element, component, or section from another element, component, or section. Accordingly, the first element, the first component, or the first section mentioned below may be the second element, the second component, or the second section within the technical spirit of the present invention.

(23) The terminology used herein is for the purpose of describing the embodiments and is not intended to limit the present disclosure. In the present disclosure, the singular also includes the plural, unless specifically stated otherwise in the phrase. As used herein, “comprises” and/or “comprising” refers to that components, steps, operations and/or elements mentioned does not exclude the presence or addition of one or more other components, steps, operations and/or elements.

(24) Unless otherwise defined, all terms (including technical and scientific terms) used herein may be used with the meaning commonly understood by those of ordinary skill in the art to which the present invention belongs. In addition, terms defined in a commonly used dictionary are not to be interpreted ideally or excessively unless clearly defined in particular.

(25) Hereinafter, embodiments of the present disclosure will be described in detail with reference to the accompanying drawings, and in the description with reference to the accompanying drawings, the same or corresponding components are given the same reference numbers, regardless of reference numerals in drawings, and an overlapped description therewith will be omitted.

(26) The present disclosure relates to a semiconductor device manufacturing facility used for manufacturing a semiconductor device and an auto teaching system applied to inspecting parts thereof. The auto teaching system according to the present disclosure can monitor a semiconductor device manufacturing facility and its parts using a wafer type sensor, and can automatically charge the wafer type sensor.

(27) Specifically, a semiconductor device manufacturing facility and its parts can be monitored using a control device constituting the auto teaching system and a program executed by the control device, and a storage device and charging device constituting the auto teaching system can be used to automatically charge the wafer type sensor for smooth use in case of emergency.

(28) Hereinafter, the present disclosure will be described in detail with reference to drawings and the like.

(29) FIG. 1 is a diagram schematically illustrating an internal configuration of an auto-teaching system according to an embodiment of the present disclosure.

(30) The auto teaching system **100** is applied to a semiconductor device manufacturing facility, and is a system for auto teaching full automation.

(31) Referring to FIG. 1, the auto teaching system **100** may include a substrate processing apparatus **110**, a wafer type sensor **120**, a control device **130**, a storage device **140**, and a charging device **150**.

(32) The substrate processing apparatus **110** is an apparatus for processing a substrate (e.g., a wafer). The substrate processing apparatus **110** may be implemented as, for example, an etching process chamber for performing an etching process on a substrate, a cleaning process chamber for performing a cleaning process on a substrate, and the like.

(33) When the substrate processing apparatus **110** is implemented as an etching process chamber, a cleaning process chamber, etc., as shown in FIG. 2, a housing **210**, a substrate support unit **220**, a plasma generating unit **230**, and a shower head unit **240** may be included.

(34) FIG. 2 is a diagram schematically illustrating an internal structure of a substrate processing apparatus constituting an auto teaching system according to an embodiment of the present disclosure. The following description refers to FIG. 2.

(35) The substrate processing apparatus **110** may process the substrate W using a dry etching process and/or a dry cleaning process in a vacuum environment. The substrate processing apparatus **110** may process the substrate W using, for example, a plasma process.

(36) The housing **210** provides a space, in which the plasma process is performed. The housing **210** may include an opening (not shown) provided as a passage, through which the substrate W enters and exits, on its sidewall.

(37) The substrate support unit **220** is installed in the inner lower region of the housing **210** and may support the substrate W using electrostatic force. However, the present embodiment is not limited thereto. The substrate support unit **220** may support the substrate W in various ways such as mechanical clamping, vacuum, and the like.

(38) When the substrate W is supported by using an electrostatic force, the substrate support unit **220** may include a base **221** and an electrostatic chuck (ESC) **222**.

(39) The electrostatic chuck **222** is a substrate support member that supports the substrate W seated thereon by using an electrostatic force. The electrostatic chuck **222** may be made of a ceramic material, and may be coupled to the base **221** to be fixed on the base **221**.

(40) The ring assembly **223** is provided to surround the edge of the electrostatic chuck **222**. The ring assembly **223** may be provided in a ring shape to support the edge region of the substrate W. The ring assembly **223** may include a focus ring **223a** and an edge ring **223b**.

(41) The focus ring **223a** is formed inside the edge ring **223b** and is provided to surround the electrostatic chuck **222**. The focus ring **223a** may be made of a silicon material, and may concentrate ions generated during a plasma process onto the substrate W.

(42) The edge ring **223b** is formed outside the focus ring **223a** and is provided to surround the focus ring **223a**. The edge ring **223b** may be made of a quartz material, and may be formed to prevent a side surface of the electrostatic chuck **222** from being damaged by plasma.

(43) The heating member **224** and the cooling member **225** are provided so that the substrate W can maintain the process temperature while the etching process is in progress inside the housing **210**. The heating member **224** and the cooling member **225** may be installed, for example, inside the electrostatic chuck **222** and inside the base **221**, respectively.

(44) The plasma generating unit **230** generates plasma from the gas remaining in the discharge space. Here, the discharge space refers to a space located above the substrate support unit **220** in the inner space of the housing **210**.

(45) The plasma generating unit **230** may generate plasma in the discharge space inside the housing **210** using an inductively coupled plasma (ICP) source. In this case, the plasma generating unit **230**

may use an antenna unit **251** installed in the upper module **250** as an upper electrode and use the electrostatic chuck **222** as a lower electrode.

(46) However, the present embodiment is not limited thereto. The plasma generating unit **230** may generate plasma in the discharge space inside the housing **210** using a capacitively coupled plasma (CCP) source. In this case, the plasma generating unit **230** may use the shower head unit **240** as an upper electrode and the electrostatic chuck **222** as a lower electrode.

(47) The plasma generating unit **230** may include an upper electrode, a lower electrode, an upper power supply **231**, and a lower power supply **232**.

(48) The upper power supply **231** applies power to the upper electrode. The upper power supply **231** may be provided to control the characteristics of the plasma. The upper power supply **231** may be provided to adjust, for example, ion bombardment energy.

(49) The lower power supply **232** applies power to the lower electrode. The lower power supply **232** may serve as a plasma source for generating plasma or may serve to control characteristics of plasma together with the upper power supply **231**.

(50) The shower head unit **240** may be installed to face the electrostatic chuck **222** in the vertical direction (the third direction **30**) inside the housing **210**. The shower head unit **240** may include a plurality of gas feeding holes to inject gas into the housing **210**, and may be provided to have a larger diameter than the electrostatic chuck **222**. The shower head unit **240** may be made of a silicon material or a metal material.

(51) In the above description, the substrate processing apparatus **110** has been described as being included in the auto teaching system **100**, but in this embodiment, it is also possible that the auto teaching system **100** includes a semiconductor device manufacturing facility instead of the substrate processing apparatus **110**. The semiconductor device manufacturing facility includes the substrate processing apparatus **110**, which will be described later, and a process chamber constituting the semiconductor device manufacturing facility may correspond to the substrate processing apparatus **110**. Meanwhile, in the present embodiment, the auto teaching system **100** itself may be a semiconductor device manufacturing facility.

(52) It will be described again with reference to FIG. **1**.

(53) The wafer type sensor **120** is applied to inspect semiconductor device manufacturing facilities and their parts. The wafer type sensor **120** may be applied to auto teaching for a semiconductor device manufacturing facility and its part, robot monitoring (e.g., robot-related vibration, torque, encoder, slope and position monitoring) used for substrate transfer in a semiconductor device manufacturing facility, and temperature and pressure measurement in semiconductor device manufacturing facilities.

(54) The wafer type sensor **120** may comprise a sensing module **310**, a first communication module **320**, a storage module **330**, a power supply module **340** and a first control module **350** to perform the above functions, as shown in FIG. **3**.

(55) FIG. **3** is a diagram schematically illustrating an internal configuration of a wafer type sensor constituting an auto teaching system according to an embodiment of the present disclosure. The following description refers to FIG. **3**.

(56) The sensing module **310** detects various signals and information necessary for inspecting a semiconductor device manufacturing facility and its part. The sensing module **310** may include an image signal detector (e.g., a camera), a light signal detector (e.g., a laser beam detector), and the like in this embodiment.

(57) In addition, the sensing module **310** may further comprise, for example, an acceleration information detector (accelerometer), an inclination information detector (inclinometer), a direction information detector (directional compass), a magnetic field directional detector, a magnetic field strength detector, a temperature information detector (thermometer), a pressure detector, a humidity detector, an acoustic detector, an acidity detector, a chemical moiety activity detector, and the like.

(58) The first communication module **320** transmits signals and information detected by the

sensing module **310** to the outside. The first communication module **320** may transmit, for example, a detection signal and information to the control device **130**.

(59) The first communication module **320** may transmit the detection signal and information in a wireless manner. In this case, the first communication module **320** may use WiFi in a wireless manner. However, the present embodiment is not limited thereto. In the present embodiment, any method can be adopted and applied as long as it is a method capable of wirelessly transmitting and receiving data. Meanwhile, the first communication module **320** may transmit the detection signal and information in a wired manner.

(60) On the other hand, the first communication module **320** may also receive a specific signal and information from the outside.

(61) The storage module **330** stores signals and information detected by the sensing module **310**, signals and information received from the outside by the first communication module **320**, and the like. The storage module **330** may include at least one memory chip.

(62) The power supply module **340** provides power so that each component constituting the wafer type sensor **120**, that is, the sensing module **310**, the first communication module **320**, the storage module **330**, the first control module **350**, etc. operate smoothly. The power supply module **340** may include at least one battery.

(63) The first control module **350** controls the entire operation of each component constituting the wafer type sensor **120**, that is, the sensing module **310**, the first communication module **320**, the storage module **330**, the power supply module **340**, and the like. The first control module **350** may be implemented as a processor such as a main processing unit (MPU), a central processing unit (CPU) or a micro processing unit (MPU), and in this embodiment, it could be understood as a concept including a digital signal processor (DSP).

(64) On the other hand, the wafer type sensor **120** may further include an A/D converter (analog to digital converter), a power ON/OFF switch, and a lighting module including a plurality of light emitting diodes (LEDs).

(65) Previously, it has been described that the sensing module **310** may include an image signal detector. In this case, the wafer type sensor **120** may be implemented as, for example, a vision wafer, that is a substrate, in which a camera module is embedded.

(66) When the wafer type sensor **120** is implemented as a vision wafer, in which the camera module **310a** is embedded, as shown in FIG. 4, it may be used to measure the gap K between the chuck member **260** and the consumable part **270** in the substrate processing apparatus **110**. In the above, the consumable part **270** may be a ring-shaped member disposed in the substrate processing apparatus **110** to surround the substrate W. The consumable part **270** may be, for example, a focus ring **223a** or an edge ring **223b**. Meanwhile, the chuck member **260** may be an electrostatic chuck **222**. FIG. 4 is a first exemplary view for describing the role of the wafer type sensor constituting the auto teaching system according to an embodiment of the present disclosure.

(67) On the other hand, when the wafer type sensor **120** measures the gap K between the chuck member **260** and the consumable part **270**, as shown in the example of FIG. 5, a plurality of pieces of information (e.g., K1, K2, K3, K4) about the gap with the consumable part **270** on each side of the chuck member **260** may be obtained.

(68) The gap K1, K2, K3, and K4 between the chuck member **260** and the consumable part **270** obtained in this way may be utilized for centering the consumable part **270** with respect to the chuck member **260**. FIG. 5 is a second exemplary view for describing the role of the wafer type sensor constituting the auto teaching system according to an embodiment of the present disclosure.

(69) On the other hand, when the wafer type sensor **120** is implemented as a vision wafer, it may be used to obtain image information about a part in a semiconductor device manufacturing facility or a substrate processing apparatus.

(70) Meanwhile, the sensing module **310** may comprise a light signal detector, for example, a laser beam detector, and in this case, the wafer type sensor **120** may be used to measure the height of the

consumable part **270**.

(71) It will be described again with reference to FIG. **1**.

(72) The control device **130** inspects a semiconductor device manufacturing facility including the substrate processing apparatus **110** and its parts by using the wafer type sensor **120**. The control device **130** may be implemented as, for example, a cluster tool controller (CTC) that performs facility monitoring using the wafer type sensor **120**.

(73) As described above, the wafer type sensor **120** may measure the gap between the chuck member **260** and the consumable part **270** in order to determine whether the consumable part **270** replaced with a new one is properly seated on the chuck member **260**. In this case, the control device **130** corrects a vacuum transfer robot (VTR) for seating the consumable part **270** around the chuck member **260** based on the information obtained by the wafer type sensor **120** (that is, information about the gap between the chuck member **260** and the consumable part **270**). Then, when the consumable part **270** is replaced and installed around the chuck member **260**, the VTR may center the consumable part **270** with respect to the chuck member **260** under the control of the control device **130**.

(74) The control device **130** may monitor the remaining battery level of the wafer type sensor **120**. Specifically, the control device **130** compares the remaining battery level of the wafer type sensor **120** with the reference value, and when it is determined that the remaining battery level of the wafer type sensor **120** is less than the reference value, it may serve to control the wafer-type sensor **120** to be charged.

(75) Hereinafter, various roles of the control device **130** will be described in more detail with reference to the drawings.

(76) FIG. **6** is a first flowchart for exemplarily describing a method of operating a control device constituting an auto teaching system according to an embodiment of the present disclosure. The following description refers to FIG. **6**.

(77) First, the control device **130** determines whether the consumable part **270** is centered in the substrate processing apparatus **110**. The control device **130** determines, for example, whether the consumable part **270** is centered with respect to the chuck member **260**.

(78) In this case, the wafer type sensor **120** measures the gap between the chuck member **260** and the consumable part **270** in the substrate processing apparatus **110** (**S410**). At this time, the wafer type sensor **120** may measure the gap from the consumable part **270** for each side of the edge of the chuck member **260** to obtain a plurality of gap information (e.g., **K1**, **K2**, **K3**, **K4** shown in FIG. **5**). The wafer type sensor **120** may perform the above function when the consumable part **270** is replaced with a new one.

(79) When a plurality of gap information between the chuck member **260** and the consumable part **270** are obtained by the wafer type sensor **120**, the control device **130** compares the plurality of gap information with each other (**S420**) and determine whether the consumable part **270** is centered with respect to the chuck member **260** (**430**).

(80) Specifically, the control device **130** may determine whether the consumable part **270** is centered with respect to the chuck member **260** based on whether the plurality of gap information are the same as each other, and even if the plurality of gap information are not the same as each other, it is also possible to determine whether the consumable part **270** is centered with respect to the chuck member **260** based on whether they are within an error range.

(81) If it is determined that the consumable part **270** is not centered with respect to the chuck member **260**, the control device **130** generates correction information related to the centering of the consumable part **270** based on information obtained by comparing a plurality of gap information (**S440**) and provides it to the transfer robot (e.g., VTR) (**S450**).

(82) Thereafter, the transfer robot corrects the position of the consumable part **270** based on the correction information (that is, re-installs the consumable part **270** around the chuck member **260**) (**S460**), and steps **S410** to **S460** may be repeatedly performed until the consumable part **270** is

centered with respect to the chuck member **260**.

(83) The method described above with reference to FIG. **6** is an example of centering the consumable part **270** using the wafer type sensor **120**. Next, an example of monitoring the remaining battery level of the wafer type sensor **120** will be described.

(84) FIG. **7** is a second flowchart for illustratively describing a method of operating a control device constituting an auto teaching system according to an embodiment of the present disclosure. The following description refers to FIG. **7**.

(85) First, the control device **130** communicates with the wafer type sensor **120** to obtain information on the remaining battery level of the wafer type sensor **120** (S510).

(86) Thereafter, the control device **130** compares the remaining battery level of the wafer type sensor **120** with the reference value (S520) to determine whether the remaining battery level is less than the reference value (e.g., 30% of the total chargeable amount) (S530).

(87) If it is determined that the remaining battery level is less than the reference value, the control device **130** controls the wafer type sensor **120** to be charged (S540). In this embodiment, the wafer type sensor **120** may be charged with power provided from a load port module (LPM) in a semiconductor device manufacturing facility to a front opening unified pod (FOUP). Specifically, the wafer type sensor **120** may be seated on a load port module (LPM) in a semiconductor device manufacturing facility and charged while being embedded in a front opening unified pod (FOUP). In this regard, a more detailed description will be given later.

(88) On the other hand, the wafer type sensor **120** may transmit a charge request signal to the control device **130** through the first communication module **320** under the control of the first control module **350** when the remaining battery level is less than the reference value. The control device **130** may control the wafer type sensor **120** to be charged when a charge request signal of the wafer type sensor **120** is received.

(89) In addition, the wafer type sensor **120** may send out a warning sound when the remaining battery level is less than the reference value, and the control device **130** may recognize the warning sound of the wafer type sensor **120** and control the wafer type sensor **120** to be charged. In this case, the wafer type sensor **120** may further include a voice/audio output module in addition to the components shown in FIG. **3** for sending out a warning sound.

(90) Next, a mixed example of the case of centering the consumable part **270** using the wafer type sensor **120** and the case of monitoring the remaining battery level of the wafer type sensor **120** will be described.

(91) FIG. **8** is a third flowchart illustrating a method of operating a control device constituting an auto teaching system according to an embodiment of the present disclosure. The following description refers to FIG. **8**.

(92) When the consumable part **270** is replaced with a new one in the substrate processing apparatus **110** (S610), the control device **130** obtains information on the remaining battery level from the wafer type sensor **120** (S620).

(93) Thereafter, the control device **130** compares the remaining battery level of the wafer type sensor **120** with the reference value to determine whether the remaining battery level is less than the reference value (S630). When it is determined that the remaining battery level is less than the reference value, the control device **130** controls the wafer type sensor **120** to be charged (S640).

(94) When it is determined that the remaining battery level is equal to or greater than the reference value or the wafer type sensor **120** is charged, the control device **130** determines whether the consumable part **270** is centered in the substrate processing apparatus **110**.

(95) For example, when determining whether the consumable part **270** is centered with respect to the chuck member **260**, the wafer type sensor **120** obtains a plurality of gap information between the chuck member **260** and the consumable part **270** (S650). Such a function of the wafer type sensor **120** may be performed when the transfer robot carries in and out the wafer type sensor **120** into and from the substrate processing apparatus **110** under the control of the control device **130**.

(96) Thereafter, the control device **130** determines whether the consumable part **270** is centered with respect to the chuck member **260** by comparing the plurality of gap information with each other (**S660**).

(97) If it is determined that the consumable part **270** is not centered with respect to the chuck member **260**, the control device **130** generates correction information related to centering of the consumable part **270** based on information obtained by comparing a plurality of gap information and provides it to the transfer robot (**S670**).

(98) Thereafter, the transfer robot corrects the position of the consumable part **270** around the electrostatic chuck **222** based on the correction information (**S680**), and steps **S610** to **S680** may be repeatedly performed until the consumable part **270** is centered with respect to the chuck member **260**.

(99) On the other hand, the control device **130** may monitor the remaining battery level of the wafer type sensor **120** from time to time, and when it is determined that the remaining battery level of the wafer type sensor **120** is less than the reference value, the current step is paused and then the wafer type sensor **120** may be transferred to the FOUP to be charged by controlling the VTR, ATR, etc. The ongoing step may be continued after charging the wafer type sensor **120**.

(100) The method described above with reference to FIGS. **6** to **8** may be performed by the control device **130**. The control device **130** may comprise a communication module that communicates with the wafer type sensor **120**, a power supply module that supplies power, and a control module that performs calculation and control functions.

(101) The control device **130** may be implemented as a computer equipped with a processor. In this case, the method described with reference to FIGS. **6** to **8** may be provided as a program (or software (SW)) executed by the control device **130**. Also, the program may be provided in a state stored in a recording medium. The recording medium is a storage medium for storing program codes executable by the processor, and may include, for example, a hard disk drive (HDD), a solid state drive (SSD), and a universal serial bus (USB).

(102) It will be described again with reference to FIG. **1**.

(103) The storage device **140** stores the wafer type sensor **120**, and the charging device **150** charges the wafer type sensor **120**. In the present embodiment, the wafer type sensor **120** may be seated on the charging device **150** and charged while being accommodated in the storage device **140**.

(104) In the above, the storage device **140** may be implemented as, for example, a container type FOUP. Also, the charging device **150** may be implemented as, for example, a load port module (LPM).

(105) The storage device **140** may include a plurality of slots in the vertical direction (the third direction **30**) therein. The storage device **140** may include, for example, as shown in FIG. **9**, a first slot **720** disposed in an upper portion of the cover member **710** and a second slot **730** disposed in a lower portion in the cover member **710**.

(106) When the storage device **140** includes the first slot **720** and the second slot **730** as described above, the wafer type sensor **120** may be mounted in the first slot **720**, and a consumable part **270** or a substrate (e.g., a wafer) may be mounted in the second slot **730**. FIG. **9** is a first exemplary diagram schematically illustrating an internal structure of a storage device constituting an auto teaching system according to an embodiment of the present disclosure.

(107) The wafer type sensor **120** may include a power ON/OFF switch. In this case, the power of the wafer type sensor **120** may be turned ON/OFF by the user.

(108) However, when performing auto teaching, the user has to turn on/off the power of the wafer type sensor **120**, and accordingly, there is an inconvenience in that auto teaching should always be performed manually.

(109) In addition, when the wafer type sensor **120** is not fully charged, the power may be turned off during auto teaching. Therefore, since the wafer type sensor **120** should be stored in a separate storage box to complete the charging before the auto teaching is performed, there is also the

inconvenience of delaying the work time.

(110) In this embodiment, in order to solve this problem, when the wafer type sensor **120** is stored in the storage device **140**, the storage device **140** may automatically charge the wafer type sensor **120**. At this time, the control device **130** monitors the state of charge of the wafer type sensor **120**, and may control the storage device **140** to perform the above function (i.e., automatically charges the wafer type sensor **120**) based on the monitoring result.

(111) Meanwhile, the control device **130** may manage the wafer type sensor **120** by continuously monitoring the state of charge of the wafer type sensor **120** even after the charging of the wafer type sensor **120** is completed.

(112) In this embodiment, it is possible to implement full auto teaching of the auto teaching system **100** through the problem solving method as described above, and to maximize the storage and work efficiency of the wafer type sensor **120** using OHT (Over Head Transport).

(113) The storage device **140** may include a battery charging module to charge the battery of the wafer type sensor **120**. Hereinafter, this will be described in detail.

(114) FIG. **10** is a second exemplary diagram schematically illustrating an internal structure of a storage device constituting an auto teaching system according to an embodiment of the present disclosure.

(115) Referring to FIG. **10**, the storage device **140** may comprise a cover member **710**, a door member **740**, a connecting module **750**, and a power transmission module **760**.

(116) The storage device **140** may charge the wafer type sensor **120** as described above. The storage device **140** may be implemented as, for example, a vision wafer dedicated FOUP, on which a charging system is mounted.

(117) The cover member **710** constitutes the outer shape of the storage device **140**. An openable and closable door member **740** may be installed on at least one side of the cover member **710** to store the wafer type sensor **120** therein.

(118) When the door member **740** is opened, the wafer type sensor **120** may be stored inside the cover member **710**. At least one wafer type sensor **120** may be stored in the inner space of the cover member **710**, and at this time, a slot (e.g., the first slot **720** of FIG. **9**) may be provided to support each wafer type sensor **120**.

(119) The connecting module **750** receives power from the outside. When power is supplied from the outside, the connecting module **750** may transmit power to the power transmission module **760** in a wired or wireless manner.

(120) The power transmission module **760** transmits the power received from the connecting module **750** to the wafer type sensor **120**. The power transmission module **760** may allow the wafer type sensor **120** to be charged through this.

(121) In this embodiment, the storage device **140** may wirelessly charge the wafer type sensor **120** using the power transmission module **760**. In this case, the storage device **140** may wirelessly charge the wafer type sensor **120** using a magnetic resonance method. In this case, the storage device **140** may include a coil for supporting magnetic resonance charging.

(122) However, the present embodiment is not limited thereto. The storage device **140** may wirelessly charge the wafer type sensor **120** using an electromagnetic induction method.

(123) Meanwhile, the storage device **140** may wirelessly charge the wafer type sensor **120** by selecting any one of a magnetic resonance method and an electromagnetic induction method. In this case, the storage device **140** may select any one of a magnetic resonance method and an electromagnetic induction method based on the distance between the power transmission module **760** and the wafer type sensor **120** to wirelessly charge the wafer type sensor **120**.

(124) For example, if the distance between the power transmission module **760** and the wafer type sensor **120** is less than the reference distance, the storage device **140** wirelessly charges the wafer type sensor **120** using an electromagnetic induction method. If the distance between the transmission module **760** and the wafer type sensor **120** exceeds the reference distance, the storage

device **140** may wirelessly charge the wafer type sensor **120** using a magnetic resonance method.

(125) Meanwhile, when the distance between the power transmission module **760** and the wafer type sensor **120** is the same as the reference distance, the storage device **140** may use any one of an electromagnetic induction method and a magnetic resonance method.

(126) Meanwhile, in the present embodiment, the storage device **140** may charge the wafer type sensor **120** in wire.

(127) The storage device **140** may automatically charge the wafer type sensor **120** when the wafer type sensor **120** is mounted therein. However, the present embodiment is not limited thereto. The storage device **140** may charge the wafer type sensor **120** according to the monitoring result of the state of charge of the wafer type sensor **120**.

(128) FIG. **11** is a third exemplary diagram schematically illustrating an internal structure of a storage device constituting an auto teaching system according to an embodiment of the present disclosure.

(129) Referring to FIG. **11**, the storage device **140** may comprise a cover member **710**, a door member **740**, a connecting module **750**, a power transmission module **760**, a second communication module **770**, and a second control module **780**.

(130) The cover member **710**, the door member **740**, the connecting module **750**, and the power transmission module **760** have been described above with reference to FIG. **10**, and detailed descriptions thereof will be omitted herein.

(131) The second communication module **770** transmits information on the state of charge of the wafer type sensor **120** to the control device **130**. The second communication module **770** may perform the above function under the control of the second control module **780**.

(132) The control device **130** may instruct the storage device **140** to charge the wafer type sensor **120** according to the state of charge of the wafer type sensor **120**. For example, if the charging value of the wafer type sensor **120** is less than a reference value (e.g., 30% compared to full charge, 50% compared to full charge, etc.), the control device **130** may instruct the storage device **140** to charge the wafer type sensor **120**. In this case, the power transmission module **760** may supply power to the wafer type sensor **120** under the control of the second control module **780**.

(133) In addition, when the charging value of the wafer type sensor **120** is equal to or greater than the reference value, the control device **130** may not instruct the storage device **140** to charge the wafer type sensor **120**. In this case, the storage device **140** may stand by without charging the wafer type sensor **120**.

(134) Meanwhile, in the present embodiment, it is also possible for the second control module **780** to determine whether to perform charging on the wafer type sensor **120**.

(135) As described above, when power is supplied from the outside, the connecting module **750** may transmit power to the power transmission module **760**. For example, the connecting module **750** may receive power from the power supply module **821** (e.g., power box) through the switching module **822** (e.g., relay module) and the power conversion module **823** installed in the load port module **820** when the storage device **140** is moved by a container transfer device **810** (e.g., OHT (Overhead Hoist Transport)) and seated on a load port module (LPM) in a semiconductor device manufacturing facility.

(136) In addition, in this embodiment, when the storage device **140** is seated on the load port module **820**, the control device **130** may monitor the state of the charge of the wafer type sensor **120** in the storage device **140**, and control the power supply module **821**, the switching module **822**, and the power conversion module **823** according to the monitoring result. In this case, a front end module (FEM) **830** such as SFEM or EFEM may serve as the control device **130**.

(137) In the above, the power supply module **821** serves to supply power. The power supply module **821** may be installed in the load port module **820**, but may be installed outside the load port module **820**.

(138) The switching module **822** is to control the flow of power supplied by the power supply

module **821**, and the power conversion module **823** is to convert the AC power supplied by the power supply module **821** to DC power. FIG. **12** is a diagram schematically illustrating an internal structure of a load port module constituting an auto teaching system according to an embodiment of the present disclosure.

(139) On the other hand, the load port module **820** may include a power output terminal **824** on the upper portion to be electrically connected to the connecting module **750** of the storage device **140** when the storage device **140** is seated thereon. The power output terminal **824** may include a DC power output PIN **825** and a FOUP align PIN **826**, to which the connecting module **750** may be connected. The FOUP align PIN **826** may be composed of, for example, three outputs. FIG. **13** is an exemplary diagram schematically illustrating a structure of a power output terminal constituting the load port module of FIG. **12**.

(140) In the above, it has been described that the power supply module **821**, the switching module **822**, the power conversion module **823** and the power output terminal **824** are installed in the load port module **820** to charge the battery of the wafer type sensor **120**. In this embodiment, the battery charging device may be defined as a concept including a power supply module **821**, a switching module **822**, a power conversion module **823**, and a power output terminal **824**.

(141) On the other hand, when the wafer type sensor **120** is not used, the storage device **140** may be stored on a separately provided rack **840** as shown in FIG. **14**. The rack **840** may be implemented as a FOUP dedicated storage Rack, and may store a plurality of storage devices **140a**, **140b**, . . . , **140n**. The wafer type sensor **120** in the storage devices **140a**, **140b**, . . . , **140n** may be charged using DC power supplied through the rack **840**. FIG. **14** is an exemplary view for describing a storage method when not in use of a storage device constituting an auto teaching system according to an embodiment of the present disclosure.

(142) In the present embodiment, as described above, the wafer type sensor **120** may be charged on the charging device **150**, that is, the load port module **820**, while being mounted in the storage device **140**, that is, the FOUP. In this case, the load port module **820** may provide power for charging the wafer type sensor **120** in the FOUP.

(143) Hereinafter, a semiconductor device manufacturing facility including the load port module (LPM) will be described.

(144) FIG. **15** is an exemplary view of a semiconductor device manufacturing facility including a load port module according to the first embodiment.

(145) Referring to FIG. **15**, a semiconductor device manufacturing facility **900** includes a load port module (LPM) **820**, an index module **910**, a load-lock chamber **920**, a transfer chamber **930**, and a process chamber **940**.

(146) The semiconductor device manufacturing facility **900** is a system for processing a plurality of substrates (e.g., wafers) through various processes such as an etching process and a cleaning process. The semiconductor device manufacturing facility **900** may be implemented as a multi-chamber type substrate processing system including transfer robots **911** and **931** in charge of transferring substrates and a plurality of process chambers **940** serving as substrate processing modules provided around them.

(147) In the load port module **820**, a container **950** (e.g., a front opening unified pod (FOUP)), in which a plurality of substrates are mounted, is seated. A plurality of such load port modules **820** may be disposed in front of the index module **910**. In the above, the container **950** is substantially the same concept as the storage device **140**, except that the reference number is different.

(148) When a plurality of load port modules **820** are disposed in front of the index module **910**, different objects may be mounted in the containers **950** seated on each load port module **820**. When three load port modules **820** are disposed in front of the index module **910**, for example, the first container **950a** seated on the first load port **820a** on the left side may mount the wafer type sensor **120**, the second container **950b** seated on the second load port **820b** in the middle may mount a substrate (wafer), and the third container **950c** seated on the third load port **820c** on the right side

may mount the consumable part **270**.

(149) However, the present embodiment is not limited thereto. The containers **950a**, **950b**, and **950c** seated on each of the load ports **820a**, **820b**, and **820c** may mount the same object. For example, each of the containers **950a**, **950b**, and **950c** may mount the wafer type sensor **120**, a substrate, a consumable part, and the like.

(150) On the other hand, it is also possible that containers seated on several load ports mount the same object, and containers seated on several other load ports mount different objects. For example, the first container **950a** and the second container **950b** may mount the wafer type sensor **120** and a substrate, and the third container **950c** may mount a consumable part.

(151) The index module **910** is disposed between the load port module **820** and the load-lock chamber **920** and interfaces to transfer the substrate between the container **950** and the load-lock chamber **920** on the load port module **820**. The index module **910** may be implemented as a front end module (FEM) such as SFEM or EFEM.

(152) The index module **910** may include a first transfer robot **911** in charge of transferring the substrate. The first transfer robot **911** operates in an atmospheric pressure environment, and may transfer a substrate between the container **950** and the load-lock chamber **920**.

(153) The load-lock chamber **920** serves as a buffer between an input port and an output port on the semiconductor device manufacturing facility **900**. The load-lock chamber **920** may include a buffer stage, in which the substrate temporarily stands by.

(154) A plurality of load-lock chambers **920** may be provided between the index module **910** and the transfer chamber **930**. In this embodiment, for example, two load-lock chambers **921** and **922** such as a first load-lock chamber **921** and a second load-lock chamber **922** may be provided between the index module **910** and the transfer chamber **930**.

(155) The first load-lock chamber **921** and the second load-lock chamber **922** may be disposed between the index module **910** and the transfer chamber **930** in the first direction **10**. In this case, the first load-lock chamber **921** and the second load-lock chamber **922** may be provided in a mutually symmetrical single-layer structure arranged side by side in the left-right direction. In the above, the first direction **10** means a horizontal direction with respect to the arrangement direction of the index module **910** and the transfer chamber **930**.

(156) However, the present embodiment is not limited thereto. The first load-lock chamber **921** and the second load-lock chamber **922** may be disposed in the third direction **30** between the index module **910** and the transfer chamber **930**. In this case, the first load-lock chamber **921** and the second load-lock chamber **922** may be provided in a multi-layer structure disposed in the vertical direction. In the above, the third direction **30** means a direction perpendicular to the arrangement direction of the index module **910** and the transfer chamber **930**.

(157) The first load-lock chamber **921** may transfer a substrate from the index module **910** to the transfer chamber **930**, and the second load-lock chamber **922** may transfer a substrate from the transfer chamber **930** to the index module **910**. However, the present embodiment is not limited thereto. The first load-lock chamber **921** may transfer a substrate from the transfer chamber **930** to the index module **910**, and the second load-lock chamber **922** may transfer a substrate from the index module **910** to the transfer chamber **930**.

(158) In the load-lock chamber **920**, a substrate may be loaded or unloaded by the second transfer robot **931** of the transfer chamber **930**. In the load-lock chamber **920**, a substrate may be loaded or unloaded by the first transfer robot **911** of the index module **910**.

(159) The load-lock chamber **920** may maintain a pressure while changing its interior into a vacuum environment and an atmospheric pressure environment by using a gate valve or the like. The load-lock chamber **920** may prevent the internal atmospheric pressure state of the transfer chamber **930** from being changed through this.

(160) More specifically, when a substrate is loaded or unloaded by the second transfer robot **931**, the load-lock chamber **920** may form its interior as a vacuum environment the same as (or close to)

that of the transfer chamber **930**. In addition, the load-lock chamber **920** may form its interior as an atmospheric pressure environment when a substrate is loaded or unloaded by the first transfer robot **911** (that is, an unprocessed substrate is supplied from the first transfer robot **911**, or a pre-processed substrate is transferred to the index module **910**).

(161) The transfer chamber **930** transfers a substrate between the load-lock chamber **920** and the process chamber **940**. The transfer chamber **930** may include at least one second transfer robot **931** for this purpose.

(162) The second transfer robot **931** transfers an unprocessed substrate from the load-lock chamber **920** to the process chamber **940**, or transfers a pre-processed substrate from the process chamber **940** to the load-lock chamber **920**. Each side of the transfer chamber **930** may be connected to the load-lock chamber **920** and the plurality of process chambers **940** for this purpose.

(163) Meanwhile, the second transfer robot **931** operates in a vacuum environment and may be freely rotated.

(164) The process chamber **940** is for processing a substrate. The process chamber **940** may be implemented as an etching chamber for processing a substrate using an etching process, for example, as a plasma reaction chamber for etching a substrate using a plasma process.

(165) A plurality of process chambers **940** may be disposed around the transfer chamber **930**. In this case, each process chamber **940** may receive a substrate from the transfer chamber **930** to process the substrate, and provide the processed substrate to the transfer chamber **930**.

(166) The process chamber **940** may have a cylindrical shape. The process chamber **940** may have a surface made of alumite, on which an anodic oxide film is formed, and an inside thereof may be hermetically configured. Meanwhile, the process chamber **940** may be formed in a shape other than the cylindrical shape in the present embodiment.

(167) The semiconductor device manufacturing facility **900** may be formed in a structure having a cluster platform. In this case, the plurality of process chambers **940** may be disposed in a cluster manner with respect to the transfer chamber **930**, and the plurality of load-lock chambers **920** may be disposed in the first direction **10**.

(168) However, the present embodiment is not limited thereto. The semiconductor device manufacturing facility **900** may be formed in a structure having a quad platform as shown in FIG. **16**. In this case, the plurality of process chambers **940** may be disposed in a quad manner with respect to the transfer chamber **930**. FIG. **16** is an exemplary view of a semiconductor device manufacturing facility including a load port module according to a second embodiment.

(169) Meanwhile, the semiconductor device manufacturing facility **900** may be formed in a structure having an in-line platform as shown in FIG. **17**. In this case, the plurality of process chambers **940** may be disposed in an inline manner with respect to the transfer chamber **930**, and a pair of process chambers **940** may be disposed in series on both sides of each transfer chamber **930**. FIG. **17** is an exemplary view of a semiconductor device manufacturing facility including a load port module according to a third embodiment.

(170) Although embodiments of the present disclosure have been described with reference to the above and the accompanying drawings, those of ordinary skill in the art to which the present disclosure pertains can understand that the present disclosure can be practiced in other specific forms without changing its technical spirit or essential features. Therefore, it should be understood that the embodiments described above are illustrative in all respects and not limiting.

Claims

1. A substrate processing system comprising: a load port module configured to dispose a container which loads a sensor; an Equipment Front End Module (EFEM) including a first transfer robot which transfers the sensor from the load port module; a load lock chamber configured to connect to the EFEM and switching between a first environment, which is an atmospheric pressure

environment, and a second environment, which is a vacuum environment; a transfer chamber including a second transfer robot which transfers the sensor from the load lock chamber; and a process chamber configured to connect to the transfer chamber and including an Electrostatic Chuck (ESC) and a focus ring surrounding an outer surface of the ESC, wherein the sensor configured to be charged wirelessly based on a power of the substrate processing system, wherein the container includes a charging unit for charging the sensor loaded on a slot therein and a contact unit configured to contact with a charging device, wherein the charging unit is configured to charge the sensor using a magnetic resonance method, wherein the charging device includes a power output terminal configured to supply a power for charging of the sensor, wherein the charging unit is disposed on an upper surface of the container, wherein the contact unit is disposed on a lower surface of the container, and wherein the power output terminal is disposed on the load port module.

2. The substrate processing system of claim 1, the container includes a plurality of slots therein, and the sensor and a processed wafer are loaded into different slots.
 3. The substrate processing system of claim 1, wherein the container is equipped with the sensor configured to sense at least a part of a semiconductor device manufacturing facility and a control module, wherein the container comprises a communication module, the control module configured to control the communication module to communicate information on a state of charge of the sensor to a control device, and wherein the control module is configured to charge the sensor using the load port module having the battery charging device in response to receiving an instruction from the control device regarding a monitoring result of a remaining battery level of the sensor.
 4. The substrate processing system of claim 1, wherein the container comprises a plurality of slots installed in a vertical direction inside the container.
 5. The substrate processing system of claim 1, wherein the container comprises: a first slot installed inside the container; and a second slot installed under the first slot, wherein different objects are mounted in the first slot and the second slot.
 6. The substrate processing system of claim 1, wherein the container charges the sensor using at least one of a magnetic resonance method and an electromagnetic induction method.
 7. The substrate processing system of claim 1, wherein the sensor is mounted in the container for charging the sensor.
 8. The substrate processing system of claim 1, wherein the charging device comprises, a power supply module for supplying first power; a power conversion module installed inside the load port module and for converting the first power into second power; and a power output terminal installed above the load port module and connected to a connector of the container.
-