

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405341
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Kang; Sungchan et al.

Directional acoustic sensor

Abstract

A directional acoustic sensor includes: a support including a first support portion and a second support portion that are separated from each other and face each other; a plurality of first resonators extending in a length direction thereof from the first support portion of the support; and a plurality of second resonators extending in the length direction thereof from the second support portion of the support and facing the plurality of first resonators, wherein each first resonator of the plurality of first resonators has a first end, wherein each second resonator of the plurality of second resonators has a second end, and wherein, in a first resonator arrangement of a region where the plurality of first resonators and the plurality of second resonators face each other, the first ends of the plurality of first resonators and the second ends of the plurality of second resonators form an intersecting structure.

Inventors: Kang; Sungchan (Hwaseong-si, KR), Kim; Cheheung (Yongin-si, KR), Rhee; Choongho (Anyang-si, KR)

Applicant: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Family ID: 82115801

Assignee: SAMSUNG ELECTRONICS CO., LTD. (Suwon-si, KR)

Appl. No.: 17/731742

Filed: April 28, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230152411 A1	May. 18, 2023

Foreign Application Priority Data

KR	10-2021-0155987	Nov. 12, 2021
----	-----------------	---------------

Publication Classification

Int. Cl.: G01S3/801 (20060101); G01S3/803 (20060101); H03H9/13 (20060101)

U.S. Cl.:

CPC G01S3/801 (20130101); G01S3/803 (20130101); H03H9/132 (20130101);

Field of Classification Search

USPC: None

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
3886504	12/1974	Hartmann	333/195	H03H 9/0038
4885781	12/1988	Seidel	381/174	G01H 11/06
5491604	12/1995	Nguyen	333/197	H03H 9/02425
5856722	12/1998	Haronian et al.	N/A	N/A
5955932	12/1998	Nguyen	361/278	G01R 33/0286
6012334	12/1999	Ando	73/648	G01H 3/08
6079274	12/1999	Ando	73/649	G01H 11/08
6236281	12/2000	Nguyen	361/278	H03H 9/02393
6438243	12/2001	Ikeuchi	381/174	H04R 15/02
6515401	12/2002	Ando et al.	N/A	N/A
6651504	12/2002	Datskos	73/632	G01H 11/06
8008105	12/2010	Huang	438/52	B06B 1/0292
8103027	12/2011	Zhang et al.	N/A	N/A
8170244	12/2011	Ryan et al.	N/A	N/A
9148729	12/2014	Josefsson	N/A	N/A
10141007	12/2017	Kim et al.	N/A	N/A
10243535	12/2018	Kawasaki	N/A	H03H 9/1092
10356509	12/2018	Park	N/A	H04R 17/025
10541670	12/2019	Yoon	N/A	H03H 3/0076
11146240	12/2020	Yoon	N/A	H03H 9/2426
11359960	12/2021	Kang	N/A	H04R 17/10
2005/0005676	12/2004	Crawley	73/24.01	B81B 3/0089
2011/0140579	12/2010	Moon	29/25.35	H02N 2/186
2011/0215680	12/2010	Yamada et al.	N/A	N/A
2012/0062340	12/2011	Huang	333/186	H03H 9/462
2013/0051588	12/2012	Ruile	29/25.35	H03H 9/1457
2013/0135264	12/2012	Black	216/13	H03H 9/178
2014/0009032	12/2013	Takahashi	29/25.35	H03H 9/02559
2015/0263700	12/2014	Yasumoto	310/313B	H01L 28/20

2016/0050506	12/2015	Kim	381/56	H04R 1/245
2017/0006385	12/2016	Kim	N/A	N/A
2017/0179920	12/2016	Kawasaki	N/A	H03H 9/725
2018/0097506	12/2017	Kang et al.	N/A	N/A
2018/0130485	12/2017	Park et al.	N/A	N/A
2018/0131347	12/2017	Rhee	N/A	H03H 9/02259
2018/0138886	12/2017	Yoon et al.	N/A	N/A
2019/0033904	12/2018	Hong et al.	N/A	N/A
2019/0072635	12/2018	Kang et al.	N/A	N/A
2019/0131954	12/2018	Okada	N/A	H03H 9/02992
2019/0174244	12/2018	Kim et al.	N/A	N/A
2019/0200119	12/2018	Kang et al.	N/A	N/A
2019/0348050	12/2018	Kim et al.	N/A	N/A
2020/0204187	12/2019	Hong et al.	N/A	N/A
2020/0212885	12/2019	Kim et al.	N/A	N/A
2022/0014172	12/2021	Nozoe	N/A	N/A
2023/0270010	12/2022	Luo	251/129.06	F16K 31/006

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
212163296	12/2019	CN	N/A
113507676	12/2020	CN	N/A
3729054	12/2004	JP	N/A
6856820	12/2020	JP	N/A
102207928	12/2020	KR	N/A

OTHER PUBLICATIONS

Brown, Joseph J., et al. "Nonlinear Mechanics of Interlocking Cantilevers." Journal of Applied Mechanics 84.12 (2017): 121012. (Year: 2017). cited by examiner

Communication dated Nov. 8, 2022 issued by the European Patent Office in European Application No. 22173724.0. cited by applicant

Kang, S., et al., "Directional Sound Sensor With Consistent Directivity and Sensitivity in the Audible Range", Journal of Microelectromechanical Systems, vol. 30, No. 3, Jun. 2021, pp. 471-479. cited by applicant

Primary Examiner: Alsomiri; Isam A

Assistant Examiner: Armstrong; Jonathan D

Attorney, Agent or Firm: Sughrue Mion, PLLC

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION

(1) This application is based on and claims priority under 35 U.S.C. § 119 to Korean Patent Application No. 10-2021-0155987, filed on Nov. 12, 2021, in the Korean Intellectual Property Office, the disclosure of which is incorporated by reference herein in its entirety.

BACKGROUND

1. Field

(2) The present disclosure relates to directional acoustic sensors, and more particularly, to directional acoustic sensors including a resonator that reacts to a pressure difference in an acoustic sound.

2. Description of the Related Art

(3) Utilization of acoustic sensors that are mounted on household appliances, video display devices, virtual reality devices, augmented reality devices, artificial intelligence speakers, etc., to detect a direction of a sound and recognize voices is increasing. Recently, a directional acoustic sensor for detecting an acoustic signal by converting a mechanical motion caused by a pressure difference into an electrical signal has been developed.

SUMMARY

(4) Provided are directional acoustic sensors which may have improved sensitivity by increasing an acoustic resistance.

(5) Additional aspects will be set forth in part in the description which follows and, in part, will be apparent from the description, or may be learned by practice of the presented embodiments of the disclosure.

(6) According to an aspect of an example embodiment, a directional acoustic sensor includes: a support including a first support portion and a second support portion that are separated from each other and face each other; a plurality of first resonators extending in a length direction thereof from the first support portion of the support; and a plurality of second resonators extending in the length direction thereof from the second support portion of the support and facing the plurality of first resonators, wherein each first resonator of the plurality of first resonators has a first end, wherein each second resonator of the plurality of second resonators has a second end, and wherein, in a first resonator arrangement of a region where the plurality of first resonators and the plurality of second resonators face each other, the first ends of the plurality of first resonators and the second ends of the plurality of second resonators form an intersecting structure.

(7) The first end of each first resonator of the plurality of first resonators may have a structure in which a partial width portion of each first resonator extends in the length direction thereof, the second end of each second resonator of the plurality of second resonators may have a structure in which a partial width portion of each second resonator that does not face the partial width portion of a corresponding first resonator extends in the length direction thereof, and a second resonator arrangement may be formed in a region where the plurality of first resonators and the plurality of second resonators face each other in a structure in which the first ends of the plurality of first resonators respectively intersect with the second ends of the plurality of second resonators.

(8) The first ends of the plurality of first resonators and the second ends of the plurality of second resonators may respectively engage with each other.

(9) The first ends of the plurality of first resonators and the second ends of the plurality of second resonators may respectively engage with each other in a male or female form.

(10) The first ends of the plurality of first resonators and the second ends of the plurality of second resonators may respectively engage with each other in an edge shape.

(11) Each first resonator of the plurality of first resonators and each second resonator of the plurality of second resonators may include a base, and a frame protruding from the base and extending in the length direction thereof.

(12) The frame may be integrally formed with the base.

(13) Each of the base and the frame may include silicon.

(14) The frame may be provided on at least one of both sides and an inside of the base.

(15) Each the first ends of the plurality of first resonators and the second ends of the plurality of second resonators may have a plate shape up to a height of the frame.

(16) The base and the frame may extend to each of the first ends of the plurality of first resonators

and each of the second ends of the plurality of second resonators.

(17) The first end of each first resonator of the plurality of first resonators may have a structure in which a width portion of a first side of each first resonator extends in the length direction thereof, the second end of each second resonator of the plurality of second resonators may have a structure in which a width portion of a second side of each second resonator extends in the length direction thereof, and the frame may extend to end portions of the first end and the second end.

(18) The first end of each first resonator of the plurality of first resonators may have a structure in which a width portion of a first side of each first resonator extends in the length direction thereof, the second end of each second resonator of the plurality of second resonators may have a structure in which a width portion of a second side of the second resonator that does not face the width portion of the first side of the first resonator extends in the length direction thereof, and the frame may extend to a circumference of the first end and the second end.

(19) Each first resonator of the plurality of first resonators and each second resonator of the plurality of second resonators may include a base and a groove pattern formed in the base to a predetermined depth.

(20) Each first resonator of the plurality of first resonators and each second resonator of the plurality of second resonators may include a base and a plurality of through holes formed in the base and having a size smaller than a wavelength of an audible frequency band.

(21) The directional acoustic sensor may further include at least one third resonator extending in the length direction thereof from the first support portion or the second support portion of the support and not facing the plurality of first resonators or the plurality of second resonators.

(22) The at least one third resonator may include a base and a frame protruding from the base and extending in the length direction thereof.

(23) Each first resonator of the plurality of first resonators and each second resonator of the plurality of second resonators may include: a driving portion configured to move in response to an input sound signal; and a sensing portion configured to detect movement of the driving portion.

(24) Each first resonator of the plurality of first resonators and each second resonator of the plurality of second resonators may include a cantilever beam having a first end fixed to the first support portion and the second support portion and a second end moving freely.

(25) The plurality of first resonators and the plurality of second resonators may have resonant frequencies different from each other.

(26) According to an aspect of an example embodiment, there is provided an electronic device including a directional acoustic sensor including: a support including a first support portion and a second support portion that are separated from each other and face each other; a plurality of first resonators extending in a length direction thereof from the first support portion of the support; and a plurality of second resonators extending in the length direction thereof from the second support portion of the support and facing the plurality of first resonators, wherein each first resonator of the plurality of first resonators has a first end, wherein each second resonator of the plurality of second resonators has a second end, and wherein, in a first resonator arrangement of a region where the plurality of first resonators and the plurality of second resonators face each other, the first ends of the plurality of first resonators and the second ends of the plurality of second resonators form an intersecting structure.

(27) The directional acoustic sensor may further include at least one third resonator extending in the length direction thereof from the first support portion or the second support portion of the support and not facing the plurality of first resonators or the plurality of second resonators.

(28) The at least one third resonator may include a base and a frame protruding from the base and extending in the length direction thereof.

(29) Each first resonator of the plurality of first resonators and each second resonator of the plurality of second resonators may include: a driving portion configured to move in response to an input sound signal, and a sensing portion configured to detect movement of the driving portion.

(30) Each first resonator of the plurality of first resonators and each second resonator of the plurality of second resonators may include a cantilever beam having a first end fixed to the first support portion and the second support portion and a second end moving freely.

(31) The plurality of first resonators and the plurality of second resonators may have resonant frequencies different from each other.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) The above and other aspects, features, and advantages of certain example embodiments of the disclosure will be more apparent from the following description taken in conjunction with the accompanying drawings, in which:

(2) FIG. 1 is a perspective view exemplarily illustrating a directional acoustic sensor according to an example embodiment;

(3) FIG. 2 is a plan view of the directional acoustic sensor of FIG. 1 according to an example embodiment;

(4) FIGS. 3A, 3B and 3C are diagrams of resonators applicable to first and second resonators of FIGS. 1 and 2 according to example embodiments;

(5) FIG. 3D is a diagram of an example of a resonator applicable to a third resonator of FIGS. 1 and 2 according to an example embodiment;

(6) FIG. 4 is a cross-sectional view taken along line IV-IV of FIG. 3A according to an embodiment;

(7) FIG. 5A is a plan view of an intersecting portion when ends of two facing resonators have plate-shaped ends according to an example embodiment;

(8) FIG. 5B is a cross-sectional view taken along line A-A* of FIG. 5A according to an example embodiment;

(9) FIG. 6A is a plan view of an intersecting portion when ends of two resonators facing each other have an end with a frame extending to the end according to an example embodiment;

(10) FIG. 6B is a cross-sectional view taken along line B-B* of FIG. 6A according to an example embodiment;

(11) FIG. 7A is a plan view of an intersecting portion when ends of two resonators facing each other have an end with a frame extending to a circumference thereof according to an example embodiment;

(12) FIG. 7B is a cross-sectional view taken along line C-C* of FIG. 7A according to an example embodiment;

(13) FIG. 8 is a diagram of an example of forming an intersecting structure in which ends of two resonators facing each other are engaged with each other in an edge shape according to an example embodiment;

(14) FIG. 9 is a diagram of an example of forming an intersecting structure in which ends of two resonators facing each other are engaged with each other in a male/female form according to an example embodiment;

(15) FIG. 10 is a schematic plan view illustrating a directional acoustic sensor according to a comparative example;

(16) FIG. 11 is a diagram of a comparison of a layout size change of a resonator arrangement before and after the application of the intersecting structure of ends of two resonators facing each other according to an example embodiment;

(17) FIG. 12 is a graph showing changes in the frequency response characteristics of resonators before and after the application of the intersecting structure of ends of two resonators facing each other according to an example embodiment;

(18) FIG. 13 is a graph showing resonant frequency characteristics for each channel of the

resonator arrangement before and after the application of the intersecting structure of the ends of two resonators facing each other according to an example embodiment;

(19) FIG. 14 is a sample photograph after fabrication of a directional acoustic sensor according to an embodiment;

(20) FIG. 15 is a photograph after packaging the directional acoustic sensor of FIG. 14 according to an example embodiment;

(21) FIG. 16 is a graph showing a result of measuring the frequency response characteristics of a directional acoustic sensor according to a manufactured example embodiment;

(22) FIGS. 17, 18 and 19 are diagrams of resonators that may be applied to two resonators facing each other according to example embodiments; and

(23) FIGS. 20, 21, 22, 23, 24 and 25 are diagrams of electronic devices to which the directional acoustic sensor according to an embodiment is applied as a voice interface device according to example embodiments.

DETAILED DESCRIPTION

(24) Reference will now be made in detail to embodiments, examples of which are illustrated in the accompanying drawings, wherein like reference numerals refer to like elements throughout. In this regard, the present embodiments may have different forms and should not be construed as being limited to the descriptions set forth herein. Accordingly, the embodiments are merely described below, by referring to the figures, to explain aspects. As used herein, the term “and/or” includes any and all combinations of one or more of the associated listed items. Expressions such as “at least one of,” when preceding a list of elements, modify the entire list of elements and do not modify the individual elements of the list.

(25) Reference will now be made in detail to embodiments, examples of which are illustrated in the accompanying drawings. In the drawings, like reference numerals refer to like elements, and the size of each component may be exaggerated for clarity and convenience of explanation. The embodiments of the inventive concept are capable of various modifications and may be embodied in many different forms.

(26) When an element or layer is referred to as being “on” or “above” another element or layer, the element or layer may be directly on another element or layer or intervening elements or layers. The singular forms “a,” “an” and “the” are intended to include the plural forms as well, unless the context clearly indicates otherwise. When a part “comprises” or “includes” an element in the specification, unless otherwise defined, it is not excluding other elements but may further include other elements.

(27) The term “above” and similar directional terms may be applied to both singular and plural. With respect to operations that constitute a method, the operations may be performed in any appropriate sequence unless the sequence of operations is clearly described or unless the context clearly indicates otherwise. The operations may not necessarily be performed in the order of sequence.

(28) Also, in the specification, the term “units” or “. . . modules” denote units or modules that process at least one function or operation, and may be realized by hardware, software, or a combination of hardware and software.

(29) The connections of lines and connection members between constituent elements depicted in the drawings are examples of functional connection and/or physical or circuitry connections, and thus, in practical devices, may be expressed as replicable or additional functional connections, physical connections, or circuitry connections.

(30) The use of any and all examples, or exemplary language provided herein, is intended merely to better illuminate the inventive concept and does not pose a limitation on the scope of the inventive concept unless otherwise claimed.

(31) A directional acoustic sensor according to an embodiment uses a principle of a resonator that responds to a pressure difference in an acoustic sound, and includes a combination of resonators

having different resonant frequencies. Each of the resonators may be formed of a cantilever beam having one end fixed to a support and the other end moving freely, and the resonant frequency of each resonator may be determined by a length of the resonator or a concentration mass of the resonator.

(32) The relationship between the characteristics of the cantilever-type resonator and the resonance frequency may be expressed as Equation (1).

$$\omega_{.0} = (1.875)^2 \sqrt{EI/mL^3} \quad (1)$$

(33) Here, $\omega_{.0}$ indicates resonance frequency, E indicates effective modulus,

(34) $I = \frac{1}{12}bt^3$

indicates moment of inertia, b indicates beam width, t is beam thickness, and m indicates effective mass, and L indicates beam length.

(35) When a length of a resonator is the same and a mass is changed, a bandwidth of the resonator may be reduced. This is because if the mass is increased to lower a frequency, a Q-factor increases and the bandwidth decreases. Therefore, in order to implement the same bandwidth characteristics even though the frequencies are different from each other, the adjustment of a resonant frequency by changing the length of the resonator is suitable for designing a directional acoustic sensor with a wide frequency band. When a required resonance frequency is designed, the number and length of resonators may be determined and the size of a device may be determined. However, when resonators having lengths different from each other are arranged, a through hole may be generated. The through hole may reduce an acoustic resistance, thereby reducing a pressure difference in acoustic sound, and may be a factor of lowering sensitivity.

(36) According to the directional acoustic sensor according to an embodiment, a through-hole portion of a cavity may be minimized by forming a resonator arrangement in which a plurality of resonators face each other, and forming the resonator arrangement in a structure in which ends of two facing resonators intersect each other. By reducing or almost eliminating a through-hole portion by such an arrangement of the resonator, a decrease in sensitivity due to a decrease in acoustic resistance may be prevented, and the element size of the directional acoustic sensor may also be reduced.

(37) FIG. 1 is a perspective view illustrating a directional acoustic sensor according to an example embodiment. FIG. 2 is a plan view of the directional acoustic sensor of FIG. 1 according to an example embodiment.

(38) Referring to FIGS. 1 and 2, the directional acoustic sensor **100** includes a support **101** and a plurality of first resonators **110** and a plurality of second resonators **130** provided on the support **101**. The directional acoustic sensor **100** according to the embodiment may include at least one third resonator **130'** provided on the support **101**, although in some embodiments, the at least one third resonator **130'** is not included.

(39) The support **101** is formed to include a cavity that penetrates therethrough, and includes first and second support portions **103** and **105** facing each other with the cavity therebetween. A separation distance between the first and second support portions **103** and **105** may correspond to a width of the cavity in a length direction of the directional acoustic sensor **100**.

(40) The support **101** may be, for example, a silicon substrate, but is not limited thereto. The plurality of first resonators **110** and the plurality of second resonators **130** may be arranged in the cavity of the support **101** in a predetermined shape. For example, the plurality of first resonators **110** and the plurality of second resonators **130** may be arranged to form a resonator arrangement to face each other in the cavity of the support **101**. The at least one third resonator **130'** may be arranged in a predetermined shape in the cavity of the support **101** so as not to face the first resonator **110** or the second resonator **130**.

(41) One end of each of the plurality of first resonators **110** may be fixed to the first support portion **103** of the support **101** to form a planarly parallel arrangement in the cavity of the support **101**. One end of each the plurality of second resonators **130** may be fixed to the second support portion **105**

of the support **101** to form the planarly parallel arrangement in the cavity of the support **101**. One end of the at least one third resonator **130'** may be fixed to, for example, the second support portion **105** of the support **101** to form the planarly parallel arrangement in the cavity of the support **101**. Here, one end of the third resonator **130'** may be fixed to the first support portion **103** of the support **101**.

(42) Each of the plurality of first resonators **110** may extend in the length direction thereof from the first support portion **103** of the support **101**. Each of the plurality of second resonators **130** may extend in the length direction thereof with respect to the second support portion **105** of the support **101**, and may be arranged to face the plurality of first resonators **110**. The at least one third resonator **130'** may extend in the length direction thereof from the second support portion **105** towards the first support portion **103**.

(43) FIGS. **1** and **2** show an example arrangement in which the plurality of first resonators **110** and the plurality of second resonators **130** face each other, and the third resonator **130'** that does not face the first resonator **110** is included.

(44) As another example, the plurality of first resonators **110** and the plurality of second resonators **130** are arranged to face each other, and the at least one third resonator **130'** may be arranged not to face the second resonator **130**. As another example, the number of first resonators **110** is the same as the number of second resonators **130**, the plurality of first resonators **110** and the plurality of second resonators **130** are all arranged to face each other, and the at least one third resonator **130'** that does not face the first resonator **110** or the second resonator **130** is not included. Hereinafter, a case in which the directional acoustic sensor **100** according to an embodiment further includes the at least one third resonator **130'** that does not face the first resonator **110**, and the third resonator **130'** is arranged parallel to the second resonator **130** will be described as an example.

(45) Here, the length direction is a direction corresponding to the length of each of the resonators, that is, the first resonator **110**, the second resonator **130**, and the third resonator **130'**, may correspond to a direction from the first support portion **103** to the second support portion **105** or correspond to a direction from the second support portion **105** to the first support portion **103**. That is, the length direction may correspond to a direction (x-axis direction) crossing the first support portion **103** and the second support portion **105**.

(46) Each of the plurality of first resonators **110** may constitute a cantilever beam in which one end is fixed to the first support portion **103** of the support **101** and the other end freely moves. Each of the plurality of second resonators **130** and the at least one third resonator **130'** may form a cantilever beam in which one end is fixed to the second support portion **105** of the support **101** and the other end freely moves. FIGS. **1** and **2** illustrate a case in which the plurality of first resonators **110**, the plurality of second resonators **130**, and the at least one third resonator **130'** move in a z-axis direction. FIG. **1** exemplarily illustrates a state in which some portion of the second resonator **130** are moved by an input acoustic sound.

(47) Each of the plurality of first resonators **110** includes a driving portion **120** configured to vibrate in response to an input sound signal, and a sensing portion configured to detect a movement of the driving portion **120**. Each of the plurality of second resonators **130** includes a driving portion **140** configured to vibrate in response to an input sound signal, and a sensing portion configured to detect a movement of the driving portion **140**. The driving portions **120** and **140** of each of the plurality of first resonators **110** and the plurality of second resonators **130** may be configured as a cantilever beam.

(48) One end of the driving portion **120** of each of the plurality of first resonators **110** may be fixed to the first support portion **103** of the support **101**, and extend in the length direction of the first resonator **110** from the first support portion **103** toward the cavity. The driving portion **120** may be integrally formed with the support **101**, and in this case, the driving portion **120** may include, for example, silicon. However, the present embodiment is not limited thereto, and the driving portion **120** may not be integrally formed with the support **101**. The driving portion **120** of each of the

plurality of first resonators **110** may have a first end **125** at an end thereof.

(49) One end of a driving portion **140** of each of the plurality of second resonators **130** and the at least one third resonator **130'** may be fixed to the second support portion **105** of the support **101**, and may extend in the length direction (an x-axis direction in FIGS. **1** and **2**) of the second and third resonators **130** and **130'** from the second support portion **105** toward the cavity. The driving portion **140** may be integrally formed with the support **101**, and in this case, the driving portion **140** may include, for example, silicon. However, the present embodiment is not limited thereto, and the driving portion **140** may not be integrally formed with the support **101**. The driving portion **140** of each of the plurality of second resonators **130** may have a second end **145** at the end thereof.

(50) An effective length of the first resonator **110** is a vibrating length of the driving portion **120**, and may include a length of the first end **125**. An effective length of the second resonator **130** is a vibrating length of the driving portion **140**, and may include a length of the second end **145**.

(51) The directional acoustic sensor **100** according to the embodiment is configured such that the first end **125** and the second end **145** of the first resonator **110** and the second resonator **130** that face each other form an intersecting structure. The length of each of the first end **125** and the second end **145** for the intersecting structure may be formed up to approximately half of the effective length of each of the first resonator **110** and the second resonator **130**. That is, the length of each of the first and second ends **125** and **145** forming the intersecting structure of the first and second resonators **110** and **130** facing each other may be up to about half the length of each of the first and second resonators **110** and **130**.

(52) Sensing portions **111** and **131** may be provided on one surface of each of the driving portions **120** and **140** to detect the movement of the driving portions **120** and **140**. The sensing portions **111** and **131** may include, for example, a piezoelectric element that generates electric energy by deformation of the piezoelectric material. In this case, each of the sensing portions **111** and **131** may include two electrodes and a piezoelectric layer provided between the two electrodes.

(53) The first end **125** of the first resonator **110** and the second end **145** of the second resonator **130** disposed to face each other may respectively correspond to the end of the cantilever beam, which is the driving portion **120** or **140**.

(54) The directional acoustic sensor **100** according to the embodiment includes a resonator arrangement region in which the first resonator **110** and the second resonator **130** face each other, and in the resonator arrangement to face each other, the first resonator **110** and the second resonator **130** may be arranged to form a structure in which the first end **125** and the second end **145** intersect each other.

(55) For example, the first resonator **110** and the second resonator **130** that face each other may have a resonator arrangement such that the first end **125** of the first resonator **110** has a structure in which a width portion of one side of the first resonator **110** extends in the length direction thereof, the second end **145** of the second resonator **130** has a structure in which a width portion of the other side of the second resonator **130** that does not face the width portion of the one side of the first resonator **110** extends in the length direction thereof, and the first end **125** of the first resonator **110** and the second end **145** of the second resonator **130** have an intersecting structure.

(56) In this case, the first end **125** and the second end **145** may be engaged with each other. The first resonator **110** and the second resonator **130** may be arranged facing each other such that the first end **125** and the second end **145** are engaged with each other, but direct collision does not occur and a gap between them is minimized. In this way, when the first end **125** and the second end **145** of the first resonator **110** and the second resonator **130** that face each other form an intersecting structure engaged with each other, in the arrangement region where the first resonator **110** and the second resonator **130** face each other, a through-hole portion of the cavity may be reduced or almost absent, and thus, a decrease in sensitivity due to a decrease in an acoustic resistance may be prevented, the sensitivity for sensing acoustic sound may be improved, and the device size of the directional acoustic sensor **100** may be reduced.

(57) The first end **125** of the first resonator **110** and the second end **145** of the second resonator **130** disposed to face each other may have the same length or different lengths, and a sum of widths of the first end **125** and the second end **145** may be less than half of a sum of a maximum width of the first resonator **110** and a maximum width of the second resonator **130**.

(58) For example, consider a case in which the maximum width of the first resonator **110** and the second resonator **130** disposed to face each other is equal to W . In this case, when the first resonator **110** and the second resonator **130** facing each other are arranged to form an intersecting structure in which the first end **125** and the second end **145** are engaged with each other, the sum of the width of the first end **125** and the width of the second end **145** may be less than or equal to W such that a gap between the first end **125** and the second end **145** is minimized without collision between the first end **125** and the second end **145**. In this case, the first end **125** and the second end **145** of the first resonator **110** and the second resonator **130** facing each other may have the same length or different lengths, and the width of the first end **125** may be the same as or different from the width of the second end **145**. For example, the first end **125** and the second end **145** of the first resonator **110** and the second resonator **130** facing each other may be the same width, and may have a width equal to or less than $W/2$, respectively. When a gap between the first end **125** and the second end **145** intersecting each other is large, an acoustic resistance may be reduced, and thus, the shape, length, and width of the first end **125** of the first resonator **110** and the second end **145** of the second resonator **130** arranged to intersect each other may be determined such that the decrease in sensitivity is prevented by suppressing the decrease in acoustic resistance and a desired resonant frequency is realized without collision between the first end **125** and the second end **145** engaged with each other.

(59) FIGS. **1** and **2** exemplarily illustrate an arrangement in which the plurality of first resonators **110** and the plurality of second resonators **130** are disposed to face each other, and the at least one third resonator **130'** does not face the first resonator **110**. In the case of the third resonator **130'** that does not face the first resonator **110**, the second end **145** having a different shape may not be provided as exemplarily shown in FIGS. **1** and **2**. For example, the third resonator **130'** may be formed to have a constant width. As another example, similar to the second resonator **130** facing the first resonator **110**, even in the case of the third resonator **130'** not facing the first resonator **110**, the second end **145** having a different shape may be provided.

(60) The plurality of first resonators **110**, the plurality of second resonators **130**, and the at least one third resonator **130'** may sense sound frequencies of different bands. That is, the plurality of first resonators **110** may be configured to have different resonance frequencies. To this end, the plurality of first resonators **110** may have dimensions different from each other. For example, the plurality of first resonators **110** may have lengths, widths, or thicknesses different from each other. Also, the plurality of second resonators **130** may be configured to have different resonance frequencies. To this end, the plurality of second resonators **130** may have dimensions different from each other. For example, the plurality of second resonators **130** may have lengths, widths, or thicknesses different from each other. In addition, the shapes, lengths, and widths of the first end **125** of the first resonator **110** and the second end **145** of the second resonator **130** arranged to intersect each other may be determined so as to realize a desired resonant frequency without collision between the first end **125** and the second end **145** that intersect each other. Also, the at least one third resonator **130'** may be configured to have a different resonance frequency. To this end, the at least one third resonator **130'** may have a different dimension. For example, the at least one third resonator **130'** may have a different length, width, or thickness.

(61) FIGS. **1** and **2** illustrate, as an example, a case in which the plurality of first resonators **110** have different lengths from each other, the plurality of second resonators **130** have different lengths from each other, the maximum widths of the first resonator **110** and the second resonator **130** are equal to W , and the first end **125** and the second end **145** have the same width of $W/2$ or less. The directional acoustic sensor **100** according to the present embodiment may have a directivity, for

example, bi-directionality in a z-axis direction.

(62) FIGS. 3A to 3C illustrate various examples of resonators **150**, **160**, **170** that may be applied as the first resonator **110** and the second resonator **130** facing each other in FIGS. 1 and 2 according to embodiments. FIG. 3D illustrates an example of a resonator **150'** that may be applied as the third resonator **130'** that does not face the first resonator **110** in FIGS. 1 and 2 according to an embodiment. FIG. 4 is a cross-sectional view taken along line IV-IV of FIG. 3A, which corresponds to a cross-sectional view of the resonators **150**, **150'**, **160**, and **170** of FIGS. 3A to 3D according to an embodiment. As a third resonator **130'** that does not face the first resonator **110**, the resonators **150**, **160**, and **170** of FIGS. 3A to 3C may be applied instead of the resonator **150'** of FIG. 3D.

(63) Referring to FIGS. 3A to 3D, each of the resonators **150**, **150'**, **160**, and **170** includes a driving portion **180** that vibrates in response to an acoustic signal, and a sensing portion **190** detecting a movement of the driving portion **180**.

(64) The driving portion **180** of each of the resonators **150**, **150'**, **160**, and **170** is configured of a cantilever beam, and may extend in a length direction (x-axis direction in FIGS. 1 and 2) of the resonators **150**, **150'**, **160**, **170** from a support **107** (corresponding to the first support portion **103** or the second support portion **105** in FIGS. 1 and 2) toward a cavity. One end of the driving portion **180** may be fixed to the support portion **107** of a support. The driving portion **180** may be integrally formed with the support, and in this case, the driving portion **180** may include, for example, silicon. However, the present embodiment is not limited thereto, and the driving portion **180** may not be formed integrally with the support. The sensing portion **190** may be provided on one surface of the driving portion **180** to detect the movement of the driving portion **180**. The sensing portion **190** may include a piezoelectric element that generates electric energy by deformation of the piezoelectric material. In this case, the sensing portion **190** may include two electrodes and a piezoelectric layer provided between the two electrodes.

(65) The driving portion **180** of the resonators **150**, **160**, **170** may include a base **181** and a frame **183** protruding from the base **181** and extending in the length direction thereof. The driving portion **180'** of the resonators **150'** may include a base **181** and a frame **183'** protruding from the base **181** and extending in the length direction thereof.

(66) Referring to FIGS. 3A to 3C, the driving portions **180** of the resonators **150**, **160**, and **170** respectively have ends **155**, **165**, and **175** at end portions thereof (corresponding to the first end **125** and the second end **145** in FIGS. 1 and 2). Referring to FIG. 3D, the driving portion **180'** of the resonator **150'** may be formed such that the frame **183'** extends also to an end portion of the base **181**. In the driving portion **180/180'** of the resonators **150**, **160**, and **170/150'**, the frame **183/183'** may be integrally formed with the base **181**, and the ends **155**, **165**, and **175** may also be integrally formed with the base **181** and the frame **183**. The base **181** and the frame **183/183'** may include silicon, and the ends **155**, **165**, and **175** may also include silicon.

(67) The frame **183/183'** may be provided on at least one of both sides and an inner side of the base **181**. The frame **183/183'**, for example, as shown in FIGS. 3A to 3D, may be provided on both sides of the base **181**. Here, the frame **183/183'** may be continuously provided in parallel to the length direction (x-axis direction in FIGS. 1 and 2) of the resonators **150**, **160**, and **170/150'**. For example, the frame **183/183'** may be continuously provided along both edges of the base **181**.

(68) FIG. 4 is a cross-sectional view taken along line IV-IV of FIG. 3A as an example. Referring to FIG. 4, the base **181** may have a predetermined width **W**, and the frame **183** may have a predetermined width **W1**. In addition, the frame **183** may have a predetermined height **t1**, and the base **181** may have a predetermined thickness **t2**. The predetermined thickness **t2** of the base **181** may be less than the height **t1** of the frame **183**, but the present embodiment is not limited thereto.

(69) By configuring the driving portion **180** of the resonator to include the base **181** and the frame **183** extending in the length direction thereof to protrude from the base **181**, compared with a plate-type resonator having a thickness corresponding to a sum of the thickness of the base **181** and the

height of the frame **183**, a mass thereof may be reduced while maintaining the same resonant frequency of the resonator. Accordingly, a bandwidth may be widened by lowering the quality factor of the resonator, and a flatness characteristic and sound quality of the directional acoustic sensor **100** including the resonator arrangement may be improved.

(70) Here, in order to implement a wide frequency range by using a limited number of resonators and to improve flatness characteristics, each of the resonators is required to have a wide bandwidth, and for this purpose, a quality factor of the resonators must be small. The quality factor Q of the resonator may be expressed by Equation (2) below.

$$Q=(m \times f)/c \quad (2)$$

(71) Here, m is an effective mass, f is a resonance frequency, and c is a damping coefficient.

(72) Referring to Equation (2), in order to reduce the quality factor while maintaining the resonant frequency of the resonator constant, it is required to reduce the mass of the resonator. When the mass of the resonator is reduced by reducing the thickness of the resonator, the length of the resonator must also be reduced to maintain the resonant frequency, and accordingly, an area of a portion receiving pressure from the input sound signal is reduced, thereby reducing the sensitivity of the directional acoustic sensor **100**.

(73) However, as in the directional acoustic sensor **100** according to the embodiment, by applying the resonators **150**, **160**, and **170/150'** having the driving portion **180/180'** including the base **181** and the frame **183/183'** extending in the length direction thereof to protrude on the base **181** to the plurality of first resonators **110**, the plurality of second resonators **130**, and the at least one third resonator **130'**, the mass of each resonator may be reduced while maintaining a resonance frequency constant, and accordingly, compared to a conventional plate-type resonator, the quality factor may be reduced and the bandwidth may be increased.

(74) As described above, in the directional acoustic sensor **100** according to the embodiment, by configuring each of the plurality of first resonators **110**, the plurality of second resonators **130**, and the at least one third resonator **130'** to include a frame extending in the length direction thereof to protrude from the base, each resonator may have a wide bandwidth while maintaining a resonant frequency, thereby improving sensitivity and flatness characteristics, and as a result, the number of resonators may be reduced, thereby improving price competitiveness. In addition, sound quality may be improved due to the improvement of the flatness characteristic.

(75) Referring to FIGS. 3A to 3C again, the ends **155**, **165**, and **175** of the driving portion **180** of the resonators **150**, **160**, and **170** (the first end **125** and the second end **145** in FIGS. 1 and 2) may be formed in various shapes.

(76) As exemplarily illustrated in FIG. 3A, the end **155** of the driving portion **180** may be formed such that a width portion of one side of the resonator **150** extends in the length direction thereof, and may be formed in a plate shape up to the thickness of the frame **183**. In the present embodiment, the end **155** may be formed to have a thickness t corresponding to a sum of a thickness t_2 of the base **181** and a thickness t_1 of the frame **183**, or may be formed to have a thickness greater than the thickness t_2 of the base **181** and less than the thickness t .

(77) FIG. 5A is a plan view of an intersecting portion when ends of two facing resonators have plate-shaped ends according to an embodiment. FIG. 5B is a cross-sectional view taken along line A-A* of FIG. 5A according to an embodiment. When the resonator **150** having the end **155** of the driving portion **180** is applied as the first resonator **110** and the second resonator **130** facing each other of the directional acoustic sensor **100** according to the embodiment, as exemplarily illustrated in FIGS. 5A and 5B, the first end **125** of the first resonator **110** and the second end **145** of the second resonator **130** may be arranged in an intersecting structure in which the first end **125** and the second end **145** are engaged with each other. The first end **125** of the first resonator **110** extends in the length direction thereof to correspond to a width portion of one side of the first resonator **110**, and the second end **145** of the second resonator **130** extends in the length direction thereof to correspond to a width portion of the other side of the second resonator **130** that does not face the

width portion of one side of the first resonator **110**. FIG. 5A is a plan view showing a portion where the first end **125** and the second end **145** intersect each other when the first end **125** of the first resonator **110** and the second end **145** of the second resonator **130** are provided with the end **155** having a plate shape as in FIG. 3A, and FIG. 5B is a cross-sectional view taken along line A-A* of FIG. 5A.

(78) As exemplarily illustrated in FIG. 3B, the end **165** of the driving portion **180** may be formed in a structure in which a width portion of one side of the resonator **160** extends in the length direction thereof, and the frame **183** extends to the end of the extended width portion of the one side.

(79) FIG. 6A is a plan view of an intersecting portion when ends of two resonators facing each other have an end with a frame extending to the end according to an embodiment. FIG. 6B is a cross-sectional view taken along line B-B* of FIG. 6A according to an embodiment. When the resonator **160** having the end **165** of the driving portion **180** is applied as the first resonator **110** and the second resonator **130** facing each other of the directional acoustic sensor **100** according to the embodiment, as exemplarily illustrated in FIGS. 6A and 6B, the first end **125** of the first resonator **110** and the second end **145** of the second resonator **130** may be arranged in an intersecting structure in which the first end **125** and the second end **145** are engaged with each other. The first end **125** of the first resonator **110** may have a structure in which a width portion of one side of the first end **125** of the first resonator **110** extends in the length direction thereof, and the second end **145** of the second resonator **130** may have a structure in which a width portion of other side of the second end **145** of the second resonator **130** that does not face the width portion of the one side of the first resonator **110** extends in the length direction thereof, and frames **127** and **147** may be formed to extend to the end portions of the first and second ends **125** and **145**. FIG. 6A is a plan view showing an intersecting portion of the first end **125** and the second end **145** when the first end **125** of the first resonator **110** and the second end **145** of the second resonator **130** facing each other include the end **165** formed by extending the frame **183** to the end as in FIG. 3B, and FIG. 6B is a cross-sectional view taken along line B-B* of FIG. 6A.

(80) As exemplarily illustrated in FIG. 3C, the end **175** of the driving portion **180** may be formed in a structure in which a width portion of one side of the resonator **170** extends in the length direction thereof, and the frame **183** extends to a circumference of the extended end **175**.

(81) FIG. 7A is a plan view of an intersecting portion when ends of two resonators facing each other have an end with a frame extending to a circumference thereof according to an embodiment. FIG. 7B is a cross-sectional view taken along line C-C* of FIG. 7A according to an embodiment. When the resonator **170** having the end **175** of the driving portion **180** is applied as the first resonator **110** and the second resonator **130** facing each other of the directional acoustic sensor **100** according to the embodiment, the first end **125** of the first resonator **110** and the second end **145** of the second resonator **130** facing each other may be arranged in an intersecting structure in which the first and second ends **125** and **145** are engaged with each other as exemplarily illustrated in FIGS. 7A and 7B. The first end **125** of the first resonator **110** may have a structure in which a width portion of one side of the first resonator **110** extends in the length direction thereof, and the second end **145** of the second resonator **130** may have a structure in which a width portion of other side of the second resonator **130** that does not face the width portion of one side of the first resonator **110** extends in the length direction of the second resonator **130**, and the frames **127** and **147** may extend to the circumference of the first end **125** and the second end **145**. FIG. 7A is a plan view showing an intersecting portion of the first end **125** and the second end **145** when the first end **125** of the first resonator **110** and the second end **145** of the second resonator **130** facing each other include the end **175** in which the frame **183** is formed by extending to a circumference of the end **175** as shown in FIG. 3C, and FIG. 7B is a cross-sectional view taken along line C-C* of FIG. 7A.

(82) When the resonators **150**, **160**, and **170** having the ends **155**, **165**, and **175** of the shape as exemplarily illustrated in FIGS. 3A to 3C are applied to the first resonator **110** and the second resonator **130** facing each other of the directional acoustic sensor **100** according to the

embodiment, the intersecting structure in which the first and second ends **125** and **145** are engaged with each other may be formed to a thickness reaching a height of the frame as in FIGS. **5A** and **5B**, or the frames **127** and **147** may be formed to extend to at least a portion of the engaged intersecting portion of the first and second ends **125** and **145** as in FIGS. **6A** and **6B** and as in FIGS. **7A** and **7B**.

(83) FIGS. **1** and **2** illustrate an example in which the structure of FIGS. **5A** and **5B** is applied as an intersecting structure of the first and second ends **125** and **145** engaged each other. Alternatively, the structure of FIGS. **6A** and **6B** or the structure of FIGS. **7A** and **7B** may be applied as the intersecting structure of the first and second ends **125** and **145** engaged each other.

(84) In FIGS. **1**, **2**, **3A**, **3B**, and **3C**, it is illustrated that the frame **183** does not extend to the end of the base **181** where the first end **125** of the driving portion **120** of the first resonator **110** and the second end **145** of the driving portion **140** of the second resonator **130** are not located, but this is merely an example, and the embodiment is not limited thereto. That is, the frame **183** may extend to the end of the base **181** where the first end **125** and the second end **145** are not located.

(85) In addition, in FIGS. **1**, **2**, **3A**, **3B**, and **3C**, it has been described and illustrated that the driving portions **120** and **140** of the first resonator **110** and the second resonator **130** have a structure including the base **181** and the frame **183** protruding from the base **181**, but this is merely an example, and the embodiment is not limited thereto. For example, the driving portions **120** and **140** of the first resonator **110** and the second resonator **130** may be formed in a structure without the frame **183**.

(86) FIG. **8** is a diagram of an example of forming an intersecting structure in which ends of two resonators facing each other are engaged with each other in an edge shape according to an embodiment. FIG. **9** is a diagram of an example of forming an intersecting structure in which ends of two resonators facing each other are engaged with each other in a male/female form according to an embodiment. In the above description, it has been described a case in which, at the intersecting portion of the first end **125** and the second end **145**, the width portion of the one side of the first resonator **110** and the width portion of the other side of the second resonator **130** that face each other extend in the length direction thereof to form an intersecting structure in which the first end **125** and the second end **145** are engaged with each other, but the embodiment is not limited thereto. For example, as shown in FIG. **8**, the first end **125** and the second end **145** may be formed in an intersecting structure that engages with each other in an edge shape. In addition, an intersecting portion where the first and second ends **125** and **145** are engaged with each other may be formed to have an intersecting structure in which the first end **125** and the second end **145** are engaged with each other in a male/female shape, as shown in FIG. **9**. The male/female shape of the first end **125** and the second end **145** may be formed opposite to that in FIG. **9**. Also, in FIGS. **8** and **9**, the first end **125** and the second end **145** may be formed in a plate-shape with a thickness reaching the height of the frame, or may be formed in a structure in which the frame extends to at least a portion of the intersecting portions of the first and second ends **125** and **145**. In FIGS. **8** and **9**, the specific structure of the intersecting portions of the first end **125** and the second end **145** engaged with each other may be inferred from FIGS. **5A** and **5B**, FIGS. **6A** and **6B**, and FIGS. **7A** and **7B**, and thus, repeated descriptions and illustrations thereof are omitted.

(87) In the embodiment described above, as an example, it is depicted that the directional acoustic sensor **100** according to the embodiment has a resonator arrangement including a plurality of first resonators **110**, a plurality of second resonators **130**, and at least one third resonator **130'**, and in FIGS. **1** and **2**, the directional acoustic sensor **100** includes a total of 16 resonators by including seven first and second resonators **110** and **130** respectively forming a resonator arrangement to face each other, respectively, and two third resonator **130'** that does not face the first resonator **110**, and the embodiment is not limited thereto.

(88) According to the directional acoustic sensor **100** according to the embodiment as described above, the first end **125** of the first resonator **110** and the second end **145** of the second resonator

130 that face each other in the resonator arrangement form an intersecting structure in which the first end **125** and the second end **145** are engaged with each other, and thus, a through-hole in the cavity may be minimized or virtually eliminated in an arrangement region where the resonators face each other. Accordingly, in the directional acoustic sensor **100** according to the embodiment, a decrease in acoustic resistance may be suppressed, such that sensitivity may be improved, and a layout size of a resonator arrangement may be reduced, such that a device size may be reduced.

(89) On the other hand, when the ends of the resonators facing each other are disposed without an intersecting structure, there may be a through-hole between the two facing resonators, whereby the acoustic resistance is reduced, and as a result, the sensitivity may be reduced than that of the directional acoustic sensor **100** according to the embodiment.

(90) FIG. **10** is a schematic plan view illustrating a directional acoustic sensor according to a comparative example. FIG. **10** shows an example in which the directional acoustic sensor **200** according to the comparative example is provided to compare to the directional acoustic sensor **100** according to the embodiment of FIG. **2**.

(91) Referring to FIG. **10**, the directional acoustic sensor **200** of the comparative example includes a support **201**, and a plurality of first resonators **210** and a plurality of second resonators **230** provided on the support **201**. The plurality of first resonators **210** and the plurality of second resonators **230** are arranged to form a resonator arrangement in which at least some of them face each other in a cavity of the support **201**.

(92) One end of each of the plurality of first resonators **210** is fixed to the first support portion **203** of the support **201** to form a planarly parallel arrangement in the cavity of the support **201**. One end of each of the plurality of second resonators **230** is fixed to the second support **205** of the support **201** to form a planarly parallel arrangement in the cavity of the support **201**.

(93) When compared with the directional acoustic sensor **100** according to the embodiment shown in FIG. **2**, the directional acoustic sensor **200** of the comparative example does not have an intersecting structure of ends of the first resonator **210** and the second resonator **230** facing each other. In FIG. **10**, reference numeral **230'** denotes a second resonator that does not face the first resonator **210**.

(94) Each of the plurality of first resonators **210** and the plurality of second resonators **230** include bases **211** and **231** and frames **213** and **233** extending in a length direction thereof to protrude from the bases **211** and **231**, and the frames **213** and **233** extend to end portions of the first resonator **210** and the second resonator **230**.

(95) In the directional acoustic sensor **200** of the comparative example, the first resonator **210** and the second resonator **230** facing each other do not have an intersecting structure of ends, there may be a through hole **240** of the cavity between the first resonator **210** and the second resonator **230** facing each other.

(96) FIG. **11** is a diagram of a comparison of a change of a layout size of a resonator arrangement before (comparative example) and after (embodiment example) application of the intersecting structure of ends of two resonators facing each other according to an embodiment. In FIG. **11**, when the resonant frequency change before (comparative example) and after (embodiment example) a change of the shape of the ends of the two facing resonators is limited to about 5% or less, a design example in which the size of device in the length direction thereof is reduced from approximately 2950 μm to approximately 2700 μm is shown. When not limiting the resonant frequency change, the ends that constitute an intersecting structure may be formed up to approximately half the length of the resonator.

(97) In FIG. **11**, a layout of the resonator arrangement before applying the intersecting structure of the two facing resonators corresponds to the directional acoustic sensor **200** of the comparative example shown in FIG. **10**, and a layout of the resonator arrangement after the application of the intersecting structure of the ends of the two facing resonators corresponds to the directional acoustic sensor **100** according to the embodiment shown in FIG. **2**.

(98) As shown in FIG. 11, the directional acoustic sensor **100** according to the embodiment to which an intersecting structure of the ends of the two resonators facing each other is applied has a reduced layout size of the resonator arrangement by about 10% compared to the directional acoustic sensor **200** of the comparative example to which the intersecting structure of the ends is not applied. Therefore, according to the directional acoustic sensor **100** according to the embodiment, the size of the device may be reduced, and thus, price competitiveness may be improved.

(99) FIG. 12 is a graph showing the change in frequency response characteristics of resonators before (comparative example) and after (embodiment example) application of an intersecting structure of ends of two resonators facing each other according to an embodiment.

(100) As shown in FIG. 12, it may be seen that the sensitivity increases by about 2.4 dB when the intersecting structure of the ends of the two resonators facing each other is applied. As such, according to the directional acoustic sensor **100** according to the embodiment, due to the intersecting structure of the ends of the two facing resonators, there is almost no through-hole between the two facing resonators, and thus, the decrease in acoustic resistance is suppressed, thereby increasing the sensitivity.

(101) FIG. 13 is a graph showing resonant frequency characteristics for each channel of a resonator arrangement before (comparative example) and after (embodiment example) the application of an intersecting structure of ends of two resonators facing each other. The channel represents each resonator, and when width, thickness, and mass conditions are the same, the resonant frequency of each channel (resonator) is approximately proportional to the square root of a beam length of the resonator. The resonance frequency graph of FIG. 13 is a result obtained through COMSOL simulation.

(102) As shown in FIG. 13, it may be seen that, even when an intersecting structure of ends of two resonators facing each other is applied, a directional acoustic sensor with almost no change in primary and secondary resonant frequencies may be implemented.

(103) From the difference in layout size of the resonator arrangement before (comparative example) and after (embodiment example) application of the intersecting structure of the ends of the two resonators facing each other as in FIG. 11, the frequency response characteristics of the resonator in FIG. 12, and the resonant frequency characteristics for each channel of FIG. 13, by applying an intersecting structure of ends of two resonators facing each other to a directional acoustic sensor, it may be seen that a directional acoustic sensor having good sensitivity and desired resonant frequency characteristics for each channel may be implemented, and a device size may be reduced. FIGS. 11 to 13 are only illustrative, and the embodiment is not limited thereto.

(104) The directional acoustic sensor **100** according to the embodiment may be manufactured, for example, as shown in FIG. 14, and may be packaged as shown in FIG. 15.

(105) FIG. 14 is a photograph after manufacturing the directional acoustic sensor **100** according to the embodiment. FIG. 15 is a photograph after packaging the directional acoustic sensor **100** of FIG. 14 according to an embodiment. FIG. 15 shows an example in which holes are formed in a packaging case such that acoustic sound is transmitted to the directional acoustic sensor **100**. FIG. 16 is a graph showing a result of measuring a frequency response characteristic of the directional acoustic sensor **100** according to the manufactured embodiment. It may be confirmed from the measurement result of FIG. 16 that the device size may be reduced without decreasing in sensitivity. Here, FIGS. 14 to 16 are only illustrative, and the present embodiment is not limited thereto, and the directional acoustic sensor **100** according to the embodiment may be modified to have various frequency response characteristics.

(106) In the above, a resonator having a structure including a base and a frame extending along both edges of the base in the length direction thereof to protrude from the base has been described as the first resonator **110** and the second resonator **130** facing each other in the directional acoustic sensor **100** according to the embodiment, but the embodiment is not limited thereto, and resonators

having various structures may be applied.

(107) FIGS. **17**, **18** and **19** are diagrams of other examples of resonators that may be applied to two resonators facing each other according to an embodiment. FIGS. **17** to **19** illustrate other examples of resonators **250**, **270**, and **290** that may be applied as the first resonator **110** and the second resonator **130** facing each other in FIGS. **1** and **2**.

(108) Referring to FIG. **17**, a driving portion **260** of the resonator **250** may include a base **181** and a frame **183** protruding from the base **181** and extending in the length direction thereof. Also, the driving portion **260** of the resonator **250** may have an end **155** (e.g., corresponding to the first end **125** and the second end **145** in FIGS. **1** and **2**) at the end thereof.

(109) The frame **183** may be continuously provided parallel to the length direction of the resonator **250** inside the base **181**. In FIG. **17**, a case in which only one frame **183** is provided is illustrated as an example, but the embodiment is not limited thereto, and a plurality of frames **183** may be provided inside the base **181**.

(110) Referring to FIG. **18**, a driving portion **280** of the resonator **270** may include a base **281** and a groove pattern **282** having a predetermined depth in the base **281**. Also, the driving portion **280** of the resonator **270** may have an end **155** (corresponding to the first end **125** and the second end **145** in FIGS. **1** and **2**) at the end thereof.

(111) The groove pattern **282** may be formed in a regular shape on the base **281**. Here, the groove pattern **282** is formed in the base **281** to a predetermined depth, thereby reducing the mass of the resonator compared to a resonator having only the base without the groove pattern.

(112) The resonator **270** according to the present embodiment includes the groove pattern **282** formed to a predetermined depth in the base **281**, thereby reducing the mass of the resonator **270** while maintaining the resonant frequency constant, and accordingly, a quality factor may be reduced and a bandwidth may be increased compared to a resonator including only a base without a groove pattern.

(113) Referring to FIG. **19**, a driving portion **295** of a resonator **290** may include a base **296** and a plurality of through holes **297** formed through the base **296**. The plurality of through-holes **297** may be formed in a regular shape in the base **296**. In addition, the driving portion **295** of the resonator **290** may have an end **155** (corresponding to the first end **125** and the second end **145** in FIGS. **1** and **2**) at the end thereof.

(114) The resonator **290** shown in FIG. **19** may have the same resonant frequency as a resonator in which a plurality of through holes are not formed. To this end, each through hole **297** may be formed to have a size smaller than the wavelength of an audible frequency band.

(115) In the present embodiment, the resonator **290** includes a plurality of through-holes **297** having a size smaller than a wavelength of an audible frequency band formed in the base **296**, thereby reducing the mass of the resonator while maintaining the resonant frequency constant, and accordingly, compared to a resonator that does not include a plurality of through-holes, a quality factor may be reduced and a bandwidth may be increased.

(116) In FIGS. **17**, **18**, and **19**, the resonators **250**, **270**, and **290** are illustrated as having plate-shaped ends **155** at the ends of the driving portions **260**, **280**, and **295**, but the embodiment is not limited thereto, and the shapes of the ends may be modified in various forms as described above.

(117) On the other hand, the resonators **250**, **270**, and **290** of FIGS. **17**, **18**, and **19** may also be applied to the third resonator **130'** that does not face the first resonator **110** in FIGS. **1** and **2**, and in this case, the structure may be changed to a structure without the end **155**, or a structure including the end **155** may be applied as it is.

(118) The directional acoustic sensor **100** according to the embodiment as described above may reduce or eliminate through-holes caused by the arrangement of the resonators having different lengths from each other by forming ends of two facing resonators to an intersecting structure engaged each other, thereby, improving the acoustic sensitivity and reducing the device size.

(119) The directional acoustic sensor **100** according to the embodiment described above may be

applied to various electronic devices to which a voice interface technology is applied, for example, a smart phone, a foldable phone, an AI speaker, AR glasses, wearable devices, robots, TVs, etc. (120) FIGS. 20, 21, 22, 23, 24 and 25 are diagrams of examples of electronic devices to which the directional acoustic sensor according to an embodiment is applied as a voice interface device according to an embodiment. For example, the directional acoustic sensor 100 according to the embodiment may be applied to AR glasses 1000, earbuds 1100, smart phones 1200, TVs 1300, artificial intelligent speakers 1400, and the like as shown in FIGS. 20 to 24. Also, the directional acoustic sensor 100 according to the embodiment may be applied to a vehicle 1500 as shown in FIG. 25. FIG. 25 shows an example in which the directional acoustic sensor 1510 according to the embodiment is provided on an upper side of the windshield, and besides above, the directional acoustic sensor 1510 according to the embodiment may be mounted at various positions inside and outside the vehicle 1500. In addition, the directional acoustic sensor 100 according to the embodiment may be applied to various electronic devices including household appliances, such as air conditioners, refrigerators, and air purifiers. Although the embodiments have been described above, this is merely examples, and various modifications are possible to those skilled in the art from the above description.

(121) According to the directional acoustic sensor according to the embodiment, by forming ends of two facing resonators in an intersecting structure, a through-hole of a cavity in an arrangement region facing resonators may be minimized, and thus a directional acoustic sensor with improved sensitivity may be realized.

(122) In addition, by forming the ends of the two resonators in an intersecting structure, the size of the resonator arrangement region may be reduced, thereby reducing the device size.

(123) It should be understood that embodiments described herein should be considered in a descriptive sense only and not for purposes of limitation. Descriptions of features or aspects within each embodiment should typically be considered as available for other similar features or aspects in other embodiments. While one or more embodiments have been described with reference to the figures, it will be understood by those of ordinary skill in the art that various changes in form and details may be made therein without departing from the spirit and scope as defined by the following claims.

Claims

1. A directional acoustic sensor comprising: a support comprising a first support portion and a second support portion that are separated from each other and face each other; a plurality of first resonators extending in a length direction thereof from the first support portion of the support, each first resonator of the plurality of first resonators comprising: a first end fixed to the first support portion and having a first width at a position where the first end is fixed to the first support portion; a base and a frame extending from the first end, wherein the frame extends to a first height and the base has a thickness that is less than the first height; and a second end opposite the first end that is fixed to the first support portion and having a second width less than the first width; and a plurality of second resonators extending in the length direction thereof from the second support portion of the support and facing the plurality of first resonators, each second resonator of the plurality of second resonators comprising: a first end fixed to the second support portion and having a third width at a position where the first end is fixed to the second support portion; a base and a frame extending from the first end, wherein the frame extends to the first height and the base has a thickness that is less than the first height; and a second end opposite the first end that is fixed to the second support portion and having a fourth width less than the third width, wherein, in a first resonator arrangement of a region where the plurality of first resonators and the plurality of second resonators face each other, the second ends of the plurality of first resonators and the second ends of the plurality of second resonators form an intersecting structure.

2. The directional acoustic sensor of claim 1, wherein the second end of each first resonator of the plurality of first resonators has a structure in which a width portion of each first resonator extends in the length direction thereof, and wherein the second end of each second resonator of the plurality of second resonators has a structure in which a width portion of each second resonator that does not face the width portion of a corresponding first resonator extends in the length direction thereof.
3. The directional acoustic sensor of claim 2, wherein the second ends of the plurality of first resonators and the second ends of the plurality of second resonators respectively engage with each other.
4. The directional acoustic sensor of claim 2, wherein the second ends of the plurality of first resonators and the second ends of the plurality of second resonators respectively engage with each other in a male or female form.
5. The directional acoustic sensor of claim 1, wherein, in each first resonator of the plurality of first resonators and each second resonator in the plurality of second resonators, the frame is integrally formed with the base.
6. The directional acoustic sensor of claim 1, wherein, in each first resonator of the plurality of first resonators and each second resonator in the plurality of second resonators, each of the base and the frame comprises silicon.
7. The directional acoustic sensor of claim 1, wherein, in each first resonator of the plurality of first resonators and each second resonator in the plurality of second resonators, the frame is provided on at least one of both sides and an inside of the base.
8. The directional acoustic sensor of claim 1, wherein each the second ends of the plurality of first resonators and the second ends of the plurality of second resonators has a plate shape up to the first height.
9. The directional acoustic sensor of claim 1, wherein, in each first resonator of the plurality of first resonators and each second resonator in the plurality of second resonators, the base and the frame respectively extend to each of the second ends of the plurality of first resonators and each of the second ends of the plurality of second resonators.
10. The directional acoustic sensor of claim 1 the frame of each first resonator and the frame of each second resonator extends to end portions of the second end of each first resonator and the second end of each second resonator, respectively.
11. The directional acoustic sensor of claim 1, wherein the frame of each first resonator and the frame of each second resonator extends to a circumference of the second end of each first resonator and the second end of each second resonator, respectively.
12. The directional acoustic sensor of claim 1, further comprising at least one third resonator extending in the length direction thereof from the first support portion or the second support portion of the support and not facing the plurality of first resonators or the plurality of second resonators.
13. The directional acoustic sensor of claim 12, wherein the at least one third resonator comprises: a base; and a frame protruding from the base and extending in the length direction thereof.
14. The directional acoustic sensor of claim 1, wherein each first resonator of the plurality of first resonators and each second resonator of the plurality of second resonators comprises: a driving portion configured to move in response to an input sound signal; and a sensing portion configured to detect movement of the driving portion.
15. The directional acoustic sensor of claim 14, wherein the second ends of each first resonator of the plurality of first resonators and each second resonator of the plurality of second resonators is configured to move freely.
16. The directional acoustic sensor of claim 14, wherein the plurality of first resonators and the plurality of second resonators have resonant frequencies different from each other.
17. An electronic device comprising: a directional acoustic sensor comprising: a support comprising a first support portion and a second support portion that are separated from each other

and face each other; a plurality of first resonators extending in a length direction thereof from the first support portion of the support, each first resonator of the plurality of first resonators comprising: a first end fixed to the first support portion and having a first width at a position where the first end is fixed to the first support portion; a base and a frame extending from the first end, wherein the frame extends to a first height and the base has a thickness that is less than the first height; and a second end opposite the first end that is fixed to the first support portion and having a second width less than the first width; and a plurality of second resonators extending in the length direction thereof from the second support portion of the support and facing the plurality of first resonators, each second resonator of the plurality of second resonators comprising: a first end fixed to the second support portion and having a third width at a position where the first end is fixed to the second support portion; a base and a frame extending from the first end, wherein the frame extends to the first height and the base has a thickness that is less than the first height; and a second end opposite the first end that is fixed to the second support portion and having a fourth width less than the third width, wherein, in a first resonator arrangement of a region where the plurality of first resonators and the plurality of second resonators face each other, the second ends of the plurality of first resonators and the second ends of the plurality of second resonators form an intersecting structure.

18. The electronic device of claim 17, wherein the directional acoustic sensor further comprises at least one third resonator extending in the length direction thereof from the first support portion or the second support portion of the support and not facing the plurality of first resonators or the plurality of second resonators.

19. The electronic device of claim 18, wherein the at least one third resonator comprises: a base; and a frame protruding from the base and extending in the length direction thereof.

20. The electronic device of claim 17, wherein each first resonator of the plurality of first resonators and each second resonator of the plurality of second resonators comprises: a driving portion configured to move in response to an input sound signal, and a sensing portion configured to detect movement of the driving portion.

21. The electronic device of claim 20, wherein the second ends of each first resonator of the plurality of first resonators and each second resonator of the plurality of second resonators are configured to move freely.

22. The electronic device of claim 20, wherein the plurality of first resonators and the plurality of second resonators have resonant frequencies different from each other.

23. A directional acoustic sensor comprising: a support; a plurality of first resonators extending in a length direction thereof from the support, each first resonator of the plurality of first resonators comprising: a first end fixed to the support and having a first width at a position where the first end is fixed to the support; a base and a frame extending from the first end, wherein the frame extends to a first height and the base has a thickness that is less than the first height; and a second end opposite the first end that is fixed to the support and having a second width less than the first width; and a plurality of second resonators extending in the length direction thereof from the support and facing the plurality of first resonators, each second resonator of the plurality of second resonators comprising: a first end fixed to the support and having a third width at a position where the first end is fixed to the support; a base and a frame extending from the first end, wherein the frame extends to the first height and the base has a thickness that is less than the first height; and a second end opposite to the first end that is fixed to the support and having a fourth width less than the third width, wherein the second ends of the plurality of first resonators and the second ends of the plurality of second resonators form an intersecting structure.
