

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12405760
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Su; Hang

Enhanced screen sharing method and system, and electronic device

Abstract

An enhanced screen sharing method includes: a first electronic device that displays a first shared interface, and sends interface data of the first shared interface to a second electronic device. The second electronic device receives the interface data, and displays a second shared interface corresponding to the first shared interface. The second electronic device enables an interconnection mode for the first electronic device, and when detecting a trigger operation performed by a user on the second shared interface, determines event information corresponding to the trigger operation. The event information includes an event type and operation area information that correspond to the trigger operation. The second electronic device sends the event information to the first electronic device. The first electronic device receives the event information, and performs a corresponding operation based on the event information.

Inventors:	Su; Hang (Xi'an, CN)
Applicant:	Huawei Technologies Co., Ltd. (Shenzhen, CN)
Family ID:	81991200
Assignee:	HUAWEI TECHNOLOGIES CO., LTD. (Shenzhen, CN)
Appl. No.:	18/336885
Filed:	June 16, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230333803 A1	Oct. 19, 2023

Foreign Application Priority Data

CN	202011518228.1	Dec. 21, 2020
----	----------------	---------------

Related U.S. Application Data

continuation parent-doc WO PCT/CN2021/137463 20211213 PENDING child-doc US 18336885

Publication Classification

Int. Cl.: G06F3/14 (20060101); G06F3/0488 (20220101)

U.S. Cl.:

CPC G06F3/1454 (20130101); G06F3/0488 (20130101);

Field of Classification Search

CPC: G06F (3/1454); G06F (3/0488); G06F (3/0482); G06F (9/451); H04M (1/72439); H04M (2250/22); H04M (1/72406); H04M (1/72469); H04N (7/147); H04N (7/141)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2008/0125104	12/2007	You et al.	N/A	N/A
2011/0165841	12/2010	Baek	455/41.2	H04L 67/10
2012/0092277	12/2011	Momchilov	345/173	G06F 3/038
2012/0178536	12/2011	Oh	463/42	H04L 12/1822
2013/0167040	12/2012	Lee	715/748	H04N 1/00129
2013/0234984	12/2012	Yoo	345/174	H04N 21/4222
2014/0240440	12/2013	Seo	715/753	H04L 51/04
2015/0169129	12/2014	Park	345/174	G06F 3/0488
2016/0062572	12/2015	Yang	715/835	H04W 4/80
2017/0083148	12/2016	Ahn	N/A	G06F 3/1446
2018/0367483	12/2017	Rodriguez	N/A	H04L 51/046

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
101582020	12/2008	CN	N/A
101582021	12/2008	CN	N/A
101789955	12/2009	CN	N/A
103685389	12/2013	CN	N/A

Primary Examiner: Siddiqui; Md Saiful A

Attorney, Agent or Firm: Conley Rose, P.C.

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATIONS (1) This is a continuation of International Patent Application No. PCT/CN2021/137463 filed on Dec. 13, 2021, which claims priority to

TECHNICAL FIELD

(1) This disclosure relates to the field of communications, and in particular, to an enhanced screen sharing method and system, and an electronic device.

BACKGROUND

(2) Continuous development of information technology and popularization and diversification of electronic devices, such as a mobile phone and a tablet, lead to increasingly rich functions of the electronic devices. For example, a technology for screen sharing and interaction between electronic devices has become increasingly mature. Screen sharing and interaction refer to a technology in which electronic devices with a screen display function respectively serve as a screen sharing initiator device (an initiator device) and a screen sharing recipient device (a recipient device), to implement sharing and exchange of information such as screen content and media content between the electronic devices.

(3) When the initiator device and the recipient device perform screen sharing and interaction, the recipient device may receive a relatively single operation performed by a user on a shared screen. For example, the recipient device may receive an operation such as graffiti performed by the user on the shared screen. There is a problem that good interaction cannot be implemented between the recipient device and the initiator device, and user experience is affected.

SUMMARY

(4) Embodiments of this disclosure provide an enhanced screen sharing method and system, and an electronic device. In a process of screen sharing between electronic devices, a recipient device of the screen sharing may receive more types of operations performed by a user on a shared interface of the screen sharing. In this way, better interaction between the recipient device and an initiator device of screen sharing is implemented, thereby improving user experience.

(5) To resolve the foregoing technical problem, according to a first aspect, an implementation of embodiments of this disclosure provides an enhanced screen sharing method. The method includes a first electronic device that displays a first shared interface, and sends interface data of the first shared interface to a second electronic device. The second electronic device receives the interface data, and displays, based on the interface data, a second shared interface corresponding to the first shared interface. The second electronic device enables an interconnection mode for the first electronic device. In the interconnection mode, the second electronic device detects a trigger operation performed by a user on the second shared interface, and determines event information corresponding to the trigger operation. The event information includes an event type and operation area information that correspond to the trigger operation. The second electronic device sends the event information to the first electronic device. The first electronic device receives the event information, and performs a corresponding operation on the first electronic device based on the event information.

(6) The second electronic device may enable, by the detected trigger operation performed by the user on the second shared interface, the first electronic device to perform the corresponding operation on the first electronic device, so as to implement interconnection between the second electronic device and the first electronic device. In this way, interaction between the second electronic device and the first electronic device can be better implemented, thereby improving availability and user friendliness of the shared interface to improve user experience.

(7) In a possible implementation of the foregoing first aspect, the event type may be, for example, an input event such as a single-tap input event, a double-tap input event, a touch-and-hold input event, or a flicking input event. The operation area information may be position coordinate information of a user trigger position (for example, a coordinate of a position at which the user performs a single-tap operation).

- (8) In a possible implementation of the foregoing first aspect, the first shared interface and the second shared interface may be completely the same, and may be collectively referred to as a shared interface.
- (9) In another possible implementation of the foregoing first aspect, the first shared interface and the second shared interface may also be partially the same.
- (10) In a possible implementation of the foregoing first aspect, that the first electronic device performs a corresponding operation on the first electronic device based on the event information includes the following. The first electronic device determines a first operation type based on the event type. The first electronic device performs the corresponding operation on the first electronic device based on the first operation type and the operation area information.
- (11) In a possible implementation of the foregoing first aspect, if the event type is a first input event, the first operation type is an application determining operation. The first electronic device determines, based on the operation area information, application identification information of an application corresponding to the operation area information on the first shared interface. The first electronic device generates event response information. The event response information includes the application identification information. The first electronic device sends the event response information to the second electronic device. The second electronic device receives the event response information, and if determining, based on the event response information, that the application corresponding to the application identification information is not currently installed in the second electronic device, downloads or downloads and installs the application corresponding to the application identification information.
- (12) In a possible implementation of the foregoing first aspect, the first input event is a double-tap input event or a touch-and-hold input event.
- (13) The second electronic device interconnects with the first electronic device, and the second electronic device may implement an operation of downloading and installing, by the second electronic device, an application corresponding to an application in the first electronic device. In this way, interaction between the two can be better implemented, thereby improving availability and user friendliness of the shared interface to improve user experience.
- (14) In a possible implementation of the foregoing first aspect, the method further includes the following. The first electronic device determines a second operation type based on the first operation type. The second operation type is an application download or download and installation operation. The first electronic device generates event response information. The event response information includes the application identification information and the second operation type. If the second electronic device determines, based on the event response information, that the application corresponding to the application identification information is not currently installed in the second electronic device, the second electronic device downloads or downloads and installs the application corresponding to the application identification information.
- (15) The second electronic device interconnects with the first electronic device, and an operation of downloading and installing, by the second electronic device, an application corresponding to an application in the first electronic device can be implemented. In this way, interaction between the two can be better implemented, thereby improving availability and user friendliness of the shared interface to improve user experience.
- (16) In a possible implementation of the foregoing first aspect, if the event type is the second input event, the first operation type is an operation object trigger operation. The first electronic device determines, based on the operation area information, an operation object corresponding to the operation area information on the first shared interface. The first electronic device performs an operation of triggering the operation object.
- (17) In a possible implementation of the foregoing first aspect, the second input event is a single-tap input event or a flicking input event.
- (18) The interconnection between the second electronic device and the first electronic device can

implement that the second electronic device interconnects with the first electronic device to perform an operation such as operation object trigger. In this way, interaction between the second electronic device and the first electronic device can be better implemented, thereby improving availability and user friendliness of the shared interface to improve user experience.

(19) In a possible implementation of the foregoing first aspect, if a first screen resolution of the first electronic device is different from a second screen resolution of the second electronic device, the method further includes the following. The second electronic device obtains initial operation area information based on the trigger operation. The second electronic device adjusts the initial operation area information based on the first screen resolution and the second screen resolution to obtain the operation area information. Alternatively, the first electronic device adjusts the received operation area information based on the first screen resolution and the second screen resolution, and performs a corresponding operation based on adjusted operation area information and the first operation type.

(20) Through resolution adjustment, the operation area information of the area in which the user performs the trigger operation can be accurately determined.

(21) In a possible implementation of the foregoing first aspect, the operation area information is position coordinate information.

(22) In a possible implementation of the foregoing first aspect, that the second electronic device enables an interconnection mode for the first electronic device includes the following. The first electronic device displays a first interconnection control. If detecting an enabling trigger operation performed by the user on the first interconnection control, the first electronic device enables the interconnection mode with the second electronic device. Alternatively, the second electronic device displays a second interconnection control. If detecting an enabling trigger operation performed by the user on the second interconnection control, the second electronic device enables the interconnection mode for the first electronic device.

(23) The interconnection mode may be enabled by the first electronic device, or may be enabled by the second electronic device. This may be set as required.

(24) In a possible implementation of the foregoing first aspect, that the second electronic device enables the interconnection mode for the first electronic device if detecting an enabling trigger operation performed by the user on the second interconnection control includes the following. If detecting the enabling trigger operation performed by the user on the second interconnection control, the second electronic device sends an interconnection request to the first electronic device. The first electronic device receives the interconnection request, and displays an interconnection determining control. If the first electronic device detects a trigger operation performed by the user on the interconnection determining control, the second electronic device generates and sends, to the second electronic device, an interconnection response indicating that interconnection is agreed. The second electronic device receives the interconnection response, and enables the interconnection mode for the first electronic device.

(25) In a possible implementation of the foregoing first aspect, the method further includes the following. The second electronic device enables the interconnection mode for the first electronic device, and generates interconnection operation prompt information. The second electronic device displays the interconnection operation prompt information. In this way, a user can conveniently perform an interconnection operation, and user experience can be improved.

(26) According to a second aspect, an implementation of embodiments of this disclosure provides an enhanced screen sharing method, applied to a first electronic device. The method includes the first electronic device that displays a first shared interface, and sends interface data of the first shared interface to a second electronic device, to enable the second electronic device to display, based on the interface data, a second shared interface corresponding to the first shared interface. The first electronic device receives event information sent by the second electronic device, and performs a corresponding operation on the first electronic device based on the event information.

The event information is information determined based on a trigger operation of a user for the shared interface in an interconnection mode for the first electronic device after the second electronic device enables the interconnection mode. The event information includes an event type and operation area information that correspond to the trigger operation.

(27) The second electronic device may enable, by a detected trigger operation performed by the user on the second shared interface, the first electronic device to perform the corresponding operation on the first electronic device, so as to implement interconnection between the second electronic device and the first electronic device. In this way, interaction between the second electronic device and the first electronic device can be better implemented, thereby improving availability and user friendliness of the shared interface to improve user experience.

(28) In a possible implementation of the foregoing second aspect, that the first electronic device performs a corresponding operation on the first electronic device based on the event information includes the following. The first electronic device determines a first operation type based on the event type. The first electronic device performs the corresponding operation on the first electronic device based on the first operation type and the operation area information.

(29) According to a third aspect, an implementation of embodiments of this disclosure provides an enhanced screen sharing method, applied to a second electronic device. The method includes the second electronic device that receives interface data of a first shared interface sent by a first electronic device, and displays, based on the interface data, a second shared interface corresponding to the first shared interface. The shared interface is an interface displayed by the first electronic device. The second electronic device enables an interconnection mode for the first electronic device. In the interconnection mode, the second electronic device detects a trigger operation performed by a user on the second shared interface, and determines event information corresponding to the trigger operation. The event information includes an event type and operation area information that correspond to the trigger operation. The second electronic device sends the event information to the first electronic device, to enable the first electronic device to perform a corresponding operation on the first electronic device based on the event information.

(30) The second electronic device may enable, by the detected trigger operation performed by the user on the second shared interface, the first electronic device to perform the corresponding operation on the first electronic device, so as to implement interconnection with the first electronic device. In this way, interaction with the first electronic device can be better implemented, thereby improving availability and user friendliness of the shared interface to improve user experience.

(31) According to a fourth aspect, an implementation of embodiments of this disclosure provides an enhanced screen sharing system, including a first electronic device and a second electronic device. The first electronic device is configured to display a first shared interface, and send interface data of the first shared interface to the second electronic device. The second electronic device is configured to receive the interface data, and display, based on the interface data, a second shared interface corresponding to the first shared interface. The second electronic device is further configured to enable an interconnection mode for the first electronic device. In the interconnection mode, the second electronic device is configured to, when detecting a trigger operation performed by a user on the second shared interface, determine event information corresponding to the trigger operation. The event information includes an event type and operation area information that correspond to the trigger operation. The second electronic device is further configured to send the event information to the first electronic device. The first electronic device is configured to receive the event information, and perform a corresponding operation on the first electronic device based on the event information.

(32) The enhanced screen sharing system provided in this implementation includes the first electronic device and the second electronic device that perform the foregoing enhanced screen sharing method. Therefore, an effect of the enhanced screen sharing method provided in the first aspect or the possible implementation of the first aspect can also be implemented.

- (33) According to a fifth aspect, an implementation of embodiments of this disclosure provides an electronic device, including a memory configured to store a computer program, where the computer program includes program instructions, and a processor configured to execute the program instructions, to enable the electronic device to perform the foregoing enhanced screen sharing method.
- (34) According to a sixth aspect, an implementation of embodiments of this disclosure provides a computer readable storage medium. The computer readable storage medium stores a computer program. The computer program includes program instructions. The program instructions are run by an electronic device, so that the electronic device performs the foregoing enhanced screen sharing method.
- (35) According to a seventh aspect, embodiments of this disclosure provide a computer program product. When the computer program product runs on an electronic product, the electronic product is enabled to perform the foregoing collaboration method between electronic devices.
- (36) It may be understood that, for beneficial effects of the second aspect to the seventh aspect, refer to related descriptions in the first aspect. Details are not described herein again.
-

Description

BRIEF DESCRIPTION OF DRAWINGS

- (1) To describe some of the technical solutions in embodiments of this disclosure more clearly, the following briefly describes accompanying drawings used for describing embodiments.
- (2) FIG. 1 is a schematic diagram of a communication system according to an embodiment of this disclosure;
- (3) FIG. 2 is a schematic diagram of a structure of a mobile phone according to an embodiment of this disclosure;
- (4) FIG. 3 is a block diagram of a software structure of a mobile phone according to an embodiment of this disclosure;
- (5) FIG. 4A, FIG. 4B, FIG. 4C, FIG. 4D, FIG. 4E, FIG. 4F, FIG. 4G, FIG. 4H, FIG. 4I, FIG. 4J, FIG. 4K, FIG. 4L, FIG. 4M, FIG. 4N, FIG. 4O, FIG. 4P, FIG. 4Q, FIG. 4R, FIG. 4S, and FIG. 4T are schematic diagrams of some interfaces of interaction between a mobile phone and another mobile phone according to an embodiment of this disclosure;
- (6) FIG. 5A, FIG. 5B, FIG. 5C, FIG. 5D, FIG. 5E, and FIG. 5F are schematic diagrams of some interfaces in a process of performing video play interconnection between a mobile phone and another mobile phone according to an embodiment of this disclosure;
- (7) FIG. 6A, FIG. 6B, FIG. 6C, and FIG. 6D are schematic diagrams of some interfaces in a process of performing music play interconnection between a mobile phone and another mobile phone according to an embodiment of this disclosure;
- (8) FIG. 7A, FIG. 7B, FIG. 7C, and FIG. 7D are schematic diagrams of some interfaces in a process of picture display interconnection between a mobile phone and another mobile phone according to an embodiment of this disclosure;
- (9) FIG. 8A, FIG. 8B, and FIG. 8C are schematic diagrams of other sharing controlling controls according to an embodiment of this disclosure;
- (10) FIG. 8D is a schematic diagram of an interface of performing a graffiti operation between a mobile phone and another mobile phone according to an embodiment of this disclosure;
- (11) FIG. 8E is a schematic drawing of mobile phones with split screen displays according to an embodiment of this disclosure;
- (12) FIG. 8F is a schematic drawing of mobile phones with multiple displays according to an embodiment of this disclosure;
- (13) FIG. 9 is a schematic diagram of an interface in a process of performing interconnection

between a mobile phone and a tablet computer according to an embodiment of this disclosure;
(14) FIG. 10A and FIG. 10B are a schematic diagram of a process of performing application download and installation interconnection between a mobile phone and another mobile phone according to an embodiment of this disclosure;

(15) FIG. 11A and FIG. 11B are a schematic diagram of a process of performing application opening interconnection between a mobile phone and another mobile phone according to an embodiment of this disclosure;

(16) FIG. 12 is a schematic diagram showing a structure of an electronic device according to some embodiments of this disclosure; and

(17) FIG. 13 is a schematic diagram showing a structure of a system on chip (SoC) according to some embodiments of this disclosure.

DESCRIPTION OF EMBODIMENTS

(18) The following further describes implementations of embodiments of this disclosure in detail with reference to accompanying drawings.

(19) Refer to FIG. 1. FIG. 1 is a schematic diagram of a communication system according to an embodiment of this disclosure.

(20) The communication system includes a mobile phone 100 and a mobile phone 200. In an implementation of embodiments of this disclosure, a video call application having a video calling function and a screen sharing function is installed in both the mobile phone 100 and the mobile phone 200. The video call application may log in by using account information and a password of a user, so as to implement interconnection between the mobile phone 100 and the mobile phone 200, and implement interaction by using the video calling function and the screen sharing function. For a specific login manner, refer to other approaches. This is not limited in embodiments of this disclosure.

(21) The communication system further includes a cloud server 300. The cloud server 300 is a server corresponding to a video call application. Communication such as video calling and screen sharing may be performed between the mobile phone 100 and the mobile phone 200 through the cloud server 300.

(22) A user of the mobile phone 100 is a user U1, and a user of the mobile phone 200 is a user U2.

(23) The user U1 opens the video call application in the mobile phone 100, and initiates a video call request to the user U2. If the user U2 accepts the video call request by operating the mobile phone 200, a video call may be made between the mobile phone 100 and the mobile phone 200.

(24) In a process of the video calling between the mobile phone 100 and the mobile phone 200, interfaces of the video call displayed by the mobile phone 100 and the mobile phone 200 may each provide more function controls, for example, a screen sharing control. If user U1 enables a screen sharing mode (which may alternatively be referred to as a screen sharing function, or an interface sharing mode) by the screen sharing control, and the user U2 operates the mobile phone 200 to accept a request for enabling the screen sharing mode, the mobile phone 100 may use a real-time interface of the mobile phone 100 as a first shared interface. In addition, the mobile phone 100 uses displayed content of the first shared interface as interface data, and sends the interface data to the mobile phone 200 in a form of a data stream (which may alternatively be referred to as a video data stream). The mobile phone 200 receives the interface data of the first shared interface, and displays, on a screen of the mobile phone based on the interface data, a second shared interface corresponding to the first shared interface, so that the mobile phone 100 shares screen content of the mobile phone 100 with the mobile phone 200. The mobile phone 100 serves as a screen sharing initiator device for screen sharing. The mobile phone 200 serves as a screen sharing recipient device for screen sharing.

(25) In the enhanced screen sharing method provided in embodiments of this disclosure, in a process of screen sharing between the mobile phone 100 and the mobile phone 200, interfaces of the mobile phone 100 and the mobile phone 200 may each provide more function controls, for

example, an interconnection control (which may alternatively be referred to as an interconnection switch). If the user U2 enables an interconnection mode (which may alternatively be referred to as an interconnection function) between the mobile phone **100** and the mobile phone **200** by the interconnection control displayed by the mobile phone **200**, in the interconnection mode, after the mobile phone **200** receives a trigger operation performed by the user U2 on the second shared interface displayed by the mobile phone **2000**. The mobile phone **200** sends event information corresponding to the trigger operation of the user U2 to the mobile phone **100**. The event information includes an event type and operation area information that correspond to the trigger operation of the user U2. The event type may be, for example, an input event such as a single-tap input event, a double-tap input event, a touch-and-hold input event, or a flicking input event. The operation area information may be position coordinate information of a user trigger position (for example, a coordinate of a position at which the user performs a single-tap operation).

(26) After receiving the event information sent by the mobile phone **200**, the mobile phone **100** may determine, based on the event information, an operation type of an operation that needs to be performed by the mobile phone **100**, and perform a corresponding operation. In this case, the mobile phone **100** performs the operation corresponding to the trigger operation of the user U2, so as to achieve an objective that the mobile phone **200** performs interconnection on the mobile phone **100**. That the mobile phone **200** performs interconnection on the mobile phone **100** means that the mobile phone **100** may perform, in the mobile phone **100** based on the event information sent by the mobile phone **200**, an operation corresponding to the event information. For example, if the mobile phone **200** detects an operation that the user U2 taps an application icon of an application in the second shared interface displayed by the mobile phone **200**, the mobile phone **100** performs, based on the received event information, a corresponding action and feedback such as opening the application. If the mobile phone **200** detects an operation that the user U2 double taps an application icon of an application in the second shared interface displayed by the mobile phone **200**, the mobile phone **100** performs, based on the received event information, a corresponding action and feedback such as application download and installation. If the mobile phone **200** detects an operation that the user U2 taps a control in the second shared interface displayed by the mobile phone **200**, the mobile phone **100** performs, based on the received event information, a corresponding action and feedback such as triggering the control.

(27) For example, the mobile phone **100** displays a first shared interface, and the mobile phone **200** displays a second shared interface corresponding to the first shared interface sent by the mobile phone **100**. If detecting a single-tap operation performed by the user U2 on the second shared interface displayed by the mobile phone **200**, the mobile phone **200** determines that an event type corresponding to the single-tap operation of the user U2 is a single-tap input event. The mobile phone **200** sends, as event information to the mobile phone **100**, the event type and a position coordinate information of a position at which the user U2 performs the single-tap operation. After receiving the event information, the mobile phone **100** determines, based on the event type, that an operation type corresponding to the single-tap input event is an operation object trigger operation. In this case, the mobile phone **100** determines, based on the position coordinate information, an operation object, corresponding to the position at which the user U2 performs the single-tap operation, on the first shared interface displayed by the mobile phone **100**, and performs an operation of triggering the operation object. For example, if the operation object is an application, an operation of opening the application is performed. If the operation object is a control in an application, an operation of triggering the control or the like is performed.

(28) If detecting a double-tap operation performed by the user U2 on the second shared interface displayed by the mobile phone **200**, the mobile phone **200** determines that an event type corresponding to the double-tap operation of the user U2 is a double-tap input event. The mobile phone **200** sends, as event information to the mobile phone **100**, the event type and a position coordinate information of a position at which the user U2 performs the double-tap operation. After

receiving the event information, the mobile phone **100** determines, based on the event type, that an operation type corresponding to the double-tap input event is an application determining operation. In this case, the mobile phone **100** determines, based on the position coordinate information, an application name of an application, corresponding to the position at which the user U2 performs the double-tap operation, on the first shared interface displayed by the mobile phone **100**. The mobile phone **100** sends the application name as event response information to the mobile phone **200**. After receiving the event response information, the mobile phone **200** determines, based on the application name, whether the corresponding application is installed in the mobile phone **200**. If the corresponding application is not installed, the mobile phone **200** directly downloads a corresponding application from an AppGallery application in the mobile phone **200** based on the application name, and completes application installation. If the corresponding application is already installed in the mobile phone **200**, the mobile phone **200** does not perform an application download and installation operation. Alternatively, the mobile phone **200** may display prompt information used to notify the user U2 that the corresponding application is currently installed in the mobile phone **200**.

(29) In addition, after determining the application name, the mobile phone **100** may further determine, based on the operation type “application determining operation”, that a corresponding operation that needs to be performed by the mobile phone **200** is application download and installation. In this case, the mobile phone **100** determines that after receiving the event response information, an operation type of the operation that needs to be performed by the mobile phone **200** is “application download and installation”. In addition, the mobile phone **100** generates event response information based on the application name and the operation type of the operation that needs to be performed by the mobile phone **200**. In other words, the event response information includes the application name and the operation type of the operation that needs to be performed by the mobile phone **200**. After receiving the event response information, the mobile phone **200** may conveniently determine, based on the operation type, that the application download and installation operation needs to be performed. In this case, the mobile phone **200** determines, based on the application name, whether the corresponding application is installed in the mobile phone **200**, and when the corresponding application is not installed, to download a corresponding application from the AppGallery application in the mobile phone **200**, and complete application installation.

(30) Certainly, the mobile phone **200** may alternatively interconnect with the mobile phone **100** based on another received trigger operation performed by the user U2 on the shared screen displayed by the mobile phone **200**, to enable the mobile phone **100** to perform another operation. In the enhanced screen sharing method provided in embodiments of this disclosure, a combination manner of an input event type (for example, a single-tap input event, a double-tap input event, or a touch-and-hold input event) and an operation object (for example, an interface control or an application) of the user may be set as required, to enable the mobile phone **100** performs a corresponding operation.

(31) For example, the foregoing single-tap operation may alternatively be a flicking operation. In other words, the input event is a flicking input event. If the mobile phone **200** detects an operation that the user U2 flicks an application icon of an application in the second shared interface displayed by the mobile phone **200**, the mobile phone **100** performs a corresponding action and feedback such as opening the application. The double-tap operation may alternatively be a touch-and-hold operation. In other words, the input event is a touch-and-hold input event. If the mobile phone **200** detects an operation that the user U2 touches and holds an application icon of an application in the second shared interface displayed by the mobile phone **200**, the mobile phone **100** performs a corresponding action and feedback such as application download and installation. Alternatively, the input event may alternatively be a three-tap input event. If the mobile phone **200** detects a three-tap operation performed by the user U2 on an application icon of an application in the second shared interface displayed by the mobile phone **200**, the mobile phone **100** performs a corresponding

action and feedback such as application uninstallation.

(32) In the enhanced screen sharing method provided in embodiments of this disclosure, the mobile phone **200** may implement interconnection with the mobile phone **100** by the trigger operation performed by the user U2 on the second shared interface, to implement an operation of downloading and installing, by the mobile phone **200**, an application corresponding to the application in the mobile phone **100**. Alternatively, the mobile phone **100** is interconnected to perform an operation such as operation object trigger. In this way, interaction with the mobile phone **100** can be better implemented, thereby improving availability and user friendliness of the shared interface are improved, to improve user experience.

(33) Refer to FIG. 2. FIG. 2 is a schematic diagram of a structure of a mobile phone according to an embodiment of this disclosure. The mobile phone may be the foregoing mobile phone **100**, and may alternatively be the mobile phone **200**.

(34) The mobile phone may include a processor **110**, an external memory interface **120**, an internal memory **121**, a Universal Serial Bus (USB) interface **130**, a charging management module **140**, a power management module **141**, a battery **142**, an antenna **1**, an antenna **2**, a mobile communication module **150**, a wireless communication module **160**, an audio module **170**, a speaker **170A**, a receiver **170B**, a microphone **170C**, a headset jack **170D**, a sensor module **180**, a key **190**, a motor **191**, an indicator **192**, a camera **193**, a display screen **194**, a subscriber identification module (SIM) card interface **195**, and the like. The sensor module **180** may include a pressure sensor **180A**, a gyro sensor **180B**, a barometric pressure sensor **180C**, a magnetic sensor **180D**, an acceleration sensor **180E**, a distance sensor **180F**, an optical proximity sensor **180G**, a fingerprint sensor **180H**, a temperature sensor **180J**, a touch sensor **180K**, an ambient optical sensor **180L**, a bone conduction sensor **180M**, and the like.

(35) It may be understood that the structure shown in embodiments of this disclosure does not constitute a limitation on the mobile phone. In some other implementations of embodiments of this disclosure, the mobile phone may include more or fewer components than those shown in the figure, or combine some components, or split some components, or have different component arrangements.

(36) The processor **110** may include one or more processing units, for example the processor **110** may include an application processor (AP), a modem processor, a graphics processing unit (GPU), an image signal processor (ISP), a controller, a video codec, a digital signal processor (DSP), a baseband processor, and the like. Different processing units may be independent components, or may be integrated into one or more processors.

(37) The processor may generate an operation control signal based on an instruction operation code and a time sequence signal to complete control of instruction fetching and instruction execution.

(38) A memory may be further disposed in the processor **110**, and is configured to store instructions and data. For example, the processor **110** is configured to enable the mobile phone to perform the enhanced screen sharing method provided in embodiments of this disclosure.

(39) A wireless communication function of the mobile phone may be implemented by the antenna **1**, the antenna **2**, the mobile communication module **150**, the wireless communication module **160**, the modem processor, the baseband processor, and the like.

(40) The mobile communication module **150** may provide a wireless communication function that is applied to the mobile phone, including second generation (2G)/third generation (3G)/fourth generation (4G)/fifth generation (5G).

(41) The wireless communication module **160** may provide a wireless communication solution that is applied to the mobile phone, including wireless local area network (WLAN) (for example, WI-FI network), BLUETOOTH (BT), and the like.

(42) In some embodiments, the antenna **1** of the mobile phone is coupled to the mobile communication module **150**, and the antenna **2** is coupled to the wireless communication module **160**, so that the mobile phone can communicate with a network and another device by a wireless

communication technology.

(43) The application processor outputs a sound signal through an audio device (which is not limited to the speaker **170A**, the receiver **170B**, and the like), or displays an image or a video through the display screen **194**.

(44) The mobile phone implements a display function by the GPU, the display screen **194**, the application processor, and the like. The GPU is a microprocessor for image processing, and is connected to the display screen **194** and the application processor. The GPU is configured to perform mathematical and geometric calculations for graphics rendering. The processor **110** may include one or more GPUs. The processor executes program instructions to generate or change display information.

(45) The display screen **194** is configured to display an image, a video, and the like. In some embodiments, the mobile phone may include one or N display screens **194**. N is a positive integer greater than 1.

(46) The mobile phone may implement a photographing function and a video calling function by the ISP, the camera **193**, the video codec, the GPU, the display screen **194**, the application processor, and the like. In some embodiments, the mobile phone may include one or N cameras **193**. N is a positive integer greater than 1. Further, the mobile phone includes at least one camera **193** that is located on a same side as the display screen **194**.

(47) The video codec is configured to compress or decompress a digital video. The mobile phone may support one or more video codecs. In this way, the mobile phone may play or record videos in multiple encoding formats, for example, Moving Picture Experts Group (MPEG) 1, MPEG2, MPEG3, and MPEG4. In addition, the mobile phone may implement encapsulation, playing, and the like of audio and video data and screen recording data.

(48) The mobile phone may implement an audio function by the audio module **170**, the speaker **170A**, the receiver **170B**, the microphone **170C**, the headset jack **170D**, the application processor, and the like, such as video calling and music playing.

(49) The audio module **170** is configured to convert digital audio information into an analog audio signal output, and is also configured to convert an analog audio input into a digital audio signal. The audio module **170** may be further configured to code and decode an audio signal. In some embodiments, the audio module **170** may be disposed in the processor **110**. Alternatively, some function modules of the audio module **170** may be disposed in the processor **110**.

(50) The speaker **170A**, also referred to as a “loudspeaker”, is configured to convert an audio electrical signal into a sound signal. The mobile phone can make video calls, listen to music, or listen to hands-free calls through speaker **170A**.

(51) The receiver **170B**, also referred to as an “earpiece”, is configured to convert an audio electrical signal into a sound signal. When the mobile phone answers a call or a voice information, the receiver **170B** may be placed close to a human ear to answer the voice.

(52) The microphone **170C**, also referred to as a “mike”, a “mic”, is configured to convert a sound signal into an electrical signal.

(53) The headset jack **170D** is configured to connect to a wired headset.

(54) The pressure sensor **180A** is configured to sense a pressure signal, and can convert the pressure signal into an electrical signal. In some embodiments, the pressure sensor **180A** may be disposed on the display screen **194**. When a touch operation (which may also be referred to as a trigger operation) is performed on the display screen **194**, the mobile phone detects intensity of the touch operation based on the pressure sensor **180A**. Alternatively, the mobile phone may calculate a touch position based on a detection signal of the pressure sensor **180A**.

(55) The touch sensor **180K** is also referred to as a “touch component”. The touch sensor **180K** may be disposed on the display screen **194**. The touch sensor **180K** and the display screen **194** form a touch panel (TP), also referred to as a “touchscreen”. The touch sensor **180K** is configured to detect a touch operation performed on or near the touch sensor. The touch sensor **180K** may

transfer the detected touch operation to the application processor to determine a touch event type. A visual output related to the touch operation may be provided by the display screen **194**. In some other embodiments, the touch sensor **180K** may alternatively be disposed on a surface of the mobile phone, and a position of the touch sensor is different from that of the display screen **194**.

(56) In embodiments of this disclosure, the mobile phone may detect a trigger operation of a user on the display screen **194** based on the pressure sensor **180A** and the touch sensor **180K**, may also detect a voice input of the user based on the receiver **170B**, and may detect a gesture input of the user based on the camera **193**. Alternatively, an input of the user is detected based on an input module such as another input keyboard. This is not limited in this embodiment.

(57) Refer to FIG. **3**. FIG. **3** is a block diagram of a software structure of a mobile phone according to an embodiment of this disclosure.

(58) In a layered architecture, software may be divided into several layers, and each of the layers has a clear function and task. Layers communicate with each other through software interfaces. In some embodiments, a system of the mobile phone is divided into three layers, an application program layer, an application program framework layer, and a kernel layer from top to bottom. In addition, the system further includes a software development kit (SDK).

(59) The kernel layer includes a sensor module and a touch panel. The sensor module may be, for example, the foregoing pressure sensor **180A**, and is configured to generate a trigger operation electronic signal based on a physical trigger operation (for example, a single-tap operation of a user) of the user on the touch panel. The trigger operation electronic signal may include single-tap input event information corresponding to the single-tap operation of the user. The trigger operation electronic signal may further include operation area information of a position at which the user performs the single-tap operation, for example, position coordinate information.

(60) The application program framework layer provides an application programming interface (API) and a programming framework for an application program at the application program layer. The application program framework layer includes some predefined functions.

(61) The application program framework layer includes an input event reading module, an input event distribution module, and a window management module. The input event reading module may be, for example, an InputReader. The input event distribution module may be, for example, an InputDispatcher. The window management module may be, for example, a window manager service (WMS).

(62) The InputReader is configured to receive an electronic signal of the trigger operation sent by the pressure sensor **180A**, continuously extract an event from an EventHub (not shown in the figure) through a thread cycle, and perform event translation to determine an input event, and encapsulate the input event and send the encapsulated input event to the InputDispatcher.

(63) The InputDispatcher stores information from all windows of the WMS. After receiving the input event from the InputReader, the InputDispatcher searches for a proper window in the stored windows to distribute the event. In embodiments of this disclosure, the InputDispatcher mainly distributes the input event to an InCallUI application (APP) at the application program layer when the mobile phone serves as a recipient, to trigger a further operation of the InCallUI APP.

(64) The WMS is configured to manage a window program. The WMS can obtain a size of a display screen of the mobile phone, and provide a window position. The inputdispatcher is enabled to correctly distribute the input event to a specified window.

(65) The application program layer may include a series of application programs, for example, include a video call interface application and a video call application. The video call interface application may be, for example, the InCallUI APP. The video call application may be, for example, a VoipService APP or an HwVoipService APP.

(66) The InCallUI APP is responsible for receiving the input event sent from the inputdispatcher, and identifying and determining the input event. In addition, when the mobile phone serves as an initiator device, the InCallUI APP is further responsible for validity of the input event and parsing

the application information of an application corresponding to the input event.

(67) An application interface provided by the InCallUI APP includes some function controls. The function controls are displayed in a form of a touch control on a screen, and may be displayed according to different scenarios in which the application is located. In embodiments of this disclosure, the function controls may include one or more of controls such as “video call”, “screen sharing”, “interconnecting”, and “graffiti”. Content of the function control displayed on the screen includes an icon and/or a text.

(68) For example, after a video call application is opened on the mobile phone and a video call application interface is displayed, a “video call” control is displayed on the mobile phone. If detecting a trigger operation performed by the user on the “video call” control, the mobile phone sets up a video call with a peer mobile phone.

(69) After setting up a video call, the mobile phone displays a “screen sharing” control. If detecting a trigger operation performed by the user on the “screen sharing” control, the mobile phone sends a current screen as a shared screen to the peer mobile phone, with which performs a video call, for display.

(70) After setting up screen sharing, the mobile phone displays an interconnection control. If the mobile phone detects a trigger operation performed by the user on the interconnection control, an interconnection mode is enabled between the mobile phone and the peer mobile phone that is in a video call and that performs screen sharing.

(71) The InCallUI APP is further responsible for displaying and adapting a communication interface. For example, the InCallUI APP includes an interface switching entry of the foregoing service functions such as video calling, screen sharing, and interconnecting, so as to display a corresponding interface.

(72) The HwVoipService APP is an application that supports a video call and screen sharing and that is provided in embodiments of this disclosure, and has a visualized user interface.

(73) An HwVoipService is responsible for service logic control, including providing implementations of functions such as providing an audio call, a video call, a device discovery, a message service, and a service function switchover. Its capabilities are encapsulated into a service API for use by the InCallUI APP.

(74) The HwVoipService APP is further responsible for interacting with the SDK.

(75) The SDK includes an SDK module, and the SDK module may be, for example, a CaasKit SDK. The CaasKit SDK is responsible for sending a signaling, parsing the signaling, and interacting with the application program layer.

(76) It should be noted that, the application program layer may further include application programs such as a Camera, a Gallery, a Phone, a Music, and a Video.

(77) The application program framework layer may further include an activity manager service (AMS), a VIEW system, a content provider, a telephony manager, a resource manager, and the like. In addition, a Multicast Source Discovery Protocol (MSDP), an awareness service, a multipath access service, and the like may also be included. This is not limited in embodiments of this disclosure.

(78) The AMS, the WMS, and the VIEW provide capability support for interconnection in embodiments of this disclosure. The AMS provides basic user interface (UX) interaction capability. The WMS is responsible for capability such as window area calculation and provides operation area information. The VIEW provides capability such as operation object monitoring. Based on a response or callback of a last application, the VIEW can capture operational behavior of a user, record an operation object, and provide information such as the operation object.

(79) The MSDP awareness service and the multipath access service are basic components of the existing audio call and video call. The kernel layer is based on the existing audio call and video call, and is the same as that in the other approaches. Details are not described herein again.

(80) The kernel layer is an underlying system. The underlying system further includes an

underlying display system configured to provide a display service. For example, the underlying system may further include a surface manager, a media library, and the like. The surface manager is configured to manage the display system and provides a blend of two-dimensional (2D) and three-dimensional (3D) layers for a plurality of application programs. The media library supports playing and recording of multiple commonly used audio and video formats, static image files, and the like. The media library supports multiple audio and video encoding formats, such as MPEG4, H.264, MPEG-1 Audio Layer III or MPEG-2 Audio Layer III (MP3), Advanced Audio Coding (AAC), Adaptive Multi-Rate (AMR), Joint Photographic Experts Group (JPEG), and Portable Network Graphics (PNG).

(81) The kernel layer is a layer between hardware and software. The kernel layer includes at least a display driver, a camera driver, an audio driver, and the like. This is not limited in embodiments of this disclosure. To be specific, the kernel layer mainly includes hard code and an MSDP virtualization device corresponding to the MSDP awareness service.

(82) An internal working process of the system, based on the software structure shown in FIG. 3, of the mobile phone **100** and the mobile phone **200** will be described in detail below.

(83) The following first describes an application scenario of the enhanced screen sharing method and an interaction process between devices.

(84) A process of setting up a video call between the mobile phone **100** and the mobile phone **200** is as follows.

(85) Refer to FIG. 4A. In an implementation of embodiments of this disclosure, each of the mobile phone **100** and the mobile phone **200** has only one physical screen, and respective home screens are displayed on the screens (as shown in FIG. 4A). Application names and application icons of applications such as an AppGallery application **A1**, a video call application **A2**, a video play application **A3**, and a music application **A4** are displayed on a home screen of the mobile phone **100**. Application names and application icons of applications such as an AppGallery application **A1** and a video call application **A2** are displayed on a home screen of the mobile phone **200**.

(86) Still refer to FIG. 4A. If the mobile phone **100** detects a single-tap operation performed by a user **U1** on the video call application **A2** on the mobile phone **100**, the video call application **A2** is opened on the mobile phone **100**, and the mobile phone **200** displays a contact selection interface shown in FIG. 4B.

(87) Still refer to FIG. 4B. If detecting a single-tap operation performed by the user **U1** on a video call control **10** corresponding to a “user **U2**” in the contact list, the mobile phone **100** does make a video call. The mobile phone **100** sends a video call request to the mobile phone **200**, a device corresponding to the user **U2**, to request to set up a video call.

(88) Still refer to FIG. 4B. After receiving the video call request sent by the mobile phone **100**, the mobile phone **200** displays prompt information **20** “you receive a video call request”. If detecting a single-tap operation performed by the user **U2** on an “accept” control, the mobile phone **200** sends a video call setup response to the mobile phone **100**.

(89) Refer to FIG. 4C. After the mobile phone **100** receives the video call setup response sent by the mobile phone **200**, a video call is set up between the mobile phone **100** and the mobile phone **200**. In addition, the mobile phone **100** and the mobile phone **200** each display a video call interface.

(90) The mobile phone **100** usually displays, by default, a video call image of the user **U1** (for example, a video call image shown in a female avatar) in an upper right corner of the screen, and displays a video call image of the user **U2** (for example, a video call image shown in a male avatar) in a main area of the screen. In addition, a “more” control **11**, a “switch camera” control, and a “hang up” control are displayed at a lower part of the screen of the mobile phone **100**. Certainly, the mobile phone **100** may alternatively display other controls.

(91) Correspondingly, the mobile phone **200** displays the video call image of the user **U2** in an upper right corner of the screen, and displays the video call image of the user **U1** in a main area of

the screen. In addition, a “more” control **21**, a “switch camera” control, and a “hang up” control are displayed at a lower part of the screen of the mobile phone **200**.

(92) A process of screen sharing between the mobile phone **100** and the mobile phone **200** is as follows.

(93) Refer to FIG. **4D**. If detecting a single-tap operation performed by the user **U1** on the “more” control **11**, the mobile phone **100** displays a “share screen” control **12**. If detecting a single-tap operation performed by the user **U1** on the “share screen” control **12**, the mobile phone **100** sends a screen sharing request to the mobile phone **200**.

(94) Still refer to FIG. **4D**. After receiving the screen sharing request sent by the mobile phone **100**, the mobile phone **200** displays prompt information **22** “another user is requesting to share screen with you”. If detecting a single-tap operation performed by the user **U2** on an “accept” control, the mobile phone **200** sends a response, to the mobile phone **100**, indicating that the screen sharing is agreed.

(95) In an implementation of this disclosure, a first shared interface and a second shared interface may be the same, and are collectively referred to as a shared interface.

(96) Refer to FIG. **4E**. After receiving the response that is sent by the mobile phone **200** and that indicates that the screen sharing is agreed, the mobile phone **100** enables a screen sharing mode for the mobile phone **200** to share the screen. The video call application **A2** in the mobile phone **100** is automatically switched to running in a background, and the mobile phone **100** displays the home screen of the mobile phone **100**. The mobile phone **100** sends the home screen interface of the mobile phone **100** as a shared interface to the mobile phone **200**. Correspondingly, the video call application **A2** in the mobile phone **200** is also automatically switched to running in the background, and the mobile phone **200** displays the shared interface sent by the mobile phone **100**.

(97) The mobile phone **100** serves as a screen sharing initiator, and the mobile phone **200** serves as a screen sharing recipient.

(98) In addition, the mobile phone **100** further displays an initiator side sharing controlling control **13**. In an implementation of embodiments of this disclosure, the initiator side sharing controlling control **13** includes sharing prompt information **130**, an interconnection control **131**, and a sharing exit control **132**.

(99) The sharing prompt information **130** includes screen sharing state prompt information “sharing” and duration information “00:00” for which the screen has been shared. The sharing duration information displays a corresponding value in real time based on a duration for which the screen has been shared between the mobile phone **100** and the mobile phone **200**. The mobile phone **100** may enable or disable an interconnection mode between the mobile phone **100** and the mobile phone **200** based on a detected single-tap operation performed by the user **U1** on the interconnection control **131**. The mobile phone **100** may exit the screen sharing mode and the interconnection mode between the mobile phone **100** and the mobile phone **200** based on a detected single-tap operation performed by the user **U1** on the sharing exit control **132**. After the mobile phone **100** and the mobile phone **200** exit the screen sharing mode, the mobile phone **100** and the mobile phone **200** may display the video call interface shown in FIG. **4C**.

(100) In addition, the interface of the mobile phone **200** displays a recipient side sharing controlling control **23**. The recipient side sharing controlling control **23** includes sharing prompt information **230**, an interconnection control **231**, and a sharing exit control **232**.

(101) The sharing prompt information **230** includes sharing state prompt information “another user in sharing” and duration information “00:00” for which the screen has been shared. The sharing duration information displays a corresponding value in real time based on a duration of screen sharing between the mobile phone **100** and the mobile phone **200**. The mobile phone **200** may enable or disable the interconnection mode between the mobile phone **100** and the mobile phone **200** based on a detected single-tap operation performed by the user **U2** on the interconnection control **231**. The mobile phone **200** may exit the screen sharing mode and the interconnection mode

between the mobile phone **100** and the mobile phone **200** based on a detected single-tap operation performed by the user **U2** on the sharing exit control **232**.

(102) It should be noted that, trigger states of the initiator side sharing controlling control **13** of the mobile phone **100** and the recipient side sharing controlling control **23** of the mobile phone **200** are synchronized with each other. To be specific, either of the mobile phone **100** and the mobile phone **200** may start and end the interconnection mode based on a tap operation performed by a corresponding user on the control. For example, if the mobile phone **100** detects the single-tap operation performed by the user **U1** on the interconnection control **131**, the interconnection mode is enabled between the mobile phone **100** and the mobile phone **200**. Then, if the mobile phone **200** detects the single-tap operation performed by the user **U2** on the interconnection control **231**, the interconnection mode is disabled between the mobile phone **100** and the mobile phone **200**, and the mobile phone **200** ends interconnection for the mobile phone **100**.

(103) Refer to FIG. **4F**. In an implementation of embodiments of this disclosure, if detecting the single-tap operation performed by the user **U2** on the interconnection control **231**, the mobile phone **200** sends an interconnection request to the mobile phone **100**. After receiving the interconnection request, the mobile phone **100** displays prompt information **14** “another user requests for interconnection”. If detecting a single-tap operation performed by the user **U1** on the “OK” control that serves as the interconnection determining control, the mobile phone **100** sends a response, to the mobile phone **200**, indicating that the interconnection is agreed.

(104) After the mobile phone **200** receives the response, sent by the mobile phone **100**, indicating that the interconnection is agreed, the interconnection mode is enabled between the mobile phone **100** and the mobile phone **200**.

(105) Refer to FIG. **4G** and FIG. **4H**. After the interconnection mode is enabled between the mobile phone **100** and the mobile phone **200**, the interconnection control **131** of the mobile phone **100** may display a text “interconnected”, to remind the user **U1** that the interconnection mode has been enabled between the mobile phone **100** and the mobile phone **200** currently.

(106) If detecting the single-tap operation performed by the user **U2** on the interconnection control **231** for the first time, the mobile phone **200** displays interconnection operation prompt information.

(107) Still refer to FIG. **4G** and FIG. **4H**. The interconnection operation prompt information displayed by the mobile phone **200** includes operation introduction graphic information **24**, description information **25**, and a confirmation control **26**. The operation introduction graphic information **24** includes a plurality of schematic areas, and indicates that the user may complete corresponding interconnection on the mobile phone **100** by single tapping a corresponding area. The description information **25** is “double tap the shared screen to trigger installation of a specific initiator application, single tap the shared screen to trigger an initiator operation”. The confirmation control **26** may display “OK”.

(108) The interconnection operation prompt information may also include only the operation introduction graphic information **24** and the confirmation control **26**, or include only the description information **25** and the confirmation control **26**. Certainly, the interconnection operation prompt information may alternatively be other information used to explain a function of the interconnection mode to the user.

(109) If detecting a single-tap operation performed by the user on the confirmation control **26**, the mobile phone **200** displays an interface shown in FIG. **4J**. The interconnection control **231** also displays a text “interconnected”, to remind the user **U2** that the mobile phone **200** and the mobile phone **100** are currently in the interconnection mode.

(110) If detecting the single-tap operation performed by the user **U2** on the interconnection control **231** not for the first time (for example, for the second time or the third time), the mobile phone **200** may display the interface shown in FIG. **4J**. To be specific, the interconnection control **231** directly displays the text “interconnected” without displaying an operation description interface shown in FIG. **4H**.

(111) In embodiments of this disclosure, the mobile phone **200** may display the interconnection operation prompt information when detecting, for the first time, the single-tap operation performed by the user **U2** on the interconnection control **231**, to remind the user how to perform an interconnection operation between the mobile phone **200** and the mobile phone **100**. This can effectively improve user experience. Certainly, the mobile phone **200** may also periodically display interconnection operation prompt information, or display the interconnection operation prompt information based on another requirement or a trigger operation of the user.

(112) Still refer to FIG. **4I** and FIG. **4J**. If detecting a double-tap operation performed by the user **U2** on the application icon or the application name of the video play application **A3** on the shared interface, the mobile phone **200** determines that an event type input by the user is a double-tap input event. The mobile phone **200** generates the event information based on a position coordinate information and the event type of the position at which the user **U2** performs the double-tap operation. In other words, the event information includes the event type (a double-tap input) and the position coordinate information at which the user performs the double-tap operation. The mobile phone **200** sends the event information to the mobile phone **100**.

(113) After receiving the event information, the mobile phone **100** determines, based on the event type, that an operation type of an operation that needs to be performed by the mobile phone **100** is an application determining operation. Then, the mobile phone **100** determines, based on the position coordinate information, an application name “video play application **A3**” of an application corresponding to the position at which the user **U2** performs the double-tap operation on the shared interface. In addition, the mobile phone **100** determines, based on the operation type, that after the mobile phone **200** receives event response information, a type of an operation that needs to be performed is an application download and installation operation. In this case, the mobile phone **100** sends the application name “video play application **A3**” and the operation type “application download and installation” as event response information to the mobile phone **200**.

(114) After receiving the event response information sent by the mobile phone **100**, the mobile phone **200** determines, based on the operation type and the application name, that the video play application **A3** needs to be downloaded and installed. The mobile phone **200** further determines whether the video play application **A3** is currently installed in the mobile phone **200**.

(115) If the video play application **A3** is already installed in the mobile phone **200**, the mobile phone **200** does not perform an operation of downloading and installing the video play application **A3**. Alternatively, the mobile phone **200** may display prompt information “video play application **A3** is currently installed, please confirm” (not shown in the figure), to notify the user **U2** that the video play application **A3** is currently installed in the mobile phone **200**.

(116) If the video play application **A3** is not installed in the mobile phone **200**, the mobile phone **200** searches for and downloads a corresponding video play application **A3** from the AppGallery application **A1** in the mobile phone **200**, and completes installation of the video play application **A3**.

(117) Refer to FIG. **4K** and FIG. **4L**. After completing the installation of the video play application **A3**, the mobile phone **200** may display prompt information **27** “video play application **A3** is successfully installed”, so as to remind the user **U2**. Certainly, in a process of downloading an application by the mobile phone **200**, the prompt information **27** may display “application is being downloaded” or the like, so as to remind the user **U2**. This may be set as required.

(118) Still refer to FIG. **4K** and FIG. **4L**. After the video play application **A3** is installed in the mobile phone **200**, if the mobile phone **200** detects a single-tap operation performed by the user **U2** on the sharing exit control **232**, the mobile phone **200** and the mobile phone **100** end the interconnection mode and the screen sharing mode, and exit the shared interface.

(119) Refer to FIG. **4M**. After ending the interconnection mode and the screen sharing mode with the mobile phone **100**, the mobile phone **200** may directly display the home screen of the mobile phone **200**. In this case, the home screen includes the application icon and the application name of

the video play application A3 installed in the mobile phone 200. In addition, an upper right of the screen of the mobile phone 200 may further display the video call image of the user U1.

(120) In addition, after ending the interconnection mode and the screen sharing mode, the mobile phone 100 displays the home screen of the mobile phone 100. In addition, the mobile phone 100 may further display the video call image of the user U2 on an upper right of the screen.

(121) In this implementation, the interconnection mode is enabled between the mobile phone 200 and the mobile phone 100. The mobile phone 200 may perform interconnection with the mobile phone 100 by a received double-tap operation performed by the user U2 on an application on the shared interface, and obtain an application name of the application by the mobile phone 100. In addition, an application corresponding to a position at which the user performs the double-tap operation is conveniently installed. This enriches interaction types between the mobile phone 200 and the mobile phone 100, and improves user experience.

(122) In another implementation of embodiments of this disclosure, the mobile phone 100 and the mobile phone 200 enable the interconnection mode. After the interface shown in FIG. 4E is displayed, if detecting the single-tap operation performed by the user U2 on the interconnection control 231, the mobile phone 200 may alternatively not need to send an interconnection request to the mobile phone 100. The interconnection mode may be automatically and directly enabled between the mobile phone 200 and the mobile phone 100, and the interface shown in FIG. 4H is displayed.

(123) In another implementation of embodiments of this disclosure, in a process in which the mobile phone 200 searches for, downloads, and installs the video call application A3, the mobile phone 200 may not display the prompt information 27 shown in FIG. 4L. This may be set as required.

(124) It should be noted that, the AppGallery applications respectively installed in the mobile phone 100 and the mobile phone 200 may be a same AppGallery application A1, or may be different applications that provide an application download function.

(125) Refer to FIG. 4N and FIG. 4O. In another implementation of embodiments of this disclosure, if the mobile phone 200 enables the interconnection mode with the mobile phone 100 and if the mobile phone 200 detects again the single-tap operation performed by the user on the interconnection control 231, the mobile phone 200 and the mobile phone 100 exit the interconnection mode.

(126) Refer to FIG. 4P. After the mobile phone 200 and the mobile phone 100 exit the interconnection mode, the mobile phone 100 may display the home screen, and the mobile phone 200 displays the shared interface. In addition, the text “interconnected” is not displayed on neither the interconnection control 131 nor the interconnection control 231, so as to remind the user that the mobile phone 100 and the mobile phone 200 are not in the interconnection mode currently.

(127) Refer to FIG. 4Q and FIG. 4R. In another implementation of embodiments of this disclosure, in a process of setting up a video call between the mobile phone 100 and the mobile phone 200, when sharing the screen with the mobile phone 200, the mobile phone 100 may continue to display a video call interface. The video call interface further includes a call interface zoom-out control 15. In addition, the mobile phone 100 sends the video call interface as a shared interface to the mobile phone 200. The mobile phone 200 displays the shared interface shared by the mobile phone 100.

(128) If the interconnection mode is enabled between the mobile phone 100 and the mobile phone 200, and the mobile phone 200 detects a single-tap operation performed by the user U2 on the call interface zoom-out control 15 on the shared interface displayed by the mobile phone 200, the mobile phone 200 determines that an event type corresponding to the single-tap operation of the user U2 is a single-tap input event. The mobile phone 200 sends, as event information to the mobile phone 100, position coordinate information and the event type of a position at which the user U2 performs the single-tap operation.

(129) After receiving the event information, the mobile phone 100 determines, based on the event

type, that an operation type is an operation object trigger operation. In this case, the mobile phone **100** determines, based on the position coordinate information, that an operation object, corresponding to the position of the single-tap operation performed by the user U2, on the shared interface is the call interface zoom-out control **15**. In this case, the mobile phone **100** performs an operation of triggering the call interface zoom-out control **15**, in other words, performs a call interface zoom-out operation, and displays an interface shown in FIG. 4S.

(130) In another implementation of this disclosure, if the mobile phone **200** and the mobile phone **100** end the interconnection operation mode and the screen sharing mode, after exiting the shared interface, the mobile phone **200** and the mobile phone **100** may each display the video call interface shown in FIG. 4C.

(131) A scenario and a process of video play interconnection between the mobile phone **100** and the mobile phone **200** are as follows.

(132) Refer to FIG. 5A and FIG. 5B. The mobile phone **100** and the mobile phone **200** enable a screen sharing mode and an interconnection mode. If detecting a single-tap operation performed by the user U2 on the video play application A3, the mobile phone **200** determines that an event type corresponding to the single-tap operation of the user U2 is a single-tap input event. The mobile phone **200** sends, as event information to the mobile phone **100**, position coordinate information and the event type of a position at which the user U2 performs the single-tap operation.

(133) After receiving the event information, the mobile phone **100** determines, based on the event type, that an operation type is an operation object trigger operation. In addition, the mobile phone **100** determines, based on the position coordinate information, that an operation object, corresponding to the position at which the user U2 performs the single-tap operation, on the shared interface is the video play application A3. The mobile phone **100** performs an operation of opening the video play application A3, and displays a video application interface shown in FIG. 5C.

(134) If detecting a single-tap operation performed by the user on a “video 1”, the mobile phone **200** determines that an event type corresponding to the single-tap operation of the user U2 is a single-tap input event. The mobile phone **200** sends, as event information to the mobile phone **100**, position coordinate information and the event type of a position at which the user U2 performs the single-tap operation.

(135) After receiving the event information, the mobile phone **100** determines, based on the event type, that an operation type is an operation object trigger operation. In addition, the mobile phone **100** determines, based on the position coordinate information, that an operation object, corresponding to the position at which the user U2 performs the single-tap operation, on the shared interface is the “video 1”. The mobile phone **100** performs an operation of opening the “video 1”, and displays a video play interface shown in FIG. 5E.

(136) A scenario and a process of music play interconnection between the mobile phone **100** and the mobile phone **200** are as follows.

(137) Refer to FIG. 6A and FIG. 6B. The mobile phone **100** and the mobile phone **200** enable a screen sharing mode and an interconnection mode. The mobile phone **100** displays an application interface of the music application A3. If detecting a single-tap operation performed by the user U2 on a “song 3”, the mobile phone **200** determines that an event type corresponding to the single-tap operation of the user U2 is a single-tap input event. The mobile phone **200** sends, as event information to the mobile phone **100**, position coordinate information and the event type of a position at which the user U2 performs the single-tap operation.

(138) After receiving the event information, the mobile phone **100** determines, based on the event type, that an operation type is an operation object trigger operation. In addition, the mobile phone **100** determines, based on the position coordinate information, that an operation object, corresponding to the position at which the user U2 performs the single-tap operation, on the shared interface is the “song 3”. The mobile phone **100** performs an operation of playing the “song 3”, and displays a video play interface shown in FIG. 6C.

(139) A scenario and a process of picture browsing interconnection between the mobile phone **100** and the mobile phone **200** are as follows.

(140) Refer to FIG. 7A and FIG. 7B. The mobile phone **100** and the mobile phone **200** enable a screen sharing mode and an interconnection mode. The mobile phone **100** displays a picture in an album application. If the mobile phone **200** detects a pinch-out operation performed by the user U2 on the picture (during which two fingers of the user being extended is the pinch-out operation, which may alternatively be referred to as an unpinch operation, and two fingers of the user being pinched is a pinch-in operation), the mobile phone **200** determines that an event type corresponding to the pinch-out operation of the user U2 is a pinch-out input event. The mobile phone **200** sends, as event information to the mobile phone **100**, initial position coordinate information, end position coordinate information, and the event type of a position at which the user U2 performs the pinch-out operation. In an example in which two fingers of the user are extended, initial position coordinate and end position coordinate of each finger are different. In this case, the mobile phone **200** draws a flicking trace of the two fingers of the user, determines the initial position coordinate and end position coordinate of each finger as position coordinate information to be mapped to the mobile phone **100** by using event information.

(141) After receiving the event information, the mobile phone **100** determines, based on the event type, that an operation type is an operation object trigger operation. In this case, the mobile phone **100** determines a pinch-out scale of the picture based on the initial position coordinate information and the end position coordinate information, performs a picture pinch-out operation, and displays a picture display interface shown in FIG. 7C.

(142) Refer to FIG. 8A and FIG. 8B. In another implementation of embodiments of this disclosure, after the interconnection mode is enabled between the mobile phone **100** and the mobile phone **200**, the initiator side sharing controlling control **13** of the mobile phone **100** serving as an initiator device may also include only the sharing prompt information **130** and the sharing exit control **132**, and does not include the foregoing interconnection control **131**. The recipient side sharing controlling control **23** of the mobile phone **200** serving as the recipient device may include the interconnection control **231**. In other words, in this implementation, enabling and disabling of the interconnection mode between the mobile phone **200** and the mobile phone **100** can be triggered only by the interconnection control **231**.

(143) Refer to FIG. 8C. In another implementation of embodiments of this disclosure, an icon of the interconnection control **131** in the initiator side sharing controlling control **13** may also be shown in FIG. 8C. In addition, the interconnection control **131** may remind the user of enabling or disabling the interconnection mode by changing a shape and a format of the icon, changing a color, or the like.

(144) In addition, in another implementation of embodiments of this disclosure, the initiator side sharing controlling control **13** may further include a graffiti control **133**, to enable the user U1 to perform a graffiti operation on the shared screen by the graffiti control **133**.

(145) Correspondingly, the recipient side sharing controlling control **23** in the mobile phone **200** may also be shown in FIG. 8C. Details are not described herein again.

(146) Refer to FIG. 8D. After receiving a graffiti operation performed by the user U1 on the “AppGallery application A1”, the mobile phone **100** displays an oval graffiti mark shown in the figure. Correspondingly, the mobile phone **200** also displays a corresponding graffiti mark. In addition, after receiving the graffiti operation performed by the user U2 on the “music application A4”, the mobile phone **200** displays a square graffiti mark shown in the figure. Correspondingly, the mobile phone **100** also displays a corresponding graffiti mark.

(147) In some other implementations of embodiments of this disclosure, the initiator side sharing controlling control **13** and the recipient side sharing controlling control **23** may alternatively be controls of another type or format such as a side toolbar, and may be set as required.

(148) In some other implementations of embodiments of this disclosure, the mobile phone **100** may

alternatively enable the interconnection mode when performing screen sharing corresponding to a scenario such as a voice call, remote assistance, or device collaboration with the mobile phone **200**. (149) It should be noted that, in embodiments of this disclosure, screen resolutions of the mobile phone **100** and the mobile phone **200** may be the same, or may be different. If screen resolutions of the mobile phone **100** and the mobile phone **200** are the same, the mobile phone **200** directly sends the obtained position coordinate information to the mobile phone **100**. If the screen resolutions of the mobile phone **100** and the mobile phone **200** are different, the mobile phone **200** may perform coordinate conversion on the obtained position coordinate information based on a correspondence between the resolutions of the mobile phone **200** and the mobile phone **100**, and send the converted position coordinate information to the mobile phone **100**. Alternatively, the mobile phone **200** directly sends the obtained position coordinate information to the mobile phone **100**. The mobile phone **100** performs coordinate conversion on the obtained position coordinate information based on a correspondence between the resolutions of the mobile phone **200** and the mobile phone **100**, and then performs the foregoing operations such as determining an application and determining an operation object.

(150) In some other implementations of embodiments of this disclosure, bidirectional screen sharing may be performed between the mobile phone **100** and the mobile phone **200**. In other words, the mobile phone **100** sends the screen of the mobile phone **100** as the first shared screen to the mobile phone **200** for display. The mobile phone **200** also sends the screen of the mobile phone **200** as the second shared screen to the mobile phone **200** for display.

(151) As shown in FIG. **8E**, if the mobile phone **100** and the mobile phone **200** are devices each having only one physical screen, such as physical display **800** of mobile phone **100**, which includes a first and second portions **802** and **804**, and physical display **801** of mobile phone **200**, which includes a first and second portions **806** and **808**, when the bidirectional screen sharing is performed between the mobile phone **100** and the mobile phone **200**, the mobile phone **100** and the mobile phone **200** separately perform screen splitting operations. In addition, a screen area after the screen splitting may be selected to display an interface of the user, such as interfaces **810** and **812** displayed in the first portions **802** and **806** of mobile phones **100** and **200**, respectively, and a shared interface shared by another user may be displayed in another screen area, such as interfaces **812** and **810** displayed in the second portions **804** and **808** of mobile phones **100** and **200**, respectively.

(152) As shown in FIG. **8F**, if the mobile phone **100** and the mobile phone **200** are devices each having two or more physical screens, such as physical displays **852** and **854** of mobile phone **100** and physical displays **856** and **858** of mobile phone **200**, when the bidirectional screen sharing is performed between the mobile phone **100** and the mobile phone **200**, the mobile phone **100** and the mobile phone **200** each select one physical screen to display their own interfaces, such as interfaces **860** and **862** of mobile phones **100** and **200**, respectively. Another physical screen displays a shared interface shared by another, such as interfaces **862** displayed on mobile phone **100** and **860** displayed on mobile phone **200** respectively.

(153) After the mobile phone **100** and the mobile phone **200** perform the bidirectional screen sharing, the mobile phone **100** may perform an interconnection operation on the screen of the mobile phone **200**, and the mobile phone **200** may perform an interconnection operation on the screen of the mobile phone **100**. In this way, a bidirectional interconnection between the mobile phone **100** and the mobile phone **200** is implemented.

(154) Refer to FIG. **9**. In another implementation of embodiments of this disclosure, the mobile phone **100** may alternatively set up a video call with a tablet computer **300**, and enable a screen sharing mode and an interconnection mode. A screen resolution of the tablet computer **300** is different from a screen resolution of the mobile phone **100**. When determining event information, the tablet computer **300** may determine a coordinate adjustment parameter based on a ratio of the screen resolution F1 of the mobile phone **100** to the screen resolution F3 of the tablet computer

300, and adjust, based on the coordinate adjustment parameter, initial position coordinate information obtained by the tablet computer **300**, to obtain position coordinate information. Then, the tablet computer **300** sends, to the mobile phone **100**, the event information that includes the position coordinate information obtained through adjustment, to enable the mobile phone **100** to accurately determine an application or a control, corresponding to the position coordinate information, on the shared screen displayed by the mobile phone **100**.

(155) For example, $Z1 = Sa \times Z0$. $Z0$ is an initial position coordinate, for example, $(x.sub.0, y.sub.0)$. Sa is a coordinate adjustment parameter, and $Z1$ is a position coordinate obtained after adjustment.

(156) In this implementation, $F1$ is $(F11 \times F12)$. $F11$ is a quantity of pixels of a screen of the mobile phone **100** in a horizontal direction (which may alternatively be referred to as a screen width direction, or an x-axis direction). $F12$ is a quantity of pixels of the screen of the mobile phone **100** in a vertical direction (which may alternatively be referred to as a screen length direction, or a y-axis direction). $F3$ is $(F31 \times F32)$. $F31$ is a quantity of pixels of a screen of the tablet computer **300** in the horizontal direction (which may alternatively be referred to as the screen width direction, or the x-axis direction). $F32$ is a quantity of pixels of the screen of the tablet computer **300** in the vertical direction (which may alternatively be referred to as the screen length direction, or the y-axis direction).

(157) In this case, the coordinate adjustment parameter Sa is $(S.sub.x1, S.sub.y1)$, where $S.sub.x1 = F11/F31$, and $S.sub.y1 = F12/F32$.

(158) The position coordinates $Z1$ obtained after the adjustment may be $(S.sub.x1 \times x.sub.0, S.sub.y1 \times y.sub.0)$.

(159) Certainly, the mobile phone **100** may alternatively enable a sharing mode and an interconnection mode with another mobile phone (for example, a large-screen mobile phone and a small-screen mobile phone) having a screen resolution different from the screen resolution of the mobile phone **100**. Alternatively, the mobile phone **100** may set up a video call with another device that has a screen display function, such as a television, and enable a screen sharing mode and an interconnection mode.

(160) Embodiments of this disclosure relate to an enhanced screen sharing method applied to an electronic device. The electronic device may be a mobile phone, a tablet computer, a television, a notebook computer, an ultra-mobile personal computer (UMPC), a handheld computer, a netbook, a personal digital assistant (PDA), a wearable device, a virtual reality device, or the like.

(161) It should be noted that, in embodiments of this disclosure, the electronic device is an electronic device that can perform wireless communication with another electronic device. The electronic device has a screen, and the electronic device has a video call function, a screen sharing function, and an interconnection function.

(162) The following describes in detail the internal working process of the system, based on the foregoing software structure shown in FIG. 3, of the mobile phone **100** and the mobile phone **200**.

(163) In an enhanced screen sharing method provided in embodiments of this disclosure, a video call is made between the mobile phone **100** and the mobile phone **200**, and screen sharing is performed. After the interconnection mode is enabled between the mobile phone **100** and the mobile phone **200**, the mobile phone **200** may perform application download and installation.

(164) Refer to FIG. 10A and FIG. 10B. The mobile phone **100** includes a video call application **A2** and an SDK module **105**. The mobile phone **200** includes a sensor module **201**, an input event reading module **202**, an input event distribution module **203**, a video call interface application **204**, a video call application **A2**, and an SDK module **205**.

(165) A process of performing application download interconnection between the mobile phone **100** and the mobile phone **200** includes the following steps.

(166) **S101**: The sensor module **201** in the mobile phone **200** sends detected double-tap operation information corresponding to a double-tap operation of the user **U2** to the input event reading module **202** in the mobile phone **200**.

(167) It should be noted that, if a trigger operation of the user U2 is a double-tap operation, after detecting a first single-tap operation of the user U2, the sensor module **201** sends first single-tap operation information corresponding to the first single-tap operation to the input event reading module **202**. After detecting a second single-tap operation of the user U2, the sensor module **201** sends second single-tap operation information corresponding to the second single-tap operation to the input event reading module **202**.

(168) The single-tap operation information may be a trigger operation electronic signal, and includes an input event type corresponding to the trigger operation of the user U2 and position coordinate information of a position at which the user U2 single taps. For example, an event type corresponding to the single-tap operation of the user U2 is a “single-tap input event”.

(169) **S102**: After receiving the first single-tap operation information and the second single-tap operation information, the input event reading module **202** determines that a time interval between receiving the first single-tap operation information and the second single-tap operation information is less than a preset double-tap operation determining time threshold. The input event reading module **202** extracts an event from an EventHub through a thread to perform event translation, and may determine that an input event corresponding to an operation of the user U2 is a double-tap input event. The input event reading module **202** sends, as event information to the input event distribution module **203**, the double-tap input event and position coordinate information of a position at which the user U2 double taps.

(170) A value range of the double-tap operation determining time threshold may be, for example, 0.1 seconds(s) to 0.6 s, for example, 0.1 s, 0.25 s, 0.5 s, or 0.6 s. Certainly, the double-tap operation determining time threshold may alternatively be another value.

(171) **S103**: The input event distribution module **203** distributes the event based on the received event information, and sends the event information to the video call interface application **204**.

(172) **S104**: The video call interface application **204** transfers the event information of the double-tap input event to the video call application A2.

(173) **S105**: The video call application A2 determines a time interval between the two single-taps in the event information of the double-tap input event, so as to achieve an objective of event identification and event effectiveness analysis. If the video call application A2 determines that the interval between the two single-taps in the event information of the double-tap input event is less than the preset double-tap operation determining time threshold, the video call application A2 determines that the input event is a double-tap input event.

(174) **S106**: The video call application A2 invokes the SDK module **205** to deliver the event information.

(175) **S107**: The SDK module **205** sends the event information to the SDK module **105** in the mobile phone **100**. The event information includes an event type “double-tap input event” and operation area information “position coordinate information of the position at which the user double taps”.

(176) The SDK module **205** may send the event information in a signaling manner through a signaling transmission channel established between the mobile phone **200** and the mobile phone **100**.

(177) It should be noted that, the SDK module **205** in the mobile phone **200** may first send event response information to a cloud server **300** corresponding to the video call application A2. Then, the cloud server **300** sends the event response information to the SDK module **105** in the mobile phone **100**.

(178) **S108**: The SDK module **105** parses the event information to obtain the event type “double-tap input event” and the operation area information “position coordinate information of the position at which the user double taps”.

(179) **S109**: The SDK module **105** sends the parsed event information to the video call application A2. To be specific, the event type “double-tap input event” and the operation area information

“position coordinate information of the position at which the user double taps” are sent to the video call application A2.

(180) **S110**: The video call application A2 may first determine, based on the event type “double-tap input event”, that the mobile phone **100** needs to perform an application determining operation. Then, the video call application A2 determines, based on the operation area information “position coordinate information of the position at which the user double taps”, whether the position coordinate information is valid, for example, whether a current interface of the mobile phone **100** includes an application icon and/or an application name of the application. If a current interface of the mobile phone **100** includes an application icon and/or an application name of the application, the video call application A2 determines whether the position at which the user double taps is at a position at which an on-screen application icon and/or the application name is located. If the position at which the user double taps is at a position at which an on-screen application icon and/or the application name is located, it is considered that the position coordinate information is valid. The video call application A2 determines, based on the operation area information “position coordinate information of the position at which the user double taps”, a corresponding area on an interface of the mobile phone **100**, and determines an application name of an application corresponding to the area, for example, a video play application A3. In addition, the video call application A2 determines that after receiving the name, a corresponding operation type that needs to be performed by the mobile phone **200** is “application download and installation”.

(181) **S111**: The video call application A2 invokes the SDK module **105** to return the event response information. The event response information includes the operation type “application download and installation” and an application name “video play application A3”.

(182) **S112**: The SDK module **105** sends the event response information to the SDK module **205** in the mobile phone **200**.

(183) The SDK module **105** may send the event information in a signaling manner through the signaling transmission channel established between the mobile phone **100** and the mobile phone **200**.

(184) It should be noted that, the SDK module **105** in the mobile phone **100** may first send the event response information to the cloud server **300** corresponding to the video call application A2. Then, the cloud server **300** sends the event response information to the SDK module **105** in the mobile phone **200**.

(185) **S113**: The SDK module **105** parses the event response information to obtain the operation type and the application name.

(186) **S114**: The SDK module **105** sends the parsed event response information to the video call application A2. To be specific, the SDK module **105** sends the operation type and the application name to the video call application A2.

(187) **S115**: The video call application A2 determines, based on the operation type “application download and installation”, that an application download and installation operation needs to be performed. The video call application A2 determines, based on the application name “video play application A3”, that an application that needs to be downloaded is the video play application A3. In this case, the video call application A2 first determines, based on the application name “video play application A3”, whether the video play application A3 is installed in the mobile phone **200**. If the video play application A3 is not installed, the video call application A2 directly downloads the video play application A3 from an AppGallery application A1 in the mobile phone **200** based on the application name, and completes application installation. If the video play application A3 is already installed in the mobile phone **200**, the mobile phone **200** does not perform the application download and installation operation. Alternatively, the mobile phone **200** may display prompt information used to notify the user U2 that the video play application A3 is currently installed in the mobile phone **200**.

(188) In the enhanced screen sharing method provided in this embodiment, in a process of screen

sharing between the mobile phone **200** and the mobile phone **100**, after the interconnection mode of the mobile phone **200** to the mobile phone **100** is enabled, the mobile phone **200** may download a corresponding application in the mobile phone **100** based on the trigger operation performed by the user U2 on the mobile phone **200**. An interaction type between the mobile phone **100** and the mobile phone **200** that perform screen sharing can be enriched, and user experience can be improved.

(189) In another implementation of embodiments, for the foregoing **S110**, when generating the event response information, the mobile phone **100** may alternatively not need to determine an operation type of an operation that needs to be performed by the mobile phone **200**, but send only the application name as the event response information to the mobile phone **200**. Subsequently, after receiving the event response information, the mobile phone **200** may directly determine, based on the application name, whether to download and install the corresponding application.

(190) Refer to FIG. **11A** and FIG. **11B**. In another implementation of embodiments of this disclosure, a process of performing application opening interconnection between the mobile phone **100** and the mobile phone **200** includes the following steps.

(191) **S201**: The sensor module **201** in the mobile phone **200** sends detected single-tap operation information corresponding to a single-tap operation of the user U2 to the input event reading module **202** in the mobile phone **200**.

(192) The single-tap operation information includes an input event type corresponding to a trigger operation of the user U2 and position coordinate information of a position at which the user U2 single taps. For example, an event type corresponding to the single-tap operation of the user U2 is a “single-tap input event”.

(193) **S202**: The input event reading module **202** receives the single-tap operation information, extracts an event from the EventHub through a thread to perform event translation, and may determine that an input event of the user U2 is a single-tap input event. The input event reading module **202** sends the single-tap input event to the input event distribution module **203**.

(194) A value range of the double-tap operation determining time threshold may be, for example, 0.1 s to 0.6 s, for example, 0.1 s, 0.35 s, 0.5 s, or 0.6 s. Certainly, the double-tap operation determining time threshold may alternatively be another value.

(195) **S203**: The input event distribution module **203** distributes the event based on the received single-tap input event, and sends event information of the single-tap input event to the video call interface application **204**.

(196) **S204**: The video call interface application **204** transfers the event information of the single-tap input event to the video call application **A2**.

(197) **S205**: The video call application **A2** determines a single-tap time in the event information of the single-tap input event, so as to achieve an objective of event identification and event effectiveness analysis. If the video call application **A2** does not receive a next input event within a preset interval time threshold after determining the single-tap input event, the video call application **A2** determines that the input event is the single-tap input event.

(198) A value range of the interval time threshold may be, for example, 0.1 s to 0.6 s, for example, 0.1 s, 0.35 s, 0.5 s, or 0.6 s. Certainly, the interval time threshold may alternatively be another value.

(199) **S206**: The video call application **A2** invokes the SDK module **205** to deliver the event information.

(200) **S207**: The SDK module **205** sends the event information to the SDK module **105** in the mobile phone **100**. The event information includes an event type “single-tap input event” and operation area information “position coordinate information of the position at which the user single taps”.

(201) **S208**: The SDK module **105** parses the event information to obtain the event type “single-tap input event” and the operation area information “position coordinate information of the position at

which the user single taps”.

(202) **S209**: The SDK module **105** sends the parsed event information to the video call application **A2**. To be specific, the event type “double-tap input event” and the operation area information “position coordinate information of the position at which the user single taps” are sent to the video call application **A2**.

(203) **S210**: The video call application **A2** may first determine, based on the event type “single-tap input event”, that the mobile phone **100** needs to perform an operation object trigger operation. Then, the video call application **A2** determines, based on the operation area information “position coordinate information of the position at which the user single taps”, whether the position coordinate information is valid, for example, whether a current interface of the mobile phone **100** includes an application icon and/or an application name of the application. If a current interface of the mobile phone **100** includes an application icon and/or an application name of the application, the video call application **A2** determines whether the position at which the user single taps is at a position at which an on-screen application icon and/or the application name is located. If the position at which the user single taps is at a position at which an on-screen application icon and/or the application name is located, it is considered that the position coordinate information is valid. The video call application **A2** determines, based on the position coordinate information “position coordinate information of the position at which the user single taps”, a corresponding area on an interface of the mobile phone **100**, and determines an operation object corresponding to the area. For example, the operation object is a video play application **A3**. In this case, the video call application **A2** determines a video play application **A3** opening operation that needs to be performed by the mobile phone **200**. The mobile phone **100** performs the video play application **A3** opening operation to open the video play application **A3**.

(204) That the mobile phone **100** performs the video play application **A3** opening operation to open the video play application **A3** may be that the video call application **A2** sends, by a window management module (not shown in the figure) in the mobile phone **100**, an video play application **A3** opening event to a video call interface application (not shown in the figure) corresponding to the video call application **A2**, to trigger the video call interface application to perform an operation of opening the video play application **A3**.

(205) In the enhanced screen sharing method provided in this embodiment, in a process of screen sharing between the mobile phone **200** and the mobile phone **100**, after the interconnection mode is enabled, the mobile phone **200** may trigger a corresponding operation object in the mobile phone **100** based on the trigger operation performed by the user **U2** on the mobile phone **200**. An interaction type between the mobile phone **100** and the mobile phone **200** that perform screen sharing can be enriched, and user experience can be improved.

(206) In an implementation of embodiments of this disclosure, if screen resolutions of the mobile phone **100** and the mobile phone **200** are the same, in the foregoing step **S204**, the video call interface application **204** directly transfers the received event information of the single-tap input event sent by the input event distribution module **203** to the video call application **A2**. In other words, the mobile phone **100** directly sends the obtained position coordinate information to the mobile phone **200**. For the foregoing **S210**, the video call application **A2** in the mobile phone **100** may directly determine the corresponding operation object based on the position coordinate information.

(207) In an implementation of embodiments of this disclosure, if screen resolutions of the mobile phone **100** and the mobile phone **200** are different, the mobile phone **100** and the mobile phone **200** need to convert the position coordinate information.

(208) For example, for step **S201**, the sensor module **201** in the mobile phone **200** obtains initial position coordinate information based on the single-tap operation of the user **U1**. For step **S204**, the video call interface application **204** may perform, based on a coordinate adjustment parameter determined by a first screen resolution **F1** of the mobile phone **100** and a second screen resolution

F2 of the mobile phone **200**, initial position coordinate information adjustment on initial position information in the received single-tap input event sent by the input event distribution module **203**, to obtain the position coordinate information. Then, the video call interface application **204** sends, to the video call application **A2**, the event information that includes the position coordinate information obtained through adjustment.

(209) In this implementation, $F1$ is $(F11 \times F12)$. $F11$ is a quantity of pixels of a screen of the mobile phone **100** in a horizontal direction (which may alternatively be referred to as a screen width direction, or an x-axis direction). $F12$ is a quantity of pixels of the screen of the mobile phone **100** in a vertical direction (which may alternatively be referred to as a screen length direction, or a y-axis direction). $F2$ is $(F21 \times F22)$. $F21$ is a quantity of pixels of a screen of the mobile phone **200** in the horizontal direction (which may alternatively be referred to as the screen width direction, or the x-axis direction). $F22$ is a quantity of pixels of the screen of the mobile phone **200** in the vertical direction (which may alternatively be referred to as the screen length direction, or the y-axis direction).

(210) In this case, $Z2 = S_b \times Z1$. $Z0$ is the initial position coordinate information (x.sub.0,y.sub.0), and $Z2$ is the position coordinate information.

(211) The coordinate adjustment parameter S_b is $(S_{\text{sub.x}2}, S_{\text{sub.y}2})$, where $S_{\text{sub.x}2} = F11/F21$, and $S_{\text{sub.y}2} = F12/F22$.

(212) In this case, $Z2$ may be $(S_{\text{sub.x}2}x_{\text{sub.0}}, S_{\text{sub.y}2}y_{\text{sub.0}})$.

(213) In an implementation of embodiments of this disclosure, the mobile phone **200** may alternatively send the event information to the mobile phone **100** as in the foregoing steps **S201** to **S207**. For step **S210**, after obtaining the event information, the video call application **A2** in the mobile phone **100** may send the event information to a video call interface application **104** in the mobile phone **100**. The video call interface application **104** adjusts the position coordinate information based on the coordinate adjustment parameter determined by the first screen resolution $F1$ of the mobile phone **100** and the second screen resolution $F2$ of the mobile phone **200**, to obtain the adjusted position coordinate information. A process of coordinate adjustment performed the mobile phone **100** is not described herein again. Then, the video call interface application **104** sends the adjusted position coordinate information to the video call application **A2**. The video call application **A2** determines a corresponding operation object based on the adjusted position coordinate information.

(214) In another implementation of embodiments of this disclosure, an application name of an application may alternatively be a name of an application package corresponding to the application, or may alternatively be another type of application identification information that may be used to identify the application.

(215) In another implementation of embodiments of this disclosure, a user may operate a screen by the foregoing touch operations such as single-tap, double-tap, and flicking, or may operate the screen by a voice or a gesture.

(216) In another implementation of embodiments of this disclosure, operation area information may alternatively be image information such as a trace corresponding to a user operation.

(217) In another implementation of embodiments of this disclosure, the mobile phone **100** and the mobile phone **200** may alternatively perform screen sharing in a scenario such as a voice call or device collaboration, and enable an interconnection mode in a screen sharing process.

(218) In an implementation of this disclosure, a first shared interface and a second shared interface may be partially the same. For example, the second electronic device may display only a part of the first display interface based on interface data of the first shared interface. Alternatively, the second electronic device may display, based on the interface data of the first shared interface, an interface in which content, such as text, is the same as that of the first display interface, but typesetting or the like is different from that of the first display interface. This may be set as required.

(219) In an implementation of this disclosure, the foregoing application download and installation

operation may be only an application download operation.

(220) Refer to FIG. 12. FIG. 12 shows a schematic diagram of a structure of an electronic device **900** according to an implementation of an embodiment of this disclosure. The electronic device **900** may include one or more processors **901** coupled to a controller hub **904**. For at least one embodiment, the controller hub **904** communicates with the processor **901** via a multi-branch bus such as a front side bus (FSB), a point-to-point interface such as a QuickPath Interconnect (QPI), or a similar connection. The processor **901** executes instructions that control a general type of data processing operation. In an embodiment, the controller hub **904** includes but is not limited to a graphics memory controller hub (GMCH) (not shown in the figure) and an input/output hub (IOH) (which may be on separate chips) (not shown in the figure). The GMCH includes a memory and a graphics controller, and is coupled to the IOH.

(221) The electronic device **900** may further include a coprocessor **906** and a memory **902** that are coupled to the controller hub **904**. Alternatively, one or both of the memory **902** and the GMCH may be integrated into the processor **901** (as described in embodiments of this disclosure). The memory **902** and the coprocessor **906** are directly coupled to the processor **901** and the controller hub **904**. The controller hub **904** is in a single chip with the IOH.

(222) In one embodiment, the coprocessor **906** is a dedicated processor. An optional property of the coprocessor **906** is shown in FIG. 12 by dashed lines.

(223) In one embodiment, the electronic device **900** may further include a network interface card (NIC) **903**. The NIC **903** may include a transceiver configured to provide a radio interface for the electronic device **900**, and further communicate with any other proper device (such as a front-end module or an antenna). In various embodiments, the NIC **903** may be integrated with other components of the electronic device **900**. The NIC **903** may implement a function of the communication unit in the foregoing embodiments.

(224) The electronic device **900** may further include an input/output (I/O) device **905**.

(225) It should be noted that FIG. 12 is merely an example. To be specific, although FIG. 12 shows that the electronic device **900** includes a plurality of components such as the processor **901**, the controller hub **904**, and the memory **902**. However, in practical application, a device using the methods in embodiments of this disclosure may include only some of the components of the electronic device **900**, for example, may include only the processor **901** and the NIC **903**. A property of an optional device in FIG. 12 is shown in dashed lines.

(226) The memory of the electronic device **900** may include one or more tangible and non-transitory computer readable storage media configured to store data and/or instructions. The computer readable storage medium stores instructions, and further, stores temporary and permanent copies of the instructions.

(227) In embodiments of this disclosure, the electronic device **900** may be a mobile phone. The instructions stored in the memory of the electronic device may include instructions that when executed by at least one unit in the processor, cause the mobile phone to implement the foregoing enhanced screen sharing method.

(228) Refer to FIG. 13. FIG. 13 shows a schematic diagram of a structure of a system on chip (SoC) **1000** according to an implementation of this disclosure. In FIG. 13, similar components have the same reference numerals. In addition, a dashed-line frame represents an optional feature of a more advanced SoC **1000**. The SoC **1000** may be used in any electronic device according to this disclosure, and may implement corresponding functions based on different devices in which the SoC is located and different instructions stored in the SoC.

(229) In FIG. 13, the SoC **1000** includes an interconnect unit **1002**, coupled to a processor **1001**, a system proxy unit **1006**, a bus controller unit **1005**, an integrated memory controller unit **1003**, one or more coprocessors **1007**, which may include an integrated graphics logic, an image processor, an audio processor, and a video processor, an static random-access memory (RAM) (or SRAM) unit **1008**, and a direct memory access (DMA) unit **1004**. In one embodiment, the coprocessor **1007**

includes a dedicated processor, such as, for example, a network or communication processor, a compression engine, a GPU, a high throughput Many-Integrated-Core (MIC) processor, or an embedded processor.

(230) The SRAM unit **1008** may include one or more computer readable media configured to store data and/or instructions. The computer readable storage medium may store instructions, and further, store temporary and permanent copies of the instructions. The instructions may include instructions that when executed by at least one unit in the processor, cause the electronic device to implement the foregoing enhanced screen sharing method.

(231) Each embodiment of the mechanism disclosed in this disclosure may be implemented in software, hardware, firmware, or a combination of these implementation methods. Embodiments of this disclosure may be implemented as a computer program or program code executed on a programmable system. The programmable program includes at least one processor and a memory (or a storage system, including a volatile and non-volatile memory and/or a storage unit).

(232) It should be noted that, terms “first”, “second” and the like are used only for distinguishing descriptions and are not to be understood as indicating or implying relative importance.

(233) It should be noted that, in the drawings, some structural or method features may be shown in a particular arrangement and/or order. However, it should be understood that such a specific arrangement and/or order may not be required. In some implementations, these features may be arranged in a manner and/or order different from that shown in the descriptive accompanying drawings. In addition, inclusion of the structural or method features in a particular figure does not imply that such features are required in all implementations, and in some implementations, these features may not be included or may be combined with other features.

(234) Although this disclosure has been illustrated and described with reference to some preferred implementations of this disclosure, a person of ordinary skill in the art should understand that the foregoing content is further detailed description of this disclosure with reference to specific implementations, and specific implementations of this disclosure are not limited to these descriptions. Those skilled in the art may make various changes in form and detail, including several simple deductions or substitutions, without departing from the spirit and scope of this disclosure.

Claims

1. An enhanced screen sharing method implemented by a first electronic device, wherein the enhanced screen sharing method comprises: displaying a first shared interface of the first electronic device, wherein the first shared interface is a home screen of the first electronic device, and the first shared interface comprises application icons of multiple applications; sending first interface data of the first shared interface to a second electronic device to enable the second electronic device to display, based on the first interface data, a second shared interface corresponding to the first shared interface, wherein the second shared interface comprises the application icons of the multiple applications; receiving event information from the second electronic device, wherein the event information is based on a trigger operation of a user for the second shared interface, and wherein the event information comprises operation area information that correspond to the trigger operation; determining, based on the operation area information, application identification information of a first application corresponding to the operation area information on the first shared interface; generating event response information comprising the application identification information; and sending the event response information to the second electronic device, wherein the event response information is for downloading the first application on the second electronic device when the application is not currently installed in the second electronic device.
2. The enhanced screen sharing method of claim 1, wherein the event information further comprises an event type, and the method further comprises: determining a first operation type

based on the event type; and determining the application identification information of the first application based on the first operation type and the operation area information.

3. The enhanced screen sharing method of claim 2, wherein the first operation type is an application determining operation when the event type is a first input event.

4. The enhanced screen sharing method of claim 3, wherein the first input event is a double-tap input event or a touch-and-hold input event.

5. The enhanced screen sharing method of claim 3, further comprising: determining a second operation type based on the first operation type, wherein the second operation type is an application download operation or an application download and installation operation; and generating event response information comprising the application identification information and the second operation type.

6. The enhanced screen sharing method of claim 2, wherein the first operation type is an operation object trigger operation when the event type is a second input event, and wherein the enhanced screen sharing method further comprises: determining, based on the operation area information, an operation object corresponding to the operation area information on the first shared interface; and performing an operation of triggering the operation object.

7. The enhanced screen sharing method of claim 6, wherein the second input event is a single-tap input event or a flicking input event.

8. The enhanced screen sharing method of claim 2, wherein a first screen resolution of the first electronic device is different from a second screen resolution of the second electronic device, and wherein the enhanced screen sharing method further comprises: adjusting the operation area information based on the first screen resolution and the second screen resolution to obtain adjusted operation area information; and performing a corresponding operation based on the adjusted operation area information and the first operation type.

9. The enhanced screen sharing method of claim 1, wherein the operation area information comprises position coordinate information.

10. The enhanced screen sharing method of claim 1, further comprising: displaying an interconnection control; and detecting an enabling trigger operation performed by the user on the interconnection control; and enabling, in response to detecting the enabling trigger operation, an interconnection mode with the second electronic device.

11. The enhanced screen sharing method of claim 1, further comprising: receiving an interconnection request from the second electronic device; displaying, in response to the interconnection request, an interconnection determining control; detecting a trigger operation performed by the user on the interconnection determining control; and generating and sending, to the second electronic device in response to detecting the trigger operation, an interconnection response indicating that interconnection is agreed to, wherein the interconnection response is for enabling an interconnection mode.

12. The enhanced screen sharing method of claim 1, further comprising: receiving, by the first electronic device, second interface data of a third shared interface of the second electronic device to enable the first electronic device to display, based on the second interface data, a fourth shared interface corresponding to the third shared interface, wherein the first shared interface is different than the third shared interface; and simultaneously displaying both the first shared interface and the fourth shared interface on the first electronic device, wherein either the first shared interface is displayed on a first portion of a first physical display of the first electronic device and the fourth shared interface is displayed on a second portion of the first physical display of the first electronic device or the first shared interface is displayed on the first physical display of the first electronic device and the fourth shared interface is displayed on a second physical display of the first electronic device.

13. An enhanced screen sharing method implemented by a second electronic device, wherein the enhanced screen sharing method comprises: receiving first interface data of a first shared interface

from a first electronic device, wherein the first shared interface is displayed by the first electronic device, the first shared interface is a home screen of the first electronic device, and the first shared interface comprises application icons of multiple applications; displaying, based on the first interface data, a second shared interface corresponding to the first shared interface, wherein the second shared interface comprises the application icons of the multiple applications; detecting a trigger operation performed by a user on the second shared interface; determining event information corresponding to the trigger operation, wherein the event information comprises operation area information that correspond to the trigger operation; sending the event information to the first electronic device to enable the first electronic device to determine a first application corresponding to the operation area information; receiving, from the first electronic device, event response information comprising application identification information of the first application; and downloading the first application according to the application identification information when the first application is not currently installed in the second electronic device.

14. The enhanced screen sharing method of claim 13, wherein a first screen resolution of the first electronic device is different from a second screen resolution of the second electronic device, and wherein the enhanced screen sharing method further comprises: obtaining initial operation area information based on the trigger operation; and adjusting the initial operation area information based on the first screen resolution and the second screen resolution to obtain the operation area information.

15. The enhanced screen sharing method of claim 13, wherein enabling the interconnection mode for the first electronic device comprises: displaying an interconnection control; and detecting an enabling trigger operation performed by the user on the interconnection control; and enabling, in response to detecting the enabling trigger operation, an interconnection mode for the first electronic device.

16. The enhanced screen sharing method of claim 15, wherein enabling the interconnection mode comprises: detecting the enabling trigger operation performed by the user on the interconnection control; sending, in response to detecting the enabling trigger operation, an interconnection request to the first electronic device; receiving an interconnection response indicating that interconnection is agreed to; and enabling, in response to receiving the interconnection response, an interconnection mode for the first electronic device.

17. The enhanced screen sharing method of claim 13, further comprising: generating interconnection operation prompt information; and displaying the interconnection operation prompt information.

18. A first electronic device comprising: a non-transitory computer readable medium configured to store instructions; and one or more processors coupled to the non-transitory computer readable medium and configured to execute the instructions to cause the first electronic device to: display a first shared interface of the first electronic device, wherein the first shared interface is a home screen of the first electronic device, and the first shared interface comprises application icons of multiple applications; send first interface data of the first shared interface to a second electronic device to enable the second electronic device to display, based on the first interface data, a second shared interface corresponding to the first shared interface, wherein the second shared interface comprises the application icons of the multiple applications; receive event information from the second electronic device, wherein the event information is based on a trigger operation of a user for the second shared interface, and wherein the event information comprises type and operation area information that correspond to the trigger operation; determine, based on the operation area information, application identification information of a first application corresponding to the operation area information on the first shared interface; generate event response information comprising the application identification information; and send the event response information to the second electronic device, wherein the event response information is for downloading the first application on the second electronic device when the application is not currently installed in the

second electronic device.

19. The first electronic device of claim 18, wherein the one or more processors are further configured to execute the instructions to cause the first electronic device to: determine a first operation type based on the event type; and further perform the corresponding operation on the first electronic device based on the first operation type and the operation area information.

20. A second electronic device comprising: a non-transitory computer readable medium configured to store instructions; and one or more processors coupled to the non-transitory computer readable medium and configured to execute the instructions to cause the second electronic device to: receive first interface data of a first shared interface from a first electronic device, wherein the first shared interface is configured to be displayed by the first electronic device, and wherein the first shared interface is a home screen of the first electronic device, and the first shared interface comprises application icons of multiple applications; display, based on the first interface data, a second shared interface corresponding to the first shared interface, wherein the second shared interface comprises the application icons of the multiple applications; detect a trigger operation performed by a user on the second shared interface; determine event information corresponding to the trigger operation, wherein the event information comprises operation area information that correspond to the trigger operation; send the event information to the first electronic device to enable the first electronic device to determine a first application corresponding to the operation area information; receive, from the first electronic device, event response information comprising application identification information of the first application; and download the first application according to the application identification information when the first application is not currently installed in the second electronic device.
