

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12406897
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Yeh; Shu-Shen et al.

Package structure with buffer layer embedded in lid layer

Abstract

Provided is a package structure including a substrate, a stiffener ring, an eccentric die, a lid layer, and a buffer layer. The stiffener ring is disposed on the substrate. The stiffener ring has an inner perimeter to enclose an accommodation area. The eccentric die is disposed within the accommodation area on the substrate. The eccentric die is offset from a center of the accommodation area to close to a first side of the stiffener ring. The lid layer is disposed on the stiffener ring and overlays the eccentric die. The buffer layer is embedded in the lid layer between the first side of the stiffener ring and the eccentric die. The buffer layer has a thickness less than a thickness of the lid layer.

Inventors: Yeh; Shu-Shen (Taoyuan, TW), Lin; Yu-Sheng (Hsinchu, TW), Yew; Ming-Chih (Hsinchu, TW), Lin; Po-Yao (Hsinchu County, TW), Jeng; Shin-Puu (Hsinchu, TW)

Applicant: Taiwan Semiconductor Manufacturing Company, Ltd. (Hsinchu, TW)

Family ID: 81896826

Assignee: Taiwan Semiconductor Manufacturing Company, Ltd. (Hsinchu, TW)

Appl. No.: 18/658981

Filed: May 08, 2024

Prior Publication Data

Document Identifier	Publication Date
US 20240290682 A1	Aug. 29, 2024

Related U.S. Application Data

continuation parent-doc US 17984259 20221110 US 12009278 child-doc US 18658981
continuation parent-doc US 17185986 20210226 US 11527457 20221213 child-doc US 17984259

Publication Classification

Int. Cl.: H01L23/367 (20060101); H01L23/24 (20060101); H01L25/00 (20060101); H01L25/18 (20230101)

U.S. Cl.:

CPC H01L23/3675 (20130101); H01L23/24 (20130101); H01L25/18 (20130101); H01L25/50 (20130101);

Field of Classification Search

CPC: H01L (23/3675); H01L (23/24); H01L (25/18); H01L (25/50); H01L (23/16)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
6011304	12/1999	Mertol	257/710	H01L 23/04
7002246	12/2005	Ho	257/E23.101	H01L 23/36
9000584	12/2014	Lin et al.	N/A	N/A
9048222	12/2014	Hung et al.	N/A	N/A
9048233	12/2014	Wu et al.	N/A	N/A
9064879	12/2014	Hung et al.	N/A	N/A
9111949	12/2014	Yu et al.	N/A	N/A
9263511	12/2015	Yu et al.	N/A	N/A
9281254	12/2015	Yu et al.	N/A	N/A
9368460	12/2015	Yu et al.	N/A	N/A
9372206	12/2015	Wu et al.	N/A	N/A
9496189	12/2015	Yu et al.	N/A	N/A
2009/0108429	12/2008	Tsao	257/E23.101	H01L 23/4006
2012/0182694	12/2011	Lin	361/728	H01L 23/16
2022/0028773	12/2021	Lu	N/A	H01L 25/03
2022/0319871	12/2021	Shah	N/A	H01L 21/566
2022/0359322	12/2021	Hung	N/A	H01L 23/16
2023/0021005	12/2022	Chiou	N/A	H01L 23/5385
2025/0070084	12/2024	Lee	N/A	H01L 25/0655
2025/0149524	12/2024	Fan	N/A	H01L 24/29
2025/0210568	12/2024	Lin	N/A	H01L 24/24

Primary Examiner: Le; Thao P

Attorney, Agent or Firm: JCIPRNET

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) This application is a continuation application of and claims the priority benefit of a prior application Ser. No. 17/984,259, filed on

Nov. 10, 2022, now allowed. The U.S. application Ser. No. 17/984,259 is a continuation application of and claims the priority benefit of U.S. application Ser. No. 17/185,986, filed on Feb. 26, 2021, now U.S. Pat. No. 11,527,457, issued on Dec. 13, 2022. The entirety of the above-mentioned patent application is hereby incorporated by reference herein and made a part of this specification.

BACKGROUND

(1) The semiconductor industry has experienced rapid growth due to continuous improvements in the integration density of various electronic components (i.e., transistors, diodes, resistors, capacitors, etc.). For the most part, this improvement in integration density has come from continuous reductions in minimum feature size, which allows more of the smaller components to be integrated into a given area. These smaller electronic components also demand smaller packages that utilize less area than previous packages. Some smaller types of packages for semiconductor components include quad flat packages (QFPs), pin grid array (PGA) packages, ball grid array (BGA) packages, flip chips (FC), three-dimensional integrated circuits (3DICs), wafer level packages (WLPs), and package on package (PoP) devices and so on.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

(1) Aspects of the present disclosure are best understood from the following detailed description when read with the accompanying figures. It is noted that, in accordance with the standard practice in the industry, various features are not drawn to scale. In fact, the dimensions of the various features may be arbitrarily increased or reduced for clarity of discussion.

(2) FIG. 1A is a top view showing a package structure in accordance with a first embodiment.

(3) FIG. 1B is an explosive view illustrating the package structure depicted in FIG. 1A.

(4) FIG. 1C is a perspective view illustrating a portion of the package structure depicted in FIG. 1A.

(5) FIG. 1D is a cross-sectional view along a cross-section A-A' of FIG. 1A.

(6) FIG. 2 is a cross-sectional view showing a package structure in accordance with a second embodiment.

(7) FIG. 3A is a cross-sectional view showing a package structure in accordance with a third embodiment.

(8) FIG. 3B to FIG. 3D are cross-sectional views showing a stiffener ring in accordance with various embodiments.

(9) FIG. 4 is a cross-sectional view showing a package structure in accordance with a fourth embodiment.

(10) FIG. 5 is a top view showing a package structure in accordance with a fifth embodiment.

(11) FIG. 6 is a top view showing a package structure in accordance with a sixth embodiment.

(12) FIG. 7 is a top view showing a package structure in accordance with a seventh embodiment.

(13) FIG. 8 is a top view showing a package structure in accordance with an eighth embodiment.

(14) FIG. 9 is a top view showing a package structure in accordance with a ninth embodiment.

(15) FIG. 10 is a top view showing a package structure in accordance with a tenth embodiment.

(16) FIG. 11 is a top view showing a package structure in accordance with an eleventh embodiment.

(17) FIG. 12 is a top view showing a package structure in accordance with a twelfth embodiment.

(18) FIG. 13 is a top view showing a package structure in accordance with a thirteenth embodiment.

(19) FIG. 14 is a top view showing a package structure in accordance with a fourteenth embodiment.

(20) FIG. 15A to FIG. 15D are cross-sectional views of a method of forming a lid layer having a

buffer layer in accordance with some alternative embodiments.

DETAILED DESCRIPTION

(21) The following disclosure provides many different embodiments, or examples, for implementing different features of the provided subject matter. Specific examples of components and arrangements are described below to simplify the present disclosure. These are, of course, merely examples and are not intended to be limiting. For example, the formation of a first feature over or on a second feature in the description that follows may include embodiments in which the first and second features are formed in direct contact, and may also include embodiments in which additional features may be formed between the first and second features, such that the first and second features may not be in direct contact. In addition, the present disclosure may repeat reference numerals and/or letters in the various examples. This repetition is for the purpose of simplicity and clarity and does not in itself dictate a relationship between the various embodiments and/or configurations discussed.

(22) Further, spatially relative terms, such as “beneath,” “below,” “lower,” “above,” “upper” and the like, may be used herein for ease of description to describe one element or feature's relationship to another element(s) or feature(s) as illustrated in the figures. The spatially relative terms are intended to encompass different orientations of the device in use or operation in addition to the orientation depicted in the figures. The apparatus may be otherwise oriented (rotated 90 degrees or at other orientations) and the spatially relative descriptors used herein may likewise be interpreted accordingly.

(23) Other features and processes may also be included. For example, testing structures may be included to aid in the verification testing of the 3D packaging or 3DIC devices. The testing structures may include, for example, test pads formed in a redistribution layer or on a substrate that allows the testing of the 3D packaging or 3DIC, the use of probes and/or probe cards, and the like. The verification testing may be performed on intermediate structures as well as the final structure. Additionally, the structures and methods disclosed herein may be used in conjunction with testing methodologies that incorporate intermediate verification of known good dies to increase the yield and decrease costs.

(24) In the semiconductor package industry, a chip having an integrated circuit is commonly mounted on a package substrate such as an interposer, a circuit board or a lead frame that provides electrical connections from the chip to the exterior of the package structure. In such packaging arrangement called flip chip mounting, where an active surface of the chip is mounted in an upside-down manner on the substrate, the chip and the substrate are usually formed of different materials having mismatched coefficients of thermal expansion (CTE). As a result, the chip and the substrate experience significantly different dimension changes when heated, and the mismatch in dimension changes causes significant thermally-induced stresses and warpage in the electrical connections between the chip and the substrate. If uncompensated, the disparity in thermal expansion can result in degradation in the performance of the chip, damage to the solder connections between the chip and the substrate, or package failure.

(25) To reduce warpage and improve the reliability of flip chip packages, a number of approaches have been offered by the microelectronics industry. A stiffener is typically employed around the chip in the package assembly. The stiffener is attached on the substrate and surround the chip to constrain the substrate in order to prevent chip warpage or other movement relative to the chip during thermal cycling. To further reduce the chance of warpage and promote thermal cooling of flip chip packages, a lid or heat spreader is often mounted on top of the package to dissipate heat and counter-balance the forces exerted by the thermal expansion mismatches between at least the chip and the substrate.

(26) With the diversification of electronic products, the chip in the package may be arranged at any position on the substrate to accommodate more components, such as capacitors, resistors, inductors, or any suitable passive components. When the chip is offset from a center of the

substrate to approach one side of the stiffener to make more room for the passive components, the thermally-induced stress will focus on the side of the stiffener close to the chip. In this case, the stress due to the CTE mismatch may cause the delamination or crack issue of the adhesive coupled between the stiffener and the lid, thereby affecting the reliability of the package structure.

(27) In accordance with some embodiments, an opening is formed in a lid layer between a first side of a stiffener ring and an eccentric die to break the stress caused by the CTE mismatch, thereby avoiding the crack and/or delamination issue of the adhesive layer and enhancing the reliability of the package structure. In addition, a buffer layer (or an embedded buffer/portion) is formed in an upper portion of the opening to prevent the electromagnetic interference (EMI).

(28) FIG. 1A is a top view showing a package structure in accordance with a first embodiment. FIG. 1B is an explosive view illustrating the package structure depicted in FIG. 1A. FIG. 1C is a perspective view illustrating a portion of the package structure depicted in FIG. 1A. FIG. 1D is a cross-sectional view along a cross-section A-A' of FIG. 1A.

(29) Referring to FIG. 1A to FIG. 1D, a package structure P1 includes a substrate **100**, a first adhesive layer **102**, a stiffener ring **104**, a second adhesive layer **106**, a lid layer **108**, a buffer layer **118**, a first die **110**, and a plurality of second dies **120**. For the clarity, the lid layer **108** and the buffer layer **118** are not shown in FIG. 1A. For the configuration of the lid layer **108** and the buffer layer **118**, please refer to FIG. 1B to FIG. 1D.

(30) In some embodiments, the substrate **100** includes a package substrate, a circuit substrate, or an interposer (hereinafter called “package substrate **100**”). The package substrate **100** may include based on an insulating core such as a fiberglass reinforced resin core. One example core material is fiberglass resin such as FR4. Alternatives for the core material include bismaleimide-triazine BT resin, or alternatively, other PCB materials or films. Build up films such as ABF or other laminates may be used for package substrate **100**.

(31) The package substrate **100** may include active and passive devices (not shown). As one of ordinary skill in the art will recognize, a wide variety of devices such as transistors, capacitors, resistors, combinations of these, and the like may be used to provide structural and functional designs for the package structure P1. The devices may be formed using any suitable methods.

(32) The package substrate **100** may also include metallization layers, vias, and bond pads over the metallization layers and vias (not shown). The metallization layers may be formed over the active and passive devices and are designed to connect the various devices to form functional circuitry. The metallization layers may be formed of alternating layers of dielectric (e.g., low-k dielectric material) and conductive material (e.g., copper) with vias interconnecting the layers of conductive material and may be formed through any suitable process (such as deposition, damascene, dual damascene, or the like). In some embodiments, the package substrate **100** is substantially free of active and passive devices.

(33) As shown in FIG. 1A, the first die **110** and the second dies **120** are mounted side by side on the package substrate **100**. In detail, the first die **110** is disposed between the second dies **120**. In some embodiments, the first die **110** and the second dies **120** may have different functions or sizes. Herein, the term “size” is referred to the length, width, or area. For example, as shown in FIG. 1A, a length **110l** and/or a width **110w** of the first die **110** is greater than a length **120l** and/or a width **120w** of one of the second dies **120**. Although the detail components in the first die **110** is not illustrated in the cross-sectional view of FIG. 1D, the first die **110** is mounted onto the package substrate **100** by a flip-chip manner. That is, an active surface **110a** of the first die **110** faces and is bonded on a top surface **100t** of the package substrate **100**.

(34) In some embodiments, the first die **110** includes a system on a chip or system on chip (SoC) including several different integrated circuits, i.e. ICs or processors, together with memories and I/O interfaces. Each of the integrated circuit integrates various components of a computer or other electronic systems into one semiconductor chip. The various components contain digital, analog, mixed-signal, and often radio-frequency functions. Also, the SoC integrates processors (or

controllers) with advanced peripherals like a graphics processing unit (GPU), a Wi-Fi module, or a co-processor. In the architecture of the SoC, both logic components and memory components are fabricated in the same silicon wafer. For high efficiency computing or mobile devices, multi-core processors are used, and the multi-core processors include large amounts of memories, such as several gigabytes. In some alternative embodiments, the first die **110** may be an application-specific integrated circuit (ASIC) die.

(35) In some embodiments, one of the second dies **120** includes a memory die, such as high bandwidth memory (HBM) die, dynamic random-access memory (DRAM) die, static random-access memory (SRAM) die, or a combination thereof. Alternatively, one of the second dies **120** may include a chip scale package (CSP) with a memory function. In such embodiment, the second die **120** may be referred to as a package die. In other embodiments, one of the second dies **120** may include a logic die, such as a central processing unit (CPU) die, a graphic processing unit (GPU) die, a micro control unit (MCU) die, an input-output (I/O) die, a baseband (BB) die, or an application processor (AP) die. Although four second dies **120** is illustrated in FIG. **1A** to surround one first die **110**, the embodiments of the present disclosure are not limited thereto. In other embodiments, the number of the first die **110** and the second dies **120** are adjusted by the need. In some embodiments, the first die **110** and the second dies **120** have different coefficients of thermal expansion (CTE). The CTE of first die **110** is less than the CTE of the second dies **120**. For example, the CTE of the first die **110** is in a range of 2.5 ppm/° C. to 3.5 ppm/° C., such as 3 ppm/° C., and the CTE of the second dies **120** is in a range of 8 ppm/° C. to 25 ppm/° C., such as 17 ppm/° C.

(36) Referring to FIG. **1B** and FIG. **1D**, the first adhesive layer **102** is formed on the package substrate **100**. In some embodiments, the first adhesive layer **102** includes any suitable adhesive, epoxy, die attach film (DAF), or the like. Alternatively, the first adhesive layer **102** may be a thermally conductive material.

(37) Thereafter, the stiffener ring **104** is adhered on the package substrate **100** by the first adhesive layer **102**. The stiffener ring **104** may be a rigid ring-like structure having substantially the same dimensions as the package substrate **100**. In some embodiments, stiffener ring **104** are pre-fabricated and available from material suppliers. As shown in FIG. **1A**, the stiffener ring **104** has an inner sidewall (or inner perimeter) **103** facing and surrounding the first die **110** and the second dies **120**. The inner sidewall **103** may enclose an accommodation area AA, and the first die **110** and the second dies **120** are disposed on the package substrate **100** within the accommodation area AA. In other words, the stiffener ring **104** may have a window in its center to expose the dies **110** and **120** and allow for the heat transfer. Noted that the stiffener ring **104** is attached on the package substrate **100** and surrounds the dies **110** and **120** to constrain the package substrate **100** in order to prevent its warpage or other movement relative to the first and second dies **110** and **120**, which may be caused by thermal cycling during package assembly, reliability testing, or field operation. The warpage and stress in the dies or package may lead to die performance degradation or package failure. In some embodiments, a thickness T1 of the stiffener ring **104** measured between the top surface **104t** and the bottom surface **104bt** may be smaller than 4000 μm.

(38) In some embodiments, the stiffener ring **104** is formed of a rigid yet flexible material. In one exemplary embodiment, the stiffener ring **104** is formed from a metal material with high thermal conductivity (k), such as steel, stainless steel, copper, aluminum, copper tungsten, the like, or combinations thereof. In another embodiment, the stiffener ring **104** includes a ceramic material. In yet another embodiment, the stiffener ring **104** includes a silicon containing material. In yet another embodiment, the stiffener ring **104** includes a composite alloy. In yet another embodiment, the stiffener ring **104** includes a plastic material. In the present embodiment, the material of the stiffener ring **104** is typically selected to have a CTE the same as or sufficiently similar to the package substrate **100** in order to apply a counter force to the package substrate **100** and reduce the bow of the package structure P1 to within tolerances accepted in the industry. For example, the

CTE of the stiffener ring **104** is smaller than 25 ppm/° C., such as 17 ppm/° C., and the CTE of the package substrate **100** is in a range of 8 ppm/° C. to 25 ppm/° C., such as 17 ppm/° C.

(39) As shown in FIG. 1A, the stiffener ring **104** may have a first portion **104A**, a second portion **104B**, a third portion **104C**, and a fourth portion **104D**. Specifically, the first portion **104A** is adjacent to a first sidewall **110s1** of the first die **110**, and the second portion **104B** is adjacent to a second sidewall **110s2** of the first die **110** opposite to the first sidewall **110s1**. In addition, the third portion **104C** is adjacent to a first sidewall **120s1** of the second die **120** and connects the first portion **104A** and the second portion **104B**. The fourth portion **104D** is adjacent to a second sidewall **120s2** of the second die **120** opposite to the first sidewall **120s1** and connects the first portion **104A** and the second portion **104B**. In the top view of FIG. 1A, the first, second, third, and fourth portions **104A**, **104B**, **104C**, and **104D** are connected to form a rectangular ring structure. However, the embodiments of the present disclosure are not limited thereto. In other embodiments, the stiffener ring **104** may be various ring structures, such as a circular ring structure or a polygonal ring structure.

(40) As shown in FIG. 1B and FIG. 1D, after attaching the stiffener ring **104** on the package substrate **100** by the first adhesive layer **102**, the second adhesive layer **106** is formed on a top surface **104t** of the stiffener ring **104**. The second adhesive layer **106** may include any suitable adhesive, epoxy, die attach film (DAF), or the like. Alternatively, the second adhesive layer **106** may be a thermally conductive material. In some embodiments, the first adhesive layer **102** and the second adhesive layer **106** have the same material or different materials.

(41) After forming the second adhesive layer **106** on the top surface **104t** of the stiffener ring **104**, the lid layer **108** is adhered on the stiffener ring **104** by the second adhesive layer **106**. The lid layer **108** may be coupled to the stiffener ring **104** to increase the rigid of the stiffener ring **104**, thereby reducing the warpage of the package structure **P1**. In some embodiments, the lid layer **108** is formed from a metal material with high thermal conductivity (k), such as steel, stainless steel, copper, aluminum, copper tungsten, the like, or combinations thereof. In another embodiment, the lid layer **108** includes a ceramic material. In yet another embodiment, the lid layer **108** includes a silicon containing material. In yet another embodiment, the lid layer **108** includes a composite alloy. In yet another embodiment, the lid layer **108** includes a plastic material. In some other embodiments, the lid layer **108** is a single contiguous material. In another embodiment, the lid layer **108** includes multiple pieces that may be the same or different materials. In the present embodiment, the lid layer **108** and the stiffener ring **104** have the same material with the same CTE to avoid the stress due to the CTE mismatch. In some embodiments, the lid layer **108** has a thickness **T2** in a range of 200 μm to 1000 μm . The thickness **T2** of the lid layer **108** may be greater than, substantially equal to, or less than the thickness **T1** of the stiffener ring **104**.

(42) As shown in FIG. 1C, in some embodiments, the lid layer **108** has an opening **111** penetrating through a top surface **108t** and a bottom surface **108bt** of the lid layer **108**. The opening **111** may include a lower opening **111a** and an upper opening **110b** on the lower opening **111a**. The lower opening **111a** may be in spatial communication with the upper opening **110b**. In some embodiments, the upper opening **111b** has an area greater than an area of the lower opening **111a**.

(43) It should be noted that, in the present embodiment, the first die **110** is an eccentric die offset from a center of the accommodation area **AA** to close to the first portion **104A** of the stiffener ring **104**, thereby making more room between the second sidewall **110s2** and the second portion **104B** for accommodating more components, such as passive components. That is, as shown in FIG. 1A, a first distance **D1** between the first sidewall **110s1** of the first die **110** and the first portion **104A** is less than a second distance **D2** between the second sidewall **110s2** of the first die **110** and the second portion **104B**. In this case, the thermally-induced stress will focus on the first portion **104A** of the stiffener ring **104** close to the first die **110**. In order to solve the said localized stress concentration issue, in the present embodiment, as shown in FIG. 1D, the opening **111** is formed in the lid layer **108** between a first side **104s1** of the stiffener ring **104** and the first sidewall **110s1** of

the first die **110** to break the stress caused by the CTE mismatch, thereby avoiding the crack and/or delamination issue of the second adhesive layer **106** and enhancing the reliability of the package structure **P1**. In some embodiments, the first distance **D1** is smaller than 5000 μm , the second distance **D2** is smaller than 5000 μm , and a ratio (**D1/D2**) of the first distance **D1** to the second distance **D2** is in a range of 0 to 1. In some embodiments, the first portion **104A** of the stiffener ring **104** has a first top width (or top area) **TW1** less than a second top width (or top area) **TW2** of the second portion **104B** of the stiffener ring **104**. However, the embodiments of the present disclosure are not limited thereto. In other embodiments, the first top width **TW1** of the first portion **104A** may be substantially equal to or greater than the second top width **TW2** of the second portion **104B**.

(44) The first die **110** may be offset along a first direction **Y**, from a center of the package substrate **100**, and substantially symmetrical along a second direction **X** in some embodiment, but not limited thereto. That is, a distance between a sidewall of the first die **110** and a corresponding sidewall of the package substrate **100** (such as a sum of width **TW1** and the first distance **D1**) is smaller than an opposite distance between a opposite sidewall of the first die **110** and a corresponding sidewall of the package substrate **100** (such as a sum of width **TW2** and the second distance **D2**).

(45) In addition, the buffer layer **118** may be formed in the upper opening **lib** to prevent the electromagnetic interference (EMI). In some embodiments, the buffer layer **118** is formed from a metal material with high thermal conductivity (**k**), such as steel, stainless steel, copper, aluminum, copper tungsten, the like, or combinations thereof. In another embodiment, the buffer layer **118** includes a ceramic material. In yet another embodiment, the buffer layer **118** includes a silicon containing material. In yet another embodiment, the buffer layer **118** includes a composite alloy. In yet another embodiment, the buffer layer **118** includes a plastic material. In some embodiments, the buffer layer **118** and the lid layer **108** may have different materials. In the present embodiment, the buffer layer **118** is softer than the lid layer **108** to relieve the thermally-induced stress and prevent the EMI issues simultaneously. For example, the buffer layer **118** may be made of aluminum, and the lid layer **108** may be made of copper. However, the embodiments of the present disclosure are not limited thereto. In other embodiments, the buffer layer **118** and the lid layer **108** may have the same material, such as copper.

(46) In some embodiments, the buffer layer **118** may be referred to as an embedded buffer/portion embedded in the lid layer **108**, and may be formed by following steps illustrated in FIG. **15A** to FIG. **15D**. While disclosed method is illustrated and described herein as a series of acts or events, it will be appreciated that the illustrated ordering of such acts or events are not to be interpreted in a limiting sense. For example, some acts may occur in different orders and/or concurrently with other acts or events apart from those illustrated and/or described herein. In some alternative embodiments, not all illustrated acts are required to implement one or more aspects or embodiments of the description herein. Further, one or more of the acts depicted herein may be carried out in one or more separate acts and/or phases.

(47) Referring to FIG. **15A**, the lid layer **108** having a top surface **108t** and a bottom surface **108bt** opposite to each other is provided.

(48) Referring to FIG. **15B**, an opening **111'** is formed to penetrate through the top surface **108t** and the bottom surface **108bt** of the lid layer **108**. In some embodiments, the through opening **111'** may be formed by using a mechanical drilling process, such as computer numerical control (CNC) lathes. However, the embodiments of the present disclosure are not limited thereto. In other embodiments, the through opening **111'** may be formed by using a laser drilling process or the like.

(49) Referring to FIG. **15B** and FIG. **15C**, an upper portion of the opening **111'** is widened to form the opening **111** with the narrower lower opening **111a** and the wider upper opening **111b**. In some embodiments, the upper opening **111b** may be widened by using a mechanical drilling process, such as computer numerical control (CNC) lathes. In this case, the opening **111** may be formed as

T-shape in the cross-sectional view of FIG. 15C. The lid layer **108** may be divided into a first portion **108a** and a second portion **108b** by the opening **111**.

(50) Referring to FIG. 15D, the buffer layer **118** is disposed in the upper opening **111b** and connected to the upper opening **111b** by a glue layer **116**. Herein, the buffer layer **118** may be referred to as an embedded portion connecting the first portion **108a** of the lid layer **108** overlying the first die **110** and the second portion **108b** of the lid layer **108** overlying the stiffener ring **104**, as shown in FIG. 1D. From another perspective, the lid layer **108** and the buffer layer **118** may constitute a lid structure **208**. Specifically, the lid structure **208** may include a body portion (i.e., the lid layer **108**) and an embedded portion (i.e., the buffer layer **118**). The embedded portion **118** is connected to the body portion **108** by the glue layer **116**. The embedded portion **118** has a top surface **118t** and a bottom surface **118bt** opposite to each other. The bottom surface **118bt** of the embedded portion **118** may be exposed by the lower opening **111a**, the bottom surface **118bt** of the embedded portion **118** may be higher than the bottom surface **108bt** of the lid layer **108**, and the top surface **118t** may be level (or coplanar) with the top surface **108t** of the body portion **108**. However, the embodiments of the present disclosure are not limited thereto. In other embodiments, the top surface **118t** may be higher than or lower than the top surface **108t** of the body portion **108**. In some embodiments, the glue layer **116** includes any suitable adhesive, epoxy, die attach film (DAF), or the like. In some embodiments, the glue layer **116** and the adhesive layer **102/106** have the same material, such as DAF. In some alternative embodiments, the glue layer **116** and the adhesive layer **102/106** have different materials. For example, the adhesive layer **102/106** is DAF, and the glue layer **116** is silver glue. In addition, since the embedded portion **118** is only disposed in the upper opening **111b**, the embedded portion **118** has a thickness **T3** less than the thickness **T2** of the body portion **108**. In some embodiments, a thickness **T3** of the embedded portion **118** measured between the top surface **118t** and the bottom surface **118bt** may be in a range of 100 μm to 900 μm . The thinned embedded portion **118** is able to effectively reduce the transfer of the thermally-induced stress from the first portion **108a** to the second portion **108b**, thereby avoiding the crack and/or delamination issue of the second adhesive layer **106** above the second portion **108b** and enhancing the reliability of the package structure **P1**.

(51) FIG. 2 is a cross-sectional view showing a package structure in accordance with a second embodiment.

(52) Referring to FIG. 2, a package structure **P2** is similar to the package structure **P1** of FIG. 1D, that is, the configurations, materials, and functions of the package structure **P2** are similar to those of the package structure **P1**, and thus the details are omitted herein. The main difference between the package structure **P2** and the package structure **P1** lies in that the package structure **P2** has a buffer layer **218** further extends to cover the top surface **104t** of the first portion **104A** of the stiffener ring **104**. In detail, as shown in FIG. 2, the buffer layer **218** has an extending length **L1** from the sidewall **111s** of the lower opening **111a** to overlying the top surface **104t** of the first portion **104A**, and the extending length **L1** may be in a range of 900 μm to 4000 μm and **L1** is smaller than **L2**. In addition, the second portion **108b** of the lid layer **108** has a length **L2** measured between the sidewall (inner sidewall) **108s1** and the sidewall (or outer sidewall) **108s2** of the lid layer **108**, and the length **L2** may be in a range of 900 μm to 4000 μm . In some embodiments, the extending length **L1** is less than the length **L2**. In some alternative embodiments, the extending length **L1** is less than one-half of the length **L2**. That is, the buffer layer **218** may be not extended beyond the center of the length **L2** of the second portion **108b** of the lid layer **108**. In this case, the buffer layer **218** may provide a better stress reduction than the buffer layer **118**, while maintaining the rigidity of the second portion **108b** of the lid layer **108**. Further, the first side **104s1** (or inner sidewall) of the stiffener ring **104** may be recessed or concave from the sidewall **111s** of the lower opening **111a**. In some embodiments, the first side **104s1** of the stiffener ring **104** is within the range of the extending length **L1**.

(53) FIG. 3A is a cross-sectional view showing a package structure in accordance with a third

embodiment. FIG. 3B to FIG. 3D are cross-sectional views showing a stiffener ring in accordance with various embodiments.

(54) Referring to FIG. 3A, a package structure P3 is similar to the package structure P2 of FIG. 2, that is, the configurations, materials, and functions of the package structure P3 are similar to those of the package structure P2, and thus the details are omitted herein. The main difference between the package structure P3 and the package structure P2 lies in that the package structure P3 includes a stiffener ring 304 having a slant sidewall (or inclined sidewall) 305 facing the first sidewall 110_{si} of the first die 110. When the first distance D1 is smaller than the second distance D2, the crack and/or delamination issue of the adhesive layers 102 and 106 may be occurred due to the stress concentration. In such embodiment, the first portion 304A of the stiffener ring 304 may have the slant sidewall 305 to decrease the rigidity of a first portion 304A of the stiffener ring 304 and increase the flexibility of the first portion 304A of the stiffener ring 304. Accordingly, the stress due to the CTE mismatch between the first die 110 and the package substrate 100 (or the lid layer 108) transmitted to the first portion 304A of the stiffener ring 304 can be effectively reduced, thereby avoiding the crack and/or delamination issue of the adhesive layers 102 and 106. It should be noted that, in the present embodiment, since the first portion 304A of the stiffener ring 304 has the slant sidewall 305, a width (or area) W1 of the top surface 304_t of the first portion 304A is less than a width (or area) W2 of the bottom surface 304_{bt} of the first portion 304A. In this case, the second adhesive layer 106 on the first portion 304A may have a width (or area) W3 is less than a width (or area) W4 of the first adhesive layer 102 between the first portion 304A and the package substrate 100. In some embodiments, the width W1 is substantially equal to the width W3, and the width W2 is substantially equal to the width W4. On the other hand, the second portion 304B, the second adhesive layer 106 on the second portion 304B, and the first adhesive layer 102 between the second portion 304B and the package substrate 100 may have the same width (or area) W5.

(55) On the other hand, since the second distance D2 between the second sidewall 110_{s2} of the first die 110 and a second portion 304B of the stiffener ring 304 is far enough, the second portion 304B of the stiffener ring 304 may maintain a vertical sidewall 309 facing the second sidewall 110_{s2} of the first die 110. In some embodiments, the slant sidewall 305 is only formed on the first portion 304A of the stiffener ring 304 facing the first sidewall 110_{s1} of the first die 110. However, the embodiments of the present disclosure are not limited thereto. In some other embodiments, the slant sidewall 305 may surround all sidewalls of the first die 110. In such embodiment, the all-around slant sidewall 305 is able to comprehensively reduce the stress of the entire stiffener ring 304. In alternative embodiments, the slant sidewall 305 may be a continuously inclined structure or a non-continuously inclined structure.

(56) In some embodiments, as shown in FIG. 3A, the buffer layer 318 has an extending length L3 overlapping with the top surface 304_t of the stiffener ring 304, and the extending length L3 may be in a range of 900 μm to 4000 μm. In addition, the second portion 108_b of the lid layer 108 has a length L4 measured between the sidewall (inner sidewall) 108_{s1} and the sidewall (or outer sidewall) 108_{s2} of the lid layer 108, and the length L4 may be in a range of 900 μm to 4000 μm. In some embodiments, the extending length L3 is less than the length L4. In some alternative embodiments, a ratio (L3/L4) of the extending length L3 to the length L4 is less than 1.0. That is, the buffer layer 318 may be not extended beyond the center of the length L4 of the second portion 108_b of the lid layer 108. In this case, the buffer layer 318 may provide a better stress reduction than the buffer layer 118, while maintaining the rigidity of the second portion 108_b of the lid layer 108.

(57) In some embodiments, the first portion 304A of the stiffener ring 304 includes various shapes or profiles in the cross-sectional view, so as to avoid the crack or delamination issue of the adhesive layers 102 and 106. In one exemplary embodiment, as shown in the enlarged view of FIG. 3A, the first portion 304A1 may have a top surface 304_t and a bottom surface 304_{bt} opposite to each other. The inner sidewall 303_a of the first portion 304A1 may have a slant sidewall 305_a and a vertical

sidewall **307**. The vertical sidewall **307** is connected to the slant sidewall **305a** and the bottom surface **304bt**, and the slant sidewall **305a** is connected to the vertical sidewall **307** and the top surface **304t**. An angle $\theta 1$ between the slant sidewall **305a** and the bottom surface **304bt** is an acute angle. In some embodiments, the angle $\theta 1$ is in a range of 30 degree to 89.9 degree. A thickness **ST1** of the first portion **304A1** measured between the top surface **304t** and the bottom surface **304bt** may be smaller than 4000 μm , a height **SH1** of the slant sidewall **305a** may be smaller than 4000 μm , and a length **SL1** of the slant sidewall **305a** may be smaller than 4000 μm . In the embodiments, as shown in FIG. 3A, the height **SH1** of the slant sidewall **305a** is less than the thickness **ST1** of the first portion **304A1**. In another embodiment, as shown in FIG. 3B, the first portion **304A2** may have a slant sidewall **305b** connecting the top surface **304t** and the bottom surface **304bt**. In some embodiments, the angle $\theta 2$ is in a range of 45 degree to 89.9 degree. A thickness **ST2** of the first portion **304A2** measured between the top surface **304t** and the bottom surface **304bt** may be in a range of 0.1 μm to 4000 μm , a height **SH2** of the slant sidewall **305b** may be in a range of 0.1 μm to 4000 μm , and a length **SL2** of the slant sidewall **305b** may be in a range of 0.1 μm to 4000 μm . In the embodiments, as shown in FIG. 3B, the height **SH2** of the slant sidewall **305b** is substantially equal to the thickness **ST2** of the first portion **304A2**. Although the slant sidewall **305a/305b** illustrated in FIGS. 3A and 3B is a flat surface, the embodiments of the present disclosure are not limited thereto. In some other embodiments, as shown in FIG. 3C, the first portion **304A3** may have a slant sidewall **305c** connecting the top surface **304t** and the bottom surface **304bt**, and the slant sidewall **305c** is a curved surface. In some other embodiments, as shown in FIG. 3D, the first portion **304A4** may have a slant sidewall **305d** connecting the top surface **304t** and the bottom surface **304bt**, and the slant sidewall **305d** is a staircase surface.

(58) FIG. 4 is a cross-sectional view showing a package structure in accordance with a fourth embodiment.

(59) Referring to FIG. 4, a package structure **P4** is similar to the package structure **P3** of FIG. 3A, that is, the configurations, materials, and functions of the package structure **P4** are similar to those of the package structure **P3**, and thus the details are omitted herein. The main difference between the package structure **P4** and the package structure **P3** lies in that the package structure **P4** has a stiffener ring **404** protruding from the package substrate **100**. Specifically, as shown in FIG. 4, the stiffener ring **404** may have an outer sidewall **404s** opposite to the inner sidewall **403** (or slant sidewall **405**). The stiffener ring **404** may include a first portion **404A** and a second portion **404B**. The first portion **404A** may be adjacent to the first sidewall **110s1** of the first die **110**, and the second portion **404B** may be adjacent to the second sidewall **110s2** of the first die **110** opposite to the first sidewall **110s1**. The first portion **404A** of the stiffener ring **404** may have a first outer sidewall **404s1** protruding from a sidewall **100s1** of the package substrate **100** by a distance **D3**. In some embodiments, the distance **D3** is in a range of 0.1 μm to 3000 μm , such as 1200 μm . On the other hand, the second portion **404B** of the stiffener ring **404** may have a second outer sidewall **404s2** aligned with a sidewall **100s2** of the package substrate **100**. It should be noted that the first portion **404A** of the stiffener ring **404** may overhang on the package substrate **100** to increase the flexibility of the first portion **404A**, thereby relieving the stress on the first portion **404A**. In this case, the crack and/or delamination issue of the adhesive layers **102** and **106** are avoided, thereby improving the reliability and the yield of the package structure **P4** is improved.

(60) FIG. 5 illustrates a package structure **P5** with a buffer layer **518** embedded in the lid layer in accordance with a fifth embodiment. In the present embodiment, the lid layer is omitted in FIG. 5 to clearly illustrate the relationship between the buffer layer **518** and the first die **110** and/or the stiffener ring **104**.

(61) Referring to FIG. 5, the package structure **P5** is similar to the package structure **P1** of FIG. 1A, that is, the configurations, materials, and functions of the package structure **P5** are similar to those of the package structure **P1**, and thus the details are omitted herein. In the present embodiment, the package structure **P5** includes the buffer layer **518** having a width **518w** greater than or

substantially equal to the width **110w** of the first die **110**. In some embodiments, the buffer layer **518** may be disposed between the first portion **104A** of the stiffener ring **104** and the first die **110**. That is, the buffer layer **518** has a length **5181** within a range between the first side **104s1** of the stiffener ring **104** and the first sidewall **110s1** of the first die **110**. In some alternative embodiments, the length **5181** of the buffer layer **518** may be widened, so that the buffer layer **518** further covers the top surface **104t** of the first portion **104A** of the stiffener ring **104**, as shown in the cross-sectional view of FIG. 2.

(62) FIG. 6 illustrates a package structure **P6** with a buffer layer **618** embedded in the lid layer in accordance with a sixth embodiment. In the present embodiment, the lid layer is omitted in FIG. 6 to clearly illustrate the relationship between the buffer layer **618** and the first die **110** and/or the stiffener ring **104**.

(63) Referring to FIG. 6, the package structure **P6** is similar to the package structure **P5** of FIG. 5, that is, the configurations, materials, and functions of the package structure **P6** are similar to those of the package structure **P5**, and thus the details are omitted herein. In the present embodiment, the package structure **P6** includes the buffer layer **618** not only overlying the first sidewall **110s1** of the first die **110**, but also further extending to cover at least two corners **110c** of the first die **110**. Usually, the highest stress may be at the regions close to the corners **110c** of the first die **110**. In such embodiment, the buffer layer **618** is able to provide a better protection to reduce the stress concentrated at the corners **110c** of the first die **110**.

(64) FIG. 7 illustrates a package structure **P7** with a buffer layer **718** embedded in the lid layer in accordance with a seventh embodiment. In the present embodiment, the lid layer is omitted in FIG. 7 to clearly illustrate the relationship between the buffer layer **718** and the first die **110** and/or the stiffener ring **104**.

(65) Referring to FIG. 7, the package structure **P7** is similar to the package structure **P6** of FIG. 6, that is, the configurations, materials, and functions of the package structure **P7** are similar to those of the package structure **P6**, and thus the details are omitted herein. In the present embodiment, the buffer layer **718** of the package structure **P7** includes at least two sub-layers **718a** and **718b** respectively covering two corners **110c** of the first die **110**. In such embodiment, the buffer layer **718** is able to provide a better protection to reduce the stress concentrated at the corners **110c** of the first die **110**.

(66) FIG. 8 illustrates a package structure **P8** with a buffer layer **818** embedded in the lid layer in accordance with an eighth embodiment. In the present embodiment, the lid layer is omitted in FIG. 8 to clearly illustrate the relationship between the buffer layer **818** and the first die **110** and/or the stiffener ring **104**.

(67) Referring to FIG. 8, the package structure **P8** is similar to the package structure **P5** of FIG. 5, that is, the configurations, materials, and functions of the package structure **P8** are similar to those of the package structure **P5**, and thus the details are omitted herein. In the present embodiment, the buffer layer **818** of the package structure **P8** has a width **818w** greater than the width **110w** of the first die **110**, and the buffer layer **818** further extends to cover the top surfaces of the second dies **120** aside the first die **110**. In some embodiments, the width **818w** of the buffer layer **818** may be extended from the first sidewall **120s1** of the left second die **120** and the second sidewall **120s2** of the right second die **120**. In such embodiment, the buffer layer **818** is able to further reduce the stress between the second dies **120** and the stiffener ring **104**. In some embodiments, the buffer layer **818** may be disposed between the first portion **104A** of the stiffener ring **104** and the first die **110**. That is, the buffer layer **818** has a length **8181** within a range between the first side **104s1** of the stiffener ring **104** and the first sidewall **110s1** of the first die **110**. In some alternative embodiments, the length **8181** of the buffer layer **818** may be widened, so that the buffer layer **818** further covers the top surface **104t** of the first portion **104A** of the stiffener ring **104**, as shown in the cross-sectional view of FIG. 2.

(68) FIG. 9 illustrates a package structure **P9** with a buffer layer **918** embedded in the lid layer in

accordance with a ninth embodiment. In the present embodiment, the lid layer is omitted in FIG. 9 to clearly illustrate the relationship between the buffer layer **918** and the first die **110** and/or the stiffener ring **104**.

(69) Referring to FIG. 9, the package structure **P9** is similar to the package structure **P8** of FIG. 8, that is, the configurations, materials, and functions of the package structure **P9** are similar to those of the package structure **P8**, and thus the details are omitted herein. The main difference between the package structure **P9** and the package structure **P8** lies in that the package structure **P9** has two second dies **120** offset from a center of the substrate **100** to close to the first portion **104A** of the stiffener ring **104**. Accordingly, the second dies **120** are also referred to as eccentric dies. When the second dies **120** are offset from the center of the substrate **100** to make more spaces **SP** for the passive components, the thermally-induced stress will focus on the first side **104s1** of the stiffener ring **104** close to the second dies **120**. In this case, the stress due to the CTE mismatch may cause the delamination or crack issue of the adhesive layers **102** and **106** on and below the stiffener ring **104**. In order to solve the said localized stress concentration issue, in the present embodiment, as shown in FIG. 9, the buffer layer **918** further extends to cover the top surfaces of the second dies **120** aside the first die **110**, and the buffer layer **918** may relieve the stress concentrated on the first side **104s1** of the stiffener ring **104** close to the second dies **120**, thereby avoiding the crack and/or delamination issue of the adhesive layers **102/106** and enhancing the reliability of the package structure **P9**.

(70) FIG. 10 illustrates a package structure **P10** with a buffer layer **1018** embedded in the lid layer in accordance with a tenth embodiment. In the present embodiment, the lid layer is omitted in FIG. 10 to clearly illustrate the relationship between the buffer layer **1018** and the first die **110** and/or the stiffener ring **104**.

(71) Referring to FIG. 10, the package structure **P10** is similar to the package structure **P7** of FIG. 7, that is, the configurations, materials, and functions of the package structure **P10** are similar to those of the package structure **P7**, and thus the details are omitted herein. In the present embodiment, the buffer layer **1018** of the package structure **P10** includes at least four sub-layers **1018a**, **1018b**, **1018c**, and **1018d** respectively covering two corners **110c** of the first die **110** and two corners **120c** of the second dies **120**. Usually, the highest stress may be at the regions close to the corners **110c** of the first die **110** and the corners **120c** of the second dies **120**. In such embodiment, the buffer layer **1018** is able to provide a better protection to reduce the stress concentrated at the corners **110c** of the first die **110** and the corners **120c** of the second dies **120**.

(72) FIG. 11 illustrates a package structure **P11** with a buffer layer **1118** embedded in the lid layer in accordance with an eleventh embodiment. In the present embodiment, the lid layer is omitted in FIG. 11 to clearly illustrate the relationship between the buffer layer **1118** and the first die **110** and/or the stiffener ring **104**.

(73) Referring to FIG. 11, the package structure **P11** is similar to the package structure **P10** of FIG. 10, that is, the configurations, materials, and functions of the package structure **P11** are similar to those of the package structure **P10**, and thus the details are omitted herein. The main difference between the package structure **P11** and the package structure **P10** lies in that the package structure **P11** has two second dies **120** offset from a center of the substrate **100** to close to the first portion **104A** of the stiffener ring **104**. Accordingly, the second dies **120** are also referred to as eccentric dies. When the second dies **120** are offset from the center of the substrate **100** to make more spaces **SP** for the passive components, the thermally-induced stress will focus on the first side **104s1** of the stiffener ring **104** close to the second dies **120**. In this case, the stress due to the CTE mismatch may cause the delamination or crack issue of the adhesive layers **102** and **106** on and below the stiffener ring **104**. In order to solve the said localized stress concentration issue, in the present embodiment, as shown in FIG. 11, the buffer layer **1118** includes at least four sub-layers **1118a**, **1118b**, **1118c**, and **1118d** respectively covering two corners **110c** of the first die **110** and two corners **120c** of the second dies **120**. Therefore, the buffer layer **1118** may relieve the stress

concentrated at the corners **110c** of the first die **110** and the corners **120c** of the second dies **120**, thereby avoiding the crack and/or delamination issue of the adhesive layers **102/106** and enhancing the reliability of the package structure **P11**.

(74) FIG. **12** illustrates a package structure **P12** with a buffer layer **1218** embedded in the lid layer in accordance with a twelfth embodiment. In the present embodiment, the lid layer is omitted in FIG. **12** to clearly illustrate the relationship between the buffer layer **1218** and the first die **110** and/or the stiffener ring **104**.

(75) Referring to FIG. **12**, the package structure **P12** is similar to the package structure **P1** of FIG. **1A**, but the buffer layer **1218** surrounds all sidewalls of the first die **110** and the second dies **120** along the inner sidewall **103**. In such embodiment, the all-around buffer layer **1218** is able to comprehensively reduce the stress of the entire stiffener ring **104**. The all-around buffer layer **1218** may be also offset along a first direction Y, from a center of the package, corresponding to the eccentric first die **110**, and substantially symmetrical along a second direction X in some embodiment, but not limited thereto.

(76) Although the buffer layer **1218** illustrated in FIG. **12** is a continuous structure, the embodiments of the present disclosure are not limited thereto. In other embodiments, a package structure **P13** has a buffer layer **1318** with a non-continuous structure, as shown in FIG. **13**. In some alternative embodiments, the buffer layer **518, 618, 718, 818, 918, 1018** or **1118** of the package structure **P5, P6, P7, P8, P9, P10** or **P11** with the continuous structure can also be replaced by the non-continuous structure.

(77) Further, the package structures **P5** to **P13** of FIGS. **5-13** illustrate the first die **110** is an eccentric die offset from a center of the accommodation area **AA**. However, the embodiments of the present disclosure are not limited thereto. In some alternative embodiments, the first die **110** may be a non-eccentric die. That is, as shown in a package structure **P14** of FIG. **14**, the first distance **D1** between the first sidewall **110s1** of the first die **110** and the first portion **104A** is substantially equal to the second distance **D2** between the second sidewall **110s2** of the first die **110** and the second portion **104B**. In such embodiment, whether the first die **110** is close to any side of the stiffener ring **104** or not, as long as a distance between the first die **110** and the stiffener ring **104** is close enough to cause excessive stress, the buffer layer **1418** is able to solve the crack or delamination issue of the adhesive layers **102/106**, thereby improving the reliability and the yield of the package structure **P14**.

(78) Although the buffer layer **1418** illustrated in FIG. **14** is an all-around buffer layer, the embodiments of the present disclosure are not limited thereto. In other embodiments, the buffer layer **1418** of the package structure **P14** may be the same configuration with the buffer layer **518, 618, 718, 818, 918, 1018, 1118** or **1318** of the package structure **P5, P6, P7, P8, P9, P10, P11** or **P13**.

(79) Moreover, the stiffener ring **304** with the slant sidewall **305** illustrated in FIG. **3A** may be added to any one of the buffer layers **518, 618, 718, 818, 918, 1018, 1118, 1218**, and **1318** of the package structures **P5, P6, P7, P8, P9, P10, P11, P12**, and **P13**, so as to achieve the effect of dramatically reducing the stress due to CTE mismatch.

(80) In accordance with an embodiment, a package structure includes a substrate, a stiffener ring, an eccentric die, a lid layer, and a buffer layer. The stiffener ring is disposed on the substrate. The stiffener ring has an inner perimeter to enclose an accommodation area. The eccentric die is disposed within the accommodation area on the substrate. The eccentric die is offset from a center of the accommodation area to close to a first side of the stiffener ring. The lid layer is disposed on the stiffener ring and overlays the eccentric die. The buffer layer is embedded in the lid layer between the first side of the stiffener ring and the eccentric die. The buffer layer has a thickness less than a thickness of the lid layer.

(81) In accordance with an embodiment, a package structure includes a package substrate, a first die, a stiffener ring, a lid layer, and an embedded buffer. The first die is disposed on the package

substrate and has a first sidewall and a second sidewall opposite to each other. The stiffener ring is disposed on the package substrate to surround the first die, wherein the stiffener ring has an inner sidewall facing the first die, and the inner sidewall at least has a slant sidewall facing the first sidewall of the first die. The lid layer is disposed on the stiffener ring and overlying the first die. The embedded buffer connects a first portion of the lid layer overlying the first die and a second portion of the lid layer overlying the stiffener ring, wherein the embedded buffer has a bottom surface higher than a bottom surface of the lid layer.

(82) In accordance with an embodiment, a method of forming a package structure includes: forming a first die on a package substrate, wherein the first die has a first sidewall and a second sidewall opposite to each other; forming a plurality of second dies side by side on the package substrate, wherein the first die is formed between the plurality of second dies; forming a stiffener ring on the package substrate to surround the first die and the plurality of second dies; and forming a lid structure on the stiffener ring to overlay the first die and the plurality of second dies. The lid structure includes: a body portion; and an embedded portion, at least formed between the first sidewall of the first die and the stiffener ring, wherein the embedded portion is connected to the body portion by a glue layer.

(83) In accordance with an embodiment, a package structure includes a package substrate, a first die, a plurality of second dies, a stiffener ring, and a lid structure. The first die is disposed on the package substrate and having a first sidewall and a second sidewall opposite to each other. The plurality of second dies are side by side disposed on the package substrate, wherein the first die is disposed between the plurality of second dies. The stiffener ring is disposed on the package substrate to surround the first die and the plurality of second dies. The lid structure is disposed on the stiffener ring and overlying the first die and the plurality of second dies. The lid structure includes a body portion; and an embedded portion at least disposed between the first sidewall of the first die and the stiffener ring. The embedded portion is connected to the body portion by a glue layer.

(84) The foregoing outlines features of several embodiments so that those skilled in the art may better understand the aspects of the present disclosure. Those skilled in the art should appreciate that they may readily use the present disclosure as a basis for designing or modifying other processes and structures for carrying out the same purposes and/or achieving the same advantages of the embodiments introduced herein. Those skilled in the art should also realize that such equivalent constructions do not depart from the spirit and scope of the present disclosure, and that they may make various changes, substitutions, and alterations herein without departing from the spirit and scope of the present disclosure.

Claims

1. A method of forming a package structure, comprising: forming a first die on a package substrate, wherein the first die has a first sidewall and a second sidewall opposite to each other; forming a stiffener ring on the package substrate to surround the first die, wherein the stiffener ring has a first inner sidewall and a second inner sidewall opposite to each other, a first distance between the first sidewall of the first die and the first inner sidewall of the stiffener ring is less than a second distance between the second sidewall of the first die and the second inner sidewall of the stiffener ring, and the first sidewall of the first die encloses a space with the first inner sidewall of the stiffener ring; forming a lid layer on the stiffener ring to overlay the first die; forming an opening to penetrate through a top surface and a bottom surface of the lid layer, wherein the opening is directly over the space enclosed by the first sidewall of the first die and the first inner sidewall of the stiffener ring; and forming a stress-relief layer in the opening.

2. The method of claim 1, further comprising: widening an upper portion of the opening to form a narrower lower opening and a wider upper opening.

3. The method of claim 2, wherein the stress-relief layer is formed in the wider upper opening without extending into the narrower lower opening.
 4. The method of claim 1, wherein the stress-relief layer and the lid layer have different materials.
 5. The method of claim 1, wherein the stress-relief layer is softer than the lid layer.
 6. The method of claim 1, wherein the stress-relief layer is connected to the lid layer by a glue layer.
 7. The method of claim 1, wherein the stress-relief layer has a thickness less than a thickness of the lid layer.
 8. The method of claim 1, further comprising: forming a plurality of second dies side by side on the package substrate before forming the stiffener ring, wherein the first die is formed between the plurality of second dies.
 9. A method of forming a package structure, comprising: forming a first die on a package substrate, wherein the first die has a first sidewall and a second sidewall opposite to each other; forming a stiffener ring on the package substrate to surround the first die, wherein the stiffener ring has an inner sidewall facing the first die, and the inner sidewall at least has a slant sidewall facing the first sidewall of the first die; forming a lid layer on the stiffener ring to overlay the first die; and forming an embedded buffer in the lid layer, wherein the embedded buffer connects a first portion of the lid layer overlying the first die and a second portion of the lid layer overlying the stiffener ring, and the embedded buffer has a bottom surface higher than a bottom surface of the lid layer.
 10. The method of claim 9, wherein the inner sidewall of the stiffener ring has a vertical sidewall facing the second sidewall of the first die.
 11. The method of claim 10, wherein a first distance between the first sidewall of the first die and the slant sidewall of the stiffener ring is less than or equal to a second distance between the second sidewall of the first die and the vertical sidewall of the stiffener ring.
 12. The method of claim 9, further comprising: a plurality of second dies, side by side disposed on the package substrate, wherein the first die is disposed between the plurality of second dies; a thermal interface material (TIM) disposed between the first die and the lid layer a first adhesive layer, disposed between the stiffener ring and the package substrate; and a second adhesive layer, disposed on the stiffener ring, wherein the lid layer is adhered on the stiffener ring by the second adhesive layer, and overlays the first die and the plurality of second dies.
 13. The method of claim 12, wherein the first die has a coefficient of thermal expansion (CTE) less than a CTE of the plurality of second dies.
 14. The method of claim 9, wherein the stiffener ring has an outer sidewall opposite to the inner sidewall, and the outer sidewall protrudes from a sidewall of the package substrate.
 15. The method of claim 9, wherein the embedded buffer and the lid layer have different materials.
 16. The method of claim 9, wherein the embedded buffer is softer than the lid layer.
 17. A method of forming a package structure, comprising: providing a stiffener ring, wherein the stiffener ring has an inner perimeter to enclose an accommodation area; placing a die within the accommodation area, wherein the die is offset from a center of the accommodation area to close to a first side of the stiffener ring; forming a lid layer to cover the stiffener ring and the die; and forming a buffer layer in the lid layer between the first side of the stiffener ring and the die, wherein the buffer layer has a bottom surface higher than a bottom surface of the lid layer.
 18. The method of claim 17, wherein the buffer layer further extends to cover at least two corners of the die.
 19. The method of claim 17, wherein the buffer layer further extends to cover a top surface of the stiffener ring.
 20. The method of claim 17, wherein the buffer layer surrounds all sidewalls of the die.
-