

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407698
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Yamamoto; Takumi et al.

Information processing device, information processing method, and computer readable medium

Abstract

A normal classification unit (**101**) extracts a true positive access that is known to be an access aimed to attack and that has been determined by a detection unit (**102**) to be an access aimed to attack. A modification unit (**107**) modifies a feature of the true positive access by using a feature of a true negative access that is known to be a normal access and that has been determined by the detection unit (**102**) to be a normal access.

Inventors:	Yamamoto; Takumi (Tokyo, JP), Kawauchi; Kiyoto (Tokyo, JP)
Applicant:	Mitsubishi Electric Corporation (Tokyo, JP)
Family ID:	81974303
Assignee:	MITSUBISHI ELECTRIC CORPORATION (Tokyo, JP)
Appl. No.:	18/297035
Filed:	April 07, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230262075 A1	Aug. 17, 2023

Related U.S. Application Data

continuation parent-doc WO PCT/JP2020/045452 20201207 PENDING child-doc US 18297035

Publication Classification

Int. Cl.: H04L9/40 (20220101)

U.S. Cl.:

CPC **H04L63/1416** (20130101); **H04L63/1441** (20130101);

Field of Classification Search

CPC: G06F (21/55); H04L (63/1425); H04L (63/14); H04L (63/1408); H04L (63/1433); H04L (63/1441); H04L (63/145)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2017/0061322	12/2016	Chari et al.	N/A	N/A
2017/0345294	12/2016	Hirotsu	N/A	G08G 1/0112
2018/0115568	12/2017	Du	N/A	N/A
2019/0034836	12/2018	Chari	N/A	G06N 20/20
2019/0080089	12/2018	Chen	N/A	G06N 20/10
2019/0294803	12/2018	Yamamoto	N/A	G06F 21/57
2019/0384910	12/2018	Orihara et al.	N/A	N/A
2021/0157909	12/2020	Yamamoto et al.	N/A	N/A
2023/0247035	12/2022	Matsubayashi	726/23	H04L 63/1425

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
2015-114833	12/2014	JP	N/A
2018-67304	12/2017	JP	N/A
6548837	12/2018	JP	N/A
2019-185183	12/2018	JP	N/A
6698956	12/2019	JP	N/A
WO 2018/159361	12/2017	WO	N/A
WO 2019/073557	12/2018	WO	N/A

OTHER PUBLICATIONS

Maryam Nezhadkamali, Android malware detection based on overlapping of static features, Oct. 26-27, 2017. cited by examiner

International Search Report (PCT/ISA/210) issued in PCT/JP2020/045452, dated on Mar. 2, 2021,. cited by applicant

Steve T.K. Jan et al., “Throwing Darts in the Dark? Detecting Bots with Limited Data using Neural Data Augmentation”, Security & Privacy 2020, (<https://people.cs.vt.edu/vbimal/publications/syntheticdatasp20.pdf>), 17 pages. cited by applicant

German Office Action for German Application No. 11 2020 007 653.9, dated Mar. 5, 2024, with partial translation. cited by applicant

Pham et al., “Generating Artificial Attack Data for Intrusion Detection Using Machine Learning”, Proceedings of the 5th Symposium on Information and Communication Technology, 2014, pp. 286-291. cited by applicant

Chinese Office Action and Search Report for Chinese Application No. 202080107438.3, dated Apr. 30, 2025, with English translation. cited by applicant

Background/Summary

CROSS REFERENCE TO RELATED APPLICATIONS (1) This application is a continuation of PCT International Application No. PCT/JP2020/045452, filed on Dec. 7, 2020, all of which is hereby expressly incorporated by reference into the present application.

TECHNICAL FIELD

(1) The present disclosure relates to an attack detection technique.

BACKGROUND ART

(2) In recent years, a targeted attack that targets a specific company or a specific organization has been increasing. Due to networking of a control system, a cyber-attack on an important infrastructure such as a power plant or a gas plant has been a threat and has been a serious concern that threatens national security.

(3) On the other hand, in the field of security monitoring, there is continuous shortage of staff who needs specialized knowledge. Therefore, there is a need for a technique that is able to detect a cyber-attack with high accuracy and efficiency, even with a small number of staff.

(4) A rule-based detection technique has been known for a long time as a technique that monitors a cyber-attack. The rule-based detection technique uses a rule (signature) that detects a known malicious pattern or a rule that detects an attack technique or behavior of an attacker.

(5) However, sophistication of attacks and an increase in unknown attacks have made it difficult to define a rule in advance and this has been bothering staff of a Security Operation Center (SOC). Further, it is required to manually adjust a rule for each system to be monitored. Therefore, the limit of the rule-based detection technique is approaching. For this reason, an advanced detection technique is desired in which a rule is not required to be defined in advance or a boundary that discriminates between normal and abnormal is automatically determined. As a technique to realize such advanced detection technique, Artificial Intelligence (hereinafter abbreviated as AI) such as machine learning is considered. The AI learns data on a plurality of classes prepared in advance and automatically finds a boundary that separates the classes. If a large amount of data for each class can be prepared, the AI is able to properly find the boundary. If the AI can be applied to monitor a cyber-attack, it is expected that the AI takes over defining and updating a rule which have been performed by staff who has specialized knowledge and skills.

(6) However, in network security, there is a problem in that it is difficult to prepare a large amount of data for each class, which is the most important issue for the AI. An attack rarely occurs and it is very difficult to prepare a large amount of attack data for learning. Therefore, it is required to increase the attack data by using any kind of method and use the increased attack data for learning.

(7) In addition, abilities of an attacker have been increasing day by day. The attacker nowadays fully investigates and understands information on an organization to be attacked, and launches an attack without being noticed by an attack detection system. An internal crime has been also increasing and it is considered that a sophisticated attack that utilizes the information on the organization to be attacked, will increase in the future. The sophistication of attack data is also required to cope with an attack that has been cleverly designed and developed to have features which are similar to features in a normal condition in order to avoid detection.

(8) To solve a problem in that it is difficult to prepare a large amount of abnormal (attack) data that avoids detection, there are techniques that automatically generate a large number of attack samples that avoid detection and improve accuracy of an attack detection technique.

(9) As existing techniques to generate attack samples that avoid detection, there are a technique of Patent Literature 1 and a technique of Patent Literature 2.

(10) Patent Literature 1 discloses a technique to automatically generate for evaluating security products, sophisticated attack samples designed to have features similar to those in a normal condition. Patent Literature 2 discloses a technique to automatically generate for evaluating security products, a false detection (False Positive: FP) in which a normal event which is not supposed to be detected is detected and a detection omission (False Negative: FN) in which an event which is supposed to be detected is not detected.

(11) Both techniques change a feature vector of an attack so as to cross a decision boundary of a normal model that has been obtained by learning behavior of normal data. Further, both techniques generate an attack on a simulated environment to have a feature corresponding to a feature vector that has crossed the boundary. Depending on both techniques, it is possible to generate a realistic and sophisticated attack by checking matters such as environment, a restriction on an attack or the like, and presence or absence of an attack function.

CITATION LIST

Patent Literature

(12) Patent Literature 1: JP 6548837 B2 Patent Literature 2: JP 6698956 B2

SUMMARY OF INVENTION

Technical Problem

(13) In the technique of Patent Literature 1 and the technique Patent Literature 2, a feature vector is modified so as to cross a decision boundary of a detection system on a feature space and search for a sample that avoids detection. For this reason, it has been difficult to efficiently apply these techniques to an attack detection technique in which a feature space is nonlinear and high-dimensional.

(14) In general, the more highly accurate the attack detection system is, the more high-dimensional and nonlinear the feature space is. Therefore, it is difficult to inversely convert a representation on the feature space into information in a real space. Hence, it is difficult to acquire a sample existing in the real space, from an attack sample that avoids detection and found on the feature space. This search is expected to be haphazard and inefficient.

(15) In view of the above, the present disclosure mainly aims to efficiently search for an attack that is actually able to exist in a real space and avoids detection.

Solution to Problem

(16) An information processing device according to the present disclosure includes: an extraction unit to extract a true positive access that is known to be an access aimed to attack and that has been determined by an attack detection system to be an access aimed to attack; and a modification unit to modify a feature of the true positive access by using a feature of a true negative access that is known to be a normal access and that has been determined by the attack detection system to be a normal access.

Advantageous Effects of Invention

(17) According to the present disclosure, it is possible to efficiently search for an attack that is actually able to exist in a real space and avoids detection.

Description

BRIEF DESCRIPTION OF DRAWINGS

(1) FIG. 1 is a diagram illustrating a hardware configuration example of an attack log generation device according to Embodiment 1.

(2) FIG. 2 is a diagram illustrating a functional configuration example of the attack log generation device according to Embodiment 1.

- (3) FIG. 3 is a flowchart illustrating an operation example of the attack log generation device according to Embodiment 1.
- (4) FIG. 4 is a diagram illustrating an internal configuration example of an attack generation unit according to Embodiment 1.
- (5) FIG. 5 is a diagram illustrating a configuration example of a simulated environment according to Embodiment 1.
- (6) FIG. 6 is a diagram illustrating an internal configuration example of a vicinity extraction unit according to Embodiment 1.
- (7) FIG. 7 is a diagram illustrating an internal configuration example of a tendency extraction unit according to Embodiment 1.
- (8) FIG. 8 is a diagram illustrating an internal configuration example of a feature modification unit according to Embodiment 1.
- (9) FIG. 9 is a flowchart illustrating an operation example the feature modification unit according to Embodiment 1.
- (10) FIG. 10 is a flowchart illustrating an operation example of the feature modification unit according to Embodiment 1.
- (11) FIG. 11 is a flowchart illustrating an operation example of the feature modification unit according to Embodiment 1.
- (12) FIG. 12 is a diagram illustrating a functional configuration example of the attack log generation device according to Embodiment 2.
- (13) FIG. 13 is a flowchart illustrating an operation example of the attack log generation device according to Embodiment 2.
- (14) FIG. 14 is a diagram illustrating an internal configuration example of the vicinity extraction unit according to Embodiment 2.
- (15) FIG. 15 is a diagram illustrating an internal configuration example of the tendency extraction unit according to Embodiment 2.
- (16) FIG. 16 is a diagram illustrating an internal configuration example of the feature modification unit according to Embodiment 2.
- (17) FIG. 17 is a flowchart illustrating an operation example of the feature modification unit according to Embodiment 2.
- (18) FIG. 18 is a flowchart illustrating an operation example of the feature modification unit according to Embodiment 2.
- (19) FIG. 19 is a flowchart illustrating an operation example of the feature modification unit according to Embodiment 2.

DESCRIPTION OF EMBODIMENTS

(20) Embodiments will be described hereinafter with reference to the drawings. In the following description of the embodiments and the drawings, portions denoted by the same reference signs indicate the same or corresponding portions.

Embodiment 1

Overview

(21) In the following, an access is called a true negative access, that is known to be a normal access and that has been determined by an attack detection system to be a normal access.

(22) Further, an access is called a true positive access, that is known to be an attack access and that has been determined by the attack detection system to be an attack access.

(23) Further, an access is called a false negative access, that is known to be an attack access aimed to attack, but that has been mistakenly determined by the attack detection system to be a normal access. The false negative access is an access that causes a detection omission.

(24) Further, an access is called a false positive access, that is known to be a normal access, but that has been mistakenly determined by the attack detection system to be an attack access. The false positive access is an access that causes a false detection.

(25) A normal log in which features of a normal access are indicated and an attack log in which features of an attack access are indicated, are used in the present embodiment. The normal log includes a plurality of fields and a value that represents a feature of the normal access is described in each field. Similarly, the attack log includes the same plurality of fields as those in the normal log and a value that represents a feature of the attack access is described in each field.

(26) Then, in the present embodiment, a true negative access log is extracted from normal logs and a true positive access log is extracted from attack logs. In addition, in the present embodiment, a feature of a true positive access is modified by using a feature of a true negative access. In the present embodiment, the feature of the true positive access is modified so that a modified true positive access which is the true positive access whose feature has been modified is determined by the attack detection system to be a normal access. That is, in the present embodiment, the feature of the true positive access is modified so that the true positive access turns to a false negative access. In this way, in the present embodiment, an attack sample of a false negative access that is able to avoid detection operated by the attack detection system, is acquired by modifying the feature of the true positive access.

Description of Configuration

(27) FIG. 1 illustrates a hardware configuration example of an attack log generation device **100** according to the present embodiment. Further, FIG. 2 illustrates a functional configuration example of the attack log generation device **100** according to the present embodiment.

(28) The attack log generation device **100** according to the present embodiment is a computer. The attack log generation device **100** is equivalent to an information processing device. Further, an operation procedure of the attack log generation device **100** is equivalent to an information processing method. Further, a program that implements operation of the attack log generation device **100** is equivalent to an information processing program.

(29) As illustrated in FIG. 1, the attack log generation device **100** includes a processor **901**, a main storage device **902**, an auxiliary storage device **903**, a keyboard **904**, a mouse **905**, and a display device **906**, as pieces of hardware.

(30) The auxiliary storage device **903** stores programs that implement functions of a normal classification unit **101**, a detection unit **102**, an attack generation unit **103**, a vicinity extraction unit **104**, a tendency extraction unit **105**, and a feature modification unit **106** illustrated in FIG. 2.

(31) These programs are loaded from the auxiliary storage device **903** into the main storage device **902**. Then, the processor **901** executes these programs and performs operation of the normal classification unit **101**, the detection unit **102**, the attack generation unit **103**, the vicinity extraction unit **104**, the tendency extraction unit **105**, and the feature modification unit **106** to be described below.

(32) FIG. 3 schematically illustrates a state where the processor **901** executes the programs that implement the functions of the normal classification unit **101**, the detection unit **102**, the attack generation unit **103**, the vicinity extraction unit **104**, the tendency extraction unit **105**, and the feature modification unit **106**.

(33) Further, a detection avoidance attack log Database (DB) **111**, a normal log DB **112**, an attack log DB **113**, a normal log statistical information DB **114**, a true negative normal log DB **115**, a vicinity true negative normal log DB **116**, and a true negative normal log tendency DB **117** illustrated in FIG. 2 are implemented by the main storage device **902** or the auxiliary storage device **903**.

(34) The keyboard **904** and the mouse **905** receive a command from a user of the attack log generation device **100**. The display device **906** displays various information to the user of the attack log generation device **100**.

(35) The attack log generation device **100** may include a communication device not illustrated in FIG. 1.

(36) In FIG. 2, the normal classification unit **101** extracts a true negative access. More specifically,

the normal classification unit **101** extracts from normal logs in the normal log DB **112**, a normal log in a true negative state that has been determined by the detection unit **102** to be normal. In the normal log, a feature of a normal access is described in a plurality of fields. That is, the normal log defines the normal access. For this reason, the true negative access is defined by the normal log in the true negative state (hereinafter referred to as the true negative normal log) extracted by the normal classification unit **101**. The normal classification unit **101** stores the extracted true negative normal log in the true negative normal log DB **115**.

(37) Further, the normal classification unit **101** extracts a true positive access from attack logs. More specifically, the normal classification unit **101** extracts from the attack logs in the attack log DB **113**, an attack log in a true positive state that has been determined by the detection unit **102** to be an attack. In the attack log, a feature of an attack access generated by the attack generation unit **103** is described in a plurality of fields. That is, the attack log defines the attack access. For this reason, the true positive access is defined by the attack log in the true positive state (hereinafter referred to as the true positive attack log) extracted by the normal classification unit **101**. The normal classification unit **101** outputs the extracted true positive attack log to the vicinity extraction unit **104**.

(38) The normal classification unit **101** is equivalent to an extraction unit. Further, a process performed by the normal classification unit **101** is equivalent to an extraction process.

(39) The detection unit **102** functions as the attack detection system.

(40) More specifically, the detection unit **102** uses machine learning to detect an attack access. As described above, a normal log determined by the detection unit **102** to be normal is stored in the true negative normal log DB **115** by the normal classification unit **101**, as the true negative normal log. Further, an attack log determined by the detection unit **102** to be an attack is output to the vicinity extraction unit **104** by the normal classification unit **101**, as the true positive attack log.

(41) The attack generation unit **103** generates an attack access along an attack scenario. Then, the attack generation unit **103** stores in the attack log DB **113**, a log that represents features of the attack access, as the attack log.

(42) The vicinity extraction unit **104**, the tendency extraction unit **105**, and the feature modification unit **106** are collectively referred to as a modification unit **107**.

(43) The modification unit **107** modifies the feature of the true positive access extracted by the normal classification unit **101**, by using the feature of the true negative access extracted by the normal classification unit **101**. More specifically, the modification unit **107** modifies the feature of the true positive access so that a modified true positive access which is the true positive access whose feature has been modified is determined by the detection unit **102** to be a normal access. Further, when the modified true positive access is determined by the detection unit **102** to be an attack access, the modification unit **107** modifies a feature of the modified true positive access by using a feature of the true negative access.

(44) A process performed by the modification unit **107** is equivalent to a modification process.

(45) The vicinity extraction unit **104** extracts from the true negative normal log DB **115**, a true negative normal log in the vicinity of the true positive attack log (hereinafter referred to as a vicinity true negative normal log) extracted by the normal classification unit **101**.

(46) More specifically, the vicinity extraction unit **104** extracts from among true negative normal logs included in the true negative normal log DB **115**, a true negative normal log having a feature similar to the feature of the true positive attack log, as the vicinity true negative normal log.

(47) When there is a plurality of features in the true positive attack log, the tendency extraction unit **105** calculates an importance degree (feature importance) of each of the plurality of features of the true positive attack log. The tendency extraction unit **105** calculates the importance degree of each of the plurality of features of the true positive attack log so that higher importance degree is set to a feature which has higher degree of distinguishing between the true negative access and the true positive access.

- (48) Further, the tendency extraction unit **105** selects from the plurality of features of the true positive attack log, a feature whose importance degree matches with a selection condition.
- (49) The feature modification unit **106** modifies the feature of the true positive attack log selected by the tendency extraction unit **105**, by using the corresponding feature of the true negative normal log.
- (50) Then, the feature modification unit **106** stores in the detection avoidance attack log DB **111**, the true positive attack log after modification, as a detection avoidance attack log.
- (51) The detection avoidance attack log DB **111** stores detection avoidance attack logs.
- (52) The normal log DB **112** stores normal logs.
- (53) The attack log DB **113** stores attack logs.
- (54) The normal log statistical information DB **114** stores statistical information on normal logs (hereinafter referred to as normal log statistical information).
- (55) The true negative normal log DB **115** stores true negative normal logs.
- (56) The vicinity true negative normal log DB **116** stores vicinity true negative normal logs extracted by the vicinity extraction unit **104**.
- (57) The true negative normal log tendency DB **117** stores tendencies of vicinity true negative normal logs (hereinafter referred to as true negative normal log tendencies) extracted by the vicinity extraction unit **104**.

Description of Operation

- (58) Next, an operation example of the attack log generation device **100** according to the present embodiment will be described with reference to FIG. 3.
- (59) First, the normal classification unit **101** extracts a true negative normal log from normal logs (step **S1_1**).
- (60) More specifically, the detection unit **102** analyzes a large number of normal logs stored in advance in the normal log DB **112** and the detection unit **102** determines whether an access defined in a normal log is a normal access or an attack access.
- (61) Then, the normal classification unit **101** extracts a normal log determined by the detection unit **102** to be a normal access, as the true negative normal log.
- (62) Then, the normal classification unit **101** stores the extracted true negative normal log in the true negative normal log DB **115**.
- (63) Next, the attack generation unit **103** executes an attack and generates an attack log (step **S1_2**).
- (64) That is, the attack generation unit **103** performs an attack access and generates the attack log in which the feature of the attack access is indicated. Then, the attack generation unit **103** stores the generated attack log in the attack log DB **113**.
- (65) Next, the detection unit **102** analyzes the attack log and determines whether the access defined in the attack log is a normal access or an attack access (step **S1_3**).
- (66) When the detection unit **102** determines that the access defined in the attack log is the normal access (NO in step **S1_3**), the process proceeds to step **S1_8**.
- (67) In step **S1_8**, the access determined by the detection unit **102** to be the normal access is the attack access (false negative access) that is able to avoid detection operated by the detection unit **102**, so that the normal classification unit **101** stores the corresponding true positive attack log in the detection avoidance attack log DB **111**, as the detection avoidance attack log.
- (68) On the other hand, when the detection unit **102** determines that the access defined in the attack log is the attack access (YES in step **S1_3**), the process proceeds to step **S1_4**. That is, the access determined by the detection unit **102** to be the attack access is the attack access (true positive access) that is able to be detected by the detection unit **102**. Therefore, it is required to modify the feature of the true positive attack log to avoid detection operated by the detection unit **102**.
- (69) In step **S1_4**, the vicinity extraction unit **104** extracts a vicinity true negative normal log. That is, the vicinity extraction unit **104** extracts from the true negative normal log DB **115**, a true negative normal log in the vicinity of the attack log (true positive attack log) acquired in step **S1_3**.

(70) The detail of step **S1_4** will be described below.

(71) Next, the tendency extraction unit **105** calculates a tendency of a feature of the vicinity true negative normal log acquired in step **S1_4** (step **S1_5**).

(72) Next, the feature modification unit **106** modifies the true positive attack log so as to include the tendency of the feature of the vicinity true negative normal log, in the true positive attack log (step **S1_6**).

(73) That is, the feature modification unit **106** modifies each field of the true positive attack log so as to include a lot of tendencies of features of the vicinity true negative normal log calculated by the tendency extraction unit **105**.

(74) Next, the detection unit **102** determines whether the access (modified true positive access) defined in the true positive attack log (modified true positive attack log) which has been modified by the feature modification unit **106**, is a normal access or an attack access (step **S1_7**).

(75) When the detection unit **102** determines that the modified true positive access is the normal access (NO in step **S1_7**), the normal classification unit **101** stores the modified true positive attack log in the detection avoidance attack log DB **111**, as the detection avoidance attack log (step **S1_8**).

(76) The modified true positive access based on the modified true positive attack log is not able to be detected by the detection unit **102** as an attack, so that the modified true positive access is an attack access that is able to avoid detection operated by the attack detection system. For this reason, the normal classification unit **101** stores the modified true positive attack log in the detection avoidance attack log DB **111**, as the detection avoidance attack log.

(77) On the other hand, when the detection unit **102** determines that the modified true positive access is the attack access (YES in step **S1_7**), the process returns to step **S1_6**. Then, the feature modification unit **106** further modifies the modified true positive attack log by using the features of the vicinity true negative normal log (step **S1_6**).

(78) The above is the general flow of the operation of the attack log generation device **100**.

(79) The detail of the operation of the normal classification unit **101**, the detection unit **102**, the attack generation unit **103**, the vicinity extraction unit **104**, the tendency extraction unit **105**, and the feature modification unit **106** will be described below.

(80) The normal classification unit **101** causes the detection unit **102** to determine whether a large number of normal logs prepared in advance in the normal log DB **112** are normal or abnormal. The detection unit **102** determines whether a normal log is normal or abnormal. That is, the detection unit **102** determines whether a feature described in the normal log corresponds to a feature of a normal access or a feature of an attack access.

(81) The normal classification unit **101** extracts a normal log determined by the detection unit **102** to be normal, as the true negative normal log. Then, the normal classification unit **101** stores the extracted true negative normal log in the true negative normal log DB **115**. At this time, for categorical data (a domain, a method, a status code, or the like) of the normal log, the normal classification unit **101** calculates an occurrence frequency and a percentile of a unique value for each categorical data. Then, the normal classification unit **101** stores a dictionary consisting of a pair of the unique value and the percentile in the normal log statistical information DB **114**, as normal log statistical information. The percentile is an index that arranges frequencies of unique values in ascending order and indicates what percentage a certain unique value falls in. The normal classification unit **101** may store instead of the pair of the unique value and the percentile, a dictionary consisting of a pair of the unique value and the occurrence frequency in the normal log statistical information DB **114**, as normal log statistical information.

(82) The detection unit **102** acquires a log (a normal log or an attack log) from the normal classification unit **101**. Then, the detection unit **102** extracts a feature from the log and converts the extracted feature into a representation (feature vector) for inputting to a machine learning algorithm. Then, the detection unit **102** applies the feature vector to a learned detection model. In this way, the detection unit **102** estimates a class to which the log belongs.

(83) A method of learning a detection model by using learning data which has been provided with supervised information (a label) that indicates to which class of a normal access or an attack access the learning data belongs, is called supervised learning.

(84) When using the supervised learning, the detection unit **102** estimates by using the learned detection model, to which class of the normal access or the attack access the feature vector belongs.

(85) A method of learning a detection model by using only normal data as learning data without preparing supervised information, is called unsupervised learning. When using the unsupervised learning, the detection unit **102** estimates by using the learned detection model, whether the feature vector belongs to the class of the normal access or not.

(86) FIG. 4 illustrates an internal configuration example of the attack generation unit **103**.

(87) As illustrated in FIG. 4, the attack generation unit **103** is configured with a simulated environment **1031**, an attack execution unit **1032**, an attack module **1033**, an attack scenario DB **1034**, and a log collection unit **1035**.

(88) FIG. 5 illustrates a configuration example of the simulated environment **1031**.

(89) The simulated environment **1031** is a virtual environment that simulates a business network of a company or an organization.

(90) The simulated environment **1031** is configured with, for example, a proxy server, a firewall, a file server, an Active Directory (AD) server, an in-company Web server, a user terminal, a springboard terminal, and a pseudo-Internet. The pseudo-Internet includes a Command and Control server of an attacker.

(91) The attack module **1033** is a plurality of basic modules that implements each step of Reconnaissance, Weaponization, Delivery, Exploitation, Installation, Command and Control, Lateral Movement, and Actions on Objective in Cyber Kill Chain.

(92) Reconnaissance is a step to collect information (an e-mail address, or the like) on a target from public information or the like.

(93) Weaponization is a step to generate an exploit kit, a malware, or the like used for an attack.

(94) Delivery is a step such as transmitting to the target, an e-mail to which a malware is attached or an e-mail with a malicious link, or directly accessing a system of the target.

(95) Exploitation is a step such as causing the target to execute an attack file such as the malware or causing the target to access to the malicious link.

(96) Installation is a step to cause Exploitation to success and infect the target with the malware.

(97) Command and Control (C&C) is a step to enable the malware and a C&C server to communicate with each other and enable the C&C server to perform remote operation on the target.

(98) Lateral Movement is a step to enable the C&C server to use a local password hash to break into another computer.

(99) Actions on Objective is a step to execute an objective of the attacker such as information exploitation, falsification, data destruction, or service suspension.

(100) The attack module **1033** is a program that implements these functions.

(101) The attack scenario DB **1034** stores attack scenarios.

(102) The attack scenario is information in which a combination of attack modules **1033** and parameters (for example, a communication frequency, a communication destination domain, an infected terminal, or the like) are defined according to a general targeted attack. In order to have variations in the attack, a large number of attack scenarios are prepared in the attack scenario DB **1034**.

(103) The attack execution unit **1032** selects one attack scenario stored in the attack scenario DB **1034**. Then, the attack execution unit **1032** executes the attack module **1033** on the simulated environment **1031** in obedience to the selected attack scenario.

(104) The log collection unit **1035** collects logs on the simulated environment **1031** at a time of executing the attack and stores the collected logs as attack logs in the attack log DB **113**.

(105) The attack log includes, for example, a proxy server log, an AD server log, a file server log, a

firewall log, or the like.

(106) FIG. 6 illustrates an internal configuration example of the vicinity extraction unit **104**.

(107) The vicinity extraction unit **104** is configured with a feature extraction unit **1041**, a feature expression unit **1042**, and a vicinity calculation unit **1043**. Further, the vicinity extraction unit **104** uses the normal log DB **112**, the true negative normal log DB **115**, and the vicinity true negative normal log DB **116**.

(108) The feature extraction unit **1041** extracts prescribed features from x pieces (assuming one piece) of true positive attack logs and y pieces of true negative normal logs. y is a number sufficiently greater than x.

(109) The feature expression unit **1042** converts the features extracted from true positive attack logs and true negative normal logs into forms (feature vectors) that are easily processed in a machine learning algorithm. The feature expression unit **1042** converts categorical data such as a domain, a method, or a status codec into for example, One-hot encoding, or Frequency Encoding described in the reference below.

(110) Reference: Steve T. K. Jan, et al., Throwing Darts in the Dark? Detecting Bots with Limited Data using Neural Data Augmentation, Security & Privacy 2020

(<https://people.cs.vt.edu/vbimal/publications/syntheticdata-sp20.pdf>)

(111) Further, the feature expression unit **1042** normalizes or standardizes numerical data. By normalizing or standardizing the numerical data, the feature expression unit **1042** makes uniform the size of numerical data between types of the features.

(112) In addition, the vicinity calculation unit **1043** uses the feature vectors of the true positive attack logs and the feature vectors of the true negative normal logs to specify $K_{sub.0}$ pieces of vicinity true negative normal logs in the vicinity of each of the true positive attack logs. The total number of true negative normal logs in the vicinity of x pieces of true positive attack logs is assumed to be $K_{sub.1}$ pieces. $K_{sub.1} \geq K_{sub.0}$. Then, the vicinity calculation unit **1043** stores the specified $K_{sub.0}$ pieces of vicinity true negative normal logs in the vicinity true negative normal log DB **116**.

(113) The vicinity calculation unit **1043**, for example, uses a K-nearest neighbor (KNN) method to specify $K_{sub.0}$ pieces of vicinity true negative normal logs. The features or feature expressions to be used by the vicinity calculation unit **1043** to specify $K_{sub.0}$ pieces of vicinity true negative normal logs may differ from features or feature expressions to be used by the detection unit **102**. Further, the vicinity calculation unit **1043** uses Euclid distance or the like, as a distance scale.

(114) FIG. 7 illustrates an internal configuration example of the tendency extraction unit **105**.

(115) The tendency extraction unit **105** is configured with a feature extraction unit **1051**, a feature expression unit **1052**, an importance degree calculation unit **1053** and a tendency calculation unit **1054**. Further, the tendency extraction unit **105** uses the vicinity true negative normal log DB **116** and the true negative normal log tendency DB **117**.

(116) The feature extraction unit **1051** acquires from the vicinity true negative normal log DB **116**, $K_{sub.1}$ pieces of vicinity true negative normal logs. Further, the feature extraction unit **1051**, for example, acquires from the vicinity extraction unit **104**, x pieces (assuming one piece) of true positive attack logs.

(117) Then, similar to the feature extraction unit **1041**, the feature extraction unit **1051** extracts the prescribed features from $K_{sub.1}$ pieces of vicinity true negative normal logs and x pieces of true positive attack logs.

(118) Similar to the feature expression unit **1042**, the feature expression unit **1052** also converts the features extracted from $K_{sub.1}$ pieces of vicinity true negative normal logs and x pieces of true positive attack logs into forms (feature vectors) that are easily processed in a machine learning algorithm. The features and feature expressions that are converted by the feature expression unit **1052** into the feature vectors may be different from features and feature expressions used by the detection unit **102**.

(119) The importance degree calculation unit **1053** uses the feature vectors acquired by the feature expression unit **1052** to learn a discriminator (C1) that distinguishes between K.sub.0 pieces of vicinity true negative normal logs and x pieces of true positive attack logs. The importance degree calculation unit **1053** calculates for each of the feature vectors of the true positive attack logs, an importance degree of a feature (feature importance) which is a degree of distinguishing by the discriminator (C1) between K.sub.0 pieces of vicinity true negative normal logs and x pieces (for example, 1 piece) of true positive attack logs. The importance degree calculation unit **1053** calculates the feature importance of each of the feature vectors so that higher importance degree is set to a feature which has higher degree of distinguishing between the vicinity true negative normal logs and the true positive attack logs.

(120) Then, the importance degree calculation unit **1053** extracts features F.sub.11 to F.sub.1n1 which are the highest n.sub.1 features as to the importance degree. n.sub.1 is greater than or equal to 1. For example, the importance degree calculation unit **1053** calculates an importance degree with using random forest.

(121) The tendency calculation unit **1054** acquires statistical information on the features F.sub.11 to F.sub.1n1 of K.sub.1 pieces of vicinity true negative normal logs. The tendency calculation unit **1054** acquires for a feature which is categorical data, a central value (median, med.sub.1) and a most frequent value (mode, mod.sub.1) of a percentile in the categorical data, as the statistical information. Further, the tendency calculation unit **1054** acquires for a feature which is numerical data, a mean (μ .sub.1) and a standard deviation (σ .sub.1) of the numerical data, as the statistical information.

(122) Then, the tendency calculation unit **1054** stores the statistical information in the true negative normal log tendency DB **117**.

(123) FIG. **8** illustrates an internal configuration example of the feature modification unit **106**.

(124) The feature modification unit **106** is configured with a data modification unit **1061** and a verification unit **1062**. The feature modification unit **106** uses the detection avoidance attack log DB **111**.

(125) FIG. **9** illustrates an operation example of the data modification unit **1061** and the verification unit **1062**.

(126) First, the data modification unit **1061** checks whether there is an unchecked feature among the features F.sub.11 to F.sub.1n1 (step S2_1).

(127) When there is the unchecked feature (YES in step S2_1), the data modification unit **1061** selects an unchecked feature F.sub.1i (i is any of 1 to n1) (step S2_2).

(128) In the following, operation of the data modification unit **1061** will be described in a case where the feature F.sub.1i is the feature F.sub.11, as an example.

(129) Next, the data modification unit **1061** acquires an actual value of the feature F.sub.11 from a corresponding field in the true positive attack log (step S2_3).

(130) Then, the data modification unit **1061** generates a list.sub.11 (step S2_4). The list.sub.11 includes a modified value acquired by modifying the actual value of the feature F.sub.11 of the true positive attack log with an actual value of the feature F.sub.11 of the vicinity true negative normal log. That is, the list.sub.11 includes a plurality of modified values in which values of the feature F.sub.11 of K.sub.1 pieces of vicinity true negative normal logs have been reflected.

(131) A method of generating the list.sub.11 will be described below.

(132) The data modification unit **1061** also performs for other features F.sub.12 to F.sub.1n1, the processes from step S2_2 to step S2_4.

(133) When the processes from step S2_2 to step S2_4 are performed for all features F.sub.11 to F.sub.1n1 (NO in step S2_1), the data modification unit **1061** combines all modified values included in the list.sub.11 to a list.sub.1n1 of the features F.sub.11 to F.sub.1n1 and generates an attack log (modified true positive attack log) corresponding to each combination (step S2_5). When the number of modified values included in each list of the list.sub.11 to the list.sub.1n1 r.sub.1j (j is

1 to $n1$), a type of the generated attack log (modified true positive attack log) is $N = \Pi r.sub.1j$. The actual value of the true positive attack log is hold in a field that does not correspond to the features $F.sub.11$ to $F.sub.1n1$.

(134) Next, the verification unit **1062** verifies each modified true positive attack log (step **S2_6**).

(135) Specifically, the verification unit **1062** causes the detection unit **102** to determine whether the access defined in each modified true positive attack log corresponds to any of a normal access and an attack access.

(136) Then, the verification unit **1062** stores in the detection avoidance attack log DB **111**, the modified true positive attack log that has been determined by the detection unit **102** to be the normal access, as the detection avoidance attack log (step **S2_7**). When $X > 1$, the verification unit **1062** generates detection avoidance attack logs for all true positive attack logs, with using the same method.

(137) Next, a method of generating the list (the $list.sub.11$ to the $list.sub.1n1$) illustrated in step **S2_4** of FIG. **9** will be described with reference to FIG. and FIG. **11**. An example of generating the $list.sub.11$ for the feature $F.sub.11$ will be described below again.

(138) The data modification unit **1061** determines whether the feature $F.sub.11$ is categorical data or numerical data (step **S3_1**).

(139) The categorical data is a domain, a method, a status code, or the like. The numerical data is a request size, a time interval, or the like.

(140) When the feature $F.sub.11$ is the categorical data, the data modification unit **1061** acquires from a dictionary in normal log statistical information, a value of a percentile of the categorical data of the feature $F.sub.11$ and sets the acquired value of the percentile to $cat.sub.11$ (step **S3_2**). Further, from the true negative normal log tendency DB **117**, the data modification unit **1061** refers to a most frequent value $mod.sub.11$, as the statistical information on the feature $F.sub.11$ of $K.sub.1$ pieces of vicinity true negative normal logs (step **S3_2**).

(141) Next, the data modification unit **1061** compares a value of $cat.sub.11$ with a value of $mod.sub.11$ (step **S3_3**).

(142) When the value of $cat.sub.11$ is equal to or greater than the value of $mod.sub.11$ (NO in step **S3_3**, NO in step **S3_4**, and YES in step **S3_5**), the data modification unit **1061** updates the value of $cat.sub.11$ so that the value of $cat.sub.11$ approaches (decreases) by $\Delta.sub.11$ each to the value of $mod.sub.11$ and adds the updated value of $cat.sub.11$ to the $list.sub.11$ (step **S3_6**). When the value of $cat.sub.11$ has been already listed in the $list.sub.11$, the data modification unit **1061** overwrites the already listed value of $cat.sub.11$ with the new value of $cat.sub.11$. $\Delta.sub.11$ is a prescribed value.

(143) The data modification unit **1061** repeats the process of step **S3_6** while the value of $cat.sub.11$ is greater than or equal to the value of $mod.sub.11$ (YES in step **S3_5**).

(144) When the value of $cat.sub.11$ is less than the value of $mod.sub.11$ (NO in step **S3_5**), the process proceeds to step **S3_9**.

(145) When the value of $cat.sub.11$ is equal to the value of $mod.sub.11$ (NO in step **S3_3** and YES in step **S3_4**), the process proceeds to step **S3_9**.

(146) Further, when the value of $cat.sub.11$ is less than the value of $mod.sub.11$ (YES in step **S3_3** and YES in step **S3_7**), the data modification unit **1061** updates the value of $cat.sub.11$ so that the value of $cat.sub.11$ approaches (increases) by $\Delta.sub.11$ each to the value of $mod.sub.11$ and adds the updated value of $cat.sub.11$ to the $list.sub.11$ (step **S3_8**). When the value of $cat.sub.11$ has been already listed in the $list.sub.11$, the data modification unit **1061** overwrites the already listed value of $cat.sub.11$ with the new value of $cat.sub.11$.

(147) The data modification unit **1061** repeats the process of step **S3_8** while the value of $cat.sub.11$ is less than or equal to the value of $mod.sub.11$ (YES in step **S3_7**).

(148) When the value of $cat.sub.11$ is greater than the value of $mod.sub.11$ (NO in step **S3_7**), the process proceeds to step **S3_9**.

(149) In step S3_9, the data modification unit **1061** confirms the list.sub.11.

(150) In step S3_1, when the feature F.sub.11 is the numerical data, the data modification unit **1061** sets the value of the numerical data of the feature F.sub.11 to num.sub.11 (step S3_10). In addition, from the true negative normal log tendency DB **117**, the data modification unit **1061** refers to a mean μ .sub.11 and a standard deviation σ .sub.11 as the statistical information on the feature F.sub.11 of K.sub.1 pieces of vicinity true negative normal logs (step S3_10).

(151) Next, the data modification unit **1061** compares a value of num.sub.11 with a value of μ .sub.11 (step S3_11).

(152) When the value of num.sub.11 is greater than the value of μ .sub.11 (NO in step S3_11, NO in step S3_12, and YES in step S3_13), the data modification unit **1061** updates the value of num.sub.11 so that the value of num.sub.11 approaches (decreases) by Δ .sub.11 each to the value of μ .sub.11 and adds the updated value of num.sub.11 to the list.sub.11 (step S3_14). When the value of num.sub.11 has been already listed in the list.sub.11, the data modification unit **1061** overwrites the already listed value of num.sub.11 with the new value of num.sub.11.

(153) Δ .sub.11 is a prescribed value. This Δ .sub.11 may be the same value as Δ .sub.11 used in a case where the feature F.sub.11 is the categorical data, or may be a different value.

(154) The data modification unit **1061** repeats the process of step S3_14 while the value of num.sub.11 is greater than or equal to the value of $(\mu$.sub.11- τ .sub.11) (YES in step S3_13).

τ .sub.11 is also a prescribed value. For example, such as $3 \times \sigma$.sub.11, τ .sub.11 is considered to be defined with using a statistical value relating to the feature F.sub.11.

(155) When the value of num.sub.11 is less than $(\mu$.sub.11- τ .sub.11) (NO in step S3_13), the process proceeds to step S3_17.

(156) When the value of num.sub.11 is equal to the value of μ .sub.11 (NO in step S3_11 and YES in step S3_12), the process proceeds to step S3_17.

(157) Further, when the value of num.sub.11 is less than the value of μ .sub.11 (YES in step S3_11 and YES in step S3_15), the data modification unit **1061** updates the value of num.sub.11 so that the value of num.sub.11 approaches (increases) by Δ .sub.11 each to the value of μ .sub.1 and adds the updated value of num.sub.11 to the list.sub.11 (step S3_16). When the value of num.sub.11 has been already listed in the list.sub.11, the data modification unit **1061** overwrites the already listed value of num.sub.11 with the new value of num.sub.11.

(158) The data modification unit **1061** repeats the process of step S3_16 while the value of num.sub.11 is less than or equal to the value of $(\mu$.sub.11+ τ .sub.11) (YES in step S3_15).

(159) When the value of num.sub.11 is greater than the value of $(\mu$.sub.11+ τ .sub.11) (NO in step S3_15), the process proceeds to step S3_17.

(160) In step S3_17, the data modification unit **1061** confirms the list.sub.11.

(161) After that, the data modification unit **1061** generates a list.sub.12 to a list.sub.1n1 for features F.sub.12 to F.sub.1n1 in the same procedure described above. After generating the list.sub.11 to the list.sub.1n1 has completed, the data modification unit **1061** operates step S2_5 in FIG. 9.

(162) Although FIG. 10 illustrates an example of using the most frequent value (mod) of the categorical data, other statistical information such as a central value (med) may be used instead of the most frequent value (mod).

Description of Effect of This Embodiment

(163) As described above, in the present embodiment, a feature of a true positive access is modified by using a feature of a true negative access so that a modified true positive access which is the true positive access whose feature has been modified is determined by an attack detection system to be a normal access. Therefore, according to the present embodiment, it is possible to acquire an attack sample of a false negative access that is able to avoid detection operated by the attack detection system. Hence, according to the present embodiment, it is possible to efficiently search for an attack that is actually able to exist in a real space and avoids detection.

(164) Further, in the present embodiment, instead of modifying a feature vector on a feature space,

an item of a log is modified on the real space and the modified item of the log is converted into the feature vector. Then, it is checked on the feature space with using the feature vector acquired by the conversion, whether an attack avoids detection or not. However, this ends up with a haphazard search. For this reason, in the present embodiment, a true negative normal log in the vicinity of a true positive attack log is specified on a newly generated feature space and the true positive attack log is modified to have a value of a feature that is often found in the true negative normal log. By doing this, it is possible to avoid the haphazard search.

Embodiment 2

(165) In Embodiment 1, an attack log that is able to avoid detection is efficiently generated by modifying a true positive attack log to have a value of a feature that is often found in a true negative normal log in the vicinity of the true positive attack log. In Embodiment 2, an example will be described in which the attack log that is able to avoid detection is efficiently generated by using a normal log in a false positive state (hereinafter referred to as a false positive normal log) in addition to the true negative normal log.

(166) The false positive normal log is a normal log in which features of a false positive access are described in a plurality of fields. As described above, the false positive access is an access that is known to be a normal access, but that has been mistakenly determined by an attack detection system to be an attack access. The false positive access is an access that causes a false detection in the attack detection system.

(167) In the present embodiment, differences from Embodiment 1 will be mainly described.

(168) Matters not described below are the same as matters described in Embodiment 1.

Description of Configuration

(169) FIG. 12 illustrates a functional configuration example of the attack log generation device 100 according to the present embodiment.

(170) In FIG. 12, a false positive normal log DB 118, a vicinity false positive normal log DB 119 and a false positive normal log tendency DB 120 are added, compared with FIG. 2.

(171) The false positive normal log DB 118 stores false positive normal logs.

(172) The vicinity false positive normal log DB 119 stores vicinity false positive normal logs which are false positive normal logs in the vicinities of true positive attack logs.

(173) The false positive normal log tendency DB 120 stores statistical information on false positive normal logs (hereinafter referred to as false positive normal log statistical information).

(174) The false positive normal log DB 118, the vicinity false positive normal log DB 119, and the false positive normal log tendency DB 120 are, for example, implemented by the main storage device 902 or the auxiliary storage device 903.

(175) In the present embodiment, the normal classification unit 101 classifies normal logs stored in the normal log DB 112 into true negative normal logs and false positive normal logs.

(176) Further, in the present embodiment, the modification unit 107 modifies a feature of a true positive access by using a feature of a true negative access and a feature of a false positive access. That is, the modification unit 107 modifies features of a true positive attack log by using features of a vicinity true negative normal log and features of a vicinity false positive normal log. More specifically, the modification unit 107 modifies the features of the true positive attack log by using features of a vicinity true negative normal log in which a feature that overlaps with the features of the vicinity false positive normal log has been eliminated among the features of the vicinity true negative normal log.

(177) In the present embodiment as well, when the detection unit 102 (attack detection system) determines that the modified true positive access defined in the modified true positive attack log is an attack access, the modification unit 107 modifies the features of the modified true positive attack log by using the features of the vicinity true negative normal log and the features of the vicinity false positive normal log.

(178) Since other configuration elements illustrated in FIG. 12 are the same as those illustrated in

FIG. 2, the description thereof will be omitted.

Description of Operation

(179) An operation example of the attack log generation device **100** according to the present embodiment will be described with reference to FIG. **13**.

(180) First, the normal classification unit **101** classifies normal logs into true negative normal logs and false positive normal logs (step **S4_1**).

(181) Specifically, the detection unit **102** analyzes a large number of normal logs stored in advance in the normal log DB **112** and the detection unit **102** determines whether an access defined in a normal log is a normal access or an attack access. Then, the normal classification unit **101** classifies the normal log determined by the detection unit **102** to be the normal access, into the true negative normal log. Further, the normal classification unit **101** classifies the normal log determined by the detection unit **102** to be the attack access, into the false positive normal log.

(182) Then, the normal classification unit **101** stores the true negative normal log in the true negative normal log DB **115** and stores the false positive normal log in the false positive normal log DB **118**.

(183) Next, the attack generation unit **103** executes an attack and generates an attack log (step **S4_2**).

(184) That is, the attack generation unit **103** performs an attack access and generates the attack log in which the features of the attack access are indicated. Then, the attack generation unit **103** stores the generated attack log in the attack log DB **113**.

(185) Next, the detection unit **102** analyzes the attack log and determines whether the access defined in the attack log is a normal access or an attack access (step **S4_3**).

(186) When the detection unit **102** determines that the access defined in the attack log is the normal access (NO in step **S4_3**), the process proceeds to step **S4_8**.

(187) In step **S4_8**, the access determined by the detection unit **102** to be the normal access is the attack access (false negative access) that is able to avoid detection operated by the detection unit **102**, so that the normal classification unit **101** stores the corresponding attack log in the detection avoidance attack log DB **111**, as the detection avoidance attack log.

(188) On the other hand, when the detection unit **102** determines that the access defined in the attack log is the attack access (YES in step **S4_3**), the process proceeds to step **S4_4**.

(189) In step **S4_4**, the vicinity extraction unit **104** extracts from the true negative normal log DB **115** and the false positive normal log DB **118**, a true negative normal log and a false positive normal log in the vicinity of the attack log (true positive attack log) acquired in step **S4_3** (step **S4_4**).

(190) Next, the tendency extraction unit **105** calculates tendencies of features of the vicinity true negative normal log and the vicinity false positive normal log extracted in step **S4_4** (step **S4_5**).

(191) Next, the feature modification unit **106** modifies the true positive attack log so as to include in the true positive attack log, a lot of tendencies of the features of the vicinity true negative normal log but not to include tendencies of the features of the vicinity false positive normal log (step **S4_6**).

(192) That is, the feature modification unit **106** modifies each field of the true positive attack log by using features of a vicinity true negative normal log in which a feature that overlaps with the features of the vicinity false positive normal log has been eliminated among the features of the vicinity true negative normal log.

(193) Next, the detection unit **102** determines whether the access (modified true positive access) defined in the true positive attack log (modified true positive attack log) which has been modified by the feature modification unit **106**, is a normal access or an attack access (step **S4_7**).

(194) When the detection unit **102** determines that the modified true positive access is the normal access (NO in step **S4_7**), the normal classification unit **101** stores the modified true positive attack log in the detection avoidance attack log DB **111**, as the detection avoidance attack log (step **S4_8**).

(195) The modified true positive access based on the modified true positive attack log is not able to be detected by the detection unit **102** as an attack, so that the modified true positive access is an attack access that is able to avoid detection operated by the attack detection system. For this reason, the normal classification unit **101** stores the modified true positive attack log in the detection avoidance attack log DB **111**, as the detection avoidance attack log.

(196) On the other hand, when the detection unit **102** determines that the modified true positive access is the attack access (YES in step **S4_7**), the process returns to step **S4_6**. Then, the feature modification unit **106** further modifies the modified true positive attack log by using the features of the vicinity true negative normal log and the features of the vicinity false positive normal log (step **S4_6**).

(197) The above is the general flow of the operation of the attack log generation device **100** according to the present embodiment.

(198) The detail of the operation of the normal classification unit **101**, the attack generation unit **103**, the vicinity extraction unit **104**, the tendency extraction unit **105**, and the feature modification unit **106** according to the present embodiment will be described below.

(199) The normal classification unit **101** causes the detection unit **102** to determine whether a large number of normal logs prepared in advance in the normal log DB **112** are normal or abnormal. The detection unit **102** determines whether a normal log is normal or abnormal. That is, the detection unit **102** determines whether a feature described in the normal log corresponds to a feature of a normal access or a feature of an attack access.

(200) The normal classification unit **101** extracts a normal log determined by the detection unit **102** to be normal, as the true negative normal log. Then, the normal classification unit **101** stores the extracted true negative normal log in the true negative normal log DB **115**. Further, the normal classification unit **101** extracts a normal log determined by the detection unit **102** to be abnormal, as the false positive normal log. Then, the normal classification unit **101** stores the extracted false positive normal log in the false positive normal log DB **118**.

(201) Further, the normal classification unit **101** stores normal log statistical information in the normal log statistical information DB **114**, as well as Embodiment 1. Since a generation procedure and a storage procedure of the normal log statistical information are as described above in Embodiment 1, the description thereof will be omitted.

(202) FIG. **14** illustrates an internal configuration example of the vicinity extraction unit **104**.

(203) As well as Embodiment 1, the vicinity extraction unit **104** is configured with the feature extraction unit **1041**, the feature expression unit **1042**, and the vicinity calculation unit **1043**. In the present embodiment, the vicinity extraction unit **104** uses the normal log DB **112**, the true negative normal log DB **115**, the vicinity true negative normal log DB **116**, the false positive normal log DB **118**, and the vicinity false positive normal log DB **119**.

(204) The feature extraction unit **1041** extracts prescribed features from true positive attack logs, true negative normal logs and false positive normal logs.

(205) The feature expression unit **1042** converts the features extracted from x pieces of true positive attack logs, $y_{sub.0}$ pieces of true negative normal logs, and $y_{sub.1}$ pieces of false positive normal logs, into forms (feature vectors) that are easily processed in a machine learning algorithm. $y_{sub.0}$ and $y_{sub.1}$ are numbers sufficiently greater than x . Since a method of converting into the feature vectors is as described in Embodiment 1, the description thereof will be omitted.

(206) The vicinity calculation unit **1043** uses the feature vectors of the true positive attack logs and the feature vectors of the true negative normal logs to specify $K_{sub.0}$ pieces of vicinity true negative normal logs in the vicinity of each of the true positive attack logs. The total number of true negative normal logs in the vicinity of x pieces of true positive attack logs is assumed to be $K_{sub.1}$ pieces. $K_{sub.1} \geq K_{sub.0}$. Then, the vicinity calculation unit **1043** stores the specified $K_{sub.0}$ pieces of vicinity true negative normal logs in the vicinity true negative normal log DB **116**.

(207) Further, the vicinity calculation unit **1043** uses the feature vectors of the true positive attack logs and the feature vectors of the false positive normal logs to specify $K_{sub.0}$ pieces of vicinity false positive normal logs in the vicinity of each of the true positive attack logs. The total number of false positive normal logs in the vicinity of x pieces of true positive attack logs is assumed to be $K_{sub.2}$ pieces. $K_{sub.2} \geq K_{sub.0}$. Then, the vicinity calculation unit **1043** stores the specified $K_{sub.2}$ pieces of vicinity false positive normal logs in the vicinity false positive normal log DB **119**.

(208) As a method of specifying the vicinity, for example, the vicinity calculation unit **1043** uses the KNN method in the same way as Embodiment 1.

(209) FIG. 5 illustrates an internal configuration example of the tendency extraction unit **105**.

(210) As well as Embodiment 1, the tendency extraction unit **105** is configured with the feature extraction unit **1051**, the feature expression unit **1052**, the importance degree calculation unit **1053**, and the tendency calculation unit **1054**. In the present embodiment, the tendency extraction unit **105** uses the vicinity true negative normal log DB **116**, the true negative normal log tendency DB **117**, the vicinity false positive normal log DB **119**, and the false positive normal log tendency DB **120**.

(211) The feature extraction unit **1051** acquires from the vicinity true negative normal log DB **116**, $K_{sub.1}$ pieces of vicinity true negative normal logs. Further, the feature extraction unit **1051**, for example, acquires from the vicinity extraction unit **104**, x pieces (assuming one piece) of true positive attack logs.

(212) The feature extraction unit **1051** extracts the prescribed features from $K_{sub.1}$ pieces of vicinity true negative normal logs and x pieces of true positive attack logs, as with Embodiment 1.

(213) In addition, the feature extraction unit **1051** acquires from the vicinity false positive normal log DB **119**, $K_{sub.2}$ pieces of vicinity false positive normal logs. Further, the feature extraction unit **1051**, for example, acquires from the vicinity extraction unit **104**, x pieces (assuming one piece) of true positive attack logs.

(214) Then, the feature extraction unit **1051** extracts the prescribed features from $K_{sub.2}$ pieces of vicinity false positive normal logs and x pieces of true positive attack logs.

(215) As well as Embodiment 1, the feature expression unit **1052** converts the features extracted from $K_{sub.1}$ pieces of vicinity true negative normal logs and x pieces of true positive attack logs into forms (feature vectors) that are easily processed in a machine learning algorithm.

(216) In addition, the feature expression unit **1052** converts the features extracted from $K_{sub.2}$ pieces of vicinity false positive normal logs and x pieces of true positive attack logs, into form (feature vectors) that are easily processed in a machine learning algorithm.

(217) As well as Embodiment 1, the importance degree calculation unit **1053** learns the discriminator ($C_{sub.1}$), calculates an importance degree of a feature, and extracts features $F_{sub.11}$ to $F_{sub.1n1}$ which are the highest $n_{sub.1}$ features as to the importance degree.

(218) In addition, the importance degree calculation unit **1053** uses the feature vectors acquired by the feature expression unit **1052** to learn a discriminator ($C_{sub.2}$) that distinguishes between $K_{sub.2}$ pieces of vicinity false positive normal logs and x pieces of true positive attack logs. The importance degree calculation unit **1053** calculates for each of the feature vectors of the true positive attack logs, an importance degree of a feature which is a degree of distinguishing by the discriminator ($C_{sub.2}$) between $K_{sub.2}$ pieces of vicinity false positive normal logs and x pieces (for example, one piece) of true positive attack logs. The importance degree calculation unit **1053** calculates the feature importance of each of the feature vectors so that higher importance degree is set to a feature which has higher degree of distinguishing between the vicinity false positive normal logs and the true positive attack logs.

(219) Then, the importance degree calculation unit **1053** extracts features $F_{sub.21}$ to $F_{sub.2n1}$ which are the highest $n_{sub.2}$ features as to the importance degree. $n_{sub.2}$ is greater than or equal to 1. For example, the importance degree calculation unit **1053** calculates an importance degree

with using random forest.

(220) As well as Embodiment 1, the tendency calculation unit **1054** acquires statistical information on the features F.sub.11 to F.sub.1n1 of K.sub.1 pieces of vicinity true negative normal logs. The tendency calculation unit **1054** stores the statistical information in the true negative normal log tendency DB **117**.

(221) In addition, the tendency calculation unit **1054** acquires statistical information on the features F.sub.21 to F.sub.2n1 of K.sub.2 pieces of vicinity false positive normal logs. The tendency calculation unit **1054** stores the statistical information in the false positive normal log tendency DB **120**.

(222) As well as Embodiment 1, the tendency calculation unit **1054** acquires for a feature which is categorical data, a central value (median, med.sub.2) and a most frequent value (mode, mod.sub.1) of a percentile in the categorical data, as the statistical information. Further, the tendency calculation unit **1054** acquires for a feature which is numerical data, a mean (μ .sub.2) and a standard deviation (σ .sub.2) of the numerical data, as the statistical information.

(223) FIG. **16** illustrates an internal configuration example of the feature modification unit **106**.

(224) As well as Embodiment 1, the feature modification unit **106** is configured with the data modification unit **1061** and the verification unit **1062**. In the present embodiment, the feature modification unit **106** uses the detection avoidance attack log DB **111**, the true negative normal log tendency DB **117**, and the false positive normal log tendency DB **120**.

(225) FIG. **17** illustrates an operation example of the data modification unit **1061** and the verification unit **1062**.

(226) Since step S5_1 to step S5_4 are the same as step S2_1 to step S2_4 in FIG. **9**, the description thereof will be omitted. Further, a method of generating a list.sub.1i in step S5_4 is as illustrated in FIG. and FIG. **11**.

(227) Next, the data modification unit **1061** performs the same process for the features F.sub.12 to F.sub.1n1 as for the features F.sub.11 to F.sub.1n1 to generate a list.sub.21 to a list.sub.2n1.

(228) Specifically, the data modification unit **1061** first checks whether there is an unchecked feature among the features F.sub.21 to F.sub.2n1 (step S5_5).

(229) When there is the unchecked feature (YES in step S5_5), the data modification unit **1061** selects an unchecked feature F.sub.2i (i is any of 1 to n1) (step S5_6). In the following, operation of the data modification unit **1061** will be described in a case where the feature F.sub.2i is the feature F.sub.21, as an example.

(230) Next, the data modification unit **1061** acquires an actual value of the feature F.sub.21 from a corresponding field in the true positive attack log (step S5_7).

(231) Then, the data modification unit **1061** generates a list.sub.21 (step S5_8). The list.sub.21 includes a modified value acquired by modifying the actual value of the feature F.sub.21 of the true positive attack log with an actual value of the feature F.sub.21 of the vicinity false positive normal log. That is, the list.sub.21 includes a plurality of modified values in which values of the feature F.sub.21 of K.sub.2 pieces of vicinity false positive normal logs have been reflected.

(232) A method of generating the list.sub.21 will be described below.

(233) The data modification unit **1061** also performs for other features F.sub.22 to F.sub.2n1, the processes from step S5_5 to step S5_8.

(234) Next, the data modification unit **1061** merges the list F.sub.11 to the list of the features F.sub.11 to F.sub.1n1 and the list.sub.21 to the list.sub.2n1 of the features F.sub.21 to F.sub.2n2 (step S5_9). A method of merging will be described below.

(235) Next, the data modification unit **1061** combines all modified values included in the merged list.sub.11 to list.sub.2n1 and generates an attack log (modified true positive attack log) corresponding to each combination (step S5_10). The actual value of the true positive attack log is hold in a field that does not correspond to the features F.sub.11 to F.sub.1n1 and the features F.sub.21 to F.sub.2n2.

(236) Next, the verification unit **1062** verifies each modified true positive attack log (step S5_11).

(237) Specifically, the verification unit **1062** causes the detection unit **102** to determine whether the access defined in each modified true positive attack log corresponds to any of a normal access or an attack access.

(238) Then, the verification unit **1062** stores in the detection avoidance attack log DB **111**, the modified true positive attack log that has been determined by the detection unit **102** to be the normal access, as the detection avoidance attack log (step S5_12). When $X > 1$, the verification unit **1062** generates detection avoidance attack logs for all true positive attack logs, with using the same method.

(239) Next, a method of generating the list (the list.sub.21 to the list.sub.2n1) illustrated in step S5_8 of FIG. 17 will be described with reference to FIG. 18 and FIG. 19. An example of generating the list.sub.21 for the feature F.sub.21 will be described below again.

(240) The data modification unit **1061** determines whether the feature F.sub.21 is categorical data or numerical data (step S6_1).

(241) The categorical data is a domain, a method, a status code, or the like. The numerical data is a request size, a time interval, or the like.

(242) When the feature F.sub.21 is the categorical data, the data modification unit **1061** acquires from a dictionary in normal log statistical information, a value of a percentile of the categorical data of the feature F.sub.21 and sets the acquired value of the percentile to cat.sub.21 (step S6_2). Further, from the false positive normal log tendency DB **120**, the data modification unit **1061** refers to a most frequent value mod.sub.21, as the statistical information on the feature F.sub.21 of K.sub.2 pieces of vicinity false positive normal logs (step S6_2).

(243) Next, the data modification unit **1061** compares a value of cat.sub.21 with a value of mod.sub.21 (step S6_3).

(244) When the value of cat.sub.21 is greater than or equal to the value of mod.sub.21 (NO in step S6_3), the data modification unit **1061** compares the value of cat.sub.21 with $(\text{mod.sub.21} + \tau.\text{sub.21})$ (step S6_4). $\tau.\text{sub.21}$ is a prescribed value.

(245) When the value of cat.sub.21 is less than or equal to $(\text{mod.sub.21} + \tau.\text{sub.21})$, the data modification unit **1061** updates the value of cat.sub.21 so that the value of cat.sub.21 departs (increases) by $\Delta.\text{sub.21}$ each from the value of mod.sub.21 and adds the updated value of cat.sub.21 to the list.sub.21 (step S6_5). When the value of cat.sub.21 has been already listed in the list.sub.21, the data modification unit **1061** overwrites the already listed value of cat.sub.21 with the new value of cat.sub.21. $\Delta.\text{sub.21}$ is a prescribed value.

(246) The data modification unit **1061** repeats the process of step S6_5 while the value of cat.sub.21 is less than or equal to a value of $(\text{mod.sub.21} + \tau.\text{sub.21})$ (YES in step S6_4).

(247) When the value of cat.sub.21 is greater than $(\text{mod.sub.21} + \tau.\text{sub.21})$ (NO in step S6_4), the process proceeds to step S6_8.

(248) Further, when the value of cat.sub.21 is less than the value of mod.sub.21 (YES in step S6_3), the data modification unit **1061** compares the value of cat.sub.21 with $(\text{mod.sub.21} - \tau.\text{sub.21})$ (step S6_6).

(249) When the value of cat.sub.21 is greater than or equal to $(\text{mod.sub.21} - \tau.\text{sub.21})$, the data modification unit **1061** updates the value of cat.sub.21 so that the value of cat.sub.21 departs (decreases) by $\Delta.\text{sub.21}$ each from the value of mod.sub.21 and adds the updated value of cat.sub.21 to the list.sub.21 (step S6_7). When the value of cat.sub.21 has been already listed in the list.sub.21, the data modification unit **1061** overwrites the already listed value of cat.sub.21 with the new value of cat.sub.21.

(250) The data modification unit **1061** repeats the process step S6_7 while the value of cat.sub.21 is greater than or equal to a value of $(\text{mod.sub.21} - \tau.\text{sub.21})$ (YES in step S6_6).

(251) When the value of cat.sub.21 is less than $(\text{mod.sub.21} - \tau.\text{sub.21})$ (NO in step S6_6), the process proceeds to step S6_8.

(252) In step **S6_8**, the data modification unit **1061** confirms the list.sub.21.

(253) In step **S6_1**, when the feature F.sub.21 is the numerical data, the data modification unit **1061** sets the value of the numerical data of the feature F.sub.21 to num.sub.21 (step **S6_9**). In addition, from the false positive normal log tendency DB **120**, the data modification unit **1061** refer to a mean μ .sub.21 and a standard deviation σ .sub.21 as the statistical information on the feature F.sub.21 of K.sub.2 pieces of vicinity false positive normal logs (step **S6_9**).

(254) Next, the data modification unit **1061** compares a value of num.sub.21 with a value of μ .sub.21 (step **S6_10**).

(255) When the value of um.sub.21 is greater than or equal to the value of μ .sub.21 (NO in step **S6_10**), the data modification unit **1061** compares the value of num.sub.21 with $(\mu$.sub.21+ τ .sub.21) (step **S6_11**).

(256) When the value of num.sub.21 is less than or equal to $(\mu$.sub.21+ τ .sub.21) (YES in step **S6_11**), the data modification unit **1061** updates the value of num.sub.21 so that the value of num.sub.21 departs (increases) by Δ .sub.21 each from the value of μ .sub.21 and adds the updated value of num.sub.21 to the list.sub.21 (step **S6_12**). When the value of num.sub.21 has been already listed in the list.sub.21, the data modification unit **1061** overwrites the already listed value of num.sub.21 with the new value of num.sub.21. Δ .sub.21 is a prescribed value. This Δ .sub.21 may be the same value as Δ .sub.21 used in a case where the feature F.sub.21 is the categorical data, or may be a different value. τ .sub.21 is also a prescribed value. For example, such as $3 \times \sigma$.sub.21, τ .sub.21 is considered to be defined with using a statistical value relating to the feature F.sub.21.

(257) The data modification unit **1061** repeats the process of step **S6_12** while the value of num.sub.21 is less than or equal to $(\mu$.sub.21+ τ .sub.21) (YES in step **S6_11**).

(258) When the value of num.sub.21 is greater than $(\mu$.sub.21+ τ .sub.21) (NO in step **S6_11**), the process proceeds to step **S6_15**.

(259) Further, the value of num.sub.21 is less than the value of μ .sub.21 (YES in step **S6_10**), the data modification unit **1061** compares the value of num.sub.21 with $(\mu$.sub.21- τ .sub.21) (step **S6_13**).

(260) When the value of num.sub.21 is greater than or equal to $(\mu$.sub.21- τ .sub.21) (YES in step **S6_13**), the data modification unit **1061** updates the value of num.sub.21 so that the value of num.sub.21 departs (decreases) by Δ .sub.21 each from the value of μ .sub.2 and adds the updated value of num.sub.21 to the list.sub.21 (step **S6_14**). When the value of num.sub.21 has been already listed in the list.sub.21, the data modification unit **1061** overwrites the already listed value of num.sub.21 with the new value of num.sub.21.

(261) The data modification unit **1061** repeats the process of step **S6_14** while the value of num.sub.21 is greater than or equal to $(\mu$.sub.21- τ .sub.21) (YES in step **S6_13**).

(262) When the value of num.sub.21 is less than $(\mu$.sub.21- τ .sub.21) (NO in step **S6_13**), the process proceeds to step **S6_15**.

(263) In step **S6_15**, the data modification unit **1061** confirms the list.sub.21.

(264) After that, the data modification unit **1061** generates a list.sub.22 to a list.sub.2n1 for features F.sub.22 to F.sub.2n1 in the same procedure described above.

(265) Although FIG. **18** illustrates an example of using the most frequent value (mod) of the categorical data, other statistical information such as a central value (med) may be used instead of the most frequent value (mod).

(266) Next, a procedure of merging the list.sub.11 to list.sub.1n1 of the features F.sub.11 to F.sub.1n1 and the list.sub.21 to the list.sub.2n1 of the features F.sub.21 to F.sub.2n2 will be described. The following description assumes that the number of true positive attack logs (X) is 1, but even when X>1, for all true positive attack logs, lists are merged with using the same method. That is, the list.sub.11 to the list.sub.1n1 of the features F.sub.11 to F.sub.1n1 generated from the same true positive attack log are merged with the list.sub.21 to the list.sub.2n1 of the features F.sub.21 to F.sub.2n1.

(267) First, the data modification unit **1061** searches for a feature which is in common between the features F.sub.11 to F.sub.1n1 and the features F.sub.21 to F.sub.2n1. Here, it is assumed that a feature F.sub.11 and a feature F.sub.23 are in common.

(268) When F.sub.11 and F.sub.23 are categorical data, the data modification unit **1061** refers to a most frequent value (mod.sub.23) corresponding to F.sub.23, from the false positive normal log tendency DB **120**. A minimum value and a maximum value of elements of a list.sub.23 of the feature F.sub.23 are respectively expressed as min(list.sub.23) and max(list.sub.23). When mod.sub.23 is less than min(list.sub.23), the data modification unit **1061** deletes from the list.sub.11, an element which is greater than or equal to mod.sub.23- α as well as less than or equal to min(list.sub.23)+ α , among the elements of the list.sub.11. When mod.sub.23 is greater than max(list.sub.23), the data modification unit **1061** deletes from the list.sub.11, an element which is greater than or equal to max(list.sub.23)- α as well as less than or equal to mod.sub.23+ α , among the elements of the list.sub.11. α is a prescribed value.

(269) When F.sub.11 and F.sub.23 are numerical data, the data modification unit **1061** refers to a mean (μ .sub.23) corresponding to F.sub.23, from the false positive normal log tendency DB **120**. A minimum value and a maximum value of elements of a list.sub.23 of the feature F.sub.23 are respectively expressed as min(list.sub.23) and max(list.sub.23). When μ .sub.23 is less than min(list.sub.23), the data modification unit **1061** deletes from the list.sub.11, an element which is greater than or equal to mod.sub.23- β as well as less than or equal to min(list.sub.23)+ β , among the elements of the list.sub.11. When μ .sub.23 is greater than max(list.sub.23), the data modification unit **1061** deletes from the list.sub.11, an element which is greater than or equal to max(list.sub.23)- α as well as less than or equal to mod.sub.23+ α , among the elements of list.sub.11. Θ is a prescribed value. For example, such as $3 \times \sigma$.sub.23, β may be defined with using a statistical value relating to F.sub.23.

(270) The data modification unit **1061** simply merges (combines) a list.sub.1i of a feature F.sub.1i and a list.sub.2i of a feature F.sub.2i, where F.sub.1i and F.sub.2i are not in common.

Description of Effect of Embodiment

(271) Also in the present embodiment, it is possible to acquire an attack sample of a false negative access that is able to avoid detection operated by an attack detection system. Further, in the present embodiment, features of a true positive attack log are modified by using features of a vicinity true negative normal log in which a feature that overlaps with a feature of vicinity false positive normal log has been eliminated among features of the vicinity true negative normal log. For this reason, compares with Embodiment 1, it is possible to acquire an attack sample of a false negative access that is more skillfully able to avoid detection.

(272) Embodiments 1 and 2 have been described above and these two embodiments may be implemented in combination.

(273) Alternatively, one of these two embodiments may be partially implemented.

(274) Alternatively, these two embodiments may be partially implemented in combination.

(275) Further, the configurations and procedures described in these two embodiments may be modified as necessary.

Supplementary Description of Hardware Configuration

(276) Finally, a supplementary description of the hardware configuration of the attack log generation device **100** will be given.

(277) The processor **901** illustrated in FIG. 1 is an Integrated Circuit (IC) that performs processing.

(278) The processor **901** is a Central Processing Unit (CPU), a Digital Signal Processor (DSP), or the like.

(279) The main storage device **902** illustrated in FIG. 1 is a Random Access Memory (RAM).

(280) The auxiliary storage device **903** illustrated in FIG. 1 is a Read Only Memory (ROM), a flash memory, a Hard Disk Drive (HDD), or the like.

(281) Further, the auxiliary storage device **903** also stores an Operating System (OS).

(282) Then, at least a part of the OS is executed by the processor **901**.

(283) While executing at least the part of the OS, the processor **901** executes the programs which implement the functions of the normal classification unit **101**, the detection unit **102**, the attack generation unit **103**, the vicinity extraction unit **104**, the tendency extraction unit **105**, and the feature modification unit **106**.

(284) By the processor **901** executing the OS, task management, memory management, file management, communication control, and the like are performed.

(285) Further, at least one of information, data, a signal value, and a variable value that indicate results of processes of the normal classification unit **101**, the detection unit **102**, the attack generation unit **103**, the vicinity extraction unit **104**, the tendency extraction unit **105**, and the feature modification unit **106** is stored in at least one of the main storage device **902**, the auxiliary storage device **903**, and a register and a cache memory in the processor **901**.

(286) Further, the programs that implement the functions of the normal classification unit **101**, the detection unit **102**, the attack generation unit **103**, the vicinity extraction unit **104**, the tendency extraction unit **105**, and the feature modification unit **106** may be stored in a portable recording medium such as a magnetic disk, a flexible disk, an optical disc, a compact disc, a Blu-ray (registered trademark) disc, or a DVD. Then, the portable recording medium storing the programs that implement the functions of the normal classification unit **101**, the detection unit **102**, the attack generation unit **103**, the vicinity extraction unit **104**, the tendency extraction unit **105**, and the feature modification unit **106** may be distributed.

(287) Further, the “unit” of each of the normal classification unit **101**, the detection unit **102**, the attack generation unit **103**, the vicinity extraction unit **104**, the tendency extraction unit **105**, and the feature modification unit **106** may be read as a “circuit”, “step”, “procedure”, “process”, or “circuitry”.

(288) Further, the attack log generation device **100** may be implemented by a processing circuit. The processing circuit is, for example, a logic Integrated Circuit (IC), a Gate Array (GA), an Application Specific Integrated Circuit (ASIC), or a Field-Programmable Gate Array (FPGA).

(289) In this case, each of the normal classification unit **101**, the detection unit **102**, the attack generation unit **103**, the vicinity extraction unit **104**, the tendency extraction unit **105**, and the feature modification unit **106** is implemented as a part of the processing circuit.

(290) In this embodiment, a superordinate concept of the processor and the processing circuit is referred to as “processing circuitry”.

(291) That is, each of the processor and the processing circuit is a specific example of the “processing circuitry”.

REFERENCE SIGNS LIST

(292) **100**: attack log generation device; **101**: normal classification unit; **102**: detection unit; **103**: attack generation unit; **104**: vicinity extraction unit; **105**: tendency extraction unit; **106**: feature modification unit; **107**: modification unit; **111**: detection avoidance attack log DB; **112**: normal log DB; **113**: attack log DB; **114**: normal log statistical information DB; **115**: true negative normal log DB; **116**: vicinity true negative normal log DB; **117**: true negative normal log tendency DB; **118**: false positive normal log DB; **119**: vicinity false positive normal log DB; **120**: false positive normal log tendency DB; **901**: processor; **902**: main storage device; **903**: auxiliary storage device; **904**: keyboard; **905**: mouse; **1031**: simulated environment; **1032**: attack execution unit; **1033**: attack module; **1034**: attack scenario DB; **1035**: log collection unit; **1041**: feature extraction unit; **1042**: feature expression unit; **1043**: vicinity calculation unit; **1051**: feature extraction unit; **1052**: feature expression unit; **1053**: importance degree calculation unit; **1054**: tendency calculation unit; **1061**: data modification unit; **1062**: verification unit

Claims

1. An information processing device comprising: processing circuitry to: extract, from a database of true positive accesses, a true positive access, wherein each of the true positive accesses is an access that is known prior to being processed by an access detection system to be an access aimed to attack, and detected by the attack detection system to be an access aimed to attack; extract, from a database of true negative accesses, a true negative access, wherein each of the true negative accesses is an access that is known prior to being processed by the access detection system to be a normal access, and determined by the attack detection system to be a normal access; and modify a feature of the extracted true positive access by using a feature of the extracted true negative access to increase the likelihood that the access detection system will determine the modified true positive access to be a normal access, wherein the processing circuitry modifies the feature of the true positive access by using the feature of the true negative access and data of a corresponding feature of a false positive access, wherein the false positive access is an access that is known prior to being processed by an access detection system to be a normal access, and detected by the attack detection system to be an access aimed to attack.
2. The information processing device according to claim 1, wherein the processing circuitry modifies the feature of the true positive access so that a modified true positive access which is the true positive access whose feature has been modified is determined by the attack detection system to be a normal access.
3. The information processing device according to claim 1, wherein when the extracted true positive access which is the true positive access whose feature has been modified is determined by the attack detection system to be an access aimed to attack, the processing circuitry further modifies the feature of the modified true positive access by using the feature of the extracted true negative access.
4. The information processing device according to claim 1, wherein the processing circuitry extracts from the database of true negative accesses, an access including a feature similar to the particular feature of the true positive access, as the true negative access, and modifies the data of the particular feature of the true positive access by using the data of the similar corresponding feature of the extracted true negative access.
5. The information processing device according to claim 1, wherein the processing circuitry selects as the feature to modify from the plurality of features of the true positive access, a feature that matches with a selection condition, and modifies the selected feature by using the feature of the true negative access.
6. The information processing device according to claim 5, wherein the processing circuitry calculates for each of the plurality of features, an importance degree of a feature which is a degree of distinguishing between the true positive access and the true negative access, and selects from the plurality of features, a feature whose importance degree matches with the selection condition.
7. The information processing device according to claim 6, wherein the processing circuitry calculates an importance degree of each of the plurality of features so that higher importance degree is set to a feature which has higher degree of distinguishing between the true positive access and the true negative access.
8. The information processing device according to claim 1, wherein when a modified true positive access which is the true positive access whose particular feature has been modified is determined by the attack detection system to be an access aimed to attack, the processing circuitry further modifies the feature of the modified true positive access by using the feature of the false positive access and the feature of the true negative access.
9. The information processing device according to claim 1, wherein the processing circuitry selects the feature of the true positive access to be modified by eliminating as a possible selection a feature corresponding to a feature of the true negative access that overlaps with a corresponding feature of the false positive access.

10. An information processing method comprising: extracting, from a database of true positive accesses, a true positive access, wherein each of the true positive accesses is an access that is known prior to being processed by an access detection system to be an access aimed to attack, and detected by the attack detection system to be an access aimed to attack; extracting, from a database of true negative accesses, a true negative access, wherein each of the true negative accesses is an access that is known prior to being processed by the access detection system to be a normal access, and determined by the attack detection system to be a normal access; and modifying a feature of the extracted true positive access by using a feature of the extracted true negative access to increase the likelihood that the attack detection system will determine the modified true positive access to be a normal access, wherein the modifying step modifies the feature of the true positive access by using the feature of the true negative access and data of a corresponding feature of a false positive access, wherein the false positive access is an access that is known prior to being processed by an access detection system to be a normal access, and detected by the attack detection system to be an access aimed to attack.

11. A non-transitory computer readable medium storing an information processing program for causing a computer to execute: an extraction process to extract, from a database of true positive accesses, a true positive access, wherein each of the true positive accesses is an access that is known prior to being processed by an access detection system to be an access aimed to attack, and detected by the attack detection system to be an access aimed to attack; a second extraction process to extract, from a database of true negative accesses, a true negative access, wherein each of the true negative accesses is an access that is known before being processed by the access detection system to be a normal access, and determined by the attack detection system to be a normal access; and a modification process to modify a feature of the extracted true positive access by using a feature of the extracted true negative access to increase the likelihood that the attack detection system will determine the modified true positive access to be a normal access, wherein the modification process modifies the feature of the true positive access by using the feature of the true negative access and data of a corresponding feature of a false positive access, wherein the false positive access is an access that is known prior to being processed by an access detection system to be a normal access, and detected by the attack detection system to be an access aimed to attack.
