

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12407808
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Muhassin; Nijumudheen et al.

Performance verification of an image sensor mounted to a vehicle

Abstract

Provided are methods for verifying the performance of an image sensor mounted to a vehicle, which can include causing alignment of a collimator with an image sensor mounted to a vehicle, receiving sensor data associated with the image sensor based at least in part on causing the alignment of the collimator with the image sensor, determining that the sensor data does not satisfy a performance specification associated with the image sensor, determining an image sensor alert associated with the image sensor based at least in part on determining that the sensor data does not satisfy the performance specification associated with the image sensor, and routing the image sensor alert.

Inventors: Muhassin; Nijumudheen (Pittsburgh, PA), Low; Yew Kwang (Singapore, SG), Dwivedi; Jayesh (Pittsburgh, PA), Buono; William (Pittsburgh, PA)

Applicant: Motional AD LLC (Boston, MA)

Family ID: 81449396

Assignee: Motional AD LLC (Boston, MA)

Appl. No.: 17/580021

Filed: January 20, 2022

Prior Publication Data

Document Identifier	Publication Date
US 20230231989 A1	Jul. 20, 2023

Publication Classification

Int. Cl.: H04N17/00 (20060101); B60W50/02 (20120101); B60W60/00 (20200101); G02B27/30 (20060101); G06T7/80 (20170101)

U.S. Cl.:

CPC **H04N17/002** (20130101); **B60W50/0205** (20130101); **G02B27/30** (20130101); **G06T7/80** (20170101); B60W60/001 (20200201); B60W2420/403 (20130101); G06T2207/30252 (20130101)

Field of Classification Search

CPC: H04N (17/002); H04N (23/55); H04N (23/57); H04N (17/004); B60W (50/0205); B60W (60/001); B60W (2420/403); G02B (27/30); G02B (27/62); G06T (7/80); G06T (2207/30252); G06T (2207/30244); G06T (7/001); G06T (7/30); G05D (1/0236); G05D (1/0214); G05D (1/0221); G05D (1/0223); G05D (1/024); G05D (1/0242); G05D (1/0251); G05D (1/0255); G05D (1/0257); G05D (1/0276); G05D (1/0278); G05D (1/028); G05D (1/0293); G01S (13/865); G01S (13/867); G01S (17/86); B60R (1/22)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2018/0294376	12/2017	Tian et al.	N/A	N/A
2019/0324432	12/2018	Cella et al.	N/A	N/A
2020/0225003	12/2019	Campbell	N/A	N/A
2020/0272899	12/2019	Dunne	N/A	G06N 3/08
2021/0037235	12/2020	Lee	N/A	G02B 27/30
2021/0181058	12/2020	Dumitrescu et al.	N/A	N/A
2022/0099972	12/2021	Birklbauer	N/A	H04N 13/344

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
WO 2020/123637	12/2019	WO	N/A
WO 2021/150689	12/2020	WO	N/A

OTHER PUBLICATIONS

Korean Office Action issued for Application No. KR 10-2022-0038394, dated Jan. 18, 2024. cited by applicant

SAE On-Road Automated Vehicle Standards Committee, "SAE International's Standard J3016: Taxonomy and Definitions for Terms Related to Driving Automation Systems for On-Road Motor Vehicles", Jun. 2018, in 35 pages. cited by applicant

Great Britain Office Action issued for Application No. GB 2204133.9, dated Apr. 26, 2022. cited by applicant

Great Britain Office Action issued for Application No. GB 2204133.9, dated Sep. 26, 2022. cited by applicant

Primary Examiner: Teitelbaum; Michael E

Attorney, Agent or Firm: Knobbe, Martens, Olson & Bear, LLP

Background/Summary

BACKGROUND

(1) Self-driving vehicles typically use sensor data to perceive the area around them. Ensuring that the sensor data received by the self-driving vehicle is accurate can be difficult and complicated.

Description

BRIEF DESCRIPTION OF THE FIGURES

- (1) FIG. 1 is an example environment in which a vehicle including one or more components of an autonomous system can be implemented;
- (2) FIG. 2 is a diagram of one or more systems of a vehicle including an autonomous system;
- (3) FIG. 3 is a diagram of components of one or more devices and/or one or more systems of FIGS. 1 and 2;
- (4) FIG. 4 is a diagram of certain components of an autonomous system;
- (5) FIG. 5 is a block diagram illustrating an example of a signal processing system;
- (6) FIG. 6 is a diagram illustrating an example frame including a plurality of collimators;
- (7) FIG. 7 is an example environment in which a vehicle including one or more sensors and a frame including a plurality of collimators can be implemented;
- (8) FIG. 8 is an example environment illustrating example sensor data including a region of interest and collimated light; and
- (9) FIG. 9 is a flow diagram illustrating an example of a routine implemented by one or more processors to determine an image sensor alert based on alignment of a collimator with an image sensor.

DETAILED DESCRIPTION

- (10) In the following description numerous specific details are set forth in order to provide a thorough understanding of the present disclosure for the purposes of explanation. It will be apparent, however, that the embodiments described by the present disclosure can be practiced without these specific details. In some instances, well-known structures and devices are illustrated in block diagram form in order to avoid unnecessarily obscuring aspects of the present disclosure.
- (11) Specific arrangements or orderings of schematic elements, such as those representing systems, devices, modules, instruction blocks, data elements, and/or the like are illustrated in the drawings for ease of description. However, it will be understood by those skilled in the art that the specific ordering or arrangement of the schematic elements in the drawings is not meant to imply that a particular order or sequence of processing, or separation of processes, is required unless explicitly described as such. Further, the inclusion of a schematic element in a drawing is not meant to imply that such element is required in all embodiments or that the features represented by such element may not be included in or combined with other elements in some embodiments unless explicitly described as such.
- (12) Further, where connecting elements such as solid or dashed lines or arrows are used in the drawings to illustrate a connection, relationship, or association between or among two or more other schematic elements, the absence of any such connecting elements is not meant to imply that no connection, relationship, or association can exist. In other words, some connections, relationships, or associations between elements are not illustrated in the drawings so as not to obscure the disclosure. In addition, for ease of illustration, a single connecting element can be used to represent multiple connections, relationships or associations between elements. For example, where a connecting element represents communication of signals, data, or instructions (e.g., “software instructions”), it should be understood by those skilled in the art that such element can

represent one or multiple signal paths (e.g., a bus), as may be needed, to affect the communication. (13) Although the terms first, second, third, and/or the like are used to describe various elements, these elements should not be limited by these terms. The terms first, second, third, and/or the like are used only to distinguish one element from another. For example, a first contact could be termed a second contact and, similarly, a second contact could be termed a first contact without departing from the scope of the described embodiments. The first contact and the second contact are both contacts, but they are not the same contact.

(14) The terminology used in the description of the various described embodiments herein is included for the purpose of describing particular embodiments only and is not intended to be limiting. As used in the description of the various described embodiments and the appended claims, the singular forms “a,” “an” and “the” are intended to include the plural forms as well and can be used interchangeably with “one or more” or “at least one,” unless the context clearly indicates otherwise. It will also be understood that the term “and/or” as used herein refers to and encompasses any and all possible combinations of one or more of the associated listed items. It will be further understood that the terms “includes,” “including,” “comprises,” and/or “comprising,” when used in this description specify the presence of stated features, integers, steps, operations, elements, and/or components, but do not preclude the presence or addition of one or more other features, integers, steps, operations, elements, components, and/or groups thereof.

(15) As used herein, the terms “communication” and “communicate” refer to at least one of the reception, receipt, transmission, transfer, provision, and/or the like of information (or information represented by, for example, data, signals, messages, instructions, commands, and/or the like). For one unit (e.g., a device, a system, a component of a device or system, combinations thereof, and/or the like) to be in communication with another unit means that the one unit is able to directly or indirectly receive information from and/or send (e.g., transmit) information to the other unit. This may refer to a direct or indirect connection that is wired and/or wireless in nature. Additionally, two units may be in communication with each other even though the information transmitted may be modified, processed, relayed, and/or routed between the first and second unit. For example, a first unit may be in communication with a second unit even though the first unit passively receives information and does not actively transmit information to the second unit. As another example, a first unit may be in communication with a second unit if at least one intermediary unit (e.g., a third unit located between the first unit and the second unit) processes information received from the first unit and transmits the processed information to the second unit. In some embodiments, a message may refer to a network packet (e.g., a data packet and/or the like) that includes data.

(16) As used herein, the term “if” is, optionally, construed to mean “when,” “upon,” “in response to determining,” “in response to detecting,” and/or the like, depending on the context. Similarly, the phrase “if it is determined” or “if [a stated condition or event] is detected” is, optionally, construed to mean “upon determining,” “in response to determining,” “upon detecting [the stated condition or event],” “in response to detecting [the stated condition or event],” and/or the like, depending on the context. Also, as used herein, the terms “has,” “have,” “having,” or the like are intended to be open-ended terms. Further, the phrase “based on” is intended to mean “based at least partially on” unless explicitly stated otherwise.

(17) Reference will now be made in detail to embodiments, examples of which are illustrated in the accompanying drawings. In the following detailed description, numerous specific details are set forth in order to provide a thorough understanding of the various described embodiments.

However, it will be apparent to one of ordinary skill in the art that the various described embodiments can be practiced without these specific details. In other instances, well-known methods, procedures, components, circuits, and networks have not been described in detail so as not to unnecessarily obscure aspects of the embodiments.

General Overview

(18) In some aspects and/or embodiments, systems, methods, and computer program products

described herein include and/or implement a signal processing system that causes alignment of an a collimator with an image sensor mounted to a vehicle, receives sensor data associated with the image sensor, determines that the sensor data does not satisfy a performance threshold, determines an image sensor alert, and routes the image sensor alert. The signal processing system can receive sensor data to test the image sensor based on the sensor data. Further, the signal processing system can test the image sensors associated with a vehicle without dismounting the image sensors from the vehicle. The signal processing system can align the image sensors with a plurality of collimators and receive sensor data from the image sensors based on the alignment of the image sensors with the plurality of collimators. Further, the signal processing system can use the sensor data to identify deviations from performance specifications (e.g., performance thresholds). As a non-limiting example, the signal processing system causes alignment of a collimator with an image sensor mounted to a vehicle, receives sensor data associated with the image sensor, determines that the sensor data does not satisfy a performance specification, determines an image sensor alert, and routes the image sensor alert.

(19) By virtue of the implementation of systems, methods, and computer program products described herein, a system can verify the performance of image sensors mounted to a vehicle without dismounting the image sensors from the vehicle. For example, the system may align the image sensors of the vehicle with various collimators (e.g., a frame of collimators) and may receive sensor data based on the alignment of the image sensors with the collimators. Further, the system can utilize the sensor data to identify deviations from performance specifications for each of the image sensors. For example, the system can determine whether the optical performance and/or the intrinsic calibration has deviated from performance specifications. Therefore, the system can more efficiently verify the performance of the image sensors without dismounting (e.g., removing) the image sensors from the vehicle. Further, the system can verify the performance of the image sensors without extrinsic recalibration of the positioning of each image sensor relative to the vehicle (e.g., due to dismounting the image sensors from the vehicle). The verification of the performance of the image sensor without dismounting the image sensor can increase the efficiency of the verification process as certain image sensors can be identified as satisfying the performance specifications and may not be designated for dismounting from the vehicle. Further, based on the identifying that additional image sensors do not satisfy the performance specifications, the additional image sensors can be designated for dismounting for recalibration. In some cases, the system can update the parameters of the image sensors based on the verification of the performance of the image sensors. Such an efficient performance verification can improve the quality and efficiency of the testing and recalibration of the image sensors.

(20) Referring now to FIG. 1, illustrated is example environment **100** in which vehicles that include autonomous systems, as well as vehicles that do not, are operated. As illustrated, environment **100** includes vehicles **102a-102n**, objects **104a-104n**, routes **106a-106n**, area **108**, vehicle-to-infrastructure (V2I) device **110**, network **112**, remote autonomous vehicle (AV) system **114**, fleet management system **116**, and V2I system **118**. Vehicles **102a-102n**, vehicle-to-infrastructure (V2I) device **110**, network **112**, autonomous vehicle (AV) system **114**, fleet management system **116**, and V2I system **118** interconnect (e.g., establish a connection to communicate and/or the like) via wired connections, wireless connections, or a combination of wired or wireless connections. In some embodiments, objects **104a-104n** interconnect with at least one of vehicles **102a-102n**, vehicle-to-infrastructure (V2I) device **110**, network **112**, autonomous vehicle (AV) system **114**, fleet management system **116**, and V2I system **118** via wired connections, wireless connections, or a combination of wired or wireless connections.

(21) Vehicles **102a-102n** (referred to individually as vehicle **102** and collectively as vehicles **102**) include at least one device configured to transport goods and/or people. In some embodiments, vehicles **102** are configured to be in communication with V2I device **110**, remote AV system **114**, fleet management system **116**, and/or V2I system **118** via network **112**. In some embodiments,

vehicles **102** include cars, buses, trucks, trains, and/or the like. In some embodiments, vehicles **102** are the same as, or similar to, vehicles **200**, described herein (see FIG. 2). In some embodiments, a vehicle **200** of a set of vehicles **200** is associated with an autonomous fleet manager. In some embodiments, vehicles **102** travel along respective routes **106a-106n** (referred to individually as route **106** and collectively as routes **106**), as described herein. In some embodiments, one or more vehicles **102** include an autonomous system (e.g., an autonomous system that is the same as or similar to autonomous system **202**).

(22) Objects **104a-104n** (referred to individually as object **104** and collectively as objects **104**) include, for example, at least one vehicle, at least one pedestrian, at least one cyclist, at least one structure (e.g., a building, a sign, a fire hydrant, etc.), and/or the like. Each object **104** is stationary (e.g., located at a fixed location for a period of time) or mobile (e.g., having a velocity and associated with at least one trajectory). In some embodiments, objects **104** are associated with corresponding locations in area **108**.

(23) Routes **106a-106n** (referred to individually as route **106** and collectively as routes **106**) are each associated with (e.g., prescribe) a sequence of actions (also known as a trajectory) connecting states along which an AV can navigate. Each route **106** starts at an initial state (e.g., a state that corresponds to a first spatiotemporal location, velocity, and/or the like) and a final goal state (e.g., a state that corresponds to a second spatiotemporal location that is different from the first spatiotemporal location) or goal region (e.g., a subspace of acceptable states (e.g., terminal states)). In some embodiments, the first state includes a location at which an individual or individuals are to be picked-up by the AV and the second state or region includes a location or locations at which the individual or individuals picked-up by the AV are to be dropped-off. In some embodiments, routes **106** include a plurality of acceptable state sequences (e.g., a plurality of spatiotemporal location sequences), the plurality of state sequences associated with (e.g., defining) a plurality of trajectories. In an example, routes **106** include only high-level actions or imprecise state locations, such as a series of connected roads dictating turning directions at roadway intersections. Additionally, or alternatively, routes **106** may include more precise actions or states such as, for example, specific target lanes or precise locations within the lane areas and targeted speed at those positions. In an example, routes **106** include a plurality of precise state sequences along the at least one high level action sequence with a limited lookahead horizon to reach intermediate goals, where the combination of successive iterations of limited horizon state sequences cumulatively correspond to a plurality of trajectories that collectively form the high-level route to terminate at the final goal state or region.

(24) Area **108** includes a physical area (e.g., a geographic region) within which vehicles **102** can navigate. In an example, area **108** includes at least one state (e.g., a country, a province, an individual state of a plurality of states included in a country, etc.), at least one portion of a state, at least one city, at least one portion of a city, etc. In some embodiments, area **108** includes at least one named thoroughfare (referred to herein as a “road”) such as a highway, an interstate highway, a parkway, a city street, etc. Additionally, or alternatively, in some examples area **108** includes at least one unnamed road such as a driveway, a section of a parking lot, a section of a vacant and/or undeveloped lot, a dirt path, etc. In some embodiments, a road includes at least one lane (e.g., a portion of the road that can be traversed by vehicles **102**). In an example, a road includes at least one lane associated with (e.g., identified based on) at least one lane marking.

(25) Vehicle-to-Infrastructure (V2I) device **110** (sometimes referred to as a Vehicle-to-Infrastructure (V2X) device) includes at least one device configured to be in communication with vehicles **102** and/or V2I infrastructure system **118**. In some embodiments, V2I device **110** is configured to be in communication with vehicles **102**, remote AV system **114**, fleet management system **116**, and/or V2I system **118** via network **112**. In some embodiments, V2I device **110** includes a radio frequency identification (RFID) device, signage, cameras (e.g., two-dimensional (2D) and/or three-dimensional (3D) cameras), lane markers, streetlights, parking meters, etc. In

some embodiments, V2I device **110** is configured to communicate directly with vehicles **102**. Additionally, or alternatively, in some embodiments V2I device **110** is configured to communicate with vehicles **102**, remote AV system **114**, and/or fleet management system **116** via V2I system **118**. In some embodiments, V2I device **110** is configured to communicate with V2I system **118** via network **112**.

(26) Network **112** includes one or more wired and/or wireless networks. In an example, network **112** includes a cellular network (e.g., a long term evolution (LTE) network, a third generation (3G) network, a fourth generation (4G) network, a fifth generation (5G) network, a code division multiple access (CDMA) network, etc.), a public land mobile network (PLMN), a local area network (LAN), a wide area network (WAN), a metropolitan area network (MAN), a telephone network (e.g., the public switched telephone network (PSTN)), a private network, an ad hoc network, an intranet, the Internet, a fiber optic-based network, a cloud computing network, etc., a combination of some or all of these networks, and/or the like.

(27) Remote AV system **114** includes at least one device configured to be in communication with vehicles **102**, V2I device **110**, network **112**, remote AV system **114**, fleet management system **116**, and/or V2I system **118** via network **112**. In an example, remote AV system **114** includes a server, a group of servers, and/or other like devices. In some embodiments, remote AV system **114** is co-located with the fleet management system **116**. In some embodiments, remote AV system **114** is involved in the installation of some or all of the components of a vehicle, including an autonomous system, an autonomous vehicle compute, software implemented by an autonomous vehicle compute, and/or the like. In some embodiments, remote AV system **114** maintains (e.g., updates and/or replaces) such components and/or software during the lifetime of the vehicle.

(28) Fleet management system **116** includes at least one device configured to be in communication with vehicles **102**, V2I device **110**, remote AV system **114**, and/or V2I infrastructure system **118**. In an example, fleet management system **116** includes a server, a group of servers, and/or other like devices. In some embodiments, fleet management system **116** is associated with a ridesharing company (e.g., an organization that controls operation of multiple vehicles (e.g., vehicles that include autonomous systems and/or vehicles that do not include autonomous systems) and/or the like).

(29) In some embodiments, V2I system **118** includes at least one device configured to be in communication with vehicles **102**, V2I device **110**, remote AV system **114**, and/or fleet management system **116** via network **112**. In some examples, V2I system **118** is configured to be in communication with V2I device **110** via a connection different from network **112**. In some embodiments, V2I system **118** includes a server, a group of servers, and/or other like devices. In some embodiments, V2I system **118** is associated with a municipality or a private institution (e.g., a private institution that maintains V2I device **110** and/or the like).

(30) The number and arrangement of elements illustrated in FIG. **1** are provided as an example. There can be additional elements, fewer elements, different elements, and/or differently arranged elements, than those illustrated in FIG. **1**. Additionally, or alternatively, at least one element of environment **100** can perform one or more functions described as being performed by at least one different element of FIG. **1**. Additionally, or alternatively, at least one set of elements of environment **100** can perform one or more functions described as being performed by at least one different set of elements of environment **100**.

(31) Referring now to FIG. **2**, vehicle **200** includes autonomous system **202**, powertrain control system **204**, steering control system **206**, and brake system **208**. In some embodiments, vehicle **200** is the same as or similar to vehicle **102** (see FIG. **1**). In some embodiments, vehicle **102** have autonomous capability (e.g., implement at least one function, feature, device, and/or the like that enable vehicle **200** to be partially or fully operated without human intervention including, without limitation, fully autonomous vehicles (e.g., vehicles that forego reliance on human intervention), highly autonomous vehicles (e.g., vehicles that forego reliance on human intervention in certain

situations), and/or the like). For a detailed description of fully autonomous vehicles and highly autonomous vehicles, reference may be made to SAE International's standard J3016: Taxonomy and Definitions for Terms Related to On-Road Motor Vehicle Automated Driving Systems, which is incorporated by reference in its entirety. In some embodiments, vehicle **200** is associated with an autonomous fleet manager and/or a ridesharing company.

(32) Autonomous system **202** includes a sensor suite that includes one or more devices such as cameras **202a**, LiDAR sensors **202b**, radar sensors **202c**, and microphones **202d**. In some embodiments, autonomous system **202** can include more or fewer devices and/or different devices (e.g., ultrasonic sensors, inertial sensors, GPS receivers (discussed below), odometry sensors that generate data associated with an indication of a distance that vehicle **200** has traveled, and/or the like). In some embodiments, autonomous system **202** uses the one or more devices included in autonomous system **202** to generate data associated with environment **100**, described herein. The data generated by the one or more devices of autonomous system **202** can be used by one or more systems described herein to observe the environment (e.g., environment **100**) in which vehicle **200** is located. In some embodiments, autonomous system **202** includes communication device **202e**, autonomous vehicle compute **202f**, and drive-by-wire (DBW) system **202h**.

(33) Cameras **202a** include at least one device configured to be in communication with communication device **202e**, autonomous vehicle compute **202f**, and/or safety controller **202g** via a bus (e.g., a bus that is the same as or similar to bus **302** of FIG. 3). Cameras **202a** include at least one camera (e.g., a digital camera using a light sensor such as a charge-coupled device (CCD), a thermal camera, an infrared (IR) camera, an event camera, and/or the like) to capture images including physical objects (e.g., cars, buses, curbs, people, and/or the like). In some embodiments, camera **202a** generates camera data as output. In some examples, camera **202a** generates camera data that includes image data associated with an image. In this example, the image data may specify at least one parameter (e.g., image characteristics such as exposure, brightness, etc., an image timestamp, and/or the like) corresponding to the image. In such an example, the image may be in a format (e.g., RAW, JPEG, PNG, and/or the like). In some embodiments, camera **202a** includes a plurality of independent cameras configured on (e.g., positioned on) a vehicle to capture images for the purpose of stereopsis (stereo vision). In some examples, camera **202a** includes a plurality of cameras that generate image data and transmit the image data to autonomous vehicle compute **202f** and/or a fleet management system (e.g., a fleet management system that is the same as or similar to fleet management system **116** of FIG. 1). In such an example, autonomous vehicle compute **202f** determines depth to one or more objects in a field of view of at least two cameras of the plurality of cameras based on the image data from the at least two cameras. In some embodiments, cameras **202a** is configured to capture images of objects within a distance from cameras **202a** (e.g., up to 100 meters, up to a kilometer, and/or the like). Accordingly, cameras **202a** include features such as sensors and lenses that are optimized for perceiving objects that are at one or more distances from cameras **202a**.

(34) In an embodiment, camera **202a** includes at least one camera configured to capture one or more images associated with one or more traffic lights, street signs and/or other physical objects that provide visual navigation information. In some embodiments, camera **202a** generates traffic light data associated with one or more images. In some examples, camera **202a** generates TLD data associated with one or more images that include a format (e.g., RAW, JPEG, PNG, and/or the like). In some embodiments, camera **202a** that generates TLD data differs from other systems described herein incorporating cameras in that camera **202a** can include one or more cameras with a wide field of view (e.g., a wide-angle lens, a fish-eye lens, a lens having a viewing angle of approximately 120 degrees or more, and/or the like) to generate images about as many physical objects as possible.

(35) Laser Detection and Ranging (LiDAR) sensors **202b** include at least one device configured to be in communication with communication device **202e**, autonomous vehicle compute **202f**, and/or

safety controller **202g** via a bus (e.g., a bus that is the same as or similar to bus **302** of FIG. 3). LiDAR sensors **202b** include a system configured to transmit light from a light emitter (e.g., a laser transmitter). Light emitted by LiDAR sensors **202b** include light (e.g., infrared light and/or the like) that is outside of the visible spectrum. In some embodiments, during operation, light emitted by LiDAR sensors **202b** encounters a physical object (e.g., a vehicle) and is reflected back to LiDAR sensors **202b**. In some embodiments, the light emitted by LiDAR sensors **202b** does not penetrate the physical objects that the light encounters. LiDAR sensors **202b** also include at least one light detector which detects the light that was emitted from the light emitter after the light encounters a physical object. In some embodiments, at least one data processing system associated with LiDAR sensors **202b** generates an image (e.g., a point cloud, a combined point cloud, and/or the like) representing the objects included in a field of view of LiDAR sensors **202b**. In some examples, the at least one data processing system associated with LiDAR sensor **202b** generates an image that represents the boundaries of a physical object, the surfaces (e.g., the topology of the surfaces) of the physical object, and/or the like. In such an example, the image is used to determine the boundaries of physical objects in the field of view of LiDAR sensors **202b**.

(36) Radio Detection and Ranging (radar) sensors **202c** include at least one device configured to be in communication with communication device **202e**, autonomous vehicle compute **202f**, and/or safety controller **202g** via a bus (e.g., a bus that is the same as or similar to bus **302** of FIG. 3). Radar sensors **202c** include a system configured to transmit radio waves (either pulsed or continuously). The radio waves transmitted by radar sensors **202c** include radio waves that are within a predetermined spectrum. In some embodiments, during operation, radio waves transmitted by radar sensors **202c** encounter a physical object and are reflected back to radar sensors **202c**. In some embodiments, the radio waves transmitted by radar sensors **202c** are not reflected by some objects. In some embodiments, at least one data processing system associated with radar sensors **202c** generates signals representing the objects included in a field of view of radar sensors **202c**. For example, the at least one data processing system associated with radar sensor **202c** generates an image that represents the boundaries of a physical object, the surfaces (e.g., the topology of the surfaces) of the physical object, and/or the like. In some examples, the image is used to determine the boundaries of physical objects in the field of view of radar sensors **202c**.

(37) Microphones **202d** includes at least one device configured to be in communication with communication device **202e**, autonomous vehicle compute **202f**, and/or safety controller **202g** via a bus (e.g., a bus that is the same as or similar to bus **302** of FIG. 3). Microphones **202d** include one or more microphones (e.g., array microphones, external microphones, and/or the like) that capture audio signals and generate data associated with (e.g., representing) the audio signals. In some examples, microphones **202d** include transducer devices and/or like devices. In some embodiments, one or more systems described herein can receive the data generated by microphones **202d** and determine a position of an object relative to vehicle **200** (e.g., a distance and/or the like) based on the audio signals associated with the data.

(38) Communication device **202e** include at least one device configured to be in communication with cameras **202a**, LiDAR sensors **202b**, radar sensors **202c**, microphones **202d**, autonomous vehicle compute **202f**, safety controller **202g**, and/or DBW system **202h**. For example, communication device **202e** may include a device that is the same as or similar to communication interface **314** of FIG. 3. In some embodiments, communication device **202e** includes a vehicle-to-vehicle (V2V) communication device (e.g., a device that enables wireless communication of data between vehicles).

(39) Autonomous vehicle compute **202f** include at least one device configured to be in communication with cameras **202a**, LiDAR sensors **202b**, radar sensors **202c**, microphones **202d**, communication device **202e**, safety controller **202g**, and/or DBW system **202h**. In some examples, autonomous vehicle compute **202f** includes a device such as a client device, a mobile device (e.g., a cellular telephone, a tablet, and/or the like) a server (e.g., a computing device including one or

more central processing units, graphical processing units, and/or the like), and/or the like. In some embodiments, autonomous vehicle compute **202f** is the same as or similar to autonomous vehicle compute **400**, described herein. Additionally, or alternatively, in some embodiments autonomous vehicle compute **202f** is configured to be in communication with an autonomous vehicle system (e.g., an autonomous vehicle system that is the same as or similar to remote AV system **114** of FIG. **1**), a fleet management system (e.g., a fleet management system that is the same as or similar to fleet management system **116** of FIG. **1**), a V2I device (e.g., a V2I device that is the same as or similar to V2I device **110** of FIG. **1**), and/or a V2I system (e.g., a V2I system that is the same as or similar to V2I system **118** of FIG. **1**).

(40) Safety controller **202g** includes at least one device configured to be in communication with cameras **202a**, LiDAR sensors **202b**, radar sensors **202c**, microphones **202d**, communication device **202e**, autonomous vehicle computer **202f**, and/or DBW system **202h**. In some examples, safety controller **202g** includes one or more controllers (electrical controllers, electromechanical controllers, and/or the like) that are configured to generate and/or transmit control signals to operate one or more devices of vehicle **200** (e.g., powertrain control system **204**, steering control system **206**, brake system **208**, and/or the like). In some embodiments, safety controller **202g** is configured to generate control signals that take precedence over (e.g., overrides) control signals generated and/or transmitted by autonomous vehicle compute **202f**.

(41) DBW system **202h** includes at least one device configured to be in communication with communication device **202e** and/or autonomous vehicle compute **202f**. In some examples, DBW system **202h** includes one or more controllers (e.g., electrical controllers, electromechanical controllers, and/or the like) that are configured to generate and/or transmit control signals to operate one or more devices of vehicle **200** (e.g., powertrain control system **204**, steering control system **206**, brake system **208**, and/or the like). Additionally, or alternatively, the one or more controllers of DBW system **202h** are configured to generate and/or transmit control signals to operate at least one different device (e.g., a turn signal, headlights, door locks, windshield wipers, and/or the like) of vehicle **200**.

(42) Powertrain control system **204** includes at least one device configured to be in communication with DBW system **202h**. In some examples, powertrain control system **204** includes at least one controller, actuator, and/or the like. In some embodiments, powertrain control system **204** receives control signals from DBW system **202h** and powertrain control system **204** causes vehicle **200** to start moving forward, stop moving forward, start moving backward, stop moving backward, accelerate in a direction, decelerate in a direction, perform a left turn, perform a right turn, and/or the like. In an example, powertrain control system **204** causes the energy (e.g., fuel, electricity, and/or the like) provided to a motor of the vehicle to increase, remain the same, or decrease, thereby causing at least one wheel of vehicle **200** to rotate or not rotate.

(43) Steering control system **206** includes at least one device configured to rotate one or more wheels of vehicle **200**. In some examples, steering control system **206** includes at least one controller, actuator, and/or the like. In some embodiments, steering control system **206** causes the front two wheels and/or the rear two wheels of vehicle **200** to rotate to the left or right to cause vehicle **200** to turn to the left or right.

(44) Brake system **208** includes at least one device configured to actuate one or more brakes to cause vehicle **200** to reduce speed and/or remain stationary. In some examples, brake system **208** includes at least one controller and/or actuator that is configured to cause one or more calipers associated with one or more wheels of vehicle **200** to close on a corresponding rotor of vehicle **200**. Additionally, or alternatively, in some examples brake system **208** includes an automatic emergency braking (AEB) system, a regenerative braking system, and/or the like.

(45) In some embodiments, vehicle **200** includes at least one platform sensor (not explicitly illustrated) that measures or infers properties of a state or a condition of vehicle **200**. In some examples, vehicle **200** includes platform sensors such as a global positioning system (GPS)

receiver, an inertial measurement unit (IMU), a wheel speed sensor, a wheel brake pressure sensor, a wheel torque sensor, an engine torque sensor, a steering angle sensor, and/or the like.

(46) Referring now to FIG. 3, illustrated is a schematic diagram of a device **300**. As illustrated, device **300** includes processor **304**, memory **306**, storage component **308**, input interface **310**, output interface **312**, communication interface **314**, and bus **302**. In some embodiments, device **300** corresponds to at least one device of vehicles **102** (e.g., at least one device of a system of vehicles **102**), and/or one or more devices of network **112** (e.g., one or more devices of a system of network **112**). In some embodiments, one or more devices of vehicles **102** (e.g., one or more devices of a system of vehicles **102**), and/or one or more devices of network **112** (e.g., one or more devices of a system of network **112**) include at least one device **300** and/or at least one component of device **300**. As shown in FIG. 3, device **300** includes bus **302**, processor **304**, memory **306**, storage component **308**, input interface **310**, output interface **312**, and communication interface **314**.

(47) Bus **302** includes a component that permits communication among the components of device **300**. In some embodiments, processor **304** is implemented in hardware, software, or a combination of hardware and software. In some examples, processor **304** includes a processor (e.g., a central processing unit (CPU), a graphics processing unit (GPU), an accelerated processing unit (APU), and/or the like), a microphone, a digital signal processor (DSP), and/or any processing component (e.g., a field-programmable gate array (FPGA), an application specific integrated circuit (ASIC), and/or the like) that can be programmed to perform at least one function. Memory **306** includes random access memory (RAM), read-only memory (ROM), and/or another type of dynamic and/or static storage device (e.g., flash memory, magnetic memory, optical memory, and/or the like) that stores data and/or instructions for use by processor **304**.

(48) Storage component **308** stores data and/or software related to the operation and use of device **300**. In some examples, storage component **308** includes a hard disk (e.g., a magnetic disk, an optical disk, a magneto-optic disk, a solid-state disk, and/or the like), a compact disc (CD), a digital versatile disc (DVD), a floppy disk, a cartridge, a magnetic tape, a CD-ROM, RAM, PROM, EPROM, FLASH-EPROM, NV-RAM, and/or another type of computer readable medium, along with a corresponding drive.

(49) Input interface **310** includes a component that permits device **300** to receive information, such as via user input (e.g., a touchscreen display, a keyboard, a keypad, a mouse, a button, a switch, a microphone, a camera, and/or the like). Additionally, or alternatively, in some embodiments input interface **310** includes a sensor that senses information (e.g., a global positioning system (GPS) receiver, an accelerometer, a gyroscope, an actuator, and/or the like). Output interface **312** includes a component that provides output information from device **300** (e.g., a display, a speaker, one or more light-emitting diodes (LEDs), and/or the like).

(50) In some embodiments, communication interface **314** includes a transceiver-like component (e.g., a transceiver, a separate receiver and transmitter, and/or the like) that permits device **300** to communicate with other devices via a wired connection, a wireless connection, or a combination of wired and wireless connections. In some examples, communication interface **314** permits device **300** to receive information from another device and/or provide information to another device. In some examples, communication interface **314** includes an Ethernet interface, an optical interface, a coaxial interface, an infrared interface, a radio frequency (RF) interface, a universal serial bus (USB) interface, a Wi-Fi® interface, a cellular network interface, and/or the like.

(51) In some embodiments, device **300** performs one or more processes described herein. Device **300** performs these processes based on processor **304** executing software instructions stored by a computer-readable medium, such as memory **306** and/or storage component **308**. A computer-readable medium (e.g., a non-transitory computer readable medium) is defined herein as a non-transitory memory device. A non-transitory memory device includes memory space located inside a single physical storage device or memory space spread across multiple physical storage devices.

(52) In some embodiments, software instructions are read into memory **306** and/or storage

component **308** from another computer-readable medium or from another device via communication interface **314**. When executed, software instructions stored in memory **306** and/or storage component **308** cause processor **304** to perform one or more processes described herein. Additionally, or alternatively, hardwired circuitry is used in place of or in combination with software instructions to perform one or more processes described herein. Thus, embodiments described herein are not limited to any specific combination of hardware circuitry and software unless explicitly stated otherwise.

(53) Memory **306** and/or storage component **308** includes data storage or at least one data structure (e.g., a database and/or the like). Device **300** is capable of receiving information from, storing information in, communicating information to, or searching information stored in the data storage or the at least one data structure in memory **306** or storage component **308**. In some examples, the information includes network data, input data, output data, or any combination thereof.

(54) In some embodiments, device **300** is configured to execute software instructions that are either stored in memory **306** and/or in the memory of another device (e.g., another device that is the same as or similar to device **300**). As used herein, the term “module” refers to at least one instruction stored in memory **306** and/or in the memory of another device that, when executed by processor **304** and/or by a processor of another device (e.g., another device that is the same as or similar to device **300**) cause device **300** (e.g., at least one component of device **300**) to perform one or more processes described herein. In some embodiments, a module is implemented in software, firmware, hardware, and/or the like.

(55) The number and arrangement of components illustrated in FIG. **3** are provided as an example. In some embodiments, device **300** can include additional components, fewer components, different components, or differently arranged components than those illustrated in FIG. **3**. Additionally, or alternatively, a set of components (e.g., one or more components) of device **300** can perform one or more functions described as being performed by another component or another set of components of device **300**.

(56) Referring now to FIG. **4**, illustrated is an example block diagram of an autonomous vehicle compute **400** (sometimes referred to as an “AV stack”). As illustrated, autonomous vehicle compute **400** includes perception system **402** (sometimes referred to as a perception module), planning system **404** (sometimes referred to as a planning module), localization system **406** (sometimes referred to as a localization module), control system **408** (sometimes referred to as a control module), and database **410**. In some embodiments, perception system **402**, planning system **404**, localization system **406**, control system **408**, and database **410** are included and/or implemented in an autonomous navigation system of a vehicle (e.g., autonomous vehicle compute **202f** of vehicle **200**). Additionally, or alternatively, in some embodiments perception system **402**, planning system **404**, localization system **406**, control system **408**, and database **410** are included in one or more standalone systems (e.g., one or more systems that are the same as or similar to autonomous vehicle compute **400** and/or the like). In some examples, perception system **402**, planning system **404**, localization system **406**, control system **408**, and database **410** are included in one or more standalone systems that are located in a vehicle and/or at least one remote system as described herein. In some embodiments, any and/or all of the systems included in autonomous vehicle compute **400** are implemented in software (e.g., in software instructions stored in memory), computer hardware (e.g., by microprocessors, microcontrollers, application-specific integrated circuits [ASICs], Field Programmable Gate Arrays (FPGAs), and/or the like), or combinations of computer software and computer hardware. It will also be understood that, in some embodiments, autonomous vehicle compute **400** is configured to be in communication with a remote system (e.g., an autonomous vehicle system that is the same as or similar to remote AV system **114**, a fleet management system **116** that is the same as or similar to fleet management system **116**, a V2I system that is the same as or similar to V2I system **118**, and/or the like).

(57) In some embodiments, perception system **402** receives data associated with at least one

physical object (e.g., data that is used by perception system **402** to detect the at least one physical object) in an environment and classifies the at least one physical object. In some examples, perception system **402** receives image data captured by at least one camera (e.g., cameras **202a**), the image associated with (e.g., representing) one or more physical objects within a field of view of the at least one camera. In such an example, perception system **402** classifies at least one physical object based on one or more groupings of physical objects (e.g., bicycles, vehicles, traffic signs, pedestrians, and/or the like). In some embodiments, perception system **402** transmits data associated with the classification of the physical objects to planning system **404** based on perception system **402** classifying the physical objects.

(58) In some embodiments, planning system **404** receives data associated with a destination and generates data associated with at least one route (e.g., routes **106**) along which a vehicle (e.g., vehicles **102**) can travel along toward a destination. In some embodiments, planning system **404** periodically or continuously receives data from perception system **402** (e.g., data associated with the classification of physical objects, described above) and planning system **404** updates the at least one trajectory or generates at least one different trajectory based on the data generated by perception system **402**. In some embodiments, planning system **404** receives data associated with an updated position of a vehicle (e.g., vehicles **102**) from localization system **406** and planning system **404** updates the at least one trajectory or generates at least one different trajectory based on the data generated by localization system **406**.

(59) In some embodiments, localization system **406** receives data associated with (e.g., representing) a location of a vehicle (e.g., vehicles **102**) in an area. In some examples, localization system **406** receives LiDAR data associated with at least one point cloud generated by at least one LiDAR sensor (e.g., LiDAR sensors **202b**). In certain examples, localization system **406** receives data associated with at least one point cloud from multiple LiDAR sensors and localization system **406** generates a combined point cloud based on each of the point clouds. In these examples, localization system **406** compares the at least one point cloud or the combined point cloud to two-dimensional (2D) and/or a three-dimensional (3D) map of the area stored in database **410**.

Localization system **406** then determines the position of the vehicle in the area based on localization system **406** comparing the at least one point cloud or the combined point cloud to the map. In some embodiments, the map includes a combined point cloud of the area generated prior to navigation of the vehicle. In some embodiments, maps include, without limitation, high-precision maps of the roadway geometric properties, maps describing road network connectivity properties, maps describing roadway physical properties (such as traffic speed, traffic volume, the number of vehicular and cyclist traffic lanes, lane width, lane traffic directions, or lane marker types and locations, or combinations thereof), and maps describing the spatial locations of road features such as crosswalks, traffic signs or other travel signals of various types. In some embodiments, the map is generated in real-time based on the data received by the perception system.

(60) In another example, localization system **406** receives Global Navigation Satellite System (GNSS) data generated by a global positioning system (GPS) receiver. In some examples, localization system **406** receives GNSS data associated with the location of the vehicle in the area and localization system **406** determines a latitude and longitude of the vehicle in the area. In such an example, localization system **406** determines the position of the vehicle in the area based on the latitude and longitude of the vehicle. In some embodiments, localization system **406** generates data associated with the position of the vehicle. In some examples, localization system **406** generates data associated with the position of the vehicle based on localization system **406** determining the position of the vehicle. In such an example, the data associated with the position of the vehicle includes data associated with one or more semantic properties corresponding to the position of the vehicle.

(61) In some embodiments, control system **408** receives data associated with at least one trajectory from planning system **404** and control system **408** controls operation of the vehicle. In some

examples, control system **408** receives data associated with at least one trajectory from planning system **404** and control system **408** controls operation of the vehicle by generating and transmitting control signals to cause a powertrain control system (e.g., DBW system **202h**, powertrain control system **204**, and/or the like), a steering control system (e.g., steering control system **206**), and/or a brake system (e.g., brake system **208**) to operate. In an example, where a trajectory includes a left turn, control system **408** transmits a control signal to cause steering control system **206** to adjust a steering angle of vehicle **200**, thereby causing vehicle **200** to turn left. Additionally, or alternatively, control system **408** generates and transmits control signals to cause other devices (e.g., headlights, turn signal, door locks, windshield wipers, and/or the like) of vehicle **200** to change states.

(62) In some embodiments, perception system **402**, planning system **404**, localization system **406**, and/or control system **408** implement at least one machine learning model (e.g., at least one multilayer perceptron (MLP), at least one convolutional neural network (CNN), at least one recurrent neural network (RNN), at least one autoencoder, at least one transformer, and/or the like). In some examples, perception system **402**, planning system **404**, localization system **406**, and/or control system **408** implement at least one machine learning model alone or in combination with one or more of the above-noted systems. In some examples, perception system **402**, planning system **404**, localization system **406**, and/or control system **408** implement at least one machine learning model as part of a pipeline (e.g., a pipeline for identifying one or more objects located in an environment and/or the like).

(63) Database **410** stores data that is transmitted to, received from, and/or updated by perception system **402**, planning system **404**, localization system **406** and/or control system **408**. In some examples, database **410** includes a storage component (e.g., a storage component that is the same as or similar to storage component **308** of FIG. 3) that stores data and/or software related to the operation and uses at least one system of autonomous vehicle compute **400**. In some embodiments, database **410** stores data associated with 2D and/or 3D maps of at least one area. In some examples, database **410** stores data associated with 2D and/or 3D maps of a portion of a city, multiple portions of multiple cities, multiple cities, a county, a state, a State (e.g., a country), and/or the like). In such an example, a vehicle (e.g., a vehicle that is the same as or similar to vehicles **102** and/or vehicle **200**) can drive along one or more drivable regions (e.g., single-lane roads, multi-lane roads, highways, back roads, off road trails, and/or the like) and cause at least one LiDAR sensor (e.g., a LiDAR sensor that is the same as or similar to LiDAR sensors **202b**) to generate data associated with an image representing the objects included in a field of view of the at least one LiDAR sensor.

(64) In some embodiments, database **410** can be implemented across a plurality of devices. In some examples, database **410** is included in a vehicle (e.g., a vehicle that is the same as or similar to vehicles **102** and/or vehicle **200**), an autonomous vehicle system (e.g., an autonomous vehicle system that is the same as or similar to remote AV system **114**, a fleet management system (e.g., a fleet management system that is the same as or similar to fleet management system **116** of FIG. 1, a V2I system (e.g., a V2I system that is the same as or similar to V2I system **118** of FIG. 1) and/or the like.

(65) Verifying Performance of Image Sensors of a Vehicle

(66) As a vehicle (e.g., an autonomous vehicle) moves through an area, the vehicle may encounter a number of different objects within the area. To identify the objects, the vehicle can capture sensor data associated with at least one sensor. The sensors can include any one or any combination of radar sensors, lidar sensors, cameras, etc. The vehicle can process the captured sensor data to obtain environmental data associated with an environment of the vehicle. Based on the environmental data, the vehicle can determine how to navigate the environment and potential obstacles within the environment that are captured by the sensor data. Further, the vehicle can navigate the environment based on the determination. For example, the vehicle can include a navigational system to assist in navigation based on the environmental data.

(67) It may be important to ensure that each of the image sensors be calibrated to determine an

accuracy of the received image data. Further, each of the image sensors can be extrinsically calibrated relative to the vehicle and/or one or more components of the vehicle and intrinsically calibrated. The extrinsic calibration of the image sensors can include calibrating a positioning of each of the image sensors relative to the positioning of the vehicle, the positioning of additional image sensors, or the positioning of any other component of the vehicle. The image sensors may be mounted to the vehicle based on the extrinsic calibration of the image sensors. The intrinsic calibration of the image sensors can include calibrating one or more parameters of the image sensor used by the image sensor to generate the sensor data. For example, the parameters of the image sensor may include focal length, image sensor format, principal point, or skew. The image sensors may be mounted to the vehicle based on the extrinsic calibration and the intrinsic calibration (e.g., the image sensors may have an initial extrinsic calibration and an initial intrinsic calibration when mounted to the vehicle). The vehicle may use the initial extrinsic calibration and initial intrinsic calibration of each image sensor to identify objects in the environment of the vehicle based on the received sensor data.

(68) During the operation of a vehicle, the performance (e.g., optimal performance) of the image sensors may degrade. For example, the optical performance may degrade from a particular performance specification. Further, it may be desirable to further calibrate one or more parameters of the image sensor. Degradations in the performance of the image sensors can decrease the safety of the vehicle for passengers as the system may not be able to accurately identify objects or features of an image (e.g., a position of another vehicle relative to the image sensor). For example, the performance of the image sensor may degrade and the images produced by the image sensor may be increasingly overexposed or underexposed, thereby making it difficult for the perception system to detect objects in the images. This can also lead to an inadequate user experience as the perception system may be unable to identify particular objects or features of an image. In some cases, the image sensors can be recalibrated by dismounting the image sensors from the vehicle and individually calibrating each image sensor. However, such a dismounting of the image sensors for calibration can be expensive and time consuming. Further, in some cases, the dismounting of the image sensors may not be appropriate for each user. This can lead to an inadequate user experience as the system may be limited to recalibrating image sensors that are each dismounted from the vehicle.

(69) To address these issues, a signal processing system can use one or more collimators (e.g., collimators aligned in a frame) to verify the performance of the image sensors without dismounting the image sensors from the vehicle. By aligning the one or more collimators with the image sensors, the signal processing system can obtain sensor data from the image sensors and verify the performance of the image sensors without dismounting the image sensors. In some cases, the signal processing system can verify the optical performance and/or the intrinsic calibration of the image sensors

(70) As described herein, the signal processing system can cause alignment of the one or more collimators with the one or more image sensors mounted to a vehicle. In some cases, the signal processing system can cause a robot (e.g., a robotic arm) to align the one or more collimators with the one or more image sensors. For example, the signal processing system can instruct the robot to move the collimators (e.g., the collimators aligned in a frame) to a particular position based on the position of the vehicle. In some embodiments, the alignment of the one or more collimators with the one or more image sensors may be customized based on the make of the vehicle, the model of the vehicle, the year of the vehicle, the type of the vehicle, any modifications to the vehicle, a number and/or type of image sensors mounted to the vehicle, or any other data associated with the vehicle. For example, the signal processing can instruct a robot to move the one or more collimators to a specific position for a pickup truck and a different position for a sedan.

(71) Further, the signal processing system can obtain sensor data associated with the image sensors based on causing alignment of the one or more collimators with the one or more image sensors.

The sensor data can include, but is not limited to, image data associated with one or more images outside of the vehicle (e.g., lidar data associated with a lidar sensor, radar data associated with a radar sensor, camera image data associated with a camera image).

(72) Based on the obtained sensor data, the signal processing system can determine whether the sensor data satisfies a performance specification. In some cases, the signal processing system can process the sensor data to identify a performance of the one or more image sensors. For example, the signal processing system can process the sensor data to identify an optical performance of the one or more image sensors and/or updated parameters for the image sensor. Further, the signal processing system can compare a value identifying the performance of the one or more image sensors with a performance specification (e.g., a performance threshold). In some cases, the performance specification may include an optical performance specification and/or original parameters for the image sensor.

(73) Further, the signal processing system can determine an image sensor alert based on comparing the performance of the one or more image sensors to the performance specification. In some cases, the signal processing system can determine the image sensor alert using alert mapping data. In some embodiments, different values for the performance of the one or more image sensors can be mapped to different image sensor alerts using the alert mapping data. For example, a first performance value that differs from a performance specification by 50% and a second performance value that differs from the performance specification by 80% may be mapped to different image sensor alerts. Accordingly, based on the performance of the one or more sensors and the performance specification, the signal processing system can identify an image sensor alert.

(74) The signal processing system may route the image sensor alert based on the type of the image sensor alert. In some cases, the signal processing system may route the image sensor alert to a computing device and the image sensor alert may identify that a particular image sensor should be dismounted from the vehicle for further testing and/or recalibration. Further, the signal processing system may route the image sensor alert to a computing device and the image sensor alert may identify that the parameters of the particular image sensor should be updated. In some embodiments, by routing the image sensor alert, the signal processing system may route the particular image sensor for further testing and/or may update the parameters of the image sensor.

(75) FIG. 5 is a block diagram illustrating an example of a signal processing environment **500**. In the illustrated example, the signal processing environment **500** includes a signal processing system **502** communicatively coupled with a sensor **504**, a computing device **510**, and a computing device **514**. In some cases, the signal processing environment **500** and/or the signal processing system **502** can form at least a part of the perception system **402**, described herein at least with reference to FIG. 4. The signal processing system **502** can receive sensor data **506** associated with the sensor **504**, and use the sensor data **506** to identify performance data associated with the sensor data **506**. Further, the signal processing system **502** can determine alert data associated with a vehicle alert. In some cases, the signal processing system **502** can use alert mapping data associated with a mapping of sensor data (and/or performance data) to alert data to determine which image sensor alerts to activate based on incoming sensor data **506**.

(76) The signal processing system **502** (or another computing system) may cause alignment of one or more collimators, not shown in FIG. 5, with the sensor **504**. As will be discussed below, the signal processing system **502** can cause the alignment of multiple collimators with multiple image sensors. In some cases, the signal processing system **502** may determine whether the one or more collimators are aligned with the sensor **504** based on the sensor data **506** identifying a slanted edge. The signal processing system **502** may cause alignment of the one or more collimators with the sensor **504** by aligning the axis of the one or more collimators with the axis of the sensor **504**.

(77) Based on the alignment of the one or more collimators with the sensor **504**, the sensor **504** generates sensor data **506** and communicates the sensor data **506** to the signal processing system **502**. In some cases, the signal processing system **502** may cause the sensor **504** to generate the

sensor data **506** based on the alignment of the one or more collimators with the sensor **504**. The sensor **504** can include any one or any combination of a camera **202a**, LiDAR sensor **202b**, radar sensor **202c**, etc., similar to that described above with reference to FIG. 2. In some embodiments, the sensor **504** may include a plurality of sensors (e.g., a plurality of different sensors) that may each provide sensor data **506** to the signal processing system **502**. Similarly, the sensor data **506** can include different types of sensor data, such as camera data associated with a camera image, radar data associated with a radar image, LiDAR data associated with a point cloud, etc. Further, the sensor data **506** can include sensor data associated with an environment outside of the vehicle. The sensor **504** may generate sensor data **506** based on one or more sensor signal processing settings (e.g., white balance, gain, tint, exposure, color balance, saturation, etc.). For example, the one or more sensor signal processing settings may identify a time period for detection of the sensor data. The sensor data **506** may include streaming sensor data and/or batch sensor data.

(78) The sensor **504** generates the sensor data **506** based on intrinsic parameters and extrinsic parameters. The intrinsic parameters may include any one or any combination of a scale factor, a focal length, a principal point (e.g., a sensor center), a skew, a geometric distortion, etc. associated with the sensor **504** and the extrinsic parameters may include a rotation, a translation, etc. associated with the sensor **504**. The sensor **504** may utilize the intrinsic parameters to map the sensor data from three-dimensional world points to a two-dimensional image plane.

(79) The signal processor **508** (or another computing system) may calibrate the sensor **504** to identify a first set of intrinsic parameters for generating the sensor data **506**. The sensor **504** may be calibrated based on a series of images. For example, the sensor **504** may be calibrated using two-dimensional sensor calibration (e.g., using a particular two-dimensional pattern), three-dimensional sensor calibration, or self-calibration to identify the first set of intrinsic parameters. Based on the calibration of the sensor **504**, the sensor **504** may identify the first set of intrinsic parameters and may generate the sensor data **506** based on the first set of intrinsic parameters.

(80) In the illustrated example, the signal processing system **502** includes a signal processor **508** to receive the sensor data **506**, however, it will be understood that the signal processing system **502** can include fewer, more, or different components. The signal processor **508** may process the sensor data **506** to generate performance data. In some cases, the signal processor **508** may process the sensor data **506** to identify optical performance data (e.g., a measurement of the optical performance potential) associated with the sensor data **506** and the sensor **504**. For example, the signal processor **508** may process the sensor data **506** to identify a modulation transfer function (“MTF”). The optical performance data may identify the contrast and/or resolution of a lens of the sensor **504**.

(81) To identify the MTF, the signal processor **508** can receive sensor data **506** identifying a collimated beam of light from the sensor **504**. The signal processor **508** can identify a line spread function from the sensor data **506** and apply a Fourier transform to the line spread function to obtain the MTF.

(82) In some cases, the signal processor **508** may process the sensor data **506** to identify a second set of intrinsic parameters. The second set of intrinsic parameters may include any one or any combination of a scale factor, a focal length, a principal point (e.g., a sensor center), a skew, a geometric distortion, etc. associated with the sensor **504**. The second set of intrinsic parameters may include a modification to any one of the first set of intrinsic parameters. For example, the first set of intrinsic parameters may include a scale factor and the second set of intrinsic parameters may include a modified scale factor. The signal processor **508** may process the sensor data **506** to recalibrate the sensor **504** to identify a second set of intrinsic parameters for generating the sensor data **506**. For example, the signal processor **508** may recalibrate the sensor **504** using the sensor data **506** to identify the second set of intrinsic parameters. Accordingly, the signal processor **508** can generate performance data (e.g., optical performance data, a second set of intrinsic parameters, etc.) using the sensor data **506**.

(83) The signal processor **508** may also receive performance specification data **512** associated with one or more performance specifications of the sensor **504**. The signal processor **508** may receive the performance specification data **512** from a computing device **510** and/or a data store. In some cases, the signal processor **508** may parse the performance specification data **512** to identify a subset of the performance specification data **512** associated with the image sensor (e.g., based on the type of image sensor). The performance specification data **512** may include predetermined performance specifications associated with the image sensor. For example, the performance specification data **512** may include a predetermined optical performance specification for the image sensor. In some cases, the performance specification data **512** may include the first set of intrinsic parameters. Further, the performance specification data **512** may include a plurality of values (e.g., thresholds, ranges, etc.) identifying one or more specifications of the sensor **504**.

(84) Further, the signal processor **508** may compare the performance data with the performance specification data **512**. In some cases, the signal processor **508** may compare the optical performance data with the optical performance specification and/or may compare the first set of intrinsic parameters with the second set of intrinsic parameters. Based on comparing the performance data with the performance specification data **512**, the signal processor **508** may determine whether the performance data satisfies the performance specification data **512**. For example, the signal processor **508** may determine whether values of the performance data match values of the performance specification data **512**. In some embodiments, the signal processor **508** may determine whether the values of the performance data are greater than a value of the performance specification data **512** (e.g., where the performance specification data **512** includes a minimum value) and/or are less than a value of the performance specification data **512** (e.g., where the performance specification data includes a maximum value). Accordingly, the signal processor **508** may determine whether the performance data satisfies the performance specification data **512** (e.g., matches a value of the performance specification data **512**, satisfies a threshold or range of the performance specification data **512**, etc.).

(85) Based on comparing the performance data with the performance specification data **512**, the signal processor **508** may identify a difference between the performance data and the performance specification data **512**. In some cases, the signal processor **508** may identify an amount of difference between the performance data and the performance specification data **512** (e.g., the quantifiable amount by which the performance data and the performance specification data **512** differ).

(86) The signal processor **508** may further obtain alert mapping data. For example, the signal processor **508** may obtain alert mapping data from a computing device (e.g., a user computing device) and/or a data store. For example, the user computing device may generate the alert mapping data and provide the alert mapping data to the signal processor **508**. In some embodiments, the alert mapping data may be user specific and/or image sensor specific alert mapping data. The alert mapping data may include a plurality of mappings. The alert mapping data may include first alert mapping data and second alert mapping data. Each mapping of the first alert mapping data may identify a difference between performance data and performance specification data **512** mapped to a particular image sensor alert. Each mapping of the second alert mapping data may identify a particular image sensor alert mapped to particular alert data. In some cases, each mapping of the alert mapping data may identify a difference between performance data and performance specification data **512** mapped to particular alert data.

(87) Based on identifying alert data **516** using the alert mapping data, the signal processor **508** may determine that a user should be notified of the image sensor alert. In some cases, the signal processor **508** may use alert mapping data associated with a mapping of the difference between the performance data and the performance specification data to alert data to determine the alert data to output to the computing device **514**. Accordingly, the signal processor **508** can provide the alert data to the computing device **514**.

(88) The alert data may include a recommendation (e.g., an instruction) for a user to perform further calibration and/or testing of the sensor **504**. For example, the alert data may include a recommendation for a user to perform manual calibration of the sensor **504**. Further, the signal processor **508** may cause the sensor **504** to be routed for additional calibration. For example, the signal processor **508** may send the alert data to a robot to activate the robot. The signal processor **508** may activate the robot to cause the robot to transport the sensor **504** for additional calibration. In some cases, the alert data may identify the type of further calibration to be performed for the sensor **504**.

(89) In some cases, the signal processor **508** may cause the computing device **514** to replace the intrinsic parameters of the sensor **504** based on sending the alert data to the computing device **514**. Further, in response to receiving the alert data, the computing device may automatically replace the first set of intrinsic parameters with the second set of intrinsic parameters.

(90) Example Frame of Collimators

(91) FIG. **6** is a diagram **600** illustrating example frame including a plurality of collimators. For example, the diagram **600** includes a plurality of collimators that are each affixed to a frame **602** (e.g., a rig, a support, a fixture, etc.). Each of the plurality of collimators can be mapped to a particular position on the frame **602**. Further, each of the plurality of collimators can be affixed to the frame **602** based on the mapping. In the example of FIG. **6**, the plurality of collimators includes a first collimator **604A**, a second collimator **604B**, a third collimator **604C**, a fourth collimator **604D**, a fifth collimator **604E**, and a sixth collimator **604F** that are each affixed to the frame **602**. It will be understood that the plurality of collimators may include more, less, or different collimators.

(92) Each of the plurality of collimators can receive a beam of light and produce a collimated beam of light. For example, each of the plurality of collimators can receive a beam of light from a light source and produce the collimated beam of light. In some embodiments, one or more of the plurality of collimators may include an associated light source to produce the beam of light. Further, each of the plurality of collimators may include a curved mirror, a lens, etc. to produce the collimated beam of light from the beam of light.

(93) In some cases, one or more of the plurality of collimators may be arranged between a laser (e.g., a solid-state laser) and a diffractive optical element. Further, the optical axes of the laser, the particular collimator, and the diffractive optical element may be mutually aligned along a particular optical path. The laser may output a beam of light (e.g., a laser beam) to the particular collimator. In some embodiments, the laser may be a fiber laser. For example, a fiber optic cable may be an amplification medium (e.g., an active gain medium) of the laser. One or more laser diodes may provide light to the fiber optic cable to cause the fiber optic cable to produce an amplified beam of light which may be output by the laser. Further, the collimator may be a fiber optic collimator to receive the amplified beam of light and produce a collimated beam of light. In some cases, the laser may output the beam of light through a beam expanding lens. The beam expanding lens can expand the beam of light and provides the expanded beam of light to the particular collimator. In other cases, the particular collimator may be a beam expanding collimator and may expand the beam of light output by the laser to provide an expanded beam of light. Further, the particular collimator may output a collimated beam of light based on the light beam provided by the laser (or the expanded light beam provided by the beam expanding lens).

(94) The diffractive optical element may receive the collimated beam of light from the particular collimator. Further, the diffractive optical element may split the collimated beam of light into multiple beams of light by passing the collimated beam through various apertures of a first surface of the diffractive optical element. The diffractive optical element may output the multiple beams of lights through various ridges of a second surface of the diffractive optical element to provide the multiple beams of light to a lens of a sensor (e.g., sensor **504**). As discussed above, the performance of the sensor may be verified using the multiple beams of light. For example, the multiple beams of light may enable calculation of at least one intrinsic parameter (e.g., a scale

factor, a focal length, a principal point (e.g., a sensor center), a skew, a geometric distortion, etc. associated with the sensor) or an optical performance of the sensor.

(95) The diffractive optical element may be designed to produce the multiple beams of light. For example, a grating angle of the diffractive optical element may be predetermined based on a desired number of light beams in which a primary light beam is to be split. Further, the diffractive optical element may be designed based on a field of view and/or a resolution of a sensor. For instance, for a sensor having a field of view of 30 degrees and a resolution of 2 degrees, the diffractive optical element may split a primary light beam into 15 light beams to cover each 2-degree resolution interval from the 30 degrees of the field of view. In some cases, size of a primary light beam and/or a size of the multiple light beams into which the primary light beam is split by the diffractive optical element may be defined based on a cross-sectional area of the diffractive optical element, such as by sizing the apertures to utilize a maximal amount of cross-sectional area of a side of the diffractive optical element.

(96) In the example of FIG. 6, the first collimator **604A** is affixed to the frame **602** at a first position, the second collimator **604B** is affixed to the frame **602** at a second position, the third collimator **604C** is affixed to the frame **602** at a third position, the fourth collimator **604D** is affixed to the frame **602** at a fourth position, the fifth collimator **604E** is affixed to the frame **602** at a fifth position, and the sixth collimator **604F** is affixed to the frame **602** at a sixth position. It will be understood that each of the plurality of collimators may be affixed to the frame at more, less, or different positions.

(97) The positioning of each of the plurality of collimators relative to the frame **602** may be based on the particular type of vehicle (e.g., characteristics of the vehicle, features of the vehicle, etc.) and/or a particular configuration of the set of sensors associated with the vehicle. As each vehicle may have different characteristics (e.g., height, width, etc.) and/or features (e.g., luggage rack, different sensors, etc.) and the sensors of the vehicle may have different configurations (e.g., multiple sensors positioned in a forward direction), the frame **602** and/or the positioning of the plurality of collimators relative to the frame **602** for each vehicle may be different. Accordingly, the frame **602** and the plurality of collimators may correspond to a subset of vehicles that share particular characteristics based on the type of vehicle and/or the configuration of the image sensors. Further, a first vehicle with sensors configured in a first configuration and a second vehicle with sensors configured in a second configuration may correspond to and/or may utilize different frames, each with different collimators affixed in different positions.

(98) Further, each of the plurality of collimators may be positioned relative to the frame **602** based on the number and/or positioning of a plurality of sensors relative to a vehicle. For example, the vehicle may include six sensors for performance verification. Further, the first collimator **604A** may be affixed to the frame **602** at a first position relative to a position of a first sensor, the second collimator **604B** may be affixed to the frame **602** at a second position relative to a position of a second sensor, the third collimator **604C** may be affixed to the frame **602** at a third position relative to a position of a third sensor, the fourth collimator **604D** may be affixed to the frame **602** at a fourth position relative to a position of a fourth sensor, the fifth collimator **604E** may be affixed to the frame **602** at a fifth position relative to a position of a fifth sensor, and the sixth collimator **604F** may be affixed to the frame **602** at a sixth position relative to a position of a sixth sensor.

(99) Further, a system may analyze the type of vehicle and/or the particular configuration of the set of sensors associated with the vehicle and determine positioning data for each of the plurality of collimators. For example, the system may determine positioning data associated with the particular type of vehicle and/or the particular configuration of the set of sensors associated with the vehicle. Further, the system may identify a frame **602** associated with the positioning data.

(100) In some cases, a system may map the positioning of each of the plurality of collimators based on the type of vehicle and/or the particular configuration of the set of sensors associated with the vehicle. For example, the system may receive data associated with the vehicle and identifying the

type of vehicle, the configuration of the set of sensors associated with the vehicle, etc. Based on the received data, the system may generate positioning data that identifies a position for each of the plurality of collimators relative to the frame **602**. In some cases, the system may provide the positioning data to a separate system associated with the design of the frame **602**. Based on the positioning data, each of the plurality of collimators may be affixed to the frame **602**. For example, the system may cause a robot to affix each of the plurality of collimators to the frame **602** based on the positioning data and/or automatically adjust the position and orientation of the collimators based on the positioning data.

(101) In some cases, the positioning data may be customized for a particular group of users, a particular user, etc. For example, the system may identify data associated with the user (e.g., a user location, a user grouping, a user profile) and identify positioning data associated with the user. In some embodiments, a user, via a user computing device, may define the positioning data for affixing the plurality of collimators to the frame **602**.

(102) In some cases, the plurality of collimators may not be affixed to the frame **602**. Further, each of the plurality of collimators may be individually positioned to interact with a sensor of the vehicle. The positioning data may define a position for each of the plurality of collimators relative to the vehicle, a particular sensor of the vehicle, or any other reference points. The signal processing system may use the positioning data to concurrently calibrate multiple image sensors mounted to a vehicle.

(103) Robot for Adjusting Frame of Collimators

(104) FIG. 7 illustrates an example environment **700** of an exterior of a vehicle **702** including one or more sensors **704** for which the performance can be verified using a frame **708** of one or more collimators **716**. The vehicle **702** may include the one or more sensors **704** to generate sensor data to identify objects in an environment of the vehicle. Further, a signal processing system may verify the performance of the one or more sensors **704** using the one or more collimators **716** on the frame **708**. For example, the one or more collimators **716** may produce collimated beams of light and the one or more sensors **704** may produce sensor data based on the collimated beams of light. Further, the signal processing system may receive the sensor data and verify the performance of the one or more sensors **704**.

(105) In the illustrated example of FIG. 7, the environment **700** includes a portion of an exterior of a vehicle **702**. In the illustrated example, the vehicle **702** includes an enclosure for one or more image sensors on the roof of the vehicle **702**. It will be understood, however, that the vehicle **702** can be configured in a variety of ways. For example, the vehicle **702** may include multiple enclosures for image sensors and/or may include image sensors located at different positions relative to the vehicle (e.g., the vehicle **702** may include a first enclosure of sensors on the side of the vehicle and a second enclosure of sensors on the roof of the vehicle). The enclosure(s) for one or more sensors can be separate from the vehicle **702** (e.g., an attachment to the vehicle) or can be integrated into the vehicle **702** (e.g., the enclosure may be a door panel, a rim, etc. of the vehicle and the sensor may be embedded within the vehicle **702**).

(106) The illustrated environment **700** further includes a frame **708** with collimators **716** attached thereto. It will be understood that the frame **708** can include one or more collimators **716** affixed at different locations relative to the frame **708**. The frame **708** may include (e.g., may be affixed to, attached to, etc.) an additional frame **710**. In some embodiments, the frame **708** and the additional frame **710** may correspond to a single frame.

(107) The illustrated environment **700** includes a robot **712**. For example, the robot **712** may be any multi-axis robot (e.g., a Fanuc M-710iC/50 robot). The robot **712** may include a robotic arm **714**. For example, the robot **712** may include a flexible robotic arm **714** with n degrees of freedom, where n can be any number (e.g., the flexible robotic arm **714** may have 12 degrees of freedom). The robotic arm **714** may be maneuverable within the illustrated environment **700**. It will be understood that any type of robot **712** may be used. For example, the robot **712** may include more,

less, or different components (e.g., the robot **712** may include multiple robotic arms).

(108) The signal processing system can identify the presence of a vehicle **702** within the illustrated environment **700**. For example, the signal processing system can receive vehicle data from one or more sensors (e.g., pressure sensors, motion sensors, etc.) identifying the presence of the vehicle **702** within the environment. Further, the signal processing system can identify a type of the vehicle **702** and/or a configuration of sensors **704** associated with the vehicle **702**. For example, the signal processing system can identify the type of the vehicle **702** and/or the configuration of sensors **704** based on the vehicle data. In some embodiments, the signal processing system may receive input (e.g., from a user computing device) identifying the presence of the vehicle **702**, the type of the vehicle **702**, and/or the configuration of the sensors **704**.

(109) Based on identifying the presence of the vehicle **702**, the type of the vehicle **702**, and/or the configuration of the sensors **704**, the signal processing system may identify particular positioning data associated with the vehicle and/or the one or more sensors associated with the vehicle. The positioning data may identify a particular position for each of the one or more collimators **716** relative to a frame **708**. The signal processing system may further identify positioning data to cause an alignment of the optical axis of each of the one or more sensors **704** of the vehicle **702** with an optical axis of a corresponding collimator of the one or more collimators **716** of the frame **708**.

(110) Further, the signal processing system, in response to the positioning data, may cause each of the one or more collimators **716** to be affixed to the frame **708** based on the positioning data. In some cases, the positioning data may identify a particular frame **708** of one or more collimators **716** (e.g., a preassembled frame of collimators). Based on the positioning data, the signal processing system may identify the frame **708** of one or more collimators **716**. Further, the signal processing system may provide instructions to the robot **712**. The instructions may cause the robot **712** (e.g., using the robotic arm **714**) to obtain the frame **708**.

(111) To obtain the frame **708**, the robot **712** may identify the additional frame **710** and utilize the additional frame **710** to obtain the frame **708**. For example, the additional frame **710** may include a platform that enables the robotic arm **714** of the robot **712** to interact with the additional frame **710** and obtain the frame **708**. In some embodiments, the robot **712** may directly obtain the frame **708** without obtaining the additional frame **710**. For example, the robotic arm **714** may obtain and move the frame **708** by directly interacting with the frame **708**. In other embodiments, the frame **708** and the additional frame **710** may be affixed and the robot **712** may obtain the frame **708** and the additional frame **710** simultaneously.

(112) Further, based on identifying the presence of the vehicle **702**, the type of the vehicle **702**, and/or the configuration of the sensors **704**, the signal processing system may identify alignment data associated with the vehicle **702** and identify how to align the frame **708** with the vehicle **702**. The alignment data may be based on the positioning data of the one or more collimators **716** and/or positioning data of the one or more sensors **704**. The alignment data may identify a position of the frame **708** relative to the vehicle **702** for alignment of the frame **708** with the vehicle **702**. As seen in FIG. 7, the vehicle **702** includes a reference location **706**. The alignment data may identify a position relative to the reference location **706**. Further, the signal processing system may identify the reference location **706** and may use the alignment data to identify a position for the frame **708** relative to the reference location **706**. Based on identifying the position for the frame **708**, the signal processing system may provide further instructions to the robot **712**. The further instructions may cause the robot **712** (e.g., using the robotic arm **714**) to move the frame **708** to the particular position. Accordingly, the robot **712** may cause alignment of the one or more sensors **704** with the one or more collimators **716** based on moving the frame to the particular position.

(113) In some cases, a robot **712** may not place the frame **708**. Instead, the frame **708** may be prepositioned in a particular location for a particular vehicle. For example, a vehicle may be driven to a prepositioned frame **708** to interact with the one or more collimators **716** of the frame **708** to verify performance of the one or more sensors **704** of the vehicle **702**.

(114) In some cases, the vehicle **702** may include one or more fixtures **718**. The robot **712** may cause alignment of the one or more sensors **704** with the one or more collimators **716** by affixing the frame **708** to the one or more fixtures **718**.

(115) Based on the alignment of the one or more sensors **704** with the one or more collimators **716**, the signal processing system can receive sensor data from the one or more sensors **704**. As discussed above, the signal processing system can use the sensor data to verify a performance of each of the one or more sensors **704**.

(116) During operation of the one or more collimators **716**, the positioning of the one or more collimators **716** relative to the frame **708** may degrade. For example, the positioning of the one or more collimators **716** may degrade due to creep, vibration, expansion, contraction, etc. To identify whether the positioning of the one or more collimators **716** has degraded relative to original positioning data, the signal processing system may receive sensor data from the one or more sensors **704**. Further, the signal processing system may obtain the sensor data and identify an MTF for each of the one or more sensors **704**. The MTF may identify a slanted edge. For example, the slanted edge may identify a difference in contrast between a first portion of the sensor data and a second portion of the sensor data.

(117) Further, each sensor of the one or more sensors **704** may be associated with a particular region of interest. The region of interest can include a contiguous set of pixels of the sensor and may be any shape. The region of interest of a particular sensor may be based on the positioning (e.g., orientation, location, etc.) of the particular sensor. Each of the one or more sensors **704** may have one or more regions of interest. For example, a particular sensor **704** may have a region of interest in the center of the sensor. The sensor **704** may designate the region of interest as a region of interest based on the region of interest identifying particular sensor data (e.g., the center of the captured sensor data). As another example, the region of interest may include a corner portion of the sensor a side portion (left or right), top/bottom portion, etc.

(118) Turning to FIG. 8, FIG. 8 illustrates an example environment **800** illustrating example sensor data including a region of interest and collimated light. In the illustrated example, the signal processing system **502** receives first sensor data **802** and second sensor data **804** from one or more sensors. The signal processing system **502** may implement a region of interest finder to identify a particular region of interest in the received sensor data. In the illustrated example, the signal processing system **502** identifies a first region of interest **803A** in the first sensor data **802** and a second region of interest **803B** in the second sensor data **804**. The signal processing system **502** may identify collimated light within the received sensor data. In the illustrated example, the signal processing system **602** identifies first collimated light **805A** in the first sensor data **802** and second collimated light **805B** in the second sensor data **804**. The signal processing system **602** compares the first collimated light **805A** and the first region of interest **803A** and compares the second collimated light **805B** and the second region of interest **803B** to determine whether each region of interest includes a portion of the collimated light (e.g., an edge of the collimated light). In the illustrated example, the signal processing system **602** may determine that the first region of interest **803A** includes an edge of the first collimated light **805A** and the second region of interest **803B** does not include an edge of the second collimated light **805B**.

(119) Returning to FIG. 7, based on the region of interest of each of the one or more sensors **704**, the signal processing system may determine whether the slanted edge identified by the MTF is located in the region of interest. For example, the signal processing system may verify whether the slanted edge is within a particular range of the region of interest. If the signal processing system identifies the slanted edge in the region of interest for a particular sensor, the signal processing system may determine the sensor and a corresponding collimator are correctly aligned. If the signal processing system does not identify the slanted edge in the region of interest for a particular sensor, the signal processing system may determine the sensor and a corresponding collimator are not correctly aligned. Accordingly, the signal processing system can determine a first subset of the one

or more sensors **704** that are correctly aligned with a first subset of the one or more collimators **716** and a second subset of the one or more sensors **704** that are not correctly aligned with a second subset of the one or more collimators **716**.

(120) Based on determining the first subset of the one or more sensors **704** that are correctly aligned with the first subset of the one or more collimators **716**, the signal processing system can verify the performance of each of the first subset of the one or more sensors **704** using the alignment of the frame **708**. The signal processing system can, simultaneously, align any number of one or more sensors **704** with any number of the one or more collimators **716** and, simultaneously or concurrently, verify the performance of each of the one or more sensors **704**. For example, the signal processing system can concurrently calibrate multiple sensors. In some cases, the signal processing system can first concurrently calibrate a first set of multiple sensors and second concurrently calibrate a second set of multiple sensors.

(121) In some cases, the signal processing system may not use the alignment of the frame **708** to verify the performance of the second subset of the one or more sensors **704** that are not correctly aligned with the second subset of the one or more collimators **716**. Subsequent to verifying the performance of each of the first subset of the one or more sensors **704**, the signal processing system can provide instructions to the robot **712** to cause the robot **712** to realign the frame **708** to align the slanted edges in the regions of interest for each of the second subset of the one or more sensors **704**. Based on realigning the frame **708**, the signal processing system can receive sensor data and determine whether the slanted edge identified by the MTF is located in the region of interest for any of the second subset of the one or more sensors **704**.

(122) If the signal processing system determines the slanted edge is located in the region of interest for any of the second subset of the one or more sensors **704**, the signal processing system may verify the performance of the particular sensor(s). Further, the signal processing system may realign the frame **708** such that the signal processing system can verify the performance of each of the one or more sensors **704**. It will be understood that the signal processing system may realign the frame **708** any number of times to verify the performance of each of the one or more sensors **704**.

(123) Based on realigning the frame **708** for a particular sensor of the one or more sensors **704**, the signal processing system can identify the shift in the alignment of the frame **708**. Based on identifying the shift in the alignment of the frame **708**, the signal processing system can cause an adjustment of the frame **708** to correct the alignment of the frame **708**. Further, the signal processing system may adjust the robot **712** by providing updated instructions to the robot **712** based on identifying the shift in the alignment of the frame **708**. In some cases, based on identifying the shift in the alignment of the frame **708**, the signal processing system can cause a repositioning of a particular collimator of the one or more collimators **716** affixed to the frame **708**.

(124) In some cases, the signal processing system can store the shift in the alignment in a data store and/or route the shift in the alignment to a computing device (e.g., a user computing device) for further analysis. Further, the signal processing system can link the shift in alignment to the vehicle **702** and/or the particular sensor. In some cases, the signal processing system can link the shift in alignment to the type of the vehicle **702**, the configuration of the one or more sensors **704**, etc. Based on linking the shift in alignment to the vehicle **702** and/or the particular sensor, the signal processing system can utilize the shift in alignment to verify performance of the one or more sensors **704** of the vehicle **702** and/or to verify performance of one or more additional sensors associated with one or more additional vehicles.

(125) Example Flow Diagram of Signal Processor

(126) FIG. **9** is a flow diagram illustrating an example of a routine **900** implemented by one or more processors (e.g., one or more processors of the signal processing system **502**). The flow diagram illustrated in FIG. **9** is provided for illustrative purposes only. It will be understood that one or more of the steps of the routine illustrated in FIG. **9** may be removed or that the ordering of

the steps may be changed. Furthermore, for the purposes of illustrating a clear example, one or more particular system components are described in the context of performing various operations during each of the data flow stages. However, other system arrangements and distributions of the processing steps across system components may be used.

(127) At block **902**, the signal processing system **502** causes alignment of a collimator with an image sensor mounted to a vehicle. The image sensor may be mounted to the vehicle based on a focus distance and/or a field of view. In some cases, the signal processing system **502** may cause alignment of multiple collimators with multiple image sensor mounted to the vehicle. For example, the signal processing system **502** may cause alignment of a first collimator with a first image sensor mounted to the vehicle and a second collimator with a second image sensor mounted to the vehicle. In some embodiments, the collimator may be a fiber optic collimator that collimates a beam of light (e.g., a laser beam from a solid-state laser).

(128) In some cases, the collimator may be affixed to (e.g., coupled to) a frame (e.g., a frame of collimators). Further, the signal processing system **502**, to cause alignment of the collimator with the image sensor, can cause alignment of the frame with the vehicle.

(129) To cause the alignment of the collimator with the image sensor, the signal processing system can send instructions to a robot. Based on the instructions, the robot can cause the alignment of the collimator with the image sensor by aligning the frame with the vehicle. In some cases, the robot may align the frame with the vehicle based on a reference location associated with the vehicle.

(130) Further, based on the alignment of the collimator with the image sensor, the signal processing system **502** may cause a display of light associated with a lighting device. The collimator may capture the light (e.g., a beam of light). Further, the collimator may produce collimated light (e.g., a collimated beam of light) based on capturing the light.

(131) In some cases, the signal processing system **502** may identify a collimator configuration of the collimator. The collimator configuration may include any parameters or settings associated with the collimator. For example, the collimator configuration may include, but is not limited to, a position of the collimator (e.g., a position of the collimator relative to the vehicle, relative to a frame, etc.), an orientation of the collimator, a power usage of the collimator, a frequency of the collimator, a length of the collimator, or a type of the collimator. The collimator configuration may be based on an image sensor type of the image sensor, an image sensor orientation of the image sensor, an image sensor configuration of the image sensor, and/or a vehicle type of the vehicle. For example, the signal processing system **502** may identify a particular collimator configuration that is associated with the image sensor type of the image sensor, the image sensor orientation of the image sensor, the image sensor configuration of the image sensor, and/or the vehicle type of the vehicle. For example, the signal processing system **502** may identify a 50 millimeter collimator for a particular image sensor type and a 100 millimeter collimator for a different image sensor type. The signal processing system **502** may cause alignment of the collimator with the image sensor based on the collimator configuration. For example, the signal processing system **502** may align a 50 millimeter collimator a particular distance (e.g., two feet) from an image sensor and align a 100 millimeter collimator a further distance (e.g., three feet) from an image sensor. In some cases, the signal processing system **502** can receive sensor data associated with the image sensor and verify the collimator configuration of the collimator based on the sensor data.

(132) In some cases, the signal processing system **502** may identify a plurality of collimator configurations and a plurality of image sensor configurations. Further, the signal processing system **502** can generate a plurality of mappings that link a particular image sensor configuration to a particular collimator configuration. The plurality of mappings may include a mapping of an image sensor configuration of the image sensor to a collimator configuration of the collimator. Further, the signal processing system **502** may cause alignment of the collimator with the image sensor based on the image sensor configuration and the collimator configuration.

(133) At block **904**, the signal processing system **502** receives sensor data associated with at least

one image sensor based at least in part on causing alignment of the collimator with the image sensor. For example, the signal processing system **502** may determine the collimator is aligned with the image sensor. The signal processing system **502** may activate the collimator and the image sensor such that the collimator provides collimated light to the image sensor. Based on receiving the collimated light, the image sensor can generate sensor data and provide the sensor data to the signal processing system **502**. The sensor data may further be associated with the vehicle and correspond to image data from image sensors sensing the exterior environment of the vehicle. For example, as described herein, the sensor data may include camera data associated with a camera, lidar data associated with a lidar device, and/or radar data associated with a radar device. In some such cases, the signal processing system **502** may receive the sensor data from a camera image sensor, a lidar sensor, a radar sensor, etc. In some cases, the signal processing system **502** may receive sensor data based on the collimated light from the collimator. The signal processing system **502** may process the sensor data to generate performance data (e.g., optical performance data) associated with the performance of the image sensor. For example, the signal processing system **502** may generate performance data that identifies the performance of the image sensor. In some cases, the performance data may include modulation transfer function data, optical transfer function data, phase transfer function data, etc.

(134) In some cases, the performance data may include calibration data (e.g., a first set of intrinsic parameters) associated with the calibration of the image sensor. For example, the calibration data can include intrinsic parameters such as a scale factor, a focal length, a principal point (e.g., a sensor center), a skew, a geometric distortion, etc. associated with the image sensor. The image sensor may generate sensor data based on the intrinsic parameters. The signal processing system **502** may calibrate the image sensor using the received sensor data to generate the calibration data associated with the image sensor. For example, the signal processing system **502** may use captured lidar data to calibrate a principal point of a lidar image sensor. The lidar image sensor may capture additional lidar data based on the calibrated principal point of the lidar image sensor.

(135) In some cases, the signal processing system **502** may verify the alignment of the collimator with the image sensor based on the sensor data. In certain cases, to verify the alignment, the signal processing system **502** may determine a first region of interest (e.g., a center of the image sensor) for the image sensor based on the sensor data. For example, the signal processing system **502** may identify a portion of the image sensor (e.g., the region of interest) that is expected to receive collimated light. In some cases, the signal processing system **502** may determine the first region of interest does not include a slanted edge (e.g., a miter edge). Based on determining the first region of interest does not include the slanted edge, the signal processing system **502** can cause an adjustment of the collimator, the frame, the robot, etc. For example, if the signal processing system **502** does not detect the slanted edge in the region of interest, the signal processing system **502** can cause the robot to move the frame, the robot, or the collimator to adjust the position or orientation of the collimator.

(136) Following an adjustment of the collimator, frame, and/or robot, the signal processing system **502** can receive updated sensor data associated with the image sensor. The signal processing system **502** may further determine a second region of interest for the image sensor based on the updated sensor data. For example, the signal processing system **502** may receive the updated sensor data and identify an updated region of interest (e.g., a center of the image sensor) for the image sensor based on the updated sensor data. The signal processing system **502** may verify the alignment of the collimator with the image sensor based on determining the second region of interest includes the slanted edge. For example, the signal processing system **502** identify a portion of the image sensor (e.g., the region of interest) that is expected to receive collimated light and may confirm that a slanted edge of the collimated light is in the region of interest.

(137) At block **906**, the signal processing system **502** determines the sensor data does not satisfy a performance specification (e.g., a performance threshold). The performance specification may be

associated with the image sensor. For example, the performance specification can indicate expected values for different parameters for the image sensor. In some cases, the signal processing system **502** may receive the performance specification from a computing device identifying that the performance specification is associated with the image sensor. For example, a user, via a user computing device, may indicate a performance specification associated with the image sensor. Based on determining the performance specification is associated with the image sensor, the signal processing system **502** may determine the sensor data does not satisfy the performance specification. For example, the signal processing system **502** may identify a performance specification and compare the sensor data with the performance specification and determine that the sensor data includes values less than, greater than, or outside of a range of values provided by the performance specification.

(138) In some cases, to compare the sensor data with the performance specification, the signal processing system **502** may compare optical performance data based on the sensor data with an optical performance data specification (e.g., an optical performance data specification, a modulation transfer function data specification, etc.). For example, the signal processing system **502** may verify whether the optical performance data satisfies (e.g., matches, is below than, is greater than, is within a particular range of, etc.) the optical performance data specification. Based on the comparison of the optical performance data with the optical performance data specification, the signal processing system **502** may determine that the sensor data does not satisfy the performance specification.

(139) In some cases, the signal processing system **502** may compare calibration data (e.g., intrinsic parameters associated with the image sensor such as a scale factor, a focal length, a principal point (e.g., a sensor center), a skew, a geometric distortion, etc.) based on the sensor data with a calibration data specification (e.g., a second set of intrinsic parameters). For example, the signal processing system **502** may verify whether the calibration data satisfies (e.g., matches, is below than, is greater than, is within a particular range of, etc.) the calibration data specification by comparing the calibration data with the calibration data specification. In certain cases, to compare the calibration data and the calibration data threshold, the signal processing system **502** may perform a ray angle comparison and/or a reprojection error comparison. Based on the comparison of the calibration data with the calibration data specification, the signal processing system **502** may determine that the sensor data does not satisfy the performance specification.

(140) At block **908**, the signal processing system **502** determines an image sensor alert associated with the image sensor based at least in part on determining that the sensor data does not satisfy the performance specification. For example, the signal processing system **502** may generate the image sensor alert based on determining the sensor data does not satisfy the performance threshold (e.g., based on comparing the performance data and the performance specification). In some cases, the image sensor alert may identify a measure of optical performance of the image sensor and/or a measure of intrinsic calibration of the image sensor. For example, the image sensor alert may identify a difference between the optical performance and/or the intrinsic calibration of the image sensor and the performance specification.

(141) In some cases, the signal processing system **502** may update the intrinsic parameters of the image sensor based on the image sensor alert. For example, the signal processing system **502** may identify a third set of intrinsic parameters (e.g., the first set of intrinsic parameters, the second set of intrinsic parameters, a separate set of intrinsic parameters). In some cases, the signal processing system **502** may provide the updated intrinsic parameters (e.g., to a user) as recommended intrinsic parameters for the image sensor. For example, the signal processing system **502** may cause display of the updated intrinsic parameters on a user computing device and may indicate that the updated intrinsic parameters are recommended for the image sensor.

(142) At block **910**, the signal processing system **502** routes the image sensor alert. Further, the signal processing system **502** may route the image sensor alert to a data store and/or to a computing

device (e.g., a user computing device). In some cases, the signal processing system **502** may route the image sensor for additional testing based on the image sensor alert. For example, the signal processing system **502** may route the image sensor alert to a robotic device. Further, the image sensor alert may cause the robotic device to obtain the image sensor and transport the image sensor for additional testing.

(143) In some cases, based on routing the image sensor alert, the signal processing system **502** (or a separate computing system) may update the image sensor based on the third set of intrinsic parameters. Further, the image sensor may generate additional sensor data based on the third set of intrinsic parameters.

(144) In some cases, the signal processing system **502** may determine the collimator has shifted from a first position to a second position. Based on the determination that the collimator has shifted, the signal processing system **502** can identify a correction factor. Further, the signal processing system **502** can apply the correction factor to a robot that causes alignment of the collimator with the image sensor. Based on applying the correction factor to the robot, the robot may adjust the alignment of the collimator with the image sensor. In some embodiments, based on applying the correction factor to the robot, the robot may cause alignment of a second image sensor associated with a second vehicle with a second collimator based on the correction factor.

(145) It will be understood that the routine **900** can be repeated multiple times using different image sensors and/or different sensor data. In some cases, the signal processing system **502** may iteratively repeat the routine **900** for multiple sets of sensor data that are received from multiple image sensors. In certain cases, the signal processing system **502** uses the routine **900** to concurrently calibrate multiple image sensors of a vehicle. In some cases, the signal processing system **502** uses the routine **900** to concurrently calibrate a first set image sensors of a vehicle, adjusts the position and/or orientation of one or more collimators, and concurrently calibrates a second set of one or more image sensors of the vehicle. In certain cases, the signal processing system **502** can repeat this process until some or all of the image sensors of the vehicle are calibrated or identified for further modification (e.g., relevant image sensor alert is generated and routed).

(146) In the foregoing description, aspects and embodiments of the present disclosure have been described with reference to numerous specific details that can vary from implementation to implementation. Accordingly, the description and drawings are to be regarded in an illustrative rather than a restrictive sense. The sole and exclusive indicator of the scope of the invention, and what is intended by the applicants to be the scope of the invention, is the literal and equivalent scope of the set of claims that issue from this application, in the specific form in which such claims issue, including any subsequent correction. Any definitions expressly set forth herein for terms contained in such claims shall govern the meaning of such terms as used in the claims. In addition, when we use the term “further comprising,” in the foregoing description or following claims, what follows this phrase can be an additional step or entity, or a sub-step/sub-entity of a previously recited step or entity.

(147) Various additional example embodiments of the disclosure can be described by the following clauses:

(148) Clause 1: A method, comprising: causing alignment of a collimator with an image sensor mounted to a vehicle; receiving, using at least one processor, sensor data associated with the image sensor based at least in part on causing the alignment of the collimator with the image sensor; determining that the sensor data does not satisfy a performance threshold associated with the image sensor; determining an image sensor alert associated with the image sensor based at least in part on the determining that the sensor data does not satisfy the performance threshold associated with the image sensor; and routing the image sensor alert.

(149) Clause 2: The method of Clause 1, wherein determining that the sensor data does not satisfy the performance threshold comprises: determining first modulation transfer function data

associated with the image sensor based at least in part on the sensor data; comparing the first modulation transfer function data with a modulation transfer function data threshold; and determining that the sensor data does not satisfy the performance threshold based at least in part on comparing the first modulation transfer function data with the modulation transfer function data threshold, wherein the image sensor is routed for additional testing based at least in part on the image sensor alert.

(150) Clause 3: The method of Clause 1 or Clause 2, wherein the image sensor alert comprises at least one of a measure of optical performance of the image sensor or a measure of intrinsic calibration of the image sensor.

(151) Clause 4: The method of any one of Clauses 1 through 3, wherein the performance threshold comprises a calibration data threshold, wherein determining the image sensor alert comprises: calibrating the image sensor based at least in part on the sensor data to generate calibration data associated with the image sensor; comparing the calibration data with the calibration data threshold; and generating the image sensor alert based at least in part on comparing the calibration data with the calibration data threshold.

(152) Clause 5: The method of Clause 4, wherein comparing the calibration data with the calibration data threshold comprises at least one of a ray angle comparison or a reprojection error comparison.

(153) Clause 6: The method of Clause 4 or Clause 5, wherein the calibration data comprises a first set of intrinsic parameters associated with the image sensor, wherein the sensor data is based at least in part on the first set of intrinsic parameters, wherein the calibration data threshold comprises a second set of intrinsic parameters, the method further comprising identifying a third set of intrinsic parameters based at least in part on the image sensor alert, wherein the third set of intrinsic parameters comprise the first set of intrinsic parameters or the second set of intrinsic parameters.

(154) Clause 7: The method of Clause 6, wherein the sensor data is first sensor data, the method further comprising: updating the image sensor based at least in part on the third set of intrinsic parameters; and receiving, using at least one processor, second sensor data associated with the image sensor based at least in part on the third intrinsic parameters.

(155) Clause 8: The method of any one of Clauses 1 through 7, wherein the image sensor is a first image sensor and the collimator is a first collimator, the method further comprising: causing alignment of a second collimator with a second image sensor mounted to the vehicle, wherein the first collimator and the second collimator are mounted to a frame.

(156) Clause 9: The method of any one of Clauses 1 through 8, further comprising: causing display of light associated with a lighting device; capturing, by the collimator, the light; and producing collimated light based at least in part on capturing the light, wherein receiving the sensor data is based at least in part on the collimated light.

(157) Clause 10: The method of any one of Clauses 1 through 9, wherein a robot causes the alignment of the collimator with the image sensor by aligning a frame with the vehicle based at least in part on a reference location associated with the vehicle, wherein the collimator is coupled to the frame.

(158) Clause 11: The method of any one of Clauses 1 through 10, wherein the image sensor is mounted to the vehicle based at least in part on a focus distance or a field-of-view.

(159) Clause 12: The method of any one of Clauses 1 through 11, wherein causing alignment of the collimator with the image sensor comprises: determining a first region of interest for the image sensor based at least in part on the sensor data; determining the first region of interest does not include a miter edge; causing an adjustment of the collimator based at least in part on determining the region of interest does not include the miter edge; receiving, using at least one processor, updated sensor data associated with the image sensor based at least in part on causing the adjustment of the collimator; determining a second region of interest for the image sensor based at least in part on the updated sensor data; and determining the second region of interest includes the

miter edge.

(160) Clause 13: The method of any one of Clauses 1 through 12, wherein a robot causes alignment of the collimator with the image sensor, the method further comprising: determining the collimator has shifted from a first position to a second position; identifying a correction factor based at least in part on determining the collimator has shifted from a first position to a second position; and applying the correction factor to the robot, wherein the correction factor causes the robot to adjust the alignment of the collimator with the image sensor.

(161) Clause 14: The method of Clause 13, wherein the vehicle is a first vehicle, the image sensor is a first image sensor, and the collimator is a first collimator, the method further comprising causing alignment of a second image sensor associated with a second vehicle with a second collimator based at least in part on the correction factor.

(162) Clause 15: The method of any one of Clauses 1 through 14, wherein the sensor data is first sensor data, wherein causing alignment of the collimator with the image sensor comprises: identifying a collimator configuration of the collimator based at least in part on the alignment of the image sensor with the collimator; receiving, using at least one processor, second sensor data associated with the image sensor; and verifying the collimator configuration of the collimator based at least in part on the second sensor data.

(163) Clause 16: The method of any one of Clauses 1 through 15, wherein causing alignment of the collimator with the image sensor comprises: identifying at least one of an image sensor type of the image sensor, an image sensor orientation of the image sensor, an image sensor configuration of the image sensor, or a vehicle type of the vehicle; identifying a collimator configuration of the collimator based at least in part on the at least one of the image sensor type of the image sensor, the image sensor orientation of the image sensor, the image sensor configuration of the image sensor, or the vehicle type of the vehicle; and causing alignment of the collimator with the image sensor is based at least in part on the collimator configuration of the collimator.

(164) Clause 17: The method of any one of Clauses 1 through 16, further comprising: identifying a plurality of image sensor configurations; identifying a plurality of collimator configurations; and generating a plurality of mappings, wherein each mapping of the plurality of mappings maps a particular image sensor configuration of the plurality of image sensor configurations to a particular collimator configuration of the plurality of collimator configurations, wherein the plurality of mappings comprises a mapping of an image sensor configuration of the plurality of image sensor configurations to a collimator configuration of the plurality of collimator configurations, wherein causing alignment of the collimator with the image sensor is based at least in part on the image sensor configuration and the collimator configuration.

(165) Clause 18: The method of any one of Clauses 1 through 17, wherein the collimator is a fiber optic collimator, wherein the fiber optic collimator collimates a laser beam from a solid-state laser.

(166) Clause 19: A system, comprising: at least one processor, and at least one non-transitory storage media storing instructions that, when executed by the at least one processor, cause the at least one processor to: cause alignment of a collimator with an image sensor mounted to a vehicle; receive sensor data associated with the image sensor based at least in part on causing the alignment of the collimator with the image sensor; determine that the sensor data does not satisfy a performance threshold associated with the image sensor; determine an image sensor alert associated with the image sensor based at least in part on determining that the sensor data does not satisfy the performance threshold associated with the image sensor; and route the image sensor alert.

(167) Clause 20: At least one non-transitory storage media storing instructions that, when executed by a computing system comprising a processor, cause the computing system to: cause alignment of a collimator with an image sensor mounted to a vehicle; receive sensor data associated with the image sensor based at least in part on causing the alignment of the collimator with the image sensor; determine that the sensor data does not satisfy a performance threshold associated with the

image sensor; determine an image sensor alert associated with the image sensor based at least in part on determining that the sensor data does not satisfy the performance threshold associated with the image sensor; and route the image sensor alert.

Claims

1. A method, comprising: causing alignment of a collimator with an image sensor mounted to a vehicle; responsive to causing the alignment of the collimator with the image sensor, receiving, using at least one processor, sensor data from the image sensor aligned with the collimator; determining that performance data associated with the image sensor does not satisfy a performance threshold associated with the image sensor based at least in part on the sensor data received from the image sensor aligned with the collimator; determining an image sensor alert associated with the image sensor based at least in part on determining that the performance data does not satisfy the performance threshold; and routing the image sensor alert.
2. The method of claim 1, wherein determining that the performance data does not satisfy the performance threshold comprises: determining first modulation transfer function data associated with the image sensor based at least in part on the sensor data received from the image sensor aligned with the collimator; comparing the first modulation transfer function data with a modulation transfer function data threshold; and determining that the performance data does not satisfy the performance threshold based at least in part on comparing the first modulation transfer function data with the modulation transfer function data threshold, wherein the image sensor is routed for additional testing based at least in part on the image sensor alert.
3. The method of claim 1, wherein the performance data comprises at least one of optical performance data or intrinsic calibration data.
4. The method of claim 1, wherein the performance threshold comprises a calibration data threshold, wherein determining the image sensor alert comprises: calibrating the image sensor based at least in part on the sensor data received from the image sensor aligned with the collimator to generate calibration data associated with the image sensor; comparing the calibration data with the calibration data threshold; and generating the image sensor alert based at least in part on comparing the calibration data with the calibration data threshold.
5. The method of claim 4, wherein comparing the calibration data with the calibration data threshold comprises at least one of a ray angle comparison or a reprojection error comparison.
6. The method of claim 4, wherein the calibration data comprises a first set of intrinsic parameters associated with the image sensor, wherein the sensor data received from the image sensor aligned with the collimator is based at least in part on the first set of intrinsic parameters, wherein the calibration data threshold comprises a second set of intrinsic parameters, the method further comprising: identifying a third set of intrinsic parameters based at least in part on the image sensor alert, wherein the third set of intrinsic parameters comprise the first set of intrinsic parameters or the second set of intrinsic parameters.
7. The method of claim 6, wherein the sensor data received from the image sensor aligned with the collimator is first sensor data, the method further comprising: updating the image sensor based at least in part on the third set of intrinsic parameters; and receiving second sensor data from the image sensor aligned with the collimator based at least in part on the third set of intrinsic parameters.
8. The method of claim 1, wherein the image sensor is a first image sensor and the collimator is a first collimator, the method further comprising: causing alignment of a second collimator with a second image sensor mounted to the vehicle, wherein the first collimator and the second collimator are mounted to a frame.
9. The method of claim 1, further comprising: causing display of light associated with a lighting device; capturing, by the collimator, the light; and producing collimated light based at least in part

on capturing the light, wherein receiving the sensor data is based at least in part on the collimated light.

10. The method of claim 1, wherein a robot causes the alignment of the collimator with the image sensor by aligning a frame with the vehicle based at least in part on a reference location associated with the vehicle, wherein the collimator is coupled to the frame.

11. The method of claim 1, wherein the image sensor is mounted to the vehicle based at least in part on a focus distance or a field-of-view.

12. The method of claim 1, wherein causing alignment of the collimator with the image sensor comprises: determining a first region of interest for the image sensor based at least in part on the sensor data received from the image sensor aligned with the collimator; determining the first region of interest does not include a miter edge; causing an adjustment of the collimator based at least in part on determining the first region of interest does not include the miter edge; receiving updated sensor data from the image sensor aligned with the collimator based at least in part on causing the adjustment of the collimator; determining a second region of interest for the image sensor based at least in part on the updated sensor data received from the image sensor aligned with the collimator; and determining the second region of interest includes the miter edge.

13. The method of claim 1, wherein a robot causes alignment of the collimator with the image sensor, the method further comprising: determining the collimator has shifted from a first position to a second position; identifying a correction factor based at least in part on determining the collimator has shifted from a first position to a second position; and applying the correction factor to the robot, wherein the correction factor causes the robot to adjust the alignment of the collimator with the image sensor.

14. The method of claim 13, wherein the vehicle is a first vehicle, the image sensor is a first image sensor, and the collimator is a first collimator, the method further comprising: causing alignment of a second image sensor associated with a second vehicle with a second collimator based at least in part on the correction factor.

15. The method of claim 1, wherein the sensor data received from the image sensor aligned with the collimator is first sensor data, wherein causing alignment of the collimator with the image sensor comprises: identifying a collimator configuration of the collimator based at least in part on the alignment of the image sensor with the collimator; receiving, using at least one processor, second sensor data from the image sensor aligned with the collimator; and verifying the collimator configuration of the collimator based at least in part on the second sensor data received from the image sensor aligned with the collimator.

16. The method of claim 1, wherein causing alignment of the collimator with the image sensor comprises: identifying at least one of an image sensor type of the image sensor, an image sensor orientation of the image sensor, an image sensor configuration of the image sensor, or a vehicle type of the vehicle; identifying a collimator configuration of the collimator based at least in part on the at least one of the image sensor type of the image sensor, the image sensor orientation of the image sensor, the image sensor configuration of the image sensor, or the vehicle type of the vehicle; and causing alignment of the collimator with the image sensor is based at least in part on the collimator configuration of the collimator.

17. The method of claim 1, further comprising: identifying a plurality of image sensor configurations; identifying a plurality of collimator configurations; and generating a plurality of mappings, wherein each mapping of the plurality of mappings maps a particular image sensor configuration of the plurality of image sensor configurations to a particular collimator configuration of the plurality of collimator configurations, wherein the plurality of mappings comprises a mapping of an image sensor configuration of the plurality of image sensor configurations to a collimator configuration of the plurality of collimator configurations, wherein causing alignment of the collimator with the image sensor is based at least in part on the image sensor configuration and the collimator configuration.

18. The method of claim 1, wherein the collimator is a fiber optic collimator, wherein the fiber optic collimator collimates a laser beam from a solid-state laser.

19. A system, comprising: at least one processor, and at least one non-transitory storage media storing instructions that, when executed by the at least one processor, cause the at least one processor to: cause alignment of a collimator with an image sensor mounted to a vehicle; responsive to causing the alignment of the collimator with the image sensor, receive sensor data from the image sensor aligned with the collimator; determine that performance data associated with the image sensor does not satisfy a performance threshold associated with the image sensor based at least in part on the sensor data received from the image sensor aligned with the collimator; determine an image sensor alert associated with the image sensor based at least in part on determining that the performance data does not satisfy the performance threshold; and route the image sensor alert.

20. At least one non-transitory storage media storing instructions that, when executed by a computing system comprising a processor, cause the computing system to: cause alignment of a collimator with an image sensor mounted to a vehicle; responsive to causing the alignment of the collimator with the image sensor, receive sensor data from the image sensor aligned with the collimator; determine that performance data associated with the image sensor does not satisfy a performance threshold associated with the image sensor based at least in part on the sensor data received from the image sensor aligned with the collimator; determine an image sensor alert associated with the image sensor based at least in part on determining that the performance data does not satisfy the performance threshold; and route the image sensor alert.
