

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent	12408145
Kind Code	B2
Date of Patent	September 02, 2025
Inventor(s)	Hahn; Gene Back et al.

Method and device for paging in sidelink communication

Abstract

A method for paging in sidelink communication includes the steps of: receiving configuration information of a resource sensing/selection window from a base station; determining P candidate resources by performing a resource sensing operation in a P resource sensing window indicated by the configuration information; selecting a P transmission resource from among the P candidate resources in a P resource selection window indicated by the configuration information; and transmitting a paging message to a receiving terminal by using the P transmission resource.

Inventors: Hahn; Gene Back (Hwaseong-si, KR), Hong; Ui Hyun (Hwaseong-si, KR), Son; Hyuk Min (Iksan-si, KR)

Applicant: HYUNDAI MOTOR COMPANY (Seoul, KR); KIA CORPORATION (Seoul, KR); Wonkwang University Center For Industry-Academy Cooperation (Iksan-si, KR)

Family ID: 81709455

Assignee: Hyundai Motor Company (Seoul, KR); Kia Corporation (Seoul, KR); Wonkwang University Center For Industry-Academy Cooperation (Iksan-si, KR)

Appl. No.: 18/198179

Filed: May 16, 2023

Prior Publication Data

Document Identifier	Publication Date
US 20230292290 A1	Sep. 14, 2023

Foreign Application Priority Data

KR	10-2021-0160106	Nov. 19, 2021
----	-----------------	---------------

Related U.S. Application Data

continuation-in-part parent-doc WO PCT/KR2021/017106 20211119 PENDING child-doc US 18198179
us-provisional-application US 63116354 20201120

Publication Classification

Int. Cl.: H04W68/02 (20090101); H04W72/02 (20090101)

U.S. Cl.:

CPC H04W68/02 (20130101); H04W72/02 (20130101);

Field of Classification Search

CPC: H04W (92/18)

References Cited

U.S. PATENT DOCUMENTS

Patent No.	Issued Date	Patentee Name	U.S. Cl.	CPC
2020/0029245	12/2019	Khoryaev et al.	N/A	N/A
2020/0037358	12/2019	Chae et al.	N/A	N/A
2020/0229171	12/2019	Khoryaev	N/A	H04W 4/40
2021/0152992	12/2020	Balasubramanian	N/A	H04W 68/02
2023/0239834	12/2022	Ye	455/458	H04W 68/02
2023/0337188	12/2022	Selvanesan	N/A	H04W 72/044

FOREIGN PATENT DOCUMENTS

Patent No.	Application Date	Country	CPC
10-2103725	12/2019	KR	N/A

OTHER PUBLICATIONS

International Search dated Feb. 25, 2022 issued in International Patent Application No. PCT/KR2021/017106 (w/ English translation). cited by applicant
“Discussion on remaining open issue for mode 2,” 3GPP TSG-RAN WG1 Meeting #101-e, e-Meeting, May 25 through Jun. 5, 2020 (R1-2004074). cited by applicant
“Discussion on remaining open issue for mode 2,” 3GPP TSG-RAN WG1 Meeting #100bis-e, e-Meeting, Apr. 20-30, 2020 (R1-2001749). cited by applicant
“Discussion on physical layer design considering sidelink DRX operation,” 3GPP TSG RAN WG1 #103-e, e-Meeting, Oct. 26 through Nov. 13, 2020 (R1-2007897). cited by applicant

Primary Examiner: Smith; Marcus

Assistant Examiner: Fakhro; Rowan K

Attorney, Agent or Firm: Morgan Lewis & Bockius LLP

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION (1) The present application is a continuation-in-part of currently pending International Patent Application No. PCT/KR2021/017106, filed Nov. 19, 2021, which claims priority to Korean Patent Application Number 10-2021-0160106, filed Nov. 19, 2021, and U.S. Provisional Patent Application No. 63/116,354, filed Nov. 20, 2020, the entire contents of which are incorporated herein for all purposes by these references

BACKGROUND OF THE PRESENT DISCLOSURE

Field of the Present Disclosure

(1) The present disclosure relates to a sidelink communication technique, and more particularly, to a technique for resource sensing and selection for transmission of a paging message.

Description of Related Art

(2) A Fifth-Generation (5G) communication system (e.g., New Radio (NR) communication system) which uses a frequency band higher than a frequency band of a Fourth-Generation (4G) communication system (e.g., Long Term Evolution (LTE) communication system or LTE-Advanced (LTE-A) communication system) as well as the frequency band of the 4G communication system has been considered for processing of wireless data. The 5G communication system can support Enhanced Mobile Broadband (eMBB) communications, Ultra-Reliable and Low-Latency communications (URLLC), massive Machine Type Communications (mMTC), and the like.

(3) The 4G communication system and 5G communication system can support Vehicle-to-Everything (V2X) communications. The V2X communications supported in a cellular communication system, such as the 4G communication system, the 5G communication system, and the like, may be referred to as “Cellular-V2X (C-V2X) communications.” The V2X communications (e.g., C-V2X communications) may include Vehicle-to-Vehicle (V2V) communications, Vehicle-to-Infrastructure (V2I) communications, Vehicle-to-Pedestrian (V2P) communication, Vehicle-to-Network (V2N) communication, and the like.

(4) In the cellular communication systems, the V2X communications (e.g., C-V2X communications) may be performed based on sidelink communication technologies (e.g., Proximity-based Services (ProSe) communication technology, Device-to-Device (D2D) communication technology, or the like). For example, sidelink channels for vehicles participating in V2V communications may be established, and communications between the vehicles may be performed using the sidelink channels. Sidelink communication may be performed using configured grant (CG) resources. The CG resources may be periodically configured, and periodic data (e.g., periodic sidelink data) may be transmitted using the CG resources.

(5) Meanwhile, when a resource allocation (RA) mode 2 is used, it is necessary to configure a sidelink resource for transmitting a paging message and/or a wake-up signal. When a paging message and/or a wake-up signal is transmitted in a preconfigured sidelink resource without considering a current resource occupancy state, a collision may occur in transmission of the paging message and/or the wake-up signal. In this case, energy efficiency and reception performance in sidelink communication may deteriorate.

(6) The information disclosed in this Background of the present disclosure is only for enhancement of understanding of the general background of the present disclosure and may not be taken as an acknowledgement or any form of suggestion that this information forms the prior art already known to a person skilled in the art.

BRIEF SUMMARY

(7) Various aspects of the present disclosure are directed to providing a method and an apparatus

for transmission of a paging message in sidelink communication.

(8) A method of a transmitting terminal, according to various exemplary embodiments of the present disclosure for achieving the above-described objective, may include: receiving, from a base station, configuration information of resource sensing/selection window; determining paging (P) candidate resources by performing a resource sensing operation within a P resource sensing window indicated by the configuration information; selecting a P transmission resource from among the P candidate resources within a P resource selection window indicated by the configuration information; and transmitting a paging message to a receiving terminal using the P transmission resource, wherein the P resource sensing window is a resource sensing window configured for transmission of the paging message, and the P resource selection window is a resource selection window configured for transmission of the paging message.

(9) The operation method may further include: determining data (D) candidate resources by performing a resource sensing operation within a D resource sensing window indicated by the configuration information; selecting a D transmission resource from among the D candidate resources within a D resource selection window indicated by the configuration information; and transmitting data to the receiving terminal using the D transmission resource, wherein the D resource sensing window is a resource sensing window configured for transmission of the data, and the D resource selection window is a resource selection window configured for transmission of the data.

(10) The P resource sensing window may be configured independently of the D resource sensing window, and the P resource selection window may be configured independently of the D resource selection window.

(11) The configuration information may include time resource information of the P resource sensing window, time resource information of the P resource selection window, time resource information of the D resource sensing window, and time resource information of the D resource selection window.

(12) A first window interval may be configured between the P resource sensing window and the P resource selection window, a second window interval may be configured between the P resource selection window and the D resource sensing window, a third window interval may be configured between the D resource sensing window and the D resource selection window, and time resource information of the first window interval, the second window interval, and the third window interval may be included in the configuration information.

(13) The configuration information may be configured for each resource pool, and one or more configuration information for resource sensing/resource window may be configured for one resource pool.

(14) The operation method may further include: when the resource sensing operation is completed before an end time of the P resource sensing window, early terminating the P resource sensing window.

(15) When the resource sensing operation is completed before a reference time configured by the base station, the P resource sensing window may be early terminated.

(16) The P resource selection window may start at an early termination time of the P resource sensing window or at a time after a window interval from the early termination time of the P resource sensing window.

(17) The P resource sensing window may be early terminated when one or more conditions are satisfied, and the one or more conditions may be determined based on at least one of a size of transmission data, a required latency, a priority per data, or a priority per sidelink service.

(18) When an early termination operation for the P resource sensing window is enabled by the base station, the P resource selection window may be early terminated.

(19) A method of a transmitting terminal, according to various exemplary embodiments of the present disclosure for achieving the above-described objective, may include: receiving, from a base

station, configuration information of resource sensing/selection window; determining paging (P) candidate resources by performing a resource sensing operation within a P resource sensing/selection window indicated by the configuration information; selecting a P transmission resource from among the P candidate resources within the P resource sensing/selection window; and transmitting a paging message to a receiving terminal using the P transmission resource.

(20) The determining of the P candidate resources may include: reconfiguring the P resource sensing/selection window when the resource sensing operation is not completed within a first reference time in the P resource sensing/selection window; and determining the P candidate resources by performing the resource sensing operation within the reconfigured P resource sensing/selection window, wherein the P transmission resource is selected within the reconfigured P resource sensing/selection window.

(21) The first reference time may be configured by the base station, and the first reference time may be indicated by an offset from a start time of the P resource sensing/selection window.

(22) The reconfigured P resource sensing/selection window may start from the first reference time or from a time after an offset configured by the base station from the first reference time.

(23) The operation method may further include: determining data (D) candidate resources by performing a resource sensing operation within a D resource sensing/selection window indicated by the configuration information; selecting a D transmission resource from among the D candidate resources within the D resource sensing/selection window; and transmitting data to the receiving terminal using the D transmission resource.

(24) The P resource sensing/selection window may be configured independently of the D resource sensing/selection window.

(25) The configuration information may include time resource information of the P resource sensing/selection window and time resource information of the D resource sensing/selection window.

(26) The determining of the D candidate resources may include: reconfiguring the D resource sensing/selection window when the resource sensing operation is not completed within a second reference time in the D resource sensing/selection window; and determining the D candidate resources by performing the resource sensing operation within the reconfigured D resource sensing/selection window.

(27) The second reference time may be configured by the base station, the second reference time may be indicated by an offset from a start time of the D resource sensing/selection window, and the reconfigured D resource sensing/selection may start from the second reference time or a time after an offset configured by the base station from the second reference time.

(28) According to an exemplary embodiment of the present disclosure, a paging (P) resource sensing window and a P resource selection window for paging message transmission may be independently configured. A transmitting terminal may detect candidate resources for transmission of a paging message within the P resource sensing window, select a transmission resource from among the candidate resources within the P resource selection window, and transmit the paging message using the selected transmission resource. Therefore, a transmission collision of the paging message in sidelink communication may be prevented. In addition, the P resource sensing window and/or the P resource selection window may be terminated early, and thus the efficiency of using sidelink resources may be improved. In addition, the P resource sensing/selection window may be reconfigured, and accordingly, a transmission success probability of the paging message may be improved.

(29) The methods and apparatuses of the present disclosure have other features and advantages which will be apparent from or are set forth in more detail in the accompanying drawings, which are incorporated herein, and the following Detailed Description, which together serve to explain certain principles of the present disclosure.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

- (1) FIG. 1 is a conceptual diagram illustrating V2X communication scenarios.
- (2) FIG. 2 is a conceptual diagram illustrating an exemplary embodiment of a cellular communication system.
- (3) FIG. 3 is a conceptual diagram illustrating an exemplary embodiment of a communication node forming a cellular communication system.
- (4) FIG. 4 is a block diagram illustrating an exemplary embodiment of a user plane protocol stack of a UE performing sidelink communication.
- (5) FIG. 5 is a block diagram illustrating a first exemplary embodiment of a control plane protocol stack of a UE performing sidelink communication.
- (6) FIG. 6 is a block diagram illustrating a second exemplary embodiment of a control plane protocol stack of a UE performing sidelink communication.
- (7) FIG. 7 is a sequence chart illustrating a first exemplary embodiment of a method for transmitting and receiving data according to a paging procedure in sidelink communication
- (8) FIG. 8 is a conceptual diagram illustrating a first exemplary embodiment of resource sensing windows and resource selection windows.
- (9) FIG. 9 is a conceptual diagram illustrating a second exemplary embodiment of resource sensing windows and resource selection windows.
- (10) FIG. 10 is a conceptual diagram illustrating a third exemplary embodiment of resource sensing windows and resource selection windows.
- (11) FIG. 11 is a conceptual diagram illustrating a fourth exemplary embodiment of resource sensing windows and resource selection windows.
- (12) FIG. 12 is a conceptual diagram illustrating a fifth exemplary embodiment of resource sensing windows and resource selection windows.
- (13) It may be understood that the appended drawings are not necessarily to scale, presenting a somewhat simplified representation of various features illustrative of the basic principles of the present disclosure. The specific design features of the present disclosure as disclosed herein, including, for example, specific dimensions, orientations, locations, and shapes will be determined in part by the particularly intended application and use environment.
- (14) In the figures, reference numbers refer to the same or equivalent parts of the present disclosure throughout the several figures of the drawing.

DETAILED DESCRIPTION

- (15) Reference will now be made in detail to various embodiments of the present disclosure(s), examples of which are illustrated in the accompanying drawings and described below. While the present disclosure(s) will be described in conjunction with exemplary embodiments of the present disclosure, it will be understood that the present description is not intended to limit the present disclosure(s) to those exemplary embodiments. On the contrary, the present disclosure(s) is/are intended to cover not only the exemplary embodiments of the present disclosure, but also various alternatives, modifications, equivalents and other embodiments, which may be included within the spirit and scope of the present disclosure as defined by the appended claims.
- (16) Since the present disclosure may be variously modified and have several forms, specific exemplary embodiments will be shown in the accompanying drawings and be described in detail in the detailed description. It should be understood, however, that it is not intended to limit the present disclosure to the specific exemplary embodiments but, on the contrary, the present disclosure is to cover all modifications and alternatives falling within the spirit and scope of the present disclosure.
- (17) Relational terms such as first, second, and the like may be used for describing various elements, but the elements should not be limited by the terms. These terms are only used to

distinguish one element from another. For example, a first component may be named a second component without departing from the scope of the present disclosure, and the second component may also be similarly named the first component. The term “and/or” means any one or a combination of a plurality of related and described items.

(18) In exemplary embodiments of the present disclosure, “at least one of A and B” may refer to “at least one of A or B” or “at least one of combinations of one or more of A and B”. In addition, “one or more of A and B” may refer to “one or more of A or B” or “one or more of combinations of one or more of A and B”.

(19) In exemplary embodiments of the present disclosure, ‘(re)transmission’ may refer to ‘transmission’, ‘retransmission’, or ‘transmission and retransmission’, ‘(re)configuration’ may refer to ‘configuration’, ‘reconfiguration’, or ‘configuration and reconfiguration’, ‘(re)connection’ may refer to ‘connection’, ‘reconnection’, or ‘connection and reconnection’, and ‘(re)access’ may refer to ‘access’, ‘re-access’, or ‘access and re-access’.

(20) When it is mentioned that a certain component is “coupled with” or “connected with” another component, it should be understood that the certain component is directly “coupled with” or “connected with” to the other component or a further component may be disposed therebetween. In contrast, when it is mentioned that a certain component is “directly coupled with” or “directly connected with” another component, it will be understood that a further component is not disposed therebetween.

(21) The terms used in the present disclosure are only used to describe specific exemplary embodiments of the present disclosure, and are not intended to limit the present disclosure. The singular expression includes the plural expression unless the context clearly dictates otherwise. In the present disclosure, terms such as ‘comprise’ or ‘have’ are intended to designate that a feature, number, step, operation, component, part, or combination thereof described in the specification exists, but it should be understood that the terms do not preclude existence or addition of one or more features, numbers, steps, operations, components, parts, or combinations thereof.

(22) Unless otherwise defined, all terms (including technical and scientific terms) used herein have the same meaning as commonly understood by one of ordinary skill in the art to which the present disclosure belongs. Terms that are generally used and have been in dictionaries should be construed as having meanings matched with contextual meanings in the art. In the present description, unless defined clearly, terms are not necessarily construed as having formal meanings.

(23) Hereinafter, forms of the present disclosure will be described in detail with reference to the accompanying drawings. In describing the present disclosure, to facilitate the entire understanding of the present disclosure, like numbers refer to like elements throughout the description of the figures and the repetitive description thereof will be omitted.

(24) FIG. 1 is a conceptual diagram illustrating V2X communication scenarios.

(25) As shown in FIG. 1, the V2X communications may include Vehicle-to-Vehicle (V2V) communications, Vehicle-to-Infrastructure (V2I) communications, Vehicle-to-Pedestrian (V2P) communications, Vehicle-to-Network (V2N) communications, and the like. The V2X communications may be supported by a cellular communication system (e.g., a cellular communication system **140**), and the V2X communications supported by the cellular communication system **140** may be referred to as “Cellular-V2X (C-V2X) communications.” Here, the cellular communication system **140** may include the 4G communication system (e.g., LTE communication system or LTE-A communication system), the 5G communication system (e.g., NR communication system), and the like.

(26) The V2V communications may include communications between a first vehicle **100** (e.g., a communication node located in the vehicle **100**) and a second vehicle **110** (e.g., a communication node located in the vehicle **110**). Various driving information such as velocity, heading, time, position, and the like may be exchanged between the vehicles **100** and **110** through the V2V communications. For example, autonomous driving (e.g., platooning) may be supported based on

the driving information exchanged through the V2V communications. The V2V communications supported in the cellular communication system **140** may be performed based on “sidelink” communication technologies (e.g., ProSe and D2D communication technologies, and the like). In the instant case, the communications between the vehicles **100** and **110** may be performed using at least one sidelink channel established between the vehicles **100** and **110**.

(27) The V2I communications may include communications between the first vehicle **100** (e.g., the communication node located in the vehicle **100**) and an infrastructure (e.g., road side unit (RSU)) **120** located on a roadside. The infrastructure **120** may also include a traffic light or a street light which is located on the roadside. For example, when the V2I communications are performed, the communications may be performed between the communication node located in the first vehicle **100** and a communication node located in a traffic light. Traffic information, driving information, and the like may be exchanged between the first vehicle **100** and the infrastructure **120** through the V2I communications. The V2I communications supported in the cellular communication system **140** may also be performed based on sidelink communication technologies (e.g., ProSe and D2D communication technologies, and the like). In the instant case, the communications between the vehicle **100** and the infrastructure **120** may be performed using at least one sidelink channel established between the vehicle **100** and the infrastructure **120**.

(28) The V2P communications may include communications between the first vehicle **100** (e.g., the communication node located in the vehicle **100**) and a person **130** (e.g., a communication node carried by the person **130**). The driving information of the first vehicle **100** and movement information of the person **130** such as velocity, heading, time, position, and the like may be exchanged between the vehicle **100** and the person **130** through the V2P communications. The communication node located in the vehicle **100** or the communication node carried by the person **130** may generate an alarm indicating a danger by judging a dangerous situation based on the obtained driving information and movement information. The V2P communications supported in the cellular communication system **140** may be performed based on sidelink communication technologies (e.g., ProSe and D2D communication technologies, and the like). In the instant case, the communications between the communication node located in the vehicle **100** and the communication node carried by the person **130** may be performed using at least one sidelink channel established between the communication nodes.

(29) The V2N communications may be communications between the first vehicle **100** (e.g., the communication node located in the vehicle **100**) and a server connected through the cellular communication system **140**. The V2N communications may be performed based on the 4G communication technology (e.g., LTE or LTE-A) or the 5G communication technology (e.g., NR). Also, the V2N communications may be performed based on a Wireless Access in Vehicular Environments (WAVE) communication technology or a Wireless Local Area Network (WLAN) communication technology which is defined in Institute of Electrical and Electronics Engineers (IEEE) 802.11, or a Wireless Personal Area Network (WPAN) communication technology defined in IEEE 802.15.

(30) Meanwhile, the cellular communication system **140** supporting the V2X communications may be configured as follows.

(31) FIG. 2 is a conceptual diagram illustrating an exemplary embodiment of a cellular communication system.

(32) As shown in FIG. 2, a cellular communication system may include an access network, a core network, and the like. The access network may include a base station **210**, a relay **220**, User Equipments (UEs) **231** through **236**, and the like. The UEs **231** through **236** may include communication nodes located in the vehicles **100** and **110** of FIG. 1, the communication node located in the infrastructure **120** of FIG. 1, the communication node carried by the person **130** of FIG. 1, and the like. When the cellular communication system supports the 4G communication technology, the core network may include a serving gateway (S-GW) **250**, a packet data network

(PDN) gateway (P-GW) **260**, a mobility management entity (MME) **270**, and the like.

(33) When the cellular communication system supports the 5G communication technology, the core network may include a user plane function (UPF) **250**, a session management function (SMF) **260**, an access and mobility management function (AMF) **270**, and the like. Alternatively, when the cellular communication system operates in a Non-Stand Alone (NSA) mode, the core network constituted by the S-GW **250**, the P-GW **260**, and the MME **270** may support the 5G communication technology as well as the 4G communication technology, and the core network constituted by the UPF **250**, the SMF **260**, and the AMF **270** may support the 4G communication technology as well as the 5G communication technology.

(34) In addition, when the cellular communication system supports a network slicing technique, the core network may be divided into a plurality of logical network slices. For example, a network slice supporting V2X communications (e.g., a V2V network slice, a V2I network slice, a V2P network slice, a V2N network slice, etc.) may be configured, and the V2X communications may be supported through the V2X network slice configured in the core network.

(35) The communication nodes (e.g., base station, relay, UE, S-GW, P-GW, MME, UPF, SMF, AMF, etc.) comprising the cellular communication system may perform communications by using at least one communication technology among a Code Division Multiple Access (CDMA) technology, a Time Division Multiple Access (TDMA) technology, a frequency division multiple access (FDMA) technology, an orthogonal frequency division multiplexing (OFDM) technology, a filtered OFDM technology, an orthogonal frequency division multiple access (OFDMA) technology, a single carrier FDMA (SC-FDMA) technology, a non-orthogonal multiple access (NOMA) technology, a generalized frequency division multiplexing (GFDM) technology, a filter bank multi-carrier (FBMC) technology, a universal filtered multi-carrier (UFMC) technology, and a space division multiple access (SDMA) technology.

(36) The communication nodes (e.g., base station, relay, UE, S-GW, P-GW, MME, UPF, SMF, AMF, etc.) including the cellular communication system may be configured as follows.

(37) FIG. 3 is a conceptual diagram illustrating an exemplary embodiment of a communication node forming a cellular communication system.

(38) As shown in FIG. 3, a communication node **300** may include at least one processor **310**, a memory **320**, and a transceiver **330** connected to a network for performing communications. Also, the communication node **300** may further include an input interface device **340**, an output interface device **350**, a storage device **360**, and the like. Each component included in the communication node **300** may communicate with each other as connected through a bus **370**.

(39) However, each of the components included in the communication node **300** may be connected to the processor **310** via a separate interface or a separate bus rather than the common bus **370**. For example, the processor **310** may be connected to at least one of the memory **320**, the transceiver **330**, the input interface device **340**, the output interface device **350**, and the storage device **360** via a dedicated interface.

(40) The processor **310** may execute at least one instruction stored in at least one of the memory **320** and the storage device **360**. The processor **310** may refer to a central processing unit (CPU), a graphics processing unit (GPU), or a dedicated processor on which methods in accordance with embodiments of the present disclosure are performed. Each of the memory **320** and the storage device **360** may include at least one of a volatile storage medium and a non-volatile storage medium. For example, the memory **320** may include at least one of read-only memory (ROM) and random access memory (RAM).

(41) Referring again to FIG. 2, in the communication system, the base station **210** may form a macro cell or a small cell, and may be connected to the core network via an ideal backhaul or a non-ideal backhaul. The base station **210** may transmit signals received from the core network to the UEs **231** through **236** and the relay **220**, and may transmit signals received from the UEs **231** through **236** and the relay **220** to the core network. The UEs **231**, **232**, **234**, **235** and **236** may

belong to cell coverage of the base station **210**. The UEs **231**, **232**, **234**, **235** and **236** may be connected to the base station **210** by performing a connection establishment procedure with the base station **210**. The UEs **231**, **232**, **234**, **235** and **236** may communicate with the base station **210** after being connected to the base station **210**.

(42) The relay **220** may be connected to the base station **210** and may relay communications between the base station **210** and the UEs **233** and **234**. That is, the relay **220** may transmit signals received from the base station **210** to the UEs **233** and **234**, and may transmit signals received from the UEs **233** and **234** to the base station **210**. The UE **234** may belong to both of the cell coverage of the base station **210** and the cell coverage of the relay **220**, and the UE **233** may belong to the cell coverage of the relay **220**. That is, the UE **233** may be located outside the cell coverage of the base station **210**. The UEs **233** and **234** may be connected to the relay **220** by performing a connection establishment procedure with the relay **220**. The UEs **233** and **234** may communicate with the relay **220** after being connected to the relay **220**.

(43) The base station **210** and the relay **220** may support multiple-input, multiple-output (MIMO) technologies (e.g., single user (SU)-MIMO, multi-user (MU)-MIMO, massive MIMO, etc.), coordinated multipoint (CoMP) communication technologies, carrier aggregation (CA) communication technologies, unlicensed band communication technologies (e.g., Licensed Assisted Access (LAA), enhanced LAA (eLAA), etc.), sidelink communication technologies (e.g., ProSe communication technology, D2D communication technology), or the like. The UEs **231**, **232**, **235** and **236** may perform operations corresponding to the base station **210** and operations supported by the base station **210**. The UEs **233** and **234** may perform operations corresponding to the relays **220** and operations supported by the relays **220**.

(44) Here, the base station **210** may be referred to as a Node B (NB), an evolved Node B (eNB), a base transceiver station (BTS), a radio remote head (RRH), a transmission reception point (TRP), a radio unit (RU), a roadside unit (RSU), a radio transceiver, an access point, an access node, or the like. The relay **220** may be referred to as a small base station, a relay node, or the like. Each of the UEs **231** through **236** may be referred to as a terminal, an access terminal, a mobile terminal, a station, a subscriber station, a mobile station, a portable subscriber station, a node, a device, an on-board unit (OBU), or the like.

(45) Meanwhile, the communications between the UEs **235** and **236** may be performed based on the sidelink communication technique. The sidelink communications may be performed based on a one-to-one scheme or a one-to-many scheme. When V2V communications are performed using the sidelink communication technique, the UE **235** may be the communication node located in the first vehicle **100** of FIG. **1** and the UE **236** may be the communication node located in the second vehicle **110** of FIG. **1**. When V2I communications are performed using the sidelink communication technique, the UE **235** may be the communication node located in first vehicle **100** of FIG. **1** and the UE **236** may be the communication node located in the infrastructure **120** of FIG. **1**. When V2P communications are performed using the sidelink communication technique, the UE **235** may be the communication node located in first vehicle **100** of FIG. **1** and the UE **236** may be the communication node carried by the person **130** of FIG. **1**.

(46) The scenarios to which the sidelink communications are applied may be classified as shown below in Table 1 according to the positions of the UEs (e.g., the UEs **235** and **236**) participating in the sidelink communications. For example, the scenario for the sidelink communications between the UEs **235** and **236** shown in FIG. **2** may be a sidelink communication scenario C.

(47) TABLE-US-00001 TABLE 1 Sidelink Communication Scenario Position of UE 235 Position of UE 236 A Out of coverage of Out of coverage of base station 210 B In coverage of base station 210 C In coverage of base station 210 D In coverage of base station 210 E In coverage of other station 210

(48) Meanwhile, a user plane protocol stack of the UEs (e.g., the UEs **235** and **236**) performing sidelink communications may be configured as follows.

(49) FIG. 4 is a block diagram illustrating an exemplary embodiment of a user plane protocol stack of a UE performing sidelink communication.

(50) As shown in FIG. 4, a left UE may be the UE 235 shown in FIG. 2 and a right UE may be the UE 236 shown in FIG. 2. The scenario for the sidelink communications between the UEs 235 and 236 may be one of the sidelink communication scenarios A through D of Table 1. The user plane protocol stack of each of the UEs 235 and 236 may include a physical (PHY) layer, a medium access control (MAC) layer, a radio link control (RLC) layer, and a packet data convergence protocol (PDCP) layer.

(51) The sidelink communications between the UEs 235 and 236 may be performed using a PC5 interface (e.g., PC5-U interface). A layer-2 identifier (ID) (e.g., a source layer-2 ID, a destination layer-2 ID) may be used for the sidelink communications, and the layer 2-ID may be an ID configured for the V2X communications (e.g., V2X service). Also, in the sidelink communications, a hybrid automatic repeat request (HARQ) feedback operation may be supported, and an RLC acknowledged mode (RLC AM) or an RLC unacknowledged mode (RLC UM) may be supported.

(52) Meanwhile, a control plane protocol stack of the UEs (e.g., the UEs 235 and 236) performing sidelink communications may be configured as follows.

(53) FIG. 5 is a block diagram illustrating a first exemplary embodiment of a control plane protocol stack of a UE performing sidelink communication, and FIG. 6 is a block diagram illustrating a second exemplary embodiment of a control plane protocol stack of a UE performing sidelink communication.

(54) As shown in FIG. 5 and FIG. 6, a left UE may be the UE 235 shown in FIG. 2 and a right UE may be the UE 236 shown in FIG. 2. The scenario for the sidelink communications between the UEs 235 and 236 may be one of the sidelink communication scenarios A through D of Table 1. The control plane protocol stack illustrated in FIG. 5 may be a control plane protocol stack for transmission and reception of broadcast information (e.g., Physical Sidelink Broadcast Channel (PSBCH)).

(55) The control plane protocol stack shown in FIG. 5 may include a PHY layer, a MAC layer, an RLC layer, and a radio resource control (RRC) layer. The sidelink communications between the UEs 235 and 236 may be performed using a PC5 interface (e.g., PC5-C interface). The control plane protocol stack shown in FIG. 6 may be a control plane protocol stack for one-to-one sidelink communication. The control plane protocol stack shown in FIG. 6 may include a PHY layer, a MAC layer, an RLC layer, a PDCP layer, and a PC5 signaling protocol layer.

(56) Meanwhile, channels used in the sidelink communications between the UEs 235 and 236 may include a Physical Sidelink Shared Channel (PSSCH), a Physical Sidelink Control Channel (PSCCH), a Physical Sidelink Discovery Channel (PSDCH), and a Physical Sidelink Broadcast Channel (PSBCH). The PSSCH may be used for transmitting and receiving sidelink data and may be configured in the UE (e.g., UE 235 or 236) by a higher layer signaling. The PSCCH may be used for transmitting and receiving sidelink control information (SCI) and may also be configured in the UE (e.g., UE 235 or 236) by a higher layer signaling.

(57) The PSDCH may be used for a discovery procedure. For example, a discovery signal may be transmitted over the PSDCH. The PSBCH may be used for transmitting and receiving broadcast information (e.g., system information). Also, a demodulation reference signal (DM-RS), a synchronization signal, or the like may be used in the sidelink communications between the UEs 235 and 236. The synchronization signal may include a primary sidelink synchronization signal (PSSS) and a secondary sidelink synchronization signal (SSSS).

(58) Meanwhile, a sidelink transmission mode (TM) may be classified into sidelink TMs 1 to 4 as shown below in Table 2.

(59) TABLE-US-00002 TABLE 2 Sidelink TM Description
1 Transmission using resources scheduled by base station
2 UE autonomous transmission without scheduling of base station
3 Transmission using resources scheduled by base station in V2X communications
4 UE autonomous

transmission without scheduling of base station in V2X communications

(60) When the sidelink TM 3 or 4 is supported, each of the UEs **235** and **236** may perform sidelink communications using a resource pool configured by the base station **210**. The resource pool may be configured for each of the sidelink control information and the sidelink data.

(61) The resource pool for the sidelink control information may be configured based on an RRC signaling procedure (e.g., a dedicated RRC signaling procedure, a broadcast RRC signaling procedure). The resource pool used for reception of the sidelink control information may be configured by a broadcast RRC signaling procedure. When the sidelink TM 3 is supported, the resource pool used for transmission of the sidelink control information may be configured by a dedicated RRC signaling procedure. In the instant case, the sidelink control information may be transmitted through resources scheduled by the base station **210** within the resource pool configured by the dedicated RRC signaling procedure. When the sidelink TM 4 is supported, the resource pool used for transmission of the sidelink control information may be configured by a dedicated RRC signaling procedure or a broadcast RRC signaling procedure. In the instant case, the sidelink control information may be transmitted through resources selected autonomously by the UE (e.g., UE **235** or **236**) within the resource pool configured by the dedicated RRC signaling procedure or the broadcast RRC signaling procedure.

(62) When the sidelink TM 3 is supported, the resource pool for transmitting and receiving sidelink data may not be configured. In the instant case, the sidelink data may be transmitted and received through resources scheduled by the base station **210**. When the sidelink TM 4 is supported, the resource pool for transmitting and receiving sidelink data may be configured by a dedicated RRC signaling procedure or a broadcast RRC signaling procedure. In the instant case, the sidelink data may be transmitted and received through resources selected autonomously by the UE (e.g., UE **235** or **236**) within the resource pool configured by the dedicated RRC signaling procedure or the broadcast RRC signaling procedure.

(63) Hereinafter, sidelink communication methods will be described. Even when a method (e.g., transmission or reception of a signal) to be performed at a first communication node among communication nodes is described, a corresponding second communication node may perform a method (e.g., reception or transmission of the signal) corresponding to the method performed at the first communication node. That is, when an operation of a UE #1 (e.g., vehicle #1) is described, a UE #2 (e.g., vehicle #2) corresponding thereto may perform an operation corresponding to the operation of the UE #1. Conversely, when an operation of the UE #2 is described, the corresponding UE #1 may perform an operation corresponding to the operation of the UE #2. In exemplary embodiments described below, an operation of a vehicle may be an operation of a communication node located in the vehicle.

(64) In exemplary embodiments of the present disclosure, signaling may be one or a combination of two or more of higher layer signaling, MAC signaling, and physical (PHY) signaling. A message used for higher layer signaling may be referred to as a 'higher layer message' or 'higher layer signaling message'. A message used for MAC signaling may be referred to as a 'MAC message' or 'MAC signaling message'. A message used for PHY signaling may be referred to as a 'PHY message' or 'PHY signaling message'. The higher layer signaling may refer to an operation of transmitting and receiving system information (e.g., master information block (MIB), system information block (SIB)) and/or an RRC message. The MAC signaling may refer to an operation of transmitting and receiving a MAC control element (CE). The PHY signaling may refer to an operation of transmitting and receiving control information (e.g., downlink control information (DCI), uplink control information (UCI), or SCI).

(65) A sidelink signal may be a synchronization signal and a reference signal used for sidelink communication. For example, the synchronization signal may be a synchronization signal/physical broadcast channel (SS/PBCH) block, sidelink synchronization signal (SLSS), primary sidelink synchronization signal (PSSS), secondary sidelink synchronization signal (SSSS), or the like. The

reference signal may be a channel state information-reference signal (CSI-RS), DM-RS, phase tracking-reference signal (PT-RS), cell-specific reference signal (CRS), sounding reference signal (SRS), discovery reference signal (DRS), or the like.

(66) A sidelink channel may be a PSSCH, PSCCH, PSDCH, PSBCH, physical sidelink feedback channel (PSFCH), or the like. In addition, a sidelink channel may refer to a sidelink channel including a sidelink signal mapped to specific resources in the corresponding sidelink channel. The sidelink communication may support a broadcast service, a multicast service, a groupcast service, and a unicast service.

(67) The sidelink communication may be performed based on a single-SCI scheme or a multi-SCI scheme. When the single-SCI scheme is used, data transmission (e.g., sidelink data transmission, sidelink-shared channel (SL-SCH) transmission) may be performed based on one SCI (e.g., 1st-stage SCI). When the multi-SCI scheme is used, data transmission may be performed using two SCIs (e.g., 1st-stage SCI and 2nd-stage SCI). The SCI(s) may be transmitted on a PSCCH and/or a PSSCH. When the single-SCI scheme is used, the SCI (e.g., 1st-stage SCI) may be transmitted on a PSCCH. When the multi-SCI scheme is used, the 1st-stage SCI may be transmitted on a PSCCH, and the 2nd-stage SCI may be transmitted on the PSCCH or a PSSCH. The 1st-stage SCI may be referred to as ‘first-stage SCI’, and the 2nd-stage SCI may be referred to as ‘second-stage SCI’. A format of the first-stage SCI may include a SCI format 1-A, and a format of the second-stage SCI may include a SCI format 2-A and a SCI format 2-B.

(68) The 1st-stage SCI may include or more information elements among priority information, frequency resource assignment information, time resource assignment information, resource reservation period information, demodulation reference signal (DMRS) pattern information, 2nd-stage SCI format information, a beta offset indicator, the number of DMRS ports, and modulation and coding scheme (MCS) information. The 2nd-stage SCI may include one or more information elements among a HARQ processor identifier (ID), a redundancy version (RV), a source ID, a destination ID, CSI request information, a zone ID, and communication range requirements.

(69) Meanwhile, a receiving terminal may operate in an RRC inactive mode, RRC idle mode, or sleep mode. When data (e.g., sidelink data) to be transmitted to the receiving terminal exists in a transmitting terminal, the transmitting terminal may transmit a paging message and/or a wake-up signal to the receiving terminal to inform that the data exists. The receiving terminal may receive the paging message and/or the wake-up signal from the transmitting terminal. The receiving terminal may determine that the data to be transmitted to the receiving terminal exists in the transmitting terminal based on information included in the paging message and/or the wake-up signal.

(70) In the instant case, the operation state of the receiving terminal may transition to an RRC connected state. The receiving terminal operating in the RRC connected state may receive the data from the transmitting terminal. The above-described operations may be performed using sidelink resources configured according to a resource allocation (RA) mode 2. In exemplary embodiments of the present disclosure, the transmitting terminal may refer to a terminal transmitting data, the receiving terminal may refer to a terminal receiving the data, and the receiving terminal may be interpreted as ‘one or more receiving terminals’. Methods for transmitting and receiving a paging message will be described in the following exemplary embodiments. The methods for transmitting and receiving a paging message may be applied identically or similarly to transmission and reception of a wake-up signal. That is, in the exemplary embodiments of the present disclosure, a paging message may be interpreted as a wake-up signal. A paging message may be used as a meaning including a wake-up signal. For example, a paging message may include a wake-up signal.

(71) Each of a resource sensing window and a resource selection window for paging message transmission may be configured independently of a resource sensing window and a resource selection window for data transmission. The resource sensing window for paging message

transmission may be referred to as a paging (P) resource sensing window, and the resource selection window for paging message transmission may be referred to as a P resource selection window. The resource sensing window for data transmission may be referred to as a data (D) resource sensing window, and the resource selection window for data transmission may be referred to as a D resource selection window.

(72) FIG. 7 is a sequence chart illustrating a first exemplary embodiment of a method for transmitting and receiving data according to a paging procedure in sidelink communication.

(73) As shown in FIG. 7, a method for transmitting and receiving data according to a paging procedure may include four steps (e.g., step S701, step S702, step S703, and step S704). As a previous step of the four steps, a transmitting terminal and/or a receiving terminal may receive resource sensing/selection window configuration information from the base station. The resource sensing/selection window configuration information may include configuration information of a P resource sensing window, configuration information of a P resource selection window, configuration information of a D resource sensing window, and/or configuration information of a D resource selection window. The resource sensing/selection window configuration information may be configured using at least one of system information, RRC message, MAC control element (CE), or control information (e.g., downlink control information (DCI)).

(74) When there is data to be transmitted to the receiving terminal, the transmitting terminal may perform a transmission operation of a paging message. For example, the transmitting terminal may perform a resource sensing operation within the P resource sensing window (S701). The transmitting terminal may be configured to determine (e.g., detect or sense) candidate resource(s) by performing the resource sensing operation. The transmitting terminal may select a transmission resource from among the candidate resource(s) within the P resource selection window, and may transmit a paging message in the selected transmission resource (S702). The receiving terminal may receive the paging message from the transmitting terminal and may be configured to determine that data exists in the transmitting terminal based on information included in the paging message. In the instant case, an operation state of the receiving terminal may transition from the RRC inactive mode, RRC idle mode, or sleep mode to the RRC connected mode.

(75) After transmitting the paging message, the transmitting terminal may perform a resource sensing operation within the D resource sensing window (S703). The transmitting terminal may be configured to determine (e.g., detect or sense) candidate resource(s) by performing the resource sensing operation. The transmitting terminal may select a transmission resource from among the candidate resource(s) within the D resource selection window, and may transmit data (e.g., sidelink data) in the selected transmission resource (S704). The receiving terminal may receive the data from the transmitting terminal.

(76) The above-described four steps may be performed as follows. In the step S701, when data to be transmitted to the receiving terminal occurs, the P resource sensing window may be started. The transmitting terminal may detect usable resource(s) (e.g., candidate resource(s)) by performing the resource sensing operation within the P resource sensing window. In the step S702, the P resource selection window may be configured, and the transmitting terminal may select a transmission resource from among the candidate resource(s) within the P resource selection window, and may transmit the paging message using the transmission resource.

(77) The receiving terminal may receive the paging message from the transmitting terminal by performing a monitoring operation in the P resource selection window. The receiving terminal may identify that data to be transmitted to the receiving terminal exists in the transmitting terminal based on the paging message. In the instant case, the receiving terminal may perform a PSCCH monitoring operation to receive SCI for scheduling the corresponding data.

(78) In the step S703, the D resource sensing window may be configured, and the transmitting terminal may detect candidate resource(s) by performing the resource sensing operation within the D resource sensing window. In the step S704, the D resource selection window may be configured,

and the transmitting terminal may select a transmission resource from among the candidate resource(s) within the D resource selection window, and may transmit the data using the transmission resource. The receiving terminal may receive the data from the transmitting terminal. (79) A time resource and/or a frequency resource of each of the P resource sensing window, the P resource selection window, the D resource sensing window, and the D resource selection window may be configured within a resource pool. The P resource sensing window, the P resource selection window, the D resource sensing window, and the D resource selection window may be configured as follows.

(80) FIG. 8 is a conceptual diagram illustrating a first exemplary embodiment of resource sensing windows and resource selection windows.

(81) As shown in FIG. 8, the P resource sensing window may be configured in a time resource from T1 to T2, the P resource selection window may be configured in a time resource from T3 to T4, the D resource sensing window may be configured in a time resource from T5 to T6, and the D resource selection window may be configured in a time resource from T7 to T8. T1 to T8 may mean continuous time or discontinuous time. Each of T1 to T8 may be expressed as a transmission time interval (TTI), symbol index, subframe index, slot index, or mini-slot index. The symbol index may be an orthogonal frequency division multiplexing (OFDM) symbol index, an orthogonal frequency division multiple access (OFDMA) symbol index, a single carrier (SC)-frequency division multiplexing (FDM) symbol index, or a single carrier-frequency division multiple access (SC-FDMA) symbol index.

(82) Frequency resources of the P resource sensing window, the P resource selection window, the D resource sensing window, and the D resource selection window may be configured to be the same or different from each other. Alternatively, the frequency resources of the P resource sensing window, the P resource selection window, the D resource sensing window, and the D resource selection window may be configured to partially overlap.

(83) A window interval (hereinafter, referred to as ‘first window interval’) between an end time (i.e., T2) of the P resource sensing window and a start time (i.e., T3) of the P resource selection window may be configured. A window interval (hereinafter referred to as ‘second window interval’) between an end time (i.e., T4) of the P resource selection window and a start time (i.e., T5) of the D resource sensing window may be configured. A window interval (hereinafter, referred to as ‘third window interval’) between an end time (i.e., T6) of the D resource sensing window and a start time (i.e., T7) of the D resource selection window may be configured. The window intervals described above may be configured identically or differently.

(84) The base station may configure one or more information elements defined in Table 3 below, and use at least one of system information, RRC message, MAC CE, or control information to transmit the one or more information elements to the terminal(s) (e.g., transmitting terminal and/or receiving terminal). The terminal(s) may identify the one or more information elements defined in Table 3 below by receiving at least one of the system information, RRC message, MAC CE, or control information from the base station. Alternatively, one or more information elements defined in Table 3 below may be configured by the transmitting terminal, and the transmitting terminal may transmit the one or more information elements to the receiving terminal by using at least one of an RRC message, MAC CE, or control information (e.g., SCI). The receiving terminal may identify the one or more information elements defined in Table 3 below by receiving at least one of the RRC message, MAC CE, or control information from the transmitting terminal.

(85) TABLE-US-00003 TABLE 3 Information element(s) Time and/or frequency resource information of the P resource sensing window Time and/or frequency resource information of the P resource selection window Time and/or frequency resource information of the D resource sensing window Time and/or frequency resource information of the D resource selection window First window interval Second window interval Third window interval

(86) The resource sensing window and the resource selection window may be configured for each

resource pool. In exemplary embodiments of the present disclosure, the resource sensing window may mean the P resource sensing window and/or the D resource sensing window, the resource selection window may mean the P resource selection window and/or the D resource selection window, and the resource pool may be referred to as 'RP'.

(87) TABLE-US-00004 TABLE 4 Resource pool Resource sensing window Resource selection window RP #1 X1 slots X2 slots RP #1 X3 slots X4 slots RP #2 X5 slots X6 slots RP #2 X7 slots X8 slots

(88) Referring to Table 4, a resource sensing window and a resource selection window for each of the RP #1 and the RP #2 may be independently configured. In Table 4, the resource sensing window and the resource selection window may be configured in the same frequency resource. When the resource sensing window and the resource selection window are configured in different frequency resources, Table 4 may further include frequency resource information. In the instant case, the frequency resources may be configured in units of subcarriers, subchannels, or resource blocks (RBs). That is, the frequency resource may be represented by subcarrier index(es), subchannel index(es), or RB index(es). A subchannel may include one or more subcarriers or one or more RBs. The RB may be a physical RB (PRB), a virtual RB (VRB), or a common RB (CRB). The frequency resource of each of the resource sensing window and the resource selection window may be expressed as a relative location (e.g., offset) from a reference resource within the resource pool.

(89) When two resource pools (e.g., RP #1 and RP #2) are allocated (e.g., configured) in the transmitting terminal, the resource sensing window and/or resource selection window defined in Table 4 may be configured. In Table 4, each of X1 to X8 may be a natural number. The time resource of each of the resource sensing window and the resource selection window may be indicated by the number of slots. Alternatively, the time resource of each of the resource sensing window and the resource selection window may be configured in units of TTIs, symbols, subframes, mini-slots, milliseconds, or seconds.

(90) The P resource sensing window and the P resource selection window may be configured in the same or similar form as in Table 4. Independently of the P resource sensing window and the P resource selection window, the D resource sensing window and the D resource selection window may be configured in the same or similar form as in Table 4. Alternatively, Table 4 may be commonly applied to the P resource sensing window, the P resource selection window, the D resource sensing window, and the D resource selection window. The configuration value (e.g., time resource) of the resource sensing window may be the same as or different from the configuration value of the resource selection window.

(91) Referring to Table 4, two resource sensing/selection window configurations may be configured for one resource pool. For example, according to a first resource sensing/selection window configuration for the RP #1, the time resource of the resource sensing window may be configured in X1 slots, and the time resource of the resource selection window may be configured in X2 slots. According to a second resource sensing/selection window configuration for the RP #1, the time resource of the resource sensing window may be configured in X3 slots, and the time resource of the resource selection window may be configured in X4 slots.

(92) When a plurality of resource sensing/selection window configurations exist for one resource pool, the transmitting terminal may use one resource sensing/selection window configuration among the plurality of resource sensing/selection window configurations according to specific condition(s). The base station may configure the specific condition(s) to the transmitting terminal and/or the receiving terminal using at least one of system information, RRC signaling, MAC CE, or control information. The specific condition(s) may be defined as shown in Table 5 below.

(93) TABLE-US-00005 TABLE 5 Description Condition #1 Size of data to be transmitted from the transmitting terminal to the receiving terminal Condition #2 Required latency Condition #3 Priority per data Condition #4 Priority per sidelink service

(94) For example, when the size of data to be transmitted from the transmitting terminal to the receiving terminal is greater than or equal to a threshold, the transmitting terminal may select a resource sensing/selection window configuration including a large time resource among the plurality of resource sensing/selection window configurations for one resource pool. When a priority of the data is high or when a required latency is short, the transmitting terminal may select a resource sensing/selection window configuration including a small time resource among the plurality of resource sensing/selection window configurations for one resource pool. When transmission resources for a plurality of data transmissions are required, the transmitting terminal may select a D resource sensing/selection window configuration including a large time resource among a plurality of D resource sensing/selection window configurations for one resource pool.

(95) TABLE-US-00006 TABLE 6 Configuration value First window interval (T3-T2) Y1 Y2
Second window interval (T5-T4) Y3 Y4 Third window interval (T7-T6) Y5 Y6

(96) The window intervals shown in FIG. 8 may be configured as shown in Table 6. Each of Y1 to Y6 may be configured in units of TTIs, symbols, subframes, slots, mini-slots, milliseconds, or seconds. A plurality of configuration values (e.g., two configuration values) may be configured for one window interval. In the instant case, the transmitting terminal may use one configuration value among the plurality of configuration values based on the specific condition(s) defined in Table 5. Alternatively, the first window interval, the second window interval, and the third window interval may have the same configuration value (e.g., time resource).

(97) FIG. 9 is a conceptual diagram illustrating a second exemplary embodiment of resource sensing windows and resource selection windows.

(98) As shown in FIG. 9, the P resource sensing window and/or the D resource sensing window may be early terminated. The P resource sensing window may be configured in a time resource from T1 to T2, and may be early terminated at T3 before T2. For example, when the resource sensing operation is completed before T3, the P resource sensing window may be early terminated at T3. T3 may be used as a reference value for early termination of the P resource sensing window. When the P resource sensing window is early terminated, the P resource selection window may start from the early termination time (i.e., T3) of the P resource sensing window, and the transmitting terminal may perform the resource selection operation within the P resource selection window. Alternatively, when the first window interval is configured, the P resource selection window may start after a time (T3+the first window interval).

(99) The D resource sensing window may be configured in a time resource from T5 to T6, and may be early terminated at T7 before T6. For example, when the resource sensing operation is completed before T7, the D resource sensing window may be early terminated at T7. T7 may be used as a reference value for early termination of the D resource sensing window. When the D resource sensing window is early terminated, the D resource selection window may start from the early termination time (i.e., T7) of the D resource sensing window, and the transmitting terminal may perform the resource selection operation within the D resource selection window.

Alternatively, when the third window interval is configured, the D resource selection window may start after a time (T7+the third window interval). The early termination time of the resource sensing window may be configured as shown in Table 7 below. The base station may transmit configuration information of the early termination time to the transmitting terminal and/or the receiving terminal using at least one of system information, RRC message, MAC CE, or control information.

(100) TABLE-US-00007 TABLE 7 Resource Early termination Resource sensing time of resource selection Resource pool window sensing window window RP #1 X1 slots Z1 slots X2 slots RP #1 X3 slots Z2 slots X4 slots RP #2 X5 slots Z3 slots X6 slots RP #2 X7 slots Z4 slots X8 slots

(101) The transmitting terminal and/or the receiving terminal may operate according to the configuration defined in Table 7. For example, the transmitting terminal may perform the resource sensing operation in the resource sensing window (e.g., P resource sensing window and/or D resource sensing window) within the RP #1. When the resource sensing operation is completed

within (X1–Z1) slots, the transmitting terminal may early terminate the resource sensing window, and perform the resource selection operation in the resource selection window configured in X2 slots. When the window interval (e.g., the first window interval and/or the third window interval) is configured, the resource selection window may start after the window interval from the early termination time of the resource sensing window.

(102) The early termination operation of the resource sensing window may be enabled or disabled by the base station. For example, when the base station transmits information indicating that the early termination operation of the resource sensing window is enabled, the transmitting terminal may perform the early termination operation of the resource sensing window. On the other hand, when the base station transmits information indicating that the early termination operation of the resource sensing window is disabled, the transmitting terminal may not perform the early termination operation of the resource sensing window. The information indicative of enabling or disabling the early termination function of the resource sensing window may be transmitted through at least one of system information, RRC message, MAC CE, or control information.

(103) The early termination operation of the resource sensing window may be performed when specific condition(s) are satisfied. The specific condition(s) may be the specific condition(s) defined in Table 5. The specific condition(s) may be configured by at least one of system information, RRC message, MAC CE, or control information. For example, when a priority of data is higher than a reference priority (e.g., reference priority configured by higher layer signaling) or when a required latency is shorter than a reference latency (e.g., reference latency configured by higher layer signaling), the transmitting terminal may perform the early termination operation of the resource sensing window. When the resource sensing window is early terminated, the transmitting terminal may immediately perform the resource selection operation.

(104) Meanwhile, a time offset from a start time of the resource sensing operation to a resource selection time (e.g., completion time of the resource selection operation) may be configured. The time offsets may be configured for each resource pool as shown in Table 8 below.

(105) TABLE-US-00008 TABLE 8 Resource pool Time offset RP #1 X RP #2 Y

(106) The base station may transmit configuration information of the time offsets to the transmitting terminal and/or the receiving terminal using at least one of system information, RRC message, MAC CE, or control information. The time offset for the P resource sensing/selection window may be configured independently of the time offset for the D resource sensing/selection window. Alternatively, the time offset for the P resource sensing/selection window may be configured to be equal to the time offset for the D resource sensing/selection window.

(107) A plurality of time offsets may be configured for one resource pool. In the instant case, the transmitting terminal may use one time offset among the plurality of time offsets based on specific condition(s) (e.g., specific condition(s) defined in Table 5). In Table 8, each of X and Y may be configured in units of TTIs, symbols, subframes, slots, mini-slots, milliseconds, or seconds. In the RP #1, the transmitting terminal may select a transmission resource within X from a start time of the resource sensing operation, and may transmit a signal (e.g., data) using the selected transmission resource. In the RP #2, the transmitting terminal may select a transmission resource within Y from a start time of the resource sensing operation, and may transmit a signal (e.g., data) using the selected transmission resource.

(108) FIG. 10 is a conceptual diagram illustrating a third exemplary embodiment of resource sensing windows and resource selection windows.

(109) As shown in FIG. 10, a P resource sensing/selection window may include the P resource sensing window and the P resource selection window, and may be configured in a time resource from T1 to T2. The time resource from T1 to T2 may be X (i.e., time offset) defined in Table 8. When a paging message is transmitted in a selected transmission resource, the P resource sensing/selection window may be early terminated. A D resource sensing/selection window may include the D resource sensing window and the D resource selection window, and may be

configured in a time resource from T3 to T4. The time resource from T3 to T4 may be X (i.e., time offset) defined in Table 8. When data is transmitted in a selected transmission resource, the D resource sensing/selection window may be early terminated.

(110) Meanwhile, in the exemplary embodiment based on Table 8 and FIG. 10, when the resource sensing operation is not completed until a specific time, the resource sensing/selection window may be initialized. An initialization offset for initialization of the resource sensing/selection window may be configured as shown in Table 9 below.

(111) TABLE-US-00009 TABLE 9 Resource pool Time offset Initialization offset RP #1 X F1 RP #2 Y F2

(112) The base station may transmit configuration information of the initialization offsets to the transmitting terminal and/or the receiving terminal using at least one of system information, RRC message, MAC CE, or control information. The initialization offset for the P resource sensing/selection window may be configured independently of the initialization offset for the D resource sensing/selection window. Alternatively, the initialization offset for the P resource sensing/selection window may be configured to be equal to the initialization offset for the D resource sensing/selection window.

(113) A plurality of initialization offsets may be configured for one resource pool. In the instant case, the transmitting terminal may use one initialization offset among the plurality of initialization offsets based on specific condition(s) (e.g., specific condition(s) defined in Table 5). In Table 9, each of F1 and F2 may be configured in units of TTIs, symbols, subframes, slots, mini-slots, milliseconds, or seconds.

(114) FIG. 11 is a conceptual diagram illustrating a fourth exemplary embodiment of resource sensing windows and resource selection windows.

(115) As shown in FIG. 11, the transmitting terminal may perform the resource sensing/selection operation in a P resource sensing/selection window #1 in the RP #1. The P resource sensing/selection window #1 may be configured in a time resource from T1 to T2. The length of the time resource from T1 to T2 may correspond to X defined in Table 9. The resource sensing operation may start at T1. T3 may be a time at which the resource sensing operation should be completed. When the resource sensing operation is not completed within T3, the transmitting terminal may reconfigure the P resource sensing/selection window based on T3. The reconfigured P resource sensing/selection window may be a P resource sensing/selection window #2, and the P resource sensing/selection window #2 may start at T3. The value of (T3-T1) may be F1 (i.e., initialization offset) defined in Table 9. The length of the P resource sensing/selection window #2 may be the same as the length of the P resource sensing/selection window #1, and a start time of the P resource sensing/selection window #2 may be different from a start time of the P resource sensing/selection window #1. The above-described operation may be equally or similarly applied to the D resource sensing/selection window.

(116) Meanwhile, in the exemplary embodiment based on Table 9 and FIG. 11, a sensing termination offset may be additionally considered. The initialization operation of the resource sensing/selection window may be performed after the sensing terminal offset from an end time of the resource sensing operation. The sensing termination offset may be configured as shown in Table 10 below.

(117) TABLE-US-00010 TABLE 10 Sensing termination Resource pool Time offset offset Initialization offset RP #1 X X1 F1 RP #2 Y X2 F2

(118) The base station may transmit configuration information of the sensing termination offsets to the transmitting terminal and/or the receiving terminal using at least one of system information, RRC message, MAC CE, or control information. The sensing termination offset for the P resource sensing/selection window may be configured independently of the sensing termination offset for the D resource sensing/selection window. Alternatively, the sensing termination offset for the P resource sensing/selection window may be configured to be equal to the sensing termination offset

for the D resource sensing/selection window.

(119) A plurality of sensing termination offsets may be configured for one resource pool. In the instant case, the transmitting terminal may use one sensing termination offset among the plurality of sensing termination offsets based on specific condition(s) (e.g., specific condition(s) defined in Table 5). In Table 10, each of X1 and Y1 may be configured in units of TTIs, symbols, subframes, slots, mini-slots, milliseconds, or seconds.

(120) FIG. 12 is a conceptual diagram illustrating a fifth exemplary embodiment of resource sensing windows and resource selection windows.

(121) As shown in FIG. 12, the transmitting terminal may perform a resource sensing/selection operation in a P resource sensing/selection window #1 in the RP #1. The P resource sensing/selection window #1 may be configured in a time resource from T1 to T2. The length of the time resource from T1 to T2 may correspond to X defined in Table 11. The resource sensing operation may start at T1. T3 may be a time at which the resource sensing operation should be completed. When the resource sensing operation is not completed within T3, the transmitting terminal may reconfigure the P resource sensing/selection window based on T4, which is a time after an initialization offset (e.g., F1 defined in Table 10) from T3. The reconfigured P resource sensing/selection window may be a P resource sensing/selection window #2, and the P resource sensing/selection window #2 may start at T4. A value of (T3-T1) may be X1 (i.e., sensing termination offset) defined in Table 10, and a value of (T4-T3) may be F1 (i.e., initialization offset) defined in Table 10. The above-described operation may be equally or similarly applied to the D resource sensing/selection window.

(122) Meanwhile, in the above-described exemplary embodiments of the present disclosure, the configuration value (e.g., values defined in Tables 3 to 10) may be expressed as an offset based on a start time of the resource sensing operation. Alternatively, the reference time of the offset may be a time other than the start time of the resource sensing operation (e.g., a time preconfigured by the base station). Among the values defined in Tables 3 to 10, some values may be fixed values in the communication system, and the remaining values may be configured by at least one of system information, RRC message, MAC CE, or control information. The values defined in Tables 3 to 10 may be cell-specific information (e.g., common information for a plurality of terminals within one cell), RP-specific information (e.g., common information for one RP), or terminal-specific information. The values defined in Tables 3 to 10 may be configured independently according to the resource pool, service type, priority, power saving operation state, quality of service (QoS) parameter (e.g., reliability, latency), and/or terminal type (e.g., vehicle (V)-UE or pedestrian (P)-UE). The values defined in Tables 3 to 10 may be implicitly indicated based on preconfigured parameter(s).

(123) The exemplary embodiments of the present disclosure may be implemented as program instructions executable by a variety of computers and recorded on a computer readable medium. The computer readable medium may include a program instruction, a data file, a data structure, or a combination thereof. The program instructions recorded on the computer readable medium may be designed and configured specifically for the present disclosure or may be publicly known and available to those who are skilled in the field of computer software.

(124) Examples of the computer readable medium may include a hardware device such as ROM, RAM, and flash memory, which are specifically configured to store and execute the program instructions. Examples of the program instructions include machine codes made by, for example, a compiler, as well as high-level language codes executable by a computer, using an interpreter. The above exemplary hardware device may be configured to operate as at least one software module to perform the exemplary embodiments of the present disclosure, and vice versa.

(125) While the exemplary embodiments of the present disclosure and their advantages have been described in detail, it should be understood that various changes, substitutions and alterations may be made herein without departing from the scope of the present disclosure.

(126) For convenience in explanation and accurate definition in the appended claims, the terms “upper”, “lower”, “inner”, “outer”, “up”, “down”, “upwards”, “downwards”, “front”, “rear”, “back”, “inside”, “outside”, “inwardly”, “outwardly”, “interior”, “exterior”, “internal”, “external”, “forwards”, and “backwards” are used to describe features of the exemplary embodiments with reference to the positions of such features as displayed in the figures. It will be further understood that the term “connect” or its derivatives refer both to direct and indirect connection.

(127) The foregoing descriptions of specific exemplary embodiments of the present disclosure have been presented for purposes of illustration and description. They are not intended to be exhaustive or to limit the present disclosure to the precise forms disclosed, and obviously many modifications and variations are possible in light of the above teachings. The exemplary embodiments were chosen and described in order to explain certain principles of the present disclosure and their practical application, to enable others skilled in the art to make and utilize various exemplary embodiments of the present disclosure, as well as various alternatives and modifications thereof. It is intended that the scope of the present disclosure be defined by the Claims appended hereto and their equivalents.

Claims

1. A method of a transmitting user equipment (UE), the method comprising: receiving, from a base station, configuration information of resource sensing/selection window; determining paging (P) candidate resources by performing a resource sensing operation within a P resource sensing window indicated by the configuration information; selecting a P transmission resource from among the P candidate resources within a P resource selection window indicated by the configuration information, wherein the P resource sensing window is early terminated when the resource sensing operation is completed before an end time of the P resource sensing window; and transmitting a paging message to a receiving UE using the P transmission resource, wherein the P resource sensing window is a resource sensing window configured for transmission of the paging message, and the P resource selection window is a resource selection window configured for transmission of the paging message.

2. The method of claim 1, further including: determining data (D) candidate resources by performing a resource sensing operation within a D resource sensing window indicated by the configuration information; selecting a D transmission resource from among the D candidate resources within a D resource selection window indicated by the configuration information; and transmitting data to the receiving UE using the D transmission resource, wherein the D resource sensing window is a resource sensing window configured for transmission of the data, and the D resource selection window is a resource selection window configured for transmission of the data.

3. The method of claim 2, wherein the P resource sensing window is configured independently of the D resource sensing window, and the P resource selection window is configured independently of the D resource selection window.

4. The method of claim 2, wherein the configuration information includes time resource information of the P resource sensing window, time resource information of the P resource selection window, time resource information of the D resource sensing window, and time resource information of the D resource selection window.

5. The method of claim 2, wherein a first window interval is configured between the P resource sensing window and the P resource selection window, a second window interval is configured between the P resource selection window and the D resource sensing window, a third window interval is configured between the D resource sensing window and the D resource selection window, and time resource information of the first window interval, the second window interval, and the third window interval is included in the configuration information.

6. The method of claim 1, wherein the configuration information is configured for each resource

pool, and one or more configuration information for resource sensing/selection window are configured for one resource pool.

7. The method of claim 1, wherein when the resource sensing operation is completed before a reference time configured by the base station, the P resource sensing window is early terminated.

8. The method of claim 1, wherein the P resource selection window starts at an early termination time of the P resource sensing window or at a time after a window interval from the early termination time of the P resource sensing window.

9. The method of claim 1, wherein the P resource sensing window is early terminated when one or more conditions are satisfied, and the one or more conditions are determined based on at least one of a size of transmission data, a required latency, a priority per data, or a priority per sidelink service.

10. The method of claim 1, wherein when an early termination operation for the P resource sensing window is enabled by the base station, the P resource selection window is early terminated.

11. A method of a transmitting user equipment (UE), the method comprising: receiving, from a base station, configuration information of resource sensing/selection window; determining paging (P) candidate resources by performing a resource sensing operation within a P resource sensing/selection window indicated by the configuration information; selecting a P transmission resource from among the P candidate resources within the P resource sensing/selection window, wherein the P resource sensing window is early terminated when the resource sensing operation is completed before an end time of the P resource sensing window; and transmitting a paging message to a receiving UE using the P transmission resource.

12. The method of claim 11, wherein the determining of the P candidate resources includes: reconfiguring the P resource sensing/selection window when the resource sensing operation is not completed within a first reference time in the P resource sensing/selection window; and determining the P candidate resources by performing the resource sensing operation within the reconfigured P resource sensing/selection window, wherein the P transmission resource is selected within the reconfigured P resource sensing/selection window.

13. The method of claim 12, wherein the first reference time is configured by the base station, and the first reference time is indicated by an offset from a start time of the P resource sensing/selection window.

14. The method of claim 12, wherein the reconfigured P resource sensing/selection window starts from the first reference time or from a time after an offset configured by the base station from the first reference time.

15. The method of claim 11, further including: determining data (D) candidate resources by performing a resource sensing operation within a D resource sensing/selection window indicated by the configuration information; selecting a D transmission resource from among the D candidate resources within the D resource sensing/selection window; and transmitting data to the receiving UE using the D transmission resource.

16. The method of claim 15, wherein the P resource sensing/selection window is configured independently of the D resource sensing/selection window.

17. The method of claim 15, wherein the configuration information includes time resource information of the P resource sensing/selection window and time resource information of the D resource sensing/selection window.

18. The method of claim 15, wherein the determining of the D candidate resources includes: reconfiguring the D resource sensing/selection window when the resource sensing operation is not completed within a second reference time in the D resource sensing/selection window; and determining the D candidate resources by performing the resource sensing operation within the reconfigured D resource sensing/selection window.

19. The method of claim 18, wherein the second reference time is configured by the base station, the second reference time is indicated by an offset from a start time of the D resource

sensing/selection window, and the reconfigured D resource sensing/selection starts from the second reference time or a time after an offset configured by the base station from the second reference time.
