

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250281927

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Kelly; John et al.

INTEGRATED FLUID MODULE AND TEST DEVICE

Abstract

An integrated testing device and fluid module are disclosed, as well as a method of manufacture. Fluid module contains a reservoir containing a test fluid, and a control vessel. The reservoir discharges test fluid into the control vessel, which discharges the test fluid in a controlled way to a test component.

Inventors: Kelly; John (Sydney, AU), Wallis; Huw (Sydney, AU), Bocchicchio; Keith (Sydney, AU), Yan Kong; Shing (Sydney, AU)

Applicant: ATOMO DIAGNOSTICS PTY LIMITED (Sydney, AU)

Family ID: 62108999

Assignee: ATOMO DIAGNOSTICS PTY LIMITED (Sydney, AU)

Appl. No.: 19/088293

Filed: March 24, 2025

Foreign Application Priority Data

AU	2016904609	Nov. 11, 2016
WO	PCT/AU2016/051134	Nov. 21, 2016

Related U.S. Application Data

parent US continuation 18138532 20230424 parent-grant-document US 12257578 child US 19088293

parent US division 16348979 20190510 parent-grant-document US 11633733 child US 18138532

Publication Classification

Int. Cl.: B01L3/00 (20060101); **A61B5/151** (20060101); **A61B5/157** (20060101); **B29C65/00** (20060101); **B29C65/18** (20060101); **B29K623/00** (20060101); **B29L31/00** (20060101)

U.S. Cl.:

CPC B01L3/502715 (20130101); **B01L3/502707** (20130101); **B29C65/18** (20130101); **B29C66/72321** (20130101); **A61B5/15144** (20130101); **A61B5/157** (20130101); **A61B2562/0295** (20130101); **B01L2200/027** (20130101); **B01L2200/0605** (20130101); **B01L2200/0684** (20130101); **B01L2300/0887** (20130101); **B29K2623/06** (20130101); **B29L2031/753** (20130101)

Background/Summary

CROSS-REFERENCE TO RELATED APPLICATION(S) [0001] This application is a continuation of U.S. patent application Ser. No. 18/138,532, entitled INTEGRATED FLUID MODULE AND TEST DEVICE, filed on Apr. 24, 2023, which is a divisional of U.S. patent application Ser. No. 16/348,979, entitled INTEGRATED FLUID MODULE AND TEST DEVICE, filed on May 10, 2019, which claims priority to International Patent Application No. PCT/AU2016/051134, filed on Nov. 21, 2016, which claims priority to Australian Patent Application No. 2016904609, filed on Nov. 11, 2016, the entirety of which is incorporated herein by reference.

TECHNICAL FIELD

[0002] The present invention relates to devices and methods for providing tests which require a test fluid, and to devices and packages which facilitate such testing.

BACKGROUND OF THE INVENTION

[0003] Various kinds of tests, for example medical tests, assays and industrial tests, are performed which enable a relatively rapid outcome to be obtained at the point of testing. These may be, for example, home tests, point of care tests, or used in laboratories, pathology clinics or hospitals.

[0004] Performing these relatively rapid tests can require complicated instructions and multiple devices and components to be used. The present invention is not concerned with the specific chemical or biochemical tests to be performed, but rather with the devices, fluid delivery and associated mechanical systems which house and contain the test components. For example, in a medical context, such devices and systems may be used with a lateral flow or other type of rapid test.

[0005] In a typical conventional home or point of care blood test, for example, the user is presented with a collection of components, including the test device itself, a separate lancet, blood collection receptacles, a container of buffer or other test fluid, an adhesive bandage, cleaning wipes, and possibly further components. The user is expected to follow a very precise sequence of steps, typically including cleaning the site, operating the lancet, obtaining a blood sample of a known volume and delivering it to the precise place required, applying a buffer solution at the right time and place and at the correct volume and rate, reading the test result and interpreting the outcome.

[0006] Many tests are performed either as infrequent or one off procedures, so that the user does not become proficient through regular use. Procedures performed at point of care are carried out generally by skilled operators, but again the complexity and dexterity required to carry out the test accurately presents a challenge and specific tests may be performed infrequently. In such situations it would be advantageous if the test device could better facilitate simple, reliable and accurate operation.

[0007] In PCT application numbers PCT/AU2011/000315 and PCT/AU2011/022321, the disclosures of which are incorporated by reference herein, the present applicant has disclosed

integrated testing devices. In particular, those devices may include a reservoir or sachet of a physiologically acceptable fluid, such as a buffer. For many tests, for example certain blood tests, it is required that a buffer or other reagent is applied to the test material after the blood sample, in order to achieve a valid result or to achieve the result within an acceptable timeframe. The devices disclosed in embodiments of these disclosures permit the user to discharge a fluid, illustratively a buffer, from the internal reservoir onto the test material.

[0008] PCT publication No. WO2015075677, the disclosure of which is hereby incorporated by reference, discloses test devices and methods, in which a reservoir within the test device discharges into a control vessel, so that the rate of delivery of fluid to a test material is controlled.

[0009] It is an object of the present invention to provide a test device, fluid delivery module and method which improve the delivery of fluids to a test material.

SUMMARY OF THE INVENTION

[0010] In a broad form, the present invention provides an integrated package for delivering a test fluid, and a process for forming such a package.

[0011] According to one aspect, the present invention provides a process for forming a liquid filled reservoir with a frangible seal, the frangible seal being across a fluid conduit extending from a liquid filled reservoir, the process including the steps of: forming a reservoir body; filling the reservoir body with a liquid; positioning a base component on the reservoir body and using a set of first tools to heat seal the base component to the reservoir body, so as to create a fluid tight seal around the reservoir body, apart from a conduit; and using a set of second tools to heat seal across the conduit, wherein the heat applied by the second tool creates a frangible seal across the conduit.

[0012] The invention further includes a fluid filled module formed by the above process.

[0013] According to another aspect, the present invention provides An integrated testing device including: a test component; a test fluid module, including a reservoir containing a test fluid, a delivery vessel, and a conduit connecting the reservoir and the delivery vessel; and a fluid delivery actuator, wherein operation of the fluid delivery actuator causes the test fluid to be released from the reservoir into the delivery vessel, the delivery vessel being adapted to provide a controlled discharge of test fluid onto the test component.

[0014] According to a further aspect, the present invention provides a method for delivered a test fluid for an integrated test, including at least the steps of: providing a test unit including a test component, a fluid module having a reservoir containing a test fluid, a delivery vessel, and a conduit connecting the reservoir and the delivery vessel, and a fluid delivery actuator; operating the fluid delivery actuator and thereby exerting a pressure on the reservoir; releasing the fluid into the delivery vessel as a result of the pressure on the reservoir; thereby providing a controlled release of fluid from the delivery vessel onto the test component.

[0015] Implementations of the present invention can also, allow for different rates of release, simply by varying the size and/or shape of the opening in the vessel. The fluid may be released directly from the control vessel onto the test component, or via a conduit or channel.

[0016] The term ‘controlled discharge’ throughout the description and claims refers to releasing the fluid from the vessel in a way which is more controlled in flow rate than simply releasing the full contents of the sachet in a single burst. It may, in one form, merely amount to slowing down the rate of flow. It may in other forms more closely control the rate of discharge and adapt it closely to the requirements of the test. In many forms, the discharge rate will not be constant.

[0017] Implementations of the present invention accordingly allow for a convenient, accurate and practical fluid delivery module, for use in integrated testing and in other applications.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0018] Illustrative embodiments of the present invention will now be described with reference to the accompanying drawings, in which:

[0019] FIG. **1** shows an isometric view of an implementation of the present invention, without the lancet activated;

[0020] FIG. **2** is a view in section of an implementation in a first position;

[0021] FIG. **3** is a view in section of an implementation in a second position;

[0022] FIG. **4** is a view in section of an implementation in a third position;

[0023] FIG. **5** is an isometric view of a blood collection arm according to one implementation;

[0024] FIG. **6** is a plan view, with the upper section removed, of the implementation of FIG. **1**;

[0025] FIG. **6A** illustrates the situation after the depressible portion has been actuated;

[0026] FIGS. **7A**, **7B** and **7C** are detailed sections illustrating fluid movement within an implementation of the device;

[0027] FIG. **8** illustrates an implementation of the package in a filled state;

[0028] FIG. **9** illustrates an implementation of the package in an emptied state;

[0029] FIG. **10** is a detailed view illustrating the relationship between the well and the test strip in one implementation;

[0030] FIG. **11** illustrates the components of an implementation of the package;

[0031] FIG. **12** illustrates a first stage in production of an implementation of a package;

[0032] FIG. **13** illustrates the unsealed area resulting from FIG. **12**;

[0033] FIG. **14** illustrates a second stage in the production of an implementation of a package;

[0034] FIG. **15** illustrates notional tools for heat sealing the implementation of FIG. **12** in the first stage of sealing;

[0035] FIG. **16** illustrates notional tools for heat sealing the implementation of FIG. **14** in the second stage of production; and

[0036] FIGS. **17A**, **17B**, **17C** illustrate the interlock mechanism according to one implementation of the present invention; and

[0037] FIGS. **18A**, **18B** and **18C** are sectional views illustrating the formation of the frangible seal.

DETAILED DESCRIPTION OF THE INVENTION

[0038] The present invention will be described with reference to a number of possible embodiments. It will be appreciated that the present invention is capable of being implemented in numerous ways, in addition to the examples provided. The embodiments are intended as illustrative, and are in no way limitative of the inventive concept or its possible implementations. Further, it will be understood that the features of different embodiments may be formed into different combinations, or added together, in order to provide further implementations of the present invention.

[0039] The present invention is principally concerned with a specific aspect of the operation of a test device, relating to the discharge of a fluid which is intended to contact the test material, and to the manufacture and construction for a module for discharging a test fluid. Accordingly, while specific examples of the remaining mechanical structures of a test unit will be provided and described, it will be understood that in principle the present invention can be used with any design of such a test unit. In particular, known test units, as well as those disclosed in the specifications incorporated by reference, may be modified so as to incorporate implementations of the present invention.

[0040] Whilst the invention will be principally described with reference to a medical application, it will be appreciated that the present invention can be applied to many other forms of industrial or laboratory tests, in which a test fluid must be added to a test material, or test sample, prior to a result being determined. Other examples of possible applications include environmental testing, biosecurity, food safety, testing for illicit drugs, and veterinary medicine.

[0041] FIGS. 1 and 2 illustrate one implementation of the present invention, in cross section in FIG. 2. The test unit **10** includes a cover **15**, which includes a depressible portion **26** for releasing the test fluid **41**. Test fluid **41** is contained in a package **40**. Test unit **10** further includes an arm **25** with a collection device **28** for a bodily fluid, in this case blood. Test unit **10** also has an opening **20** for a blood sample to be received, and an indicator opening **21**, through which the result of the test can be seen.

[0042] Package **40** includes a fluid reservoir **43** containing test fluid **41**, a frangible seal **55**, and a well **50**.

[0043] As will be described in more detail below, in use, the operator according to this embodiment operates lancet **30** to release blood from a suitable site on the body, for example a finger. In this implementation lancet **30** is integrated with the unit, although in other implementations it could be a separately supplied device. Lancet **30** is spring loaded and once actuated will penetrate the user's finger. The user may need to milk the blood from the lanced site in order to provide a sufficient sample

[0044] In FIG. 2, lancet **30** is ready for use, once the cover **31** is removed. In FIG. 3, lancet **30** has been operated and is then withdrawn within body **10** (for safety). The device is now ready for collection of blood. Collection device **28** is placed onto the exuded blood, and withdraws (in this case by capillary action) a sample. Other sample collection arrangements may be used in alternative implementations, for example a non-integral suction or capillary device, or direct placement of the fluid onto the test material **60**. In the illustrated arrangement, collection device **28** will retain only the required volume of blood.

[0045] After the collecting device is filled, the arm **25** may then be rotated (as will be described in more detail below) into a delivery position. The collection device is then in contact, via opening **20**, with test material **60**, and the sample is discharged onto test material **60**. This is shown in FIG. 4.

[0046] The user may then depress section **26**, which applies a force to package **40** so that the pressure in fluid reservoir **43** is increased sufficiently that frangible seal **55** fails and allows test fluid **41** to be released and flow into well **50**. Well **50** has one or more openings (not shown in these views) which allow test fluid **41** to discharge at a controlled rate onto test material **60**.

[0047] It is emphasised that the present invention can be applied to any kind of test, in to control the rate of test fluid introduction to the test material. In this case, the test is illustratively a lateral flow test. However, any other desired type of desired type of immunoassay, chromatographic assay, DNA assay, enzymatic assay, or other test may be used. The test may be an or use an electronic, optical or other sensor, as well as or in place of the lateral flow or similar test. The test may be read by the operator, or interpreted with an electronic or other automated system. Similarly, the test fluid may be water, a buffer solution, or any other required fluid to conduct, support or be otherwise used in conjunction with the test.

[0048] It is in other implementations, the fluid may mix with the sample to be tested prior to introduction to the test material. It will equally be understood that while the implementations illustrated show the uses of a single package. In other implementations multiple packages may be present, for example to perform multiple tests in a single unit. In yet other implementations, the package may discharge from the well onto more than one test material, for example using separate discharge openings.

[0049] FIG. 5 illustrates in more detail the arm **25** and associated structures. In the illustrated implementation, the arm **25** operates as an interlock to prevent the delivery of test fluid **41** onto test material **60** until the arm **25** has rotated into the delivery position.

[0050] In FIG. 5, cams **32**, **32A** can be seen. The rotational position of cams **32**, **32A** determines whether the fluid in the reservoir can be released, via engagements with corresponding parts of the depressible portion **26**.

[0051] In FIG. 17A, the lancet **30** is in a rest position, and so no blood has yet been drawn. Projection **33** on depressible portion **26** is engaged by cam **32**, and cannot move downwards. In

FIG. 17B, the lancet **30** has been engaged and operated, and has moved to a safe rest position **31**. Blood can now be collected in collection device **28**. Cam **32** still blocks projection **33**.

[0052] In FIG. 17C, arm **25** has been rotated, so that blood can be deposited onto the test material **60** via opening **20**. Cam **32** has now rotated so that recess **34** is located adjacent projection **33**, and the depressible portion **26** can now be moved downward, so as to exert pressure on package **40** and release the fluid (not shown in this view). Thus, cam **32** acts as an interlock to prevent premature release of the test fluid. It will be appreciated that other mechanical system could be used to achieve this. Examples of such mechanisms are provided in the applicant's patent applications referenced above. In many cases, the timing of the delivery of the fluid is critical to a proper result, and premature release will invalidate the test.

[0053] The operation of the overall system, and its discharge, can be better understood from FIG. 6 and FIGS. 7A, 7B and 7C. FIG. 6 is a plan view, partly in section, so that the arrangement of the components in the fluid flow path can be better understood. Package **40** can be seen, the fluid reservoir **43** containing test fluid **41**. Fluid reservoir **43** connects to well **50** through discharge conduit **52**, which is initially blocked by frangible seal **55**. When sufficient force is applied by depressible portion **26** to fluid reservoir **43**, the frangible seal fails, fluid flows through the discharge conduit **52** into well **50**. Well **50** includes a outlet **51**. In this implementation, outlet **51** discharges directly onto area **61** of the test material **60**. Referring to FIG. 4, it can be seen that the buffer is in this implementation discharged at point **61** so that it will pass through the area **62** where the blood sample has been deposited, so as to facilitate the test. However, it will be appreciated that by suitable relative positioning, different ordering and positioning of the test fluid and sample may be provided.

[0054] FIGS. 7A, 7B and 7C illustrate in more detail the sequence of test fluid discharge in the illustrative device.

[0055] In FIG. 7A, the fluid delivery reservoir **43** contains the test fluid **41** and has yet to be discharged by pressure from depressible portion **26**. This is the condition in which the test device is supplied, and in this state, test fluid **41** is completely sealed by frangible seal **55** within the fluid delivery reservoir, thereby maintaining a desired composition and condition of the test fluid.

[0056] In FIG. 7B, depressible portion **26** has been depressed, so that the fluid reservoir **43** has been effectively emptied through conduit **52** and test fluid **41** is being discharged (as illustrated by the arrow **57**) into well **50**. Well **50** is directly engaged with test material **60** at area **61**. It will be appreciated that in other implementations, different fluid flow paths and geometry could be employed.

[0057] However, it has been determined by the inventors that using a direct discharge and minimising the intervening fluid paths minimises the volume of fluid which remains in the fluid path, through surface effects, surface tension, and other fluidic adherence to the surfaces in the fluid path. Whilst this is not essential, minimising these losses permits a more accurate volume of test fluid to be delivered, and minuses waste.

[0058] In FIG. 7C, the test fluid **41** is discharging in a controlled way through opening **51** onto test component **60**. Thus, test fluid **41** is discharged in a measured, controlled way onto test component **60** and not in an uncontained rush. Thus, well **50** acts as a control vessel, and allows for the rate of flow of test fluid **41** to be controlled.

[0059] It will be understood that while the fluid will discharge over time, it will not necessarily be at a constant rate. The rate will be determined in part by the sizes of the opening (or openings) in the well, as well as the absorption by the test material. Flow may slow as more or most of the fluid has left the vessel, for example.

[0060] It has been determined by the inventors in preferred implementations, it is advantageous for the volume of the well to be smaller than the than the volume of the fluid reservoir. This allows of the depression of the depressible portion **26** to exert force over a period of time, so as to provide a positive pressure from the fluid **41** in the fluid reservoir **43**, through well **50**, outlet **51**, and into the

test material at area **61**. This in turn provides for a consistent flow of test fluid **41** into the test material **60**. This also more positively forces the fluid into the test material. Test material **60** in this implementation draws test fluid **41** into and along the test material **60**, by capillary action, so that further fluid can be drawn in from well **50** and ultimately from reservoir **43**.

[0061] It will also be understood that the fluid should contact the test material as directly as possible, and that it is desirable that the volume of test fluid **41** can be controlled to provide consistent delivery volumes, as well as a consistent and correct total volume delivered. This is facilitated by the volume of well **50** being smaller than the volume of reservoir **43**. As will be described in more detail below with reference to FIG. **11**, a vent opening **111** is advantageously provided in the seal over well **50**, **102**. If no vent is provided, air cannot enter to replace the test fluid **41** as it is dispensed onto test material **60**. This in turn may create a pressure lock, preventing or impeding the passage of test fluid **41** onto test material **60**, or fluid delivered outside of the test material due to pressure build up behind the delivered fluid, exiting the well.

[0062] Vent opening **111** also assists in another respect. In some circumstances the user may apply pressure sufficient to excessively compress reservoir **43**. This can then result in an uncontrolled rapid burst of fluid ‘exploding’ inside teste unit **10**, so the fluid is delivered to the interior in general and not in the desired controlled way to the test material **60**. Vent opening **111** in this case provides a way for excess fluid pressure to vent, without the whole fluid reservoir **43** failing.

[0063] To facilitate the flow, it is advantageous that there is a good fluid engagement between the outlet **51** and area **62**. If the engagement is loose, then test fluid **41** may be discharged within the device but not on test material which is undesirable.

[0064] In this implementation, a further feature is that an interlock is provide between the depressible portion **26** and the test unit, so that once actuated the depressible portion stays in the depressed position and the reservoir **43** compressed.

[0065] Referring first to FIG. **4**, the test strip unit **10** incudes a front projection **36**. This is located just in front of the depressible portion **26**. Depressible portion **26** also includes a lower projection **37** with a foot **38** at the base, and angled face **39**.

[0066] FIG. **6A** illustrates the situation after the depressible portion **26** has been actuated. The fluid has been forced, or is in the process of being forced, from reservoir **43** into well **50**. Foot **38** has been forced past the top edge of projection **36**, and projection **36** now engages angled face **39**. Thus, depressible portion **26** is now retained in the depressed state, thereby maintaining pressure on reservoir **43**. This retention also prevents any chance that fluid could return into the reservoir, or that the force to maintain pressure on the reservoir and hence force fluid through well **50** and into test material **60** will not be maintained. As such, this interlock feature assists in ensuring controlled delivery of fluid to the test material **60**.

[0067] Further, it is desirable that there be as little air within the fluid reservoir as possible. This allows for the force applied by the user via depressible portion **26** to act directly on the test fluid, when depressible portion **26** is engaged, rather than first compressing air within the package **40**. Reducing the air content inside the sealed reservoir **43** reduces the burst force which the use needs to apply to release test fluid **41**. A smaller burst force is desirable from a usability perspective, as it is easier for the user to operate and control. A larger burst force means that the user has to press harder which may be physically difficult in some cases, as well as increasing the risk of inadvertent damage to the test unit, or uncontrolled test fluid discharge due to excessive force, This similarly allows for more reliable operation of the package, and thus the overall device.

[0068] The fluid in the sachet may be any kind of fluid necessary or desired to perform, assist or validate the test. It will be appreciated that the fluid may have different properties, for example density, viscosity and surface tension, and that appropriate changes to the package may need to be made. The present invention is concerned with how the fluid is delivered, and is applicable to any desired fluid for use with a test.

[0069] The test material may be, illustratively, a lateral flow test for a component of blood,

electrolyte, blood sugar, cholesterol or any other blood component. It may be adapted to detect specific biological or immunological responses, for example the presence of a pathogen or antibodies to a pathogen. Any kind of test on a body fluid which is suitable for this type of test unit can be used. The present invention is not specific to any type or form of test material, whether of lateral flow type or otherwise. Similarly, it is not constrained to blood, but could be applied to tests on any suitable bodily fluid, for example urine, interstitial fluid, faeces, or sputum, whether directly applied to the test unit or after pre-processing. The present invention may be applied also to other chemical and biochemical tests, for example in industrial, laboratory or other applications.

[0070] It will be appreciated that the specific dimensions, shapes and parameters will need to be determined, in part by trial and error, for specific applications. The required volume of fluid will determine the size of the fluid reservoir. The properties of the specific fluid, and the required rate of flow will determine the size and nature of the outlets required in the well. The surface properties of the interaction between the specific fluid and the materials over which it will flow also need to be considered. For example, in an aqueous fluid, given the relatively high surface tension, smooth shapes are preferred over corners to ensure a smooth flow of the fluid. The well **50** illustrated is contained wholly within the test unit, however, it will be appreciated that this could be partly open if desired. The required flow rate and volume are specific to the particular test material being used, and will generally be advised by the test material manufacturer.

[0071] FIG. **8** illustrates one form of package **40** according to the present invention. It includes reservoir **43**, containing test fluid **41**, connected by conduit **52** to well **50**. In FIG. **8**, the package **40** is filled with test fluid. As can be seen in the sectional view, there is little or no air within reservoir **43**. Frangible seal **55** provides a seal for reservoir **43**, until such time as fluid release is required.

[0072] FIG. **9** illustrates the device of FIG. **8**, after the test fluid **41** has been discharged into the well **50**. Hence, reservoir **43** has now been substantially emptied. Force applied to reservoir **43** has raised the pressure in the test fluid **41** so that frangible seal **55** has failed, and test fluid **41** has passed through conduit **52** into well **50**. Fluid **41** is then discharged at a controlled rate from well **50**, as can be seen from the arrows in FIG. **9**. It is noted that for clarity, the perspective view is upside down relative to the sectional view.

[0073] FIG. **10** illustrates only the package **40** and well **50**, relative to test strip **60**. The direct engagement of well **50** with test strip ensures that test fluid **41** is discharged onto the required location **61**, with a minimal risk of fluid loss.

[0074] FIG. **11** illustrates the components of a package prior to assembly according to one implementation of the present invention. The empty blank parts to form the upper seal **117** and body **110** of the package are shown. Prior to sealing, the reservoir recess **101** must be filled with the required test fluid **41** (not shown in this and following views for clarity). The well structure **102** and vent opening **111** are also visible.

[0075] It will be understood that the sachet or reservoir may be provided using any suitable technology. However, the following discussion relates to formation of package **40** using a heat sealing approach using multilayer materials.

[0076] The package may be formed from any suitable material. It will be appreciated that the material must be compatible with the fluid, and be inert with respect to the fluid. A heat sealed foil polymer is preferred. The polymer provides heat sealing, and the foil layer assists with protection and conservation of the fluid. It will be appreciated that in the present application fluid volumes are small, and high impermeability of the packaging is important for shelf life and retention of appropriate fluid properties.

[0077] For aqueous buffer solutions, a suitable material for the top seal is a peelable foil laminate, product code RFA 037, available commercially from Amcor Flexibles. This is a heat sealable material with layers of PET, adhesive, aluminium, and polyethylene. The material has a nominal thickness of about 60 μm .

[0078] A suitable material for the base (reservoir and well) is a cold formable laminate Formpak 3-

ply, product code 13355, available from Amcor Flexibles. This is a cold formable material with layers of aluminium, OPA and PE, with a nominal thickness of about 100 μm .

[0079] The following discussion relates particularly to the application of the present invention to packages containing a small fluid volume, typically in the range of about 50 to 250 μl , and typically about 200 μl .

[0080] In general terms, the preferred manufacturing process is to form the upper seal **117** and body **110** from suitable material, then to heat seal them together, and form the frangible seal **121** by a secondary heat sealed section. It has been determined that it is impractical to do this using a single process. The frangible seal must have a well-controlled strength. The preferred material for the body **110** includes a foil layer, which has been found to conduct heat beyond the desired confines of the seal. As a result, this approach does not produce a well formed seal.

[0081] The inventors have adopted a preferred two stage manufacturing process. In this process, a perimeter seal is first formed, identified as **120** in FIG. **12**. This does not seal the frangible seal, but rather the external periphery of the package **110**. As can be more clearly seen in FIG. **13**, region **103**, which will form the fluid conduit and seal in the finished product, are not sealed. In a second stage, a relatively narrow secondary seal **121** is formed, as illustrated in FIG. **14**.

[0082] A further aspect has been identified by the inventors. Even in the two stage process, there is possible heat transfer through the foil, so that some degree of sealing occurs in the conduit region. This is largely because it is very narrow, and the distance from the heated tool to the area which is not desired for sealing in the first stage is small. It is important that heat transfer is prevented between the top and bottom layers in the first stage in order to achieve a reliable seal in the second stage. If the conduit area is sealed in the first stage, the quality of the seal and its parameters cannot be properly controlled, and hence the burst force of the seal cannot be reliably controlled or predicted. This is addressed by two separate improvements.

[0083] It will be appreciated that a seal can only be created between the top and bottom layers if they are in contact, and heated. Heat causes activation of the sealing layer, in this example a PE layer, and thus potentially creates an uncontrolled seal.

[0084] In one aspect, the conduit area is formed with a larger curvature, so that the surfaces around the conduit are not in contact and so less liable to unwanted heat transfer which may cause sealing of the conduit area. It will be understood that in alternative designs, the modifications to the shape of the conduit could be to the seal, body, or both.

[0085] In a second aspect, the tool is formed not merely with an opening around the conduit part, but with an open section, so as to further reduce the unwanted heat transferred by conduction or radiation to the conduit section to eliminate any sealing of the conduit area. This cooperates with the physical gap between the layers created by the first aspect, to effectively remove the possibility of heat transfer while the layers are in contact, and hence prevents sealing of the conduit in the first stage.

[0086] This can be seen in FIG. **15**. It will be appreciated that the external dimensions of the tool will be dictated by the machine with which it is designed to be used, and so these are shown purely in a schematic way. It will further be appreciated that while a single cavity is shown, multi-cavity tools may be used following the general principles outlined.

[0087] The components of package **110** (the seal is not readily visible, but is of course present) are positioned so that upper tool **130** and power tool **131** are able to be moved into an operative position, generally abutting the package **110**. It can be seen that the upper tool includes a recess **132** which defines the non-sealed area, and that this recess is open **134** at the top. A similar arrangement is present in recess **133** in lower tool **131**. Thus, these tools cooperate to move into contact, heat the material of the package components, and produce a seal such as is shown in FIGS. **12** and **13**. That is, the frangible seal **121** has not been formed.

[0088] FIG. **16** illustrates the second stage in manufacture of the package according to this implementation. Upper tool **140** and lower tool **141** include respective blade type portions **142**,

143. When there are moved into position, they form a relatively narrow seal by heat sealing the respective portions of the package, so as to provide frangible seal **121**.

[0089] It will be appreciated that while the package, and its sub-components, have been illustrated having a particular shape which is operable with the mechanical systems described, for different systems and applications it would be expected that the shapes, volumes, sizes, and so forth would vary to suit the particular actuation arrangements for the package.

[0090] FIGS. **18A**, **18B** and **18C** illustrate the stages of sealing discussed above, using a longitudinal cross-section. In FIG. **18B**, the reservoir **40** and well **50** can be seen, before fluid is added to reservoir **41**. A discharge conduit **52** is defined between layers **52A**, **52B**, which as discussed above in use will facilitate fluid transfer to well **50**.

[0091] In FIG. **18B**, fluid has been added, and the peripheral seal has been completed, but conduit **52** remains open and the surfaces **52A** and **52B** remain separated. In FIG. **18C**, frangible seal **55** has been formed by the blades **142**, **143** (not visible in this view). Thus, the layers **52A**, **52B** are forced together and the seal formed as part of the same process step.

[0092] This implementation accordingly allows for the rate of delivery of a test fluid to be closely controlled. The fluid is first released into the well. The size, number, and shape of the outlets, as well as the shape of the well, will determine the rate (whether variable or constant) at which the fluid is released. The interaction with the rest of the package, the pressure applied by the depressible portion, and the overall fluid flow path will influence the flow rate. For example, if the outlets are relatively small, the fluid will be released over a longer time period. The combination of controlling the volume of the fluid, and its fluid path, allows for relatively accurate control of the delivery of the fluid, and further ensures that it is delivered to the correct point on the test material.

[0093] The present invention may be implemented in ways that do not incorporate all of the preferred features noted in relation to the implementation above. The various aspects of the invention described have advantages without incorporating all the components of the described implementations. For instance, the sample of blood or other fluid could be placed directly into a suitable recess or opening in the test unit, without using the sample delivery arm or another mechanism. The package may be inserted by a user into the test unit rather than being integral.

[0094] It will be understood that the illustrative embodiments are only provided by way of example, and many other structures could be used to implement the invention. For example, the package described could be utilised with different mechanical structures than those described, and used for completely different applications to those discussed.

Claims

1. An integrated testing device including: a test component; a test fluid module, including a reservoir containing a test fluid, a conduit, and a frangible seal between the reservoir and the conduit; and a fluid delivery actuator, wherein operation of the fluid delivery actuator causes the pressure to increase in the reservoir, and the frangible seal to adapted to open under sufficient pressure to allow fluid to pass from the reservoir to the conduit, so as to provide a controlled discharge of test fluid from the reservoir through the conduit and onto the test component.
2. An integrated testing device according to claim 1, wherein the fluid delivery actuator includes a first interlock, so that once actuated the delivery actuator remains in the actuated position.
3. An integrated testing device according to claim 2, wherein the fluid actuator exerts a force on the reservoir, so as to provide pressure to control the release of test fluid, and the first interlock is operative to maintain the force until the fluid has been discharged from the reservoir.
4. An integrated testing device according to claim 1, wherein the test fluid module and conduit are formed as an integral unit.
5. An integrated testing device according to claim 4, wherein the conduit includes a delivery vessel to operatively control the flow of fluid.

- 6.** An integrated testing device according to claim 5, wherein the delivery vessel includes one or more outlets which operatively discharge onto the test component.
- 7.** An integrated testing device according to claim 6, wherein the one or more outlets discharge directly onto the test component.
- 8.** An integrated testing device according to claim 5, wherein the discharge vessel includes an orifice separate from said outlets to permit venting and air intake.
- 9.** An integrated testing device according to claim 6, wherein the outlets are closely engaged with the test component.
- 10.** An integrated testing device according to claim 5, wherein the volume of the reservoir is larger than the volume of the delivery vessel.
- 11.** A integrated testing device according to claim 1, wherein during the discharge of the test fluid into the delivery vessel, a back pressure from the engagement with the test material improves control of the liquid delivery to the test material.
- 12.** An integrated testing device according to claim 1, wherein the device includes a second interlock to prevent premature discharge of the test fluid.
-