

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication	20250284221
Kind Code	A1
Publication Date	September 11, 2025
Inventor(s)	Tanaka; Chihiro

DEVELOPING DEVICE

Abstract

A developing device includes a first rotatable member to which developer is delivered, a second rotatable member provided opposed to the first rotatable member, to which the developer is delivered from the first rotatable member by a magnetic field generated by a first magnet, to carry and feed the developer, and a third rotatable member provided opposed to the second rotatable member, to which the developer is delivered from the second rotatable member. A guiding portion is provided opposed to the second and third rotatable members to guide the developer peeled off from the third rotatable member by a repelling magnetic field generated by a third magnet. Where a shortest distance between the second rotatable member and the guiding portion is B [μm], and a shortest distance between the third rotatable member and the guiding portion is C [μm], the following relationship is satisfied: $B+100\ \mu\text{m}\leq C$.

Inventors:	Tanaka; Chihiro (Chiba, JP)
Applicant:	CANON KABUSHIKI KAISHA (Tokyo, JP)
Family ID:	1000008621073
Appl. No.:	19/217086
Filed:	May 23, 2025

Foreign Application Priority Data

JP	2023-020080	Feb. 13, 2023
JP	2024-003031	Jan. 12, 2024

Related U.S. Application Data

parent US continuation 18418570 20240122 parent-grant-document US 12339598 child US 19217086

Publication Classification

Int. Cl.: G03G15/08 (20060101)

U.S. Cl.:

CPC G03G15/0812 (20130101); G03G15/0891 (20130101); G03G2215/0648 (20130101)

Background/Summary

FIELD OF THE INVENTION AND RELATED ART

[0001] The present invention relates to a developing device for developing an electrostatic latent image, formed on an image bearing member, with a developer.

[0002] As the developing device, a constitution in which two developing rollers for developing the electrostatic latent image, formed on the image bearing member, with the developer are arranged side by side is proposed (Japanese Laid-Open Patent Application (JP-A) No. 2013-254107). The developing device disclosed in JP-A 2013-254107, of the two developing rollers, to a first developing roller positioned at a lower portion in the vertical direction, the developer is supplied from a supplying portion, and to a second developing roller positioned at an upper portion in the vertical direction, the developer is delivered from the first developing roller positioned at the lower portion. Then, the developer is peeled off from the second developing roller positioned at the upper portion and then is collected.

[0003] In the case of the constitution disclosed in JP-A 2013-254107, the developer is peeled off from the second developing roller by a peeling roller. Then, the developer peeled off from the second developing roller is dropped by its own weight or delivered to the peeling roller. Here, in a developer delivering step from the second developing roller to the peeling roller, of the developer on the second developing roller, a part of the developer is carried along with an air flow and is dropped on the first developing roller positioned immediately below the second developing roller by the influence of the air flow generated in a gap between the second developing roller and the peeling roller.

[0004] The developer dropped on the first developing roller is a used developer which is used in a developing step by the first developing roller and the second developing roller, and an amount of toner in the developer becomes smaller than an amount of normal toner existing in the supplying portion.

[0005] When such a used developer is dropped on the first developing roller, there is a liability that the developer enters a developer delivering portion positioned in the neighborhood of a closest position between the first developing roller and the second developing roller by the influence of a magnetic force on the first developing roller. When the used developer is delivered again to the second developing roller at the developer delivering portion between the first developing roller and the second developing roller, the developer on the second developing roller becomes a mixture of the normal developer and the used developer in which the amount of the toner is small, and therefore, non-uniformity in amount of the toner moving to the image bearing member when the electrostatic latent image on the image bearing member is developed with the developer occurs, so that density unevenness occurs on a final output image. This phenomenon is referred to as a so-called co-rotation (drag) phenomenon.

[0006] Thus, in the developing device including the two developing rollers as disclosed in JP-A 2013-254107, there is a liability that an image defect such as the density unevenness is liable to occur on the output image. Particularly, in a use condition such that an image forming apparatus is

operated at a high speed, the above-described problem is liable to occur by the influence of temperature rise in the developing device.

SUMMARY OF THE INVENTION

[0007] A principal object of the present invention is to provide a developing device capable of suppressing an occurrence of an image defect.

[0008] According to an aspect of the present invention, there is provided a developing device comprising: a first chamber configured to accommodate a developer containing toner and a carrier; a first feeding screw provided in the first chamber and configured to feed the developer in the first chamber; a second chamber partitioned from the first chamber by a partition wall; a second feeding screw provided in the second chamber and configured to feed the developer in the second chamber, the second feeding screw having a rotation center positioned above a rotation center of the first feeding screw in a vertical direction; a first rotatable member to which the developer is supplied from the first chamber and configured to carry and feed the developer for developing an electrostatic latent image formed on an image bearing member; a first magnet fixedly provided inside the first rotatable member; a second rotatable member which is provided opposed to the first rotatable member, to which the developer is delivered from the first rotatable member by a magnetic field generated by the first magnet, and which is configured to carry and feed the developer for developing the electrostatic latent image, the second rotatable member having a rotation center positioned above a rotation center of the first rotatable member in the vertical direction; a second magnet fixedly provided inside the second rotatable member; a third rotatable member which is provided opposed to the second rotatable member, to which the developer is delivered from the second rotatable member by a magnetic field generated by the second magnet, and which is configured to carry and feed the developer for collecting, in the second member, the developer after the electrostatic latent image is developed with the developer, the third rotatable member having a rotation center positioned above the rotation center of the second rotatable member in the vertical direction; a third magnet fixedly provided inside the third rotatable member; and a guiding portion provided opposed to each of the second rotatable member and the third rotatable member and configured to guide the developer, to the second feeding screw, peeled off from the third rotatable member by a repelling magnetic field generated by the third magnet, wherein in a case that a shortest distance between the second rotatable member and the guiding portion is B [μm], and a shortest distance between the third rotatable member and the guiding portion is C [μm], the following relationship is satisfied:

[00001] $B + 100 \cdot \text{Math.m} \leq C$.

[0009] Further features of the present invention will become apparent from the following description of exemplary embodiments with reference to the attached drawings.

Description

BRIEF DESCRIPTION OF THE DRAWINGS

[0010] FIG. 1 is a schematic sectional view of an image forming apparatus according to an embodiment.

[0011] FIG. 2 is a schematic sectional view of a developing device according to the embodiment.

[0012] FIG. 3 is a schematic view showing a magnetic pole arrangement of a first developing roller in the embodiment.

[0013] FIG. 4 is a schematic view showing a magnetic pole arrangement of a second developing roller in the embodiment.

[0014] FIG. 5 is a schematic view showing a magnetic pole arrangement of a peeling roller in the embodiment.

[0015] FIG. 6 is an enlarged view of a periphery of the second developing roller and the peeling

roller in the embodiment.

DESCRIPTION OF THE EMBODIMENTS

[0016] An embodiment will be described using FIGS. **1** to **6**. First, a general structure of an image forming apparatus in the embodiment will be described with reference to FIG. **1**.

[Image Forming Apparatus]

[0017] An image forming apparatus **100** is a full-color image forming apparatus, and in the case of this embodiment, the image forming apparatus **100** is, for example, an MFP (multi-function peripheral) having a copy function, a printer function, and a scan function. The image forming apparatus **100** includes, as shown in FIG. **1**, image forming portions PY, PM, PC, and PK for performing an image forming step of forming toner images of four colors of yellow, magenta, cyan, and black, respectively, which are juxtaposed.

[0018] The image forming portions PY, PM, PC, and PK for the respective colors include primary chargers **21Y**, **21M**, **21C**, and **21K**, developing devices **1Y**, **1M**, **1C**, and **1K**, optical write portions (exposure devices) **22Y**, **22M**, **22C**, and **22K**, photosensitive drums **28Y**, **28M**, **28C**, and **28K**, and a cleaning devices **26Y**, **26M**, **26C**, and **26K**, respectively. Further, the image forming apparatus **100** includes a transfer device **2** and a fixing device **3**. Structures of the image forming portions PY, PM, PC, and PK are similar to each other, and therefore, in the following, description will be described using the image forming portion PY as a representative.

[0019] The photosensitive drum **28Y** as an image bearing member is a photosensitive member, having a photosensitive layer formed of a resin such as polycarbonate, containing an organic photoconductor (OPC), and is constituted so as to be rotated at a predetermined speed. The primary charger **21Y** includes a corona discharge pole disposed at a periphery of the photosensitive drum **28Y** and electrically charges a surface of the photosensitive drum **28Y** by generated ions.

[0020] In the optical write portion **22Y**, a scanning optical device is assembled, and by exposing the charged photosensitive drum **28Y** to light on the basis of image data, a potential of an exposed portion is lowered, so that a charge pattern (electrostatic latent image) corresponding to the image data is formed. The developing device **1Y** develops the electrostatic latent image, formed on the photosensitive drum **28Y**, by transferring a developer accommodated therein onto the photosensitive drum **28Y**. The developer is prepared by mixing a carrier with toner of an associated color, and the electrostatic latent image is visualized (developed) with the toner.

[0021] The transfer device **2** includes primary transfer rollers **23Y**, **23M**, **23C**, and **23K**, an intermediary transfer belt **24**, and a secondary transfer roller **25**. The intermediary transfer belt **24** is wound around the primary transfer rollers **23Y**, **23M**, **23C**, and **23K** and a plurality of rollers, and is supported so as to be travelable.

[0022] The primary transfer rollers **23Y**, **23M**, **23C**, and **23K** are disposed in a named order from above in FIG. **1** and correspond to the colors of Y (yellow), M (magenta), C (cyan), and K (black), respectively. The secondary transfer roller **25** is disposed outside the intermediary transfer belt **24** and is constituted so that a recording material is capable of passing through belt the secondary transfer roller **25** and the intermediary transfer belt **24**. The recording material is a sheet such as a form (paper) or a plastic sheet.

[0023] The toner images of the respective colors formed on the photosensitive drums **28Y**, **28M**, **28C**, and **28K** are successively transferred onto the intermediary transfer belt **24** by the primary transfer rollers **23Y**, **23M**, **23C**, and **23K**, respectively, so that a color toner image including superimposed layers of the colors of yellow, magenta, cyan, and black. The thus-formed toner image is transferred by the secondary transfer roller **25** onto the recording material fed from a cassette in which recording materials are accommodated. The recording material on which the toner image is transferred is pressed and heated in the fixing device **3**. By this, the toner on the recording material is melted, so that the color image is fixed on the recording material.

[0024] Developer storage portions **27Y**, **27M**, **27C**, and **27K** are provided correspondingly to the developing devices **1Y**, **1M**, **1C**, and **1K**, respectively, and in which bottles accommodating

developers corresponding to the colors of yellow, magenta, cyan, and black are exchangeably mounted in a named order from above, respectively. The developer storage portions **27Y**, **27M**, **27C**, and **27K** are constituted so that the developers are capable of being fed (supplied) therefrom to the developing devices **1Y**, **1M**, **1C**, and **1K** corresponding to the colors of the developers stored therein, respectively.

[0025] For example, a toner weight ratio of the developer accommodated in each bottle is 80 to 95%, and a toner weight ratio of the developer in each of the developing devices **1Y**, **1M**, **1C**, and **1K** is 5 to 10%. For that reason, when the toner is consumed by development in each of the developing devices **1Y**, **1M**, **1C**, and **1K**, the developer containing the toner in an amount corresponding to a consumption amount of the toner is supplied, so that the toner weight ratio of the developer in each of the developing devices **1Y**, **1M**, **1C**, and **1K** is maintained in a constant amount.

[Developing Device]

[0026] Next, the photosensitive drums **1Y**, **1M**, **1C**, and **1K** will be specifically described using FIGS. 2 to 5.

[0027] Structures of the developing devices **1Y**, **1M**, **1C**, and **1K** are the same, and therefore, in the following, the developing device **1Y** will be described as a representative. FIG. 2 is a conceptual view illustrating the developing device **1Y** shown in FIG. 1, and FIGS. 3 to 5 are conceptual views illustrating magnetic pole structures of a first magnet **36**, a second magnet **37**, and a third magnet **38** which are provided inside the developing device **1Y**, respectively.

[0028] The developing device **1Y** includes, as shown in FIG. 2, a first developing roller **30**, a second developing roller **31**, a peeling roller **32**, a developer supplying screw **42**, a developer stirring screw **43**, and a developer collecting screw **44**, and these members are accommodated in a developing container **60**.

[0029] The first developing roller **30** is a developer carrying member which is rotationally driven, and is provided at a position adjacent to the photosensitive drum **28Y** so that a rotational axis thereof is substantially parallel to a rotational axis of the photosensitive drum **28Y**. The first developing roller **30** includes a first sleeve **33** which is rotatable, and the first magnet (fixed magnet) **36** non-rotationally provided inside the first sleeve **33** and for attracting the developer to a surface of the first sleeve **33** by a magnetic force. Then, the first developing roller **30** attracts (carries) the developer, scooped from the developer supplying screw **42**, on the basis of the magnetic force, and develops the electrostatic latent image formed on the rotating photosensitive drum **28Y** (image bearing member), with the developer.

[0030] The first sleeve **33** is a non-magnetic cylindrical member and is rotationally driven about a rotation shaft **39**. A rotational direction of the first sleeve **33** is the clockwise direction as indicated by an arrow in FIG. 2 and is a direction opposite to a rotational direction of the photosensitive drum **28**. For this reason, the first sleeve **33** and the photosensitive drum **28Y** rotate in the same direction at mutually opposing positions.

[0031] The first magnet **36** is disposed inside the first sleeve **33** and includes, as shown in FIG. 3, a plurality of sector magnetic poles **101** to **107** and a sector non-magnetic pole portion **110**. Between an inner periphery of the first sleeve **33** and an outer periphery of the first magnet **36**, a space permitting rotation of the first sleeve **33** is provided.

[0032] The developer attracted onto the first sleeve **33** is conveyed toward the photosensitive drum **28Y** by a rotation operation of the first sleeve **33**, so that the electrostatic latent image formed on the photosensitive drum **28Y** is developed with the developer. After the electrostatic latent image formed on the photosensitive drum **28Y** is developed with the developer, the developer on the first sleeve **33** is conveyed to the neighborhood of the second developing roller **31** by a rotation operation of the first sleeve **33**. Then, in the neighborhood of a closest position between the first developing roller **30** and the second developing roller **31**, the developer is peeled off from the first sleeve **33** and then delivered to a surface of a second sleeve **34** by a magnetic field generated by the

first magnet **36** included in the first developing roller **30** and by the second magnet **37** included in the second developing roller **31**.

[0033] The second developing roller **31** is a developer carrying member which is rotationally driven, and is provided downstream of the first developing roller **30** with respect to the rotational direction of the photosensitive drum **28Y** and above a rotation center of the first developing roller **30** with respect to the vertical direction. To the second developing roller **31**, the developer is delivered from the first developing roller **30** by the magnetic force. The second developing roller **31** is, similarly as the first developing roller **30**, provided at a position adjacent to the photosensitive drum **28Y** so that a rotational axis thereof is substantially parallel to a rotational axis of the photosensitive drum **28Y**. Accordingly, the second developing roller **31** and the first developing roller **30** are substantially parallel to each other in rotational axis.

[0034] Such a second developing roller **31** includes a second sleeve **34** which is rotatable, and the second magnet (fixed magnet) **37** non-rotationally provided inside the second sleeve **34** and for attracting the developer to a surface of the second sleeve **34** by a magnetic force. Then, on the basis of the magnetic force, to the second developing roller **31**, the developer is delivered from the first developing roller **30** (the first sleeve **33**), and the second developing roller **31** attracts (carries) the developer, and develops the electrostatic latent image formed on the rotating photosensitive drum **28Y**, with the developer. On a side of the second developing roller **31**, the peeling roller **32** described later is positioned.

[0035] The second sleeve **34** is a non-magnetic cylindrical member and is rotationally driven about a rotation shaft **40**. A rotational direction of the second sleeve **34** is the clockwise direction as indicated by an arrow in FIG. **2** and is a direction opposite to a rotational direction of the photosensitive drum **28**. For this reason, the second sleeve **34** and the photosensitive drum **28Y** rotate in the same direction at mutually opposing positions. Further, the first sleeve **33** and the second sleeve **34** rotate in opposite directions at mutually opposing positions.

[0036] The second magnet **37** is disposed inside the second sleeve **34** and includes, as shown in FIG. **4**, a plurality of sector magnetic poles **201** to **207** and a sector non-magnetic pole portion **210**. Between an inner periphery of the second sleeve **34** and an outer periphery of the second magnet **37**, a space permitting rotation of the second sleeve **34** is provided.

[0037] The developer attracted onto the second sleeve **34** is conveyed toward the photosensitive drum **28Y** by a rotation operation of the second sleeve **34**, so that the electrostatic latent image formed on the photosensitive drum **28Y** is developed with the developer. After the electrostatic latent image formed on the photosensitive drum **28Y** is developed with the developer, the developer remaining on the second sleeve **34** is conveyed to the neighborhood of the peeling roller **32** by a rotation operation of the second sleeve **34**. Then, in the neighborhood of a closest position between the second developing roller **31** and the peeling roller **32**, the developer is delivered from the second sleeve **34** to a third sleeve **35** of the peeling roller **32** by a magnetic field generated by the second magnet **37** included in the second developing roller **31** and by the third magnet **38** included in the peeling roller **32**.

[0038] The peeling roller **32** as a peeling portion is provided on a side opposite from the photosensitive drum **28Y** with respect to a rotation center R (see FIG. **6** described later) of the second sleeve **34** and peels off, from the second developing roller **31**, the developer after the electrostatic latent image on the photosensitive drum **28Y** is developed by the second developing roller **31**. Specifically, the peeling roller **32** is a developer carrying member which is rotationally driven, and is provided between the second developing roller **31** and the developer collecting screw **44** so that a rotation center thereof is positioned above the rotation center R of the second developing roller **31**.

[0039] Further, the peeling roller **32** is disposed so that a rotational axis thereof is substantially parallel to a rotational axis of the second developing roller **31**. Such a peeling roller **32** includes a third sleeve **35** which is rotatable, and the third magnet (fixed magnet) **38** non-rotationally provided

inside the third sleeve **35** and for attracting the developer to a surface of the third sleeve **35** by a magnetic force, and is constituted so that the developer is delivered from the second developing roller **31** thereto on the basis of the magnetic force.

[0040] The third sleeve **35** is a non-magnetic cylindrical member and is rotationally driven about a rotation shaft **41**. A rotational direction of the third sleeve **35** is the counterclockwise direction as indicated by an arrow in FIG. **2** and is a direction opposite to a rotational direction of the second sleeve **34**. For this reason, the third sleeve **35** and the second sleeve **34** rotate in the same direction at mutually opposing positions.

[0041] The third magnet **38** is disposed inside the third sleeve **35** and includes, as shown in FIG. **5**, a plurality of sector magnetic poles **301** to **305** and a sector non-magnetic pole portion **310**. Between an inner periphery of the third sleeve **35** and an outer periphery of the third magnet **38**, a space permitting rotation of the third sleeve **35** is provided.

[0042] The developer attracted to the third sleeve **35** is conveyed to a downstream side of the rotational direction by a rotation operation of the third sleeve **35** is peeled off from the third sleeve **35** at a position close to the developer collecting screw **44** by the third magnet **38** included in the peeling roller **32**, so that the developer is dropped toward a guiding member **45** positioned below with respect to the vertical direction, by a self-weight thereof. Then, the developer dropped on the guiding member **45** is guided toward the developer collecting screw **44** by its own weight.

[0043] The guiding member **45** and the developer collecting screw **44** constitute a developer collecting portion **47** as a collecting portion for collecting the developer peeled off from the third sleeve **35** on the peeling roller **32**. In the developer collecting portion **47**, the developer collecting screw **44** is positioned below a rotation center of the peeling roller **32** in the vertical direction, and conveys the developer delivered (collected) from the peeling roller **32**, while stirring the developer.

[0044] The guiding member **45** as a guiding portion is disposed below the rotation center of the peeling roller **32** with respect to the vertical direction, and guides the developer, peeled off by the peeling roller **32**, toward the developer collecting screw **44**. Such a guiding member **45** is provided with an inclined surface **45a** along which the developer slides down by its own weight in order to reliably guide the peeled developer toward the developer collecting screw **44**. The inclined surface **45a** is inclined with respect to a horizontal direction so that a position thereof on the developer collecting screw **44** side is lower than a lower position of the peeling roller **32**.

[0045] In an attitude of the developing device **1Y** when the developing device **1Y** is mounted in the image forming apparatus **100**, it is assumed that the developing device **1Y** is viewed in a cross section perpendicular to a rotational axis of the peeling roller **32**. At this time, of two intersection points where a horizontal line **L** passing through the rotation center of the peeling roller **32** crosses the peeling roller **32**, the point on a side closer to a rotation center of the developer collecting screw **44** is an intersection point **X**, and the point on a side remoter from the rotation center of the developer collecting screw **44** is an intersection point **X'** (see FIG. **2** and FIG. **6** described later). Further, at this time, a tangential line of the peeling roller **32** passing through the intersection point **X** is a tangential line **M**, a perpendicular line passing through a lowest point **Y** of the inclined surface **45a** of the guiding member **45** is a perpendicular line **H**, and a perpendicular line passing through a free end **Z** of the guiding member **45** is a perpendicular line **N** (see FIG. **6** described later). At this time, as a positional relationship between the peeling roller **32** and the guiding member **45**, setting is made so that the tangential line **M** crosses the inclined surface **45a** of the guiding member **45**, while the perpendicular line **H** does not cross the peeling roller **32** (see FIG. **6** described later). Further, as a positional relationship between the peeling roller **32** and the guiding member **45**, setting is made so that the perpendicular line **N** crosses a magnetic pole **304** of the third magnet **38** included in the peeling roller **32** (see FIGS. **5** and **6** described later).

[0046] In this embodiment, in order to suppress that the developer splashed by rotation of the developer collecting screw **44** is drawn by the peeling roller **32**, positions of the peeling roller **32** and the developer collecting screw **44** are spaced from each other to some extent (see FIG. **2**). On

the other hand, in this embodiment, the positional relationships between the peeling roller **32** and the guiding member **45** are set as described above, so that even when a constitution in which the positions of the peeling roller **32** and the developer collecting screw **44** are spaced from each other is employed, the guiding member **45** is capable of reliably guiding, toward the developer collecting screw **44**, the developer peeled off from the peeling roller **32**.

[0047] The developer collecting screw **44** as a collecting member and a conveying (feeding) portion conveys the collected developer to a developer circulating portion **46** described below. That is, the developer collecting screw **44** is a screw conveyer member used for conveying the developer, collected by being slide down along the inclined surface **45a** of the guiding member **45**, in one direction while stirring the developer.

[0048] The developer circulating portion **46** is a supplying portion for supplying the developer to the first developing roller **30**, and includes a regulating member **50**, the developer supplying screw **42**, and the developer stirring screw **43**. In the developer circulating portion **46**, the developer is supplied to the first developing roller **30** while the developer is conveyed in the substantially horizontal direction while being stirred in the developer supplying screw **42** and the developer stirring screw **43**. Further, as described above, the developer collected by the developer collecting portion **47** is dropped by its own weight and is guided to the developer circulating portion **46**. That is, the developer circulating portion **46** is positioned below the developer collecting portion **47** with respect to the vertical direction.

[0049] The developer supplying screw **42**, the developer stirring screw **43**, and the developer collecting screw **44** are screw conveyor members for conveying the developer in one direction while stirring the developer, and the developer supplying screw **42** and the developer stirring screw **43** are positioned below the developer collecting screw **44** with respect to the vertical direction. Further, the developer supplying screw **42**, the developer stirring screw **43**, and the developer collecting screw **44** are disposed so that their rotational axes are substantially parallel to each other. The rotational axes of these screws are also substantially parallel to the rotational axis of the first developing roller **30**.

[0050] The developer supplying screw **42** is positioned between the first developing roller **30** and the developer stirring screw **43**, and between itself and the developer stirring screw **43**, a partition wall **48** of the developing container **60** is provided. The partition wall **48** of the developing container **60** is extended along rotational axis directions of the developer supplying screw **42** and the developer stirring screw **43**. The partition wall **48** is provided with a communication opening (not shown) for establishing communication between a first feeding path **61** along which the developer is fed by the developer supplying screw **42** and a second feeding path **62** along which the developer is fed by the developer stirring screw **43** is provided.

[0051] The developer stirred by the developer collecting screw **44** passes through a communication opening (not shown) formed in a partition wall **63** of the developing container **60** positioned between the developer collecting screw **44** and the developer supplying screw **42** and then is dropped toward the developer supplying screw **42** by its own weight. The above-described guiding member **45** is formed integrally with the partition wall **63**, and above the partition wall **63**, the developer collecting screw **44** is disposed. A position of the communication opening through which the developer stirred by the developer collecting screw **44** is dropped by its own weight and is guided into the developer circulating portion **46** may preferably be disposed while avoiding a region (an intermediary portion with respect to the developer supplying screw **42**) in which the developer is supplied toward the first developing roller **30**. In this embodiment, the position of the communication opening is a position where the communication opening position is included in a range of a downstream end portion (terminal portion) with respect to a developer feeding direction of the first feeding path **61** in which the developer supplying screw **42** is disposed.

[0052] Developer feeding directions of the developer supplying screw **42** and the developer stirring screw **43** are mutually opposite directions. Further, a starting end side (upstream end side in the

developer feeding direction) and a terminal end side (downstream end side in the developer feeding direction) of the first feeding path **61** in which the developer supplying screw **42** is disposed, and a terminal end side and a starting end side of the second feeding path **62** in which the developer stirring screw **43** is disposed communicate with each other, respectively, via communication openings provided in the partition wall **48**. Accordingly, the developer is circulated in the rotational directions of the developer supplying screw **42** and the developer stirring screw **43** indicated by arrows in FIG. 2 and in the substantially horizontal direction in the developing container **60**, so that a part of the developer is supplied toward the first developing roller **30**.

[0053] A developer supply opening **51** (see FIG. 2) is provided above the developer stirring screw **43** in the developing container **60** and is connected to the developer storage portion **27Y** (see FIG. 1). Further, the developer supply opening **51** is constituted so as to be capable of supplying the developer, accommodated in a bottle mounted in the developer storage portion **27Y**, to the second feeding path **62** in which the developer stirring screw **43** is disposed.

[0054] As described above, above, a toner weight ratio of the developer accommodated in the bottle of the developer storage portion **27Y** is larger than a toner weight ratio of the developer in the developing device **1Y**, and therefore, by adjusting an amount of the developer supplied to the developer stirring screw **43**, the toner weight ratio of the developer in the developing device **1Y** can be maintained at a certain level.

[0055] A toner concentration detecting sensor **49** (see FIG. 2) is provided for detecting a toner concentration of the developer contained in the developer circulating portion **46**. The toner concentration detecting sensor **49** is a sensor for detecting (magnetic) permeability. The toner concentration corresponds to a consumption amount of the toner in the developing device **1Y**, and therefore, is utilized in control of supply of the developer from the developer storage portion **27Y**. For example, when the toner concentration is detected that the toner concentration is lowered than a predetermined value, the developer is supplied from the developer storage portion **27Y**. The permeability changes depending on the toner concentration, and therefore, by utilizing the permeability, it is possible to detect the toner concentration.

[0056] The regulating member **50** is disposed adjacent to the first developing roller **30** and is used for regulating an amount of the developer supplied from the developer circulating portion **46** to the first developing roller **30**. The regulating member **50** can be constituted so as to regulate an amount of the developer attracted to the first developing roller **30**, on the basis of a gap between the surface of the first sleeve **33** of the first developing roller **30** and an end portion of the regulating member **50**.

[0057] A circulating path of the developer in the developing container **60** is such that the developer is fed in the substantially horizontal direction while being stirred in the developer circulating portion **46** and thereafter is supplied to the first developing roller **30**, and then is delivered from the first developing roller **30** to the second developing roller **31** positioned above the first developing roller **30**, on the basis of the magnetic force. Then, the developer is delivered from the second developing roller **31** to the peeling roller **32** positioned beside the second developing roller **31**, on the basis of the magnetic force again, and thereafter, is peeled off from the peeling roller **32** by the third magnet **38** included in the peeling roller **32**, and thereafter, the developer is collected by the developer collecting portion **47** and then is guided again into the developer circulating portion **46**.

[0058] Further, as described above, in this embodiment, a two-component development type is used as a development type, and as the developer, a developer obtained by mixing non-magnetic toner having a negative charging property with a carrier having a magnetic property is used. The non-magnetic toner is toner obtained by containing a colorant, a wax component, and the like in a resin such as polyethylene or styrene-acrylic resin, by forming the mixture in powder through pulverization or polymerization, and then by adding fine powder of titanium oxide, silica, or the like to a surface the powder. The magnetic carrier is a carrier obtained by coating a resin material on a surface layer of a core comprising resin particles obtained by kneading ferrite particles or

magnetic powder. The toner concentration in the developer (a weight ratio of the toner to the developer) in an initial state is 8% in this embodiment.

[0059] In general, the two-component development type using the toner and the carrier has a feature such that stress exerted on the toner is less than stress exerted on the toner in a one-component development type using a one-component developer because the toner and the carrier are charged to predetermined polarities by subjecting the toner and the carrier to triboelectric contact. A surface area of the carrier in the developer is larger than a surface area of the toner in the developer, so that a degree of carrier contamination with the toner deposited on the carrier surface is also small. However, by long-term use, an amount of a contaminant (spent) deposited on the carrier surface increases, and therefore, toner charging capacity gradually lower. As a result, problems of a fog and a toner scattering arise. Although an amount of the carrier accommodated in the developing device is increased in order to prolong a lifetime of the two-component developing device, this causes upsizing of the developing device, and therefore is not desirable.

[0060] In order to solve the above-described problems on the two-component developer, in this embodiment, an ACR (auto carrier refresh) type is employed. The ACR type is a type such that an increase in amount of a deteriorated developer is suppressed by not only supplying a fresh developer little by little from the developer storage portion **27Y** into the developing device **1Y** but also discharging the developer, deteriorated in charging performance, little by little through a discharge opening (not shown) of the developing device **1Y**. By this, the deteriorated carrier in the developing device **1Y** is replaced with a fresh carrier, so that the charging performance of the carrier in the developing device **1Y** can be maintained at an approximately constant level.

[Magnetic Poles of Magnets]

[0061] Next, magnetic pole constitutions of the first magnet **36**, the second magnet **37**, and the third magnet **38** included in the first developing roller **30**, the second developing roller **31**, and the peeling roller **32**, respectively, which are shown in FIGS. **3**, **4**, and **5**, respectively, will be described.

[0062] As shown in FIG. **3**, the first magnet **36** included in the first developing roller **30** is provided with a plurality of magnetic poles **101**, **102**, **103**, **104**, **105**, **106**, and **108**. The magnetic poles **101** to **106** and **108** are disposed in a named order in the rotational direction of the first sleeve **33**.

[0063] The magnetic pole **106** is a magnetic pole for delivering the developer from the first sleeve **33** to the second sleeve **34** by a magnetic field generated in cooperation with the second developing roller **31** and the second magnet **37**. Further, in this embodiment, with respect to a rotational direction of the first sleeve **33**, at a position adjacent to a downstream side of the magnetic pole **106**, a non-magnetic pole portion **110** as a low magnetic force portion lower in magnetic force than the magnetic pole **106** is provided. Further, the magnetic pole **108** is disposed at a position adjacent to the downstream side of the non-magnetic pole portion **110** with respect to the rotation direction of the first sleeve **33**. The non-magnetic pole portion **110** does not have the magnetic force, but may also be a magnetic pole low in magnetic force and, for example, a magnetic pole of which member force is 5 mT or less. This is true for non-magnetic pole portions **210** and **310**.

[0064] Further, the magnetic pole **101** is an S pole and is used for attracting the developer, supplied from the developer supplying screw **42**, to the first sleeve **33**. The magnetic poles **102**, **103**, **104**, and **105** are an N pole, an S pole, an N pole, and an S pole are used for feeding upward the developer attracted by the magnetic pole **101** with rotation of the first sleeve **33**. The magnetic pole **106** is an N pole and delivers the developer from the first sleeve **33** to the second sleeve **34** opposing the first sleeve **33** by a magnetic field generated in cooperation with a magnetic pole **201** in the second magnet **37** included in the second developing roller **31** as described above.

[0065] As shown in FIG. **4**, the second magnet **37** included in the second developing roller **31** is provided with a plurality of magnetic poles **201**, **202**, **203**, **204**, **205**, **206**, and **207**. The magnetic poles **201** to **207** are disposed in a named order in the rotational direction of the second sleeve **34**.

[0066] The magnetic pole **201** is a magnetic pole for attracting the developer from the first sleeve

33 to the second sleeve **34** by a magnetic field generated in cooperation with the magnetic pole **106** of the first magnet **36** of the first developing roller **30**. The magnetic pole **207** is a magnetic pole for delivering the developer from the second sleeve **34** to the third sleeve **35** by a magnetic field generated in cooperation with the third magnet **38** of the peeling roller **32**.

[0067] Further, the magnetic pole **201** is an S pole and is used for attracting the developer from the first developing roller **30** (first sleeve **33**) to the second sleeve **34** as described above. The magnetic poles **202**, **203**, **204**, **205** and **206** are an N pole, an S pole, an N pole, an S pole, and an N pole are used for feeding upward the developer attracted by the magnetic pole **201** with rotation of the second sleeve **34**. The magnetic pole **207** is an S pole and delivers the developer, after passing through a developing region with the photosensitive drum **28Y** corresponding to the magnetic pole **203**, from the second sleeve **34** to the third sleeve **35** opposing the second sleeve **34** by a magnetic field generated in cooperation with a magnetic pole **303** in the third magnet **38** included in the peeling roller **32**.

[0068] As shown in FIG. 5, the third magnet **38** included in the peeling roller **32** is provided with a plurality of magnetic poles **301**, **302**, **303**, **304**, and **305**. The magnetic poles **301** to **305** are disposed in a named order in the rotational direction of the third sleeve **35**.

[0069] The magnetic pole **303** is an N pole and is used for attracting the developer, peeled off from the second sleeve **34** as described above, to the third sleeve **35**. The magnetic poles **301**, **302**, and **304** are an N pole, an S pole, and an S pole are used for feeding the developer on the third sleeve **35** with rotation of the third sleeve **35**. Particularly, the magnetic pole **304** is used for feeding downward the developer attracted by the magnetic pole **303** with rotation of the third sleeve **35**. The magnetic pole **305** is an N pole and is peeling pole used for peeling off the developer, attracted to the third sleeve **35**, from the third sleeve **35** by a repelling magnetic field generated in cooperation with the magnetic pole **301** having the same pole.

[Structure of Periphery of Second Developing Roller and Peeling Roller]

[0070] Next, referring to FIG. 6, a structure of a periphery of the second developing roller **31** and the peeling roller **32** will be described.

[0071] In this embodiment, the developer in the developing device **1Y** moves from the surface of the first sleeve **33** of the first developing roller **30** to the surface of the second sleeve **34** of the second developing roller **31**, and moves to the surface of the third sleeve **35** of the peeling roller **32** after being used in a developing step of the electrostatic latent image on the photosensitive drum **28Y**. In recent years, speed-up of the image forming apparatus advances, so that rotational speeds of the first developing roller **30**, the second developing roller **31**, and the peeling roller **32** become fast. For this reason, when the developer moves from the surface of the second sleeve **34** of the second developing roller **31** to the surface of the third sleeve **35** of the peeling roller **32**, an air flow generates in a gap **A1** between the second developing roller **31** and the peeling roller **32**, so that a part of the developer on the second sleeve **34** is scattered by the air flow. The scattered developer moves along a flow of the air flow.

[0072] Here, in the case where a closest distance between the second developing roller **31** and the guiding member **45** is **B** and a closest distance between the peeling roller **32** and the guiding member **45** is **C**, the flow of the air flow is influenced by a relationship between the closest distances **B** and **C**. The closest distance **B** is a closest distance between the second developing roller **31** and a free end **Z** of the guiding member **45**. The air flow is liable to flow toward a large gap, and therefore, when the above-described relationship between the closest distances **B** and **C** is $B \geq C$, the scattered developer is carried along with the air flow in a direction toward a gap **B1** between the second developing roller **31** and the guiding member **45**. The developer carried in the direction toward the gap **B1** between the second developing roller **31** and the guiding member **45** passes through this gap **B1** and is then dropped. The first developing roller **30** is disposed at a position overlapping with the gap **B1** between the second developing roller **31** and the guiding member **45** with respect to the vertical direction, and therefore, the developer passed through this

gap B1 moves in a direction toward the first sleeve 33 of the first developing roller 30. [0073] When the used developer approaches the neighborhood of the first sleeve 33, the used developer is pulled toward the magnetic pole 106 of the first magnet 36 included in the first developing roller 30. As described above, a delivering magnetic field is generated between the magnetic pole 106 of the first magnet 36 included in the first developing roller 30 and the magnetic pole 201 of the second magnet 37 included in the second developing roller 31. For this reason, the above-described used developer moves toward the second developing roller 31 by the delivering magnetic field. That is, the used developer dropped from the surface of the second sleeve 34 is scooped on the second sleeve 34 again, and thus drag occurs, so that an uneven (irregular) image is generated on an output image.

[0074] Therefore, in this embodiment, an arrangement of the guiding member 45 and the peeling roller 32 is regulated so that the relationship between B which is the closest distance between the second developing roller 31 and the guiding member 45 and C which is the closest distance between the peeling roller 32 and the guiding member 45 satisfies $B < C$. A constitution is created so as to satisfy $B < C$, it is possible to suppress that the used developer scattered from the second developing roller 31 moves to the neighborhood of the closest portion between the first developing roller 30 and the second developing roller 31. As a result, an occurrence of the drag on the second sleeve 34 of the second developing roller 31 is suppressed, so that an occurrence of an image defect such as the uneven image can be suppressed.

[0075] Further, in the case where a closest distance between the second developing roller 31 and the peeling roller 32 is A, it is preferable that $B < A$ is satisfied. This will be described. First, an air flow generated in a gap A1 between the second developing roller 31 and the peeling roller 32 includes a component flowing toward a gap B1 between the second developing roller 31 and the guiding member 45 or toward a gap C1 between the peeling roller 32 and the guiding member 45, and a component coming out of the gap A1. A balance between an air flow (in flow amount) flowing in a space surrounded by the gaps A1, B1, and C1 and an air flow (discharge amount) going out of the space is kept. If this balance is not kept and the in flow amount is large, internal pressure continuously increases. Accordingly, the air flow escapes from the gap so as to keep the balance between the inflow amount of the air flow and the discharge amount of the air flow.

[0076] In the case where the rotational speeds of the various rollers are constant, a flow rate of the air flow is determined by a magnitude of an associated gap, so that the flow rate increases with a larger gap. Further, the air flow flows toward a large gap decreased in resistance. When a relationship between the closest distance A in the gap A1 and the closest distance B in the gap B1 is considered on the assumption that the closest distance C in the gap C1 and the closest distance B in the gap B1 is $B < C$, in the case where a relationship of $B > A$ is satisfied, a flow of the air flow toward both the gaps B1 and C1 which are large in gap generates. Further, the gap C1 is larger than the gap B1, and therefore, the air flow flowing in the gap C1 increases in amount, but the air flow flowing in the gap B1 generates in a certain amount.

[0077] On the other hand, in the case where a relationship of $B < A$ is satisfied, the gap B1 is narrower than the gap A1, and therefore, the air flow flows in the gap A1 or in the gap C1. Thus, by satisfying $B < A$ in addition to a condition of $B < C$, the air flow does not readily flow in the gap B1, so that the scattered developer can be suppressed from being carried toward the first developing roller 30 side.

[0078] Further, in the above-described relation ship between the distances A, B, and C, in this embodiment, it is preferable that $A \leq C$ is satisfied. This is because the air flow is made easy to flow from the gap A1 to the gap C1. By employing a relationship: $A < C$, a flow sending the developer to the developer collecting screw 44 is formed, so that it is possible to suppress that the developer flows in the gap B1. Further, in the case where the air flow flows back from the gap A1, the direction thereof is such that the developer blows out from the developing device, and therefore, leads to scattering of the developer to the outside of the developing device. For this reason, by

satisfying $A < C$, it is possible to suppress the scattering of the developer to the outside of the developing device.

[0079] Incidentally, when the flow of the developer to the gap B1 can be suppressed, $B < C$ may only be satisfied, and $A > C$ may be satisfied. However, as described above, in order to make the flow from the gap A1 to the gap C1 easy, $A \leq C$ may preferably be satisfied. When the suppression of the scattering of the developer to the outside of the developing device is taken into consideration, it is further preferable that $A < C$ is satisfied. That is, in this embodiment, it is preferable that $B < A < C$ is satisfied, whereby the flow of the air flow can be made a flow such that the developer is efficiently sent to the developer collecting screw 44, and in addition, it is possible to suppress the scattering of the developer to the outside of the developing device.

[0080] In the case of this embodiment, for example, the closest distance A between the second developing roller 31 and the peeling roller 32 is 2600 μm , the closest distance B between the second developing roller 31 and the free end Z of the guiding member 45 is 1000 μm , and the closest distance C between the peeling roller 32 and the guiding member 45 is 3000 μm . As described above, the air flow is liable to flow toward the side where the gap is large, and therefore, a relationship between the gaps B1 and C1 is set to satisfy $B < C$. That is, the air flow generated in the gap A1 is by drive of the second developing roller 31 and the peeling roller 32 flows toward the gap C1 between the peeling roller 32 and the guiding member 45 which provide a large gap. By this, the scattered developer is also carried toward the gap C1 along the air flow.

[0081] Further, by making the gap B1 between the second developing roller 31 and the free end Z of the guiding member 45 smaller than the gap A1, the air flow is caused to less flow toward the gap B1. In the case where a relationship between the gaps B1 and A1 is $A < B$, an air flow such that the air flow generated in the gap A1 flows in the gap B1 large in distance is created, so that the scattered developer is carried toward the gap B1.

[0082] Accordingly, as in this embodiment, it is preferred to constitute the gaps A1, B1, and C1 so as to satisfy that a relationship between the closest distances A, B, and C is $B < A < C$, and by satisfying $B < A < C$, the flow of the air flow can be effectively directed toward the gap C1. As a result of this, the used developer scattered from the second developing roller 31 is suppressed from moving the neighborhood of the closest portion between the first developing roller 30 and the second developing roller 31. By this, it is possible to suppress that the drag occurs on the second sleeve 34 of the second developing roller 31.

[0083] In this embodiment, the closest distance A in the gap A1 between the second developing roller 31 and the peeling roller 32 is set to 200 μm as a lower-limit value and to 3500 μm as an upper-limit value. The reason why the lower-limit value of the closest distance A in the gap A1 is set to 200 μm is that in the case where the closest distance A is below 200 μm , there is a liability that the second developing roller 31 and the peeling roller 32 are in contact with each other and thus slide with each other due to a component tolerance, a play, vibration, or the like. On the other hand, the reason why the upper-limit value of the closest distance A in the gap A1 is set to 3500 μm is that in the case where the closest distance A exceeds 3500 μm , there is a liability that the magnetic field generated by cooperation of the magnetic pole 207 in the second magnet 37 with the magnetic pole 303 in the third magnet 38 is weakened and thus efficiency of delivering of the developer from the second sleeve 34 to the third sleeve 35 lowers.

[0084] In this embodiment, the closest distance B in the gap B1 between the second developing roller 31 and the guiding member 45 is set to 200 μm as a lower-limit value and to 2000 μm as an upper-limit value. The reason why the lower-limit value of the closest distance B in the gap B1 is set to 200 μm is that in the case where the closest distance A is below 200 μm , there is a liability that the second developing roller 31 and the guiding member 45 are in contact with each other and thus slide with each other due to a component tolerance, a play, vibration, or the like. On the other hand, the reason why the upper-limit value of the closest distance A in the gap A1 is set to 2000 μm will be described in the following. In the case where the closest distance B exceeds 2000 μm , when

the air flow generated in the gap A1 between the second developing roller 31 and the peeling roller 32 flows toward the gap B1, a resistance received by the air flow flowing in the gap B1 becomes especially small. As a result of this, the air flow is liable to flow from the gap A1 to the gap B1, so that even in the case where the gap C1 is larger than the gap B1, there is a liability that an amount of the air flow flowing in the gap B1 becomes large.

[0085] Further, in this embodiment, a lower-limit value of the closest distance C in the gap C1 between the peeling roller 32 and the guiding member 45 is set to 200 μm , and an upper-limit value of the closest distance C is set to a value larger than the above-described upper-limit value of the closest distance B. The reason why the lower-limit value of the closest distance C in the gap C1 is set to 200 μm is that in the case where the closest distance C is below 200 μm , there is a liability that the peeling roller 32 and the guiding member 45 are in contact with each other and thus slide with each other due to a component tolerance, a play, vibration, or the like.

[0086] Further, in the case where the closest distance C is below 200 μm , when the air flow generated in the gap A1 between the second developing roller 31 and the peeling roller 32 flows toward the gap C1, a resistance received by the air flow flowing in the gap C1 becomes especially large. As a result of this, the air flow does not readily flow from the gap A1 to the gap C1, so that there is a liability that the air flow flows back from the gap A1. Here, the set values employed in this embodiment are examples, the relationship between the closest distance B in the gap B1 and the closest distance C in the gap C1 may preferably be that the closest distance C is larger than the closest distance B by 100 μm or more, more preferably 300 μm or more, further preferably 500 μm or more. The relationship between the closest distance A in the gap A1 and the closest distance B in the gap B1 may preferably be that the closest distance A is larger than the closest distance B by 100 μm or more, more preferably 300 μm or more, further preferably 500 μm or more. The relationship between the closest distance A in the gap A1 and the closest distance C in the gap C1 may preferably be that the closest distance A is larger than the closest distance C by 100 μm or more, more preferably 300 μm or more, further preferably 500 μm or more.

[0087] As described above, according to this embodiment, in the developing device in which the developer is delivered from the first developing roller 30 to the second developing roller 31, positioned above the first developing roller 30, on the basis of the magnetic force, and then is delivered from the second developing roller 31 to the peeling roller 32 on the basis of the magnetic force again, it is possible to suppress the occurrence of the image defect. That is, with respect to the rotational direction of the second sleeve 34, on a side downstream of the delivering position of the developer between the second developing roller 31 and the peeling roller 32, the used developer dropped from the second sleeve 34 can be suppressed from being conveyed to the delivering portion between the first developing roller 30 and the second developing roller 31 in the neighborhood of the closest position between the first developing roller 30 and the second developing roller 31. By this, the drag of the developer on the first developing roller 30 is also suppressed, so that the developing device 1Y such that even in a region in which the image is formed at a higher speed, the developer is stably collected from the second sleeve 34 and is circulated in the developer circulation portion 46 and then is capable of being supplied to the first sleeve 33, and the image forming apparatus 100 including the developing device 1Y can be provided.

Other Embodiments

[0088] The present invention is not limited to the constitution of the above-described embodiment. For example, the image forming apparatus 100 is not limited to the MFP, but may also be a copying machine, a printer, or a facsimile machine. Further, the constitutions of the developer supplying screw 42, the developer stirring screw 43, and the developer collecting screw 44 are not particularly limited when the constitutions can convey the developer, and for example, it is possible to apply a helical blade, a paddle-like blade.

[0089] While the present invention has been described with reference to exemplary embodiments,

it is to be understood that the invention is not limited to the disclosed exemplary embodiments. The scope of the following claims is to be accorded the broadest interpretation so as to encompass all such modifications and equivalent structures and functions.

[0090] This application claims the benefit of Japanese Patent Applications Nos. 2023-020080 filed on Feb. 13, 2023, and 2024-003031 filed on Jan. 12, 2024, which are hereby incorporated by reference herein in their entirety.

Claims

1-20. (canceled)

21. A developing device comprising: a first chamber configured to accommodate a developer containing toner and a carrier; a first feeding screw provided in the first chamber and configured to feed the developer in the first chamber; a second chamber partitioned from the first chamber by a partition wall; a second feeding screw provided in the second chamber and configured to feed the developer in the second chamber, the second feeding screw having a rotation center positioned above a rotation center of the first feeding screw in a vertical direction; a first rotatable member to which the developer is supplied from the first chamber and configured to carry and feed the developer for developing an electrostatic latent image formed on an image bearing member; a first magnet fixedly provided inside the first rotatable member; a regulating member which is provided opposed to the first rotatable member and regulates an amount of the developer carried on the first rotatable member; a second rotatable member which is provided opposed to the first rotatable member, to which the developer is delivered from the first rotatable member by a magnetic field generated by the first magnet, and which is configured to carry and feed the developer for developing the electrostatic latent image, the second rotatable member having a rotation center positioned above a rotation center of the first rotatable member in the vertical direction; a second magnet fixedly provided inside the second rotatable member; a third rotatable member which is provided opposed to the second rotatable member, to which the developer is delivered from the second rotatable member by a magnetic field generated by the second magnet, and which is configured to carry and feed the developer for collecting, into the second chamber, the developer after the electrostatic latent image is developed with the developer, the third rotatable member having a rotation center positioned above the rotation center of the second rotatable member in the vertical direction; a third magnet fixedly provided inside the third rotatable member; and a guiding portion provided opposed to each of the second rotatable member and the third rotatable member and configured to guide the developer, to the second feeding screw, peeled off from the third rotatable member by a repelling magnetic field generated by the third magnet, wherein in a position where the first rotatable member and the second rotatable member oppose each other, the second rotatable member rotates in a direction opposite to the first rotatable member, and wherein in a case that a shortest distance between the second rotatable member and the guiding portion is B [μm], and a shortest distance between the third rotatable member and the guiding portion is C [μm], the following relationship is satisfied: $B + 100.\text{Math.m} \leq C$.

22. A developing device according to claim 21, wherein the following relationship is satisfied: $B < C$.

23. A developing device according to claim 21, wherein the following relationship is satisfied: $B + 500.\text{Math.m} \leq C$.

24. A developing device according to claim 21, wherein the following relationships are satisfied: $200.\text{Math.m} \leq B \leq 2000.\text{Math.m}$, and $200.\text{Math.m} \leq C$.

25. A developing device according to claim 21, wherein in a case that a closest distance between the second rotatable member and the third rotatable member is A [μm], the following relationship is satisfied:

$B < A$.

26. A developing device according to claim 25, wherein the following relationship is satisfied:
 $B + 100.\text{Math.m} \leq A$.
27. A developing device according to claim 25, wherein the following relationship is satisfied:
 $B + 300.\text{Math.m} \leq A$.
28. A developing device according to claim 25, wherein the following relationship is satisfied:
 $B + 500.\text{Math.m} \leq A$.
29. A developing device according to claim 25, wherein the following relationships are satisfied:
 $200.\text{Math.m} \leq A \leq 3500.\text{Math.m}$, $200.\text{Math.m} \leq B \leq 2000.\text{Math.m}$, and $200.\text{Math.m} \leq C$.
30. A developing device according to claim 21, wherein in a case that a closest distance between the second rotatable member and the third rotatable member is A [μm], the following relationship is satisfied:
 $A \leq C$.
31. A developing device according to claim 30, wherein the following relationship is satisfied:
 $A < C$.
32. A developing device according to claim 31, wherein the following relationship is satisfied:
 $A + 100.\text{Math.m} \leq C$.
33. A developing device according to claim 31, wherein the following relationship is satisfied:
 $A + 300.\text{Math.m} \leq C$.
34. A developing device according to claim 31, wherein the following relationship is satisfied:
 $A + 500.\text{Math.m} \leq C$.
35. A developing device according to claim 30, wherein the following relationship is satisfied:
 $B < A$.
36. A developing device according to claim 30, wherein the following relationships are satisfied:
 $200.\text{Math.m} \leq A \leq 3500.\text{Math.m}$, $200.\text{Math.m} \leq B \leq 2000.\text{Math.m}$, and $200.\text{Math.m} \leq C$.
37. A developing device according to claim 21, further comprising a communicating portion configured to permit communication of the developer from the second chamber to the first chamber.
38. A developing device according to claim 21, further comprising: a third chamber partitioned from the first chamber by another partition wall different from the partition wall; a third feeding screw provided in the third chamber and configured to feed the developer in the third chamber; a first communicating portion configured to permit communication of the developer from the third chamber to the first chamber; and a second communicating portion configured to permit communication of the developer from the first chamber to the third chamber.
39. A developing device according to claim 38, further comprising a developer supply portion configured to supply the developer to the third chamber, wherein the developer supply portion is disposed above the third feeding screw in the vertical direction.
40. A developing device according to claim 21, wherein when the developing device is viewed in a cross section perpendicular to a rotational axis of the third rotatable member, in a case of two intersection points where a horizontal line L passing through the rotation center of the third rotatable member crosses the third rotatable member, the intersection point on a side closer to the second feeding screw is an intersection point X and the intersection point on a side more remote from the second feeding screw is an intersection point X' , a tangential line M of the third rotatable member passing through the intersection point X crosses the guiding portion.
41. A developing device according to claim 21, wherein when the developing device is viewed in a cross section perpendicular to a rotational axis of the third rotatable member, a perpendicular line H passing through a lowest point Y of the guiding portion does not intersect the third rotatable member.
42. A developing device according to claim 21, wherein when the developing device is viewed in a cross section perpendicular to a rotational axis of the third rotatable member, a perpendicular line N passing through a free end Z of the guiding portion closest to the second rotatable member

intersects the third rotatable member.

43. A developing device according to claim 21, wherein in a position where the second rotatable member and the third rotatable member oppose each other, the third rotatable member rotates in a same direction as the second rotatable member.

44. A developing device according to claim 21, wherein the image bearing member is rotatable, and in a position where the image bearing member and the first rotatable member oppose each other, the first rotatable member rotates in a same direction as the image bearing member.

45. A developing device according to claim 21, wherein the image bearing member is rotatable, and in a position where the image bearing member and the second rotatable member oppose each other, the second rotatable member rotates in a same direction as the image bearing member.

46. A developing device according to claim 21, wherein the second feeding screw is positioned below a rotation center of the third rotatable member in the vertical direction.

47. A developing device according to claim 21, wherein the guiding portion is positioned below a rotation center of the third rotatable member in the vertical direction.

48. A developing device according to claim 21, wherein an opposing position where the regulating member is opposed to the first rotatable member is positioned below the rotation center of the first rotatable member in the vertical direction.
