

US Patent & Trademark Office

Patent Public Search | Text View

United States Patent Application Publication

20250285507

Kind Code

A1

Publication Date

September 11, 2025

Inventor(s)

Nelson; Dwayne R. et al.

GAMING SYSTEM AND METHOD FOR MODIFYING AWARDS BASED ON A SPORTING EVENT

Abstract

Gaming systems and methods which utilize the results of a sporting event to determine a modification of an award, such as an increment of a progressive award.

Inventors: Nelson; Dwayne R. (Las Vegas, NV), Knox; Jeffrey (Las Vegas, NV)

Applicant: IGT (Las Vegas, NV)

Family ID: 74344208

Appl. No.: 19/215894

Filed: May 22, 2025

Related U.S. Application Data

parent US continuation 17879288 20220802 PENDING child US 19215894

parent US continuation 16514363 20190717 parent-grant-document US 11443594 child US 17879288

Publication Classification

Int. Cl.: G07F17/32 (20060101); G06Q50/34 (20120101)

U.S. Cl.:

CPC G07F17/3258 (20130101); G06Q50/34 (20130101); G07F17/3288 (20130101);

Background/Summary

PRIORITY CLAIM [0001] This application is a continuation of, claims priority to and the benefit of U.S. patent application Ser. No. 17/879,288, filed on Aug. 2, 2022, which is a continuation of, claims priority to and the benefit of U.S. patent application Ser. No. 16/514,363, filed on Jul. 17, 2019, the entire contents of which are each incorporated by reference herein.

BACKGROUND

[0002] Gaming machines may provide players awards in primary games. Gaming machines generally require the player to place or make a wager to activate the primary or base game. The award may be based on the player obtaining a winning symbol or symbol combination and on the amount of the wager.

Description

BRIEF DESCRIPTION OF THE FIGURES

[0003] FIG. 1 is a flowchart of one embodiment of the gaming system disclosed herein illustrating incrementing a progressive award based on an occurrence of an event in a sporting event.

[0004] FIGS. 2A, 2B and 2C are front views of one embodiment of the gaming system disclosed herein wherein a progressive award is modified based on an event occurring in a sporting event.

[0005] FIG. 3 is a schematic block diagram of one embodiment of an electronic configuration of an example gaming system disclosed herein.

[0006] FIGS. 4A and 4B are perspective views of example alternative embodiments of the gaming system disclosed herein.

[0007] FIG. 4C is a front view of an example personal gaming device of the gaming system disclosed herein.

DETAILED DESCRIPTION

Modifying Awards Based on Sporting Events

[0008] In various embodiments, the present disclosure relates generally to gaming systems and methods which utilize the results of a sporting event to determine a modification of an award, such as an increment of a progressive award.

[0009] In certain embodiments, the gaming system maintains one or more progressive awards available to be won in association with one or more games. In addition to maintaining such progressive awards, the gaming system displays a video stream of a sporting event. In these embodiments, the gaming system determines zero, one or more modifications of the maintained progressive awards based on or otherwise influenced by a sporting event. That is, responsive to one or more events occurring (or not occurring) in a sporting event and independent of any amount directly attributed to any wagers placed on any games associated with the progressive award or the timing these wagers are placed, the gaming system disclosed herein causes a progressive award modification event to occur and causes the progressive award to increment (or alternatively decrement) in value. Such a configuration introduces an additional avenue for a bystander to interact with a sporting event and potentially win relatively higher valued progressive awards in the process. That is, even if certain players are not actively wagering on games associated with the progressive award due to the progressive award not being deemed to be at a desirable value by such players (and thus the progressive award is not growing in value via that avenue), the progressive award will still potentially increment based on one or more events occurring in the sporting event. These sporting event driven progressive award increase events will cause the progressive award to potentially increment to at least a desirable value (which in turn may cause more players to play games associated with the progressive award and further increase the progressive award).

[0010] While certain embodiments described below are directed to modifying an award, such as increasing or decreasing a progressive award, based on one or more sporting events, it should be

appreciated that such embodiments may additionally or alternatively be employed in association with modifying any game feature employed in association with any game displayed by the gaming system. It should be further appreciated that the gaming system utilized to modify an award based on one or more events occurring (or not occurring) in a sporting event may be any suitable electronic gaming machine (such as a slot machine, a video poker machine, a video lottery terminal, a terminal associated with an electronic table game, a video keno machine, a video bingo machine located on a casino floor, or a sports betting terminal), and/or any suitable personal gaming device (wherein the data associated with the progressive award and the sporting event are accessed over a network).

[0011] FIG. 1 is a flowchart of an example process or method of operating the gaming system of the present disclosure. In various embodiments, the process is represented by a set of instructions stored in one or more memories and executed by one or more processors. Although the process is described with reference to the flowchart shown in FIG. 1, many other processes of performing the acts associated with this illustrated process may be employed. For example, the order of certain of the illustrated blocks or diamonds may be changed, certain of the illustrated blocks or diamonds may be optional, or certain of the illustrated blocks or diamonds may not be employed.

[0012] In various embodiments, the gaming system maintains a progressive award as indicated in block 102 of FIG. 1. As described below, the maintained progressive award starts or resets at a reset amount or level and increments based on events occurring (or not occurring) in a sporting event associated with the progressive award.

[0013] In certain embodiments, the gaming system maintains a single progressive award in association with a single sporting event wherein, as described below, one or more events which occur (or do not occur) during the sporting event influence the amount contributed to the maintained progressive award. For example, for a football game between Team A and Team B, the gaming system maintains a progressive award in association with that football game.

[0014] In certain embodiments, the gaming system maintains a plurality of different progressive awards in association with a single sporting event. For example, the gaming system maintains a first progressive award in association with the home team of the sporting event and the gaming system maintains a second progressive award in association with the visiting team of the sporting event.

[0015] In certain embodiments, the gaming system maintains a single progressive award in association with a plurality of sporting events of one sport over a designated period of time. For example, the gaming system maintains a professional football week progressive award wherein a plurality of professional football games, such as each of the professional football games occurring for a given week, are associated with the same progressive award.

[0016] In certain embodiments, the gaming system maintains a single progressive award in association with a plurality of sporting events of a plurality of different sports over a designated period of time. For example, the gaming system maintains a progressive award wherein one or more professional football games, such as each of the professional football games occurring for a given week and one or more professional baseball games, such as each of the professional baseball games occurring for the same given week, are associated with the same progressive award.

[0017] In certain embodiments, the gaming system maintains a plurality of different progressive awards in association with a plurality of different sporting events over a designated period of time. For example, the gaming system maintains a plurality of professional football progressive awards wherein a plurality of different professional football games, such as each of the professional football games occurring for a given week, are associated with a different progressive award.

[0018] In certain embodiments, the gaming system maintains a single progressive award in association with a single sports team wherein, as described below, one or more events which occur (or do not occur) in association with that single sports team influence the amount contributed to the maintained progressive award. For example, for a football game between Team A and Team B, the

gaming system maintains a progressive award in association with Team A of that football game. In another example, the gaming system maintains a Team X progressive award wherein each of the games played by Team X over a given season are associated with that progressive award.

[0019] In certain embodiments, the gaming system maintains a plurality of different progressive awards in association with a plurality of different sports teams. For example, the gaming system maintains a first progressive award with Team A and further maintains a second progressive award with Team B.

[0020] In certain embodiments, the gaming system maintains a single progressive award in association with a plurality of sports teams of one sport over a designated period of time. For example, the gaming system maintains a national league progressive award wherein a plurality of baseball teams in the national league are associated with the same progressive award.

[0021] In certain embodiments, the gaming system maintains a single progressive award in association with a plurality of sports teams of a plurality of different sports over a designated period of time. For example, the gaming system maintains a Chicago progressive award wherein each of the professional hockey team located in Chicago and the professional soccer team located in Chicago are associated with the same progressive award.

[0022] In certain embodiments, the gaming system maintains a plurality of different progressive awards in association with a single sports team. For example, the gaming system maintains an offense progressive award associated with plays made by the offense of a college football team. In this example, the gaming system further maintains a defense progressive award associated with plays made by the defense of the college football team.

[0023] In certain embodiments, the gaming system maintains a single progressive award in association with a single sporting event participant wherein, as described below, one or more events which occur (or do not occur) in association with that sporting event participant in one or more sporting events influence the amount contributed to the maintained progressive award. In certain embodiments, the gaming system maintains a single progressive award in association with a plurality of different sporting event participants.

[0024] In certain embodiments, the gaming system maintains a single progressive award in association with a plurality of sporting event participants of one sport over a designated period of time. For example, the gaming system maintains a starting point guard progressive award wherein a plurality of starting point guards of a plurality of professional basketball teams are associated with the same progressive award.

[0025] In certain embodiments, the gaming system maintains a single progressive award in association with a plurality of sporting event participants of a plurality of different sports over a designated period of time. For example, the gaming system maintains a Las Vegas born players progressive award wherein each professional baseball player and each professional tennis player born in Las Vegas are associated with the same progressive award.

[0026] In certain embodiments, the gaming system maintains a plurality of different progressive awards in association with a plurality of different sporting event participants. For example, the gaming system maintains a first progressive award with Player X of a sporting event and a second progressive award with Player Y of the sporting event.

[0027] In certain embodiments, the gaming system maintains a plurality of different progressive awards in association with a single sporting event participant. For example, the gaming system maintains a points progressive award associated with any points scored by a professional hockey player. In this example, the gaming system further maintains an assists progressive award associated with any assists made by the same professional hockey player. In certain embodiments, the gaming system maintains a single progressive award in association with a single sporting event participant.

[0028] It should be appreciated that any suitable configuration of associating sporting events, sports teams and/or sporting event participants with one or more progressive awards may be

employed in association with the gaming system disclosed herein. It should be further appreciated that the gaming system may associate one or more progressive awards with any suitable sporting event, sports team or sporting event participant of any suitable sport at any professional and/or amateur level including, but not limited to, football, basketball, baseball, boxing, horse racing, wrestling, mixed martial arts, golf, cricket, soccer, hockey, field hockey, tennis, volleyball, table tennis, rugby, swimming, diving, archery, cycling, billiards, fishing, gymnastics, hunting, track and field, sailing, and/or car racing.

[0029] In certain embodiments, each of the progressive awards maintained by the gaming system have the same progressive award reset value. In certain embodiments, a plurality of the progressive awards maintained by the gaming system have different progressive award reset values.

[0030] In different embodiments, in addition to maintaining a progressive award, upon a sporting event display condition being satisfied, the gaming system displays a sporting event as indicated by block **104** of FIG. **1**. In certain embodiments, the sporting event includes displaying a game field and zero, one or more sporting event elements on the displayed game field. For example, as seen in FIG. **2A**, the gaming system displays a game field **200** (e.g., a football field) associated with a displayed stream of a live sporting event (e.g., a live football game) **202**, wherein a first team of sporting event participants **204a** to **204j** (i.e., a first set of sporting event elements) and a second team of sporting event participants **206a** to **206k** (i.e., a second set of sporting event elements) are each lined up on the displayed game field **200** (e.g., the football field).

[0031] In certain embodiments, the sporting event display condition is satisfied and the gaming system displays the sporting event upon a placement of a sporting event wager associated with an outcome of the sporting event (e.g., Team X will win the game), and/or a sporting event wager associated with an outcome of a sporting event which accounts for a point spread (e.g., Team X will win the game by ten points). In certain embodiments, the sporting event display condition is satisfied and the gaming system displays the sporting event upon an input received to place a sporting event wager associated with an in-game event, such as a wager placed on an event occurring (or not occurring) within the sporting event (e.g., Player A will make the next free throw or Team X will pass on the next play). In certain embodiments, the sporting event display condition is satisfied and the gaming system displays the sporting event upon a placement of a wager on a game (such as a game of chance or a game of skill) associated with an opportunity to win the progressive award. In certain embodiments, the sporting event display condition is satisfied and the gaming system displays the sporting event upon receipt of an input to display the sporting event. In certain embodiments, the sporting event display condition is satisfied and the gaming system displays the sporting event upon a determination by the gaming system to display the sporting event to attract users to the gaming system.

[0032] In certain embodiments, the sporting event displayed includes a live sporting event, such as sporting event currently being played. In certain embodiments, the sporting event displayed includes a historical sporting event, such as a prerecorded sporting event, or a recreation of a prior sporting event. In these embodiments, to prevent players from determining an outcome of the historic sporting event prior to the play of the skill-based game, the gaming system masks or otherwise anonymizes certain of the identifying information associated with that sporting event, such as anonymizes identifying information about teams, historical team records, sporting event players, and/or historical sporting event player statistics. In certain embodiments, the displayed sporting event includes a virtual or electronic sport (“eSport”) event played by humans, by computer driven participants or by a mix of human and computer driven participants. As such, it should be appreciated that while described herein as modifying the amount of a progressive award based on one or more events occurring (or not occurring) during a live sporting event, the gaming system is operable to modify the amount of a progressive award based on one or more events occurring (or not occurring) during a non-live sporting event, such as a prerecorded sporting event or a recreation of a historical sporting event and/or an eSport event.

[0033] In addition to displaying a sporting event, the gaming system determines if a progressive award modification event has occurred based on an event in the displayed sporting event as indicated in diamond **106** of FIG. **1** That is, in determining whether or not to modify a progressive award, the gaming system determines whether or not an event occurred in a displayed sporting event.

[0034] In certain embodiments wherein the progressive award is associated with a sporting event, the progressive award modification event is associated with an action or event occurring in the sporting event. In these embodiments, the occurrence of the action or event (or the lack of the occurrence of the action or event) determine if the progressive award modification event has occurred. That is, rather than the gaming system modifying the progressive award independent of the displayed sporting event, the gaming system utilizes one or more aspects of the displayed sporting event to potentially modify the maintained progressive award. For example, if the progressive award is associated with a live football game being displayed **202**, the progressive award modifying action in the sporting event is the scoring of points and a 45 yard field goal is being attempted in the live football game being displayed, the gaming system determines if the progressive award modification event occurs based on the results of the attempted field goal. It should be appreciated that, as seen in FIG. **2B**, the display of the potential progressive award modification event is in addition to the gaming system displaying the current play of a poker game including a plurality of playing cards **208a** to **208c**.

[0035] In certain embodiments wherein the progressive award is associated with a sporting event, the progressive award modification event is associated with a series of actions or events occurring in the sporting event. In these embodiments, the occurrence of this series of actions or events (or the lack of the occurrence of these actions or events) determine if the progressive award modification event has occurred such that the gaming system utilizes multiple aspects of the displayed sporting event to potentially modify the maintained progressive award. For example, if the progressive award is associated with a baseball game and the series of events includes the throwing of three strikes in a row, the gaming system determines if the progressive award modification event occurs based on whether or not three strikes are thrown in a row (regardless of which baseball player on which baseball team or which combination of baseball players on which baseball team(s) contributed to throwing three strikes in a row).

[0036] In certain embodiments wherein the progressive award is associated with a plurality of sporting events, the progressive award modification event is associated with a series of actions or events occurring over a plurality of sporting events. In these embodiments, the occurrence of this series of actions or events (or the lack of the occurrence of these actions or events) determine if the progressive award modification event has occurred such that the gaming system utilizes multiple aspects of multiple sporting events to potentially modify the maintained progressive award. For example, if the progressive award is associated with each of the professional soccer games being played on a particular day and the series of events includes at least a designated quantity of goals being scored across each of the games being played on that particular day, the gaming system determines if the progressive award modification event occurs based on whether or not the designated quantity of goals were scored (regardless of which soccer players on which soccer team or which combination of soccer players on which soccer team(s) contributed to scoring the designated quantity of goals).

[0037] In certain embodiments wherein the progressive award is associated with one or more sports teams, the progressive award modification event is associated with an action or event occurring in a sporting event by the one or more sports teams. In these embodiments, the occurrence of the action or event (or the lack of the occurrence of the action or event) in association with one or more particular sports teams (and not in association with any other sports teams) determine if the progressive award modification event has occurred. That is, rather than the gaming system modifying the progressive award independent of the displayed sporting event, the gaming system

utilizes one or more sports team specific aspects of a sporting event to potentially modify the maintained progressive award. For example, if the progressive award is associated with the first team of a live football game, the progressive award modifying action in the sporting event is the first team obtaining a first down by running the football, the gaming system determines if the progressive award modification event occurs based on whether or not the first team runs the football for a first down.

[0038] In certain embodiments wherein the progressive award is associated with one or more sports teams, the progressive award modification event is associated with a series of actions or events occurring by the one or more sports teams in the sporting event. In these embodiments, the occurrence of this series of actions or events (or the lack of the occurrence of these actions or events) in association with one or more particular sports teams (and not in association with any other sports teams) determine if the progressive award modification event has occurred such that the gaming system utilizes multiple sports team aspects of the displayed sporting event to potentially modify the maintained progressive award. For example, if the progressive award is associated with a particular baseball team of a baseball game and the series of events includes that sports team obtaining three hits in a row, the gaming system determines if the progressive award modification event occurs based on whether or not that particular baseball team obtained three hits in a row.

[0039] In certain embodiments wherein the progressive award is associated with one or more sports teams, the progressive award modification event is associated with a series of actions or events occurring by the one or more sports teams over a plurality of sporting events. In these embodiments, the occurrence of this series of actions or events (or the lack of the occurrence of these actions or events) in association with one or more particular sports teams over the multiple sporting events (and not in association with any other sports teams over the multiple sporting events) determine if the progressive award modification event has occurred such that the gaming system utilizes multiple sports team aspects of multiple sporting events to potentially modify the maintained progressive award. For example, if the progressive award is associated with each of the home hockey teams for the hockey games being played on a particular day and the series of events includes at least a designated quantity of goals being scored by the home teams across each of the games being played on that particular day, the gaming system determines if the progressive award modification event occurs based on whether or not the designated quantity of goals were scored.

[0040] In certain embodiments wherein the progressive award is associated with one or more particular sporting event participants, the progressive award modification event is associated with an action or event occurring by that/those particular sporting event participants in a sporting event. In these embodiments, the occurrence of the action or event (or the lack of the occurrence of the action or event) in association with that/those particular sporting event participants (and not by any other sporting event participants) determine if the progressive award modification event has occurred. That is, rather than the gaming system modifying the progressive award independent of a sporting event, the gaming system utilizes one or more sporting event participant specific aspects of the sporting event to potentially modify the maintained progressive award. For example, if the progressive award is associated with an individual football player of a live football game and the progressive award modifying action is that individual football player advancing the ball more than three yards during a single play, the gaming system determines if the progressive award modification event occurs based on whether or not that individual football player advanced the ball more than three yards during a single play.

[0041] In certain embodiments wherein the progressive award is associated with one or more particular sporting event participants, the progressive award modification event is associated with a series of actions or events occurring by that/those particular sporting event participants in a sporting event. In these embodiments, the occurrence of this series of actions or events (or the lack of the occurrence of these actions or events) in association with that/those particular sporting event

participants (and not by any other sporting event participants) determine if the progressive award modification event has occurred such that the gaming system utilizes multiple sporting event participant specific aspects of a sporting event to potentially modify the maintained progressive award. For example, if the progressive award is associated with a particular pitcher of a baseball game and the series of events includes that particular pitcher throwing of two strikes in a row, the gaming system determines if the progressive award modification event occurs based on whether or not that particular pitcher threw two strikes in a row.

[0042] In certain embodiments wherein the progressive award is associated with one or more particular sporting event participants, the progressive award modification event is associated with a series of actions or events by that/those particular sporting event participants occurring over a plurality of sporting events. In these embodiments, the occurrence of this series of actions or events (or the lack of the occurrence of these actions or events) in association with that/those particular sporting event participants (and not by any other sporting event participants) determine if the progressive award modification event has occurred such that the gaming system utilizes multiple sporting event participant aspects of multiple sporting events to potentially modify the maintained progressive award. For example, if the progressive award is associated with each of centers on the roster of a basketball team and the series of events includes a designated quantity of blocks made by those centers over the course of five basketball games played, the gaming system determines if the progressive award modification event occurs based on whether or not the collection of the centers on the roster of the basketball team made the designated quantity of blocks over the course of five basketball games played.

[0043] It should be appreciated that any suitable configuration of associating sporting events, sports teams and/or sporting event participants with one or more progressive award modification events may be employed in association with the gaming system disclosed herein. It should be further appreciated that any suitable action (or inaction) or any suitable combination of actions (or inactions) occurring in any suitable sporting event may be employed in determining whether one or more progressive award modification events occur in association with the gaming system disclosed herein.

[0044] Returning to FIG. 1, if the gaming system determines that a progressive award modification event occurred based on an event in the displayed sporting event, the gaming system modifies the maintained progressive award as indicated in block **108** of FIG. 1. In these embodiments, the occurrence of an event (or the lack of the occurrence of the event) in the sporting event causes the gaming system to modify, such as increase, the value of the progressive award. For example, as seen in FIG. 2C, upon determining that the attempted 45 yard field goal in the live football game was good (i.e., the progressive award modification event occurred), the gaming system increased the value of the progressive award from \$1248.15 to \$1252.65.

[0045] In certain embodiments, each occurrence of a progressive award modification event results in the same modification amount of the progressive award. For example, if the progressive award is associated with a baseball game and a progressive award modification event occurs whenever a hit occurs in the baseball game, then whenever a current batter gets a hit, the gaming system increments the associated progressive award by \$1 regardless of the type of hit. In different embodiments, different occurrences of the same progressive award modification event result in different modification amounts of the progressive award. For example, if the progressive award is associated with a baseball game and a progressive award modification event occurs whenever a hit occurs in the baseball game, then a current batter hitting a single results in an increment of the associated progressive award by \$1, the current batter hitting a double results in an increment of the associated progressive award by \$2, the current batter hitting a triple results in an increment of the associated progressive award by \$3, and the current batter hitting a home run results in an increment of the associated progressive award by \$4.

[0046] In certain embodiments, different progressive award modification events results in the same

modification amount of the progressive award. For example, if the progressive award is associated with a football game, a first progressive award modification event occurs whenever a first down occurs in the football game and a second progressive award modification event occurs whenever a turnover occurs in the football game, then when either a first down occurs in the football game (i.e., the first progressive award modification event occurs) or a turnover occurs in the football game (i.e., the second progressive award modification event occurs), the gaming system increments the associated progressive award by \$0.50. In different embodiments, occurrences of different progressive award modification events result in different modification amounts of the progressive award. For example, if the progressive award is associated with a football game, a first progressive award modification event occurs whenever a first down occurs in the football game and a second progressive award modification event occurs whenever a turnover occurs in the football game, then when a first down occurs in the football game (i.e., the first progressive award modification event occurs), the gaming system increments the associated progressive award by \$0.50 and when a turnover occurs in the football game (i.e., the second progressive award modification event occurs), the gaming system increments the associated progressive award by \$2.00.

[0047] In certain embodiments, certain conditions of the sporting event are utilized to determine an amount to modify the progressive award. For example, the gaming system accounts for the field position of the ball of a live football game (e.g., as seen in FIG. 2C, the length of the made field goal determines the amount contributed to the progressive award), and/or the weather conditions of the live football game (e.g., a completed pass made in rainy conditions is associated with a larger contribution to the progressive award than the same completed pass made in sunny conditions) in determining an amount to modify the progressive award.

[0048] In certain embodiments, the occurrence of the progressive award modification event is conditional on the player having placed a sporting event wager on the displayed sporting event. In certain embodiments, the occurrence of the progressive award modification event is independent of the player having placed a sporting event wager on the displayed sporting event. In certain embodiments, the occurrence of the progressive award modification event is conditional on one or more parameters of the sporting event. For example, prior to determining to increase a progressive award associated with the player's favorite baseball team (as indicated by the player or determined in association with a player tracking system which maintains a player tracking account associated with the player), that baseball team must first be batting in the sporting event. In certain embodiments, the occurrence of the progressive award modification event is independent of any parameters of the sporting event.

[0049] In certain embodiments wherein the progressive award is associated with a particular sports team and/or sporting event participant, the progressive award modification event occurs in association with that particular sports team and/or sporting event participant. In these embodiments, the gaming system modifies the progressive award associated with the particular sports team and/or sporting event participant based on a particular action by that sports team and/or sporting event participant in the sporting event. For example, if a progressive award is associated with a particular basketball player scoring points in a game, then the progressive award modification event occurs each time that basketball player scores one or more points (but does not occur when any teammate of that particular basketball player scores any points).

[0050] In certain embodiments, if the progressive award modification event does not occur, the gaming system does not modify the progressive award. In these embodiments, the lack of the occurrence of an event (or the occurrence of the event) in the sporting event causes the gaming system not to modify the value of the progressive award. For example, upon determining that the attempted 45 yard field goal in the live football game was missed (i.e., the progressive award modification event did not occur), the gaming system maintains the current value of the progressive award. In certain embodiments, a negative event in the sporting event (or the lack of occurrence of an event in the sporting event) result in a negative modification of a progressive award. For

example, upon determining that the attempted 45 yard field goal in the live football game was not good, the gaming system decreases the value of the progressive award.

[0051] Following the modification of the progressive award based on an event in the displayed sporting event or if the gaming system determines that a progressive award modification event did not occur based on an event in the displayed sporting event, the gaming system determines if a progressive award triggering event occurs as indicated in diamond **110** of FIG. **1**. In certain embodiments, the progressive award triggering event occurs based on a displayed event associated with a play of a game and/or a sporting event. In certain embodiments, the progressive award triggering event occurs based on an event independent of any displayed event associated with a play of a game and/or a sporting event.

[0052] If the gaming system determines that a progressive award triggering event occurred, the gaming system provides the maintained progressive award as indicated in block **112**. On the other hand, if the gaming system determines that the progressive award triggering event did not occur, the gaming system returns to diamond **106** of FIG. **1** and continues monitoring for an occurrence of another progressive award modification event.

[0053] In certain embodiments wherein the progressive award is associated with one or more sporting events, the gaming system causes a progressive award triggering event to occur in association with the conclusion of the play of the one or more sporting events. For example, at the end of a professional tennis match associated with a progressive award, the gaming system selects a player, such as a player that placed a sporting event wager on the winner of the professional tennis match, to win the progressive award. In certain embodiments wherein the progressive award is associated with a sporting event, the gaming system causes a progressive award triggering event to occur in association with the conclusion of a portion of the sporting event. For example, at the end of each quarter of a professional football game associated with a progressive award, the gaming system enables a plurality of players to participate in a competitive community game wherein the winner of the competitive community game wins the progressive award. In these embodiments, the gaming system maintains the progressive award during such sporting events, grows the progressive award based on events occurring in the sporting events, and then provides the progressive award upon the conclusion of such sporting events.

[0054] In certain embodiments wherein the progressive award is associated with one or more sporting events, if the gaming system determines that no progressive award triggering event occurred in association with the conclusion of the play of the one or more sporting events, the gaming system rolls the amount of the progressive award into another progressive award associated with another sporting event. In certain embodiments wherein the progressive award is associated with a sporting event, if the gaming system determines that no progressive award triggering event occurred in association with the conclusion of a portion of the sporting event, the gaming system rolls the amount of the progressive award into another progressive award associated with either another portion of the same sporting event or another sporting event.

[0055] In certain embodiments, certain conditions of the sporting event are utilized to determine whether a progressive award modification event and/or a progressive award triggering event occur. For example, if a progressive award is associated with a specific football team, that football team needs to satisfy one or more conditions in the sporting event, such as have possession of the ball, be leading in time of possession, and/or have the least amount of penalties, for a progressive award modification event and/or a progressive award triggering event to be able to occur in association with that progressive award.

[0056] In certain embodiments, the modification of the progressive award based on one or more events occurring (or not occurring) in a sporting event is funded, at least partially, via an amount provided by one or more marketing and/or advertising departments, such as a casino's marketing department. In certain embodiments, the modification of the progressive award based on one or more events occurring (or not occurring) in a sporting event is additionally or alternatively funded,

at least in part, based on an amount provided by a gaming establishment. In another embodiment, the modification of the progressive award based on one or more events occurring (or not occurring) in a sporting event is additionally or alternatively funded, at least in part, based on one or more wagers placed on one or more plays of one or more games associated with the progressive award. In certain embodiments, the modification of the progressive award based on one or more events occurring (or not occurring) in a sporting event is additionally or alternatively funded, at least in part, based on one or more side wagers placed. It should be appreciated that the modification of the progressive award based on one or more events occurring (or not occurring) in a sporting event may be funded via any suitable manner.

[0057] In certain embodiments, in addition to modifying the progressive award based on one or more events occurring (or not occurring) in a sporting event, the gaming system modifies the progressive award based on wagers placed on games associated with the progressive award. That is, the gaming system grows the progressive award based on a small percentage (such as 0.1%) of coin-in or wagered amounts on one or more plays of one or more games associated with the progressive award. In another embodiment, the percentages of wagered amounts that go to a progressive award for different wager amounts are different. For example, a wager of one to twenty-five credits increments a progressive award. 1% of the wager, a wager of twenty-six to fifty credits increments a progressive award 0.08% of the wager and a wager of fifty-one to seventy-five credits increments a progressive award 0.07% of the wager.

[0058] In different embodiments, the progressive awards maintained by the system and increased based on the occurrence of zero, one or more events of a sporting event include, but are not limited to, one or more of: a quantity of monetary credits, a quantity of non-monetary credits, a quantity of promotional credits, a quantity of player tracking points, a modifier, such as a multiplier, a quantity of free plays of one or more games, a quantity of plays of one or more secondary or bonus games, a multiplier of a quantity of free plays of a game, and/or a quantity of lottery or drawing tickets.

[0059] In different embodiments, a progressive award modification event, and/or a progressive award triggering event occurs based on an outcome associated with one or more plays of any primary games. In one embodiment, such determinations are symbol driven based on the generation of one or more designated symbols or symbol combinations. In various embodiments, a generation of a designated symbol (or sub-symbol) or a designated set of symbols (or sub-symbols) over one or more plays of a primary game causes such conditions to be satisfied and/or one or more of such events to occur.

[0060] In various embodiments, the gaming system employs any suitable game (including a wagering game and/or a non-wagering game) in determining if a progressive award triggering event occurs. In different embodiments, such plays of a game includes, but are not limited to: a play of any suitable video or mechanical slot or reel game; a play of any suitable card game, such as but not limited to any suitable poker game, any suitable blackjack game, or any suitable Baccarat game; a play of any suitable keno game; a play of any suitable bingo game; a play of any suitable table game (whether or not such table game is occurring at a gaming table); a play of any suitable wheel game; a play of any suitable offer and acceptance game; a play of any suitable award ladder game; a play of any suitable puzzle-type game; a play of any suitable persistence game; a play of any suitable selection game; a play of any suitable cascading symbols game; a play of any suitable ways to win game; a play of any suitable scatter pay game; a play of any suitable coin-pusher game; a play of any suitable elimination game; a play of any suitable stacked wilds game; a play of any suitable trail game; a play of any suitable bingo game; a play of any suitable video scratch-off game; a play of any suitable pick-until-complete game; a play of any suitable shooting simulation game; a play of any suitable racing game; a play of any suitable promotional game; a play of any suitable high-low game; a play of any suitable lottery game; a play of any suitable number selection game; a play of any suitable dice game; a play of any suitable skill game; a play of any suitable auction game; a play of any suitable reverse-auction game; and/or a play of any suitable group

game.

[0061] In different embodiments, the gaming system does not provide any apparent reasons to the players for an occurrence of a progressive award modification event, and/or a progressive award triggering event. In these embodiments, such determinations are not triggered by an event in a primary game or based specifically on any of the plays of any primary games. That is, these events occur without any explanation or alternatively with simple explanations.

[0062] In one such embodiment, a progressive award modification event, and/or a progressive award triggering event occurs based on an amount of coin-in. In this embodiment, the gaming system determines if an amount of coin-in reaches or exceeds a designated amount of coin-in (i.e., a threshold coin-in amount). Upon the amount of coin-in wagered reaching or exceeding the threshold coin-in amount, the gaming system causes one or more of such events or conditions to occur. In another such embodiment, a progressive award modification event, and/or a progressive award triggering event occurs based on an amount of virtual currency-in. In this embodiment, the gaming system determines if an amount of virtual currency-in wagered reaches or exceeds a designated amount of virtual currency-in (i.e., a threshold virtual currency-in amount). Upon the amount of virtual currency-in wagered reaching or exceeding the threshold virtual currency-in amount, the gaming system causes one or more of such events or conditions to occur. In different embodiments, the threshold coin-in amount and/or the threshold virtual currency-in amount is predetermined, randomly determined, determined based on a player's status (such as determined through a player tracking system), determined based on a generated symbol or symbol combination, determined based on a random determination by the central controller, determined based on a random determination at the gaming system, determined based on one or more side wagers placed, determined based on the player's primary game wager, determined based on time (such as the time of day) or determined based on any other suitable method or criteria.

[0063] In one such embodiment, a progressive award modification event, and/or a progressive award triggering event occurs based on an amount of coin-out. In this embodiment, the gaming system determines if an amount of coin-out reaches or exceeds a designated amount of coin-out (i.e., a threshold coin-out amount). Upon the amount of coin-out reaching or exceeding the threshold coin-out amount, the gaming system causes one or more of such events or conditions to occur. In another such embodiment, a progressive award modification event, and/or a progressive award triggering event occurs based on an amount of virtual currency-out. In this embodiment, the gaming system determines if an amount of virtual currency-out reaches or exceeds a designated amount of virtual currency-out (i.e., a threshold virtual currency-out amount). Upon the amount of virtual currency-out reaching or exceeding the threshold virtual currency-out amount, the gaming system causes one or more of such events or conditions to occur. In different embodiments, the threshold coin-out amount and/or the threshold virtual currency-out amount is predetermined, randomly determined, determined based on a player's status (such as determined through a player tracking system), determined based on a generated symbol or symbol combination, determined based on a random determination by the central controller, determined based on a random determination at the gaming system, determined based on one or more side wagers placed, determined based on the player's primary game wager, determined based on time (such as the time of day) or determined based on any other suitable method or criteria.

[0064] In different embodiments, a progressive award modification event, and/or a progressive award triggering event occurs based on a predefined variable reaching a defined parameter threshold. For example, when the 500,000th player has played an electronic gaming machine ("EGM") (ascertained from a player tracking system), one or more of such events or conditions occur. In another example, when the 5000th game has been played on an EGM, one or more of such events or conditions occur. In different embodiments, the predefined parameter thresholds include a length of time, a length of time after a certain dollar amount is hit, a wager level threshold for a specific device (which EGM is the first to contribute \$250,000), a number of EGMs active, or

any other parameter that defines a suitable threshold.

[0065] In different embodiments, a progressive award modification event, and/or a progressive award triggering event occurs based on a quantity of games played. In this embodiment, a quantity of games played is set for when one or more of such events or conditions will occur. In one embodiment, such a set quantity of games played is based on historic data.

[0066] In different embodiments, a progressive award modification event, and/or a progressive award triggering event occurs based on time. In this embodiment, a time is set for when one or more of such events or conditions will occur. In one embodiment, such a set time is based on historic data.

[0067] In different embodiments, a progressive award modification event, and/or a progressive award triggering event occurs based upon gaming system operator defined player eligibility parameters stored on a player tracking system (such as via a player tracking card or other suitable manner). In this embodiment, the parameters for eligibility are defined by the gaming system operator based on any suitable criterion. In one embodiment, the gaming system recognizes the player's identification (via the player tracking system) when the player inserts or otherwise associates their player tracking card in the EGM and/or logs into the player tracking system using a mobile device, such as a personal gaming device. The gaming system determines the player tracking level of the player and if the current player tracking level defined by the gaming system operator is eligible for one or more of such events or conditions. In one embodiment, the gaming system operator defines minimum bet levels required for such events or conditions to occur based on the player's card level.

[0068] In different embodiments, a progressive award modification event, and/or a progressive award triggering event occurs based on a system determination, including one or more random selections by the central controller. For example, as described above, the gaming system tracks all active EGMs and the wagers they placed, wherein based on the EGM's state as well as one or more wager pools associated with the EGM, the gaming system determines whether to one or more of such events or conditions will occur. In one such embodiment, the player who consistently places a higher wager is more likely to be associated with an occurrence of one or more of such events or conditions than a player who consistently places a minimum wager. It should be appreciated that the criteria for determining whether a player is in active status or inactive status for determining if one or more of such events occur may be the same as, substantially the same as, or different than the criteria for determining whether a player is in active status or inactive status for another one of such events to occur.

[0069] In different embodiments, a progressive award modification event, and/or a progressive award triggering event occurs based on a determination of if any numbers allotted to an EGM match a randomly selected number. In this embodiment, upon or prior to each play of each EGM, an EGM selects a random number from a range of numbers and during each primary game, the EGM allocates the first N numbers in the range, where N is the number of credits bet by the player in that primary game. At the end of the primary game, the randomly selected number is compared with the numbers allocated to the player and if a match occurs, one or more of such events or conditions occur.

[0070] It should be appreciated that any suitable manner of causing a progressive award modification event, and/or a progressive award triggering event to occur may be implemented in accordance with the gaming system and method disclosed herein. It should be further appreciated that one or more of the above-described triggers occurring may be combined in one or more different embodiments. It should be additionally appreciated that in alternative embodiments, an occurrence of a progressive award modification event and/or a progressive award triggering event result in a modification of the chances of a progressive award modification event and/or a progressive award triggering event subsequently occurring.

[0071] In one embodiment, the gaming system causes at least one display device of the gaming

system to display the sporting event and/or the progressive award modified based on the occurrences of zero, one or more events of the sporting event. In another embodiment, the gaming system additionally or alternatively causes one or more community or overhead display devices to display part or all of the sporting event and/or the progressive award modified based on the occurrences of zero, one or more events of the sporting event to one or more other players or bystanders either at a gaming establishment or viewing over a network, such as the internet. In another embodiment, the gaming system additionally or alternatively causes one or more internet sites to each display the sporting event and/or the progressive award modified based on the occurrences of zero, one or more events of the sporting event such that a player is enabled to log on from a personal web browser.

[0072] In different embodiments, the gaming system disclosed herein modifies an amount of a lottery pool based on or otherwise influenced by a sporting event. In certain embodiments, one or more of the progressive award modification events disclosed herein which occur based on an event in a sporting event cause a lottery pool to increase. In certain embodiments, one or more wagers placed in association with a sporting event cause a lottery pool to increase. In certain of these embodiments, the lottery pool which is influenced by one or more sporting events includes a secondary lottery pool wherein a player winning a lottery results in that player winning an amount from a primary lottery pool plus an amount from the secondary lottery pool if that player also placed a wager in association with a sporting event.

Alternative Embodiments

[0073] It should be appreciated that in different embodiments, one or more of: [0074] i. when a sporting event display condition is satisfied; [0075] ii. which available sporting events to display; [0076] iii. whether to utilize a historic sporting event, a live sporting event and/or a future sporting event; [0077] iv. a quantity of available sporting events to display; [0078] v. which progressive awards to maintain; [0079] vi. which sporting event(s), sports team(s) and/or sporting event participant(s) to associate with a progressive award; [0080] vii. when a progressive award modification event occurs; [0081] viii. which event(s) or non-event(s) of which sporting events are associated with a progressive award modification event; [0082] ix. an amount to modify a progressive award upon an occurrence of a progressive award modification event; [0083] X. when a progressive award triggering event occurs; and/or [0084] xi. any determination disclosed herein; [0085] is/are predetermined, randomly determined, randomly determined based on one or more weighted percentages, determined based on a generated symbol or symbol combination, determined independent of a generated symbol or symbol combination, determined based on a random determination by the central controller, determined independent of a random determination by the central controller, determined based on a random determination at the gaming system, determined independent of a random determination at the gaming system, determined based on at least one play of at least one game, determined independent of at least one play of at least one game, determined based on a player's selection, determined independent of a player's selection, determined based on one or more side wagers placed, determined independent of one or more side wagers placed, determined based on the player's primary game wager, determined independent of the player's primary game wager, determined based on time (such as the time of day), determined independent of time (such as the time of day), determined based on an amount of coin-in accumulated in one or more pools, determined independent of an amount of coin-in accumulated in one or more pools, determined based on a status of the player (i.e., a player tracking status), determined independent of a status of the player (i.e., a player tracking status), determined based on one or more other determinations disclosed herein, determined independent of any other determination disclosed herein or determined based on any other suitable method or criteria.

Gaming Systems

[0086] The above-described embodiments of the present disclosure may be implemented in accordance with or in conjunction with one or more of a variety of different types of gaming

systems, such as, but not limited to, those described below.

[0087] The present disclosure contemplates a variety of different gaming systems each having one or more of a plurality of different features, attributes, or characteristics. A “gaming system” as used herein refers to various configurations of: (a) one or more central servers, central controllers, or remote hosts; (b) one or more electronic gaming machines such as those located on a casino floor; and/or (c) one or more personal gaming devices, such as desktop computers, laptop computers, tablet computers or computing devices, personal digital assistants, mobile phones, and other mobile computing devices.

[0088] Thus, in various embodiments, the gaming system of the present disclosure includes: (a) one or more electronic gaming machines in combination with one or more central servers, central controllers, or remote hosts; (b) one or more personal gaming devices in combination with one or more central servers, central controllers, or remote hosts; (c) one or more personal gaming devices in combination with one or more electronic gaming machines; (d) one or more personal gaming devices, one or more electronic gaming machines, and one or more central servers, central controllers, or remote hosts in combination with one another; (e) a single electronic gaming machine; (f) a plurality of electronic gaming machines in combination with one another; (g) a single personal gaming device; (h) a plurality of personal gaming devices in combination with one another; (i) a single central server, central controller, or remote host; and/or (j) a plurality of central servers, central controllers, or remote hosts in combination with one another.

[0089] For brevity and clarity and unless specifically stated otherwise, the term “EGM” is used herein to refer to an electronic gaming machine (such as a slot machine, a video poker machine, a video lottery terminal (VLT), a terminal associated with an electronic table game, a video keno machine, or a video bingo machine located on a casino floor). Additionally, for brevity and clarity and unless specifically stated otherwise, “EGM” as used herein represents one EGM or a plurality of EGMs, “personal gaming device” as used herein represents one personal gaming device or a plurality of personal gaming devices, and “central server, central controller, or remote host” as used herein represents one central server, central controller, or remote host or a plurality of central servers, central controllers, or remote hosts.

[0090] As noted above, in various embodiments, the gaming system includes an EGM (or personal gaming device) in combination with a central server, central controller, or remote host. In such embodiments, the EGM (or personal gaming device) is configured to communicate with the central server, central controller, or remote host through a data network or remote communication link. In certain such embodiments, the EGM (or personal gaming device) is configured to communicate with another EGM (or personal gaming device) through the same data network or remote communication link or through a different data network or remote communication link. For example, the gaming system includes a plurality of EGMs that are each configured to communicate with a central server, central controller, or remote host through a data network.

[0091] In certain embodiments in which the gaming system includes an EGM (or personal gaming device) in combination with a central server, central controller, or remote host, the central server, central controller, or remote host is any suitable computing device (such as a server) that includes at least one processor and at least one memory device or data storage device. As further described herein, the EGM (or personal gaming device) includes at least one EGM (or personal gaming device) processor configured to transmit and receive data or signals representing events, messages, commands, or any other suitable information between the EGM (or personal gaming device) and the central server, central controller, or remote host. The at least one processor of that EGM (or personal gaming device) is configured to execute the events, messages, or commands represented by such data or signals in conjunction with the operation of the EGM (or personal gaming device). Moreover, the at least one processor of the central server, central controller, or remote host is configured to transmit and receive data or signals representing events, messages, commands, or any other suitable information between the central server, central controller, or remote host and the

EGM (or personal gaming device). The at least one processor of the central server, central controller, or remote host is configured to execute the events, messages, or commands represented by such data or signals in conjunction with the operation of the central server, central controller, or remote host. One, more than one, or each of the functions of the central server, central controller, or remote host may be performed by the at least one processor of the EGM (or personal gaming device). Further, one, more than one, or each of the functions of the at least one processor of the EGM (or personal gaming device) may be performed by the at least one processor of the central server, central controller, or remote host.

[0092] In certain such embodiments, computerized instructions for controlling any games (such as any primary or base games and/or any secondary or bonus games) displayed by the EGM (or personal gaming device) are executed by the central server, central controller, or remote host. In such “thin client” embodiments, the central server, central controller, or remote host remotely controls any games (or other suitable interfaces) displayed by the EGM (or personal gaming device), and the EGM (or personal gaming device) is utilized to display such games (or suitable interfaces) and to receive one or more inputs or commands. In other such embodiments, computerized instructions for controlling any games displayed by the EGM (or personal gaming device) are communicated from the central server, central controller, or remote host to the EGM (or personal gaming device) and are stored in at least one memory device of the EGM (or personal gaming device). In such “thick client” embodiments, the at least one processor of the EGM (or personal gaming device) executes the computerized instructions to control any games (or other suitable interfaces) displayed by the EGM (or personal gaming device).

[0093] In various embodiments in which the gaming system includes a plurality of EGMs (or personal gaming devices), one or more of the EGMs (or personal gaming devices) are thin client EGMs (or personal gaming devices) and one or more of the EGMs (or personal gaming devices) are thick client EGMs (or personal gaming devices). In other embodiments in which the gaming system includes one or more EGMs (or personal gaming devices), certain functions of one or more of the EGMs (or personal gaming devices) are implemented in a thin client environment, and certain other functions of one or more of the EGMs (or personal gaming devices) are implemented in a thick client environment. In one such embodiment in which the gaming system includes an EGM (or personal gaming device) and a central server, central controller, or remote host, computerized instructions for controlling any primary or base games displayed by the EGM (or personal gaming device) are communicated from the central server, central controller, or remote host to the EGM (or personal gaming device) in a thick client configuration, and computerized instructions for controlling any secondary or bonus games or other functions displayed by the EGM (or personal gaming device) are executed by the central server, central controller, or remote host in a thin client configuration.

[0094] In certain embodiments in which the gaming system includes: (a) an EGM (or personal gaming device) configured to communicate with a central server, central controller, or remote host through a data network; and/or (b) a plurality of EGMs (or personal gaming devices) configured to communicate with one another through a data network, the data network is a local area network (LAN) in which the EGMs (or personal gaming devices) are located substantially proximate to one another and/or the central server, central controller, or remote host. In one example, the EGMs (or personal gaming devices) and the central server, central controller, or remote host are located in a gaming establishment or a portion of a gaming establishment.

[0095] In other embodiments in which the gaming system includes: (a) an EGM (or personal gaming device) configured to communicate with a central server, central controller, or remote host through a data network; and/or (b) a plurality of EGMs (or personal gaming devices) configured to communicate with one another through a data network, the data network is a wide area network (WAN) in which one or more of the EGMs (or personal gaming devices) are not necessarily located substantially proximate to another one of the EGMs (or personal gaming devices) and/or the central

server, central controller, or remote host. For example, one or more of the EGMs (or personal gaming devices) are located: (a) in an area of a gaming establishment different from an area of the gaming establishment in which the central server, central controller, or remote host is located; or (b) in a gaming establishment different from the gaming establishment in which the central server, central controller, or remote host is located. In another example, the central server, central controller, or remote host is not located within a gaming establishment in which the EGMs (or personal gaming devices) are located. In certain embodiments in which the data network is a WAN, the gaming system includes a central server, central controller, or remote host and an EGM (or personal gaming device) each located in a different gaming establishment in a same geographic area, such as a same city or a same state. Gaming systems in which the data network is a WAN are substantially identical to gaming systems in which the data network is a LAN, though the quantity of EGMs (or personal gaming devices) in such gaming systems may vary relative to one another. [0096] In further embodiments in which the gaming system includes: (a) an EGM (or personal gaming device) configured to communicate with a central server, central controller, or remote host through a data network; and/or (b) a plurality of EGMs (or personal gaming devices) configured to communicate with one another through a data network, the data network is an internet (such as the Internet) or an intranet. In certain such embodiments, an Internet browser of the EGM (or personal gaming device) is usable to access an Internet game page from any location where an Internet connection is available. In one such embodiment, after the EGM (or personal gaming device) accesses the Internet game page, the central server, central controller, or remote host identifies a player before enabling that player to place any wagers on any plays of any wagering games. In one example, the central server, central controller, or remote host identifies the player by requiring a player account of the player to be logged into via an input of a unique username and password combination assigned to the player. The central server, central controller, or remote host may, however, identify the player in any other suitable manner, such as by validating a player tracking identification number associated with the player; by reading a player tracking card or other smart card inserted into a card reader (as described below); by validating a unique player identification number associated with the player by the central server, central controller, or remote host; or by identifying the EGM (or personal gaming device), such as by identifying the MAC address or the IP address of the Internet facilitator. In various embodiments, once the central server, central controller, or remote host identifies the player, the central server, central controller, or remote host enables placement of one or more wagers on one or more plays of one or more primary or base games and/or one or more secondary or bonus games, and displays those plays via the Internet browser of the EGM (or personal gaming device). Examples of implementations of Internet-based gaming are further described in U.S. Pat. No. 8,764,566, entitled "Internet Remote Game Server," and U.S. Pat. No. 8,147,334, entitled "Universal Game Server".

[0097] The central server, central controller, or remote host and the EGM (or personal gaming device) are configured to connect to the data network or remote communications link in any suitable manner. In various embodiments, such a connection is accomplished via: a conventional phone line or other data transmission line, a digital subscriber line (DSL), a T-1 line, a coaxial cable, a fiber optic cable, a wireless or wired routing device, a mobile communications network connection (such as a cellular network or mobile Internet network), or any other suitable medium. The expansion in the quantity of computing devices and the quantity and speed of Internet connections in recent years increases opportunities for players to use a variety of EGMs (or personal gaming devices) to play games from an ever-increasing quantity of remote sites. Additionally, the enhanced bandwidth of digital wireless communications may render such technology suitable for some or all communications, particularly if such communications are encrypted. Higher data transmission speeds may be useful for enhancing the sophistication and response of the display and interaction with players.

EGM Components

[0098] FIG. 3 is a block diagram of an example EGM **1000** and FIGS. 4A and 4B include two different example EGMs **2000a** and **2000b**. The EGMs **1000**, **2000a**, and **2000b** are merely example EGMs, and different EGMs may be implemented using different combinations of the components shown in the EGMs **1000**, **2000a**, and **2000b**. Although the below refers to EGMs, in various embodiments personal gaming devices (such as personal gaming device **2000c** of FIG. 4C) may include some or all of the below components.

[0099] In these embodiments, the EGM **1000** includes a master gaming controller **1012** configured to communicate with and to operate with a plurality of peripheral devices **1022**.

[0100] The master gaming controller **1012** includes at least one processor **1010**. The at least one processor **1010** is any suitable processing device or set of processing devices, such as a microprocessor, a microcontroller-based platform, a suitable integrated circuit, or one or more application-specific integrated circuits (ASICs), configured to execute software enabling various configuration and reconfiguration tasks, such as: (1) communicating with a remote source (such as a server that stores authentication information or game information) via a communication interface **1006** of the master gaming controller **1012**; (2) converting signals read by an interface to a format corresponding to that used by software or memory of the EGM; (3) accessing memory to configure or reconfigure game parameters in the memory according to indicia read from the EGM; (4) communicating with interfaces and the peripheral devices **1022** (such as input/output devices); and/or (5) controlling the peripheral devices **1022**. In certain embodiments, one or more components of the master gaming controller **1012** (such as the at least one processor **1010**) reside within a housing of the EGM (described below), while in other embodiments at least one component of the master gaming controller **1012** resides outside of the housing of the EGM.

[0101] The master gaming controller **1012** also includes at least one memory device **1016**, which includes: (1) volatile memory (e.g., RAM **1009**, which can include non-volatile RAM, magnetic RAM, ferroelectric RAM, and any other suitable forms); (2) non-volatile memory **1019** (e.g., disk memory, FLASH memory, EPROMs, EEPROMs, memristor-based non-volatile solid-state memory, etc.); (3) unalterable memory (e.g., EPROMs **1008**); (4) read-only memory; and/or (5) a secondary memory storage device **1015**, such as a non-volatile memory device, configured to store gaming software related information (the gaming software related information and the memory may be used to store various audio files and games not currently being used and invoked in a configuration or reconfiguration). Any other suitable magnetic, optical, and/or semiconductor memory may operate in conjunction with the EGM disclosed herein. In certain embodiments, the at least one memory device **1016** resides within the housing of the EGM (described below), while in other embodiments at least one component of the at least one memory device **1016** resides outside of the housing of the EGM. In these embodiments, any combination of one or more computer readable media may be utilized. The computer readable media may be a computer readable signal medium or a computer readable storage medium. A computer readable storage medium may be, for example, but not limited to, an electronic, magnetic, optical, electromagnetic, or semiconductor system, apparatus, or device, or any suitable combination of the foregoing. More specific examples (a non-exhaustive list) of the computer readable storage medium would include the following: a portable computer diskette, a hard disk, a random access memory (RAM), a read-only memory (ROM), an erasable programmable read-only memory (EPROM or Flash memory), an appropriate optical fiber with a repeater, a portable compact disc read-only memory (CD-ROM), an optical storage device, a magnetic storage device, or any suitable combination of the foregoing. In the context of this document, a computer readable storage medium may be any tangible medium that can contain, or store a program for use by or in connection with an instruction execution system, apparatus, or device.

[0102] A computer readable signal medium may include a propagated data signal with computer readable program code embodied therein, for example, in baseband or as part of a carrier wave. Such a propagated signal may take any of a variety of forms, including, but not limited to, electro-

magnetic, optical, or any suitable combination thereof. A computer readable signal medium may be any computer readable medium that is not a computer readable storage medium and that can communicate, propagate, or transport a program for use by or in connection with an instruction execution system, apparatus, or device. Program code embodied on a computer readable signal medium may be transmitted using any appropriate medium, including but not limited to wireless, wireline, optical fiber cable, RF, etc., or any suitable combination of the foregoing.

[0103] The at least one memory device **1016** is configured to store, for example: (1) configuration software **1014**, such as all the parameters and settings for a game playable on the EGM; (2) associations **1018** between configuration indicia read from an EGM with one or more parameters and settings; (3) communication protocols configured to enable the at least one processor **1010** to communicate with the peripheral devices **1022**; and/or (4) communication transport protocols (such as TCP/IP, USB, Firewire, IEEE1394, Bluetooth, IEEE 802.11x (IEEE 802.11 standards), hiperlan/2, HomeRF, etc.) configured to enable the EGM to communicate with local and non-local devices using such protocols. In one implementation, the master gaming controller **1012** communicates with other devices using a serial communication protocol. A few non-limiting examples of serial communication protocols that other devices, such as peripherals (e.g., a bill validator or a ticket printer), may use to communicate with the master game controller **1012** include USB, RS-232, and Netplex (a proprietary protocol developed by IGT).

[0104] As will be appreciated by one skilled in the art, aspects of the present disclosure may be illustrated and described herein in any of a number of patentable classes or context including any new and useful process, machine, manufacture, or composition of matter, or any new and useful improvement thereof. Accordingly, aspects of the present disclosure may be implemented entirely hardware, entirely software (including firmware, resident software, micro-code, etc.) or combining software and hardware implementation that may all generally be referred to herein as a “circuit,” “module,” “component,” or “system.” Furthermore, aspects of the present disclosure may take the form of a computer program product embodied in one or more computer readable media having computer readable program code embodied thereon.

[0105] Computer program code for carrying out operations for aspects of the present disclosure may be written in any combination of one or more programming languages, including an object oriented programming language such as Java, Scala, Smalltalk, Eiffel, JADE, Emerald, C++, C #, VB.NET, Python or the like, conventional procedural programming languages, such as the “C” programming language, Visual Basic, Fortran 2003, Perl, COBOL 2002, PHP, ABAP, dynamic programming languages such as Python, Ruby and Groovy, or other programming languages. The program code may execute entirely on the user's computer, partly on the user's computer, as a stand-alone software package, partly on the user's computer and partly on a remote computer or entirely on the remote computer or server. In the latter scenario, the remote computer may be connected to the user's computer through any type of network, including a local area network (LAN) or a wide area network (WAN), or the connection may be made to an external computer (for example, through the Internet using an Internet Service Provider) or in a cloud computing environment or offered as a service such as a Software as a Service (Saas).

[0106] Aspects of the present disclosure are described herein with reference to flowchart illustrations and/or block diagrams of methods, apparatuses (systems) and computer program products according to embodiments of the disclosure. It will be understood that each block of the flowchart illustrations and/or block diagrams, and combinations of blocks in the flowchart illustrations and/or block diagrams, can be implemented by computer program instructions. These computer program instructions may be provided to a processor of a general purpose computer, special purpose computer, or other programmable data processing apparatus to produce a machine, such that the instructions, which execute via the processor of the computer or other programmable instruction execution apparatus, create a mechanism for implementing the functions/acts specified in the flowchart and/or block diagram block or blocks.

[0107] These computer program instructions may also be stored in a computer readable medium that when executed can direct a computer, other programmable data processing apparatus, or other devices to function in a particular manner, such that the instructions when stored in the computer readable medium produce an article of manufacture including instructions which when executed, cause a computer to implement the function/act specified in the flowchart and/or block diagram block or blocks. The computer program instructions may also be loaded onto a computer, other programmable instruction execution apparatus, or other devices to cause a series of operational steps to be performed on the computer, other programmable apparatuses or other devices to produce a computer implemented process such that the instructions which execute on the computer or other programmable apparatus provide processes for implementing the functions/acts specified in the flowchart and/or block diagram block or blocks.

[0108] In certain embodiments, the at least one memory device **1016** is configured to store program code and instructions executable by the at least one processor of the EGM to control the EGM. The at least one memory device **1016** of the EGM also stores other operating data, such as image data, event data, input data, random number generators (RNGs) or pseudo-RNGs, payable data or information, and/or applicable game rules that relate to the play of one or more games on the EGM. In various embodiments, part or all of the program code and/or the operating data described above is stored in at least one detachable or removable memory device including, but not limited to, a cartridge, a disk, a CD ROM, a DVD, a USB memory device, or any other suitable non-transitory computer readable medium. In certain such embodiments, an operator (such as a gaming establishment operator) and/or a player uses such a removable memory device in an EGM to implement at least part of the present disclosure. In other embodiments, part or all of the program code and/or the operating data is downloaded to the at least one memory device of the EGM through any suitable data network described above (such as an Internet or intranet).

[0109] The at least one memory device **1016** also stores a plurality of device drivers **1042**. Examples of different types of device drivers include device drivers for EGM components and device drivers for the peripheral components **1022**. Typically, the device drivers **1042** utilize various communication protocols that enable communication with a particular physical device. The device driver abstracts the hardware implementation of that device. For example, a device driver may be written for each type of card reader that could potentially be connected to the EGM. Non-limiting examples of communication protocols used to implement the device drivers include Netplex, USB, Serial, Ethernet **175**, Firewire, I/O debouncer, direct memory map, serial, PCI, parallel, RF, Bluetooth™, near-field communications (e.g., using near-field magnetics), 802.11 (WiFi), etc. In one embodiment, when one type of a particular device is exchanged for another type of the particular device, the at least one processor of the EGM loads the new device driver from the at least one memory device to enable communication with the new device. For instance, one type of card reader in the EGM can be replaced with a second different type of card reader when device drivers for both card readers are stored in the at least one memory device.

[0110] In certain embodiments, the software units stored in the at least one memory device **1016** can be upgraded as needed. For instance, when the at least one memory device **1016** is a hard drive, new games, new game options, new parameters, new settings for existing parameters, new settings for new parameters, new device drivers, and new communication protocols can be uploaded to the at least one memory device **1016** from the master game controller **1012** or from some other external device. As another example, when the at least one memory device **1016** includes a CD/DVD drive including a CD/DVD configured to store game options, parameters, and settings, the software stored in the at least one memory device **1016** can be upgraded by replacing a first CD/DVD with a second CD/DVD. In yet another example, when the at least one memory device **1016** uses flash memory **1019** or EPROM **1008** units configured to store games, game options, parameters, and settings, the software stored in the flash and/or EPROM memory units can be upgraded by replacing one or more memory units with new memory units that include the upgraded

software. In another embodiment, one or more of the memory devices, such as the hard drive, may be employed in a game software download process from a remote software server.

[0111] In some embodiments, the at least one memory device **1016** also stores authentication and/or validation components **1044** configured to authenticate/validate specified EGM components and/or information, such as hardware components, software components, firmware components, peripheral device components, user input device components, information received from one or more user input devices, information stored in the at least one memory device **1016**, etc. Examples of various authentication and/or validation components are described in U.S. Pat. No. 6,620,047, entitled “Electronic Gaming Apparatus Having Authentication Data Sets”.

[0112] In certain embodiments, the peripheral devices **1022** include several device interfaces, such as: (1) at least one output device **1020** including at least one display device **1035**; (2) at least one input device **1030** (which may include contact and/or non-contact interfaces); (3) at least one transponder **1054**; (4) at least one wireless communication component **1056**; (5) at least one wired/wireless power distribution component **1058**; (6) at least one sensor **1060**; (7) at least one data preservation component **1062**; (8) at least one motion/gesture analysis and interpretation component **1064**; (9) at least one motion detection component **1066**; (10) at least one portable power source **1068**; (11) at least one geolocation module **1076**; (12) at least one user identification module **1077**; (13) at least one player/device tracking module **1078**; and (14) at least one information filtering module **1079**.

[0113] The at least one output device **1020** includes at least one display device **1035** configured to display any game(s) displayed by the EGM and any suitable information associated with such game(s). In certain embodiments, the display devices are connected to or mounted on a housing of the EGM (described below). In various embodiments, the display devices serve as digital glass configured to advertise certain games or other aspects of the gaming establishment in which the EGM is located. In various embodiments, the EGM includes one or more of the following display devices: (a) a central display device; (b) a player tracking display configured to display various information regarding a player's player tracking status (as described below); (c) a secondary or upper display device in addition to the central display device and the player tracking display; (d) a credit display configured to display a current quantity of credits, amount of cash, account balance, or the equivalent; and (e) a bet display configured to display an amount wagered for one or more plays of one or more games. The example EGM **2000a** illustrated in FIG. 4A includes a central display device **2116**, a player tracking display **2140**, a credit display **2120**, and a bet display **2122**. The example EGM **2000b** illustrated in FIG. 4B includes a central display device **2116**, an upper display device **2118**, a player tracking display **2140**, a credit display **2120**, and a bet display **2122**.

[0114] In various embodiments, the display devices include, without limitation: a monitor, a television display, a plasma display, a liquid crystal display (LCD), a display based on light emitting diodes (LEDs), a display based on a plurality of organic light-emitting diodes (OLEDs), a display based on polymer light-emitting diodes (PLEDs), a display based on a plurality of surface-conduction electron-emitters (SEDs), a display including a projected and/or reflected image, or any other suitable electronic device or display mechanism. In certain embodiments, as described above, the display device includes a touch-screen with an associated touch-screen controller. The display devices may be of any suitable sizes, shapes, and configurations.

[0115] The display devices of the EGM are configured to display one or more game and/or non-game images, symbols, and indicia. In certain embodiments, the display devices of the EGM are configured to display any suitable visual representation or exhibition of the movement of objects; dynamic lighting; video images; images of people, characters, places, things, and faces of cards; and the like. In certain embodiments, the display devices of the EGM are configured to display one or more video reels, one or more video wheels, and/or one or more video dice. In other embodiments, certain of the displayed images, symbols, and indicia are in mechanical form. That is, in these embodiments, the display device includes any electromechanical device, such as one or

more rotatable wheels, one or more reels, and/or one or more dice, configured to display at least one or a plurality of game or other suitable images, symbols, or indicia.

[0116] In various embodiments, the at least one output device **1020** includes a payout device. In these embodiments, after the EGM receives an actuation of a cashout device (described below), the EGM causes the payout device to provide a payment to the player. In one embodiment, the payout device is one or more of: (a) a ticket printer and dispenser configured to print and dispense a ticket or credit slip associated with a monetary value, wherein the ticket or credit slip may be redeemed for its monetary value via a cashier, a kiosk, or other suitable redemption system; (b) a bill dispenser configured to dispense paper currency; (c) a coin dispenser configured to dispense coins or tokens (such as into a coin payout tray); and (d) any suitable combination thereof. The example EGMs **2000a** and **2000b** illustrated in FIGS. 4A and 4B each include a ticket printer and dispenser **2136**. Examples of ticket-in ticket-out (TITO) technology are described in U.S. Pat. No. 5,429,361, entitled “Gaming Machine Information, Communication and Display System”; U.S. Pat. No. 5,470,079, entitled “Gaming Machine Accounting and Monitoring System”; U.S. Pat. No. 5,265,874, entitled “Cashless Gaming Apparatus and Method”; U.S. Pat. No. 6,729,957, entitled “Gaming Method and Host Computer with Ticket-In/Ticket-Out Capability”; U.S. Pat. No. 6,729,958, entitled “Gaming System with Ticket-In/Ticket-Out Capability”; U.S. Pat. No. 6,736,725, entitled “Gaming Method and Host Computer with Ticket-In/Ticket-Out Capability”; U.S. Pat. No. 7,275,991, entitled “Slot Machine with Ticket-In/Ticket-Out Capability”; and U.S. Pat. No. 6,048,269, entitled “Coinless Slot Machine System and Method”.

[0117] In certain embodiments, rather than dispensing bills, coins, or a physical ticket having a monetary value to the player following receipt of an actuation of the cashout device, the payout device is configured to cause a payment to be provided to the player in the form of an electronic funds transfer, such as via a direct deposit into a bank account, a casino account, or a prepaid account of the player; via a transfer of funds onto an electronically recordable identification card or smart card of the player; or via sending a virtual ticket having a monetary value to an electronic device of the player. Examples of providing payment using virtual tickets are described in U.S. Pat. No. 8,613,659, entitled “Virtual Ticket-In and Ticket-Out on a Gaming Machine”.

[0118] While any credit balances, any wagers, any values, and any awards are described herein as amounts of monetary credits or currency, one or more of such credit balances, such wagers, such values, and such awards may be for non-monetary credits, promotional credits, of player tracking points or credits.

[0119] In certain embodiments, the at least one output device **1020** is a sound generating device controlled by one or more sound cards. In one such embodiment, the sound generating device includes one or more speakers or other sound generating hardware and/or software configured to generate sounds, such as by playing music for any games or by playing music for other modes of the EGM, such as an attract mode. The example EGMs **2000a** and **2000b** illustrated in FIGS. 4A and 4B each include a plurality of speakers **2150**. In another such embodiment, the EGM provides dynamic sounds coupled with attractive multimedia images displayed on one or more of the display devices to provide an audio-visual representation or to otherwise display full-motion video with sound to attract players to the EGM. In certain embodiments, the EGM displays a sequence of audio and/or visual attraction messages during idle periods to attract potential players to the EGM. The videos may be customized to provide any appropriate information.

[0120] The at least one input device **1030** may include any suitable device that enables an input signal to be produced and received by the at least one processor **1010** of the EGM.

[0121] In one embodiment, the at least one input device **1030** includes a payment device configured to communicate with the at least one processor of the EGM to fund the EGM. In certain embodiments, the payment device includes one or more of: (a) a bill acceptor into which paper money is inserted to fund the EGM; (b) a ticket acceptor into which a ticket or a voucher is inserted to fund the EGM; (c) a coin slot into which coins or tokens are inserted to fund the EGM; (d) a

reader or a validator for credit cards, debit cards, or credit slips into which a credit card, debit card, or credit slip is inserted to fund the EGM; (e) a player identification card reader into which a player identification card is inserted to fund the EGM; or (f) any suitable combination thereof. The example EGMs **2000a** and **2000b** illustrated in FIGS. **4A** and **4B** each include a combined bill and ticket acceptor **2128** and a coin slot **2126**.

[0122] In one embodiment, the at least one input device **1030** includes a payment device configured to enable the EGM to be funded via an electronic funds transfer, such as a transfer of funds from a bank account. In another embodiment, the EGM includes a payment device configured to communicate with a mobile device of a player, such as a mobile phone, a radio frequency identification tag, or any other suitable wired or wireless device, to retrieve relevant information associated with that player to fund the EGM. Examples of funding an EGM via communication between the EGM and a mobile device (such as a mobile phone) of a player are described in U.S. Patent Application Publication No. 2013/0344942, entitled “Avatar as Security Measure for Mobile Device Use with Electronic Gaming Machine”. When the EGM is funded, the at least one processor determines the amount of funds entered and displays the corresponding amount on a credit display or any other suitable display as described below.

[0123] In certain embodiments, the at least one input device **1030** includes at least one wagering or betting device. In various embodiments, the one or more wagering or betting devices are each: (1) a mechanical button supported by the housing of the EGM (such as a hard key or a programmable soft key), or (2) an icon displayed on a display device of the EGM (described below) that is actuatable via a touch screen of the EGM (described below) or via use of a suitable input device of the EGM (such as a mouse or a joystick). One such wagering or betting device is as a maximum wager or bet device that, when actuated, causes the EGM to place a maximum wager on a play of a game. Another such wagering or betting device is a repeat bet device that, when actuated, causes the EGM to place a wager that is equal to the previously-placed wager on a play of a game. A further such wagering or betting device is a bet one device that, when actuated, causes the EGM to increase the wager by one credit. Generally, upon actuation of one of the wagering or betting devices, the quantity of credits displayed in a credit meter (described below) decreases by the amount of credits wagered, while the quantity of credits displayed in a bet display (described below) increases by the amount of credits wagered.

[0124] In various embodiments, the at least one input device **1030** includes at least one game play activation device. In various embodiments, the one or more game play initiation devices are each: (1) a mechanical button supported by the housing of the EGM (such as a hard key or a programmable soft key), or (2) an icon displayed on a display device of the EGM (described below) that is actuatable via a touch screen of the EGM (described below) or via use of a suitable input device of the EGM (such as a mouse or a joystick). After a player appropriately funds the EGM and places a wager, the EGM activates the game play activation device to enable the player to actuate the game play activation device to initiate a play of a game on the EGM (or another suitable sequence of events associated with the EGM). After the EGM receives an actuation of the game play activation device, the EGM initiates the play of the game. The example EGMs **2000a** and **2000b** illustrated in FIGS. **4A** and **4B** each include a game play activation device in the form of a game play initiation button **2132**. In other embodiments, the EGM begins game play automatically upon appropriate funding rather than upon utilization of the game play activation device.

[0125] In other embodiments, the at least one input device **1030** includes a cashout device. In various embodiments, the cashout device is: (1) a mechanical button supported by the housing of the EGM (such as a hard key or a programmable soft key), or (2) an icon displayed on a display device of the EGM (described below) that is actuatable via a touch screen of the EGM (described below) or via use of a suitable input device of the EGM (such as a mouse or a joystick). When the EGM receives an actuation of the cashout device from a player and the player has a positive (i.e.,

greater-than-zero) credit balance, the EGM initiates a payout associated with the player's credit balance. The example EGMs **2000a** and **2000b** illustrated in FIGS. **4A** and **4B** each include a cashout device in the form of a cashout button **2134**.

[0126] In various embodiments, the at least one input device **1030** includes a plurality of buttons that are programmable by the EGM operator to, when actuated, cause the EGM to perform particular functions. For instance, such buttons may be hard keys, programmable soft keys, or icons icon displayed on a display device of the EGM (described below) that are actuatable via a touch screen of the EGM (described below) or via use of a suitable input device of the EGM (such as a mouse or a joystick). The example EGMs **2000a** and **2000b** illustrated in FIGS. **4A** and **4B** each include a plurality of such buttons **2130**.

[0127] In certain embodiments, the at least one input device **1030** includes a touch-screen coupled to a touch-screen controller or other touch-sensitive display overlay to enable interaction with any images displayed on a display device (as described below). One such input device is a conventional touch-screen button panel. The touch-screen and the touch-screen controller are connected to a video controller. In these embodiments, signals are input to the EGM by touching the touch screen at the appropriate locations.

[0128] In embodiments including a player tracking system, as further described below, the at least one input device **1030** includes a card reader in communication with the at least one processor of the EGM. The example EGMs **2000a** and **2000b** illustrated in FIGS. **4A** and **4B** each include a card reader **2138**. The card reader is configured to read a player identification card inserted into the card reader.

[0129] The at least one wireless communication component **1056** includes one or more communication interfaces having different architectures and utilizing a variety of protocols, such as (but not limited to) 802.11 (WiFi); 802.15 (including Bluetooth™); 802.16 (WiMax); 802.22; cellular standards such as CDMA, CDMA2000, and WCDMA; Radio Frequency (e.g., RFID); infrared; and Near Field Magnetic communication protocols. The at least one wireless communication component **1056** transmits electrical, electromagnetic, or optical signals that carry digital data streams or analog signals representing various types of information.

[0130] The at least one wired/wireless power distribution component **1058** includes components or devices that are configured to provide power to other devices. For example, in one embodiment, the at least one power distribution component **1058** includes a magnetic induction system that is configured to provide wireless power to one or more user input devices near the EGM. In one embodiment, a user input device docking region is provided, and includes a power distribution component that is configured to recharge a user input device without requiring metal-to-metal contact. In one embodiment, the at least one power distribution component **1058** is configured to distribute power to one or more internal components of the EGM, such as one or more rechargeable power sources (e.g., rechargeable batteries) located at the EGM.

[0131] In certain embodiments, the at least one sensor **1060** includes at least one of: optical sensors, pressure sensors, RF sensors, infrared sensors, image sensors, thermal sensors, and biometric sensors. The at least one sensor **1060** may be used for a variety of functions, such as: detecting movements and/or gestures of various objects within a predetermined proximity to the EGM; detecting the presence and/or identity of various persons (e.g., players, casino employees, etc.), devices (e.g., user input devices), and/or systems within a predetermined proximity to the EGM.

[0132] The at least one data preservation component **1062** is configured to detect or sense one or more events and/or conditions that, for example, may result in damage to the EGM and/or that may result in loss of information associated with the EGM. Additionally, the data preservation system **1062** may be operable to initiate one or more appropriate action(s) in response to the detection of such events/conditions.

[0133] The at least one motion/gesture analysis and interpretation component **1064** is configured to

analyze and/or interpret information relating to detected player movements and/or gestures to determine appropriate player input information relating to the detected player movements and/or gestures. For example, in one embodiment, the at least one motion/gesture analysis and interpretation component **1064** is configured to perform one or more of the following functions: analyze the detected gross motion or gestures of a player; interpret the player's motion or gestures (e.g., in the context of a casino game being played) to identify instructions or input from the player; utilize the interpreted instructions/input to advance the game state; etc. In other embodiments, at least a portion of these additional functions may be implemented at a remote system or device.

[0134] The at least one portable power source **1068** enables the EGM to operate in a mobile environment. For example, in one embodiment, the EGM **300** includes one or more rechargeable batteries.

[0135] The at least one geolocation module **1076** is configured to acquire geolocation information from one or more remote sources and use the acquired geolocation information to determine information relating to a relative and/or absolute position of the EGM. For example, in one implementation, the at least one geolocation module **1076** is configured to receive GPS signal information for use in determining the position or location of the EGM. In another implementation, the at least one geolocation module **1076** is configured to receive multiple wireless signals from multiple remote devices (e.g., EGMs, servers, wireless access points, etc.) and use the signal information to compute position/location information relating to the position or location of the EGM.

[0136] The at least one user identification module **1077** is configured to determine the identity of the current user or current owner of the EGM. For example, in one embodiment, the current user is required to perform a login process at the EGM in order to access one or more features.

Alternatively, the EGM is configured to automatically determine the identity of the current user based on one or more external signals, such as an RFID tag or badge worn by the current user and that provides a wireless signal to the EGM that is used to determine the identity of the current user. In at least one embodiment, various security features are incorporated into the EGM to prevent unauthorized users from accessing confidential or sensitive information.

[0137] The at least one information filtering module **1079** is configured to perform filtering (e.g., based on specified criteria) of selected information to be displayed at one or more displays **1035** of the EGM.

[0138] In various embodiments, the EGM includes a plurality of communication ports configured to enable the at least one processor of the EGM to communicate with and to operate with external peripherals, such as: accelerometers, arcade sticks, bar code readers, bill validators, biometric input devices, bonus devices, button panels, card readers, coin dispensers, coin hoppers, display screens or other displays or video sources, expansion buses, information panels, keypads, lights, mass storage devices, microphones, motion sensors, motors, printers, reels, SCSI ports, solenoids, speakers, thumbsticks, ticket readers, touch screens, trackballs, touchpads, wheels, and wireless communication devices. U.S. Pat. No. 7,290,072 describes a variety of EGMs including one or more communication ports that enable the EGMs to communicate and operate with one or more external peripherals.

[0139] As generally described above, in certain embodiments, such as the example EGMs **2000a** and **2000b** illustrated in FIGS. 4A and 4B, the EGM has a support structure, housing, or cabinet that provides support for a plurality of the input devices and the output devices of the EGM.

Further, the EGM is configured such that a player may operate it while standing or sitting. In various embodiments, the EGM is positioned on a base or stand, or is configured as a pub-style tabletop game (not shown) that a player may operate typically while sitting. As illustrated by the different example EGMs **2000a** and **2000b** shown in FIGS. 4A and 4B, EGMs may have varying housing and display configurations.

[0140] In certain embodiments, the EGM is a device that has obtained approval from a regulatory

gaming commission, and in other embodiments, the EGM is a device that has not obtained approval from a regulatory gaming commission.

[0141] The EGMs described above are merely three examples of different types of EGMs. Certain of these example EGMs may include one or more elements that may not be included in all gaming systems, and these example EGMs may not include one or more elements that are included in other gaming systems. For example, certain EGMs include a coin acceptor while others do not.

Operation of Primary or Base Games and/or Secondary or Bonus Games

[0142] In various embodiments, an EGM may be implemented in one of a variety of different configurations. In various embodiments, the EGM may be implemented as one of: (a) a dedicated EGM in which computerized game programs executable by the EGM for controlling any primary or base games (referred to herein as “primary games”) and/or any secondary or bonus games or other functions (referred to herein as “secondary games”) displayed by the EGM are provided with the EGM before delivery to a gaming establishment or before being provided to a player; and (b) a changeable EGM in which computerized game programs executable by the EGM for controlling any primary games and/or secondary games displayed by the EGM are downloadable or otherwise transferred to the EGM through a data network or remote communication link; from a USB drive, flash memory card, or other suitable memory device; or in any other suitable manner after the EGM is physically located in a gaming establishment or after the EGM is provided to a player.

[0143] As generally explained above, in various embodiments in which the gaming system includes a central server, central controller, or remote host and a changeable EGM, the at least one memory device of the central server, central controller, or remote host stores different game programs and instructions executable by the at least one processor of the changeable EGM to control one or more primary games and/or secondary games displayed by the changeable EGM. More specifically, each such executable game program represents a different game or a different type of game that the at least one changeable EGM is configured to operate. In one example, certain of the game programs are executable by the changeable EGM to operate games having the same or substantially the same game play but different paytables. In different embodiments, each executable game program is associated with a primary game, a secondary game, or both. In certain embodiments, an executable game program is executable by the at least one processor of the at least one changeable EGM as a secondary game to be played simultaneously with a play of a primary game (which may be downloaded to or otherwise stored on the at least one changeable EGM), or vice versa.

[0144] In operation of such embodiments, the central server, central controller, or remote host is configured to communicate one or more of the stored executable game programs to the at least one processor of the changeable EGM. In different embodiments, a stored executable game program is communicated or delivered to the at least one processor of the changeable EGM by: (a) embedding the executable game program in a device or a component (such as a microchip to be inserted into the changeable EGM); (b) writing the executable game program onto a disc or other media; or (c) uploading or streaming the executable game program over a data network (such as a dedicated data network). After the executable game program is communicated from the central server, central controller, or remote host to the changeable EGM, the at least one processor of the changeable EGM executes the executable game program to enable the primary game and/or the secondary game associated with that executable game program to be played using the display device(s) and/or the input device(s) of the changeable EGM. That is, when an executable game program is communicated to the at least one processor of the changeable EGM, the at least one processor of the changeable EGM changes the game or the type of game that may be played using the changeable EGM.

[0145] In certain embodiments, the gaming system randomly determines any game outcome(s) (such as a win outcome) and/or award(s) (such as a quantity of credits to award for the win outcome) for a play of a primary game and/or a play of a secondary game based on probability data. In certain such embodiments, this random determination is provided through utilization of an

RNG, such as a true RNG or a pseudo RNG, or any other suitable randomization process. In one such embodiment, each game outcome or award is associated with a probability, and the gaming system generates the game outcome(s) and/or the award(s) to be provided based on the associated probabilities. In these embodiments, since the gaming system generates game outcomes and/or awards randomly or based on one or more probability calculations, there is no certainty that the gaming system will ever provide any specific game outcome and/or award.

[0146] In certain embodiments, the gaming system maintains one or more predetermined pools or sets of predetermined game outcomes and/or awards. In certain such embodiments, upon generation or receipt of a game outcome and/or award request, the gaming system independently selects one of the predetermined game outcomes and/or awards from the one or more pools or sets. The gaming system flags or marks the selected game outcome and/or award as used. Once a game outcome or an award is flagged as used, it is prevented from further selection from its respective pool or set; that is, the gaming system does not select that game outcome or award upon another game outcome and/or award request. The gaming system provides the selected game outcome and/or award. Examples of this type of award evaluation are described in U.S. Pat. No. 7,470,183, entitled "Finite Pool Gaming Method and Apparatus"; U.S. Pat. No. 7,563,163, entitled "Gaming Device Including Outcome Pools for Providing Game Outcomes"; U.S. Pat. No. 7,833,092, entitled "Method and System for Compensating for Player Choice in a Game of Chance"; U.S. Pat. No. 8,070,579, entitled "Bingo System with Downloadable Common Patterns"; and U.S. Pat. No. 8,398,472, entitled "Central Determination Poker Game".

[0147] In certain embodiments, the gaming system determines a predetermined game outcome and/or award based on the results of a bingo, keno, or lottery game. In certain such embodiments, the gaming system utilizes one or more bingo, keno, or lottery games to determine the predetermined game outcome and/or award provided for a primary game and/or a secondary game. The gaming system is provided or associated with a bingo card. Each bingo card consists of a matrix or array of elements, wherein each element is designated with separate indicia. After a bingo card is provided, the gaming system randomly selects or draws a plurality of the elements. As each element is selected, a determination is made as to whether the selected element is present on the bingo card. If the selected element is present on the bingo card, that selected element on the provided bingo card is marked or flagged. This process of selecting elements and marking any selected elements on the provided bingo cards continues until one or more predetermined patterns are marked on one or more of the provided bingo cards. After one or more predetermined patterns are marked on one or more of the provided bingo cards, game outcome and/or award is determined based, at least in part, on the selected elements on the provided bingo cards. Examples of this type of award determination are described in U.S. Pat. No. 7,753,774, entitled "Using Multiple Bingo Cards to Represent Multiple Slot Paylines and Other Class III Game Options"; U.S. Pat. No. 7,731,581, entitled "Multi-Player Bingo Game with Multiple Alternative Outcome Displays"; U.S. Pat. No. 7,955,170, entitled "Providing Non-Bingo Outcomes for a Bingo Game"; U.S. Pat. No. 8,070,579, entitled "Bingo System with Downloadable Common Patterns"; and U.S. Pat. No. 8,500,538, entitled "Bingo Gaming System and Method for Providing Multiple Outcomes from Single Bingo Pattern".

[0148] In certain embodiments in which the gaming system includes a central server, central controller, or remote host and an EGM, the EGM is configured to communicate with the central server, central controller, or remote host for monitoring purposes only. In such embodiments, the EGM determines the game outcome(s) and/or award(s) to be provided in any of the manners described above, and the central server, central controller, or remote host monitors the activities and events occurring on the EGM. In one such embodiment, the gaming system includes a real-time or online accounting and gaming information system configured to communicate with the central server, central controller, or remote host. In this embodiment, the accounting and gaming information system includes: (a) a player database configured to store player profiles, (b) a player

tracking module configured to track players (as described below), and (c) a credit system configured to provide automated transactions. Examples of such accounting systems are described in U.S. Pat. No. 6,913,534, entitled “Gaming Machine Having a Lottery Game and Capability for Integration with Gaming Device Accounting System and Player Tracking System,” and U.S. Pat. No. 8,597,116, entitled “Virtual Player Tracking and Related Services”.

[0149] As noted above, in various embodiments, the gaming system includes one or more executable game programs executable by at least one processor of the gaming system to provide one or more primary games and one or more secondary games. The primary game(s) and the secondary game(s) may comprise any suitable games and/or wagering games, such as, but not limited to: electro-mechanical or video slot or spinning reel type games; video card games such as video draw poker, multi-hand video draw poker, other video poker games, video blackjack games, and video baccarat games; video keno games; video bingo games; and video selection games.

[0150] In certain embodiments in which the primary game is a slot or spinning reel type game, the gaming system includes one or more reels in either an electromechanical form with mechanical rotating reels or in a video form with simulated reels and movement thereof. Each reel displays a plurality of indicia or symbols, such as bells, hearts, fruits, numbers, letters, bars, or other images that typically correspond to a theme associated with the gaming system. In certain such embodiments, the gaming system includes one or more paylines associated with the reels. In certain embodiments, one or more of the reels are independent reels or unisymbol reels. In such embodiments, each independent reel generates and displays one symbol.

[0151] In various embodiments, one or more of the paylines is horizontal, vertical, circular, diagonal, angled, or any suitable combination thereof. In other embodiments, each of one or more of the paylines is associated with a plurality of adjacent symbol display areas on a requisite number of adjacent reels. In one such embodiment, one or more paylines are formed between at least two symbol display areas that are adjacent to each other by either sharing a common side or sharing a common corner (i.e., such paylines are connected paylines). The gaming system enables a wager to be placed on one or more of such paylines to activate such paylines. In other embodiments in which one or more paylines are formed between at least two adjacent symbol display areas, the gaming system enables a wager to be placed on a plurality of symbol display areas, which activates those symbol display areas.

[0152] In various embodiments, the gaming system provides one or more awards after a spin of the reels when specified types and/or configurations of the indicia or symbols on the reels occur on an active payline or otherwise occur in a winning pattern, occur on the requisite number of adjacent reels, and/or occur in a scatter pay arrangement.

[0153] In certain embodiments, the gaming system employs a ways to win award determination. In these embodiments, any outcome to be provided is determined based on a number of associated symbols that are generated in active symbol display areas on the requisite number of adjacent reels (i.e., not on paylines passing through any displayed winning symbol combinations). If a winning symbol combination is generated on the reels, one award for that occurrence of the generated winning symbol combination is provided. Examples of ways to win award determinations are described in U.S. Pat. No. 8,012,011, entitled “Gaming Device and Method Having Independent Reels and Multiple Ways of Winning”; U.S. Pat. No. 8,241,104, entitled “Gaming Device and Method Having Designated Rules for Determining Ways To Win”; and U.S. Pat. No. 8,430,739, entitled “Gaming System and Method Having Wager Dependent Different Symbol Evaluations”.

[0154] In various embodiments, the gaming system includes a progressive award. Typically, a progressive award includes an initial amount and an additional amount funded through a portion of each wager placed to initiate a play of a primary game. When one or more designated symbol accumulator redistribution events occurs, the gaming system provides at least a portion of the progressive award. After the gaming system provides the progressive award, an amount of the progressive award is reset to the initial amount and a portion of each subsequent wager is allocated

to the next progressive award. Examples of progressive gaming systems are described in U.S. Pat. No. 7,585,223, entitled "Server Based Gaming System Having Multiple Progressive Awards"; U.S. Pat. No. 7,651,392, entitled "Gaming Device System Having Partial Progressive Payout"; U.S. Pat. No. 7,666,093, entitled "Gaming Method and Device Involving Progressive Wagers"; U.S. Pat. No. 7,780,523, entitled "Server Based Gaming System Having Multiple Progressive Awards"; and U.S. Pat. No. 8,337,298, entitled "Gaming Device Having Multiple Different Types of Progressive Awards".

[0155] As generally noted above, in addition to providing winning credits or other awards for one or more plays of the primary game(s), in various embodiments the gaming system provides credits or other awards for one or more plays of one or more secondary games. The secondary game typically enables an award to be obtained addition to any award obtained through play of the primary game(s). The secondary game(s) typically produces a higher level of player excitement than the primary game(s) because the secondary game(s) provides a greater expectation of winning than the primary game(s) and is accompanied with more attractive or unusual features than the primary game(s). The secondary game(s) may be any type of suitable game, either similar to or completely different from the primary game.

[0156] In various embodiments, the gaming system automatically provides or initiates the secondary game upon the occurrence of a designated symbol accumulator redistribution event or the satisfaction of a qualifying condition. In other embodiments, the gaming system initiates the secondary game upon the occurrence of the designated symbol accumulator redistribution event or the satisfaction of the qualifying condition and upon receipt of an initiation input. In certain embodiments, the designated symbol accumulator redistribution event or qualifying condition is a selected outcome in the primary game(s) or a particular arrangement of one or more indicia on a display device for a play of the primary game(s), such as a "BONUS" symbol appearing on three adjacent reels along a payline following a spin of the reels for a play of the primary game. In other embodiments, the designated symbol accumulator redistribution event or qualifying condition occurs based on a certain amount of game play (such as number of games, number of credits, amount of time) being exceeded, or based on a specified number of points being earned during game play. Any suitable designated symbol accumulator redistribution event or qualifying condition or any suitable combination of a plurality of different designated symbol accumulator redistribution events or qualifying conditions may be employed.

[0157] In other embodiments, at least one processor of the gaming system randomly determines when to provide one or more plays of one or more secondary games. In one such embodiment, no apparent reason is provided for providing the secondary game. In this embodiment, qualifying for a secondary game is not triggered by the occurrence of an event in any primary game or based specifically on any of the plays of any primary game. That is, qualification is provided without any explanation or, alternatively, with a simple explanation. In another such embodiment, the gaming system determines qualification for a secondary game at least partially based on a game triggered or symbol triggered event, such as at least partially based on play of a primary game.

[0158] In various embodiments, after qualification for a secondary game has been determined, the secondary game participation may be enhanced through continued play on the primary game. Thus, in certain embodiments, for each secondary game qualifying event, such as a secondary game symbol, that is obtained, a given number of secondary game wagering points or credits is accumulated in a "secondary game meter" configured to accrue the secondary game wagering credits or entries toward eventual participation in the secondary game. In one such embodiment, the occurrence of multiple such secondary game qualifying events in the primary game results in an arithmetic or exponential increase in the number of secondary game wagering credits awarded. In another such embodiment, any extra secondary game wagering credits may be redeemed during the secondary game to extend play of the secondary game.

[0159] In certain embodiments, no separate entry fee or buy-in for the secondary game is required.

That is, entry into the secondary game cannot be purchased; rather, in these embodiments entry must be won or earned through play of the primary game, thereby encouraging play of the primary game. In other embodiments, qualification for the secondary game is accomplished through a simple “buy-in.” For example, qualification through other specified activities is unsuccessful, payment of a fee or placement of an additional wager “buys-in” to the secondary game. In certain embodiments, a separate side wager must be placed on the secondary game or a wager of a designated amount must be placed on the primary game to enable qualification for the secondary game. In these embodiments, the secondary game initiation event must occur and the side wager (or designated primary game wager amount) must have been placed for the secondary game to trigger.

[0160] In various embodiments in which the gaming system includes a plurality of EGMs, the EGMs are configured to communicate with one another to provide a group gaming environment. In certain such embodiments, the EGMs enable players of those EGMs to work in conjunction with one another, such as by enabling the players to play together as a team or group, to win one or more awards. In other such embodiments, the EGMs enable players of those EGMs to compete against one another for one or more awards. In one such embodiment, the EGMs enable the players of those EGMs to participate in one or more gaming tournaments for one or more awards. Examples of group gaming systems are described in U.S. Pat. No. 8,070,583, entitled “Server Based Gaming System and Method for Selectively Providing One or More Different Tournaments”; U.S. Pat. No. 8,500,548, entitled “Gaming System and Method for Providing Team Progressive Awards”; and U.S. Pat. No. 8,562,423, entitled “Method and Apparatus for Rewarding Multiple Game Players for a Single Win”.

[0161] In various embodiments, the gaming system includes one or more player tracking systems. Such player tracking systems enable operators of the gaming system (such as casinos or other gaming establishments) to recognize the value of customer loyalty by identifying frequent customers and rewarding them for their patronage. Such a player tracking system is configured to track a player's gaming activity. In one such embodiment, the player tracking system does so through the use of player tracking cards. In this embodiment, a player is issued a player identification card that has an encoded player identification number that uniquely identifies the player. When the player's playing tracking card is inserted into a card reader of the gaming system to begin a gaming session, the card reader reads the player identification number off the player tracking card to identify the player. The gaming system timely tracks any suitable information or data relating to the identified player's gaming session. The gaming system also timely tracks when the player tracking card is removed to conclude play for that gaming session. In another embodiment, rather than requiring insertion of a player tracking card into the card reader, the gaming system utilizes one or more portable devices, such as a mobile phone, a radio frequency identification tag, or any other suitable wireless device, to track when a gaming session begins and ends. In another embodiment, the gaming system utilizes any suitable biometric technology or ticket technology to track when a gaming session begins and ends.

[0162] In such embodiments, during one or more gaming sessions, the gaming system tracks any suitable information or data, such as any amounts wagered, average wager amounts, and/or the time at which these wagers are placed. In different embodiments, for one or more players, the player tracking system includes the player's account number, the player's card number, the player's first name, the player's surname, the player's preferred name, the player's player tracking ranking, any promotion status associated with the player's player tracking card, the player's address, the player's birthday, the player's anniversary, the player's recent gaming sessions, or any other suitable data. In various embodiments, such tracked information and/or any suitable feature associated with the player tracking system is displayed on a player tracking display. In various embodiments, such tracked information and/or any suitable feature associated with the player tracking system is displayed via one or more service windows that are displayed on the central display device and/or

the upper display device. Examples of player tracking systems are described in U.S. Pat. No. 6,722,985, entitled “Universal Player Tracking System”; U.S. Pat. No. 6,908,387, entitled “Player Tracking Communication Mechanisms in a Gaming Machine”; U.S. Pat. No. 7,311,605, entitled “Player Tracking Assembly for Complete Patron Tracking for Both Gaming and Non-Gaming Casino Activity”; U.S. Pat. No. 7,611,411, entitled “Player Tracking Instruments Having Multiple Communication Modes”; U.S. Pat. No. 7,617,151, entitled “Alternative Player Tracking Techniques”; and U.S. Pat. No. 8,057,298, entitled “Virtual Player Tracking and Related Services”.
Web-Based Gaming

[0163] In various embodiments, the gaming system includes one or more servers configured to communicate with a personal gaming device—such as a smartphone, a tablet computer, a desktop computer, or a laptop computer—to enable web-based game play using the personal gaming device. In various embodiments, the player must first access a gaming website via an Internet browser of the personal gaming device or execute an application (commonly called an “app”) installed on the personal gaming device before the player can use the personal gaming device to participate in web-based game play. In certain embodiments, the one or more servers and the personal gaming device operate in a thin-client environment. In these embodiments, the personal gaming device receives inputs via one or more input devices (such as a touch screen and/or physical buttons), the personal gaming device sends the received inputs to the one or more servers, the one or more servers make various determinations based on the inputs and determine content to be displayed (such as a randomly determined game outcome and corresponding award), the one or more servers send the content to the personal gaming device, and the personal gaming device displays the content.

[0164] In certain such embodiments, the one or more servers must identify the player before enabling game play on the personal gaming device (or, in some embodiments, before enabling monetary wager-based game play on the personal gaming device). In these embodiments, the player must identify herself to the one or more servers, such as by inputting the player's unique username and password combination, providing an input to a biometric sensor (e.g., a fingerprint sensor, a retinal sensor, a voice sensor, or a facial-recognition sensor), or providing any other suitable information.

[0165] Once identified, the one or more servers enable the player to establish an account balance from which the player can draw credits usable to wager on plays of a game. In certain embodiments, the one or more servers enable the player to initiate an electronic funds transfer to transfer funds from a bank account to the player's account balance. In other embodiments, the one or more servers enable the player to make a payment using the player's credit card, debit card, or other suitable device to add money to the player's account balance. In other embodiments, the one or more servers enable the player to add money to the player's account balance via a peer-to-peer type application, such as PayPal or Venmo. The one or more servers also enable the player to cash out the player's account balance (or part of it) in any suitable manner, such as via an electronic funds transfer, by initiating creation of a paper check that is mailed to the player, or by initiating printing of a voucher at a kiosk in a gaming establishment.

[0166] In certain embodiments, the one or more servers include a payment server that handles establishing and cashing out players' account balances and a separate game server configured to determine the outcome and any associated award for a play of a game. In these embodiments, the game server is configured to communicate with the personal gaming device and the payment device, and the personal gaming device and the payment device are not configured to directly communicate with one another. In these embodiments, when the game server receives data representing a request to start a play of a game at a desired wager, the game server sends data representing the desired wager to the payment server. The payment server determines whether the player's account balance can cover the desired wager (i.e., includes a monetary balance at least equal to the desired wager).

[0167] If the payment server determines that the player's account balance cannot cover the desired wager, the payment server notifies the game server, which then instructs the personal gaming device to display a suitable notification to the player that the player's account balance is too low to place the desired wager. If the payment server determines that the player's account balance can cover the desired wager, the payment server deducts the desired wager from the account balance and notifies the game server. The game server then determines an outcome and any associated award for the play of the game. The game server notifies the payment server of any nonzero award, and the payment server increases the player's account balance by the nonzero award. The game server sends data representing the outcome and any award to the personal gaming device, which displays the outcome and any award.

[0168] In certain embodiments, the one or more servers enable web-based game play using a personal gaming device only if the personal gaming device satisfies one or more jurisdictional requirements. In one embodiment, the one or more servers enable web-based game play using the personal gaming device only if the personal gaming device is located within a designated geographic area (such as within certain state or county lines or within the boundaries of a gaming establishment). In this embodiment, the geolocation module of the personal gaming device determines the location of the personal gaming device and sends the location to the one or more servers, which determine whether the personal gaming device is located within the designated geographic area. In various embodiments, the one or more servers enable non-monetary wager-based game play if the personal gaming device is located outside of the designated geographic area.

[0169] In various embodiments, the gaming system includes an EGM configured to communicate with a personal gaming device—such as a smartphone, a tablet computer, a desktop computer, or a laptop computer—to enable tethered mobile game play using the personal gaming device. Generally, in these embodiments, the EGM establishes communication with the personal gaming device and enables the player to play games on the EGM remotely via the personal gaming device. In certain embodiments, the gaming system includes a geo-fence system that enables tethered game play within a particular geographic area but not outside of that geographic area. Examples of tethering an EGM to a personal gaming device and geo-fencing are described in U.S. Patent Appl. Pub. No. 2013/0267324, entitled “Remote Gaming Method Allowing Temporary Inactivation Without Terminating Playing Session Due to Game Inactivity”.

Social Network Integration

[0170] In certain embodiments, the gaming system is configured to communicate with a social network server that hosts or partially hosts a social networking website via a data network (such as the Internet) to integrate a player's gaming experience with the player's social networking account. This enables the gaming system to send certain information to the social network server that the social network server can use to create content (such as text, an image, and/or a video) and post it to the player's wall, newsfeed, or similar area of the social networking website accessible by the player's connections (and in certain cases the public) such that the player's connections can view that information. This also enables the gaming system to receive certain information from the social network server, such as the player's likes or dislikes or the player's list of connections. In certain embodiments, the gaming system enables the player to link the player's player account to the player's social networking account(s). This enables the gaming system to, once it identifies the player and initiates a gaming session (such as via the player logging in to a website (or an application) on the player's personal gaming device or via the player inserting the player's player tracking card into an EGM), link that gaming session to the player's social networking account(s). In other embodiments, the gaming system enables the player to link the player's social networking account(s) to individual gaming sessions when desired by providing the required login information.

[0171] For instance, in one embodiment, if a player wins a particular award (e.g., a progressive award or a jackpot award) or an award that exceeds a certain threshold (e.g., an award exceeding \$1,000), the gaming system sends information about the award to the social network server to

enable the server to create associated content (such as a screenshot of the outcome and associated award) and to post that content to the player's wall (or other suitable area) of the social networking website for the player's connections to see (and to entice them to play). In another embodiment, if a player joins a multiplayer game and there is another seat available, the gaming system sends that information to the social network server to enable the server to create associated content (such as text indicating a vacancy for that particular game) and to post that content to the player's wall (or other suitable area) of the social networking website for the player's connections to see (and to entice them to fill the vacancy). In another embodiment, if the player consents, the gaming system sends advertisement information or offer information to the social network server to enable the social network server to create associated content (such as text or an image reflecting an advertisement and/or an offer) and to post that content to the player's wall (or other suitable area) of the social networking website for the player's connections to see. In another embodiment, the gaming system enables the player to recommend a game to the player's connections by posting a recommendation to the player's wall (or other suitable area) of the social networking website.

Differentiating Certain Gaming Systems from General Purpose Computing Devices

[0172] Certain of the gaming systems described herein, such as EGMs located in a casino or another gaming establishment, include certain components and/or are configured to operate in certain manners that differentiate these systems from general purpose computing devices, i.e., certain personal gaming devices such as desktop computers and laptop computers.

[0173] For instance, EGMs are highly regulated to ensure fairness and, in many cases, EGMs are configured to award monetary awards up to multiple millions of dollars. To satisfy security and regulatory requirements in a gaming environment, hardware and/or software architectures are implemented in EGMs that differ significantly from those of general purpose computing devices. For purposes of illustration, a description of EGMs relative to general purpose computing devices and some examples of these additional (or different) hardware and/or software architectures found in EGMs are described below.

[0174] At first glance, one might think that adapting general purpose computing device technologies to the gaming industry and EGMs would be a simple proposition because both general purpose computing devices and EGMs employ processors that control a variety of devices. However, due to at least: (1) the regulatory requirements placed on EGMs, (2) the harsh environment in which EGMs operate, (3) security requirements, and (4) fault tolerance requirements, adapting general purpose computing device technologies to EGMs can be quite difficult. Further, techniques and methods for solving a problem in the general purpose computing device industry, such as device compatibility and connectivity issues, might not be adequate in the gaming industry. For instance, a fault or a weakness tolerated in a general purpose computing device, such as security holes in software or frequent crashes, is not tolerated in an EGM because in an EGM these faults can lead to a direct loss of funds from the EGM, such as stolen cash or loss of revenue when the EGM is not operating properly or when the random outcome determination is manipulated.

[0175] Certain differences between general purpose computing devices and EGMs are described below. A first difference between EGMs and general purpose computing devices is that EGMs are state-based systems. A state-based system stores and maintains its current state in a non-volatile memory such that, in the event of a power failure or other malfunction, the state-based system can return to that state when the power is restored or the malfunction is remedied. For instance, for a state-based EGM, if the EGM displays an award for a game of chance but the power to the EGM fails before the EGM provides the award to the player, the EGM stores the pre-power failure state in a non-volatile memory, returns to that state upon restoration of power, and provides the award to the player. This requirement affects the software and hardware design on EGMs. General purpose computing devices are not state-based machines, and a majority of data is usually lost when a malfunction occurs on a general purpose computing device.

[0176] A second difference between EGMs and general purpose computing devices is that, for regulatory purposes, the software on the EGM utilized to operate the EGM has been designed to be static and monolithic to prevent cheating by the operator of the EGM. For instance, one solution that has been employed in the gaming industry to prevent cheating and to satisfy regulatory requirements has been to manufacture an EGM that can use a proprietary processor running instructions to provide the game of chance from an EPROM or other form of non-volatile memory. The coding instructions on the EPROM are static (non-changeable) and must be approved by a gaming regulators in a particular jurisdiction and installed in the presence of a person representing the gaming jurisdiction. Any changes to any part of the software required to generate the game of chance, such as adding a new device driver used to operate a device during generation of the game of chance, can require burning a new EPROM approved by the gaming jurisdiction and reinstalling the new EPROM on the EGM in the presence of a gaming regulator. Regardless of whether the EPROM solution is used, to gain approval in most gaming jurisdictions, an EGM must demonstrate sufficient safeguards that prevent an operator or a player of an EGM from manipulating the EGM's hardware and software in a manner that gives him an unfair, and in some cases illegal, advantage.

[0177] A third difference between EGMs and general purpose computing devices is authentication—EGMs storing code are configured to authenticate the code to determine if the code is unaltered before executing the code. If the code has been altered, the EGM prevents the code from being executed. The code authentication requirements in the gaming industry affect both hardware and software designs on EGMs. Certain EGMs use hash functions to authenticate code. For instance, one EGM stores game program code, a hash function, and an authentication hash (which may be encrypted). Before executing the game program code, the EGM hashes the game program code using the hash function to obtain a result hash and compares the result hash to the authentication hash. If the result hash matches the authentication hash, the EGM determines that the game program code is valid and executes the game program code. If the result hash does not match the authentication hash, the EGM determines that the game program code has been altered (i.e., may have been tampered with) and prevents execution of the game program code. Examples of EGM code authentication are described in U.S. Pat. No. 6,962,530, entitled “Authentication in a Secure Computerized Gaming System”; U.S. Pat. No. 7,043,641, entitled “Encryption in a Secure Computerized Gaming System”; U.S. Pat. No. 7,201,662, entitled “Method and Apparatus for Software Authentication”; and U.S. Pat. No. 8,627,097, entitled “System and Method Enabling Parallel Processing of Hash Functions Using Authentication Checkpoint Hashes”.

[0178] A fourth difference between EGMs and general purpose computing devices is that EGMs have unique peripheral device requirements that differ from those of a general purpose computing device, such as peripheral device security requirements not usually addressed by general purpose computing devices. For instance, monetary devices, such as coin dispensers, bill validators, and ticket printers and computing devices that are used to govern the input and output of cash or other items having monetary value (such as tickets) to and from an EGM have security requirements that are not typically addressed in general purpose computing devices. Therefore, many general purpose computing device techniques and methods developed to facilitate device connectivity and device compatibility do not address the emphasis placed on security in the gaming industry.

[0179] To address some of the issues described above, a number of hardware/software components and architectures are utilized in EGMs that are not typically found in general purpose computing devices. These hardware/software components and architectures, as described below in more detail, include but are not limited to watchdog timers, voltage monitoring systems, state-based software architecture and supporting hardware, specialized communication interfaces, security monitoring, and trusted memory.

[0180] Certain EGMs use a watchdog timer to provide a software failure detection mechanism. In a normally-operating EGM, the operating software periodically accesses control registers in the watchdog timer subsystem to “re-trigger” the watchdog. Should the operating software fail to

access the control registers within a preset timeframe, the watchdog timer will timeout and generate a system reset. Typical watchdog timer circuits include a loadable timeout counter register to enable the operating software to set the timeout interval within a certain range of time. A differentiating feature of some circuits is that the operating software cannot completely disable the function of the watchdog timer. In other words, the watchdog timer always functions from the time power is applied to the board.

[0181] Certain EGMs use several power supply voltages to operate portions of the computer circuitry. These can be generated in a central power supply or locally on the computer board. If any of these voltages falls out of the tolerance limits of the circuitry they power, unpredictable operation of the EGM may result. Though most modern general purpose computing devices include voltage monitoring circuitry, these types of circuits only report voltage status to the operating software. Out of tolerance voltages can cause software malfunction, creating a potential uncontrolled condition in the general purpose computing device. Certain EGMs have power supplies with relatively tighter voltage margins than that required by the operating circuitry. In addition, the voltage monitoring circuitry implemented in certain EGMs typically has two thresholds of control. The first threshold generates a software event that can be detected by the operating software and an error condition then generated. This threshold is triggered when a power supply voltage falls out of the tolerance range of the power supply, but is still within the operating range of the circuitry. The second threshold is set when a power supply voltage falls out of the operating tolerance of the circuitry. In this case, the circuitry generates a reset, halting operation of the EGM.

[0182] As described above, certain EGMs are state-based machines. Different functions of the game provided by the EGM (e.g., bet, play, result, points in the graphical presentation, etc.) may be defined as a state. When the EGM moves a game from one state to another, the EGM stores critical data regarding the game software in a custom non-volatile memory subsystem. This ensures that the player's wager and credits are preserved and to minimize potential disputes in the event of a malfunction on the EGM. In general, the EGM does not advance from a first state to a second state until critical information that enables the first state to be reconstructed has been stored. This feature enables the EGM to recover operation to the current state of play in the event of a malfunction, loss of power, etc. that occurred just before the malfunction. In at least one embodiment, the EGM is configured to store such critical information using atomic transactions.

[0183] Generally, an atomic operation in computer science refers to a set of operations that can be combined so that they appear to the rest of the system to be a single operation with only two possible outcomes: success or failure. As related to data storage, an atomic transaction may be characterized as series of database operations which either all occur, or all do not occur. A guarantee of atomicity prevents updates to the database occurring only partially, which can result in data corruption.

[0184] To ensure the success of atomic transactions relating to critical information to be stored in the EGM memory before a failure event (e.g., malfunction, loss of power, etc.), memory that includes one or more of the following criteria be used: direct memory access capability; data read/write capability which meets or exceeds minimum read/write access characteristics (such as at least 5.08 Mbytes/see (Read) and/or at least 38.0 Mbytes/see (Write)). Memory devices that meet or exceed the above criteria may be referred to as "fault-tolerant" memory devices.

[0185] Typically, battery-backed RAM devices may be configured to function as fault-tolerant devices according to the above criteria, whereas flash RAM and/or disk drive memory are typically not configurable to function as fault-tolerant devices according to the above criteria. Accordingly, battery-backed RAM devices are typically used to preserve EGM critical data, although other types of non-volatile memory devices may be employed. These memory devices are typically not used in typical general purpose computing devices.

[0186] Thus, in at least one embodiment, the EGM is configured to store critical information in

fault-tolerant memory (e.g., battery-backed RAM devices) using atomic transactions. Further, in at least one embodiment, the fault-tolerant memory is able to successfully complete all desired atomic transactions (e.g., relating to the storage of EGM critical information) within a time period of 200 milliseconds or less. In at least one embodiment, the time period of 200 milliseconds represents a maximum amount of time for which sufficient power may be available to the various EGM components after a power outage event has occurred at the EGM.

[0187] As described previously, the EGM may not advance from a first state to a second state until critical information that enables the first state to be reconstructed has been atomically stored. After the state of the EGM is restored during the play of a game of chance, game play may resume and the game may be completed in a manner that is no different than if the malfunction had not occurred. Thus, for example, when a malfunction occurs during a game of chance, the EGM may be restored to a state in the game of chance just before when the malfunction occurred. The restored state may include metering information and graphical information that was displayed on the EGM in the state before the malfunction. For example, when the malfunction occurs during the play of a card game after the cards have been dealt, the EGM may be restored with the cards that were previously displayed as part of the card game. As another example, a bonus game may be triggered during the play of a game of chance in which a player is required to make a number of selections on a video display screen. When a malfunction has occurred after the player has made one or more selections, the EGM may be restored to a state that shows the graphical presentation just before the malfunction including an indication of selections that have already been made by the player. In general, the EGM may be restored to any state in a plurality of states that occur in the game of chance that occurs while the game of chance is played or to states that occur between the play of a game of chance.

[0188] Game history information regarding previous games played such as an amount wagered, the outcome of the game, and the like may also be stored in a non-volatile memory device. The information stored in the non-volatile memory may be detailed enough to reconstruct a portion of the graphical presentation that was previously presented on the EGM and the state of the EGM (e.g., credits) at the time the game of chance was played. The game history information may be utilized in the event of a dispute. For example, a player may decide that in a previous game of chance that they did not receive credit for an award that they believed they won. The game history information may be used to reconstruct the state of the EGM before, during, and/or after the disputed game to demonstrate whether the player was correct or not in the player's assertion. Examples of a state-based EGM, recovery from malfunctions, and game history are described in U.S. Pat. No. 6,804,763, entitled "High Performance Battery Backed RAM Interface"; U.S. Pat. No. 6,863,608, entitled "Frame Capture of Actual Game Play"; U.S. Pat. No. 7,111,141, entitled "Dynamic NV-RAM"; and U.S. Pat. No. 7,384,339, entitled, "Frame Capture of Actual Game Play".

[0189] Another feature of EGMs is that they often include unique interfaces, including serial interfaces, to connect to specific subsystems internal and external to the EGM. The serial devices may have electrical interface requirements that differ from the "standard" EIA serial interfaces provided by general purpose computing devices. These interfaces may include, for example, Fiber Optic Serial, optically coupled serial interfaces, current loop style serial interfaces, etc. In addition, to conserve serial interfaces internally in the EGM, serial devices may be connected in a shared, daisy-chain fashion in which multiple peripheral devices are connected to a single serial channel.

[0190] The serial interfaces may be used to transmit information using communication protocols that are unique to the gaming industry. For example, IGT's Netplex is a proprietary communication protocol used for serial communication between EGMs. As another example, SAS is a communication protocol used to transmit information, such as metering information, from an EGM to a remote device. Often SAS is used in conjunction with a player tracking system.

[0191] Certain EGMs may alternatively be treated as peripheral devices to a casino communication

controller and connected in a shared daisy chain fashion to a single serial interface. In both cases, the peripheral devices are assigned device addresses. If so, the serial controller circuitry must implement a method to generate or detect unique device addresses. General purpose computing device serial ports are not able to do this.

[0192] Security monitoring circuits detect intrusion into an EGM by monitoring security switches attached to access doors in the EGM cabinet. Access violations result in suspension of game play and can trigger additional security operations to preserve the current state of game play. These circuits also function when power is off by use of a battery backup. In power-off operation, these circuits continue to monitor the access doors of the EGM. When power is restored, the EGM can determine whether any security violations occurred while power was off, e.g., via software for reading status registers. This can trigger event log entries and further data authentication operations by the EGM software.

[0193] Trusted memory devices and/or trusted memory sources are included in an EGM to ensure the authenticity of the software that may be stored on less secure memory subsystems, such as mass storage devices. Trusted memory devices and controlling circuitry are typically designed to not enable modification of the code and data stored in the memory device while the memory device is installed in the EGM. The code and data stored in these devices may include authentication algorithms, random number generators, authentication keys, operating system kernels, etc. The purpose of these trusted memory devices is to provide gaming regulatory authorities a root trusted authority within the computing environment of the EGM that can be tracked and verified as original. This may be accomplished via removal of the trusted memory device from the EGM computer and verification of the secure memory device contents is a separate third party verification device. Once the trusted memory device is verified as authentic, and based on the approval of the verification algorithms included in the trusted device, the EGM is enabled to verify the authenticity of additional code and data that may be located in the gaming computer assembly, such as code and data stored on hard disk drives. Examples of trusted memory devices are described in U.S. Pat. No. 6,685,567, entitled "Process Verification".

[0194] In at least one embodiment, at least a portion of the trusted memory devices/sources may correspond to memory that cannot easily be altered (e.g., "unalterable memory") such as EPROMS, PROMS, Bios, Extended Bios, and/or other memory sources that are able to be configured, verified, and/or authenticated (e.g., for authenticity) in a secure and controlled manner.

[0195] According to one embodiment, when a trusted information source is in communication with a remote device via a network, the remote device may employ a verification scheme to verify the identity of the trusted information source. For example, the trusted information source and the remote device may exchange information using public and private encryption keys to verify each other's identities. In another embodiment, the remote device and the trusted information source may engage in methods using zero knowledge proofs to authenticate each of their respective identities.

[0196] EGMs storing trusted information may utilize apparatuses or methods to detect and prevent tampering. For instance, trusted information stored in a trusted memory device may be encrypted to prevent its misuse. In addition, the trusted memory device may be secured behind a locked door. Further, one or more sensors may be coupled to the memory device to detect tampering with the memory device and provide some record of the tampering. In yet another example, the memory device storing trusted information might be designed to detect tampering attempts and clear or erase itself when an attempt at tampering has been detected. Examples of trusted memory devices/sources are described in U.S. Pat. No. 7,515,718, entitled "Secured Virtual Network in a Gaming Environment".

[0197] Mass storage devices used in a general purpose computing devices typically enable code and data to be read from and written to the mass storage device. In a gaming environment, modification of the gaming code stored on a mass storage device is strictly controlled and would only be enabled under specific maintenance type events with electronic and physical enablers

required. Though this level of security could be provided by software, EGMs that include mass storage devices include hardware level mass storage data protection circuitry that operates at the circuit level to monitor attempts to modify data on the mass storage device and will generate both software and hardware error triggers should a data modification be attempted without the proper electronic and physical enablers being present. Examples of using a mass storage device are described in U.S. Pat. No. 6,149,522, entitled "Method of Authenticating Game Data Sets in an Electronic Casino Gaming System".

[0198] Various changes and modifications to the present embodiments described herein will be apparent to those skilled in the art. Such changes and modifications can be made without departing from the spirit and scope of the present subject matter and without diminishing its intended technical scope. It is therefore intended that such changes and modifications be covered by the appended claims.

Claims

1. A system comprising: a processor; and a memory device that stores a plurality of instructions that, when executed by the processor, cause the processor to: responsive to a receipt of first slot accounting system protocol data, cause a display, by a display device, of a value, and responsive to a receipt of second slot accounting system protocol data, cause a display, by the display device, of a modification of the value, wherein: the modification of the value occurs following a server operating independent of the processor determining that an event occurred during a sporting event, the displayed modification of the value is based on the event occurring during the sporting event, a first event occurring during the sporting event result in a first displayed modification of the value, a second, different event occurring during the sporting event results in a second, different displayed modification of the value, and the displayed modification of the value occurs independent of any modification of the value based on any received monetary value.
2. The system of claim 1, wherein the displayed modification of the value is associated with a quantity of activations following the event occurring during the sporting event.
3. The system of claim 1, wherein the displayed modification of the value is associated an amount of time following the event occurring during the sporting event.
4. The system of claim 1, wherein the event occurring during the sporting event comprises a series of events occurring during the sporting event.
5. The system of claim 4, wherein the sporting event comprises a plurality of sporting events, a first event of the series of events occurs during a first sporting event of the plurality of sporting events and a second event of the series of events occurs during a second, different sporting event of the plurality of sporting events.
6. The system of claim 1, wherein the value is associated with a sports team of the sporting event and the event occurring during the sporting event comprises an outcome of the sporting event occurring in association with that sports team of the sporting event.
7. The system of claim 1, wherein the value is associated with a sporting event participant of the sporting event and the event occurring during the sporting event comprises an outcome of the sporting event occurring in association with that sporting event participant of the sporting event.
8. The system of claim 1, wherein the display device comprises an electronic gaming machine display device.
9. The system of claim 1, wherein the first displayed modification of the value comprises an addition of a first amount and the second, different displayed modification of the value comprises an addition of a second, different amount.
10. A system comprising: a processor; and a memory device that stores a plurality of instructions that, when executed by the processor, cause the processor to: responsive to a receipt of first slot accounting system protocol data, cause a display, by a display device, of a value, responsive to a

receipt of second slot accounting system protocol data, cause a display, by the display device, of a modification of the value, wherein the modification of the value occurs following a server operating independent of the processor determining that a first event occurred during a sporting event and the modification of the value occurs independent of any modification of the value based on any received monetary value, responsive to a receipt of third slot accounting system protocol data, cause a display, by the display device, of an association of the value with a user, wherein the association occurs following the server operating independent of the processor determining that a second, different event occurred during the sporting event, and responsive to a receipt of fourth slot accounting system protocol data, cause a display, by the display device, of the value being rolled into another value, wherein the fourth slot accounting system protocol data is received responsive to the second, different event not occurring during the sporting event.

11. The system of claim 10, wherein the other value is associated with a different portion of the sporting event.

12. A method of operating a system, the method comprising: responsive to a receipt of first slot accounting system protocol data, displaying, by a display device, a value, and responsive to a receipt of second slot accounting system protocol data, displaying, by the display device, a modification of the value, wherein: the modification of the value occurs following a server operating independent of the electronic gaming machine determining that an event occurred during a sporting event, the displayed modification of the value is based on the event occurring during the sporting event, a first event occurring during the sporting event results in a first displayed modification of the value, a second, different event occurring during the sporting event results in a second, different displayed modification of the value, and the displayed modification of the value occurs independent of any modification of the value based on any received monetary value.

13. The method of claim 12, wherein the displayed modification of the value is associated with a quantity of activations following the event occurring during the sporting event.

14. The method of claim 12, wherein the displayed modification of the value is associated with an amount of time following the event occurring during the sporting event.

15. The method of claim 12, wherein the event occurring during the sporting event comprises a series of events occurring during the sporting event.

16. The method of claim 15, wherein the sporting event comprises a plurality of sporting events, a first event of the series of events occurs during a first sporting event of the plurality of sporting events and a second event of the series of events occurs during a second, different sporting event of the plurality of sporting events.

17. The method of claim 12, wherein the value is associated with a sports team of the sporting event and the event occurring during the sporting event comprises an outcome of the sporting event occurring in association with that sports team of the sporting event.

18. The method of claim 12, wherein the value is associated with a sporting event participant of the sporting event and the event occurring during the sporting event comprises an outcome of the sporting event occurring in association with that sporting event participant of the sporting event.

19. The method of claim 12, wherein the display device comprises an electronic gaming machine display device.

20. The method of claim 12, wherein the first displayed modification of the value comprises an addition of a first amount and the second, different displayed modification of the value comprises an addition of a second, different amount.
